



MORE INFORMATION



www.anupampaints.com



FACTORY ADDRESS

M/s. Anupam Enterprises,
Plot No.: 5/27, Foundry Park,
Laskarpur, Ranihati Amta Road,
Howrah - 711 414.

OFFICE ADDRESS

Poddar Point, 113 Park Street,
5th Floor, Block - B,
Kolkata - 700 016



033-22651204
033-22651205



care@anupampaints.com



Technical Data Sheet

Colouring Success Stories!



AZURA EXTERIOR EMULSION LONG LIFE ANTI DIRT 15

Dirt Resistance – 15 yr protection

- Specially Designed for Long Term Protection.
- Rich Sheen Formula.
- Excellent Resistance to Algae & Fungal Growth.
- Excellent Light Fastness with Non-Fading Bright Colours.
- Weather Guard, Long Term Protection.



PAINT – Premium Acrylic
Exterior Emulsion

Azura Exterior Emulsion Long Life 15 is a water-based paint for long-lasting, algae-free beautiful walls. Beyond the excellent light fastness and protection to wear and tear, it comes with an exceptional performance warranty against dirt. Tough yet flexible, the Azura Exterior Emulsion Long Life 15 film bridges hair cracks and is specifically formulated to prevent the growth of algae and fungi. We have used a Hybrid technology of Aliphatic PU dispersion and specially designed Acrylic Polymer for long protection, Silene, Polysiloxane Technology for increase in Hydrophobic nature of dried film. Also we have selected the most effective Biocide combination for better weather protection.

Product Benefits

- **Silene, Poly Siloxane Technology:-** The product has Polysiloxane to protect the film from extreme rainfall & high humidity by improving water impermeability & hydrophobic nature of the dried film.
- **Effective Waterproofing:-** The effective waterproofing capabilities of Azura Exterior Emulsion Long Life 15 system form a barrier against water penetration.
- **Crack Bridging:-** Azura Exterior Emulsion Long Life 15 has higher elongation with fibre reinforcement technology providing a unique crack bridging ability up to 2mm.
- **Structural Protection:-** Azura Exterior Emulsion Long Life 15, System has excellent CO₂ diffusion (anti-carbonation) resistance & prevents the corrosion of rebar within the concrete matrix, leading to superior structural protection.

Recommended Usage

• Exterior Walls	For painting exterior walls, exterior cement plasters, exterior ceilings, asbestos sheets, concrete etc. *Not to be applied on surfaces/substrates with continuous seepage or dampness.
------------------	--

General Properties

Finish	Silky Smooth	Weather Resistance	Excellent for a longer period
Opacity	Excellent		
Flow and Leveling	Excellent		Resistance to Algae and Fungi
Durability	15 yrs in all weather conditions		Resistance to Alkali
Light Fastness	Excellent		Gloss Levels/ Sheen Levels
			Gloss, 20 -25% at 60 deg C Sheen, 40 -50% at 85 deg C

*Performance Warranty-conditions apply

Safety, Environment & Health

No Added Lead, Mercury, Arsenic or Chromium	Non Flammable – Water Based Paint
---	-----------------------------------

Application

Surface Preparation:

- Cleaning:** Free the surface from loose particles and peeling paint. Remove any previous growth of algae, fungi or moss by thorough wire brushing and cleaning with water. Antifungal wash after cleaning the algae & fungi has been proved very effective.
- Filling:** Any surface imperfections like holes, dents and fine cracks are to be filled with Cement Putty or Acrylic Putty.
- Primer:** Ensure that fresh plastered surfaces are completely cured and dry. Apply a coat of Azura Exterior Primer WT or Azura Dual Damp Arrestor Alkali Bloc Primer WT thinning with 1 ltr of paint with 500 ml of clean water. Allow drying for 4-6 hours.

Application (Topcoat):

Apply 2 coats of Azura Exterior Emulsion Long Life Anti Dirt 15 diluting with clean water. Maintain an interval of 4-6 hours between successive coats. For horizontal surfaces, application of additional coat is recommended.
● For darker shades, additional coat is recommended for complete hiding.

Application	Brush	✓
	Roller	✓
	Spray	✓
Dilution	Brush	20-25% by volume with clean potable water
	Roller	10-15% by volume with clean potable water
	Spray	35-40% by volume with clean potable water
Drying time	Within 30 min - 1 hr	
Overcoating Time	4 - 6 hrs	
No. of coats specified	2 Coats	
Coverage (Theoretical)	60*-65* sq ft/litre for two coat finish under ideal conditions. For Virgin surface coverage will be less.	

Stability of Thinned Paint	Use within 24 hrs.
Precautions while Painting	• Avoid painting when the temperature is below 10°C & Humidity more than 80%. • Painting is not recommended if the moisture content and alkalinity of the surface is high. • For newly plastered walls painting is recommended after 4 weeks of curing. • Please do not over-thin or over-extend the brush while painting.
Cleaning up equipments	Wash all tools with water immediately after application.
Post Application Instructions	For best performance of paint, surfaces should be washed and cleaned at regular intervals of six months.

General Information

Bases Information	5 Bases (A1 A2 A9, Fast Yellow & Brown) Also White	Colour Options	• Colours in Fandack, Mini-fandack and Exterior Shade Card
Preferable Primer	Azura Dual Primer WT.		• White
Preferable Putty	Cement Based Putty	Fandack	Choose from thousands of Fandack shades
		Packing	• White – 1, 4, 10, 20 Ltr Packs • Bases – 0.9, 1, 3.6, 4, 9, 10, 18, 20 Ltr Packs (Colourants added extra)

General Safety and Environment Information

- Keep container upright and tightly closed in a cool, dry and well ventilated location.
- Keep out of reach of children. Do not store near food, drinks or animal feed.
- Dispose unwanted paint safely. Do not dispose into drains, water sources or open sewers.
- Wash all tools with clean water immediately after application.
- Use sand or earth to contain any paint spillage.
- Wear appropriate attire, especially gloves, eye protection and nose mask.
- Work in a well-ventilated area. Do not breathe vapour or spray.
- Avoid contact with skin as it may cause irritation.
- In the case of accidental contact, wash area immediately with water and seek immediate medical attention.
- To remove the paint from skin, use soap and water or appropriate cleaner.

VOC Level: VOC content does not exceed 30 ppm & complies with applicable low-VOC requirements.

AZURA ADVANCE EXTERIOR EMULSION

Algae & Fungal Resistance

- **Poly Siloxane Technology:** The product has Polysiloxane to protect the film from extreme rainfall & high humidity by improving water impermeability & hydrophobic nature of the dried film.
- **Oxidised Polyethylene Wax Emulsion:** Increased scratch resistance, improved abrasion resistance, better adhesion & water repellency, better slip and lubricity.
- **Effective Waterproofing:** The effective waterproofing capabilities of Azura Advance Exterior Emulsion system form a barrier against water penetration.
- **Crack Bridging:** Azura Advance Exterior Emulsion has higher elongation with fibre reinforcement technology providing a unique crack bridging ability up to 2mm.
- **Structural Protection:** Azura Advance Exterior Emulsion System has excellent CO₂ diffusion (carbonation) resistance & prevents the corrosion of rebar within the concrete matrix, leading to superior structural protection.



Azura Advance Exterior Emulsion

Azura Advance Exterior Emulsion Long Life is a water-based paint for long-lasting, algae-free beautiful walls. Beyond the excellent light fastness and protection to wear and tear, it comes with an exceptional performance warranty against dirt. Tough yet flexible, the Azura Advance Exterior Emulsion film bridges hair cracks and is specifically formulated to prevent the growth of algae and fungi. We have used specially designed Acrylic Polymer for long protection, Polysiloxane Technology for increase in Hydrophobic nature of dried film & Oxidised Polyethylene Wax Emulsion for increased rub, scratch & abrasion resistance. Also we have selected the most effective Biocide combination for better weather protection.

Recommended Usage

• Exterior Walls	For painting exterior walls, exterior cement plasters, exterior ceilings, asbestos sheets, concrete etc. *Not to be applied on surfaces/substrates with continuous seepage or dampness.
------------------	--

General Properties

Finish	Silky Smooth	Weather Resistance	Excellent for a longer period
Opacity	Excellent		
Flow and Leveling	Excellent	Resistance to Algae & Fungi	Excellent
Durability	5 yrs* in High Rainfall Areas. 10 years in Normal Weather conditions	Resistance to Alkali	Passes the Alkali Resistance test
Light Fastness	Excellent	Gloss Levels	20 -30% at 60 degree C 40 - 50% at 85 degree .

Safety, Environment & Health

No Added Lead, Mercury, Arsenic or Chromium	Non Flammable: Water-Based Paint
---	----------------------------------

General Information

Bases Information	5 Bases (A1 A2 A9, Fast Yellow) & White	Colour Options	• Colours in Fandack, Mini-Fandack and Exterior Shade Card • White
Preferable Primer	Azura Advance Dual Primer Water Thinnable Primer		
Preferable Putty	Cement Based Putty	Packing	• White - 1, 4, 10, 20 Ltr Packs • Bases - 0.9, 1, 3.6, 4, 9, 10, 18, 20 Ltr Packs (Colourants added extra)

Application

Surface Preparation:

1. Cleaning: Free the surface from loose particles and peeling paint. Remove any previous growth of algae, fungi or moss by thorough wire-brushing and cleaning with water. Antifungal wash after cleaning the algae & fungi has been proven very effective.

2. Filling – Any surface imperfections like holes, dents and fine cracks are to be filled with Cement Putty or Acrylic Putty.

3. Primer – Ensure that fresh plastered surfaces are completely cured and dry. Apply a coat of Azura Advance Damp Arrestor Alkali Bloc Dual Primer WT thinning with 30% water. Allow drying for 4-6 hours.

Application (Topcoat):

Apply 2 coats of Azura Advance Exterior Emulsion Long Life diluting with clean water. Maintain an interval of 4-6 hours between successive coats. For horizontal surfaces, the application of an additional coat is recommended.

- For darker shades, additional coat is recommended for complete hiding.

Application	Brush	✓
	Roller	✓
	Spray	✓
Dilution	Brush	20-25% by volume with clean potable water
	Roller	10-15% by volume with clean potable water
	Spray	30-35% by volume with clean potable water
Drying time	Within 30 minutes -1 hr	
Overcoating Time	4 - 6 hrs	
No. of coats specified	2 Coats	
Coverage (Theoretical)	65*-70* sq ft/litre for a two coat finish under ideal conditions. For Virgin surface coverage will be less.	

Stability of Thinned Paint	Use within 24 hrs.
Precautions while Painting	• Avoid painting when the temperature is below 10 0C. • Painting is not recommended if the moisture content and alkalinity of the surface is high. • For newly plastered walls painting is recommended after 12 weeks of curing. • Please do not over-thin or over-extend the brush while painting.
Cleaning up equipments	Wash all tools with water immediately after application.
Post Application Instructions	For best performance of paint, surfaces should be washed and cleaned at regular intervals of six months.

General Safety and Environment Information

• Keep container upright and tightly closed in a cool, dry and well ventilated location. • Keep out of reach of children. Do not store near food, drinks or animal feed. • Dispose unwanted paint safely. Do not dispose into drains, water sources or open sewers. • Wash all tools with clean water immediately after application.	• Use sand or earth to contain any paint spillage. • Wear appropriate attire, especially gloves, eye protection and nose mask. • Work in a well-ventilated area. Do not breathe vapour or spray. • Avoid contact with skin as it may cause irritation. • In the case of accidental contact, wash area immediately with water and seek immediate medical attention. • To remove the paint from skin, use soap and water or appropriate cleaner.
---	---

Strong Benefits

- Specially Designed for Long Term Protection in High Rainfall & High Humidity Areas.
- Rich Sheen Formula.
- Excellent Resistance to Algae & Fungal Growth.
- Excellent Light Fastness with Non-Fading Bright Colors.
- Weather Guard, Long Term Protection.

VOC Level: VOC content does not exceed 30 ppm & complies with applicable low-VOC requirements.

AZURA PREMIUM EXTERIOR EMULSION LONG LIFE ANTI DIRT. 10

Dirt Resistance – 10 yr protection

- Dirt Resistance, 10 year performance warranty*
- Rich Gloss & Sheen Formula
- Excellent Resistance to Algae & Fungal Growth
- Excellent Light Fastness with Non-Fading Bright Colours
- Weather Guard, Long Term Protection



PAINT – Premium Acrylic
Exterior Emulsion

Azura Exterior Emulsion Long Life Anti Dirt is an advanced Water Based paint for long lasting dirt free beautiful walls. It is having Silicone Emulsion Technology, & Non toxic single pack PU emulsion Technology to Beyond the excellent light fastness and protection to wear and tear, it comes with an exceptional 10 yr performance warranty against dirt & overall performance. Tough yet flexible, the Azura Ext. Emulsion film bridges hair cracks and is specifically formulated to prevent growth of algae and fungi.

Recommended Usage

• Exterior Walls	For painting exterior walls, exterior cement plasters, exterior ceilings, asbestos sheets, concrete etc. *Not to be applied on surfaces/substrates with continuous seepage or dampness.
------------------	--

General Properties

Finish	Silky Smooth		Weather Resistance	Excellent for a longer period
Opacity	Excellent		Resistance to Algae and Fungi	Excellent
Flow and Leveling	Excellent		Resistance to Alkali	Passes the Alkali Resistance test.
Durability	10 yrs*		Gloss Levels/ Sheen Levels	20 -30% at 60 deg C and 40 -50% at 85 deg C
Light Fastness	Excellent			

*Performance Warranty-conditions apply

Safety, Environment & Health

No Added Lead, Mercury, Arsenic or Chromium	Non Flammable – Water Based Paint
---	-----------------------------------

General Information

Bases Information	5 Bases (A1 A2 A9, Fast Yellow & Brown) Also White	Colour Options	• Colours in Fandack, Mini-fandack and Interior Shade Card • White
Preferable Primer	Azura Water Thinnable Exterior Primer.	Fandack	Choose from thousands of Fandack shades
Preferable Putty	Cement Based Putty	Packing	• White – 1, 4, 10, 20 Ltr Packs • Bases – 0.9, 1, 3.6, 4, 9, 10, 18, 20 Ltr Packs (Colourants added extra)

Application

Surface Preparation:

- Cleaning:** Free the surface from loose particles and peeling paint. Remove any previous growth of algae, fungi or moss by thorough wire brushing and cleaning with water. Antifungal wash after cleaning the algae & fungi has been proved very effective.
- Filling:** Any surface imperfections like holes, dents and fine cracks are to be filled with Cement Putty or Acrylic Putty.
- Primer:** Ensure that fresh plastered surfaces are completely cured and dry. Apply a coat of Azura Exterior Primer WT or Azura Dual Damp Arrestor Alkali Bloc Primer WT thinning with 1 ltr of paint with 1 ltr of clean water. Allow drying for 4-6 hours.

Application (Topcoat):

Apply 2 coats of Azura Exterior Emulsion Long Life Anti Dirt diluting with clean water. Maintain an interval of 4-6 hours between successive coats. For horizontal surfaces, application of additional coat is recommended.

- For darker shades, additional coat is recommended for complete hiding.

Application	Brush	✓
	Roller	✓
	Spray	✓
Dilution	Brush	20-25% by volume with clean potable water
	Roller	10-15% by volume with clean potable water
	Spray	35-40% by volume with clean potable water
Drying time	Within 1 hr	
Overcoating Time	4 – 6 hrs	
No. of coats specified	2 Coats	
Coverage (Theoretical)	65*-70* sq ft/litre for two coat finish under ideal conditions. For Virgin surface coverage will be less.	

Stability of Thinned Paint	Use within 24 hrs.
Precautions while Painting	• Avoid painting when the temperature is below 10°C. • Painting is not recommended if the moisture content and alkalinity of the surface is high. • For newly plastered walls painting is recommended after 4 weeks of curing. • Please do not over-thin or over-extend the brush while painting.
Cleaning up equipments	Wash all tools with water immediately after application.
Post Application Instructions	For best performance of paint, surfaces should be washed and cleaned at regular intervals of six months.

General Safety and Environment Information

- Keep container upright and tightly closed in a cool, dry and well ventilated location.
- Keep out of reach of children. Do not store near food, drinks or animal feed.
- Dispose unwanted paint safely. Do not dispose into drains, water sources or open sewers.
- Wash all tools with clean water immediately after application.
- Use sand or earth to contain any paint spillage.
- Wear appropriate attire, especially gloves, eye protection and nose mask.
- Work in a well-ventilated area. Do not breathe vapour or spray.
- Avoid contact with skin as it may cause irritation.
- In the case of accidental contact, wash area immediately with water and seek immediate medical attention.
- To remove the paint from skin, use soap and water or appropriate cleaner.

VOC Level: VOC content does not exceed 30 ppm & complies with applicable low-VOC requirements.

*Actual Coverage may vary depending upon the application process and surface conditions.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

ASURE RADIANCE EXTERIOR EMULSION

Elegant exteriors with long life robust protection

- High Sheen Formula
- Excellent Resistance to Algae & Fungal Growth
- Excellent Light Fastness with Non-Fading Bright Colours
- Weather Guard, Long Term Protection



Total Protection for your exterior walls against any extreme weather, be it the heavy rainfall, high humidity, scorching heat or freezing cold, Asure Radiance is specially designed to protect and maintain the splendor of your exteriors. Made with 100% Pure Acrylic Emulsion Base it provides a very smooth and silky finish that enhances the aesthetic of the exterior surfaces.

Recommended Usage

• Exterior Walls	For painting exterior walls, exterior cement plasters, exterior ceilings, asbestos sheets, concrete etc. *Not to be applied on surfaces/substrates with continuous seepage or dampness.
------------------	--

General Properties

Finish	Silky Smooth	Weather Resistance	Excellent for a longer period
Opacity	Excellent		
Flow and Leveling	Excellent		Resistance to Algae and Fungi Excellent
Durability	5 +1 years.		Resistance to Alkali Passes the Alkali Resistance test
Light Fastness	Excellent		Gloss Levels/ Sheen Levels 30 -35% at 60 deg C 40 - 50% at 85 deg for light shades, 30 -35% at 85 deg for dark shades

Safety, Environment & Health

No Added Lead, Mercury, Arsenic or Chromium	Non Flammable	Flash Point - Not below 30 oC
---	---------------	-------------------------------

General Information

Bases Information	4 Bases (A1,A2,A9 & Yellow)	Colour Options	• Colours in any Fandack,& Exterior Shade Card • Also White
Preferable Primer	Azura Super White Exterior Primer WT/ Azura Damp Arrestor Alkali Bloc Dual Primer WT		Colour Any Colour from any Shade cards
Preferable Putty	Cement Based Putty		Packing • White - 1, 4, 10, 20 Ltr Packs • Bases - 0.9, 1, 3.6, 4, 9, 10, 18, 20 Ltr Packs (Colourants added extra)

Application

Surface Preparation:

1. Cleaning: Free the surface from loose particles and peeling paint. Remove any previous growth of algae, fungi or moss by thorough wire brushing and cleaning with water.

2. Filling: Any surface imperfections like holes, dents and fine cracks are to be filled with Cement Plaster or White Cement Based Putty.

3. Primer: Ensure that fresh plastered surfaces are completely cured and dry. Apply a coat of Azura Super White Exterior Primer WT/Azura Damp Arrestor Dual Primer WT, dilute with 50-60% clean water.

Application (Topcoat):

Apply 2 coats of Asure Radiance Exterior Emulsion by diluting with clean Water. Maintain an interval of 4-5 hours between successive coats.

- For darker shades, additional coat is recommended for complete hiding.

Application	Brush	✓
	Roller	✓
	Spray	✓
Dilution	Brush	20-25% by volume with clean water
	Roller	10-15% by volume with clean water
	Spray	40-50% by volume with clean potable water
Drying time	Within 1 hr	
Overcoating Time	4 - 5 hrs	
No. of coats specified	2 Coats	
Coverage (Theoretical)	60*-65* sq ft/litre for two coat finish under normal conditions. For Virgin surface coverage will be less.	

Stability of Thinned Paint	Use within 24 hrs.
Precautions while Painting	• Avoid painting when the temperature is below 10 oC. • Painting is not recommended if the moisture content and alkalinity of the surface is high. • For newly plastered walls painting is recommended after 12 weeks of curing. • Please do not over-thin or over-extend the brush while painting.
Cleaning up equipments	Wash all tools with water immediately after application.
Post Application Instructions	For best performance of paint all algal and fungal growth must be properly washed and cleaned at regular intervals of six months.

General Safety and Environment Information

• Keep container upright and tightly closed in a cool, dry and well ventilated location. • Keep out of reach of children. Do not store near food, drinks or animal feed. • Dispose unwanted paint safely. Do not dispose into drains, water sources or open sewers. • Wash all tools with clean water immediately after application.	• Use sand or earth to contain any paint spillage. • Wear appropriate attire, especially gloves, eye protection and nose mask. • Work in a well-ventilated area. Do not breathe vapour or spray. • Avoid contact with skin as it may cause irritation. • In the case of accidental contact, wash area immediately with water and seek immediate medical attention. • To remove the paint from skin, use soap and water or appropriate cleaner.
---	---

VOC Level: VOC content does not exceed 30 ppm & complies with applicable low-VOC requirements.

* Actual Coverage may vary depending upon the application process and surface conditions.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

ANEX ADVANCE EXTERIOR EMULSION

- High Gloss & High Sheen Formula.
- Excellent Resistance to Algae & Fungal Growth
- High Light Fastness Bright Colors.
- Robust Long Term Protection Formulation.



Paint – Anex Advance
Exterior Emulsion

It is design with finest super fine pigments & specially modified Acrylic Emulsion for Total Protection for your exterior walls against any extreme weather. Anex Advance Exterior Emulsion is a value for money with excellent protection of Exterior Walls.

Recommended Usage

•Exterior Walls	For painting exterior walls, exterior cement plasters, exterior ceilings, asbestos sheets, concrete etc. *Not to be applied on surfaces/substrates with continuous seepage or dampness.
-----------------	--

General Properties

Finish	Rich Silky Smooth	Weather Resistance	Excellent for a longer period
Opacity	Excellent	Resistance to Algae & Fungi	Excellent
Flow and Leveling	Excellent	Resistance to Alkali	Passes the Alkali Resistance test
Durability	5+1 yrs	Gloss Levels/ Sheen Levels	50 -55% at 85 deg for light shades, 20-25% at 60 deg Gloss
Light Fastness	Excellent		

Safety, Environment & Health

No Added Lead, Mercury, Arsenic or Chromium	Flash Point – Not below 30 °C
Non Flammable	

Application

1. Cleaning: Free the surface from loose particles and peeling paint. Remove any previous growth of algae, fungi or moss by thorough wire brushing and cleaning with water. 2. Filling: Any surface imperfections like holes, dents and fine cracks are to be filled with Arrest Crack Fillers or White Cement Based Putty. 3. Primer: Ensure that fresh plastered surfaces are completely cured and dry. Apply a coat of Azura Super White Exterior Primer WT/ Azura Damp Arrestor Dual Primer WT,& Allow drying for 4-5 hours. Application (Topcoat): Apply 2 coats of Anex Advance Exterior Emulsion by diluting with clean Water. Maintain an interval of 4-5 hours between successive coats. • For darker shades, additional coat is recommended for complete hiding.	Application	Brush	✓
		Roller	✓
		Spray	✓
	Dilution	Brush	25-30% by volume with clean water
		Roller	10-15% by volume with clean water
		Spray	40-50% by volume with clean potable water
	Drying time	Within 1 hr	
	Overcoating Time	4-5 hrs	
	No. of coats specified	2 coats	
	Coverage (Theoretical)	60*-65* sq ft/litre for two coat finish under normal conditions.	
Stability of Thinned Paint	Use within 24 hrs.		
Precautions while Painting	• Avoid painting when the temperature is below 10 0C. • Painting is not recommended if the moisture content and alkalinity of the surface is high. • For newly plastered walls painting is recommended after 12 weeks of curing. • Please do not over-thin or over-extend the brush while painting.		
Cleaning up equipments	Wash all tools with water immediately after application.		
Post Application Instructions	For best performance of paint all algal and fungal growth must be properly washed and cleaned at regular intervals of six months.		

General Safety and Environment Information

• Keep container upright and tightly closed in a cool, dry and well ventilated location. • Keep out of reach of children. Do not store near food, drinks or animal feed. • Dispose unwanted paint safely. Do not dispose into drains, water sources or open sewers. • Wash all tools with clean water immediately after application.	• Use sand or earth to contain any paint spillage. • Wear appropriate attire, especially gloves, eye protection and nose mask. • Work in a well-ventilated area. Do not breathe vapour or spray. • Avoid contact with skin as it may cause irritation. • In the case of accidental contact, wash area immediately with water and seek immediate medical attention. • To remove the paint from skin, use soap and water or appropriate cleaner.
---	---

VOC Level: VOC content does not exceed 40 ppm & complies with applicable low-VOC requirements.

ANEX EXTERIOR EMULSION

Durable Exteriors, Unmatched Price

- Value for Money Emulsion
- Algae & Fungi Resistant
- Good Light Fastness
- Resistant to Alkali



PAINT – Economy Acrylic Exterior Emulsion

Anex Exterior Emulsion Paint is a Water Based emulsion paint, meeting the protective and decorative needs of your building's exterior. It is a fast dry coating with good coverage and adhesion. With its superior resistance to algae and fungal growth as well as to regular wear and tear, it performs admirably on exposure from humid to dry environments. High durability with superior protection makes it the best economy exterior emulsion in its class.

Recommended Usage

• Exterior Walls	For painting exterior walls, exterior cement plasters, exterior ceilings, asbestos sheets, concrete etc. *Not to be applied on surfaces/substrates with continuous seepage or dampness.
------------------	--

General Properties

Finish	Smooth & Matt		Weather Resistance	Satisfactory
Opacity	Excellent		Resistance to Algae and Fungi	Satisfactory
Flow and Leveling	Excellent		Resistance to Alkali	Passes the Alkali Resistance test.
Durability	3+1 yrs (in non-coastal areas)		Gloss Levels/ Sheen Levels	Matt Finish
Light Fastness	Satisfactory			

Safety, Environment & Health

No Added Lead, Mercury, Arsenic or Chromium	Non Flammable	Flash Point – Not below 30°C
---	---------------	------------------------------

General Information

Bases Information	5 Bases (A1 A2 A9, Fast Yellow & Brown) Also White	Colour Options	• Colours in Fandek, Mini-fandek and Exterior Shade Card • White
Preferable Primer	Azura Super White Exterior Primer		Fandek Choose from thousands of Fandek shades
Preferable Putty	Cement Based Putty		Packing • White – 1, 4, 10, 20 Ltr Packs • Bases – 0.9, 1, 3.6, 4, 9, 10, 18, 20 Ltr Packs (Colourants added extra)

Application

Surface Preparation: 1. Cleaning: Free the surface from loose particles and peeling paint. Remove any previous growth of algae, fungi or moss by thorough wire brushing and cleaning with water. 2. Filling: Any surface imperfections like holes, dents and fine cracks are to be filled with Cement Plaster or White Cement Based Putty. 3. Primer: Ensure that fresh plastered surfaces are completely cured and dry. Apply a coat of Azura Super White Exterior Primer WT or Azura Dual Damp Arrestor Primer WT, 1 ltr of paint with 1 ltr of clean water. Allow drying for 4-5 hours.	Application	Brush	✓
		Roller	✓
		Spray	✓
Application (Topcoat): Apply 2 coats of Anex Exterior Emulsion by diluting with clean water. Maintain an interval of 4-5 hours between successive coats. For horizontal surfaces, application of additional coat is recommended. ● For darker shades, additional coat is recommended for complete hiding.	Dilution	Brush	25-35% by volume with clean water
		Roller	10-15% by volume with clean water
		Spray	40-45% by volume with clean potable water
	Drying time	Within 1 hr	
	Overcoating Time	4 – 5 hrs	
	No. of coats specified	2 Coats	
	Coverage (Theoretical)	65*-75* sq ft/litre for two coat finish under normal conditions. For Virgin surface coverage will be less.	

Stability of Thinned Paint	Use within 24 hrs.
Precautions while Painting	• Avoid painting when the temperature is below 10°C. • Painting is not recommended if the moisture content and alkalinity of the surface is high. • For newly plastered walls painting is recommended after 12 weeks of curing. • Please do not over-thin or over-extend the brush while painting.
Cleaning up equipments	Wash all tools with water immediately after application.
Post Application Instructions	For best performance of paint, surfaces should be washed and cleaned at regular intervals of six months.

General Safety and Environment Information

• Keep container upright and tightly closed in a cool, dry and well ventilated location. • Keep out of reach of children. Do not store near food, drinks or animal feed. • Dispose unwanted paint safely. Do not dispose into drains, water sources or open sewers. • Wash all tools with clean water immediately after application.	• Use sand or earth to contain any paint spillage. • Wear appropriate attire, especially gloves, eye protection and nose mask. • Work in a well-ventilated area. Do not breathe vapour or spray. • Avoid contact with skin as it may cause irritation. • In the case of accidental contact, wash area immediately with water and seek immediate medical attention. • To remove the paint from skin, use soap and water or appropriate cleaner.
---	---

VOC Level: VOC content does not exceed 40 ppm & complies with applicable low-VOC requirements.

*Actual Coverage may vary depending upon the application process and surface conditions.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

AZURA LUXURY EMULSION PEARL GLOW

Royal Artistic Signatures – Ultimate in Wall Finish

- Smooth & Silky Sheen
- Best in Class Washability & Scrub Resistance
- Maximum Durability & Colour Retention
- With Finest Pigments



PAINT – Luxury Pearl Glow
Interior Acrylic Emulsion

Azura Luxury Emulsion Pearl Glow is the best in acrylic emulsion technology combined with urge to look beyond the spectrum. It is a superior quality water-based paint using special Pure acrylic emulsion and the finest pigments which are durable and light fast. Your eyes will tell you a lot and so will a gentle touch of your fingers and of course your mind will pass the final judgment.

It adds an extra dimension to your walls, making them stand out. What contributes to this fantastic transformation is a combination of attributes such as excellent flow and leveling characteristics, a rich sheen and a soft, smooth finish.

Recommended Usage

• Interior Walls	For painting internal walls, smooth plaster, false ceilings, asbestos sheets, brick-work, concrete etc. On previously painted surfaces it can be applied directly.
------------------	--

General Properties

Finish	Smooth and Silky	Light Fastness	Excellent
Opacity	Excellent	Resistance to Alkali	Passes the Alkali Resistance test
Flow and Leveling	Excellent	Gloss Levels/ Sheen Levels	25 – 35% gloss at 60Degree C 45 – 50% at 85 deg for light shades & 25 – 30% at 85 deg for dark shade.
Durability	7 – 8 yrs		

Safety, Environment & Health

No Added Lead, Mercury, Arsenic or Chromium	Non Flammable	Flash Point – Not below 30°C
---	---------------	------------------------------

General Information

Bases Information	4 Bases (A1, A2, A9 & Fast Yellow) Also White	Colour Options	• Colours in Fandack, Mini-fandack and Interior Shade Card • White
Preferable Primer	Azura Dual Damp Arrestor Primer WT	Fandack	Choose from thousands of Fandack shades
Preferable Putty	1. Acrylic Wall Putty 2. Cement Based Putty	Packing	• White – 1, 4, 10, 20 Ltr Packs • Bases – 0.9, 1, 3.6, 4, 9, 10, 18, 20 Ltr Packs (Colourants added extra)

Application

Application	Brush	✓
	Roller	✓
	Spray	✓
Dilution	Brush	25–35% by volume with clean water
	Roller	15–30% by volume with clean water
	Spray	40–50% by volume with clean water
Drying time	Within 1 hr	
Overcoating Time	4 – 5 hrs	
No. of coats specified	2–3 Coats	
Coverage (Theoretical)	150*–175* sq ft/litre for two coat finish under normal conditions. . For virgin surface coverage will be less.	

Stability of Thinned Paint	Use within 24 hrs.
Precautions while Painting	• Avoid painting when the temperature is below 10 0C. • Painting is not recommended if the moisture content and alkalinity of the surface is high. • For newly plastered walls painting is recommended after 12 weeks of curing. • Please do not over-thin or over-extend the brush while painting. • Sources of damp and efflorescence must be plugged by appropriate treatment before painting
Cleaning up equipments	Wash all tools with water immediately after application.
Post Application Instructions	To remove stains, sponge clean with a mild soap solution and wipe clean. Before cleaning, please ensure a drying time of one week.

General Safety and Environment Information

• Keep container upright and tightly closed in a cool, dry and well ventilated location. • Keep out of reach of children. Do not store near food, drinks or animal feed. • Dispose unwanted paint safely. Do not dispose into drains, water sources or open sewers. • Wash all tools with clean water immediately after application.	• Use sand or earth to contain any paint spillage. • Wear appropriate attire, especially gloves, eye protection and nose mask. • Work in a well-ventilated area. Do not breathe vapour or spray. • Avoid contact with skin as it may cause irritation. • In the case of accidental contact, wash area immediately with water and seek immediate medical attention. • To remove the paint from skin, use soap and water or appropriate cleaner.
---	---

VOC Level: VOC content does not exceed 30 ppm & complies with applicable low-VOC requirements.

*Actual Coverage may vary depending upon the application process and surface conditions.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

ASURE CLEANWALLS INTERIOR PREMIUM EMULSION

High Sheen Emulsion

- Unique Sheen Finish
- Superior Washability & Scrub Resistance
- Excellent Colour Retention & Durability
- Excellent Opacity & Coverage



Asure CleanWalls Interior Acrylic Emulsion produces the most classy and elegant walls with a High Gloss & High Sheen Smooth finish. Based on Special Acrylic Polymer Emulsion and pigmented with carefully selected Rutile Titanium Dioxide, it provides excellent opacity with good flow & levelling characteristics. It not only fulfils your decorative needs but with good alkali resistance and washability also gives a protective edge to your interior walls.

Recommended Usage

• Interior Walls	For painting internal walls, smooth plaster, false ceilings, asbestos sheets, brick-work, concrete etc. On previously painted surfaces it can be applied directly.
------------------	--

General Properties

Finish	Smooth and High Sheen		Top Coat Adhesion	Excellent
Opacity	Excellent			
Flow and Leveling	Excellent		Gloss Levels/ Sheen Levels	Highest Gloss & Sheen.
Durability	5+1 yrs		Resistance to Alkali	Passes the Alkali Resistance test

Safety, Environment & Health

Low VOC - Below 30 gm/lt	No Added Lead, Mercury, Arsenic or Chromium	Non Flammable	Flash Point - Not below 30 °C
-----------------------------	---	---------------	-------------------------------

General Information

Bases Information	4 Bases (A1,A2,A9 & Yellow)		Colour Options	• Colours in Fandack, and Azura Shade Card • White
Preferable Primer	1. Anex Super White Interior Primer Water WT 2. Azura Damp Arrestor Alkali Block Dual Primer WT.		Colour	Any Colour from any Shade cards
Preferable Putty	1. Acrylic Wall Putty 2. Cement Based Putty		Packing	• White - 1, 4, 10, 20 Ltr Packs • Bases - 0.9, 1, 3.6, 4, 9, 10, 18, 20 Ltr Packs (Colourants added extra)

Application

Surface Preparation:

1. Cleaning: Ensure the surface is clean, dry and free from efflorescence. Sand the surface with Emery Paper 180 to remove loose particles, paint, dust, grease and cracked or flaked paint. Wipe the surface clean.

2. Primer – 1st coat: Apply a coat of Anex Interior Super White Primer WT/ Azura Damp Arrestor Alkali Bloc Dual Primer WT. Allow drying for 4-6 hours.

3. Putty: Fill up minor dents, cracks and undulations with thin coats of Acrylic Wall Putty. Allow drying time for 4-6 hours. Smoothen with Emery Paper 180 and wipe the surface clean.

4. Primer – 2nd coat: Apply another coat of Anex Interior Super White Primer WT/ Azura Damp Arrestor Alkali Bloc Dual Primer WT. Allow drying for 4-6 hours. Sand with Emery Paper 320 or 400. Wipe the surface clean.

Application (Topcoat):

Apply 2 coats of Asure Cleanwalls Interior Premium Emulsion after diluting with clean water. Maintain an interval of 4-5 hours between successive coats.

● For darker shades, additional coat is recommended for complete hiding.

Application	Brush	✓
	Roller	✓
	Spray	✓
Dilution	Brush	25-35% by volume with clean potable water
	Roller	15-25% by volume with clean potable water
	Spray	40-45% by volume with clean potable water
Drying time	Within 1 hr	
Overcoating Time	4 – 5 hrs	
No. of coats specified	2 Coats	
Coverage (Theoretical)	125*-150* sq ft/litre for two coat finish under normal conditions. For Virgin surface coverage will be less.	

Stability of Thinned Paint	Use within 24 hrs.
Precautions while Painting	• Avoid painting when the temperature is below 10 °C. • Painting is not recommended if the moisture content and alkalinity of the surface is high. • For newly plastered walls painting is recommended after 12 weeks of curing. • Please do not over-thin or over-extend the brush while painting.
Cleaning up equipments	Wash all tools with water immediately after application.
Post Application Instructions	To remove stains, sponge clean with a mild soap solution and wipe clean. Before cleaning, please ensure a drying time of one week.

General Safety and Environment Information

• Keep container upright and tightly closed in a cool, dry and well ventilated location. • Keep out of reach of children. Do not store near food, drinks or animal feed. • Dispose unwanted paint safely. Do not dispose into drains, water sources or open sewers. • Wash all tools with clean water immediately after application.	• Use sand or earth to contain any paint spillage. • Wear appropriate attire, especially gloves, eye protection and nose mask. • Work in a well-ventilated area. Do not breathe vapour or spray. • Avoid contact with skin as it may cause irritation. • In the case of accidental contact, wash area immediately with water and seek immediate medical attention. • To remove the paint from skin, use soap and water or appropriate cleaner.
---	---

VOC Level: VOC content does not exceed 30 ppm & complies with applicable low-VOC requirements.

* Actual Coverage may vary depending upon the application process and surface conditions.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

ANEX ADVANCE INTERIOR EMULSION

- Excellent Gloss/Sheen Finish.
- Value for Money Interior Superior Quality Emulsion.
- Excellent Colour Retention & Durability
- Higher Opacity & Coverage.
- Long Protection against Fungal & Alae Growth



Paint – Anex Advance
Interior Emulsion

Anex Advance Interior Acrylic Emulsion gives high Sheen/Gloss for your dream walls. Based on Special Acrylic Polymer Emulsion and super fine pigmented with carefully selected Rutile Titanium Dioxide, it provides excellent opacity with good flow & leveling characteristics.

General Properties

Finish	Smooth and High Sheen	Light Fastness	Excellent
Opacity	Excellent		High Gloss & Sheen
Flow and Leveling	Excellent		
Durability	5+1 yrs		Passes the Alkali Resistance test

Safety, Environment & Health

Low VOC – Below 30 gm/lt	No Added Lead, Mercury, Arsenic or Chromium
Non Flammable	Flash Point – Not below 30 °C

Application

Surface Preparation: 1. Cleaning: Ensure the surface is clean, dry and free from efflorescence. Sand the surface with Emery Paper 180 to remove loose particles, paint, dust, grease and cracked or flaked paint. Wipe the surface clean. 2. Primer – 1st coat: Apply a coat of Azura Super White Primer WT/ Azura Damp Arrestor Alkali Bloc Dual Primer WT. Allow drying for 4-6 hours. 3. Putty: Fill up minor dents, cracks and undulations with thin coats of Acrylic Wall Putty. Allow drying time for 4-6 hours. Smoothen with Emery Paper 180 and wipe the surface clean. 4. Primer – 2nd coat: Apply another coat Azura Super White Exterior Primer WT/ Azura Damp Arrestor Alkali Bloc Dual Primer WT for virgin surface. Allow drying for 4-6 hours. Sand with Emery Paper 320 or 400. Wipe the surface clean.	Application	Brush	✓
		Roller	✓
		Spray	✓
	Dilution	Brush	25-30% by volume with clean potable water
		Roller	15-20% by volume with clean potable water.
		Spray	45-45% by volume with clean potable water
	Drying time	Within 1 hr.	
	Overcoating Time	4 - 5 hrs	
	No. of coats specified	2 Coats	
	Coverage (Theoretical)	125*-150* sq ft/litre for two coat finish under normal conditions	

Application

Application (Topcoat):

Apply 2 coats of Anex Advance Interior Emulsion Interior Emulsion after diluting with clean water. Maintain an interval of 4-5 hours between successive coats.

- For darker shades, additional coat is recommended for complete hiding.

Stability of Thinned Paint	Use within 24 hrs.
Precautions while Painting	• Avoid painting when the temperature is below 10 °C. • Painting is not recommended if the moisture content and alkalinity of the surface is high. • For newly plastered walls painting is recommended after 12 weeks of curing. • Please do not over-thin or over-extend the brush while painting. • Sources of damp and efflorescence must be plugged by appropriate treatment before painting.
Cleaning up equipments	Wash all tools with water immediately after application.
Post Application Instructions	To remove stains, sponge clean with a mild soap solution and wipe clean. Before cleaning, please ensure a drying time of one week.

VOC Level: VOC content does not exceed 40 ppm & complies with applicable low-VOC requirements.

ANEX SUPER WHITE INTERIOR EMULSION

Value for money Emulsion

- Low VOC
- Higher Coverage
- Cost/Area Comparable to Economic Emulsion
- Long Lasting Paint for Beautiful & Attractive Walls



PAINT – Economy Acrylic Interior Emulsion

Anex Super White Interior Emulsion is an acrylic based economy quality emulsion paint with a smooth matt finish, much superior to Economic Emulsion. Anex Super White Interior Emulsion is an assurance of beautiful, attractive walls that lasts for years.

Recommended Usage

• Interior Walls	For painting internal walls, smooth plaster, false ceilings, asbestos sheets, brick-work, concrete etc. On previously painted surfaces it can be applied directly.
------------------	--

General Properties

Finish	Smooth and Matt		Light Fastness	Satisfactory
Opacity	Satisfactory		Flow and Leveling	Satisfactory
Durability	4 – 5 yrs		Gloss Levels/ Sheen Levels	Matt Finish

Safety, Environment & Health

Low VOC – Below 30 gm/lt	No Added Lead, Mercury, Arsenic or Chromium	Non Flammable	Flash Point – Not below 30°C
--------------------------	---	---------------	------------------------------

General Information

Bases Information	4 Bases (A1,A2,A9 & Fast Yellow) Also White		Colour Options	• Colours in Fandack, Mini-fandack and Shade Card • White
Preferable Primer	Anex Super White Interior Primer WT.		Fandack	Choose from thousands of Fandack shades
Preferable Putty	1. Acrylic Wall Putty 2. Cement Based Putty		Packing	• White & A1 Base – 1, 4, 10, 20 Ltr Packs • A2 & A9 Bases – 0.9, 3.6, 9, 18, Ltr Packs (Colourants added extra)

Application

Surface Preparation:

1. Cleaning: Ensure the surface is clean, dry and free from efflorescence. Sand the surface with Emery Paper 180 to remove loose particles, paint, dust, grease and cracked or flaked paint. Wipe the surface clean.

2. Primer – 1st coat: Apply a coat of Anex Super White Water Thinnable Cement Primer. Allow drying for 4-6 hours.

3. Putty: Fill up minor dents, cracks and undulations with thin coats of Acrylic Wall Putty. Allow drying time for 4-6 hours. Smoothen with Emery Paper 180 and wipe the surface clean.

4. Primer – 2nd coat: Apply another coat of Azura Super White Water Thinnable Cement Primer. Allow drying for 4-6 hours. Sand with Emery Paper 320 or 400. Wipe the surface clean.

Application (Topcoat):

Apply 2-3 coats of Anex Super White Acrylic Emulsion after diluting with clean water. Maintain an interval of 4-5 hours between successive coats.

- For darker shades, additional coat is recommended for complete hiding.

Application	Brush	✓
	Roller	✓
	Spray	✓
Dilution	Brush	25-35% by volume with clean water
	Roller	15-25% by volume with clean water
	Spray	40-45% by volume with clean water
Drying time	Within 1 hr	
Overcoating Time	4 – 5 hrs	
No. of coats specified	2-3 Coats	
Coverage (Theoretical)	120*-140* sq ft/litre for two coat finish under normal conditions. For Virgin surface coverage will be less.	

Stability of Thinned Paint	Use within 24 hrs.
Precautions while Painting	• Avoid painting when the temperature is below 10 °C or above 42 °C • Painting is not recommended if the moisture content and alkalinity of the surface is high. • For newly plastered walls painting is recommended after 12 weeks of curing. • Please do not over-extend the brush while painting. • Sources of damp and efflorescence must be plugged by appropriate treatment before painting
Cleaning up equipments	Wash all tools with water immediately after application.
Post Application Instructions	To remove stains, sponge clean with a mild soap solution and wipe clean. Before cleaning, please ensure a drying time of one week.

General Safety and Environment Information

• Keep container upright and tightly closed in a cool, dry and well ventilated location. • Keep out of reach of children. Do not store near food, drinks or animal feed. • Dispose unwanted paint safely. Do not dispose into drains, water sources or open sewers. • Wash all tools with clean water immediately after application.	• Use sand or earth to contain any paint spillage. • Wear appropriate attire, especially gloves, eye protection and nose mask. • Work in a well-ventilated area. Do not breathe vapour or spray. • Avoid contact with skin as it may cause irritation. • In the case of accidental contact, wash area immediately with water and seek immediate medical attention. • To remove the paint from skin, use soap and water or appropriate cleaner.
---	---

VOC Level: VOC content does not exceed 40 ppm & complies with applicable low-VOC requirements.

*Actual Coverage may vary depending upon the application process and surface conditions. The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

AZURA ADVANCE DAMP ARRESTOR ALKALI BLOC DUAL PRIMER

PRIMER – Water Based Primer for Dual Purpose

- For Exterior & Interior Walls
- Good Flow & Leveling
- Good Top Coat Adhesion
- Damp Arrestor & Alkali Bloc
- Quick Drying



Azura Advance Damp Arrestor
Alkali Bloc Dual Primer

Azura Advance Damp Arrestor Alkali Bloc Dual Primer is a white-colored primer based on 100% Acrylic Emulsion which is specially designed for Damp Arrest & Alkali Bloc application on exterior & interior walls made of sand, cement, plaster, asbestos, brick etc. It covers stains and discolorations; hides surface marks & darker colours; as well as seals and levels the porous surfaces; thus, preparing the surface for a beautiful, uniform and long-lasting final coat. It has nanoparticles Fumed Silica & Lucent fibre reinforcement technology.

Strong Benefits

The Nanoparticles & Fumed Silica Technology helps fill up all the porosity, improving water penetration controls.	Lucent Fibre Technology helps reinforce Paint film for better film strength.	This Primer has excellent top coat adhesion and retention.
---	--	--

Recommended Usage

• Exterior Walls	It can be used as a primer for exterior walls, interior walls & ceilings made of sand, cement, plaster, asbestos, cement, brick etc.
------------------	--

General Properties

Finish	Smooth & Matt	Top Coat Adhesion	Satisfactory
Opacity	Satisfactory	Resistance to Algae & Fungi	Satisfactory
Flow and Leveling	Satisfactory	Resistance to Alkali	Satisfactory
Durability	10 yrs on system	Flexibility	Satisfactory
Consistency	Thixotropic	Damp arresting Quality	Excellent

Safety, Environment & Health

No Added Lead, Mercury, Arsenic or Chromium	Non Flammable
---	---------------

General Information

Preferable Putty	Cement Based Putty	Packing	1, 4, 10, 20 Ltr Packs
------------------	--------------------	---------	------------------------

Application

Surface Preparation: 1. Cleaning: Free the surface from loose particles and peeling paint. Remove any previous growth of algae, fungi or moss by thorough wire-brushing and cleaning with water. Antifungal wash after cleaning the algae & fungi has been proven very effective. 2. Filling – Any surface imperfections like holes, dents and fine cracks are to be filled with Cement Putty or Acrylic Putty. 3. Primer – Ensure that fresh plastered surfaces are completely cured and dry. Apply a coat of Azura Advance Damp Arrestor Alkali Bloc Dual Primer WT thinning with 30% water. Allow drying for 4-6 hours. Application (Topcoat): Apply 2 coats of Azura Advance Exterior Emulsion Long Life diluting with clean water. Maintain an interval of 4-6 hours between successive coats. For horizontal surfaces, the application of an additional coat is recommended. ● For darker shades, additional coat is recommended for complete hiding.	Application	Brush	✓
		Roller	✗
		Spray	✓
	Dilution	Brush	Single Coat: Dilute 35 – 45% by volume with clean potable water. For porous surfaces, a two coat application is necessary. 1st coat is to be done by thinning primer with 1:1 by volume with clean potable water. For 2nd coat, dilute 40-50% by volume with water.
		Roller	NA
		Spray	50-55% by volume with clean potable water.
	Drying time	Within 1 hr	
	Overcoating Time	4 – 5 hrs	
	No. of coats specified	1-2 Coats	
	Coverage (Theoretical)	90-95* sq ft/litre per coat under normal conditions. For Virgin surface coverage will be less.	
Stability of Thinned Paint	Use within 24 hrs.		
Precautions while Painting	• Avoid painting when the temperature is below 10 °C. • Painting is not recommended if the moisture content and alkalinity of the surface is high. • For newly plastered walls painting is recommended after 12 weeks of curing.		
Cleaning up equipments	Wash all tools with water immediately after application.		

General Safety and Environment Information

• Keep container upright and tightly closed in a cool, dry and well ventilated location. • Keep out of reach of children. Do not store near food, drinks or animal feed. • Dispose unwanted paint safely. Do not dispose into drains, water sources or open sewers. • Wash all tools with clean water immediately after application.	• Use sand or earth to contain any paint spillage. • Wear appropriate attire, especially gloves, eye protection and nose mask. • Work in a well-ventilated area. Do not breathe vapour or spray. • Avoid contact with skin as it may cause irritation. • In the case of accidental contact, wash area immediately with water and seek immediate medical attention. • To remove the paint from skin, use soap and water or appropriate cleaner.
---	---

VOC Level: VOC content does not exceed 30 ppm & complies with applicable low-VOC requirements.

AZURA DAMP ARRESTOR ALKALI BLOC ACRYLIC BASE SUPER WHITE DUAL PRIMER WT

- For Exterior & Interior Walls
- Good Flow & Leveling
- Good Top Coat Adhesion
- Damp Arrestor & Alkali Bloc
- Quick Drying



PRIMER – Water Based Primer
for Dual Walls

Azura Damp Arrestor Alkali Bloc Acrylic Base Super White Dual Primer W.T is a white coloured primer based on 100% Acrylic Emulsion which is specially designed for Damp Arrestor & Alkali Bloc application on exterior & interior walls made of sand cement plaster, asbestos, brick etc. It covers stains and discolorations; hides surface marks & darker colours; as well as seals and levels the porous surfaces; thus, preparing the surface for a beautiful, uniform and long-lasting final coat.

Recommended Usage

- | | |
|------------------|--|
| • Exterior Walls | It can be used as primer for interior walls & ceilings made of sand cement plaster, asbestos, cement, brick etc. |
|------------------|--|

General Properties

Finish	Smooth & Matt		Top Coat Adhesion	Satisfactory
Opacity	Satisfactory		Resistance to Algae & Fungi	Satisfactory
Flow and Leveling	Satisfactory		Resistance to Alkali	Satisfactory
Durability	5-7 yrs on system		Flexibility	Satisfactory
Consistency	Thixotropic		Damp arresting Quality	Excellent.

Safety, Environment & Health

No Added Lead, Mercury, Arsenic or Chromium	Non Flammable
---	---------------

General Information

Preferable Putty	Cement Based Putty		Packing	1, 4, 10, 20 Ltr Packs
------------------	--------------------	--	---------	------------------------

Application

1. Cleaning: Ensure the surface is clean, dry and free from efflorescence. Any algae, fungi or moss should be removed thoroughly by wire brushing & cleaning with water. Sand the surface with Emery Paper 180 to remove loose particles, paint, dust, grease and cracked or flaked paint. Wipe the surface clean. 2. Primer –1st Coat: Apply a coat of Azura Super White Exterior Primer W.T by diluting it in the ratio of 1:1 by volume with water. Allow drying for 4-5 hours. Sand with Emery Paper 180 and wipe the surface clean. 3. Putty (Optional): Fill up minor dents, cracks and undulations with thin coats of Cement Wall Putty. Allow drying time for 4-6 hours. Smoothen with Emery Paper 180 and wipe the surface clean. 4. Primer –2nd Coat: Apply another coat of Azura Super White Exterior Primer W.T by diluting with 60-70% by volume with water. Allow drying for 4-5 hours. Sand lightly with Emery Paper 320 or 400. Wipe the surface clean.	Application	Brush	✓
		Roller	✗
		Spray	✓
	Dilution	Brush	Single Coat: Dilute 30 – 40% by volume with clean potable water. Double Coat: For porous surface two coats application is necessary. 1st coat to be done by thinning primer with 1:1 by volume with clean potable water. For 2nd coat dilute 45-50% by volume with water.
		Roller	NA
		Spray	60-70% by volume with clean potable water.
	Drying time	Within 1 hr	
	Overcoating Time	4 – 5 hrs	
	No. of coats specified	1 -2 coats	
	Coverage (Theoretical)	105-130* sq ft/litre per coat under normal conditions. For Virgin surface coverage will be less.	
Stability of Thinned Paint		Use within 24 hrs.	
Precautions while Painting		• Avoid painting when the temperature is below 10 °C. • Painting is not recommended if the moisture content and alkalinity of the surface is high. • For newly plastered walls painting is recommended after 12 weeks of curing.	
Cleaning up equipments		Wash all tools with water immediately after application.	

General Safety and Environment Information

- | | |
|---|---|
| <ul style="list-style-type: none"> • Keep container upright and tightly closed in a cool, dry and well ventilated location. • Keep out of reach of children. Do not store near food, drinks or animal feed. • Dispose unwanted paint safely. Do not dispose into drains, water sources or open sewers. • Wash all tools with clean water immediately after application. | <ul style="list-style-type: none"> • Use sand or earth to contain any paint spillage. • Wear appropriate attire, especially gloves, eye protection and nose mask. • Work in a well-ventilated area. Do not breathe vapour or spray. • Avoid contact with skin as it may cause irritation. • In the case of accidental contact, wash area immediately with water and seek immediate medical attention. • To remove the paint from skin, use soap and water or appropriate cleaner. |
|---|---|

VOC Level: VOC content does not exceed 30 ppm & complies with applicable low-VOC requirements.

*Actual Coverage may vary depending upon the application process and surface conditions.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

AZURA ACRYLIC BASE SUPER WHITE EXTERIOR PRIMER WT

Durable Brilliant Silver Finish

- For Exterior Walls
- Good Flow & Leveling
- Good Top Coat Adhesion
- Quick Drying



PRIMER – Water Based Primer for Exterior Walls

Azura Acrylic Base Super White Exterior Primer W.T is a white coloured primer based on 100% Acrylic Emulsion which is specially designed for application on exterior walls made of sand cement plaster, asbestos, brick etc. It covers stains and discolorations; hides surface marks & darker colours; as well as seals and levels the porous surfaces; thus preparing the surface for a beautiful, uniform and long-lasting final coat.

Recommended Usage

- Exterior Walls

It can be used as primer for interior walls & ceilings made of sand cement plaster, asbestos, cement, brick etc.

General Properties

Finish	Smooth & Matt		Top Coat Adhesion	Satisfactory
Opacity	Satisfactory		Resistance to Algae & Fungi	Satisfactory
Flow and Leveling	Satisfactory		Resistance to Alkali	Satisfactory
Durability	4-5 yrs on system		Flexibility	Satisfactory
Consistency	Thixotropic		Gloss Levels/ Sheen Levels	Matt Finish

Safety, Environment & Health

No Added Lead, Mercury, Arsenic or Chromium

Non Flammable

General Information

Preferable Putty	Cement Based Putty		Packing	1, 4, 10, 20 Ltr Packs
------------------	--------------------	--	---------	------------------------

Application

1. Cleaning:

Ensure the surface is clean, dry and free from efflorescence. Any algae, fungi or moss should be removed thoroughly by wire brushing & cleaning with water. Sand the surface with Emery Paper 180 to remove loose particles, paint, dust, grease and cracked or flaked paint. Wipe the surface clean.

2. Primer –1st Coat:

Apply a coat of Azura Super White Exterior Primer W.T by diluting it in the ratio of 1:1 by volume with water. Allow drying for 4-5 hours. Sand with Emery Paper 180 and wipe the surface clean.

3. Putty (Optional):

Fill up minor dents, cracks and undulations with thin coats of Cement Wall Putty. Allow drying time for 4-6 hours. Smoothen with Emery Paper 180 and wipe the surface clean.

4. Primer –2nd Coat:

Apply another coat of Azura Super White Exterior Primer W.T by diluting with 60-70% by volume with water. Allow drying for 4-5 hours. Sand lightly with Emery Paper 320 or 400. Wipe the surface clean.

Application	Brush	✓
	Roller	✗
	Spray	✓
Dilution	Brush	Single Coat: Dilute 30 – 40% by volume with clean potable water. Double Coat: For porous surface two coats application is necessary. 1st coat to be done by thinning primer with 1:1 by volume with clean potable water. For 2nd coat dilute 40-50% by volume with water.
	Roller	NA
	Spray	60-70% by volume with clean potable water.
Drying time	Within 1 hr	
Overcoating Time	4 – 5 hrs	
No. of coats specified	1 -2 coats	
Coverage (Theoretical)	105-130* sq ft/litre per coat under normal conditions. For Virgin surface coverage will be less.	

Stability of Thinned Paint

Use within 24 hrs.

Precautions while Painting

- Avoid painting when the temperature is below 10 °C.
- Painting is not recommended if the moisture content and alkalinity of the surface is high.
- For newly plastered walls painting is recommended after 12 weeks of curing.

Cleaning up equipments

Wash all tools with water immediately after application.

General Safety and Environment Information

- Keep container upright and tightly closed in a cool, dry and well ventilated location.
- Keep out of reach of children. Do not store near food, drinks or animal feed.
- Dispose unwanted paint safely. Do not dispose into drains, water sources or open sewers.
- Wash all tools with clean water immediately after application.

- Use sand or earth to contain any paint spillage.
- Wear appropriate attire, especially gloves, eye protection and nose mask.
- Work in a well-ventilated area. Do not breathe vapour or spray.
- Avoid contact with skin as it may cause irritation.
- In the case of accidental contact, wash area immediately with water and seek immediate medical attention.
- To remove the paint from skin, use soap and water or appropriate cleaner.

VOC Level: VOC content does not exceed 30 ppm & complies with applicable low-VOC requirements.

*Actual Coverage may vary depending upon the application process and surface conditions.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

ANEX SUPER WHITE ACRYLIC INTERIOR PRIMER WT

- Low VOC
- For Interior Walls
- Good Top Coat Adhesion
- Good Flow & Leveling
- Hides Stains & Discolourations
- Quick Drying



PRIMER – Water Based Primer for Interior Walls

WTCP is a white coloured primer based on acrylic co-polymer emulsion which can be applied over a variety of interior walls & ceilings. It fills the porous areas absolutely, prepares the wall by hiding stains & dark discolorations and levels the surface for best adhesion of the top coat. It also resists alkali providing recipe for a smooth and durable finish top coat.

Recommended Usage

- Interior Walls

It can be used as primer for interior walls & ceilings made of sand cement plaster, asbestos, cement, brick etc.

General Properties

Finish	Smooth & Matt		Top Coat Adhesion	Satisfactory
Opacity	Satisfactory		Resistance to Alkali	Satisfactory
Flow and Leveling	Satisfactory			
Durability	4-5 yrs on system		Flexibility	Satisfactory
Consistency	Thixotropic		Gloss Levels/ Sheen Levels	Matt Finish

Safety, Environment & Health

Low VOC- Below 30 gm/lt	No Added Lead, Mercury, Arsenic or Chromium	Non Flammable
-------------------------	---	---------------

General Information

Preferable Putty	1. Acrylic Wall Putty 2. Cement Based Putty		Packing	1, 4, 10, 20 Ltr Packs
------------------	--	--	---------	------------------------

Application

1. Cleaning: Ensure the surface is clean, dry and free from efflorescence. Sand the surface with Emery Paper 180 to remove loose particles, paint, dust, grease and cracked or flaked paint. Wipe the surface clean. 2. Primer-1st Coat: Apply a coat of Anex Water Thinnable Super White Primer by diluting it in the ratio of 1:1 by volume with water. Allow drying for 4-5 hours. Sand with Emery Paper 180 paper and wipe the surface clean. 3. Putty (Optional): Fill up minor dents, cracks and undulations with thin coats of Acrylic Wall Putty. Allow drying time for 4-6 hours. Smoothen with Emery Paper 180 and wipe the surface clean. 4. Primer -2nd Coat: Apply another coat of Anex Water Thinnable Super White Primer by diluting with 60-70% by volume with water. Allow drying for 4-5 hours. Sand lightly with Emery Paper 320 or 400. Wipe the surface clean.	Application	Brush	✓
		Roller	✗
		Spray	✓
Dilution		Brush	Single Coat: Dilute 35 – 40% by volume with clean potable water. Double Coat: For porous surface two coats application is necessary. 1st coat to be done by thinning primer with 1:1 by volume with clean potable water. For 2nd coat dilute 40-50% by volume with water.
		Roller	NA
		Spray	40-50% by volume with clean potable water.
Drying time			Within 1 hr
Overcoating Time			4 – 5 hrs
No. of coats specified			1 -2 coat
Coverage (Theoretical)			150-180* sq ft/litre per coat under normal conditions. For Virgin surface coverage will be less.

Stability of Thinned Paint

Use within 24 hrs.

Precautions while Painting

- Avoid painting when the temperature is below 10 °C.
- Painting is not recommended if the moisture content and alkalinity of the surface is high.
- For newly plastered walls painting is recommended after 12 weeks of curing.

Cleaning up equipments

Wash all tools with water immediately after application.

General Safety and Environment Information

- Keep container upright and tightly closed in a cool, dry and well ventilated location.
- Keep out of reach of children. Do not store near food, drinks or animal feed.
- Dispose unwanted paint safely. Do not dispose into drains, water sources or open sewers.
- Wash all tools with clean water immediately after application.
- Use sand or earth to contain any paint spillage.
- Wear appropriate attire, especially gloves, eye protection and nose mask.
- Work in a well-ventilated area. Do not breathe vapour or spray.
- Avoid contact with skin as it may cause irritation.
- In the case of accidental contact, wash area immediately with water and seek immediate medical attention.
- To remove the paint from skin, use soap and water or appropriate cleaner.

VOC Level: VOC content does not exceed 40 ppm & complies with applicable low-VOC requirements.

*Actual Coverage may vary depending upon the application process and surface conditions.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

AMAJE SUPER WHITE UNIVERSAL PRIMER WT

- For Interior & Exterior Walls
- Good Top Coat Adhesion
- Good Flow & Leveling
- Excellent Coverage
- Quick Drying



Amaje Super White Universal Primer WT is a white coloured primer based on acrylic co-polymer emulsion which can be applied over a variety of Interior & Exterior walls & ceilings. It fills the porous areas absolutely, prepares the wall by hiding stains & dark discolorations and levels the surface for best adhesion of the top coat. It also resists alkali providing recipe for a smooth and durable finish top coat.

Recommended Usage

- | | |
|------------------|---|
| • Interior Walls | It can be used as primer for Interior & Exterior walls & ceilings made of sand cement plaster, asbestos, cement, brick etc. |
|------------------|---|

General Properties

Finish	Smooth & Matt		Top Coat Adhesion	Satisfactory
Opacity	Satisfactory		Resistance to Alkali	Satisfactory
Flow and Leveling	Satisfactory		Flexibility	Satisfactory
Durability	5+1 years on system		Gloss Levels/ Sheen Levels	Matt Finish
Consistency	Thixotropic			

Safety, Environment & Health

- | | | |
|-------------------------------|---|-----------------|
| • Low VOC
- Below 30 gm/lt | • No Added Lead, Mercury, Arsenic or Chromium | • Non Flammable |
|-------------------------------|---|-----------------|

General Information

Preferable Putty	1. Acrylic Wall Putty 2. Cement Based Putty	Packing	1, 4, 10, 20 Ltr Packs
------------------	--	---------	------------------------

Application

Surface Preparation:

1. Cleaning: Ensure the surface is clean, dry and free from efflorescence. Sand the surface with Emery Paper 180 to remove loose particles, paint, dust, grease and cracked or flaked paint. Wipe the surface clean.

2. Primer-1st Coat: Apply a coat of Amaje Super White Universal Primer WT by diluting it in the ratio of 1:1 by volume with clean water. Allow drying for 4-5 hours. Sand with Emery Paper 180 paper and wipe the surface clean.

3. 7. Putty (Optional): Fill up minor dents, cracks and undulations with thin coats of Acrylic Wall Putty. Allow drying time for 4-6 hours. Smoothen with Emery Paper 180 and wipe the surface clean.

4. Primer -2nd Coat: Apply another coat of Amaje Super White Universal Primer WT by diluting with 60-70% by volume with water. Allow drying for 4-5 hours. Sand lightly with Emery Paper 320 or 400. Wipe the surface clean.

- For darker shades, additional coat is recommended for complete hiding.

Stability of Thinned Paint	Use within 24 hrs.
Precautions while Painting	• Avoid painting when the temperature is below 10 °C. • Painting is not recommended if the moisture content and alkalinity of the surface is high. • For newly plastered walls painting is recommended after 12 weeks of curing.
Cleaning up equipments	Wash all tools with water immediately after application.

General Safety and Environment Information

- | | |
|---|---|
| <ul style="list-style-type: none"> • Keep container upright and tightly closed in a cool, dry and well ventilated location. • Keep out of reach of children. Do not store near food, drinks or animal feed. • Dispose unwanted paint safely. Do not dispose into drains, water sources or open sewers. • Wash all tools with clean water immediately after application. | <ul style="list-style-type: none"> • Use sand or earth to contain any paint spillage. • Wear appropriate attire, especially gloves, eye protection and nose mask. • Work in a well-ventilated area. Do not breathe vapour or spray. • Avoid contact with skin as it may cause irritation. • In the case of accidental contact, wash area immediately with water and seek immediate medical attention. • To remove the paint from skin, use soap and water or appropriate cleaner. |
|---|---|

VOC Level: VOC content does not exceed 30 ppm & complies with applicable low-VOC requirements.

* Actual Coverage may vary depending upon the application process and surface conditions.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

AZURA 5 IN 1 HI-GLOSS SYNTHETIC ENAMEL

Ultimate Gloss Enamel

- Anti-Rust
- Tough Resistant Film
- Super-gloss Finish and Retention
- Strong Resistance to Wear and Abrasion
- Resistant to Mild Corrosive Chemicals



Azura Hi-Gloss Synthetic Enamel is the most advanced gloss paint with excellent film integrity and built-in-toughness. It extends a luxurious, brilliant glossy finish to the surface for years. Its abrasion resistance qualities, along with ability to resist corrosive chemicals keeps your painted surface smooth and smart even against the most severe punishment.

Recommended Usage

• Metal Surfaces	Recommended for use on metal and wood surfaces in both interior and exterior.
• Wood Surfaces	

General Properties

Finish	High Gloss		Flexibility	Excellent - ¼ inch (As per IS 101)
Opacity	Excellent		Hardness	Excellent - 900-1000 gms (As per IS 101)
Flow and Leveling	Excellent		Consistency	Smooth & Uniform
Durability	4+ yrs		Weather Resistance	Satisfactory
Gloss Levels/ Sheen Levels	85 - 90% at 60 deg		Acid & Alkali Resistance	Resistant to mild Acid & Alkali
Light Fastness	Satisfactory			

Safety, Environment & Health

Flammable - Avoid Exposure to flame	Flash Point - Not below 30 °C
-------------------------------------	-------------------------------

General Information

Bases Information	3 Bases (A1,A2,A9)		Colour Options	• Colours in Fandack, Mini-fandack and Azura Hi-Gloss Enamel Shade Card • Dazzel White & Black
Preferable Primer	• Ferrous Metal - Anex Red Oxide Primer • Non Ferrous Metal - Anex Zinc Chrome Yellow Primer • Wood - White/Pink Primer		Fandack	Choose from thousands of Fandack shades
Preferable Putty	Wood - Synthetic Putty		Packing	• Ready Shades - 0.05, 0.1, 0.2, 0.5, 1, 4, 10, 20 Ltr Packs • Bases - 0.9, 1, 3.6, 4, 9, 10, 18, 20 Ltr Packs (Colourants added extra)

Application

Surface Preparation:

1. Cleaning: Free the surface from grease, rust, moisture, loose particles and peeling/flaking paint by sanding with Emery Paper 180.

2. Priming: Ferrous Metal Surface - Apply 1-2 coats of Anex Red Oxide Primer on the metal surface by thinning (if necessary) with Thinner. Allow drying for 8-10 hrs after each coat.

Non-Ferrous Metal Surface - Apply 1-2 coat of Anex Zinc Chrome Yellow Primer on the metal surface by thinning (if necessary) it with Thinner. Allow drying for 8 hrs.

Wooden Surface - Apply first coat of Pink/White Primer on the wooden surface by thinning (if necessary) with Thinner. Allow drying for 5-6 hrs. Use any synthetic Putty to fill minor cracks, dents or holes. After drying sand the surface with Emery Paper 180. Apply another coat of Pink/White Primer. Allow drying for 5-6 hrs.

Application (Topcoat):

Apply two coats of Azura Hi-Gloss Synthetic Enamel after thorough stirring and diluting (if required) with Thinner. Maintain an interval of 6-8 hrs between successive coats.

Stability of Thinned Paint	Use within 24 hrs.
Precautions while Painting	• Avoid painting when the temperature is below 10 °C. • Painting is not recommended if the moisture content and alkalinity of the surface is high. • For newly plastered walls painting is recommended after 12 weeks of curing. • Please do not over-thin or over-extend the brush while painting
Cleaning up equipments	All equipments should be cleaned with Thinner.
Post Application Instructions	To remove stains, sponge clean with a mild soap solution and wipe clean. Before cleaning, please ensure a drying time of one week

General Safety and Environment Information

- Keep container upright and tightly closed in a cool, dry and well ventilated location away from heat source, flammables and direct sunlight.
- Keep out of reach of children. Do not store near food, drinks or animal feed.
- Dispose unwanted paint safely. Do not dispose into drains, water sources or open sewers.
- Wash all tools after application with General Purpose Thinner or Mineral Turpentine.
- Use sand or earth to contain any paint spillage
- Wear appropriate attire, especially gloves, eye protection and nose mask.
- Work in a well-ventilated area. Do not breathe vapour or spray.
- Remove paint from skin by washing with water and soap or appropriate cleaner.
- Avoid contact with skin as it may cause irritation.
- In the case of accidental contact, wash area immediately with water and seek immediate medical attention.
- To remove the paint from skin, use soap and water or appropriate cleaner.

*Actual Coverage may vary depending upon the application process and surface conditions.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

AZURA SINGLE PACK ALUMINIUM PAINT

Durable Brilliant Silver Finish

- Maximum Colour and Gloss Retention
- Excellent Hiding and Coverage
- Exceptional Water, Weather & Corrosion Resistance
- Exceptional Durability



PAINT – Single Pack Synthetic Aluminium Paint

Azura Single Pack Aluminum Paint is a single pack 'ready to use' Aluminium Paint. Based on a synthetic medium, it incorporates flake Aluminium with a high leafing quality producing a smooth film with more uniform colour. Every coat of Azura Single Pack Aluminium Paints promises exceptional colour brilliance which reflects heat & light and provides superb resistance to weather and corrosion. Recommended for both interior and exterior surfaces, it can be applied on Oil & Petroleum storage tanks, pipelines, rolling shutter etc as well.

Recommended Usage

• Metal Surfaces	Recommended for use in all interior & exterior metal surfaces after proper surface preparation. Also applicable on wooden surfaces.
• Wood Surfaces	

General Properties

Finish	Bright, Lustrous & Smooth.		Hardness (Mandrell)	Passes 1 Kg load
Opacity	NA		Heat Resistance	Paint film stable even at 200°C
Flow and Leveling	Satisfactory		Chemical Resistance	Resistant to mild chemical fume attack.
Durability	Minimum 4 years.		Special Feature	It is stabilized system and does not darken in storage.
Consistency	Smooth & Uniform		Water Resistance	Resistant to atmospheric humidity present in normal interior & exterior environment and also withstand repeated washing. But unsuitable for use on immersed surfaces.
Flexibility & Adhesion	Excellent			
Corrosion Resistance	Excellent			

Depends on depends on surface preparation & environmental condition.

Safety, Environment & Health

Flammable – Avoid Exposure to flame	Flash Point – Not below 30 oC
-------------------------------------	-------------------------------

General Information

Bases Information	NA	Colour Options	Silver Finish
Preferable Primer	• Ferrous Metal – Anex Red Oxide Primer • Non Ferrous Metal – Anex Zinc Chromate Yellow Primer • Wood – White/Pink Primer		Fandeck
Preferable Putty	Wood – Synthetic Putty		Packing
			1, 4, 20 Ltr Packs

Application

Surface Preparation:

1. Cleaning: Free the surface from grease, rust, moisture, loose particles and peeling/flaking paint by sanding with Emery Paper 180. Steel surfaces should be manually prepared through power or hand tool. New galvanized and Aluminium surfaces should be cleaned and degreased, followed by pre-treatment with an appropriate pre-treatment primer to ensure good adhesion.

2. Primer: Ferrous Metal Surface – Apply 1-2 coats of Anex Red Oxide Primer on the metal surface by thinning (if necessary) with Thinner. Allow drying for 6-8 hrs after each coat. Non-Ferrous Metal Surface – Apply 1-2 coat of Anex Zinc Chrome Yellow Primer on the metal surface by thinning (if necessary) with Thinner. Allow drying for 8 hrs.

Wooden Surface – Apply first coat of Pink/White Primer on the wooden surface by thinning (if necessary) with Thinner. Allow drying for 5-6 hrs. Use any synthetic Putty to fill minor cracks, dents or holes. After drying sand the surface with Emery Paper 180. Apply another coat of Pink/White Primer. Allow drying for 5-6 hrs.

Application (Topcoat):

Apply single coat of Azura Single Pack Aluminium Paint after thorough stirring. Allow it to dry for 4-6 hrs.

- For greater heat resistance at higher temperature, metal surface should be coated only with Azura Single Pack Aluminium Paints after applying primer.

Application	Brush	✓
	Roller	✗
	Spray	✓
Dilution	Brush	Ready for Use. Thinning not necessary.
	Roller	NA
	Spray	10% by volume with Thinner.
Drying time	Within 3 hrs	
Overcoating Time	4 – 6 hrs	
No. of coats specified	1 coat	
Coverage (Theoretical)	22 – 24 sq.m/litre. at 12-14 micron DFT	
Stability of Thinned Paint	NA (No thinning is required. Paint is stable)	
Precautions while Painting	• Proper surface preparation & normal atmospheric condition. • Please do not over-thin or over-extend the brush while painting.	
Cleaning up equipments	All equipments should be cleaned with Thinner.	
Post Application Instructions	To remove stains, sponge clean with a mild soap solution and wipe clean. Before cleaning, please ensure a drying time of one week	

General Safety and Environment Information

- Keep container upright and tightly closed in a cool, dry and well ventilated location away from heat source, flammables and direct sunlight.
- Keep out of reach of children. Do not store near food, drinks or animal feed.
- Dispose unwanted paint safely. Do not dispose into drains, water sources or open sewers.
- Wash all tools after application with General Purpose Thinner or Mineral Turpentine.
- Use sand or earth to contain any paint spillage
- Wear appropriate attire, especially gloves, eye protection and nose mask.
- Work in a well-ventilated area. Do not breathe vapour or spray.
- Remove paint from skin by washing with water and soap or appropriate cleaner.
- Avoid contact with skin as it may cause irritation.
- In the case of accidental contact, wash area immediately with water and seek immediate medical attention.
- To remove the paint from skin, use soap and water or appropriate cleaner.

*Actual Coverage may vary depending upon the application process and surface conditions.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

AREST ADVANCE PU BASED WATER PROOF & HEAT REFLECTING ROOFCOAT

Arest Advance Pu Based Water Proof & heat reflecting Roof Coat is a synthetic fiber reinforced non toxic single pack Polyurethane Based Elastomeric Acrylic Emulsion gives a water proofing membrane. On curing it form a thick & elastomeric membrane which gives an ultimate water proofing. Its a aliphatic Polyurethane & Acrylic hybrid formation.



Arest Advance Pu Based Water Proof & heat reflecting RoofCoat

Product Strong Benefits

1. Adhesion	Very strong Adhesion with masonry surfaces.
2. Water Proofing	Waterproofing Protection of up to 6-7 Bars of positive hydrostatic pressure.
3. Crack Bridging ability	Excellent Crack Bridging ability for Elastomeric film properties.
4. High Solar Reflectance Index (SRI).	Sparkling White Color & thick film thickness gives high levels of heat reflectance.
5. Room Temperature Reduction	It is white in color so reflect heat & light highly effectively. It gives temperature reduction between inside & outside up to 10 degree Centigrade.
6. Mechanical Strength of the film	As the product reinforced with synthetic fiber so provides high mechanical strength.
7. Anti Carbonation	Damp Proof system provides excellent Carbon Dioxide diffusion resistance & strongly prevents corrosion of rebar within the concrete matrix & gives better structural protection.
8. Durability	12+ Yrs
9. Use	Product is in liquid form & single pack ready to apply.

Performance Characteristics as per ASTM Standard	Value for Arest Waterproof Roof Coat
Pull off Adhesion Strength (ASTM 454) Dry Concrete	Minimum 1.5 MPa (S/F) MPa
Tensile Strength(ASTM D 2370/98: 14 days)	1.5+/- 0.15 MPa 1.8+/- 0.15 MPa
% Elongation(ASTM D2370/98: 14 Days)	350+/- 10% (Horizontal) 220+/- 10% (Vertical)
Crack Bridging (ASNZ 4548, 14 Days)	3.6+/- 0.125 mm for(Horizontal) 1.27 +/- mm for (Vertical)
Water Vapour permeability (EN ISO 7783)	4.12 g/m2/day
% Solid (ASTM C 1250)	55 to 61% @ 120DC 1 hr.
Over Coating Interval	Overnight.
Specific Gravity	1.22 to 1.32 at 30DC
Temperature Reduction(In house method)	10 DC

Application

Surface Preparation:

1. Cleaning: Free the surface from loose particles and peeling paint. Remove any previous growth of algae, fungi or moss by thorough wire brushing and cleaning with water. Antifungal wash after cleaning the algae & fungi has been proved very effective.

2. Filling: Any surface imperfections like holes, dents and fine cracks are to be filled with Cement Putty or Acrylic Putty.

3. Primer: Ensure that fresh plastered surfaces are completely cured and dry. Apply a coat of Arest Flexible Base Coat Primer WT thinning with clean water. Allow drying for 4-6 hours.

Application (Topcoat):

Apply 2 coats of Arest Advance Pu Based Water Proof & heat reflecting RoofCoat with clean water. Maintain an interval of one day between successive coats. For First two of top Coat dilute with 30% clean Water and for last coat apply paint without water addition. Every coat will apply at 90 degree angle to previous coat

● For darker shades, additional coat is recommended for complete hiding.

Application	Brush	✓
	Roller	✓
	Spray	✓
Dilution	Brush	15-20% by volume with clean potable water Final topcoat should be without dilution.
	Roller	10-15% by volume with clean potable water
	Spray	30-35% by volume with clean potable water
Drying time	Within 1 hr	
Overcoating Time	4-6 hrs	
No. of coats specified	2 Coats	
Coverage (Theoretical)	One coat Arest Universel Basecoat with 30% dilution covers 50 sq ft/liter*	
	124-25* sq ft/litre for two coat finish under ideal conditions	
Stability of Thinned Paint	Use within 24 hrs.	
Precautions while Painting	• Avoid painting when the temperature is below 10° C. • Painting is not recommended if the moisture content and alkalinity of the surface is high. • For newly plastered walls painting is recommended after 12 weeks of curing. • Please do not over-thin or over-extend the brush while painting.	
Cleaning up equipments	Wash all tools with water immediately after application.	
Post Application Instructions	For best performance of paint, surfaces should be washed and cleaned at regular intervals of six months.	

Special Application notes

Over Flexible Base Coat apply First Coat of Water Proofing Roof Coat at 90 Degree direction to Base Coat application allow for proper dry for overnight. Apply Second Coat of Water Proofing Roof Coat next day at a direction of 90 degree to first coat & allow to dry overnight for next coat. Apply third coat of Water Proofing Roof Coat without any dilution at a direction of 90 Degree to previous coat and allow to dry overnight. Do not use the roof for another three days.

VOC Level: VOC content does not exceed 30 ppm & complies with applicable low-VOC requirements.

AREST 5 IN 1 WATERPROOF ROOF COAT: WATERPROOFING & HEAT REFLECTOR

Arest Water Proofing Roof Coat is a synthetic Fiber reinforced Elastomeric Pure Acrylic Emulsion gives a water Proofing Membrane. On curing it form a Thick & Elastomeric membrane which gives an ultimate Water Proofing.



Arest 5 in 1 Waterproof Roof Coat:
Waterproofing & Heat Reduction

Product Strong Benefits

1. Adhesion	Very strong Adhesion with masonry surfaces, Concrete Surface, Brick Walls, Asbestos sheet.
2. Water Proofing	Waterproofing Protection of up to 6-7 Bars of positive hydrostatic pressure.
3. Crack Bridging ability	Excellent Crack Bridging ability for Elastomeric film properties.
4. High Solar Reflectance Index (SRI).	Sparkling White Color & thick film thickness gives high levels of heat reflectance.
5. Room Temperature Reduction	It is white in color so reflect heat & light highly effectively. It gives temperature reduction between inside & outside up to 10 degree Centigrade.
6. Mechanical Strength of the film	As the product reinforced with synthetic fiber so provides high mechanical strength.
7. Anti Carbonation	Damp Proof system provides excellent Carbon Dioxide diffusion resistance & strongly prevents corrosion of rebar within the concrete matrix & gives better structural protection.
8. Durability	10 Yrs
9. Use	Product is in liquid form & single pack ready to apply.

Performance Characteristics as per ASTM Standar	Value for Arest Waterproof Roof Coat
Pull off Adhesion Strength (ASTM 454) Dry Concrete	Minimum 1.5 MPa (S/F) MPa
Tensile Strength(ASTM D 2370/98: 14 days)	1.5+/- 0.15 MPa 1.8+/- 0.15 MPa
% Elongation(ASTM D2370/98: 14 Days)	350+/- 10% (Horizontal) 220+/- 10% (Vertical)
Crack Bridging (ASNZ 4548, 14 Days)	3.6+/- 0.125 mm for(Horizontal) 1.27 +/- mm for (Vertical)
Water Vapour permeability (EN ISO 7783)	4.12 g/m2/day
% Solid (ASTM C 1250)	55 to 61% @ 120DC 1 hr.
Over Coating Interval	Overnight.
Specific Gravity	1.22 to 1.32 at 30DC
Temperature Reduction(In house method)	10 DC

Application

Surface Preparation:

1. Cleaning: Free the surface from loose particles and peeling paint. Remove any previous growth of algae, fungi or moss by thorough wire brushing and cleaning with water. Antifungal wash after cleaning the algae & fungi has been proved very effective.

2. Filling: Any surface imperfections like holes, dents and fine cracks are to be filled with Cement Putty or Acrylic Putty.

3. Primer: Ensure that fresh plastered surfaces are completely cured and dry. Apply a coat of Arest Flexible Base Coat Primer WT thinning with clean water. Allow drying for 4-6 hours.

Application (Topcoat):

Apply 3 coats of Arest Water Proofing Top Coat Exterior Emulsion with clean water. Maintain an interval of one day between successive coats. For First two of top Coat dilute with 30% clean Water and for last coat apply paint without water addition. Every coat will apply at 90 degree angle to previous coat

● For darker shades, additional coat is recommended for complete hiding.

Application	Brush	✓
	Roller	✓
	Spray	✓
Dilution	Brush	1st Coat 30% by volume with clean potable water 2nd coat with 20% dilution. 3rd coat without dilution.
	Roller	10-15% by volume with clean potable water
	Spray	30% by volume with clean potable water
Drying time	Within 1 hr	
Overcoating Time	After 12 hrs	
No. of coats specified	3 Coats	
Coverage (Theoretical)	22-24* sq ft/litre for three coat finish under ideal conditions	
Stability of Thinned Paint	Use within 24 hrs.	
Precautions while Painting	• Avoid painting when the temperature is below 10° C. • Painting is not recommended if the moisture content and alkalinity of the surface is high. • For newly plastered walls painting is recommended after 12 weeks of curing. • Please do not over-thin or over-extend the brush while painting.	
Cleaning up equipments	Wash all tools with water immediately after application.	
Post Application Instructions	For best performance of paint, surfaces should be washed and cleaned at regular intervals of six months.	

*Special Application notes

Over Flexible Base Coat apply First Coat of Water Proofing Roof Coat at 90 Degree direction to Base Coat application allow for proper dry for overnight. Apply Second Coat of Water Proofing Roof Coat next day at a direction of 90 degree to first coat & allow to dry overnight for next coat. Apply third coat of Water Proofing Roof Coat without any dilution at a direction of 90 Degree to previous coat and allow to dry overnight. Do not use the roof for another three days.

VOC Level: VOC content does not exceed 30 ppm & complies with applicable low-VOC requirements.

AREST 5 IN 1 UNIVERSAL FLEXIBLE WATERPROOFING BASE COAT

– 10 years Performance Warranty

Anupam Paints Arrest Water Proofing Flexible Base Coat is an exterior/Interior waterproof undercoat paint formulated with specially designed elastomeric pure acrylics Emulsion based on nanotechnology. Its having surface cross linking properties coupled with organic-inorganic nano composite & fiber reinforcement technology giving excellent mechanical strength of the paint film.



Arrest Premium Waterproofing Basecoat

Product Benefits

Effective Waterproofing	The superlative waterproofing capabilities of the Anupam Paints Arrest Water Proofing Flexible Base Coat forms an effective barrier against water penetration.
Crack bridging	The Anupam Paints Arrest Water Proofing Flexible Base Coat film has significantly higher elongation and comes with unique fiber reinforcement technology offering a unique crack bridging ability of up to 2mm.
Structural Protection	Anupam Water proofing Flexible Base Coat has Structural protection from carbon and chlorine which gives protection against corrosion providing structural protection.
More benefits	Excellent opacity and whiteness Improves appearance of topcoat Does not chalk and can be applied on adequately cured fresh plaster . Provides excellent adhesion to topcoat emulsion Prevents peeling off of topcoat emulsion.

Product Features

Available Packing	1Ltr, 4Ltrs, 10Ltrs & 20 Ltrs.
Colors Available	Only White
Application	By Brush/Roller
Coverage	On Normal Masonry Surface. 50-55 Sq.Ft per Ltr with 20-30% dilution
Durability	10 Yrs on system
Recommended Surfaces	It can be used on both exterior as well as interior, cement plasters, asbestos sheets, concrete and brick works

User direction for Application Procedure

Surface Preparation:

- Any freshly plastered surfaces must be properly cure, which take at least 28 days for complete cure.
- The surfaces to be coated should be thoroughly clean, dry and free from all loose dirt, chalk, grease, oily substances, fungi, algae and flaking paint by brushing with wire brush or stiff coir brush. Then followed by water jetting for through cleaning.
- To remove old paints, fungi, algae growth it is better to have wet brushing rather than dry brushing.
- For areas severely affected by algae or fungus growth a Biowash treatment is recommended.
- Fill up all minor cracks and defects with Arrest Crack Fillers (5mm, 10mm & 20mm) according to the crack size and depth.

Application process

- Clean the roof & Parapets walls properly as per recommendation.
 - After Drying apply 1 coat of Arrest Flexible Basecoat with 20-30% dilution and allow for 6-8 hrs of drying.
 - After Proper Dry apply 3 coats of Arrest Water Proofing Roof Coat.
 - 1st coat with 30% dilution, 2nd Coat with 20% dilution & 3rd coat without dilution.
 - Ensure 6-8 hours of drying between the 2 coats. Ideal film thickness is essential for water proofing.
- If recommended coverage is not achieved additional coat must be applied for desired performance.

Drying Time: (Single coat at standard thickness):

Touch Dry: 30-45 Mins.

Recoat: 6-8 hours. Drying time may vary according to temperature and humidity. For instance, drying time will be significantly longer in cool & damp conditions.

VOC Level: VOC content does not exceed 30 ppm & complies with applicable low-VOC requirements.

AREST 5 IN 1 UNIVERSAL CRACK FILLER UPTO 20MM

– 5 years Performance Warranty

Anupam Paint's Crack Filler is a ready to use Lucent fiber reinforced crack filling compound for Interior & Exterior use. It has strong crack bridging power with flexibility up to 3 mm.



Arest 5 in 1 Universal
Crack Filler

Products Benefits

Crack Filling Ability:	Strong filling capacity of crack up to 3mm.
Mechanical Strength:	Lucent Fiber reinforcement with acrylic emulsion strength.
Waterproofing:	With special elastomeric emulsion gives water resistance film.
Flexibility:	High elongation film for special emulsion content.
Adhesion:	Very strong adhesion in various surfaces like plaster. POP, & asbestors.
Single pack ready to use crack Filler.	

Products Features

Coverage:	For plaster crack of 3mm of width 5mm depth recommended system. Two Coats 75 running Feet.
Drying Time to touch dry:	6-8 Hours.
Process of applications:	Clean the surface and widen the crack to form a V shaped groove. This will provide a strong adhesion of crack.
Durability:	7-8 Yrs

Technical Details

Ready to Use
Sp. Gravity at 25 dc – 1.28
Drying Time:- Minimum 6 hours depending on temperature & Humidity.

VOC Level: VOC content does not exceed 30 ppm & complies with applicable low-VOC requirements.

AREST UNIVERSAL DAMP BLOCK 2K SYSTEM

– 7 Years Performance Warranty

Arrest Universal Damp block 2K is a two component acrylic cementitious & flexible high performance waterproofing coating. Arrest Universal Damp block 2K consists of high grade and best quality Nano particals fumed silica with Acrylic Fiber Technology for reinforcement of Coating & selected best grade of additives which provides excellent pore sealing and water proofing property. The Special grade binder used in Arrest Universal Damp Block 2K provides good flexibility and excellent resistance to ingress of water. Water Block 2K is specially formulated to protect and provide waterproofing to concrete and similar structures. Arrest Universal Damp Block 2K can be used for protecting damp interior & Exterior walls, swimming pools, water tanks as its provides an excellent durable, flexible and impermeable protecting layer. It is recommended to apply two coats, first coat vertical & Second coat Horizontal application.

It is having Excellent Alkali Bloc, Superior Water proofing, Excellent flexibility & Multi surface Adhesion.



Arest Universal
Damp Block 2K

PRODUCT RELATED INFORMATION

Composition: Solid Part :	Nano particals Silica with Acrylic Fiber technology for reinforcement & inert fillers
Liquid Part :	Acrylic Flexible waterproofing Emulsion
Volatile organic compound (VOC) level in the Mix :	Less than 10gm/liter
Gloss/Sheen Level :	Matt Flash
Stability of Mixed Part :	Open container once open & mixed should be used
Pack size :	Available in 3kg pack only
Practical Coverage :	Surface with normal porosity will cover 10-15 sq.ft /kg
Durability :	5-6 Yrs

Technical Data

It's a two component System	Powder Part & Liquid Part
Density of the Mixture	1.6 to 1.7 gr/cm ³
Layer Thickness	1.5 to 2 mm in two coats
Drying Time	1-2 days after first Coat & 4-6 days after second coats.
Application Process	Mix liquid part & Solid part only.
Mixing	Do not mix any other liquid &/or powder.

VOC Level: VOC content does not exceed 30 ppm & complies with applicable low-VOC requirements.

AREST SINGLE PACK ALIPHATIC POLYURETHANE DISPERSION MODIFIED SEALER/ TOP COAT

Arest is a single component, Clear, waterborne, modified polyurethane Dispersion & Acrylic based hybrid coating containing an organic in-film preservative coating for internal & external walls and ceilings. For concrete, bricks, cement based and gypsum substrates, timber, tiles and plastic.

Advantages

- Easy application.
- Fast drying.
- Two coats in single working day.
- Elastomeric, resists cracking and flaking.
- Good resistance to repeated cleaning regimes.
- Using mild detergents and cleaning solutions.
- Seamless Semi glossy easy clean finish.

Surface Preparation

The surface must be professionally prepared and in a clean, dry condition free of oil, wax and dust. Wood, open-pored linoleum and decorative screed floors must be primed before applying. Floor and material temperature must not fall below 15 dc during application. Recoating after 6- 8 hours interval, at 20 dc 8 hours & at 30 dc 6 hours. Relative Humidity not more than 80%

Application method

By Brush, Roller & Airless spray.

Coverage

80- 105 sqft per Ltr per coat. In the case of a very absorbent substrate higher consumption is possible, depending on absorbency.

Technical Data

Elongation at Break:	100% (ISO 527-3)
Tensile Strength:	1.5 MPa (ISO 527-3)
Tensile Adhesion Strength:	>1.5 MPa (concrete), (According to EN 1542)
Dilution System:	Prime coat add 10% potable water Top Coat without dilution
DFT of applied film:	100 microns in two coats
Cleaning of Tools:	Application tools & other application equipment clean with clean water immediately after application.
Drying Time & Cleaning:	Carefully use the coated surfaces after application. Drying time depends on temperature & Humidity content of the atmosphere. At 25 degrees centigrade & 50 relative humidity the film takes 7 days' time is needed for full cure & development of Chemical resistance properties. For low temperature zone, High humidity & poor ventilated area drying time will be more may be up to 14 days. After complete drying one can clean the surface with mild soap solution.

Basis of Technical Data: All technical data stated in this sheet are based on laboratory tests. Actual figure may vary due to circumstances beyond our control.

VOC Level: VOC content does not exceed 30 ppm & complies with applicable low-VOC requirements.

AZURA WUD GLAZE PU SINGLE PACK



PRIMER – Solvent Based clear coat for wood product

- Hi Gloss Clear Coat
- For Wood & related surfaces
- Excellent Adhesion to Wood Surfaces
- Smooth, High Bonding Film
- Long Life Glossy Finish

Azura Wud Glaze PU single pack is a modified alkyd resin based clear coat improved with Polyurethane. It gives long lasting natural look of wooden surfaces. It is recommended to use in Wooden surfaces, plywood, particleboard, Fireboard etc for interior & Exterior use. It is not only enhancing the natural look but also gives good resistance to wear & tear.

Recommended Usage

- | | |
|---------------------------|--|
| • Wood & related surfaces | To be used for top coat application of wood & other related surfaces after proper surface preparation. |
|---------------------------|--|

General Properties

Finish	Glossy		Gloss retention	Excellent
Opacity	Clear Coat		Corrosion Resistance	Excellent
Flow and Leveling	Satisfactory		Flexibility	Excellent
Durability	5-6 yrs on system		Gloss Levels/ Sheen Levels	Hi Gloss
Consistency	Smooth & Free Flowing			

Safety, Environment & Health

Flammable – Avoid Exposure to flame

General Information

Preferable Putty	NA		Packing	0.5, 1, 4, Ltr Packs
------------------	----	--	---------	----------------------

ANEX WUD PRIMER WHITE ST



PRIMER – Solvent Based for Wud

- Alkali Resistant
- Excellent Sealing Properties
- Excellent Coverage
- Quick Drying
- Excellent Top Coat Holding

Anex Wud Primer White ST manufactured from selected pigments is a solvent based undercoating that promises the perfect surface preparation for wooden surfaces. It can be applied on exterior or interior wooden surfaces, where it wonderfully hides every surface stain, mark or discolouration. Glossy, semi-glossy and flat oil finishes may be applied directly to undercoated surface.

Recommended Usage

- Wooden Surfaces
- It can be applied on exterior or interior wooden surfaces.

General Properties

Finish	Smooth & Matt		Top Coat Adhesion	Excellent
Opacity	Satisfactory		Resistance to Alkali	Excellent
Flow and Leveling	Satisfactory		Flexibility	Satisfactory
Durability	4-5 yrs on system		Gloss Levels/ Sheen Levels	Matt Finish
Consistency	Smooth & Free Flowing			

Safety, Environment & Health

Flammable – Avoid Exposure to flame

General Information

Preferable Putty	Wooden Surfaces – Synthetic Putty		Packing	0.5, 1, 4, 10, 20 Ltr Packs
------------------	-----------------------------------	--	---------	-----------------------------

Application				
1. Cleaning: Ensure the surface is clean, dry and free from dirt and greasy matters. Sand the surface with Emery Paper 180 to remove loose particles, paint, dust/grease and cracked or flaked paint. Wipe the surface clean. 2. Primer -No prime coat is required. Use directly by brush or by diluting it with Thinner if required. Allow drying for 8-10 hours. 3. Surface dry :- 30 Minutes 4. Touch Dry :- 1 hour. 5. Hard Dry :- Over Night.	Application	Brush	✓	
		Roller	✗	
		Spray	✓	
	Dilution	Brush	5% by volume with Thinner (if required)	
		Roller	NA	
		Spray	20-25% by volume with Thinner	
	Drying time	Within 1 hrs		
	Overcoating Time	6-8 hrs		
	No. of coats specified	1 -2 coats		
Coverage (Theoretical)	180-200* sq ft/litre per coat under normal conditions of 20 micron DFT. For virgin wood coverage will be less.			
Stability of Thinned Paint	Use within 24 hrs.			
Precautions while Painting	• Avoid painting when the temperature is below 10 °C. • Painting is not recommended when the humidity is more than 85% & if the moisture content is more than 15%.			
Cleaning up equipments	All equipments should be cleaned with Thinner.			

General Safety and Environment Information

- | | |
|---|---|
| <ul style="list-style-type: none"> • Keep container upright and tightly closed in a cool, dry and well ventilated location. • Keep out of reach of children. Do not store near food, drinks or animal feed. • Dispose unwanted paint safely. Do not dispose into drains, water sources or open sewers. • Wash all tools with clean water immediately after application. | <ul style="list-style-type: none"> • Use sand or earth to contain any paint spillage. • Wear appropriate attire, especially gloves, eye protection and nose mask. • Work in a well-ventilated area. Do not breathe vapour or spray. • Avoid contact with skin as it may cause irritation. • In the case of accidental contact, wash area immediately with water and seek immediate medical attention. • To remove the paint from skin, use soap and water or appropriate cleaner. |
|---|---|

* Actual Coverage may vary depending upon the application process and surface conditions.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

Application

1. Cleaning: Ensure the surface is clean, dry and free from efflorescence. Sand the surface with Emery Paper 180 to remove loose particles, paint, dust, grease raked or flaked paint. Wipe the surface clean. 2. Primer –1st Coat: Apply a coat of Anex Wud Primer White ST directly by brush or by diluting it with Thinner. Allow drying for 5-6 hours. Sand with Emery Paper 180 and wipe the surface clean. 3. Putty (Optional): Fill up minor dents, cracks and undulations with thin coats of Synthetic Putty (on wooden surface). Allow drying time for 4-6 hours. Smoothen with Emery Paper 180 and wipe the surface clean. 4. Primer –2nd Coat: Apply another coat of Anex Wud Primer White ST by diluting with Thinner. Allow drying for 5-6 hours. Sand lightly with Emery Paper 320 or 400. Wipe the surface clean.	Application	Brush	✓
		Roller	✗
		Spray	✓
	Dilution	Brush	10% by volume with Thinner (if required)
		Roller	NA
		Spray	20-25% by volume with Thinner
	Drying time	4 hrs	
	Overcoating Time	5-6 hrs	
	No. of coats specified	1-2 coats	
Coverage (Theoretical)	100-110* sq ft/litre per coat under normal conditions		
Stability of Thinned Paint	Use within 24 hrs.		
Precautions while Painting	• Avoid painting when the temperature is below 10 0C. • Painting is not recommended if the moisture content and alkalinity of the surface is high.		
Cleaning up equipments	All equipments should be cleaned with Thinner.		

General Safety and Environment Information

- Keep container upright and tightly closed in a cool, dry and well ventilated location. - Keep out of reach of children. Do not store near food, drinks or animal feed. - Dispose unwanted paint safely. Do not dispose into drains, water sources or open sewers. - Wash all tools with clean water immediately after application.	- Use sand or earth to contain any paint spillage. - Wear appropriate attire, especially gloves, eye protection and nose mask. - Work in a well-ventilated area. Do not breathe vapour or spray. - Avoid contact with skin as it may cause irritation. - In the case of accidental contact, wash area immediately with water and seek immediate medical attention. - To remove the paint from skin, use soap and water or appropriate cleaner.
---	---

* Actual Coverage may vary depending upon the application process and surface conditions.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

ANEX RED OXIDE PRIMER

- Anti Corrosive
- For Ferrous & Steel Surfaces
- Excellent Adhesion to Metal Surfaces
- Smooth, High Bonding Film. Easy to Cover
- Good Opacity and High Spreading Power



PRIMER – Solvent Based Primer for Ferrous Metals

Anex Red Oxide Primer is a fine quality, rust-resistant primer ideal for use on ferrous and steel surfaces. Based on a synthetic medium in which red oxide pigment is added to give the traditional red oxide colour, it provides protection from exposure to chemical fumes, excessive heat and humidity, rain and wind. It can be brushed directly or sprayed on Ferro-metallic surfaces to produce a high bonding film that ensures a smooth top coat. It can be used for both interior and exterior mild steel surfaces.

Recommended Usage

• Ferro-metallic surfaces	To be used for priming Ferro-metallic surfaces after proper surface preparation.
---------------------------	--

General Properties

Finish	Matt		Top Coat Adhesion	Excellent
Opacity	Satisfactory		Corrosion Resistance	Excellent
Flow and Leveling	Satisfactory		Flexibility	Excellent
Durability	5-6 yrs on system		Gloss Levels/ Sheen Levels	Matt Finish
Consistency	Smooth & Free Flowing			

Safety, Environment & Health

Flammable – Avoid Exposure to flame

General Information

Preferable Putty	NA		Packing	0.5, 1, 4, 10, 20 Ltr Packs
------------------	----	--	---------	-----------------------------

Application

1. Cleaning: Ensure the surface is clean, dry and free from rust and greasy matters. Sand the surface with Emery Paper 180 to remove loose particles, paint, dust/grease and cracked or flaked paint. Wipe the surface clean. 2. Primer –1st Coat: Apply a coat of Anex Red Oxide Primer directly by brush or by diluting it with Thinner. Allow drying for 6-8 hours. Sand with Emery Paper 180 and wipe the surface clean. 3. Primer –2nd Coat: Apply another coat of Anex Red Oxide Primer by diluting with Thinner. Allow drying for 6-8 hours. Sand lightly with Emery Paper 320 or 400. Wipe the surface clean.	Application	Brush	✓
		Roller	✗
		Spray	✓
	Dilution	Brush	5% by volume with Thinner (if required)
		Roller	NA
		Spray	20-25% by volume with Thinner
	Drying time		Within 1 hr
	Overcoating Time		8 – 10 hrs
	No. of coats specified		1-2 coat
	Coverage (Theoretical)		120-130* sq ft/litre per coat under normal conditions
Stability of Thinned Paint	Use within 24 hrs.		
Precautions while Painting	• Avoid painting when the temperature is below 10 °C. • Painting is not recommended if the moisture content and alkalinity of the surface is high. • For newly plastered walls painting is recommended after 12 weeks of curing.		
Cleaning up equipments	All equipments should be cleaned with Thinner.		

General Safety and Environment Information

- | | |
|---|--|
| <ul style="list-style-type: none"> • Keep container upright and tightly closed in a cool, dry and well ventilated location away from heat source, flammables and direct sunlight. • Keep out of reach of children. Do not store near food, drinks or animal feed. • Dispose unwanted paint safely. Do not dispose into drains, water sources or open sewers. • Wash all tools with clean water immediately after application. | <ul style="list-style-type: none"> • Wear appropriate attire, especially gloves, eye protection and nose mask. • Work in a well-ventilated area. Do not breathe vapour or spray. • Remove paint from skin by washing with water and soap or appropriate cleaner. • Avoid contact with skin as it may cause irritation. • In the case of accidental contact, wash area immediately with water and seek immediate medical attention. • To remove the paint from skin, use soap and water or appropriate cleaner. |
|---|--|

*Actual Coverage may vary depending upon the application process and surface conditions.

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

AZURA HI-EFFICIENT BIOWASH

- Advanced Well Cleaning Solution

Azura Hi-Efficient Biowash is manufactured using eco-friendly, biodegradable ingredients that are highly effective in cleaning both interior and exterior walls of residential and commercial structures. It eliminates biological growth, particularly on exterior walls, where black or green patches may appear over time after painting. These patches are living organisms that must be destroyed before repainting. After the Biowash is applied, it is necessary to rinse the walls with fresh water to ensure complete removal.



Azura Hi-Efficient Biowash

Benefits of Using Biowash:

- It removes contaminants such as dirt, grease, and previous residues that can hinder proper paint adhesion.
- It is suitable for a variety of surfaces, including wood, metal, concrete, and previously painted areas before repainting.
- It effectively removes mould and mildew.
- It eliminates algae growth, which is common on external surfaces, especially on older buildings.
- Proper surface cleaning with Biowash reduces the likelihood of peeling, blistering, or premature paint failure by promoting better adhesion.
- Coverage: 120 Sqft/Ltr.

Safe & Non-Toxic

Azura Biowash is typically free from harsh chemicals, making it safer for both the user and the environment compared to more abrasive or toxic cleaners.

Application

Biowash is generally applied by spraying, brushing, or rolling onto the surfaces. It needs to sit for a period of 90-150 minutes to allow for effective cleaning action.

Scrubbing

For stubborn stains or heavily soiled areas, light scrubbing may be necessary to help lift contaminants.

Rinsing

Once the Biowash has done its job, the surface should be thoroughly rinsed with water to remove any cleaning solution and contaminants.

Drying

After washing, the surface must be allowed to dry properly before applying fresh paint.

VOC Level: VOC content does not exceed 30 ppm & complies with applicable low-VOC requirements.

AZURA PEARL METALLICA GOLD & SILVER

- 3 in 1 – Azura Pearl Metallica Gold & Silver – Smooth, Patterned or Textured
- Designer Metallic Hi Sheen Lustre Finish
- Based on Special Acrylic Emulsion and Pearl Pigments
- Maximum Durability & Colour Retention



PAINT – Azura Gold Metallica Emulsion

Give expressions to the most artistic imaginations for your walls with Azura Pearl Metallica. A water-based paint based on special acrylic emulsion and pearl pigments that creates a range of most exquisite interior effects. Containing special additives, it helps maintain the elegant look for a very long time. It offers stiff resistance to contaminations such that it finds application even on alkalic materials like concrete, cement or mortar.

Recommended Usage

• Interior Walls • Exterior Walls • Wooden Surface	For Painting Internal walls, smooth plaster, false ceilings, asbestos sheets, concrete etc. It also can be applied externally as well as on wood.
--	---

General Properties

Finish	Metallic & Lustre	Flow and Leveling	Excellent
Opacity	Excellent	Light Fastness	Excellent
Durability	5 yrs (min)	Resistance to Alkali	Passes the Alkali Resistance test

Safety, Environment & Health

No Added Lead, Mercury, Arsenic or Chromium	Non Flammable – Water based paint.
---	------------------------------------

General Information

Bases Information	NA	Colour Options	Gold & Silver
Preferable Primer	1. Water Thinnable Cement Primer 2. Cement Primer Oil Based		
Preferable Putty	1. Anupam Acrylic Wall Putty 2. Cement Based Putty	Packing	Ready Shades – 0.2ml, 1 Ltr Packs.

Application

Surface Preparation: 1. Cleaning: Ensure the surface is clean, dry and free from efflorescence. Sand the Surface with Emery Paper 180 to remove loose particles, paint, dust/grease and cracked or flaked paint. Wipe the surface clean. 2. Primer – 1st coat: Apply a coat of Azura Alkali Bloc Dual Primer Water Thinnable Cement Primer. Allow drying for 4-6 hours. 3. Putty: Fill up minor dents, cracks and undulations with thin coats of Anupam Acrylic Wall Putty. Allow drying time for 4-6 hours. Smoothen with Emery Paper 180 and wipe the surface clean. 4. Primer – 2nd coat: If necessary, Apply another coat of Azura Alkali Bloc Dual Water Thinnable Primer. Allow drying for 4-6 hours. Sand with Emery Paper 320 or 400. Wipe the surface clean.	Application	Brush	✓
		Roller	✓
		Spray	✓
	Dilution	Brush	Smooth: Dilute 25-30% by volume with clean potable water.
			Pattern: Thinning not recommended.
			Texture: Thinning not recommended.
		Roller	Smooth: Dilute 15-20% by volume with clean potable water.
			Pattern: Thinning not recommended.
			Texture: Thinning not recommended.
		Spray	Dilute 40-50% by volume with clean potable water.
	Drying time	Surface Dry within 1 hr.	
	Overcoating Time	6 – 8 hrs	
	No. of coats specified	2-3 Coats	
	Coverage (Theoretical)	85*-107* sq. ft/ltr on smooth, well prepared surface	

Application (Topcoat):

- Smooth Finish** – Stir well and pour Azura Pearl Metallica in a roller tray and apply minimum 2 coats maintaining an interval of 6-8 hours between successive coats. It can be applied with a brush followed by rolling. If required apply 3rd coats.
- Patterns** – Apply 2-3 coats of Azura Pearl Metallica Sheen Emulsion on the prepared wall. Allow it to dry for 4-5 hrs. Stir well and pour Azura Pearl Metallica in a roller tray and apply one coat on the surface using a roller and thereafter create effects by using one of the tools from the variety of tools for the desired effect. Apply in small manageable sections & not the entire wall at a time. Repeat until the entire surface is completed.
- Texture Patterns** – Create the desired texture by using Texture Plaster and Anupam's texture rollers. Work in small sections and complete the entire wall. Allow the texture plaster to dry overnight. Stir well and pour Azura Pearl Metallica in a roller tray and apply one coat with a brush or roller.

Stability of Thinned Paint	Use within 24 hrs.
Precautions while Painting	• Avoid painting when the temperature is below 10 °C. • Painting is not recommended if the moisture content and alkalinity of the surface is high. • For newly plastered walls painting is recommended after 4 weeks of curing. • Please do not over-thin or over-extend the brush while painting. • Sources of damp and efflorescence must be plugged by appropriate treatment before painting
Cleaning up equipments	Wash all tools with water immediately after application.
Post Application Instructions	To remove stains, sponge clean with a mild soap solution and wipe clean. Before cleaning, please ensure a drying time of one week.

General Safety and Environment Information

- Keep container upright and tightly closed in a cool, dry and well ventilated location.
- Keep out of reach of children. Do not store near food, drinks or animal feed.
- Dispose unwanted paint safely. Do not dispose into drains, water sources or open sewers.
- Wash all tools with clean water immediately after application.
- Use sand or earth to contain any paint spillage.
- Wear appropriate attire, especially gloves, eye protection and nose mask.
- Work in a well-ventilated area. Do not breathe vapour or spray.
- Avoid contact with skin as it may cause irritation.
- In the case of accidental contact, wash area immediately with water and seek immediate medical attention.
- To remove the paint from skin, use soap and water or appropriate cleaner.

VOC Level: VOC content does not exceed 30 ppm & complies with applicable low-VOC requirements.

*Actual Coverage may vary depending upon the application process and surface conditions. The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.



PAINT – Azura Gold Metallica Emulsion



PAINT – Azura Silver Metallica Emulsion

SPECIAL TEXTURE MIX FOR INTERIOR & EXTERIOR WALLS

Anupam Paint Special Texture Mix is a texture mix composite design with special type Acrylic polymer with cement compatible & high quality silica sand for Interior & Exterior walls for different types of Texture patterns.

Special Features

- It's a Lead Free & heavy metal free product.
- It is super adhesion & Excellent UV protection Coating.
- High resistance to Fungus & Algal growth coating.
- Hides surface undulations & Fine crack.
- Tough textured Finish lasts long & low maintenance.
- It's a low VOC product.

Coverage

An even coating of 2mm thickness 2.5 Sq.ft to 4 sq.ft per kg in one coat depending surface condition.

Surface Preparation

New plaster surface must be allowed to cure for at least 28 days before application.

Cleaning surface, should be free from any loose paint, dirt, grease, fungus & algae growth need to remove by wire brush. In case any crack up to 3mm with Arrest Crack fillers. The dent & holes should also been filled with Arrest Crack filler.

Special Texture Mix should not be used on surface that are subjected to continuous seepage or dampness.

Technical Details

- Drying Time:- Surface drying 30-60 Minutes.
- Flash Point:- NA
- Thinning is not recommended.
- Keep the paint air tight when not is use.
- Stir the materials before use.
- Do not apply the paint when ambient temperature is below 10 degrees centigrade.

VOC Level: VOC content does not exceed 30 ppm & complies with applicable low-VOC requirements.

TDS DETAILS FOR THE FOLLOWING PRODUCTS ARE AVAILABLE ON REQUEST

A. Speciality Coatings:

- Heavy Duty Non-Skid Paint
- Duramac – Road Marking Paint
- Sound Insulating Coating
- Fireseal – Intumescent Fire Retardant Coating
- Anti Graffiti Coating
- Marine Coatings
- Super Build Glass Flake Coatings
- Heat Resistant Aluminum Coating
- Inorganic Zinc Silicate Coating
- Black Bituminous Coating
- Pipeline Coatings
- Rust Cleaners

B. Epoxy Coatings:

- Durapoxy – Range of Epoxies – Primers, Intermediates, Mastics, Linings & Finishes
- Duracoat – Hi-Build Epoxy Coatings
- Durapatch – Epoxy Floor Patching and Concrete Repair Compound
- Epoxy Food Grade Coating
- Solvent Free Epoxy Coating
- Coroguard – Coal Tar Epoxy Coatings
- Anticora MIO – Epoxy Micaceous Iron Oxide Coating

C. Wood Coatings:

- Qualac – Range of Wood Coatings

D. Fluorescent Coatings:

- Anuglow: Range of Fluorescent Coatings

E. Chlorinated Rubber Coatings:

- Anuchlor – Range of Chlorinated Rubber Primers, MIO, Paints

F. Silicone Coatings:

- Heatguard – High Heat Resistant Silicone Coating

G. Primers:

- Anticora – Range of Anti Corrosive Primers
- Anuzinc – Epoxy Zinc Rich Primer
- Blastprime EZP 200 – Epoxy Zinc Phosphate Blast Primer
- Anuprime – Etch Primer/Adhesion Promoting Primer
- PP & FRP Primers – Range of Primers for Plastic Surfaces
- Range of Synthetic Primers

H. Polyurethane Coatings:

- Anuthane – Range of Polyurethane Coatings
- Thermosetting Acrylic Enamel
- Monocoat – Aliphatic PU High Build Enamel
- Range of Alkyd Based Enamels

I. Cathodic Electro-Deposition (CED) Coatings:

J. Polyaspartic Coatings:

K. Polysiloxane/Polysilazane based Coatings:

L. Fluoropolymer Coatings:

M. Others:

- Range of Industrial Use Putty
- All types of Thinners

**Our paints are enhanced with Carbon Nano-Struct Technology
– For coatings that Outperform and Outlast**