

## Assignment 3.6

set hive.support.concurrency = true;

set hive.enforce.bucketing = true;

set hive.exec.dynamic.partition.mode = nonstrict;

set hive.txn.manager = org.apache.hadoop.hive.ql.lockmgr.DbTxnManager;

set hive.compactor.initiator.on = true;

set hive.compactor.worker.threads = a positive number on at least one instance of the Thrift metastore service;

```
hive> set hive.support.concurrency = true;
hive> set hive.enforce.bucketing = true;
hive> set hive.exec.dynamic.partition.mode = nonstrict;
hive> set hive.txn.manager = org.apache.hadoop.hive.ql.lockmgr.DbTxnManager;
hive> set hive.compactor.initiator.on = true;
hive> set hive.compactor.worker.threads = 5;
hive> _
```

CREATE TABLE cmdb(id int, servername String, datacenter string) clustered by (datacenter) into 5 buckets stored as orc TBLPROPERTIES('transactional'='true');

```
hive> CREATE TABLE cmdb(id int, servername String, datacenter string) clustered by (datacenter) into 5 buckets stored
as orc TBLPROPERTIES('transactional'='true');
OK
Time taken: 0.51 seconds
```

INSERT INTO table cmdb

values(1,'srv1','ASIA'),(2,'srv2','AMER'),(3,'srv3','ASIA'),(4,'srv4','AFRI'),(5,'srv5','EURO'),(6,'srv6','EUR  
O'),(7,'srv7','AMER') ,(8,'srv8','AFRI') ,(9,'srv9','ASIA');

```
hive> INSERT INTO table cmdb values(1,'srv1','ASIA'),(2,'srv2','AMER'),(3,'srv3','ASIA'),(4,'srv4','AFRI'),(5,'srv5',
'EURO'),(6,'srv6','EURO'),(7,'srv7','AMER') ,(8,'srv8','AFRI') ,(9,'srv9','ASIA');
```

SELECT \* FROM cmdb;

```
hive> SELECT * FROM cmdb;
OK
8      srv8      AFRI
6      srv6      EURO
5      srv5      EURO
4      srv4      AFRI
9      srv9      ASIA
3      srv3      ASIA
1      srv1      ASIA
7      srv7      AMER
2      srv2      AMER
Time taken: 0.14 seconds, Fetched: 9 row(s)
hive>
```

UPDATE cmdb set datacentre = 'USA' where datacentre = 'AMER';

```
hive> UPDATE cmdb set datacenter = 'USA' where datacenter = 'AMER';
FAILED: SemanticException [Error 10302]: Updating values of bucketing columns is not supported. Column datacenter.
```

UPDATE cmdb set servername = 'Cloud5' where servername = 'srv5';

```
hive> UPDATE cmdb set servername = 'Cloud5' where servername = 'srv5';
WARNING: Hive-on-MR is deprecated in Hive 2 and may not be available in the future versions. Consider using a different execution engine (i.e. spark, tez) or using Hive 1.X releases.
Query ID = acadgild_20180520085337_820c9ba0-f381-4b0f-a7ea-b31f8bb53119
Total jobs = 1
Launching Job 1 out of 1
```

```
hive> SELECT * FROM cmdb;
OK
8      srv8      AFRI
6      srv6      EURO
5      Cloud5    EURO
4      srv4      AFRI
9      srv9      ASIA
3      srv3      ASIA
1      srv1      ASIA
7      srv7      AMER
2      srv2      AMER
Time taken: 0.185 seconds, Fetched: 9 row(s)
hive>
```

DELETE FROM cmdb where id = 7;

```
hive> DELETE FROM cmdb where id = 7;
WARNING: Hive-on-MR is deprecated in Hive 2 and may not be available in the future versions. Consider using a different execution engine (i.e. spark, tez) or using Hive 1.X releases.
Query ID = acadgild_20180520085718_7ec06326-ca24-45f4-a81d-5769943e1e9f
```

```
hive> SELECT * FROM cmdb;
```

```
OK
```

```
8      srv8      AFRI
```

```
6      srv6      EURO
```

```
5      Cloud5    EURO
```

```
4      srv4      AFRI
```

```
9      srv9      ASIA
```

```
3      srv3      ASIA
```

```
1      srv1      ASIA
```

```
2      srv2      AMER
```

```
Time taken: 0.172 seconds, Fetched: 8 row(s)
```