



Bindu Agarwalla

Day 11

KIIT University



Contents



- WAP to input name, roll number and marks in 5 subjects for a student, and display it.
- WAP to input name, roll number and marks in 5 subjects for n number of students. Write functions to:-
 - a. Find total marks and percentage of all n students.
 - b. Display details of a student with a given roll number.
 - c. Display the details for all the students having percentage in a given range.

Contents



□ WAP to enter id, name, age and basic salary of n number of employees. Calculate the gross salary of all the employees and display it along with all other details . [Gross salary= Basic salary + DA + HRA,

DA = 80% of Basic salary

HRA=10% of Basic salary]

Program to Store Information(name, roll and marks) of a Student Using Structure

```
#include <stdio.h>
struct student{
    char name[50];
    int roll;
    float marks[5];
};

int main(){
    struct student s;
    int i, n;
    printf("Enter information of student:\n\n");
    printf("Enter name: ");
    scanf("%s",s.name);
    printf("Enter roll number: ");
    scanf(" %d",&s.roll);
    printf("Enter marks: ");
    for (j=0;i<n;i++)
        scanf("%f",&s.marks[i]);
```

Program to Store Information(name, roll and marks) of a Student Using Structure



```
printf("\nDisplaying Information\n");
printf("Name: %s\n",s.name);
printf("Roll: %d\n",s.roll);
for (i=0;i<n;i++)
    printf("Marks: %.2f\n",s.marks[i]);
return 0;
}
```



Program to Store Information(name, roll and marks) of n number Student Using Structure

```
#include <stdio.h>
struct student{
    char name[50];
    int roll;
    float marks[5]; float total; float perc;
};

int main(){
    struct student s[10];
    int i, j, n, sum=0;
    printf("\n Enter the no of students");
    scanf("%d",&n);
    printf("Enter information of student:\n\n");

    for(i=0;i<n;i++)
    {
        printf("Enter name: ");
        scanf("%s",s[i].name);
        printf("Enter roll number: ");
        scanf("%d",&s[i].roll);
        printf("Enter marks: ");
        sum=0;
```

Program to Store Information(name, roll and marks) of n number Student Using Structure

```
    for (j=0;j<5;j++){
        scanf("%f",&s[i].marks[j]);
        sum=sum+s[i].marks[j];
    }
    s[i].tot=sum;
    s[i].perc= sum/5;
}
printf("\nDisplaying Information\n");
for(i=0;i<n;i++)
{ if(input==s[i].roll)
{
    printf("Name: %s\n",s[i].name);
    printf("Roll: %d\n",s[i].roll);
    for (j=0;j<5;j++)
        printf("Marks: %.2f\n",s[i].marks[j]);
    printf("Total: %.2f\n",s[i].tot);
    printf("Perc: %.2f\n",s[i].perc);}
}

return 0;
}
```

Note: This line is for displaying a student detail in a given range.
if(s[i].perc>=lower && s[i]. perc<=upper)

Program to Add Two Distances (in inch-feet) System Using Structures

```
#include <stdio.h>
struct Distance{
    int feet;
    float inch;
}d1,d2,sum;

int main(){
    printf("Enter information for 1st distance\n");
    printf("Enter feet: ");
    scanf("%d",&d1.feet);
    printf("Enter inch: ");
    scanf("%f",&d1.inch);
    printf("\nEnter information for 2nd distance\n");
    printf("Enter feet: ");
    scanf("%d",&d2.feet);
    printf("Enter inch: ");
    scanf("%f",&d2.inch);
    sum.feet=d1.feet+d2.feet;
    sum.inch=d1.inch+d2.inch;
```


Program to Add Two Distances (in inch-feet) System Using Structures ..



If inch is greater than 12, changing it to feet. */

```
if (sum.inch>12.0)
{
    sum.inch=sum.inch-12.0;
    ++sum.feet;
}
printf("\nSum of distances=%d\'-%.1f\'",sum.feet,sum.inch);
return 0;
}
```

Program to Add Two Complex Numbers by Passing Structure to a Function

```
#include <stdio.h>
typedef struct complex{
    float real;
    float imag;
};

complex add(complex n1,complex n2);

int main(){
    struct complex n1,n2,temp;
    printf("For 1st complex number \n");
    printf("Enter real and imaginary respectively:\n");
    scanf("%f%f",&n1.real,&n1.imag);
    printf("\nFor 2nd complex number \n");
    printf("Enter real and imaginary respectively:\n");
    scanf("%f%f",&n2.real,&n2.imag);
    temp=add(n1,n2);
    printf("Sum=%.1f+%.1fi",temp.real,temp.imag);
    return 0;
}
```



Program to Add Two Complex Numbers by Passing Structure to a Function..

```
complex add(complex n1,complex n2){  
    struct complex temp;  
    temp.real=n1.real+n2.real;  
    temp.imag=n1.imag+n2.imag;  
    return(temp);  
}
```



Program to Store Information of 10 Students Using Structure

```
#include <stdio.h>
struct student{
    char name[50];
    int roll;
    float marks;
};
int main(){
    struct student s[10];
    int i;
    printf("Enter information of students:\n");
    for(i=0;i<10;++i)
    {
        s[i].roll=i+1;
        printf("\nFor roll number %d\n",s[i].roll);
        printf("Enter name: ");
        scanf("%s",s[i].name);
        printf("Enter marks: ");
        scanf("%f",&s[i].marks);
        printf("\n");
    }
}
```

Program to Store Information of 10 Students Using Structure..

```
printf("Displaying information of students:\n\n");
for(i=0;i<10;++i)
{
    printf("\nInformation for roll number %d:\n",i+1);
    printf("Name: ");
    puts(s[i].name);
    printf("Marks: %.1f",s[i].marks);
}
return 0;
}
```

Structure within structure

```
#include <stdio.h>
struct stud_Res
{
    int rno;
    char std[10];
    struct stud_Marks
    {
        char subj_nm[30];
        int subj_mark;
    }marks;
}result;
```

structure within structure

```
void main()
{
    printf("\n\t Enter Roll Number : ");
    scanf("%d",&result.rno);
    printf("\n\t Enter Standard : ");
    scanf("%s",result.std);
    printf("\n\t Enter Subject Code : ");
    scanf("%s",result.marks.subj_nm);
    printf("\n\t Enter Marks : ");
    scanf("%d",&result.marks.subj_mark);
    printf("\n\n\t Roll Number : %d",result.rno);
    printf("\n\n\t Standard : %s",result.std);
    printf("\n\t Subject Code : %s",result.marks.subj_nm);
    printf("\n\n\t Marks : %d",result.marks.subj_mark);
}
```

Array in structure

```
#include <stdio.h>
```

```
struct result
```

```
{
```

```
    int rno, mrks[5];
```

```
    char nm;
```

```
}res;
```

```
void main()
```

```
{
```

```
    int i,total;
```

```
    total = 0;
```

```
    printf("\n\t Enter Roll Number : ");
```

```
    scanf("%d",&res.rno);
```

```
    printf("\n\t Enter Marks of 3 Subjects : ");
```




Thank You

