

Satinitigan_Karl_HW4

Karl Satinitigan

2/16/2020

MACS30100

Non-linear regression

Egalitarianism and income

```
library(tidyverse)
```

```
## -- Attaching packages ----- tidyverse_conflict
## v ggplot2 3.2.1      v purrr  0.3.3
## v tibble  2.1.3      v dplyr  0.8.3
## v tidyr   1.0.0      v stringr 1.4.0
## v readr   1.3.1      v forcats 0.4.0

## -- Conflicts ----- tidyverse_conflict
## x dplyr::filter() masks stats::filter()
## x dplyr::lag()     masks stats::lag()
```

```
library(tidymodels)
```

```
## Registered S3 method overwritten by 'xts':
##   method      from
##   as.zoo.xts zoo

## -- Attaching packages ----- tidymodels_conflict

## v broom      0.5.4      v recipes  0.1.9
## v dials      0.0.4      v rsample  0.0.5
## v infer      0.5.1      v yardstick 0.0.4
## v parsnip    0.0.5

## -- Conflicts ----- tidymodels_conflict
## x scales::discard() masks purrr::discard()
## x dplyr::filter()   masks stats::filter()
## x recipes::fixed()  masks stringr::fixed()
## x dplyr::lag()       masks stats::lag()
## x dials::margin()   masks ggplot2::margin()
## x yardstick::spec() masks readr::spec()
## x recipes::step()   masks stats::step()
```

```
library(rcfss)
library(knitr)
library(splines)
library(lattice)
library(here)
```

```
## here() starts at /Users/karl/Documents/UChicago/0 Computational Modeling/Problem Sets/Satinitigan_Karl_HW4
```

```
library(patchwork)
library(margins)
```

```
library(ISLR)
library(boot)
```

```
##
## Attaching package: 'boot'
## The following object is masked from 'package:lattice':
##
##      melanoma
```

```
library(readr)
library(glmnet)
```

```
## Loading required package: Matrix
##
## Attaching package: 'Matrix'
## The following objects are masked from 'package:tidyr':
##
##      expand, pack, unpack
## Loaded glmnet 3.0-2
```

```
library(caret)
```

```
##
## Attaching package: 'caret'
## The following objects are masked from 'package:yardstick':
##
##      precision, recall
## The following object is masked from 'package:purrr':
##
##      lift
```

```
library(pls)
```

```
##
## Attaching package: 'pls'
## The following object is masked from 'package:caret':
##
##      R2
## The following object is masked from 'package:stats':
##
##      loadings
```

```
set.seed(1234)
theme_set(theme_minimal())
```

```
gsstrain <- read_csv(url("https://raw.githubusercontent.com/ksatinitigan/problem-set-4/master/data/gss_"))
```

```
## Parsed with column specification:
## cols(
##   .default = col_character(),
##   age = col_double(),
##   authoritarianism = col_double(),
##   childs = col_double(),
```

```

##   con_govt = col_double(),
##   egalit_scale = col_double(),
##   income06 = col_double(),
##   science_quiz = col_double(),
##   sibs = col_double(),
##   social_connect = col_double(),
##   tolerance = col_double(),
##   tvhours = col_double(),
##   wordsum = col_double()
## )

## See spec(...) for full column specifications.

gsstest <- read_csv(url("https://raw.githubusercontent.com/ksatinitigan/problem-set-4/master/data/gss_t


## Parsed with column specification:
## cols(
##   .default = col_character(),
##   age = col_double(),
##   authoritarianism = col_double(),
##   chlds = col_double(),
##   con_govt = col_double(),
##   egalit_scale = col_double(),
##   income06 = col_double(),
##   science_quiz = col_double(),
##   sibs = col_double(),
##   social_connect = col_double(),
##   tolerance = col_double(),
##   tvhours = col_double(),
##   wordsum = col_double()
## )
## See spec(...) for full column specifications.

### Polynomial regression

cvMSE <- NA
for (i in 1:10){
  glmfit <- glm(egalit_scale ~ poly(income06, i), data = gsstrain)
  cvMSE[i] <- cv.glm(gsstrain, glmfit, K = 10)$delta[1]
}


plot(1:10, cvMSE, xlab = "degree", ylab = "MSE", type = "b")
mindegree <- which.min(cvMSE)
points(mindegree, cvMSE[mindegree], col = "blue", cex = 2, pch = 10)

```




d = 9

```
plot(egalit_scale ~ income06, data = gsstrain, col = "grey60")
incomelim <- range(gsstrain$income06)
incomegrid <- seq(from = incomelim[1], to = incomelim[2])
polyfit <- lm(egalit_scale ~ poly(income06, 9), data = gsstrain)
polypred <- predict(polyfit, newdata = list(income06 = incomegrid))
lines(incomegrid, polypred, col="blue")
```




```
gsstrain %>%
  mutate(pred = predict(polyfit, gsstrain)) %>%
  ggplot() +
```

```
geom_point(aes(income06, egalit_scale, col = 'blue')) +
geom_line(aes(income06, pred, col = 'goldenrod2'), size = 1.5) +
scale_color_manual(name = 'Value Type',
                    labels = c('Observed', 'Predicted'),
                    values = c('#56B4E9', '#E69F00')) +
labs(x = 'income06', y = 'egalit_scale') +
theme(legend.position = 'top')
```




Step function

```
cvError <- NA
for (i in 2:15) {
  gsstrain$income06cut <- cut(gsstrain$income06, i)
  lmfit <- glm(egalit_scale ~ income06cut, data = gsstrain)
  cvError[i] <- cv.glm(gsstrain, lmfit, K = 10)$delta[1]
}
plot(2:15, cvError[-1], xlab = "cuts", ylab = "error", type = "b")
points(x = which.min(cvError), y = min(cvError, na.rm = TRUE), col = "blue", cex = 2, pch = 10)
```




cuts = 4

```
plot(egalit_scale ~ income06, data = gsstrain, col = "grey60")
stepfit <- glm(egalit_scale ~ cut(income06, 4), data = gsstrain)
steppedpred <- predict(stepfit, list(income06 = incomegrid))
lines(incomegrid, steppedpred, col="blue")
```



```
gsstrain %>%
  mutate(pred = predict(stepfit, gsstrain)) %>%
  ggplot() +
  geom_point(aes(income06, egalit_scale, col = 'blue')) +
  geom_line(aes(income06, pred, col = 'goldenrod2'), size = 1.5) +
```

```
scale_color_manual(name = 'Value Type',
  labels = c('Observed', 'Predicted'),
  values = c('#56B4E9', '#E69F00')) +
labs(x = 'income06', y = 'egalit_scale') +
theme(legend.position = 'top')
```



```
### Natural regression spline
```

```
spline <- train(egalit_scale ~ income06, data = gsstrain,
  method = "gamSpline",
  trControl = trainControl(method = "cv", number = 10),
  tuneGrid = expand.grid(df = seq(1, 12, 1)))
```

```
## Loading required package: gam
```

```
## Loading required package: foreach
```

```
##
```

```
## Attaching package: 'foreach'
```


```
## The following objects are masked from 'package:purrr':
```

```
##
```


```
## accumulate, when
```

```
## Loaded gam 1.16.1
```

```
income_lm <- train(egalit_scale ~ income06, data = gsstrain,
  method = "lm",
  trControl = trainControl(method = "cv", number = 10))
plot(spline)
```



```
d = 2
gsstrain %>%
  mutate(pred = predict(spline, gsstrain)) %>%
  ggplot() +
  geom_point(aes(income06, egalit_scale, col = 'blue')) +
  geom_line(aes(income06, pred, col = 'goldenrod2'), size = 1.5) +
  scale_color_manual(name = 'Value Type',
                     labels = c('Observed', 'Predicted'),
                     values = c('#56B4E9', '#E69F00')) +
  labs(x = 'income06', y = 'egalit_scale') +
  theme(legend.position = 'top')
```

```
## Egalitarianism and everything
```

```
gsstrainEv <- read_csv(url("https://raw.githubusercontent.com/ksatinitigan/problem-set-4/master/data/gss"))
```

```
## Parsed with column specification:
```

```
## cols(
##   .default = col_character(),
##   age = col_double(),
##   authoritarianism = col_double(),
##   childs = col_double(),
##   con_govt = col_double(),
##   egalit_scale = col_double(),
##   income06 = col_double(),
##   science_quiz = col_double(),
##   sibs = col_double(),
##   social_connect = col_double(),
##   tolerance = col_double(),
##   tvhours = col_double(),
##   wordsum = col_double()
## )
```

```
## See spec(...) for full column specifications.
```

```
gsstestEv <- read_csv(url("https://raw.githubusercontent.com/ksatinitigan/problem-set-4/master/data/gss"))
```

```
## Parsed with column specification:
```

```
## cols(
##   .default = col_character(),
```

```

## age = col_double(),
## authoritarianism = col_double(),
## childs = col_double(),
## con_govt = col_double(),
## egalit_scale = col_double(),
## income06 = col_double(),
## science_quiz = col_double(),
## sibs = col_double(),
## social_connect = col_double(),
## tolerance = col_double(),
## tvhours = col_double(),
## wordsum = col_double()
## )
## See spec(...) for full column specifications.

gsstrainEvmain <- gsstrainEv$egalit_scale
gsstrainEvmod <- dummyVars(egalit_scale ~., gsstrainEv)
gsstrainEvmat <- predict(gsstrainEvmod, newdata = gsstrainEv)
gsstrainEv <- data.frame(gsstrainEvmat)
gsstrainEvmain <- cbind(gsstrainEvmain, gsstrainEv)
gsstrainEvmain <- rename(gsstrainEvmain, egalit_scale = gsstrainEvmain)
parameters1 <- preprocess(gsstrainEvmain, method = c("center", "scale", "zv"))
gsstrainEvmain <- predict(parameters1, gsstrainEvmain)
gsstrainEvmain <- subset(gsstrainEvmain, select = -c(religORTHODOX.CHRISTIAN))

gsstestEvmain <- gsstestEv$egalit_scale
gsstestEvmod <- dummyVars(egalit_scale ~., gsstestEv)
gsstestEvmat <- predict(gsstestEvmod, newdata = gsstestEv)
gsstestEv <- data.frame(gsstestEvmat)
gsstestEvmain <- cbind(gsstestEvmain, gsstestEv)
gsstestEvmain <- rename(gsstestEvmain, egalit_scale = gsstestEvmain)
parameters2 <- preprocess(gsstestEvmain, method = c("center", "scale", "zv"))
gsstestEvmain <- predict(parameters2, gsstestEvmain)

### Linear regression

linear <- lm(egalit_scale ~., gsstrainEvmain)
linearpred <- predict(linear, gsstestEvmain)
linearMSE <- mean((gsstestEvmain$egalit_scale - linearpred)^2)
linearMSE

```

```
## [1] 0.6933239
```

Test MSE is 0.6933239

```

### Elastic net regression

gsstrainx <- model.matrix(egalit_scale ~ ., gsstrainEvmain)[, -1]
gsstrainy <- gsstrainEvmain$egalit_scale

gsstestx <- model.matrix(egalit_scale ~., gsstestEvmain)[, -1]
gsstesty <- gsstestEvmain$egalit_scale

for (i in seq(0, 1, .1))
elasticCV <- cv.glmnet(gsstrainx, gsstrainy, alpha=i)

```

```

bestlamelastic = elasticCV$lambda.min

elastic <- glmnet(gsstrainx, gsstrainsy, alpha=1, lambda=bestlamelastic)
elastic$beta

## 134 x 1 sparse Matrix of class "dgCMatrix"
##                               s0
## age                           -7.493173e-02
## attend.Once.yr                 .
## attend.Once.wk                 .
## attend2.3.times..mo           .
## attendEvery.wk                -1.397717e-03
## attendNever                   .
## attendNrly.evry.wk            4.960351e-03
## attendOnce.mo                 .
## attendOnce.yr                 .
## attendSev.times.yr            .
## authoritarianism              .
## blackNo                       -2.321410e-02
## blackYes                      1.467229e-14
## bornNO                        .
## bornYES                      .
## childs                       2.538804e-02
## colathALLOWED                .
## colathNOT.ALLOWED             .
## colracALLOWED                .
## colracNOT.ALLOWED             .
## colcomFIRED                  .
## colcomNOT.FIRED              .
## colmilALLOWED                .
## colmilNOT.ALLOWED             .
## colhomoALLOWED               -5.018626e-03
## colhomoNOT.ALLOWED           .
## colmslmNot.allowed            .
## colmslmYes..allowed           .
## con_govt                     .
## degree.HS                    8.045364e-03
## degreeBachelor.deg           -7.019781e-02
## degreeGraduate.deg           .
## degreeHS                     .
## degreeJunior.Coll            -1.184257e-02
## evangelicalHigh               .
## evangelicalLow                .
## evangelicalMod                .
## grassLEGAL                   7.263818e-02
## grassNOT.LEGAL               -2.715536e-14
## happyNOT.TOO.HAPPY           2.175888e-03
## happyPRETTY.HAPPY            .
## happyVERY.HAPPY              -3.453241e-03
## hispanic_2No                 .
## hispanic_2Yes                .
## homosexALMST.ALWAYS.WRG      .
## homosexALWAYS.WRONG          .
## homosexNOT.WRONG.AT.ALL      .

```

## homosexSOMETIMES.WRONG	.
## income06	-7.886866e-02
## maritalDivorced	.
## maritalMarried	.
## maritalNever.married	.
## maritalSeparated	.
## maritalWidowed	-4.634981e-04
## modeIN.PERSON	.
## modeOVER.THE.PHONE	.
## newsEVERYDAY	.
## newsFEW.TIMES.A.WEEK	.
## newsLESS.THAN.ONCE.WK	.
## newsNEVER	5.573449e-03
## newsONCE.A.WEEK	.
## owngunNO	4.434837e-02
## owngunREFUSED	.
## owngunYES	.
## partyid_3Dem	8.347713e-02
## partyid_3Ind	.
## partyid_3Rep	-7.206378e-02
## polviewsConserv	-7.537283e-02
## polviewsExtrmCons	-6.393625e-02
## polviewsExtrmLib	5.906472e-02
## polviewsLiberal	1.262032e-01
## polviewsModerate	.
## polviewsSlghtCons	-1.692359e-02
## polviewsSlghtLib	6.651629e-02
## pornlaw2Illegal.to.all	.
## pornlaw2Not.illegal.to.all	.
## prayLT.ONCE.A.WEEK	.
## prayNEVER	.
## prayONCE.A.DAY	.
## prayONCE.A.WEEK	.
## praySEVERAL.TIMES.A.DAY	.
## praySEVERAL.TIMES.A.WEEK	.
## pres08McCain	-2.033679e-01
## pres08Obama	7.875645e-15
## reborn_rNo	.
## reborn_rYes	.
## religBUDDHISM	.
## religCATHOLIC	.
## religCHRISTIAN	.
## religHINDUISM	-8.173875e-03
## religINTER.NONDENOMINATIONAL	.
## religJEWISH	.
## religMOSLEM.ISLAM	.
## religNATIVE.AMERICAN	.
## religNONE	.
## religOTHER	.
## religOTHER.EASTERN	.
## religPROTESTANT	.
## science_quiz	-1.461911e-02
## sexFemale	4.395364e-02
## sexMale	.

```
## sibs 2.592854e-02
## social_connect .
## social_cons3Conserv .
## social_cons3Liberal .
## social_cons3Mod .
## southNonsouth .
## southSouth .
## spend3Conserv -4.426462e-02
## spend3Liberal 3.506361e-02
## spend3Mod .
## teensexALMST.ALWAYS.WRG .
## teensexALWAYS.WRONG .
## teensexNOT.WRONG.AT.ALL .
## teensexSOMETIMES.WRONG .
## tolerance -6.007539e-02
## tvhours 3.908390e-02
## vetyears2.TO.4.YEARS .
## vetyearsLESS.THAN.2.YRS .
## vetyearsMORE.THAN.4.YRS .
## vetyearsNONE 5.895945e-03
## wordsum .
## zodiacAQUARIUS 1.709432e-03
## zodiacARIES .
## zodiacCANCER .
## zodiacCAPRICORN .
## zodiacGEMINI .
## zodiacLEO .
## zodiacLIBRA .
## zodiacPISCES .
## zodiacSAGITTARIUS .
## zodiacSCORPIO -2.312972e-03
## zodiacTAURUS .
## zodiacVIRGO 5.821476e-03

predictelastic <- predict(elastic, s=bestlamelastic, newx = gsstestx)
elasticMSE <- mean((predictelastic - gsstesty)^2)
elasticMSE
```

```
## [1] 0.6716835
```

Test MSE is 0.6716835

```
### Principal component regression
```

```
PCRfit <- train(egalit_scale ~., data = gsstrainEvmain,
               method="pcr",
               scale = TRUE,
               trControl = trainControl("cv", number = 10),
               tuneLength = 10
             )
PCRfit
```

```
## Principal Component Analysis
##
## 1481 samples
## 134 predictor
```

```
##
## No pre-processing
## Resampling: Cross-Validated (10 fold)
## Summary of sample sizes: 1334, 1332, 1333, 1333, 1333, 1333, ...
## Resampling results across tuning parameters:
##
##   ncomp  RMSE      Rsquared  MAE
##   1      0.9899626  0.01969522  0.8229787
##   2      0.8577424  0.26541727  0.6955589
##   3      0.8338368  0.30593300  0.6666252
##   4      0.8334023  0.30661140  0.6662629
##   5      0.8333524  0.30681542  0.6660915
##   6      0.8283919  0.31510024  0.6622930
##   7      0.8271728  0.31663633  0.6609357
##   8      0.8278173  0.31557526  0.6614885
##   9      0.8269553  0.31652529  0.6604562
##  10      0.8276962  0.31518942  0.6610947
##
## RMSE was used to select the optimal model using the smallest value.
## The final value used for the model was ncomp = 9.
```

```
predictPCR <- predict(PCRfit, gsstestEvmain)
```

Components = 9

```
### Partial least squares regression
```

```
PLSfit <- train(egalit_scale ~., data = gsstrainEvmain,
               method = "pls",
               scale = TRUE,
               trControl = trainControl("cv", number = 10),
               tuneLength = 10)
```

```
PLSfit
```

```
## Partial Least Squares
##
## 1481 samples
## 134 predictor
##
## No pre-processing
## Resampling: Cross-Validated (10 fold)
## Summary of sample sizes: 1332, 1333, 1333, 1334, 1333, 1332, ...
## Resampling results across tuning parameters:
##
##   ncomp  RMSE      Rsquared  MAE
##   1      0.8434902  0.2896075  0.6685268
##   2      0.8222004  0.3260621  0.6489407
##   3      0.8212299  0.3310959  0.6468318
##   4      0.8252532  0.3269075  0.6488906
##   5      0.8292209  0.3221465  0.6510618
##   6      0.8287369  0.3231171  0.6507819
##   7      0.8275695  0.3248878  0.6499408
##   8      0.8270338  0.3256262  0.6498263
##   9      0.8269436  0.3257067  0.6498385
##  10      0.8270934  0.3255213  0.6498679
##
```

```
## RMSE was used to select the optimal model using the smallest value.  
## The final value used for the model was ncomp = 3.  
predictPLS <- predict(PLSfit, gsstestEvmain)
```

Components = 2