# TCP Congestion Control Advanced Techniques (Contd.)

CPSC 433/533, Spring 2021 Anurag Khandelwal

#### Router-assisted Congestion Control

- Three tasks for CC:
  - Isolation/fairness
  - Adjustment
  - Detecting congestion

#### Max-Min Fairness


• Given a set of bandwidth demands  $r_i$  and total bandwidth C, max-min bandwidth allocations are:

$$a_i = min(f, r_i)$$


where f is the unique value such that  $\sum_{i} a_{i} = C$ 

- Property:
  - If you don't get full demand, no one gets more than you
- This is what round robin service gives if all packets are the same size


### Practical Fair Queueing (FQ)



### Practical Fair Queueing (FQ)



### Practical Fair Queueing (FQ)



#### FQ vs. FIFO

#### FQ vs. FIFO

#### FQ Advantages:

- Isolation: cheating flows don't benefit
- Bandwidth share does not depend on RTT
- Flows can pick any rate adjustment scheme they want

#### FQ vs. FIFO

#### FQ Advantages:

- Isolation: cheating flows don't benefit
- Bandwidth share does not depend on RTT
- Flows can pick any rate adjustment scheme they want

#### Disadvantages

• More complex than FIFO: per flow queue/state, additional per-packet book-keeping

#### Router-assisted Congestion Control

- Three tasks for CC:
  - Isolation/fairness
  - Adjustment
  - Detecting congestion

Packets carry "rate field"


- Packets carry "rate field"
- Routers insert "fair share" f in the packet header

- Packets carry "rate field"
- Routers insert "fair share" f in the packet header
- End-systems set sending rate (or window size) to f
  - Hopefully (still need some policing of end-systems!)


- Packets carry "rate field"
- Routers insert "fair share" f in the packet header
- End-systems set sending rate (or window size) to f
  - Hopefully (still need some policing of end-systems!)
- Basic idea behind the "Rate Control Protocol" (RCP) from Dukkipati et. al. '07

#### Flow Completion Time: TCP vs. RCP (Ignore XCP)

#### Flow Duration (seconds) vs. Flow Size



### Why the Improvement?



#### Router-assisted Congestion Control

- Three tasks for CC:
  - Isolation/fairness
  - Adjustment
  - Detecting congestion

- Single bit in packet header; set by congested routers
  - If data packet has bit set, then ACK has ECN bit set

- Single bit in packet header; set by congested routers
  - If data packet has bit set, then ACK has ECN bit set
- Congestion semantics can be exactly like that of drop
  - i.e., end-system reacts as though it saw a drop

- Single bit in packet header; set by congested routers
  - If data packet has bit set, then ACK has ECN bit set
- Congestion semantics can be exactly like that of drop
  - i.e., end-system reacts as though it saw a drop

#### Advantages:

- Don't confuse corruption with congestion; recovery with rate adjustment
- Can serve as an early indicator of congestion to avoid delays
- Easy (easier) to incrementally deploy
  - Today: defined in RFC 3168 using **ToS/DSCP** bits in the IP header

• Use ECN as congestion markers

- Use ECN as congestion markers
- Whenever I get an ECN bit set, I have to pay \$\$

- Use ECN as congestion markers
- Whenever I get an ECN bit set, I have to pay \$\$
- Now there's no debate over what a flow is, or what fair is...

- Use ECN as congestion markers
- Whenever I get an ECN bit set, I have to pay \$\$
- Now there's no debate over what a flow is, or what fair is...
- Idea started by Frank Kelly at Cambridge
  - "Optimal" solution, backed by much math
  - Great idea: simple, elegant, effective
  - Unclear that it will impact practice

## Recap: TCP

#### Recap:TCP

#### • TCP

- Somewhat hacky
- But practical/deployable
- Good enough for Internet traffic
- Needs of data centers might change status quo (future lecture)

- Communication between application processes
  - Multiplex and demultiplex from/to application processes using **ports**


- Communication between application processes
- Provide common end-to-end services for application layer [optional]
  - Reliable, in-order data delivery
  - Well-placed data delivery
    - Too fast may overwhelm the receiver/network
    - Too slow is not efficient


- Communication between application processes
- Provide common end-to-end services for application layer [optional]
- TCP and UDP are the common transport protocols
  - Also SCTP, MTCP, SST, RDP, DCCP, ...

- Communication between application processes
- Provide common end-to-end services for application layer [optional]
- TCP and UDP are the common transport protocols
- UDP is a minimalist, no-frills transport protocol
  - Only provides multiplex/demultiplex capabilities

- Communication between application processes
- Provide common end-to-end services for application layer [optional]
- TCP and UDP are the common transport protocols
- UDP is a minimalist, no-frills transport protocol
- TCP is the whole-hog protocol
  - Offers applications a reliable, in-order, byte stream abstraction
  - With congestion control
  - But no performance guarantees (delay, bw, etc.)


### Taking Stock






#### Course so far:


• Concepts, Links, delays, switches




- Concepts, Links, delays, switches
- Overall Architecture, Layers, protocols principles



- Concepts, Links, delays, switches
- Overall Architecture, Layers, protocols principles
- Network Layer, Best-effort global delivery of packets



- Concepts, Links, delays, switches
- Overall Architecture, Layers, protocols principles
- Network Layer, Best-effort global delivery of packets
- Transport Layer, Reliable (or unreliable) delivery of data



What's left?

#### Course so far:

- Concepts, Links, delays, switches
- Overall Architecture, Layers, protocols principles
- Network Layer, Best-effort global delivery of packets
- Transport Layer, Reliable (or unreliable) delivery of data

User A
Application

Transport

Network


Link

#### Course so far:

- Concepts, Links, delays, switches
- Overall Architecture, Layers, protocols principles
- Network Layer, Best-effort global delivery of packets
- Transport Layer, Reliable (or unreliable) delivery of data

#### What's left?

Application Layer, DNS, HTTP (today)




#### Course so far:

- Concepts, Links, delays, switches
- Overall Architecture, Layers, protocols principles
- Network Layer, Best-effort global delivery of packets
- Transport Layer, Reliable (or unreliable) delivery of data

#### What's left?

- Application Layer, DNS, HTTP (today)
- Lower Layers, Ethernet, Wireless




#### Course so far:

- Concepts, Links, delays, switches
- Overall Architecture, Layers, protocols principles
- Network Layer, Best-effort global delivery of packets
- Transport Layer, Reliable (or unreliable) delivery of data

#### What's left?

- Application Layer, DNS, HTTP (today)
- Lower Layers, Ethernet, Wireless
- Advanced Topics, Datacenters, SDN



# On to the Application Layer!

- Domain Name System (DNS)
  - What's behind (e.g.) zoo.cs.yale.edu?

- Domain Name System (DNS)
  - What's behind (e.g.) zoo.cs.yale.edu?
- HTTP and the Web
  - What happens when you click on a link?

- Domain Name System (DNS)
  - What's behind (e.g.) zoo.cs.yale.edu?
- HTTP and the Web
  - What happens when you click on a link?

- Host address: e.g., 169.229.131.109
  - A number used by protocols
  - Conforms to network structure (the "where")

- Host address: e.g., 169.229.131.109
  - A number used by protocols
  - Conforms to network structure (the "where")
- Host names: e.g., zoo.cs.yale.edu
  - Mnemonic name usable by humans
  - Conforms to organizational structure (the "who")

- Host address: e.g., 169.229.131.109
  - A number used by protocols
  - Conforms to network structure (the "where")
- Host names: e.g., zoo.cs.yale.edu
  - Mnemonic name usable by humans
  - Conforms to organizational structure (the "who")
- The Domain Name System (DNS) is how we map from one to the other
  - A directory service for hosts on the Internet

# Why Bother?

# Why Bother?

- Convenience
  - Easier to remember <u>www.google.com</u> than 172.217.8.174

# Why Bother?

### Convenience

- Easier to remember <u>www.google.com</u> than 172.217.8.174
- Provides a level of indirection!
  - Decoupled names from addresses
  - Many uses beyond just naming a specific host

- Mappings stored in a hosts.txt file (in /etc/hosts)
  - Maintained by the Stanford Research Institute (SRI)
  - New versions periodically copied from SRI (via FTP)

- Mappings stored in a hosts.txt file (in /etc/hosts)
  - Maintained by the Stanford Research Institute (SRI)
  - New versions periodically copied from SRI (via FTP)
- As the Internet grew, this system broke down (obviously)
  - SRI couldn't handle the load
  - Conflicts in selecting names
  - Hosts had inaccurate copies of hosts.txt

- Mappings stored in a hosts.txt file (in /etc/hosts)
  - Maintained by the Stanford Research Institute (SRI)
  - New versions periodically copied from SRI (via FTP)
- As the Internet grew, this system broke down (obviously)
  - SRI couldn't handle the load
  - Conflicts in selecting names
  - Hosts had inaccurate copies of hosts.txt
- The Domain Name Service (DNS) was invented to fix this

- Many names
- Many updates
- Many users creating names
- Many users looking up names

- Many names
- Many updates
- Many users creating names
- Many users looking up names
- Highly available

- Many names
- Many updates
- Many users creating names
- Many users looking up names
- Highly available
- Correct
  - No naming conflicts (uniqueness)
  - Consistency → observe the latest update

- Many names
- Many updates
- Many users creating names
- Many users looking up names
- Highly available
- Correct
  - No naming conflicts (uniqueness)
  - Consistency → observe the latest update
- Lookups are fast

Partition the namespace

- Partition the namespace
- Distribute the administration of each partition
  - Autonomy to update my partition's machines' names
  - Don't have to track other partition's updates

- Partition the namespace
- Distribute the administration of each partition
  - Autonomy to update my partition's machines' names
  - Don't have to track other partition's updates
- Distribute name resolution for each partition
  - If I need to figure out the address for a name, I ask the partition that it belongs to


- Partition the namespace
- Distribute the administration of each partition
  - Autonomy to update my partition's machines' names
  - Don't have to track other partition's updates
- Distribute name resolution for each partition
  - If I need to figure out the address for a name, I ask the partition that it belongs to
- How should we partition things?


## Key Idea: Hierarchical Distribution


- Hierarchical naming
  - As opposed to flat namespace


- Hierarchical naming
  - As opposed to flat namespace
- Hierarchical administration
  - As opposed to centralized administration


- Hierarchical naming
  - As opposed to flat namespace
- Hierarchical administration
  - As opposed to centralized administration
- Hierarchical storage
  - As opposed to centralized storage





















Each domain's responsibility to maintain


uniqueness across their sub-domains











- Top of hierarchy: Root servers
  - Location hardwired into relevant servers
  - Store addresses **all** next level DNS servers...

- Top of hierarchy: Root servers
  - Location hardwired into relevant servers
  - Store addresses **all** next level DNS servers...
- Next Level: Top-Level Domain (TLD) servers
  - .com, .edu, etc.; managed professionally
  - Store addresses of next level DNS servers under them...

- Top of hierarchy: Root servers
  - Location hardwired into relevant servers
  - Store addresses **all** next level DNS servers...
- Next Level: Top-Level Domain (TLD) servers
  - .com, .edu, etc.; managed professionally
  - Store addresses of next level DNS servers under them...
- Bottom Level: Authoritative DNS servers
  - Store the actual name-to-address mappings
  - Maintained by the corresponding administrative authority

• Every server knows the address of the root name server

- Every server knows the address of the root name server
- Root servers know the address of all TLD servers

- Every server knows the address of the root name server
- Root servers know the address of all TLD servers

•


- Every server knows the address of the root name server
- Root servers know the address of all TLD servers
- •
- An authoritative DNS server stores name-to-address mappings ("resource records") for all DNS names in the domain that it has authority for

- Every server knows the address of the root name server
- Root servers know the address of all TLD servers
- •
- An authoritative DNS server stores name-to-address mappings ("resource records") for all DNS names in the domain that it has authority for
- Each server stores a subset of the total DNS database

- Every server knows the address of the root name server
- Root servers know the address of all TLD servers
- •
- An authoritative DNS server stores name-to-address mappings ("resource records") for all DNS names in the domain that it has authority for
- Each server stores a subset of the total DNS database
- Each server can discover the server(s) responsible for any portion of the hierarchy


#### DNS Root Servers

• 13 root servers (labeled A-M; see <a href="http://www.root-servers">http://www.root-servers</a>)



#### DNS Root Servers

- 13 root servers (labeled A-M; see <a href="http://www.root-servers">http://www.root-servers</a>)
- Replicated via any-casting



Routing finds shortest paths to destination

- Routing finds shortest paths to destination
- What happens if multiple machines advertise the same address?

- Routing finds shortest paths to destination
- What happens if multiple machines advertise the same address?
- The network will deliver the packet to the closest machine with that address

- Routing finds shortest paths to destination
- What happens if multiple machines advertise the same address?
- The network will deliver the packet to the closest machine with that address
- This is called "anycast"
  - Very robust
  - Requires no modification to routing algorithms

#### DNS Records

#### DNS Records

- DNS Servers store resource records (RRs)
  - RR is (name, value, type, TTL)

### DNS Records

- DNS Servers store resource records (RRs)
  - RR is (name, value, type, TTL)
- Type = A:  $(\rightarrow \underline{A}ddress)$ 
  - Name = hostname
  - Value = IP address

### DNS Records

- DNS Servers store resource records (RRs)
  - RR is (name, value, type, TTL)
- Type = A:  $(\rightarrow \underline{A}ddress)$ 
  - Name = hostname
  - Value = IP address
- Type = NS:  $(\rightarrow Name Server)$ 
  - Name = domain
  - Value = name of DNS server for domain

### DNS Records

- DNS Servers store resource records (RRs)
  - RR is (name, value, type, TTL)
- Type = A:  $(\rightarrow \underline{A}ddress)$ 
  - Name = hostname
  - Value = IP address
- Type = NS:  $(\rightarrow Name Server)$ 
  - Name = domain
  - Value = name of DNS server for domain
- Type =  $MX: (\rightarrow Mail\ eXchanger)$ 
  - Name = domain in email address
  - Value = name(s) of mail server(s)

• Example: you just created company "FooBar"

- Example: you just created company "FooBar"
- You get a block of IP addresses from your ISP
  - Say 212.44.9.128/25

- Example: you just created company "FooBar"
- You get a block of IP addresses from your ISP
  - Say 212.44.9.128/25
- Register foobar.com at registrar (e.g., GoDaddy)
  - Provide registrar with names and IP addresses of your authoritative name server(s)
  - Registrar inserts RR pairs into the .com TLD server
    - (foobar.com, dns l.foobar.com, NS)
    - (dns1.foobar.com, 212.44.9.129, A)

- Example: you just created company "FooBar"
- You get a block of IP addresses from your ISP
  - Say 212.44.9.128/25
- Register foobar.com at registrar (e.g., GoDaddy)
  - Provide registrar with names and IP addresses of your authoritative name server(s)
  - Registrar inserts RR pairs into the .com TLD server
    - (foobar.com, dns l.foobar.com, NS)
    - (dns1.foobar.com, 212.44.9.129, A)
- Store resource records in your server dns I.foobar.com
  - e.g., type A records: (<u>foobar.com</u>, 212.44.9.130, A), (<u>social.foobar.com</u>, 212.44.9.131, A), etc.
  - e.g., type MX records for <u>foobar.com</u>

- Two components
  - Local DNS server
  - Resolver software on hosts

#### Two components


- Local DNS server
- Resolver software on hosts
- Local DNS server ("default name server")
  - Clients configured with the default server's address or learn it via a host configuration protocol (e.g., DHCP future lecture)


#### Two components


- Local DNS server
- Resolver software on hosts
- Local DNS server ("default name server")
  - Clients configured with the default server's address or learn it via a host configuration protocol (e.g., DHCP future lecture)


#### Client application:


- Obtain DNS name (e.g., from URL)
- Triggers DNS request to its local DNS server




























# Root **DNS Server** .edu Servers nyu.edu Servers





# Root **DNS Server** .edu Servers nyu.edu Servers




#### Recursive DNS Query

# Root DNS Server







# Local DNS server (mydns.yale.edu)





# Root DNS Server





#### Root DNS Server











### DNS Protocol

### DNS Protocol

- Query and Reply messages; both with the same message format
  - See text for details

### DNS Protocol

- Query and Reply messages; both with the same message format
  - See text for details
- Client-Server Interaction on UDP Port 53
  - Spec. supports TCP too, but not always implemented

# Goals: How are we doing?

#### Scalable

- Many names
- Many updates
- Many users creating names
- Many users looking up names
- Highly available
- Correct
  - No naming conflicts (uniqueness)
  - Consistency
- Lookups are fast

# Per-domain Availability

# Per-domain Availability

#### • DNS servers are replicated

- Primary and secondary name servers required
- Name service available if at least one replica is up
- Queries can be load-balanced between replicas

# Per-domain Availability

#### • DNS servers are replicated

- Primary and secondary name servers required
- Name service available if at least one replica is up
- Queries can be load-balanced between replicas

#### • Try alternate servers on timeout


• Exponential backoff when retrying same server


# Goals: How are we doing?

#### Scalable

- Many names
- Many updates
- Many users creating names
- Many users looking up names
- Highly available
- Correct
  - No naming conflicts (uniqueness)
  - Consistency
- Lookups are fast

#### Root DNS Server





# Caching

## Caching

Caching of DNS responses at all levels

## Caching

- Caching of DNS responses at all levels
- Reduces load at all levels

## Caching

- Caching of DNS responses at all levels
- Reduces load at all levels
- Reduces delay experienced by DNS client

# DNS Caching

## DNS Caching

#### How DNS caching works

- DNS servers cache responses to queries
- Responses include a "time-to-live" (TTL) field
- Server deletes cached entry after TTL expires

## DNS Caching

#### How DNS caching works

- DNS servers cache responses to queries
- Responses include a "time-to-live" (TTL) field
- Server deletes cached entry after TTL expires

#### Why caching is effective

- The top-level servers very rarely change
- $\bullet$  Popular sites visited often  $\rightarrow$  local DNS server often has the information cached

## Negative Caching

## Negative Caching

- Remember things that don't work
  - Misspellings like <u>www.cnn.comm</u> and <u>www.cnnn.com</u>
  - These can take a long time to fail the first time
  - Good to remember that they don't work
  - ... so the failure takes less time the next time around


## Negative Caching

- Remember things that don't work
  - Misspellings like <u>www.cnn.comm</u> and <u>www.cnnn.com</u>
  - These can take a long time to fail the first time
  - Good to remember that they don't work
  - ... so the failure takes less time the next time around
- Negative caching is optional


Time to put your malicious hats on...

How can one attach DNS?

# Local DNS server (mydns.yale.edu)




Root
DNS Server




nyu.edu Servers

## Local DNS server (mydns.yale.edu)




Root
DNS Server







## Root DNS Server

# Local DNS server (mydns.yale.edu)










## Root DNS Server

# Local DNS server (mydns.yale.edu)








### How Can One Attack DNS?


#### How Can One Attack DNS?


- Impersonate the local DNS server
  - Give the wrong IP address to the DNS client

## Local DNS server (mydns.yale.edu)




# Root DNS Server






## Root DNS Server

Local DNS server (mydns.yale.edu)








#### Root **DNS Server** Local DNS server (mydns.yale.edu) .edu Servers **Denis** (The Denial-of-Service nyu.edu Servers **DNS Client** (me.cs.yale.edu) Attacker)

#### How Can One Attack DNS?

- Impersonate the local DNS server
  - Give the wrong IP address to the DNS client
- Denial-of-service the root or TLD servers
  - Make them unavailable to the rest of the world

## Local DNS server (mydns.yale.edu)




Root
DNS Server





nyu.edu Servers

## Local DNS server (mydns.yale.edu)




Root
DNS Server






## Root DNS Server

Local DNS server (mydns.yale.edu)







#### How Can One Attack DNS?

- Impersonate the local DNS server
  - Give the wrong IP address to the DNS client
- Denial-of-service the root or TLD servers
  - Make them unavailable to the rest of the world
- Poison the cache of a DNS server
  - Increase the delay experienced by DNS clients

Administrative delegation and hierarchy results in:

Easy unique naming

- Easy unique naming
- "Fate sharing" for network failures

- Easy unique naming
- "Fate sharing" for network failures
- Reasonable trust model

- Easy unique naming
- "Fate sharing" for network failures
- Reasonable trust model
- Caching lends scalability, performance

- Addresses can **change** underneath
  - Move <u>www.cnn.com</u> to a new IP address
  - Humans/applications are unaffected

- Addresses can **change** underneath
  - Move <u>www.cnn.com</u> to a new IP address
  - Humans/applications are unaffected
- Name could map to multiple IP addresses
  - Enables load-balancing

- Addresses can **change** underneath
  - Move <u>www.cnn.com</u> to a new IP address
  - Humans/applications are unaffected
- Name could map to multiple IP addresses
  - Enables load-balancing
- Multiple names for the same addresses
  - E.g., many services (mail, www, ftp) on same machine

- Addresses can **change** underneath
  - Move <u>www.cnn.com</u> to a new IP address
  - Humans/applications are unaffected
- Name could map to multiple IP addresses
  - Enables load-balancing
- Multiple names for the same addresses
  - E.g., many services (mail, www, ftp) on same machine
- Allowing "host" names to evolve into "service" names