

Question - 1

Java Keywords

SCORE: 5 points

Easy

Java

Which keyword is used to take control out of the enclosing loop?

- ☐ for
- ☒ break
- ☐ if
- ☐ continue

Question - 2

Java Constants

SCORE: 5 points

Easy

Java

How is a constant declared so that it can be accessed without making an instance of a class in which it is declared?

- ☐ public final int intConst
- ☐ public static int intConst
- ☒ public static final int intConst
- ☐ public int intConst

Question - 3

Java Types

SCORE: 5 points

Easy

Java

Which of the following is not a Java primitive type?

- ☒ String
- ☐ float
- ☐ double
- ☐ int
- ☐ byte

Question - 4

Classes and Objects

SCORE: 5 points

classes and objects


Inheritance

Abstract Class

method overriding

Easy

Observe the following class diagram and state



Which of the following statements are true regarding it?

- ☒ Employee class is abstract and cannot be instantiated.
- ☒ Both HourlyEmployee and SalariedEmployee class should override the calcSalary() method, in order to get instantiated.
- ☐ Employee class cannot contains concrete methods.
- ☐ There is a composition relationship between Employee and the other two classes.

Question - 5

Method Overloading

SCORE: 5 points

Methods

Method overloading

Easy

```
public void foo(ArrayList<String> data)
{
    //some code
}
public void foo (ArrayList<Integer> data)
{
    //some code
}
public ArrayList<String> foo (ArrayList<String> data)
{
    //some code
}
private void foo(List<String> data)
{
    //some code
}
public void foo(ArrayList<String> data, boolean flag)
{

```

```
//some code  
}
```

Which of the statements are true regarding this code?

- ☐ All the methods are considered as overloaded methods, except for private void foo(List data) because it has a private access modifier.
- ☐ All methods can coexist without issue.
- ☒ 'foo(ArrayList)' clashes with 'foo(ArrayList)', as both methods have the same erasure.
- ☐ private void foo(List data) {} is an overloaded method, while public ArrayList foo (ArrayList data) {} is not.

Question - 6
Java BufferedReader

SCORE: 5 points

Easy file handling

file1.txt

Hello

World

file2.txt

Hackerrank

What is the output of this code?

```
import java.io.*;  
public class Main{  
    public static void main(String args[]) throws IOException {  
        String str1, str2, str=null;  
        File file1 = new File("file1.txt");  
        File file2 = new File("file2.txt");  
        BufferedReader br1 = new BufferedReader(new FileReader(file1));  
        BufferedReader br2 = new BufferedReader(new FileReader(file2));  
        while ((str1 = br1.readLine()) != null)  
        {  
            str2 = br2.readLine();  
            if(str2 != null)  
            {  
                str=str1+" "+str2;  
                System.out.println(str);  
            }  
            br1.close();  
        }  
    }  
}
```

- ☐ Hello World
IOException: Stream closed

- ☐ Hello Hackerrank
World
- ☐ Hello World Hackerrank
- ☒ Hello Hackerrank
IOException: Stream closed

Question - 7

SCORE: 5 points

Java parseInt

Exception Handling

Easy

What is the output of the following code?

```
public class Main{
    public static void main(String[] args) {
        try
        {
            int[] a = new int[5];
            String s="1.0";
            try
            {
                System.out.println(Integer.parseInt(s+a[4]));
            }
            catch (Exception e)
            {
                System.out.println("Exception 1 occurs. "+ e.getClass());
            }
            throw new Exception();
        }
        catch (Exception e) {
            System.out.println("Exception 2 occurs");
        }
    }
}
```

- ☐ 1
Exception 2 occurs
- ☒ Exception 1 occurs. class java.lang.NumberFormatException
Exception 2 occurs
- ☐ Exception 1 occurs. class ArrayIndexOutOfBoundsException
Exception 2 occurs
- ☐ Compile-Time Error

Question - 8

SCORE: 5 points

Java Design Pattern

Easy

Design Patterns

The following code represents which design pattern?

```

class Student {
    private static Student s;
    private Student() {
    }
    public static Student getInstance() {
        if(s == null) {
            s = new Student();
        }
        return s;
    }
}
class Main {
    public static void main(String[] args) {
        Student s;
        s= Student.getInstance();
    }
}

```

- ☒ Singleton Design Pattern
- ☐ Factory Design Pattern
- ☐ Adapter Design Pattern
- ☐ Iterator Pattern

Question - 9

Java Concatenate

SCORE: 5 points

Interfaces Easy

In main(), after creating an object of MyClass, which code option returns the string s concatenated with the sum of two numbers x and y? For example, if s = 'HackerRank', x = 2, and y = 3, the output should be HackerRank 5

```

public interface MyInterface {
    String foo(String s, int x, int y);
}

```

```

public class MyClass {
    public String foo2(MyInterface i, String s, int x, int y) {
        return i.foo(s, x, y);
    }
}

```

```

public class Main {
    public static void main(String[] args) {
        MyClass myClass = new MyClass();
        // code to write
    }
}

```

- ☐ String result = myClass.foo2((s, x, y) -> s + " " + x + y, "HackerRank", 2, 3); System.out.println(result);

- ☒ String result = myClass.foo2((s, x, y) -> s + " " + (x + y), "HackerRank", 2, 3); System.out.println(result);
- ☐ String result = myClass.foo2->(s + " " + x + y, "HackerRank", 2, 3); System.out.println(result);
- ☐ String result = myClass.foo2((s, x, y) -> "HackerRank " + 2 + 3); System.out.println(result);

Question - 10

Java Interface

SCORE: 5 points

Interfaces

Easy

What is the output of the following program?

```
@FunctionalInterface
public interface MyInterface {
    void foo();
}
```

```
public class MyClass implements MyInterface {
    public void foo() {
        System.out.println("Hello");
    }
}
```

```
public class MyClass2 extends MyClass implements MyInterface{
    public void foo() {
        System.out.println("Hello 2");
    }
}
```

```
public class Main extends MyClass2{
    public static void main(String[] args) {
        MyClass c = new MyClass2();
        c.foo();
    }
}
```

- ☒ Hello 2
- ☐ Hello
- ☐ MyClass2 cannot extend a class and an interface at the same time.
- ☐ Runtime error

Question - 11

Java Operators

SCORE: 5 points

Java

Easy

What is the value of the variable z in the statement `int x = 5; int y = x++; int z = ++y; ?`

- ☐ 5
- ☒ 6
- ☐ 7
- ☐ 8

Question - 12

Java Variables

SCORE: 5 points

Java Easy

What is the value of the variable c in the statement `int a = 5; int b = 6; int c = a = b; ?`

- ☐ 5
- ☐ 11
- ☐ 56
- ☒ 6

Question - 13

Java Inheritance Overriding

SCORE: 5 points

Java Polymorphism Abstraction Inheritance OOPS Easy

What will be the output of the following code block?

Animal.java

```
public abstract class Animal
{
    public abstract void makenoise();
}
```

Dog.java

```
public class Dog extends Animal
{
    public void makenoise()
    {
        System.out.println("Make Dog Noise...");
    }
}
```

GoldenRetriever.java

```
public class GoldenRetriever extends Dog
{
    public void makenoise()
    {
        super.makenoise();
        System.out.println("Make Golden Retriever Noise");
    }
}
```

```
public static void main(String ... arg)
{
    Dog dog=new GoldenRetriever();
    dog.makenoise();
}
}
```

- ☐ Make Dog Noise...
- ☐ Make Golden Retriever Noise
- ☒ Make Dog Noise...
Make Golden Retriever Noise
- ☐ throws ClassCastException on runtime

Question - 14

Java String Pool

SCORE: 5 points

Java Strings Language Proficiency Memory Allocation Easy

How many strings will be added to the string pool upon execution of the following code block?

```
public static void main(String[] args) {
    String str = "Hello There!";
    String mtr = "Hello" + " " + "There" + "!";
    String dtr = "Hello " + "There" + "!";
    String gtr = "Hello There" + "!";
}
```

- ☒ 1
- ☐ 3
- ☐ 5
- ☐ 7
- ☐ 9

Question - 15

Which of the following operators is overloaded for string objects?

SCORE: 5 points

Easy Java Polymorphism Operator Overloading

Which of the following operators is overloaded for string objects?

- ☐ +
- ☐ -
- ☐ ==

- ☐ >>
- ☒ Java doesn't support operator overloading

Question - 16

SCORE: 5 points

Select the correct statement, from the options below:

Java Medium Garbage Collection

Select the correct statement, from the options below:

- ☒ If object obj1 can access object obj2 that is eligible for garbage collection, then obj1 is also eligible for garbage collection
- ☐ Objects can be explicitly destroyed using the keyword delete
- ☐ An object will be garbage collected immediately after it becomes unreachable
- ☐ None of the above

Question - 17

SCORE: 5 points

Given the following code, what is the most likely result:

Java OOPS Programming Easy

Given the following code, what is the most likely result:

```
import java.util.*;
public class Compares
{
    public static void main( String args[])
    {
        String[] cities = {"Bangalore","Pune","San Francisco","New York City"};
        MySort ms = new MySort();
        Arrays.sort(cities, ms);
        System.out.println(Arrays.binarySearch(cities, "New York City"));
    }
    static class MySort implements Comparator
    {
        public int compare( String a, String b)
        {
            return b.compareTo(a);
        }
    }
}
```

- ☐ -1
- ☐ 1
- ☐ 2
- ☒ Compilation fails

Question - 18

Bitwise Operators in Java

SCORE: 5 points

Java Easy Operators

Consider the following Java snippet:

```
int x = 3 & 5;  
int y = 3 | 5;
```

The values of 'x' and 'y' (respectively) are:

- ☒ 1,7
- ☐ 2,8
- ☐ 8,-2
- ☐ 1,8
- ☐ 2,7

Question - 19

JDK Design Patterns

SCORE: 5 points

Java Algorithms Easy

One example of _____ Design pattern from JDK itself is the Collections.sort() method and the Comparator Interface, through which we can specify different criteria for sorting a collection of objects.

Which of the following is the best fit for the blank in this line?

- ☐ Singleton
- ☐ Adapter
- ☐ Factory
- ☒ Strategy

Question - 20

Value of k After Function Runs

SCORE: 5 points

Java OOPS Easy Programming

Which is true of the following program?

```
public class TestFirstApp {  
    static void doIt(int x, int y, int m) {  
        if (x == 5) {  
            m=y;  
        } else {
```

```
        m=x;
    }

}

public static void main(String[] args) {
    int i=6, j=4, k=9;
    TestFirstApp.doIt(i,j,k);
    System.out.print(k);
}
```

- ☐ Doesn't matter what the values of i and j are, the output will always be 5 .
- ☐ Doesn't matter what the values of k and j are, the output will always be 5 .
- ☒ Doesn't matter what the values of i and j are, the output will always be 9 .
- ☐ Doesn't matter what the values of k and j are, the output will always be 9 .

Question - 21

Default Packages

SCORE: 5 points

Java

Easy

Which of the following packages is imported by default?

- ☒ java.lang
- ☐ java.io
- ☐ java.math
- ☐ java.text

Question - 22

Automatic Imports

SCORE: 5 points

Java

Easy

Classes from packages **java.lang**, **java.io** and **java.util** are imported by default without having to be specified explicitly using import statements in a Java program.

True or False?

- ☐ True
- ☒ False

Question - 23

Static Code Analysis 3

SCORE: 5 points

Java

Easy

Exception Handling

OOPS

Programming

What will be the output of this Java code snippet? Assume that all necessary imports have been taken care of.

```
public class Test{
    public static void main(String args[]) {
        try {
            int x = 0;
            for (x=1; x<4; x++);
            System.out.println(x);
        } catch(Exception e) {}
        finally {
            System.out.println("Error");
        }
    }
}
```

- ☐ 1 2 3
- ☐ 4
- ☐ 1 2 3 4
- ☒ 4 Error

Question - 24

Interfaces

SCORE: 5 points

Java

Easy

Interfaces

OOPS

Programming

Which of the below is true about Interfaces?

- ☐ Interface can contain constructors
- ☐ A class can implement just one interface
- ☐ An interface can declare public and protected method only
- ☒ An interface cannot have instance variables

Question - 25

Will This Compile? 2

SCORE: 5 points

Java

Medium

OOPS

Programming

What is the output for the below code ?

```
public class A {
    public void printName(){
        System.out.println("Value-A");
    }
}
public class B extends A{
    public void printName(){
        System.out.println("Value-B");
    }
}
```

```

    }

    public class C extends A{
        public void printName(){
            System.out.println("Value-C");
        }
    }

1. public class Test{
2.     public static void main (String[] args) {
3.         B b = new B();
4.         C c = new C();
5.         b = c;
6.         newPrint(b);
7.     }
8.     public static void newPrint(A a){
9.         a.printName();
10.    }
11. }

```

- ☐ Value-B
- ☐ Value-C
- ☒ Compilation fails due to an error on lines 5
- ☐ Compilation fails due to an error on lines 9

Question - 26

SCORE: 5 points

Java Class Path

Java

Easy

There is a java file named *Test.java* that needs access to a class contained in *app.jar* in the *exam* directory.

Which of the following commands sets classpath to compile clean?

- ☒ javac -classpath exam/app.jar Test.java
- ☐ javac -classpath app.jar Test.java
- ☐ javac -classpath exam Test.java
- ☐ None of the above

Question - 27

SCORE: 5 points

Java Print a Sum

Java

Language Proficiency

Classes

Inheritance

OOPS

Easy

What is the output of the following code?

```

1. public class A {
2.     int add(int i, int j){
3.         return i+j;

```

```

4.     }
5. }
6. public class B extends A{
7.     public static void main(String argv[]){
8.         short s = 9;
9.         System.out.println(add(s,6));
10.    }
11.}

```

- ☐ Compilation fails due to an error on line 2
- ☒ Compilation fails due to error on line 9, non-static method referenced from a static context.
- ☐ Compilation fails due to a type mismatch on line 9.
- ☐ 15

Question - 28

SCORE: 5 points

What is result of the following command?

Java

Easy

What is result of the following command?

```

1. import java.util.*;
2. class Priorities {
3.     public static void main(String[] args) {
4.         PriorityQueue toDo = new PriorityQueue();
5.         toDo.add("dishes");
6.         toDo.add("laundry");
7.         toDo.add("bills");
8.         toDo.offer("bills");
9.         System.out.print(toDo.size() + " " + toDo.poll());
10.        System.out.print(" " + toDo.peek() + " " + toDo.poll());
11.        System.out.println(" " + toDo.poll() + " " + toDo.poll());
12.    }
13. }

```

- ☐ 3 bills dishes laundry null null
- ☐ 3 bills bills dishes laundry null
- ☐ 3 dishes dishes laundry bills null
- ☐ 4 bills bills dishes laundry null
- ☒ 4 bills bills bills dishes laundry
- ☐ 4 dishes laundry laundry bills bills
- ☐ Compilation fails.
- ☐ An exception is thrown at runtime.

Question - 29

SCORE: 5 points

Which of the following statements is correct? Select the one correct answer.

Which of the following statements is correct? Select the one correct answer.

- ☐ Each Java file must have exactly one package statement to specify where the class is stored.
- ☐ If a Java file has both an import and a package statement, the import statement must come before package statement.
- ☐ A Java file must have at least one class defined.
- ☒ If a Java file has a package statement, it must be the first statement (except comments).

Question - 30

SCORE: 5 points

Arrays in Java

Java

Easy

Data Structures

Arrays

Which of the following statements is true?

- ☒ Arrays in Java are essentially objects.
- ☐ It is not possible to assign one array to another. However, individual elements of the array can be assigned.
- ☐ Array elements are indexed from 1 to the size of the array.
- ☐ If a method tries to access an array element beyond its range, a compile warning is generated.

Question - 31

SCORE: 5 points

Java: Inner Classes

Application Development

Java

Language Proficiency

Problem Solving

Easy

Examine the following Java code, it includes an inner class, what will be the output of the following code?

```
public final class Test4 {
    class Inner {
        void test() {
            if (Test4.this.flag) {
                sample();
            }
        }
    }
    private boolean flag = true;
    public void sample() {
        System.out.println("Sample");
    }
    public Test4() {
        (new Inner()).test();
    }
    public static void main(String args []) {
        new Test4();
    }
}
```

- ☒ Prints out "Sample"
- ☐ Program produces no output but terminates correctly
- ☐ Program does not terminate.
- ☐ The program will not compile

Question - 32

SCORE: 5 points

C++ Loop Control

Application Development

Java

Easy

Given the following code what is the effect of a = 5:

```
public class Test {
    public void add(int a) {
loop: for (int i = 1; i < 3; i++){
        for (int j = 1; j < 3; j++) {
            if (a == 5) {
                break loop;
            }
            System.out.println(i * j);
        }
    }
}
```

- ☐ Generate a runtime error
- ☐ Throw an ArrayIndexOutOfBoundsException
- ☐ Print the values: 1, 2, 2, 4
- ☒ Produces no output

Question - 33

SCORE: 5 points

Calling a Constructor

Application Development

Java

Easy

Where in a constructor, can you place a call to a constructor defined in the super class?

- ☐ Anywhere
- ☒ The first statement in the constructor
- ☐ The last statement in the constructor
- ☐ You can't call super in a constructor

Question - 34

SCORE: 5 points

Which of the following statements is correct?

Which of the following statements is correct for a method which is overriding the following method:

```
public void add(int a) {...}
```

- ☒ the overriding method must return void
- ☐ the overriding method must return int
- ☐ the overriding method can return whatever it likes

Question - 35

SCORE: 5 points

Java: Find the Output

Consider the following Java code snippet:

```
public int divide(int a, int b) {  
    int c = -1;  
  
    try {  
        c = a / b;  
    }  
    catch (Exception e) {  
        System.err.print("Exception ");  
    }  
    finally {  
        System.err.println("Finally ");  
    }  
  
    return c;  
}
```

What will our code *print* when we call *divide(4, 0)*?

- ☒ Exception Finally
- ☐ Finally Exception
- ☐ Exception
- ☐ Finally
- ☐ No output
- ☐ -1

Question - 36

SCORE: 5 points

What is the correct declaration of an abstract method that is intended to be pub?

What is the correct declaration of an abstract method that is intended to be public?

- ☒ public abstract void add();
- ☐ public abstract void add() {}
- ☐ public abstract add();
- ☐ public virtual add();

Question - 37

SCORE: 5 points

Java: String Array

Which of the following Java declaration of the String array is correct?

- ☐ String temp [] = new String {"j" "a" "z"};
- ☐ String temp [] = { "j" " " b" "c"};
- ☐ String temp = {"a", "b", "c"};
- ☒ String temp [] = {"a", "b", "c"};

Question - 38

SCORE: 5 points

Which of the following will output -4.0 ?

Which of the following will output -4.0 ?

- ☐ System.out.println(Math.floor(-4.7));
- ☐ System.out.println(Math.round(-4.7));
- ☒ System.out.println(Math.ceil(-4.7));
- ☐ System.out.println(Math.Min(-4.7));

Question - 39

SCORE: 5 points

Java: Classes

Which of the following are true for Java Classes?

- ☐ The Void class extends the Class class.

- ☐ The Float class extends the Double class.
- ☐ The System class extends the Runtime class.
- ☒ The Integer class extends the Number class.

Question - 40

Java : Object Class

SCORE: 5 points

Application Development Java Language Proficiency Problem Solving Easy

Which of the following is true?

- ☐ The Class class is the superclass of the Object class.
- ☐ The Object class is final.
- ☒ The Class objects are constructed by the JVM as classes are loaded by an instance of java.lang.ClassLoader
- ☐ None of the above

Question - 41

Declarations

SCORE: 5 points

Application Development Java Easy

Given the following declarations

```
String s1=new String("Hello")
String s2=new String("there");
String s3=new String();
```

Which of the following are legal operations?

- ☒ s3=s1 + s2;
- ☐ s3=s1 - s2;
- ☐ s3=s1 & s2
- ☐ s3=s1 && s2

Question - 42

Java String Concatenation

SCORE: 5 points

Application Development Java Easy

What is the output of the following program?

```
public class Question {
    public static void main(String args[]) {
        String s1 = "abc";
        String s2 = "def";
        String s3 = s1.concat(s2.toUpperCase( ) );
        System.out.println(s1+s2+s3);
    }
}
```

- ☐ abcdefabcdef
- ☐ abcabcDEFDEF
- ☒ abcdefabcDEF
- ☐ None of the above

Question - 43

"Syntax Review 2"

SCORE: 5 points

Application Development

Java

Easy

What is the result of trying to compile and run this program?

```
public class Test {
    public static void main(String[] args){
        int[] a = {1};
        Test t = new Test();
        t.increment(a);
        System.out.println(a[a.length - 1]);
    }
    void increment(int[] i){
        i[i.length - 1]++;
    }
}
```

- ☐ It generates a compiler error.
- ☒ It compiles and prints 2.
- ☐ It compiles and prints 1.
- ☐ It compiles and generates an `ArrayIndexOutOfBoundsException` exception at runtime.

Question - 44

Java : Division Check

SCORE: 5 points

Java

Language Proficiency

Easy

Arithmetic Operators

What is the result when one tries to compile and run the following code?

```
public final static void main(String[] args){
    double d = 10.0 / -0;
    if(d == Double.POSITIVE_INFINITY)
```

```
        System.out.println("Positive infinity");  
    else  
        System.out.println("Negative infinity");  
}
```

- ☒ Positive infinity
- ☐ Negative infinity
- ☐ Will fail to compile
- ☐ Runtime exception

Question - 45

"Syntax Review 1"

SCORE: 5 points

Application Development

Java

Easy

The following code is in a file called Test.java

```
class Base {  
    public static void main(String[] args){  
        System.out.println("Hello");  
    }  
}  
  
public class Test extends Base{}
```

What happens when it is compiled and run?

- ☐ It fails to compile.
- ☐ It compiles and generates a runtime error.
- ☐ It compiles and runs with no output.
- ☒ It compiles and prints "Hello".

Question - 1
Custom Error

SCORE: 5 points

Error Handling

Javascript

Easy

Type Checking

Variable Scopes

What is the output of this JavaScript code snippet?

```
class CustomError extends Error {
  constructor(message) {
    super(message);
    this.name = "CustomError";
  }
}

function validateData(data) {
  if (!data || typeof data !== "object") {
    throw new CustomError("Invalid data provided");
  }

  if (!data.hasOwnProperty("id") || typeof data.id !== "number") {
    throw new CustomError("Data object is missing an id property");
  }

  return true;
}

const data1 = { id: 42 };
const data2 = "Invalid data";

try {
  validateData(data1);
  console.log("Data1 is valid");
  validateData(data2);
  console.log("Data2 is valid");
} catch (error) {
  if (error instanceof CustomError) {
    console.log(`CustomError: ${error.message}`);
  } else {
    console.log(`Error: ${error.message}`);
  }
}
```



Data1 is valid

CustomError: Invalid data provided



Data1 is valid

CustomError: Data object is missing an id property



Data1 is valid

Error: Invalid data provided

☐ No output

Question - 2

SCORE: 5 points

SetTimeout

Functions

Javascript

events

Easy

Loops

Javascript Timers

Arrays

What is the output of this JavaScript code snippet?

```
const numbers = [1, 2, 3, 4, 5];

for (var i = 0; i < numbers.length; i++) {
  setTimeout(() => {
    console.log(`Number: ${numbers[i]}`);
  }, i * 1000);
}
```

- ☐ Number: 1
Number: 2
Number: 3
Number: 4
Number: 5
- ☒ Number: undefined
Number: undefined
Number: undefined
Number: undefined
Number: undefined
- ☐ Number: 5
Number: 5
Number: 5
Number: 5
Number: 5
- ☐ No output will be displayed.

Question - 3

SCORE: 5 points

Proxy

Proxy

Javascript

Type Checking

Easy

```
class Person {
  constructor(name, age) {
    this.name = name;
    this.age = age;
  }
}
```

```

    }

    greet() {
        console.log(`Hello, my name is ${this.name}.`);
    }
}

const personHandler = {
    get(target, property) {
        if (property === "age") {
            return target[property] + " years old";
        }
        return target[property];
    },
};

const person = new Person("John", 30);
const proxyPerson = new Proxy(person, personHandler);

console.log(proxyPerson.name);
console.log(proxyPerson.age);
proxyPerson.greet();

```

What is the output of this JavaScript code snippet?

- ☒ John
30 years old
Hello, my name is John.
- ☐ John
30
Hello, my name is John.
- ☐ John
30 year old
Hello, my name is John.
- ☐ John
Hello, my name is John
30 years old.

Question - 4

Currying

SCORE: 5 points

JavaScript

currying

Easy

Function Composition

Currying

What is the value of *result* in the following code?

```

function multiply(a) {
    return function(b) {
        return function(c) {
            return a * b * c;
        };
    };
};

```



```
};  
  
const double = multiply(2);  
const triple = multiply(3);  
  
const result = triple(double(4)(5))(1);
```

- ☐ Type Error
- ☒ 120
- ☐ 60
- ☐ 240

Question - 5

Equality

SCORE: 5 points

Easy Javascript Type Checking

What is the output of the following code?

```
const str = "1";  
const obj = new String("1");  
console.log(obj == "1");  
console.log(obj === str);  
console.log(obj == str);
```

- ☐ True, False, False
- ☒ True, False, True
- ☐ True, True, True
- ☐ True, True, False

Question - 6

Closures

SCORE: 5 points

Javascript Javascript Events Closures Easy Closure

What is the output of the following code?

```
const series = (...funcs) => (arg) => {  
  return funcs.reduce((prev, curr) => curr(prev), arg);  
};  
const result = series(num => num * 10, num => num + 20, num => num / 2, num => num - 5)(4);
```

- ☐ 20
- ☒ 25
- ☐ 30
- ☐ 0

Question - 7

JavaScript: Objects

SCORE: 5 points

JavaScript

Easy

Error Handling

Three of the following snippets will create a new JavaScript object with the name "Alex" and age 25. Which one uses incorrect syntax?

- ☐

let person = new Object({name: "Alex", age:25});
- ☐

let person = {name: "Alex", age: 25};
- ☐

let person = {}
person.name = "Alex";
person.age = 25;
- ☒

let person;
person['name'] = "Alex";
person['age'] = 25;

Question - 8

JavaScript: Typecasting Functions I

SCORE: 5 points

JavaScript

Easy

Hoisting

Match the JavaScript typecasting functions with their respective output.

Function	Output
1. <i>String([])</i>	A. 0
2. <i>String({})</i>	B. -Infinity
3. <i>Number(null)</i>	C. "[object Object]"

4. <i>Number("Infinity")</i>	D. ""
------------------------------	-------

- ☐ 1. A
2. B
3. D
4. C
- ☒ 1. D
2. C
3. A
4. B
- ☐ 1. A
2. D
3. B
4. C
- ☐ None of the above

Question - 9

JavaScript: Typecasting Functions II

SCORE: 5 points

JavaScript

Easy

Match the JavaScript typecasting functions with their respective output.

Function Call	Output
1. <i>Boolean(Infinity)</i>	a. 20
2. <i>Number([20, 30])</i>	b. true
3. <i>Boolean("")</i>	c. NaN
4. <i>Number(["20"])</i>	d. false

- ☒ 1-b
2-c
3-d
4-a
- ☐ 1-d
2-a
3-b
4-c
- ☐ 1-d
2-b
3-a
4-c
- ☐ None of the above

Question - 10

SCORE: 5 points

Declare variables with const keyword in JavaScript

Easy

Javascript Aptitude

One way to declare a variable in JavaScript is to use the keyword *const*. Which of the following are true about *const*? Choose one or more.

- ☐ A variable declared with const is always globally scoped.
- ☒ A variable declared with const is always block-scoped.
- ☐ A variable declared with const can be re-declared.
- ☐ A variable declared with const can be assigned to later.

Question - 11

SCORE: 5 points

Declare variables with let keyword in JavaScript

Easy

Javascript Aptitude

One way to declare a variable in JavaScript is to use the keyword *let*. Which of the following are true about *let*? Choose one or more.

- ☐ A variable declared with let is always globally scoped.
- ☒ A variable declared with let is always block-scoped.
- ☐ A variable declared with let can be re-declared.
- ☒ A variable declared with let can be assigned to later.

Question - 12

SCORE: 5 points

localStorage object

Easy

Javascript Aptitude

The localStorage object is used to store the data locally. Which of the following are true about localStorage objects? Select one or more.

- ☒ The data in localStorage is stored without an expiration date.
- ☐ localStorage allows for several data types, including numbers and strings.
- ☒ All data values stored in localStorage are stored as strings.
- ☒ localStorage is used to store limited data sizes. It is usually restricted to just a few megabytes.

Question - 13

SCORE: 5 points

JSON data format

Easy

Javascript Aptitude

JSON uses a few strict rules to encode its content. Which of the following are true about those rules? Choose one or more.

- ☒ JSON uses double quotation marks to delimit strings.
- ☐ JSON uses single quotation marks to delimit strings.
- ☒ Trailing commas are forbidden.
- ☐ Trailing commas are allowed and recommended because of cleaner diffs when working with version control systems.

Question - 14
JavaScript Basics

SCORE: 5 points

Easy JavaScript Javascript Aptitude

JavaScript is perhaps the most widely used programming language for Web client purposes. All modern Web browsers use it. Which of the following are true?

- ☐ JavaScript is a strongly typed language. This implies that adding a number to a string is not possible and will result in a runtime error.
- ☒ When JavaScript code is executed in a browser, it uses client computational resources rather than server resources.
- ☐ JavaScript does not support recursion.
- ☒ Angular, React, and Vue are popular JavaScript frameworks used in Web development.

Question - 15
NPM and Bower

SCORE: 5 points

NPM Bower Easy

Which one of the following statements is true?

- ☒ Bower is an NPM package and can be installed using NPM.
- ☐ NPM is a Bower package and can be installed using Bower.
- ☐ Both NPM and Bower can be installed using each other.
- ☐ Bower and NPM aren't related and cannot be installed using each other.

Question - 16
NPM

SCORE: 5 points

NPM Easy

What does NPM stand for?

- ☒ Node Package Manager
- ☐ Node Packet Manager

- ☐ Node Package Master
- ☐ Node Packet Master

Question - 17

Node Package Installation

SCORE: 5 points

NPM Easy

What is the command to install a node package globally for all the users in the system?

- ☒ npm install -g package
- ☐ npm install --glob package
- ☐ npm install package
- ☐ npm_global_install install package

Question - 18

Find the File

SCORE: 5 points

NPM Easy

In general, where is the package.json file present in any node application or module?

- ☐ Inside the node_modules folder
- ☒ In the root directory of the application/module
- ☐ Inside the packages folder
- ☐ Package.json is present in the /tmp folder

Question - 19

Meta Data

SCORE: 5 points

JavaScript Easy Javascript Aptitude

Which file holds the metadata for Grunt plugins?

- ☐ Gruntfile.js
- ☐ Gruntfile.coffee
- ☒ Package.json
- ☐ None of these

Question - 20

SCORE: 5 points

Method Requirements

JavaScript

Easy

Javascript Aptitude

If one task depends on the successful completion of another task (or tasks), what method can be used to force Grunt to abort if the other task didn't run, or if the other task failed?

- ☐ this.prerequisite
- ☐ this.successList
- ☐ this.dependencies
- ☒ this.requires

Question - 21

SCORE: 5 points

Install Grunt

JavaScript

Easy

Javascript Aptitude

How can you install Grunt in an Ubuntu Linux server?

- ☒ Using npm
- ☐ Using bower
- ☐ Using apt-get
- ☐ Using dpkg

Question - 22

SCORE: 5 points

Task Existence

JavaScript

Easy

Javascript Aptitude

How do you check if a task exists in Grunt?

- ☒ grunt.task.exists(name)
- ☐ grunt.task.present(name)
- ☐ grunt.task(name)
- ☐ grunt.task.task_exists(name)

Question - 23

SCORE: 5 points

Grunt Output III

JavaScript

Easy

Object Destructuring

```
grunt.initConfig({
  log: {
    foo: [1, 2, 3],
    bar: 'hello world',
    baz: false
  }
});

grunt.registerMultiTask('log', 'Log stuff.', function() {
  grunt.log.writeln(this.target + ': ' + this.data);
});
```

What is the output of the following Grunt task, when it is run as `grunt log`?

- ☐ foo: 1,2,3
- ☐ baz: false
- ☐ bar: hello world
- ☒ foo: 1,2,3 bar: hello world baz: false

Question - 24

Grunt Output II

SCORE: 5 points

JavaScript

Easy

Object Destructuring

```
grunt.initConfig({
  log: {
    foo: [1, 2, 3],
    bar: 'hello world',
    baz: false
  }
});

grunt.registerMultiTask('log', 'Log stuff.', function() {
  grunt.log.writeln(this.target + ': ' + this.data);
});
```

What is the output of the following Grunt task, when it is run as `grunt log:bar`?

- ☐ foo: 1,2,3
- ☒ bar: hello world
- ☐ foo: 1,2,3 bar: hello world baz: false
- ☐ baz: false

Question - 25

Grunt Output I

SCORE: 5 points

JavaScript

Easy

Object Destructuring


```
grunt.initConfig({
  log: {
    foo: [1, 2, 3],
    bar: 'hello world',
    baz: false
  }
});

grunt.registerMultiTask('log', 'Log stuff.', function() {
  grunt.log.writeln(this.target + ': ' + this.data);
});
```

What is the output of the following Grunt task, when it is run as `grunt log:foo`?

- ☐ foo: 1,2,3 bar: hello world baz: false
- ☒ foo: 1,2,3
- ☐ bar: hello world
- ☐ baz: false

Question - 26

SCORE: 5 points

Test Specification

JavaScript

Easy

Javascript Aptitude

In Grunt, if you don't specify a test to run, what is the name of the task that gets run by default (assuming the task exists)?

- ☐ Main
- ☒ Default
- ☐ Start
- ☐ Install

Question - 27

SCORE: 5 points

Negative Comparator

JasmineJS

Easy

How do you use a negative comparator in Jasmine?

- ☐ .negative
- ☒ .not
- ☐ .negation
- ☐ .nor

Question - 28

Declared Variables

SCORE: 5 points

JasmineJS

Easy

Variables declared in a describe are available to any *it* block inside the suite. True or False.

- ☒ True
- ☐ False

Question - 29

Pass the Test Case

SCORE: 5 points

JasmineJS

Easy

Functions

Callstacks

```
// your applications custom code
function getValue( a, b ) {
  //YOUR CODE COMES HERE
};

// the Jasmine test code
describe("getValue(a, b) function", function() {
  it("should be equal", function(){
    expect( getValue(1, 2) ).toBe( 7 );
  });
  it("should be equal", function(){
    expect( getValue(7, 4) ).toBe( 29 );
  });
});
```

What should be the code at *//YOUR CODE COMES HERE*, so that the Jasmine test cases pass?

- ☐ return 2*a + 3*b;
- ☒ return 3*a + 2*b;
- ☐ return 3*a + 3*b;
- ☐ return 2*a + 2*b;

Question - 30

Execution Stop

SCORE: 5 points

JasmineJS

Easy

Javascript Aptitude

In Jasmine, what is the configuration parameter to stop the execution of the script after the first failure of an expectation?

- ☐ stopOnFailure

- ☒ stopSpecOnExpectationFailure
- ☐ exitOnFailure
- ☐ exitSpecOnExpectationFailure

Question - 31

It Functions

SCORE: 5 points

JasmineJS Easy Javascript Aptitude

How many `expect` can we have in an `it` function?

- ☐ 0
- ☐ 1
- ☐ 2
- ☒ An it function can have any number of expects.

Question - 32

Browser Display

SCORE: 5 points

JavaScript Document Object Model Functions Easy

Using JavaScript, check whether the browser is online. Display "*I am online*" if it is. Otherwise, display "*I am offline*".
If the browser is online, display the current *latitude* and *longitude* of your location.

```
<p id="status"></p>
<p id="location"></p>
```

The `<p>` with `id="status"` is used to display the status: "*I am offline*" or "*I am online*".

The `<p>` with `id="location"` is used to display the latitude and longitude in the format below:

Latitude: 12.9321589
Longitude: 77.61325529999999

```
function checkStatus() {

    if(navigator.onLine){
        document.getElementById("status").innerHTML = "I am online";
        if (navigator.geolocation) {
            navigator.geolocation.getCurrentPosition(printLocation);
        }

    }
    else
```

```

document.getElementById("status").innerHTML = "I am offline";
}
function printLocation(position) {
    document.getElementById("location").innerHTML = "Latitude: " + position.coords.latitude +
    "<br/>Longitude: " + position.coords.longitude;
}

```

☐ function checkStatus() {

```

    if(navigator.onLine){
        document.getElementById("status").innerHTML = "I am online";
        if (navigator.geolocation) {
            navigator.geolocation.getCurrentPosition(printLocation);
        }

    }
    else

        document.getElementById("status").innerHTML = "I am offline";
}
function printLocation(position) {
    document.getElementById("location").innerHTML = "Latitude: " + position.coords.latitude +
    "<br/>Longitude: " + position.coords.longitude;
}

```

☐ function checkStatus() {

```

    if(navigator.online){
        document.getElementById("status").innerHTML = "I am online";
        if (navigator.geolocation) {
            navigator.geolocation.getCurrentPosition(printLocation);
        }

    }
    else

        document.getElementById("status").innerHTML = "I am offline";
}
function printLocation(position) {
    document.getElementById("location").innerHTML = "Latitude: " + position.coords.latitude +
    "<br/>Longitude: " + position.coords.longitude;
}

```

☐ function checkStatus() {

```

    if(navigator.onLine){
        document.getElementById("status").innerHTML = "I am online";
        if (navigator.geolocation) {
            navigator.geolocation.getCurrentPosition(printLocation);
        }

    }
    else
        document.getElementById("status").innerHTML = "I am offline";
}
function printLocation(position) {
    document.getElementById("location").innerHTML = "Latitude: " + position.coords.latitude +

```

```
"<br/>Longitude: " + position.coords.longitude;
```

```
}
```

Question - 33

JavaScript Visibility

SCORE: 5 points

JavaScript

Easy

jQuery

A text taken from Wikipedia is given below. You have to toggle the visibility of paragraphs with `class="hide"` when the toggle button is clicked. Initially, all the paragraphs are displayed (see figure 1). When the toggle button is clicked, the visibility of elements with `<p class="hide">` is toggled.

jQuery is a cross-platform JavaScript library designed to simplify the client-side scripting of HTML.

jQuery is the most popular JavaScript library in use today, with installation on 65% of the top 10 million highest-trafficked sites on the Web. jQuery is free, open-source software licensed under the MIT License

jQuery's syntax is designed to make it easier to navigate a document, select DOM elements, create animations, handle events, and develop Ajax applications.

jQuery also provides capabilities for developers to create plug-ins on top of the JavaScript library. This enables developers to create abstractions for low-level interaction and animation, advanced effects and high-level, theme-able widgets.

Microsoft and Nokia bundle jQuery on their platforms.[7] Microsoft includes it with Visual Studio[8] for use within Microsoft's ASP.NET AJAX and ASP.NET MVC frameworks while Nokia has integrated it into the Web Run-Time widget development platform.[9] jQuery has also been used in MediaWiki since version 1.16.[10]

jQuery, at its core, is a DOM (Document Object Model) manipulation library. The DOM is a tree-structure representation of all the elements of a Web page and jQuery simplifies the syntax for finding, selecting, and manipulating these DOM elements. For example, jQuery can be used for finding an element in the document with a certain property (e.g. all elements with an h1 tag), changing one or more of its attributes (e.g. color, visibility), or making it respond to an event (e.g. a mouse click).

Toggle

Figure 1

jQuery's syntax is designed to make it easier to navigate a document, select DOM elements, create animations, handle events, and develop Ajax applications.

jQuery also provides capabilities for developers to create plug-ins on top of the JavaScript library. This enables developers to create abstractions for low-level interaction and animation, advanced effects and high-level, theme-able widgets.

Microsoft and Nokia bundle jQuery on their platforms.[7] Microsoft includes it with Visual Studio[8] for use within Microsoft's ASP.NET AJAX and ASP.NET MVC frameworks while Nokia has integrated it into the Web Run-Time widget development platform.[9] jQuery has also been used in MediaWiki since version 1.16.[10]

Toggle

Figure 2

The partial code is given below:

```
<script>
<!--Fill in the code here-->
</script>
<p class="hide">jQuery is a cross-platform JavaScript library designed to simplify the client-side scripting of HTML.</h2>
```

```
<p class="hide">jQuery is the most popular JavaScript library in use today, with installation on 65% of the top 10 million highest-trafficked sites on the
Web. jQuery is free, open-source software licensed under the MIT License</p>
```

```
<p>jQuery's syntax is designed to make it easier to navigate a document, select DOM elements, create animations, handle events, and develop Ajax
applications. </p>
```

```
<p class="visible">jQuery also provides capabilities for developers to create plug-ins on top of the JavaScript library. This enables developers to create
abstractions for low-level interaction and animation, advanced effects, and high-level, theme-able widgets. </p>
```

```
<p class="visible">Microsoft and Nokia bundle jQuery on their platforms.[7] Microsoft includes it with Visual Studio[8] for use within Microsoft's ASP.NET AJAX
and ASP.NET MVC frameworks while Nokia has integrated it into the Web Run-Time widget development platform.[9] jQuery has also been used in MediaWiki
since version 1.16.[10]</p>
```

```
<p class="hide">jQuery, at its core, is a DOM (Document Object Model) manipulation library. The DOM is a tree-structure representation of all the elements of
a Web page and jQuery simplifies the syntax for finding, selecting, and manipulating these DOM elements. For example, jQuery can be used for finding an
element in the document with a certain property (e.g. all elements with an h1 tag), changing one or more of its attributes (e.g. color, visibility), or making it
respond to an event (e.g. a mouse click).
```

```
</p>
```

<button>Toggle</button>

- ☐ \$(document).ready(function(){
 \$("button").click(function() {
 \$("p.hide").Toggle();

 });
});
- ☒ \$(document).ready(function(){
 \$("button").click(function() {
 \$("p.hide").toggle();

 });
});
- ☐ \$(document).ready(function(){
 \$("button").click(function() {
 \$("p:hide").toggle();

 });
});
- ☐ \$(document).ready(function(){
 \$("button").click(function() {
 \$("p:hide").Toggle();

 });
});

Question - 34

Code Prediction

SCORE: 5 points

JavaScript Easy Loops Variable Scopes

Predict the output of the following code:

```
function Education() {  
    this.education = "B.Tech";  
}  
  
function main() {  
    Person = new Education();  
    Person.name = "Michael";  
    Person.surname = "Hicks";  
    var Person;  
    Person.residence = "Bangalore";  
    Person.age = 23;  
    Object.freeze(Person);  
    console.log(delete Person.name);  
  
    for (const item in Person) {  
        console.log(item);  
    }  
}
```

- ☐ False education name surname residence age
- ☒ false education name surname residence age
- ☐ True education surname residence age
- ☐ true education surname residence age
- ☐ false education surname residence age
- ☐ true education name surname residence age
- ☐ Compile time error

Question - 35

Array Element Passing

SCORE: 5 points

JavaScript Exception Handling Arrays Closure Loops Easy

Examine the code snippet below. You have to identify the correct snippet for the main and pass each element of the array *list=[0,4,1,3]* such that for every number less than 2, the error message, *"num should be greater than 2"*, is displayed.

Otherwise, the value returned from the function *twice* is displayed. What could be the possible solution(s)?

```
function Myfunc() {
  this.twice = function(num) {
    if (num < 2) {
      throw "num should be greater than 2"
    }
    return num * 2;
  }
}
```

- ☒

```
const myfunc = new Myfunc();
const list = new Array(0, 4, 1, 3);
for (let i = 0; i < 4; i++) {
  try {
    const res = myfunc.twice(list[i]);
    console.log(res);
  } catch (e) {
    console.log(e);
  }
}
```
- ☐

```
const myfunc = new Myfunc();
const list = {0, 4, 1, 3};
for (let i = 0; i < 4; i++) {
  try {
    const res = myfunc.twice(list[i]);
    console.log(res);
  }
```

- ```
} catch (e) {
 console.log(e);
}
}
```
- ☒ `const myfunc = new Myfunc();  
const list = [0, 4, 1, 3];  
for (let i = 0; i < 4; i++) {  
 try {  
 const res = myfunc.twice(list[i]);  
 console.log(res);  
 } catch (e) {  
 console.log(e);  
 }  
}`
- ☐ `const myfunc = new Myfunc();  
const list = [0, 4, 1, 3];  
try {  
 for (let i = 0; i < 4; i++) {  
 const res = myfunc.twice(list[i]);  
 console.log(res);  
 }  
} catch (e) {  
 console.log(e);  
}`

### Question - 36

#### First Five Alerts

SCORE: 5 points

Closures JavaScript Easy Closure

Select the option that has the correct sequence of first five alert messages, when the following javascript code snippet is run:

```
function func(x) {
 var z = 8;

 return function(y) {
 alert(x + y + z);
 }
}

var n1 = new Number(32);
var a1 = func(n1);
var n2 = new Number(16);
var a2 = func(n2);
var n3 = new Number(8);
var a3 = func(n3);
var n4 = new Number(4);
var a4 = func(n4);
var n5 = new Number(2);
var a5 = func(n5);
a1(2);
a2(4);
a3(8);
a4(16);
a5(32);
```

- ☐ 34, 36, 40, 48, 64



- ☐ 2, 4, 8, 16, 32
- ☐ 24, 24, 28, 28, 42
- ☒ 42, 28, 24, 28, 42

### Question - 37

SCORE: 5 points

Which of the following is not true of Javascript?

JavaScript Web Development Easy Javascript Aptitude

Which of the following is not true of Javascript?

- ☐ Javascript is case sensitive
- ☒ Semicolons at the end of Javascript statements are required
- ☐ Javascript statements can be grouped together in blocks
- ☐ Javascript is loosely typed

### Question - 38

SCORE: 5 points

What is the Purpose of the 'noscript' tag?

JavaScript Web Development Easy Javascript Aptitude

What is the purpose of the 'noscript' tag in javascript? Select the most accurate response

- ☐ Suppresses any script results that would be displayed on the web page
- ☐ Prevents scripts on the page from executing.
- ☒ Enclose text to be displayed by non-JavaScript browsers
- ☐ All of the above

### Question - 39

SCORE: 5 points

How to Capture Click Events in a Window

JavaScript Web Development Easy

Which of the following javascript commands would capture all click events in a web page window?

- ☐ window.routeEvents(Event.CLICK);
- ☐ window.raiseEvents(Event.CLICK);
- ☐ window.handleEvents(Event.CLICK);
- ☒ window.captureEvents(Event.CLICK);

## Question - 40

SCORE: 5 points

querySelector

JavaScript

Web Development

Easy

HTML Tags

In Javascript, consider the following selector:

```
document.querySelector("p.five");
```

Which html elements would this query select in the document? Select the most accurate statement.

- ☐ The first five <p> elements
- ☒ The first <p> element with class='five'
- ☐ All <p> elements with class='five'
- ☐ None - this is not a valid selector query

## Question - 41

SCORE: 5 points

Which function would you use to find html elements using tag name?

JavaScript

Web Development

Easy

HTML Tags

Which function would you use to find html elements using tag name?

- ☐ document.getElementByTagName()
- ☒ document.getElementsByTagName()
- ☐ document.getElementsUsingTagName()
- ☐ document.getElementUsingTagName()

## Question - 42

SCORE: 5 points

What is the correct way to create a javascript array?

JavaScript

Web Development

Easy

Javascript Aptitude

Arrays

What is the correct way to create a javascript array?

- ☒ var items = ["Orange","Apple"];
- ☐ var items = {"Orange","Apple"};
- ☐ var items = new array("Orange","Apple");
- ☐ var items[] = {"Orange","Apple"};

### Question - 43

SCORE: 5 points

What is the data type of *null* in Javascript?

JavaScript Web Development Easy Javascript Aptitude

What is the data type of *null* in Javascript?

- ☐ undefined
- ☐ integer
- ☒ object
- ☐ none

### Question - 44

SCORE: 5 points

What is correct way to run a Javascript in "strict mode"?

JavaScript Web Development Easy Javascript Aptitude

What is correct way to run a Javascript in "strict mode"?

- ☐ `<script mode=strict>`  
`</script>`
- ☒ `<script>`  
`"use strict"`  
`</script>`
- ☐ `<script strictMode=True>`  
`</script>`
- ☐ `<script strict>`  
`</script>`

### Question - 45

SCORE: 5 points

Which of the following javascript functions perform the given tasks correctly?

JavaScript Web Development Easy ES6 Features

Which of the following javascript functions perform the given tasks correctly?

- The function takes one numeric variable as parameter.
- If the variable is 0 than it creates a dialogue box which says "zero".
- If the variable is 1 than it creates a dialogue box which says "one".
- Otherwise it creates a dialogue box which says "Invalid input".



```
const myFunction = value => {
 switch (value) {
 case 0:
 str = "0";
 break;
 case 1:
 str = "1";
 break;
 default:
 str = "Invalid input";
 break;
 }
 return alert(str);
}
```

☐

```
const myFunction = value => {
 switch (value) {
 case 0:
 str = "zero";
 case 1:
 str = "one";
 default:
 str = "Invalid input";
 }
 alert(str);
}
```

☐

```
const myFunction = value => {
 switch (value) {
 case "0":
 str = "zero";
 break;
 case "1":
 str = "one";
 break;
 default:
 str = "Invalid input";
 break;
 }
 alert(str);
}
```

☒

```
const myFunction = value => {
 switch (value) {
 case 0:
 str = "zero";
 break;
 case 1:
 str = "one";
 break;
 default:
 str = "Invalid input";
 break;
 }
 alert(str);
}
```

Which of the following are NOT JavaScript reserved words?

- ☐ throws
- ☒ auto
- ☐ throw
- ☒ struct

### Question - 47

SCORE: 5 points

What is 'this'?

In the global execution context (outside of any function), what does the keyword 'this' in javascript refer to? Select the most accurate answer.

- ☐ null
- ☒ the global object
- ☐ the web page
- ☐ the web browser

### Question - 48

SCORE: 5 points

JS Data Types

Which of the following is not a primitive Datatype in Javascript?

- ☒ Array
- ☐ Number
- ☐ String
- ☐ Boolean

### Question - 49

SCORE: 5 points

Value of x

Consider the following code. What would the line `console.log(x)` display below?

```
var x = 100;

function test() {
 if(false) {
 var x = 199;
 }
 console.log(x); //what does this log?
}

test();
```

- ☐ 100
- ☐ 199
- ☒ undefined
- ☐ null

### Question - 50

#### Equivalence Testing in JS

SCORE: 5 points

JavaScript

Web Development

Easy

Type Checking

Which of the following is a difference between == and === in Javascript? Select the most accurate answer.

- ☐ == compares type and value. === compares type.
- ☐ == compares value. === compares type
- ☒ == compares value. === compares value and type
- ☐ == and === are equivalent

### Question - 51

#### Logging to the console

SCORE: 5 points

JavaScript

Web Development

Easy

Javascript Timers

In what order will the numbers 1-4 be logged to the console when the code below is executed?

```
(function() {
 console.log(1);
 setTimeout(function(){console.log(2)}, 1000);
 setTimeout(function(){console.log(3)}, 0);
 console.log(4);
})();
```

- ☐ 1 2 3 4
- ☐ 4 3 2 1
- ☒ 1 4 3 2
- ☐ 1 3 4 2

### Question - 52

SCORE: 5 points

#### Screen Properties

JavaScript

Web Development

Easy

Javascript Aptitude

Which of the following is not a screen property in Javascript?

- ☐ Height
- ☐ Width
- ☒ Selected
- ☐ ColorDepth

### Question - 53

SCORE: 5 points

#### Loops in JavaScript

JavaScript

Web Development

Easy

Loops

Which of the following is not a looping structure in JavaScript?

- ☐ for
- ☐ while
- ☐ do - while
- ☒ do - if
- ☐ for each

### Question - 54

SCORE: 5 points

#### Which of the following is not a core datatype?

Python

Easy

Which of the following is not a core datatype?

- ☐ Lists
- ☐ Dictionary
- ☐ Tuples
- ☒ Class

### Question - 55

SCORE: 5 points

#### The XML service(s) enable networking with javascript HTTP requests is:

The XML service(s) enable networking with javascript HTTP requests is:

- ☐ XMLHttpRequest
- ☒ XMLHttpRequest
- ☐ XMLHttpRequestResponse
- ☐ All of the above

### Question - 56

What is the output?

SCORE: 5 points

What is the value of y after the following code?

```
let x;
let y = x === null;
```

- ☒ false
- ☐ true
- ☐ undefined
- ☐ null

### Question - 57

What is the correct way to write a JavaScript array?

SCORE: 5 points

What is the correct way to write a JavaScript array?

- ☒ var txt = new Array("tim","kim","jim")
- ☐ var txt = new Array="tim","kim","jim"
- ☐ var txt = new Array:1=("tim")2=("kim")3=("jim")
- ☐ var txt = new Array(1:"tim",2:"kim",3:"jim")

### Question - 58

JavaScript: Appending Element to the Array

SCORE: 5 points



```
let arr = [1, 2, 3];
// complete the missing Javascript code on this line
console.log(arr); // outputs [1, 2, 3, 4]
```

- ☐ arr[arr.length + 1] = value
- ☒ arr[arr.length] = value
- ☐ arr[arr.length - 1] = value
- ☐ arr = arr + value

**Question - 59**

SCORE: 5 points

**How can you add a comment in a JavaScript?**

How can you add a comment in a JavaScript?

- ☒ //This is a comment
- ☐ REM This is a comment-->
- ☐ 'This is a comment
- ☐ #This is a comment

**Question - 60**

SCORE: 5 points

**Which of the following HTTP status codes denotes a server error?**

Which of the following HTTP status codes denotes a server error?

- ☐ 100
- ☐ 200
- ☐ 400
- ☒ 500

**Question - 61**

SCORE: 5 points

**JavaScript Assignment**

Consider the following JavaScript code snippet:

```
function foo () {
 return 5
}
```

What will the code `let myVar = foo;` do?

- ☐ Assign the integer value 5 to the variable *myVar*
- ☒ Assign a reference to the *foo* function to the variable *myVar*
- ☐ Throw an exception
- ☐ Nothing

### Question - 62

SCORE: 5 points

What is the correct way to have the function `checkState` called after 10 seconds?

Web Development JavaScript Front-End Development Easy Javascript Timers

What is the correct way to have the function `checkState` called after 10 seconds?

- ☐ `window.setTimeout(checkState, 10);`
- ☒ `window.setTimeout(checkState, 10000);`
- ☐ `window.setTimeout(checkState(), 10000);`
- ☐ `window.setTimeout(checkState(), 10);`

### Question - 63

SCORE: 5 points

What is the correct syntax to include a script named `myScript.js` into a page?

Web Development JavaScript Front-End Development Easy

What is the correct syntax to include a script named `myScript.js` into a page?

- ☐ `<script href="myScript.js">`
- ☐ `<script name="myScript.js">`
- ☒ `<script src="myScript.js">`
- ☐ `<script root="myScript.js">`

### Question - 64

SCORE: 5 points

Which HTTP server does AJAX require?

Web Development JavaScript Front-End Development Easy Javascript Aptitude

Which HTTP server does AJAX require?

- ☐ Apache
- ☐ Microsoft web server
- ☒ Any HTTP server will work
- ☐ Sun application server

### Question - 65

SCORE: 5 points

Which of the following is the right option?

Web Development

JavaScript

Front-End Development

Easy

HTML Tags

You want to update the following element with the XMLHttpRequest status. Which of the following approaches is correct for the purpose?

`<div id="statusCode"></div>`

- ☐ `var myDiv = document.getElementById ("statusCode"); myDiv.innerHTML = req.statusCode;`
- ☒ `var myDiv = document.getElementById ("statusCode"); myDiv.innerHTML = req.status;`
- ☐ `var myDiv = document.getElementById ("statusCode"); myDiv.setStatus (req.statusCode);`
- ☐ `var myDiv = document.getElementById ("statusCode"); myDiv.status = req.status;`

### Question - 66

SCORE: 5 points

What is the purpose of the NOSCRIPT tag?

Web Development

JavaScript

Front-End Development

Easy

What is the purpose of the NOSCRIPT tag?

- ☐ To prevent the page scripts from executing
- ☐ To shield a part of a page from being modified by JS, so that a statement like `aDiv.innerHTML = 'something'` has no effect.
- ☒ To enclose text to be displayed if the browser doesn't support JS
- ☐ There is no NOSCRIPT tag

### Question - 67

SCORE: 5 points

What should be called before 'send ()' to prepare an XMLHttpRequest object?

Web Development

JavaScript

Front-End Development

Easy

Javascript Aptitude

What should be called before 'send ()' to prepare an XMLHttpRequest object?

- ☐ `prepare ()`

☒ open ()

☐ init ()

☐ build ()

### Question - 1

#### Kubernetes Two or More Instructions

SCORE: 5 points

Easy Kubernetes

You are composing a Kubernetes scenario file in YAML format. You want to put more than one instruction inside one file. How can this be achieved?

- ☐ # namespace creation instruction  
( one or more space)  
# pod creation instruction
- ☒ # namespace creation instruction  
---  
# pod creation instruction
- ☐ # namespace creation instruction  
# pod creation instruction
- ☐ There is no way to put more that one instruction per file.

### Question - 2

#### Kubernetes Run Command

SCORE: 5 points

Easy Kubernetes

After setting up a Kubernetes cluster, you want to run the package manager update process in a particular pod. How this can be achieved?

- ☐ kubectl run pod/frontend-controller-01 --cmd="apt-get update"
- ☐ kubectl exec pod/frontend-controller-01 --cmd="apt-get update"
- ☐ kubectl run pod/frontend-controller-01 -- apt-get update
- ☒ kubectl exec pod/frontend-controller-01 -- apt-get update

### Question - 3

#### Kubernetes Pod Logs

SCORE: 5 points

Easy Kubernetes

After a rollback to the previous deployment of a Kubernetes service, you need to fetch the last log entries of all the pods marked with a specific "publisher" label. What is the correct way to do this?

- ☐ kubectl logs --last=10 -l publisher=hacker-company
- ☐ kubectl get logs --count=10 --selector="publisher=hacker-company"

- ☒ kubectl logs --tail=10 -l publisher=hacker-company
- ☐ kubectl get logs --count=-10 -l publisher=hacker-company

#### Question - 4

##### Kubernetes Find Documentation

SCORE: 5 points

Easy Kubernetes

While refactoring an existing Kubernetes cluster, you want to create a new service but you have forgotten the resource schema. How can you get a short explanation of a specific resource definition?

- ☒ kubectl explain service
- ☐ kubectl help service
- ☐ kubectl describe service
- ☐ kubectl expose service

#### Question - 5

##### Kubernetes Get Deployment Information

SCORE: 5 points

Easy Kubernetes

While optimizing an existing Kubernetes cluster, you need to get extended information about the deployment named "hacker-application". How can you do this?

- ☒ kubectl describe deployment hacker-application
- ☐ kubectl expose deployment hacker-application
- ☐ kubectl explain deployment hacker-application
- ☐ none of the above

#### Question - 6

##### Kubernetes Pods Query

SCORE: 5 points

Easy Kubernetes

As part of your Kubernetes cluster maintenance process, you need to find out all the pods working in the staging environment. You know each pod has a specific label named "environment" which refers to a particular environment name. How can you get all the pods with the label "environment=staging"?

- ☐ kubectl get pods --label environment=staging
- ☒ kubectl get pods --selector=environment=staging
- ☐ kubectl label environment=staging
- ☐ kubectl expose pods environment=staging

## Question - 7

### Kubernetes Labels & Annotations

SCORE: 5 points

Easy Kubernetes

You are replicating an existing production deployment on staging. As part of this process, you have decided to attach an environment-oriented label and set annotation. How can you do this?

- ☐ `kubecttl attach label deployment hacker-application environment=staging`  
`kubecttl set annotation deployment hacker-application url="https://staging.hacker-company.com"`
- ☐ `kubecttl set label deployment hacker-application environment=staging`  
`kubecttl set annotation deployment hacker-application url="https://staging.hacker-company.com"`
- ☒ `kubecttl label deployment hacker-application environment=staging`  
`kubecttl annotate deployment hacker-application url="https://staging.hacker-company.com"`
- ☐ `kubecttl create label deployment hacker-application environment=staging`  
`kubecttl create annotation deployment hacker-application url="https://staging.hacker-company.com"`

## Question - 8

### Kubernetes Basic Pod

SCORE: 5 points

Kubernetes Easy

As the next part of your Kubernetes cluster maintenance, you want to test that everything still works properly. For a quick check, you want to execute a test image run. What is the right command?

- ☐ `kubecttl exec --image=hello-world test`
- ☐ `kubecttl exec --rm -i --image=hello-world --restart=Never test`
- ☐ `kubecttl create image hello-world`
- ☒ `kubecttl run --rm -i --image=hello-world --restart=Never test`

## Question - 9

### Kubernetes Deployment Scale

SCORE: 5 points

Kubernetes Easy

While maintaining your company's Kubernetes cluster, you found that Redis deployment should be scaled according to the metrics you see. What command should be executed to scale operation up to 3 (increase the number of ReplicaSets)?

- ☒ `kubecttl scale --replicas=3 -n hacker-company ReplicaSet/redis`
- ☐ `kubecttl scale --number=3 -n hacker-company ReplicaSet/redis`
- ☐ `kubecttl scale --to=3 -n hacker-company ReplicaSet/redis`
- ☐ `kubecttl patch --set="replicas=3" -n hacker-company ReplicaSet/redis`

## Question - 10

### Kubernetes Pods Status

SCORE: 5 points

Easy

Kubernetes

You are working on one of your company's existing Kubernetes clusters. You want to retrieve information about all the pods you have for a specific namespace. Which of these commands will achieve this?

- ☐ kubectl explain pods hacker-company
- ☐ kubectl explain pods -n hacker-company
- ☒ kubectl get pods -n hacker-company
- ☐ kubectl expose pods -n hacker-company



## Question - 1

### Error Handling in AWS Lambdas

SCORE: 5 points

AWS

Lambda Function

Error Handling

Easy

Node.js

```
const AWS = require('aws-sdk');
const s3 = new AWS.S3();

exports.handler = async (event, context) => {
 const { Records } = event;
 const promises = Records.map(async (record) => {
 const { s3: { bucket, object } } = record;
 const params = {
 Bucket: bucket.name,
 Key: object.key,
 };

 try {
 const data = await s3.getObject(params).promise();
 console.log(`Successfully retrieved object: ${object.key}`);
 return data;
 } catch (error) {
 console.error(`Error retrieving object: ${object.key}`);
 throw error;
 }
 });

 try {
 const results = await Promise.all(promises);
 return { statusCode: 200, body: JSON.stringify(results) };
 } catch (error) {
 return { statusCode: 500, body: `Error: ${error.message}` };
 }
};
```

Which of the following statements is true about this AWS Lambda function written in Node.js?

- ☐ The function will only log errors encountered when retrieving objects and will not return an error status code to the caller.
- ☐ The Lambda function will continue processing the remaining S3 objects even if an error occurs while retrieving one of the objects.
- ☒ The Lambda function uses the Promise.all() method to process all S3 objects in parallel and waits for all promises to resolve or reject.
- ☐ The Lambda function processes the S3 objects sequentially, one after another.

## Question - 2

### Clustered Express Middleware

SCORE: 5 points

ExpressJS

Middleware

Easy

Node.js

```

const cluster = require('cluster');
const os = require('os');
const express = require('express');

if (cluster.isMaster) {
 const numCPUs = os.cpus().length;

 for (let i = 0; i < numCPUs; i++) {
 cluster.fork();
 }

 cluster.on('exit', (worker, code, signal) => {
 console.log(`Worker ${worker.process.pid} died`);
 cluster.fork();
 });
} else {
 const app = express();
 const port = 3000;

 app.get('/', (req, res) => {
 res.send('Hello from the clustered Express server!');
 });

 app.listen(port, () => {
 console.log(`Worker ${process.pid} listening on port ${port}`);
 });
}

```

Which statement is true regarding this snippet?

- ☒ The application forks a new worker process for each available CPU core.
- ☐ The master process listens for incoming requests on a different port than the worker processes.
- ☐ The cluster.isMaster property is used to determine whether the current process is running on a Windows system or not.
- ☐ If a worker process dies, it will not be replaced by a new worker process.

|                                             |                        |
|---------------------------------------------|------------------------|
| <b>Question - 3</b><br><b>Mocking Beans</b> | <b>SCORE: 5 points</b> |
|---------------------------------------------|------------------------|

- Spring Test
- Easy
- Mockito
- Spring Mocking

Given the following implementation of *DataService* which uses *ApiClient* component to call external APIs:

```

@Component
public class ApiClient {
 public void call() {
 //not relevant code
 }
}

@Service
public class DataService {
 @Autowired
 private ApiClient apiClient;
 public void collectData() {
 apiClient.call();
 }
}

```

```
}
}
```

The requirement is to implement the test and don't call external API during the test execution. The following code has been implemented:

```
@SpringBootTest
class DataServiceTest {
 <CODE HERE>
 @Autowired
 DataService dataService;
 @Test
 void collectData() {
 dataService.collectData();
 //test code
 }
}
```

What should be inserted instead of *<CODE HERE>* to achieve the goal?

- ☐ @Mock ApiClient apiClient; @InjectMocks
- ☐ @InjectMocks
- ☒ @MockBean ApiClient apiClient;
- ☐ @Captor ApiClient apiClient;
- ☐ @SpyBean ApiClient apiClient;

Question - 4  
Secure Method

SCORE: 5 points

Spring Expression Language

spring security

Easy

Given the following controller method, assume that *userService* is correctly implemented and autowired.

```
<CODE_HERE>
@GetMapping("/users/{id}")
public ResponseEntity<UserResponse> get(@PathVariable @NotNull UUID id) {
 return ResponseEntity.ok(userService.get(id));
}
```

The requirement is to make sure that only users with any of *ROLE\_ADMIN* or *ROLE\_USER\_MANAGER* roles assigned will be able to execute this method. What can be put in place of *<CODE\_HERE>* to implement this requirement using Spring Security?

- ☐ @PostAuthorize("hasRole('ROLE\_ADMIN') or hasRole('ROLE\_USER\_MANAGER')")
- ☒ @PreAuthorize("hasAnyRole('ROLE\_ADMIN','ROLE\_USER\_MANAGER')")
- ☐ @Secured("hasRole('ROLE\_ADMIN') or hasRole('ROLE\_USER\_MANAGER')")
- ☐ @PreAuthorize("hasRole('ROLE\_ADMIN') and hasRole('ROLE\_USER\_MANAGER')")

Question - 5  
Transactional Tests

SCORE: 5 points

Spring Test

Easy

transaction management

Given the following test code, which of the statements is true?

```
@ExtendWith(SpringExtension.class)
@Transactional
@ContextConfiguration
class UserRepositoryTest {
 @Test
 @Commit
 void test1() {
 /* non relevant code */
 }
 @Test
 @Rollback(false)
 void test2() {
 /* non relevant code */
 }
}
```

- ☐ Only the transaction for method test1() will be committed.
- ☐ Only the transaction for method test2() will be committed.
- ☒ Transactions for both methods will be committed.
- ☐ @Transactional will lead to a runtime error when running the tests.

## Question - 6

### Postgres Specific Service

SCORE: 5 points

Starter Parent

Spring Configuration

Easy

The requirement is to implement a Spring Boot `@Service` that should be loaded to the spring context only if the `org.postgresql.Driver` class is present on the classpath, and the `application.properties` file contains the property `database.vendor=postgres`.

```
<CODE HERE>
@Service
public class PostgresSpecificService {
 /* not relevant code*/
}
```

Which of the following annotation options can replace `<CODE HERE>` to achieve this?

- ☐ `@ConditionalOnProperty(name = "database.vendor", value = "postgres") @ConditionalOnClass(name = "org.postgresql.Driver")`
- ☒ `@ConditionalOnProperty(prefix = "database", name = "vendor", havingValue = "postgres") @ConditionalOnClass(name = "org.postgresql.Driver")`
- ☐ `@ConditionalOnProperty(name = "database.vendor", havingValue = "postgres") @ConditionalOnMissingBean(org.postgresql.Driver.class)`
- ☐ `@ConditionalOnProperty(prefix = "database", name = "vendor", havingValue = "postgres") @ConditionalOnBean(name = "org.postgresql.Driver")`
- ☐ None of the above

## Question - 7

### Bean Scopes

SCORE: 5 points

Starter Parent Easy Spring Scope

Consider the following code.

```
<CODE HERE>

public class Processor {
 public void process() {
 /* not relevant code */
 }
}

@RestController
public class ProcessController {
 @Autowired
 private Processor processor;
 @GetMapping("/process")
 public void process() {
 processor.process();
 }
}
```

What should be inserted in place of `<CODE HERE>` to have a new instance of processor created every time the `/process` endpoint is called?

- ☐ @Scope("prototype") @Component
- ☐ @Prototype
- ☒ @Component @Scope(scopeName = "prototype", proxyMode= ScopedProxyMode.TARGET\_CLASS)
- ☐ @Component('autowireCandidate=true')
- ☐ @Service(alwaysNew=true)

## Question - 8

### Spring AOP Usage

SCORE: 5 points

Spring Spring Boot Easy

Consider the following code.

#### NotifierMetricLogger.java

```
package spring.listener;

import org.aspectj.lang.annotation.Around;
import org.aspectj.lang.annotation.Aspect;
import org.aspectj.lang.annotation.Before;
import org.aspectj.lang.annotation.AdviceName;
import org.springframework.stereotype.Component;
import org.aspectj.lang.JoinPoint;
import org.aspectj.lang.ProceedingJoinPoint;
import java.util.logging.Logger;

//X
@Component
public class NotifierMetricLogger {
```

```

private static final Logger log = Logger.getLogger(NotifierAspect.class.getName());
//Y
public Object beforeNotifyLogging(ProceedingJoinPoint joinPoint) throws Throwable {
 long startDate = System.currentTimeMillis();
 Object proceed = joinPoint.proceed();
 long executionTime = System.currentTimeMillis() - startDate;
 log.info("Notify process time :" + executionTime);
 return proceed;
}
}

```

### TwitterNotifier.java

```

package spring.service.impl;

import spring.service.Notifier;
import org.springframework.stereotype.Component;
import java.util.logging.Logger;

@Component
public class TwitterNotifier implements Notifier {
 private static final Logger log = Logger.getLogger(TwitterNotifier.class.getName());
 @Override
 public void notify(String message) {
 log.info("TwitterNotifier: " + message);
 //send notification to home page
 }
}

```

### Notifier.java

```

package spring.service;

public interface Notifier {
 void notify(String message);
}

```

Assuming the Spring Boot application is configured to use AOP with `@EnableAspectJAutoProxy(proxyTargetClass = true)` annotation, to capture *TwitterNotifier.notify(String message)* method's process time, which of the following options should be placed in the X and Y positions in NotifierMetricLogger.java?

- ☐ X = @Aspect  
Y = @Before("execution(\* spring.service.impl.\*.notify(..))")
- ☐ X = @AdviceName("NotifierMetricLogger")  
Y = @Around("execution(\* spring.service.impl.\*.notify(..))")
- ☐ X = @AdviceName("NotifierMetricLogger")  
Y = @Before("execution(\* spring.service.impl.\*.notify(..))")
- ☒ X = @Aspect  
Y = @Around("execution(\* spring.service.Notifier.notify(..))")

### Question - 9 Spring Circular Bean Trap

SCORE: 5 points

Spring

Spring Boot

Easy

Consider the following code.

### Circular.java

```
package spring.circular;

public interface Circular {
 void doCircularThings();
}
```

### CircularBeanA.java

```
package spring.circular;
import org.springframework.stereotype.Component;
import javax.annotation.PostConstruct;

//X
@Component
public class CircularBeanA implements Circular {
 private Circular circularBeanB;

 public CircularBeanA(
 //Y
 Circular circularBeanB) {
 this.circularBeanB = circularBeanB;
 }

 @Override
 public void doCircularThings() {
 System.out.println("CircularBeanA: did bad things");
 }

 @PostConstruct
 private void init() {
 System.out.println("CircularBeanA: initialized");
 }
}
```

### CircularBeanB.java

```
package spring.circular;

import org.springframework.context.annotation.Lazy;
import org.springframework.stereotype.Component;
import javax.annotation.PostConstruct;

@Component
public class CircularBeanB implements Circular {
 private Circular circularBeanA;

 public CircularBeanB(
 @Lazy
 //Z
 Circular circularBeanA) {
 this.circularBeanA = circularBeanA;
 }

 @Override
 public void doCircularThings() {

 }

 @PostConstruct
```

```

public void init() {
 System.out.println("CircularBeanB: initialized");
 circularBeanA.doCircularThings();
}
}

```

Which of the following options are true regarding this code?

- ☐ The application runs successfully and it'll output  
CircularBeanA: initialized  
CircularBeanB: initialized  
CircularBeanA: did bad things
- ☐ The application won't run.  
The code doesn't compile.
- ☐ The application runs but it will throw `NoUniqueBeanDefinitionException` and it will exit.
- ☐ If @Qualifier("circularBeanA") annotation is put on Z and @Qualifier("circularBeanB") put on Y, the application will not throw BeanCurrentlyInCreationException and runs successfully.
- ☒ The application runs and it will write  
CircularBeanB: initialized into console then  
it will throw org.springframework.beans.factory.BeanCurrentlyInCreationException.
- ☒ If @PostConstruct annotation is removed in CircularBeanB, it will run successfully and will print  
CircularBeanA: initialized into console
- ☐ if @Primary annotation is put in X place, it will run successfully.

<b>Question - 10</b> <b>Bean definition enhancement</b>	<b>SCORE: 5 points</b>
------------------------------------------------------------	------------------------

Spring Boot

Starter Parent

Easy

During the startup of a Spring Boot application, it needs to read bean configuration metadata and change it before the container instantiates any beans.

How can this be achieved in an efficient and scalable way?

- ☐ Implement BeanPostProcessor.
- ☒ Implement BeanFactoryPostProcessor.
- ☐ It is not possible to change beans metadata on runtime. All beans metadata is defined at compile time.
- ☐ Implement Aspect.

<b>Question - 11</b> <b>Behavior Inheritance</b>	<b>SCORE: 5 points</b>
-----------------------------------------------------	------------------------

Spring Boot

Starter Parent

Easy

A Spring Boot application has the following hierarchy of classes.

```

public class Animal {
 @PostConstruct
 private void init() {
 System.out.println("Animal init");
 }
}

```



```

 }

@Component
public class Cat extends Animal{
 @PostConstruct
 public void init() {
 System.out.println("Cat init");
 }
}

@Lazy
@Component
public class Dog extends Animal{
 @PostConstruct
 public void init() {
 System.out.println("Dog init");
 }
}

```

What is the output?

- ☐ IllegalArgumentException: @PostConstruct should be applied to a public method
- ☐ Cat init Dog init
- ☒ Animal init Cat init
- ☐ Animal init Cat init Animal init Dog init
- ☐ Animal init Cat init Dog init or Animal init Dog init Cat init

## Question - 12

### Multiple Beans Definition

SCORE: 5 points

Spring Spring Boot Dependency Management Easy

A Spring application has an interface called *Server*, and two implementations: *ServerA* and *ServerB*. There is a class, *ServerManager*, that uses the *Server* bean as a dependency.

```

public interface Server {
}

@Service
public class ServerA implements Server {
}

@Service
public class ServerB extends ServerA {
}

@Service
public class ServerManager {
 @Autowired
 Server server;
}

```

Which of the following statements is true about this code?

- ☐ The code throws `InterfaceNotInstantiableException`.

- ☐ The code runs fine. A random Server implementation is injected into the `server` field.
- ☒ The code throws `NoUniqueBeanDefinitionException`.
- ☐ The code does not compile.

### Question - 13

#### Testing a Spring Application

SCORE: 5 points

Spring

Spring Boot

Spring Test

Easy

There is a Spring boot web application that uses a relational database for data storage. The *org.springframework.boot:spring-boot-starter-data-jdbc* starter is used in the implementation of the data access layer. Now tests are needed that cover the functionality of the data layer in isolation.

What Spring test annotation is recommended when constructing the test context?

- ☐ @DataJpaTest
- ☒ @DataJdbcTest
- ☐ @SpringBootTest
- ☐ @WebMvcTest

### Question - 14

#### Path Variable

SCORE: 5 points

Spring

Spring Boot

Spring MVC

Easy

In the Spring MVC controller, which of these are valid uses of the @PathVariable annotation?

- ☒ @RequestMapping(value="/users/{userId}/addresses/{addressId}") public String viewUserAddress(@PathVariable String userId, @PathVariable String addressId, Model m)
- ☐ @RequestMapping(value="/users/{userId}") public String viewUser(@PathVariable("users") String user, Model m)
- ☒ @RequestMapping(value="/users/{userId}") public String viewUser(@PathVariable String userId, Model m)
- ☒ @RequestMapping(value="/users/{userId}") public String viewUser(@PathVariable("userId") String personnelId, Model m)

### Question - 15

#### Component Dependency

SCORE: 5 points

Spring

Spring Boot

Configuration

Easy

The following @Configuration contains definitions for 2 beans: ServiceA and ServiceB. Imports are omitted.

```
@Configuration
public class ServiceConfiguration {
 @Bean
 public ServiceA serviceA(ServiceB serviceB) {
 return new ServiceA(serviceB);
 }
}
```

```

 }
 @Bean
 public ServiceB serviceB(ServiceC serviceC) {
 return new ServiceB(serviceC);
 }
 @Bean
 public ServiceC serviceC(ServiceA serviceA) {
 return new ServiceC(serviceA);
 }
}

```

Which of the following statements is true?

- ☐ This code does not compile.
- ☐ This code runs fine and creates 3 Beans: `ServiceA`, `ServiceB` and `ServiceC`.
- ☒ The code throws `BeanCurrentlyInCreationException` when run.
- ☐ The code throws `StackoverflowError` when run.

## Question - 16

### Application Properties Override

SCORE: 5 points

Spring Boot

Application Properties

Easy

In the classpath of a Spring Boot application, there are 2 files with properties *application.properties* and *application-prod.properties*. It is required to always load properties from *application.properties* and override with values in the *application-prod.properties* file only when the application is deployed on the production server.

What should the value of the environment be to achieve this on the production server?

- ☐ spring.properties=application-prod.properties
- ☐ spring.profiles.active=application-prod
- ☒ spring.profiles.active=prod
- ☐ environment=prod

## Question - 17

### Create a User Controller

SCORE: 5 points

Spring Boot

Spring MVC

Easy

An *HTTP POST* endpoint accepts a JSON representation of a *User* object. It uses the following *User* and *UserController* classes.

```

public class User {
 @NotEmpty
 private String name;
 @NotEmpty
 private String surname;
}

@RestController
public class UserController {

```

```
@PostMapping("/users")
public void create(@RequestBody User user) {
 System.out.println("name: "+user.getName() + " surname: "+user.getSurname());
}
}
```

What is the result of a call with the payload below?

```
{
 "name": "Duke",
 "surname": null
}
```

- ☐ BAD REQUEST 400 and a message that `user.surname` is validated by @NotEmpty annotation.
- ☒ OK 200 and prints 'name: Duke surname: null'
- ☐ SERVER ERROR 500 because of a NullPointerException during validation of `null` string for @NotEmpty
- ☐ OK 200 and prints 'name: Duke surname:'

## Question - 18

### Spring Dependency Injection

SCORE: 5 points

Spring

Easy

```
@Service
public ProductService {
 private ProductRepository productRepository;
 private ProductMapper productMapper;

 @Autowired
 public ProductService(ProductRepository productRepository,
 ProductMapper productMapper){
 this.productRepository = productRepository;
 this.productMapper = productMapper;
 }
}
```

Which type of injection is implemented in the ProductService?

- ☐ Setter
- ☐ Getter
- ☐ Property
- ☒ Construction

## Question - 19

### Profile

SCORE: 5 points

Which command-line argument starts a Spring Boot application with the “staging” Spring profile?

- ☐ --spring.active.profile=staging
- ☐ --profiles.active=staging
- ☐ --active.profile=staging
- ☒ --spring.profiles.active=staging

## Question - 20

### Query Annotation

SCORE: 5 points

Which of the following annotations can be used for a specific custom query in a Spring data JPA repository method?

- ☐ @JpaQuery
- ☐ @SqlQuery
- ☐ @DataQuery
- ☒ @Query

## Question - 21

### Property Value Injection

SCORE: 5 points

Which of the following annotations can be used to inject property values into Spring Boot beans and configuration classes?

- ☐ @Values
- ☐ @Property
- ☐ @Inject
- ☒ @Value

## Question - 22

### Dependency Injection

SCORE: 5 points

Which of the following options can be used for dependency injection in Spring Boot?

- ☒ Setter injection

- ☐ jsonConfiguration
- ☒ Constructor injection
- ☒ @Autowired

## Question - 23

### Endpoints

SCORE: 5 points

Spring Boot Easy

Which Spring-based code snippet must fill the blank such that Actuator security rules are present, and all endpoints fetch for actuator?

```
@Bean
public PrivacyChain demoChain(ServerHttpSecurity http) {
 return http.authorizeExchange()
 .pathMatchers(_____).permitAll()
 .and().build();
}
```

- ☐ /actuators/\*\*
- ☐ /actuators.\*\*
- ☒ /actuator/\*\*
- ☐ /actuator/info/\*\*

## Question - 24

### Actuator

SCORE: 5 points

Spring Boot Easy

A dependency has been added to pom.xml in a Spring application as follows.

```
<dependency>

<groupId>org.springframework.boot</groupId>

<artifactId>spring-boot-starter-actuator</artifactId>

</dependency>
```

What is the starter used for?

- ☒ application analysis
- ☐ creation of an application
- ☐ automation of an application
- ☐ production of application instances

## Question - 25

### Validator

SCORE: 5 points

Spring Boot

Easy

In a RESTful application using Spring, which of the following is not used to create an object validator?

- ☐ @Min(value = 1)  
@Max(999999)  
private int id;
- ☒ @Size(limit = 100)  
private String name;
- ☐ @NotNull  
private Boolean isActive;
- ☐ @ValidCategory(categoryType="sample")  
private String category;

## Question - 26

### Rest Handle

SCORE: 5 points

Spring Boot

Easy

When building a Spring-based RESTful application, a new resource must be created with the request URI of "/handle". Which of the following code segments is most appropriate?

- ☒ @RestController  
public class demoHandler {  
    private static Map<String, Product> dataRepo = new HashMap<>();  
    @RequestMapping(value = "/handle", method = RequestMethod.POST)  
    public ResponseEntity<Object> createProduct(@RequestBody Product product) {  
        .....  
    }  
}
- ☐ @RestController  
public class demoHandler {  
    private static Map<String, Product> dataRepo = new HashMap<>();  
    @RequestMapping(value = "/handle", method = RequestMethod.DELETE)  
    public ResponseEntity<Object> createProduct(@RequestBody Product product) {  
        .....  
    }  
}
- ☐ @RestController

```

public class demoHandler {
 private static Map<String, Product> dataRepo = new HashMap<>();
 @RequestMapping(value = "/handle", method = RequestMethod.CREATE)
 public ResponseEntity<Object> createProduct(@RequestBody Product product) {

 }
}

```

☐ @RestController

```

public class demoHandler {
 private static Map<String, Product> dataRepo = new HashMap<>();
 @RequestMapping(value = "/handle", method = RequestMethod.GET)
 public ResponseEntity<Object> createProduct(@RequestBody Product product) {

 }
}

```

## Question - 27

### Classes Segment

SCORE: 5 points

Spring Boot Easy

A Spring application has four classes. Select the option which would contain the business logic.

- ☒ @Service public class A{ .. }
- ☐ @Repository public class A{ .. }
- ☐ @Primary public class A{ .. }
- ☐ @Session public class A{ .. }

## Question - 28

### Mechanism

SCORE: 5 points

Spring Boot Easy

Which annotation should be used instead of <<blank>> that will allow one to use the class for data storage, update, and retrieval?

```

<<blank>>
public class DemoSession implements DemoInterface{

 @Override
 public void save(Student student) {

 }
}

```



- ☐ @Service
- ☒ @Repository
- ☐ @Session
- ☐ @Autowired

### Question - 29

#### Spring Annotation

SCORE: 5 points

Spring Boot Easy

What does the annotation in this Spring-based code segment do?

```
@Component
public class ComponentExample {
 int x;
 public void show() {
 System.out.println("Hello");
 }
}
```

- ☐ It allows Spring to create containers.
- ☐ It allows Spring to create components.
- ☐ It allows Spring to collect bean instances.
- ☒ It allows Spring to detect custom beans automatically.

### Question - 30

#### Employee

SCORE: 5 points

Spring Boot Easy

In the following Spring Boot code, what kind of dependency is injected by the annotation?

```
public class Employee {

 @Autowired
 private Roll roll;

 Employee() {
 }
}
```

- ☐ constructor based
- ☐ setter bean

- ☒ field based
- ☐ Spring IOC

### Question - 31

SCORE: 5 points

Book

Easy Spring Boot

```
@Entity
public class Book {

 @Id
 Long id;
 String author;
 String year;

}
```

For this model, which option is a valid derived query method for its corresponding JpaRepository?

- ☐ findAuthorById
- ☒ findByAuthor
- ☐ findByAuthorAndIdAndYear
- ☐ findBook

### Question - 32

SCORE: 5 points

FooBar

Easy Spring Boot

```
@RequestMapping(value = {"/ex/basic/bar", "/ex/basic/foo"}, method = RequestMethod.GET)
public String getPath() {
 return "FooBar";
}
```

Which link will hit the following method, where the application context is '/home'?

- ☒ "GET request http://localhost:8080/home/ex/basic/bar"
- ☐ "GET request http://localhost:8080/home/ex/basic"
- ☐ "POST Request http://localhost:8080/home/ex/basic/bar"
- ☐ Two routes cannot be mapped to one resource.

### Question - 33

SCORE: 5 points

Easy

Spring Boot

In Spring's approach to building RESTful web services, how are the HTTP requests handled?

- ☒ They are handled by a controller and identified by the `@RestController` annotation.
- ☐ They are handled by an object.
- ☐ They are handled by a class.
- ☐ They are handled by a controller and identified by the `@GreetingController` annotation.

**Question - 34****Transactions**

SCORE: 5 points

Microservices

Easy

A payment gateway company that integrates PayPal, Stripe, and many other vendors uses microservices for their infrastructure. Whenever a user clicks on the payment button, a request to the backend is made and money is instantly deducted. Whenever a user presses the button twice, the charges are deducted twice. How can you fix this problem?

- ☐ Disable the button after it is pressed one time.
- ☐ Disable the transaction from the backend once it is approved one time.
- ☐ Add an idempotence key to the request and add the transaction to the queue.
- ☒ A and C
- ☐ A and B

**Question - 35****Microservices Security**

SCORE: 5 points

Microservices

Easy

A company deals has implemented the GPT-3 AI Text Generation using microservices infrastructure for handling thousands of users. The operations team receives a notification that three of their services are down. There is evidence of image pullback failure. Upon investigating, they deduced that one of their services was internet facing and was exploited. The exploited service started messaging other services with corrupted data. The team applied security patches to fix the problem.

What is the fix?

- ☒ The team added mTLS and added rules for inter-service communications. After that, they pushed the internet-facing server behind a load balancer and applied JWT tokens for authentication.
- ☐ The team cut off the internet-facing service from the infrastructure and applied a JWT token for each call to other services.
- ☐ A and B

<b>Question - 36</b> <b>Semantic Monitoring Drawback</b>	<b>SCORE: 5 points</b>
-------------------------------------------------------------	------------------------

Easy
Microservices

Semantic monitoring (a.k.a. synthetic monitoring) runs a subset of an application's automated tests against the live production system on a regular basis. What are the side effects of semantic monitoring?

- ☐ extra load on the services
- ☐ There is a probability that tests will inject test data into production.
- ☐ There is a possibility that semantic monitoring provides false positives.
- ☒ All of the above

<b>Question - 37</b> <b>Tests in Production</b>	<b>SCORE: 5 points</b>
----------------------------------------------------	------------------------

Microservices
Easy

Semantic monitoring (a.k.a. synthetic monitoring) runs a subset of an application's automated tests against the live production system on a regular basis. Which of the following options is the most appropriate and actionable benefit of semantic monitoring?

- ☒ decrease in average downtime as we can pinpoint which service is at fault
- ☐ detailed monitoring about production environment
- ☐ consistent health checks about different services

<b>Question - 38</b> <b>Conway's Law</b>	<b>SCORE: 5 points</b>
---------------------------------------------	------------------------

Microservices
Easy

A food retail company has an infrastructure based on microservices. While in development the various departments were isolated from each other and were provided with tight deadlines. The department leads informed their teams that if anything went wrong, they could do it over again.

According to Conway's law (the organization system design structure replicates their communication structure), the scenario should be remedied. Which of the following options correctly remedies the problems that arose in the scenario?

- ☐ Give up features while adding more communication channels to the team and create independent teams.
- ☐ Restructure the team to report to multiple people at the same time.
- ☐ Start micro-managing a set of teams by allocating tasks more closely to make delivery effective.
- ☒ Restructure and also create independent teams that will dictate their communication channels.

Question - 39

Client Side Load Balancing

SCORE: 5 points

Microservices

Easy

A streaming service provider uses a microservices architecture to support its infrastructure. To ensure a seamless user experience, the service uses client-side load balancing, where the client automatically connects to different servers based on availability. However, a security flaw has been identified: the client stores sensitive data, such as server locations and authentication tokens, on the client side, making them vulnerable to exposure and misuse.

What is the most effective way to mitigate this security vulnerability?

- ☐ A: Each service will need to authenticate the requests individually and cannot trust other services.
- ☐ B: Add more layers of authentication and authorization in between the servers/clients
- ☐ C: Add mTLS certificates that expire after 10 minutes.
- ☒ B and C

Question - 40


Master Master Replication 3

SCORE: 5 points

Microservices

Medium

Consider the diagram below.



A team of developers has successfully refactored the system to resolve problems in consistency, latency, and lag. They would like to test the environment before going to production.

How should the following steps be organized to conduct the tests?

1. Perform E2E (end-to-end) tests first and identify the key differences.
2. Divert some production traffic to the test environment to see how it works i.e. A/B Testing.
3. Perform unit testing.

- ☐ 1 -> 2 -> 3
- ☐ 2 -> 3 -> 1

## Question - 41

## Master Master Replication 2


SCORE: 5 points

Microservices

Medium

The team has identified the issues of increased latency, volatile consistency, greater replication lag, and potential for data loss of data in the architecture diagram below. How should the steps be organized to mitigate these issues?

1. Create a separate test environment.
2. Start adding queues and caches.
3. Start refactoring the database.



- ☐ 3 -> 2 -> 1
- ☒ 1 -> 3 -> 2
- ☐ 1 -> 2 -> 3
- ☐ 2 -> 1 -> 3

## Question - 42


## Master Master Replication

SCORE: 5 points

Microservices

Medium

Consider the diagram below:



A team of developers manages Service A and Service B. The services read and write data to the Master-Master replication stateful set. What is a potential flaw in the system?

the system?

- ☐ increased latency due to synchronization
- ☐ volatile consistency due to lag in write
- ☐ The more read slaves are added to the system, the more you have to replicate, which leads to greater replication lag.
- ☐ potential loss of data if one of the masters fails
- ☒ All of the above.

### Question - 43

#### Microservices Reliability

SCORE: 5 points

Microservices

Medium

A chat-based app like Whatsapp is using microservices to connect thousands of real-time users together. They have a flaw in the design of the microservices that all the reads and writes go through one service, "Service A". Service A provides them a great deal of volatility and unpredictability. The company would like to refactor the codebase to address the unpredictability of the system.

Which of the following decisions should they go with?

- ☒ Separate the read and write APIs into separate services.
- ☒ Add a queue to the write API and a cache on the read API so the system can efficiently handle messages.
- ☐ Add redundancy to Service A.

### Question - 44

#### Disaster Recovery

SCORE: 5 points

Microservices

Medium

A common cause of failure in microservices is downstream services. Downstream services are the services that are impure. That is, they have dependencies such as database connections, queues, etc. How would you mitigate the failure of these services?

- ☒ Add redundancy to the downstream services.
- ☐ Add master/worker nodes to the downstream services.
- ☐ Add more services to downstream services for better logging and error handling.

☐ None of the above

### Question - 45

#### Service Discovery

SCORE: 5 points

Service Mesh

Microservices

Easy

On March 8, 2022, a music provider detected a global outage in its services. Their system is based on microservices. For microservices to be able to find each other, they utilize service discovery technologies like Google Traffic Detector. The incident happened due to a bug within Google Traffic Detector.

Since this issue was from a third-party provider, what is the likely solution to this problem?

- ☐ Migrate service discovery to other vendors, e.g. AWS, and Azure.
- ☐ Migrate microservices back to monolith.
- ☒ Add multiple service discovery options in the infrastructure.
- ☐ Ask the vendor to fix the problem and wait for the fix.

### Question - 46

#### Microservices Usage

SCORE: 5 points

Microservices

Easy

A services-based company is building an AI tooling system that can help their client streamline their training and inference data set using AWS Fargate. However Fargate does not provide GPU access to users, and it is expensive for the client. The team decided to implement a custom solution that can scale and train custom models of users. Given the short time span, they have two options:

1. Build the custom Solution using Microservices, LinkerD, MicroK8s.
2. Use an existing system like KubeFlow and build custom features on top of it.

Which of the following is the best way forward?

- ☒ Try 2 then 1.
- ☐ Try and test 1.
- ☐ Try 1 and then 2.

### Question - 47

#### Distributed System Characteristics

SCORE: 5 points

Microservices

Medium

Distributed Systems

Which of the following are advantages of a distributed system?

- ☒ If one component fails in a distributed system, the remaining components may be able to continue operating.
- ☐ It is less difficult to implement a distributed database system because of its low cost of installation.
- ☐ The amount of processing overhead is less than with a monolithic architecture.



- ☒ It overcomes bottlenecks of the processing pipeline easier than with a centralized system.

## Question - 48

### Understanding Microservice

SCORE: 5 points

Medium

Distributed Systems

Microservices

Which of the following statements describe the properties of a microservice?

- ☒ Focuses on a single responsibility principle
- ☐ Too large and complex to fully understand and make changes fast and correctly.
- ☒ Responsible for its own task and communicates with other services through simple APIs to solve a larger complex business problem
- ☐ Should implement a fully testable end-to-end business use-case

## Question - 49

### Communication Methods

SCORE: 5 points

Distributed Systems

HTTP

JSON

Easy

Which of these is a method of communication between microservices in a larger application?

- ☐ HTTP Protocol
- ☐ Event-driven or Message-driven
- ☐ SOAP
- ☒ All of these

### Question - 1

#### MySQL: Column Deletion

SCORE: 5 points

MySQL

Easy

Choose the expression that deletes a column.

- ☐ DELETE status FROM queue
- ☒ ALTER TABLE queue DROP COLUMN status
- ☐ DELETE COLUMN status FROM queue
- ☐ ALTER TABLE queue DROP status COLUMN

### Question - 2

#### MySQL: Self Join

SCORE: 5 points

MySQL

Easy

Select an expression that demonstrates a self join type.

- ☒ SELECT \* FROM users users, users clients
- ☐ SELECT \* FROM users SELF JOIN users AS clients
- ☐ SELECT \* FROM users JOIN users AS clients
- ☐ None of the above, a self join type does not exist in MySQL

### Question - 3

#### MySQL: Sorting Direction

SCORE: 5 points

MySQL

Easy

Select the extraneous expression (not the same as the others).  
Select all that apply.

- ☐ SELECT \* FROM categories ORDER BY id
- ☐ SELECT \* FROM categories ORDER BY id ASC
- ☒ SELECT \* FROM categories ORDER BY id DESC
- ☐ None of the above, all expressions are the same.

## Question - 4

### MySQL: Comma In From Clause

SCORE: 5 points

MySQL Easy

Choose the correct explanation of the next query:

```
SELECT * FROM users, clients
```

- ☒ Selects everything in the "users" table, then adds columns from the "clients" table.
- ☐ If the "users" table exists, selects everything from there. Otherwise, queries the "clients" table as a fallback.
- ☐ Selects everything in the "users" table, then assigns the "clients" alias.
- ☐ Selects everything in the "users" table, then adds rows from the "clients" table.

## Question - 5

### MySQL: Space In From Clause

SCORE: 5 points

MySQL Easy

Choose the correct explanation of the next query:  
Select all that apply.

```
SELECT * FROM users clients
```

- ☐ Selects everything in the "users" table, then adds columns from the "clients" table.
- ☐ If the "users" table exists, selects everything from there. Otherwise, queries the "clients" table as a fallback.
- ☒ Selects everything in the "users" table, then assigns the "clients" alias.
- ☐ Selects everything in the "users" table, then adds rows from the "clients" table.

## Question - 6

### Query Based Question 3

SCORE: 5 points

React Easy

Consider the following code.

```
import React from "react";

class App extends React.Component {
 state = {
```

```

name: "",
email: "",
contact: "",
};

setValue = (event) => {};

render() {
 const { name, email, contact } = this.state;
 return (
 <React.Fragment>
 <p>Name = {name}</p> <p>Email = {email}</p> {" "}
 <p>Contact = {contact}</p>
 <input name="name" onChange={this.setValue} />
 <input name="email" onChange={this.setValue} />
 <input name="contact" onChange={this.setValue} /> {" "}
 </React.Fragment>
);
}
}

export default App;

```

There is a common `setValue` function that is used to update all the states on change. Which of the following options provides that functionality?

- ☒ `setValue = (event) => { this.setState({ [event.target.name]: event.target.value });};`
- ☐ `setValue = (event) => { this.setState({event.target.name: event.target.value });};`
- ☐ `setValue = (event) => { this.setState({ [event.name]: event.value });};`
- ☐ None of the above

## Question - 7

### Class Component Initial Rendering

SCORE: 5 points

React Class Components Easy

Consider the following code.

```

import React from "react";

class App extends React.Component {
 constructor(props) {
 super(props);
 this.state = {
 Number: 0
 };
 }

 componentDidMount() {
 this.increment()
 this.increment()
 this.increment()
 }

 componentWillUnmount() {
 this.increment()
 }

 increment = () => {
 this.setState({
 Number: this.state.Number + 1
 });
 };
}

```

```

 };

 render() {
 return (
 <div>
 <p>Number: {this.state.Number}</p>
 <button onClick={this.increment}>Increment</button>
 </div>
);
 }
 }

 export default App;

```

While first rendered, what is displayed in the `p` tag?

- ☐ 0
- ☒ 1
- ☐ 3
- ☐ Undefined

## Question - 8

### React Class Component State

SCORE: 5 points

React

Class Components

Easy

What is the output?

```

import React from "react"

class App extends React.Component {
 constructor(props) {
 super(props);
 this.state = { Number: 0 };
 }

 componentDidMount() {
 this.setState({ Number: 1 });
 console.log(this.state.Number);
 this.setState({ Number: 2 });
 console.log(this.state.Number);
 this.setState({ Number: 3 }, () => {
 console.log(this.state.Number);
 });
 }

 render() {
 return <div>{this.state.Number}</div>;
 }
}

export default App;

```

- ☐ 0,0,0
- ☐ 1,1,1

☐ 1,2,3

☒ 0,0,3

## Question - 9

### Array Functions

SCORE: 5 points

React

Array Functions

Easy

Consider the following code snippet.

```
import React from "react";

function App() {
 const data = [{ Name: "Ranjit", Roll: 122 }, { Name: "Ron", Roll: 122 }];
 const display = () => {
 let result;
 return (
 <div>
 <h1>{result.Name}</h1>
 <h1>{result.Roll}</h1>
 </div>
);
 };
 return <div>{display()}</div>;
}

export default App;
```

Which is the preferred method to initialize the result variable to fetch an object named *Ranjit*?

- ☐ let result= data.map((data) => data.name=="Ranjit");
- ☐ let result= data.filter((data) => data.name=="Ranjit");
- ☒ let result= data.find((data) => data.name=="Ranjit");
- ☐ None of the above

## Question - 10

### State Update

SCORE: 5 points

React

React Hooks

Functional Components

Easy

Consider the following code.

```
import React, { useState } from "react";

const App = () => {
 const [student, setStudent] = useState({
 Name: "Abc",
 Roll: "123",
 Presence: 0,
 });

 const update = (Presence) => {
 };
}
```

```

return (
 <>
 <p>{student.Presence}</p>
 <button onClick={() => update(student.Presence + 1)}>
 Update Student
 </button>
 </>
);
};

export default App;

```

Which option increments the student presence by 1?

- ☐ this.setState({Presence});
- ☐ setStudent(pre=>{...pre,Presence});
- ☒ setStudent({ ...student, Presence });
- ☐ None of the above

Question - 11  
Initial Rendering

SCORE: 5 points

- React
- Easy
- Functional Components
- State Management

What is the output of the following code?

```

import React, { useState } from "react";

const App = () => {
 const [number, setNumber] = useState(0);
 console.log(number); //output
 return (
 <>
 <p>{number}</p>
 <button onClick={setNumber((pre) => pre + 1)}>increment</button>
 </>
);
};

export default App;

```

- ☐ 0
- ☐ 1
- ☐ undefined
- ☒ Error

Question - 12  
Event

SCORE: 5 points

- Event Handlers
- Easy

Which React code snippet returns the mouse position?



```
useEffect (() => {
 const setFromEvent = (e) => setPosition({ x:
e.clientX, y: e.clientY });
window.addEventListener("mousemove",
setFromEvent);

 return () => {
 window.removeEventListener("mousemove",
setFromEvent);
 };
}, []);
```



```
useEffect (() => {
 const setFromEvent = (e) => setPosition({ x:
e.clientX, y: e.clientY });
window.addEventListener("mousemove",
setFromEvent);
}, []);
```



Both of the snippets above will provide the functionality required.



```
useCallback(() => {
 const setFromEvent = (e) => setPosition({ x:
e.clientX, y: e.clientY });
 window.addEventListener("mousemove",
setFromEvent);

 return () => {
 window.removeEventListener("mousemove",
setFromEvent);
 };
}, [])
```



None of the above

## Question - 13

### State Management

SCORE: 5 points

State Management

Easy

Which change to the following code will cause it to increment *count* every second.

```
function Counter() {
 let [count, setCount] = useState(0);
 useEffect (() => {
 let id=setInterval(() => {
 setCount(count + 1);
 }, 1000);
 return () => clearInterval(id);
 }, []);
```



```
return <h1>{count}</h1>;
}
```

- ☐ Replace line 5 with `setCount(++count);`
- ☐ Replace line 5 with `setCount(prevCount+ 1);`
- ☐ Replace line 5 with `setCount(count++);`
- ☒ Replace line 5 with `setCount(prevCount => prevCount+ 1);`
- ☐ None of the above

## Question - 14

SCORE: 5 points

### Components

Easy

Class Components

This code is part of a React application.

```
const Home = () => {
 const [isLoading, setLoading] = useState(true);
 if(isLoading) {
 return <Loader />;
 }
 useEffect (() => { //fetchData }, []);
}
```

Which of the following statements is correct?

- ☐ The isLoading state has been initialized to TRUE, but it should be FALSE initially.
- ☐ An error will be thrown as the useEffect hook is called conditionally.
- ☒ The Loader component will always be shown, and the useEffect hook will not be executed.
- ☐ None of the above

## Question - 15

SCORE: 5 points

### MySQL: Search In Specific Range Of Values

MySQL

Easy

Select the expression with the correct syntax.

- ☒ `SELECT * FROM logs WHERE priority IN ( 'high', 'medium' )`
- ☐ `SELECT * FROM logs WHERE priority VALUES IN ( 'high', 'medium' )`
- ☐ `SELECT * FROM logs WHERE priority IN VALUES ( 'high', 'medium' )`
- ☐ `SELECT * FROM logs WHERE priority IN SET ( 'high', 'medium' )`

## Question - 16

### MySQL: Combining Tables

SCORE: 5 points

MySQL Easy

Select the expressions that cause a MySQL error.

- ☐ SELECT \* FROM logs l1 JOIN logs l2 ON l1.id = l2.id
- ☒ SELECT \* FROM logs l1 AND FROM logs l2 ON l1.id = l2.id
- ☒ SELECT \* FROM logs l1 UNION logs l2 ON l1.id = l2.id
- ☐ SELECT \* FROM logs l1 LEFT JOIN logs l2 ON l1.id = l2.id

## Question - 17

### MySQL: Result Limit Offset

SCORE: 5 points

MySQL Easy

Select the expression with the correct syntax.

- ☒ SELECT \* FROM logs LIMIT 3, 5
- ☐ SELECT \* FROM logs LIMIT 3 - 5
- ☐ SELECT \* FROM logs LIMIT 3 TO 5
- ☐ SELECT \* FROM logs LIMIT 3 FOR 5

## Question - 18

### MySQL: Rounding Numbers

SCORE: 5 points

MySQL Easy

Choose an expression that returns 0.

- ☐ SELECT CEIL(.4)
- ☐ SELECT ROUND(.5)
- ☒ SELECT FLOOR(.6)
- ☐ None of the above, all expressions return 1

## Question - 19

### MySQL: Field Selection

SCORE: 5 points

MySQL Easy

Select the expression that causes a MySQL error.

- ☐ SELECT 1, 2, 3
- ☒ SELECT 1 2 3
- ☐ SELECT '1 2 3'
- ☐ None of the above, all expressions are correct

### Question - 20

#### MySQL: Result Set Combine Operator

SCORE: 5 points

Easy MySQL

This operator is used to combine the result set of two or more SELECT statements.

- ☐ FIND\_IN\_SET
- ☐ GROUP BY
- ☒ UNION
- ☐ COMBINE

### Question - 21

#### MySQL: Condition Operators

SCORE: 5 points

Easy Database

Which expression causes a MySQL error?

- ☐ SELECT IF( 1 < 2, 'yes', 'no' )
- ☐ SELECT IFNULL( NULL, 10 )
- ☐ SELECT CASE WHEN 1>0 THEN 'true' ELSE 'false' END
- ☒ SELECT IFNOT( 'true', FALSE )
- ☐ SELECT NULLIF( 1, 1 )

### Question - 22

#### MySQL: GROUP BY Statement

SCORE: 5 points

MySQL Easy

Select the expression that is not correct.

- ☐ The GROUP BY statement groups rows with the same value into total rows.

- ☒ Aggregate functions (COUNT(), MAX(), MIN(), etc.) can be used only with an explicit GROUP BY statement.
- ☐ You can apply an additional condition after the grouping using the HAVING clause.
- ☐ None of the above, all expressions are correct.

## Question - 23

### MySQL: Joins

SCORE: 5 points

MySQL Easy

Which expression is not correct?

- ☐ MySQL joins are used to join rows from two or more tables based on the associated column between them.
- ☐ The INNER JOIN keyword selects records that have matching values in both tables.
- ☐ A self-join is just a normal join, but the table joins itself.
- ☒ Using the RIGHT JOIN keyword returns only records that are joined in the right way.

## Question - 24

### MySQL: PRIMARY KEY Constraint

SCORE: 5 points

Easy MySQL

Which expression is not correct?

- ☐ The primary key uniquely identifies each record in the table.
- ☐ The primary key must contain unique values.
- ☒ The primary key can contain NULL values, but this is highly undesirable for performance reasons.
- ☐ A table can have only one primary key.

## Question - 25

### MySQL: NULL Constraint

SCORE: 5 points

MySQL Easy Constraints

Which of the following SQL CREATE TABLE statements differs from the others in terms of the NULL constraint?

- ☐ CREATE TABLE users ( id INT )
- ☐ CREATE TABLE users ( id INT NULL )
- ☒ CREATE TABLE users ( id INT NOT NULL )
- ☐ None of the above, all expressions are the same.

## Question - 26

### MySQL: Deleting a Table

SCORE: 5 points

MySQL

Easy

Select the expression(s) with the correct syntax.

- ☒ DROP TABLE IF EXISTS users
- ☐ DELETE TABLE IF EXISTS users
- ☒ DROP TABLE users
- ☐ DESTROY TABLE users

## Question - 27

### MySQL: Deleting a Database

SCORE: 5 points

Easy

Which expression has the correct syntax?

- ☐ REMOVE DATABASE users
- ☐ DELETE DATABASE users
- ☒ DROP DATABASE users
- ☐ DESTROY DATABASE users

## Question - 28

### MySQL: Creating a Database

SCORE: 5 points

Easy

MySQL

Select the expression with the correct syntax.

- ☐ CREATE DATABASE WITH NAME users
- ☐ CREATE DB WITH NAME users
- ☐ CREATE DB users
- ☒ CREATE DATABASE users

## Question - 29

### MySQL: Comment Types

SCORE: 5 points

MySQL

Easy

Which of the following are MySQL comments?

- ☒ # this is the comment
- ☒ -- this is the comment
- ☒ /\* this is the comment \*/
- ☐ <!-- this is the comment -->

Question - 30  
MySQL: Join Type That Left Then Right

SCORE: 5 points

MySQL Easy

Which of these MySQL join types return all records from the left table and the matched records from the right table?  
Select all that apply.

- ☒ LEFT JOIN
- ☐ LEFT INNER JOIN
- ☐ LEFT RIGHT JOIN
- ☒ LEFT OUTER JOIN

Question - 31  
MySQL: String Comparison

SCORE: 5 points

MySQL Easy

Select the expression that causes a MySQL error.

- ☐ SELECT \* FROM transactions WHERE flag IN('A', 'B', 'C')
- ☐ SELECT \* FROM transactions WHERE flag BETWEEN 'A' AND 'C'
- ☐ SELECT \* FROM transactions WHERE flag >= 'A' AND flag <= 'C'
- ☒ none of the above, all expressions are correct

Question - 32  
MySQL: Like Expression Pattern

SCORE: 5 points

MySQL Easy

Select all ID values that will NOT be matched by the following query  
Select all that apply.

```
SELECT id FROM customers WHERE id LIKE '_a%'
```

- ☐ \_a%
- ☐ fa23345f-ad73-404d-8988-72f1385e3aeb
- ☐ \_a466d3
- ☒ none of the above, all values will be matched

### Question - 33

SCORE: 5 points

#### MySQL: Join Type That Matching Values in Both Tables

MySQL

Easy

Which MySQL join type returns records that have matching values in both tables?  
Select all that apply.

- ☐ OUTER JOIN
- ☒ INNER JOIN
- ☐ CROSS JOIN
- ☐ FULL JOIN

### Question - 34

SCORE: 5 points

#### MySQL: Results Limit

MySQL

Easy

Select expressions with correct syntax.

- ☒ SELECT \* FROM customers LIMIT 5 OFFSET 10
- ☐ SELECT \* FROM customers LIMIT 5 + 10
- ☐ SELECT \* FROM customers LIMIT 5 TO 10
- ☒ SELECT \* FROM customers LIMIT 5, 10

### Question - 35

SCORE: 5 points

#### MySQL: Results Order

MySQL

Easy

Select the expression that causes a MySQL error.  
Select all that apply.

- ☐ SELECT id, name FROM customers ORDER BY name ASC
- ☐ SELECT id, name FROM customers ORDER BY name
- ☐ SELECT id, name FROM customers ORDER BY 2

☒ none of the above, all expressions are correct

## Question - 36

SCORE: 5 points

### MySQL: White Space in Field Alias

MySQL

Easy

Select the expressions with correct syntax.

- ☒ SELECT name AS "customer name" FROM customers
- ☒ SELECT name AS 'customer name' FROM customers
- ☒ SELECT name AS `customer name` FROM customers
- ☐ SELECT name AS customer\ name FROM customers

## Question - 37

SCORE: 5 points

### MySQL: Join Types

MySQL

Easy

Which of the following are valid MySQL join types?

Select all that apply.

- ☒ LEFT
- ☒ CROSS
- ☒ RIGHT
- ☐ TOP

## Question - 38

SCORE: 5 points

### React: True statements

React

Front-End Development

Easy

Which of the following statement(s) is true about ReactJS?

1. Only one root element can be returned per component.
2. Both arguments of the useEffect hook are compulsory.
3. The useState hook returns an object.
4. The useState hook cannot be used outside of a functional component.

- ☒ 1
- ☐ 2
- ☐ 3
- ☒ 4



## Question - 39

SCORE: 5 points

React: Route

React

Front-End Development

Router

Easy

```
import React from 'react';
import {BrowserRouter as Router, Switch, Route} from "react-router-dom";
import Home from "./Home";
import About from "./About";

function App() {
 return (
 <Router>
 <Switch>
 <Route path="/" component={Home} />
 <Route path="/about" exact component={About} />
 </Switch>
 </Router>
)
}

export default App
```

What component will get rendered if the URL is "http://localhost:3000/about"?

- ☒ <Home />
- ☐ <About />
- ☐ <Home /> <About />
- ☐ No output

## Question - 40

SCORE: 5 points

React: Children

React

Front-End Development

Props

Easy

What is the output?

```
import React from 'react'

function Test (props) {
 return (
 <div>
 <p>Hello {props.name}</p>
 <p>{props.children}</p>
 </div>
);
}

export default function App() {
 return (
 <Test name="candidate" children="Frontend">
 <p>Welcome to Hackerrank!</p>
 </Test>
)
}
```

- }
- ☐ Hello candidate  
Frontend
  - ☒ Hello candidate  
Welcome to Hackerrank!
  - ☐ Hello candidate  
undefined
  - ☐ Error

## Question - 41

### React: Check statements

SCORE: 5 points

React

Front-End Development

Props

Easy

```
import React from 'react';
function Sample(props) {
 return (
 <>
 <div>
 <p>{props.name}</p> { /* Statement 1 */}
 <p>{props.designation}</p> { /* Statement 2 */}
 </div>

 <div>
 <p>{props[0]}</p> { /* Statement 3 */}
 <p>{props['designation']}</p> { /* Statement 4 */}
 </div>
 </>
)
}
```

```
export default Sample;
```

Which of the statement(s) will not generate an error? ('name' and 'designation' are the props passed to the <Sample /> from the App component)

- ☒ Statement 1
- ☐ Statement 2
- ☒ Statement 3
- ☒ Statements 4

## Question - 42

### React: Welcome

SCORE: 5 points

React

Front-End Development

Easy

```
import React from "react";
function App() {
 return (
 <div>
 <p>Hi</p>
 <p>Welcome to Hackerrank</p>
 </div>
 <div>
 <p>This is a react problem!</p>
 </div>
);
}
export default App;
```

What is the output of the code snippet?

- ☐ Hi  
Welcome to Hackerrank
- ☐ Hi  
Welcome to Hackerrank  
This is a react problem!
- ☐ This is a react problem!
- ☒ This code will generate an error.

## Question - 43

SCORE: 5 points

React: Add class

Front-End Development

React

Classes

Easy

Which of the following code snippets can be used to dynamically add a class to a tag in ReactJS? Assume all imports and exports are there.

S1:

```
function App() {
 const [state, setState] = useState(false);
 return (
 <div>
 <button onClick={() => setState(!state)}>Click me!</button>
 <h1 className={state && "red-color"}>Hello</h1>
 </div>
);
}
```

S2:

```
function App() {
 const [state, setState] = useState(false);
 const color = "red-color";
 return (
 <div>
 <button onClick={() => setState(!state)}>Change color</button>
 <h1 className={color}>Hello</h1>
 </div>
);
}
```

S3:

```
function App() {
 const [state, setState] = useState(false);
 return (
 <div>
 <button onClick={() => setState(!state)}>Click me!</button>
 <h1 className={state ? "red-color": "blue-color"}>Hello</h1>
 </div>
);
}
```

S4:

```
function App() {
 const [state, setState] = useState(false);
 return (
 <div>
 <button onClick={() => setState(!state)}>Click me!</button>
 <h1 className="red-color">Hello</h1>
 </div>
);
}
```

- ☒ S1
- ☐ S2
- ☒ S3
- ☐ S4

Question - 44  
React: Hooks and Their Applications

SCORE: 5 points

React   Hooks   Easy

Match the commonly used React hooks and their applications.

Hook	Application
1. useState	a. Perform side effects on updates
2. useEffect	b. Returns memorized values
3. useContext	c. Used to track state
4. useMemo	d. Manage state globally

- ☐ 1.b
- ☐ 2.c
- ☐ 3.d
- ☐ 4.a
- ☒ 1.c
- ☐ 2.a
- ☐ 3.d

☐ 1.d  
2.c  
3.a  
4.b

☐ 1.b  
2.d  
3.a  
4.c

## Question - 45

SCORE: 5 points

### React: Styling in JavaScript

React

CSS3

Easy

Styling React

Select the appropriate option to generate inline styles equivalent to the CSS stylesheet.

```
.my-style{
 background-color: blue;
 color: red;
 font-size: large;
 border: solid 10px black;
}
```

☐

```
const MyComponent = () => {
 return (
 <div style="background-color: blue;
 color:red;
 font-size:large;
 border:solid 10px black; ">

 My CSS Div
 </div>
)
};
```

☐

```
const MyComponent = () => {
 return (
 <div style={background-color: "blue",
 color:"red",
 font-size:"large",
 border:"solid 10px black"}>

 My CSS Div
 </div>
)
};
```

☒

```
const MyComponent = () => {
 return (
 <div style={{background-color: "blue",
 color:"red",
 fontSize:"large",
 border: "solid 10px black"}}>
```

```

 My CSS Div
 </div>
)
};

```

☐

```

const MyComponent = () => {
 return (
 <div style={'background-color': "blue",
 'color':"red",
 'fontSize':"large",
 'border': "solid 10px black"}>
 My CSS Div
 </div>
)
};

```

Question - 46
 SCORE: 5 points

React: Valid Routes

React
 React Router
 Routes
 Easy

Which route is not valid for this React Router component?

```

<Routes>
 <Route path="/" element={<Home />} />
 <Route path="/user/:id" element={<User />} />
 <Route path="/user/:id/edit" element={<UserEdit />} />
 <Route path="/post/:id" element={<Post />} />
 <Route path="/posts" element={<Posts />} />
</Routes>

```

- ☐ /user/1/edit
- ☐ /post/10
- ☒ /post
- ☐ /profile/12

Question - 47
 SCORE: 5 points

React: Components and Routes

React
 Easy
 React Router
 Routes

Which component will load when the Route '/signin' is requested from this React Router?

```

<BrowserRouter>
 <Routes>
 <Route path="/" element={<LandingPage />} />
 <Route path="/home" element={<HomePage />} />
 </Routes>
</BrowserRouter>

```

```
<Route path="/about" element={<AboutPage />} /> />
<Route path="/contact" element={<ContactPage />} /> />
<Route path="/login" element={<LoginPage />} /> />
<Route path="/signup" element={<SignupPage />} /> />
<Route path="*" element={<NotFoundPage />} /> />
</Routes>
</BrowserRouter>
```

- ☐ LoginPage
- ☐ SignupPage
- ☒ NotFoundPage
- ☐ HomePage

Correct Answer: NotFoundPage

## Question - 48

React: Counter

SCORE: 5 points

React Hooks Easy

```
const Counter = () => {
 const [number, setNumber] = React.useState(0);
 const incrementNumber = () => {
 setNumber(number + 1);
 };
 React.useEffect(() => setNumber(10), [number]);
 return (
 <div>
 Count: {number}
 <button onClick={() => incrementNumber()}>Increment Counter</button>
 </div>
)
};
export default Counter;
```

The ReactJS Counter component is rendered as shown. The value of *{number}* is 10. What will be the value of *{number}* after clicking "Increment Counter" 3 times?

Count: 10

Increment Counter

- ☐ 15
- ☐ 13
- ☒ 10
- ☐ 0

## Question - 49

SCORE: 5 points

### React: Functional Components

React

Easy

Syntax

Which is the functional component that is equivalent to this React Class component?

```
class Hello extends React.Component{
 render(){
 const {name, age} = this.props;
 return(
 <div>
 Hello {name} is {age} years old.
 </div>
)
 }
}

Hello.propTypes = {
 name: PropTypes.string,
 age: PropTypes.number
}

Hello.defaultProps = {
 name: 'David'
}

export default Hello;
```



```
function Hello({ name = 'David', age }) {
 return (
 <div>
 <p>Hello {name} is {age} years old</p>
 </div>
);
}
Hello.propTypes = {
 name: PropTypes.string,
 age: PropTypes.number.isRequired
};
export default Hello;
```



```
function Hello({ name, age }) {
 return (
 <div>
 <p>Hello {name} is {age} years old</p>
 </div>
);
}
Hello.propTypes = {
 name: PropTypes.string,
 age: PropTypes.number.isRequired
};
export default Hello;
```





```
function Hello({ name = 'David', age }) {
 return (
 <div>
 <p>Hello {name} is {age} years old</p>
 </div>
)
}
Hello.propTypes = {
 name: PropTypes.string,
 age: PropTypes.number.isRequired
};
export default Hello;
```

☐ The Class component cannot be converted into a functional component.

**Question - 50**  
**React: States and Props**

SCORE: 5 points

React   Component State Management   State Management   Easy

Consider these React components as rendered below.  
 ScoreBoard.js

```
const ScoreBoard = () => {
 const [score, setScore] = React.useState(0);
 const [goal, setGoal] = React.useState(0);

 const newScore = (event) => {
 setScore(score + 1);
 setGoal(goal + 1);
 }
 return (
 <div>
 <p>Score: {score}</p>
 <p>Goal: {goal}</p>
 <ScoreManager newScore={newScore} score={score} goal={goal} />
 </div>
)
}

export default ScoreBoard;
```

ScoreManager.js

```
const ScoreManager = (props, { score, goal }) => {
 const resetScore = (event) => {
 score = 0
 goal = 0
 }
 return (
 <div>
 <button onClick={props.newScore}> Add Score </button>
 <button onClick={resetScore}> Reset Score </button>
 </div>
)
};
export default ScoreManager;
```

Output:

Score: 0

Goal: 0

Add Score

Reset Score

What will be the values of Score and Goal printed after clicking the 'Add Score' button 5 times and then clicking the 'Reset Score' button

☒ Score: 5  
Goal: 5

☐ Score: 0  
Goal: 0

☐ Score: 4  
Goal: 4

☐ Score: 5  
Goal: 0

## Question - 51

SCORE: 5 points

React: Events

React

EventListener


Easy

```
import React from 'react';
import PropTypes from 'prop-types';
import './Question2.css';

const GoalComponent = () => {
 const shoot = (message, event) => console.log(message);
 return (
 <div className="Question2">
 <div className='main-div' onClick={(event) => shoot("No Goal", event)}>
 <button onClick={(event) => shoot("Goal", event)} >
 Click Me
 </button>
 </div>
 </div>
)
}

export default GoalComponent;
```

The given React component renders as shown below.



What is logged to the console when "Click Me" is clicked?

- ☐ Goal
- ☐ No Goal
- ☒ Goal  
No Goal
- ☐ No Goal  
Goal

Question - 52  
Render Function

SCORE: 5 points

- Easy
- React
- React Component Lifecycle

Which of the following functions gets invoked after the render() function when `state` or `props` is updated?

- ☐ componentWillMount()
- ☐ componentDidMount()
- ☐ componentWillReceiveProps()
- ☒ componentDidUpdate()

Question - 53  
Method Search

SCORE: 5 points

- Easy
- React
- React Component Lifecycle

Which of the following methods is/are invoked when there is an error during rendering in the React lifecycle?

- ☐ getDerivedStateFromError()
- ☐ componentDidCatch()
- ☒ Both A and B.
- ☐ None of the above

Question - 54  
Wrap Code

SCORE: 5 points

Assuming options state values are given in the constructor, which code should wrap the components that are going to have access to the context inside a class component?

- ☒ `<NotesContext.Provider value={this.state.notes}> //code </NotesContext.Provider>`
- ☐ `<NotesContext value={this.state.notes}> //code </Notes.Provider>`
- ☐ `<NotesContext.Provider value={this.state.notes}> //code <Notes.Provider/>`
- ☐ `<NotesContext.Provider value={this.state.notes}/> //code <Notes.Provider>`

## Question - 55

SCORE: 5 points

Submit

What element type does this render?

```
function Music() {
 return Tiesto - Surrounded by Light;
}

ReactDOM.render(<Music/>, document.getElementById('root'));
```

- ☐ div
- ☒ span
- ☐ Component
- ☐ None above

## Question - 56

SCORE: 5 points

Hooks

Which is the equivalent code using hooks?

```
import React, { Component } from 'react'
export default class SampleComponent extends Component {
 componentDidMount() {
 //
 }
 render() {
 return (<div>Hello</div>)
 }
}
```

- ☐ import React, { useEffect } from 'react';  
const SampleComponent = () => {  
 useEffect(() => {  
 //  
 }, [this]);  
 return ('Hello')  
}  
export Component
- ☐ import React, { useEffect } from 'react';  
Default const SampleComponent= () => { Effect(() => { {/.../} }, []); return ('Hello') } export SampleComponent
- ☒ import React, { useEffect } from 'react';  
const SampleComponent = () => {  
 useEffect(() => { // }, []); return ('Hello');  
} export SampleComponent
- ☐ None above

### Question - 57

Click 3

SCORE: 5 points

Easy React

What is displayed in H1 when after a user clicks the button 3 times?

```
import React, { useState } from 'react';
export default function App() {
 const [clicked, setClicked] = useState(3);
 return (
 <div className="App">
 <button onClick={() => setClicked((clicked - 1) * 2)}>
 Click Me
 </button>
 <h1>{clicked}</h1>
 </div>
);
}
```

- ☐ 5
- ☐ 6
- ☐ 14
- ☒ 10

### Question - 58

Science Project

SCORE: 5 points

Easy React

Which of the following is a valid syntax to use the variable inside a component?

```
const SkyColor = "Blue";
```

- ☐ <Uppersky className="Space\_Details">\${Skycolor}</Uppersky>
- ☐ <Uppersky className="Space\_Details"><Skycolor></Skycolor> </Uppersky>
- ☐ <Uppersky className="Space\_Details" class="SkyColor"></Uppersky>
- ☒ <Uppersky className="Space\_Details">{SkyColor}</Uppersky>

## Question - 59

SCORE: 5 points

Hello

React

React Component

Easy

What is the output generated by the App component?

App.js

```
import Component from "../Component";
function App() {
 return (
 <>
 <Component title = "Hello"/>
 <Component title = "Everyone"/>
 <Component title = "Good Morning"/>
 </>
);
}
```

export default App;

Component.js

```
export default function Component(props){
 return (
 <div>
 <h1>{props.title}</h1>
 </div>
);
}
```

- ☐ Hello  
Hello  
Hello
- ☒ Hello  
Everyone  
Good Morning
- ☐ This code wouldn't compile
- ☐ Hello  
Exception thrown

## Question - 60

### React State

SCORE: 5 points

React

Easy

Which option replaces "//insert code" to update the state of a component multiple times with `newState` function calls?

```
export default class Game extends React.Component{
 constructor(props){
 super(props);
 this.state = { name : "Peter" };
 this.newState = this.newState.bind(this)
 }
 newState(){
 //insert code
 }
}
```

- ☐ this.setState="David";
- ☐ this.setChangeState({name:"David"})
- ☒ this.setState({name:"David"})
- ☐ Both A and B

## Question - 61

### Name

SCORE: 5 points

React

React Component

Easy

Assuming this component is imported and used on a page, what is its output?

```
import React, { Component } from 'react';
class App extends Component {
 constructor(){
 super();
 this.state={name:"peter"}
 }
 render(){
 return (
 <div>
 {this.state.name}
 </div>
)
 }
} export default App
```

- ☐ This code will not compile.
- ☐ Error

- ☐ Peter
- ☒ peter

## Question - 62

### Clock

SCORE: 5 points

Easy React React Component Lifecycle

This component is used on a page that has a div tag with a root ID. What happens when this code runs?

```
import React from 'react';
import ReactDOM from 'react-dom';
export default class Clock extends React.Component {
 constructor(props) {
 super(props);
 this.state = { time : new Date() };
 }
 render() {
 return (
 <div><h1>{ this.props.title } !</h1>
 <h2>{this.state.time}</h2></div>;
)
 }
}
ReactDOM.render(
 <Clock title="ThisisMyClock" />,
 document.getElementById('root')
);
```

- ☐ {CurrentTimeinFormat}ThisisMyClock is displayed.
- ☒ There is a runtime exception.
- ☐ ThisisMyClock{CurrentTimeinFormat} is displayed.
- ☐ None of the above

## Question - 63

### Leap Year

SCORE: 5 points

Easy React

The parameter *year* is passed as a prop. What code replaces "//CODE HERE" to complete the function?

```
let LeapYear=(props)=>{
 //CODE HERE
 if((year % 4 === 0 && year % 100 !== 0) || year % 400 === 0){
 return <p>{year} is a leap year.</p>
 }else{
 return <p>{year} is not a leap year.</p>
 }
}
export default LeapYear
```



- ☐ let year;
- ☒ let year = props.year;
- ☐ year = props.year;
- ☐ let props.year;

## Question - 64

### Attribute Access

SCORE: 5 points

Easy React

Which option will access attributes of the CSS file at "./mystyle.module.css"?

```
.TextDesign {
 colour: Blue;
 padding: 40px;
 font-family: Arial;
 text-align: centre;
}
```

- ☐

```
import React from 'react';
import ReactDOM from 'react-dom';
import styles from './mystyle.module.css';
class TextColor extends React.Component {
 render() {
 return <h1 className=styles>Hello I am a text!</h1> }
 }
}
export default TextColor;
```
- ☐

```
import React from 'react';
import ReactDOM from 'react-dom';
import styles from './mystyle.module.css';
class TextColor extends React.Component {
 render() {
 return <h1 id={styles.color}>Hello I am a text!</h1>;
 }
}
export default TextColor;
```
- ☐

```
import React from 'react';
import ReactDOM from 'react-dom';
import styles from './mystyle.module.css';
class TextColor extends React.Component {
 render() {
 return <h1 className={Textdesign.color}>Hello I am a text!</h1>;
 }
}
export default TextColor;
```
- ☒

```
import React from 'react';
import ReactDOM from 'react-dom';
import styles from './mystyle.module.css';
```

```
class TextColor extends React.Component {
 render() {
 return <h1 className={styles.TextDesign}>Hello I am a text!</h1>;
 }
}
export default TextColor;
```

Question - 65  
Student Result

SCORE: 5 points

SQL Easy

Consider the table below:

Table Student	
ID	SCORE
1	2
2	5
3	5
4	6
5	9

How many tuples does the result of the following SQL query contain where result = 'Supplementary'?

```
SELECT id,
CASE
 WHEN score<=2 THEN 'Fail'
 WHEN score<6 THEN 'Supplementary'
 ELSE 'Distinction'
END as result
FROM student
```

- ☒ 2
- ☐ 3
- ☐ 0
- ☐ 1

Question - 66  
Common Students

SCORE: 5 points

SQL Easy

Consider the following tables:

Table s1

column	description
id	unique identifier
name	student name

Table s2

column	description
id	unique identifier
name	student name

Which of the following SQL queries will result in students' names common to both tables having the same id, sorted alphabetically? Multiple students can have the same name but their ids will be unique.

- ☒ select s1.name from s1 INNER JOIN s2 ON s1.id=s2.id ORDER BY s1.name
- ☐ select name from s1 OUTER JOIN s2 ON s1.id=s2.id ORDER BY id
- ☐ select s1.name from s1 LEFT JOIN s2 ON s1.id=s2.id ORDER BY name
- ☐ select name from s1 LEFT JOIN s2 ON s1.id>s2.id

## Question - 67

SCORE: 5 points

### Output Rows

SQL

Easy

Consider the following tables:

Table A

ID	Name	Salary
101	John	1500
102	Steve	1500
103	Remo	500
104	Alan	2000
105	Maverick	1000
106	Glen	2000
107	Jacob	2000

Table B

ID	Department
101	Sales
102	Finance

103	Finance
104	HR
105	HR
106	Sales
107	IT

How many tuples does the following SQL query return?

```
SELECT * FROM (SELECT b.department,
 Avg(a.salary) AS avg_Salary
 FROM a
 LEFT JOIN b
 ON a.id = b.id
 GROUP BY b.department) AS C
WHERE C.avg_salary > 1500
```

- ☐ 0
- ☐ 1
- ☒ 2
- ☐ 3

## Question - 68

### Print the Domain Name

SCORE: 5 points

SQL Easy Database

The email has the value of an email ID. Fill in the blanks of the following SQL statements so that it prints the domain name. The domain name of nymame@abcd.com is abcd.com.

SELECT SUBSTR (email,INSTR (email,\_\_\_\_\_) )FROM DUAL ;

- ☒ '@',1)+1)
- ☐ '@',1))
- ☐ '@',1)-1)
- ☐ none of these

## Question - 69

### Which command?

SCORE: 5 points

SQL Easy Database

There are multiple records in a table and some are duplicates. Which command will fetch only one copy of the duplicate records?

- ☒ SELECT DISTINCT
- ☐ SELECT UNIQUE
- ☐ SELECT DIFFERENT
- ☐ All of the above

### Question - 70

#### SQL ROUND

SCORE: 5 points

SQL Easy Database

The SQL statement

SELECT ROUND(45.926, -2) FROM DUAL ;

- ☐ is illegal
- ☐ prints garbage
- ☐ prints 45.92
- ☒ prints 0

### Question - 71

#### Which command is behaving incorrectly?

SCORE: 5 points

SQL Database Easy

What command should you try if DBMS\_OUTPUT.PUT\_LINE is not doing what it is supposed to do?

- ☐ SET ECHO ON
- ☐ SET DISPLAY ON
- ☐ SET TERMOUT ON
- ☒ SET SERVEROUTPUT ON

### Question - 72

#### SQL Order of Operations

SCORE: 5 points

SQL Easy

Which is the correct order of execution of operations in SQL?

- ☒ SELECT, FROM, JOIN, WHERE, GROUP BY, HAVING, ORDER BY

- ☐ SELECT, FROM, GROUP BY, WHERE, HAVING, ORDER BY
- ☐ FROM, GROUP BY, WHERE, ORDER BY, HAVING, SELECT
- ☐ SELECT, FROM, GROUP BY, HAVING, WHERE, ORDER BY

### Question - 73

Select Statements

SCORE: 5 points

SQL

Easy

Database

Which of the following SELECT statements prints the string 56? Choose all that apply.

- ☒ SELECT SUBSTR ('123456',5) FROM DUAL ;
- ☒ SELECT SUBSTR ('123456',-2) FROM DUAL ;
- ☒ SELECT SUBSTR ('123456',5,2) FROM DUAL ;
- ☒ SELECT SUBSTR ('123456',-2,2) FROM DUAL