

EXPERIMENT 1-DDL Commands – CREATE, ALTER, DROP

```
mysql> CREATE TABLE STUDENT (  
->     RegNo INT,  
->     Name VARCHAR(15),  
->     Gender CHAR(1),  
->     DOB DATE,  
->     MobileNo BIGINT,  
->     City VARCHAR(15)  
-> );  
Query OK, 0 rows affected (0.02 sec)
```

```
mysql> DESC STUDENT;  
+-----+-----+-----+-----+-----+-----+  
| Field      | Type          | Null | Key | Default | Extra |  
+-----+-----+-----+-----+-----+-----+  
| RegNo      | int           | YES  |     | NULL    |       |  
| Name       | varchar(15)   | YES  |     | NULL    |       |  
| Gender     | char(1)       | YES  |     | NULL    |       |  
| DOB        | date          | YES  |     | NULL    |       |  
| MobileNo   | bigint        | YES  |     | NULL    |       |  
| City       | varchar(15)   | YES  |     | NULL    |       |  
+-----+-----+-----+-----+-----+-----+  
6 rows in set (0.00 sec)
```

```
mysql> CREATE TABLE FACULTY (  
->     FacNo VARCHAR(4),  
->     FacName VARCHAR(15),  
->     Gender CHAR(1),  
->     DOB DATE,  
->     DOJ DATE,  
->     MobileNo BIGINT  
-> );  
Query OK, 0 rows affected (0.03 sec)
```

```
mysql> DESC FACULTY;  
+-----+-----+-----+-----+-----+-----+  
| Field      | Type          | Null | Key | Default | Extra |  
+-----+-----+-----+-----+-----+-----+  
| FacNo      | varchar(4)    | YES  |     | NULL    |       |  
| FacName    | varchar(15)   | YES  |     | NULL    |       |  
| Gender     | char(1)       | YES  |     | NULL    |       |  
| DOB        | date          | YES  |     | NULL    |       |  
| DOJ        | date          | YES  |     | NULL    |       |  
| MobileNo   | bigint        | YES  |     | NULL    |       |  
+-----+-----+-----+-----+-----+-----+  
6 rows in set (0.00 sec)
```

```
mysql> CREATE TABLE DEPARTMENT (  
->     DeptNo VARCHAR(4),  
->     DeptName VARCHAR(15),  
->     DeptHead VARCHAR(4)  
-> );  
ERROR 1050 (42S01): Table 'department' already exists  
mysql> DESC DEPARTMENT;  
+-----+-----+-----+-----+-----+-----+  
| Field      | Type          | Null | Key | Default | Extra |  
+-----+-----+-----+-----+-----+-----+  
| DeptID     | int           | NO   | PRI | NULL    |       |  
| DeptName   | varchar(50)   | YES  |     | NULL    |       |  
+-----+-----+-----+-----+-----+-----+  
2 rows in set (0.00 sec)
```

```
mysql> CREATE TABLE COURSE (
->     CourseNo VARCHAR(3),
->     CourseDesc VARCHAR(14),
->     CourseType CHAR(1),
->     SemNo CHAR(1),
->     HallNo VARCHAR(4),
->     FacNo VARCHAR(4)
-> );
Query OK, 0 rows affected (0.03 sec)
```

```
mysql> DESC COURSE;
```

Field	Type	Null	Key	Default	Extra
CourseNo	varchar(3)	YES		NULL	
CourseDesc	varchar(14)	YES		NULL	
CourseType	char(1)	YES		NULL	
SemNo	char(1)	YES		NULL	
HallNo	varchar(4)	YES		NULL	
FacNo	varchar(4)	YES		NULL	

6 rows in set (0.00 sec)

```
mysql> ALTER TABLE FACULTY
-> ADD Dept VARCHAR(10);
Query OK, 0 rows affected (0.02 sec)
Records: 0 Duplicates: 0 Warnings: 0
```

```
mysql> DESC FACULTY;
```

Field	Type	Null	Key	Default	Extra
FacNo	varchar(4)	YES		NULL	
FacName	varchar(15)	YES		NULL	
Gender	char(1)	YES		NULL	
DOB	date	YES		NULL	
DOJ	date	YES		NULL	
MobileNo	bigint	YES		NULL	
Dept	varchar(10)	YES		NULL	

7 rows in set (0.00 sec)