```
mysql> USE college;
Database changed
mysql>
mysql> CREATE TABLE STUDENT_GROUP (
    ->     RegNo INT PRIMARY KEY,
    ->     Name VARCHAR(20),
    ->     Marks INT,
    ->     City VARCHAR(20)
    -> );
Query OK, 0 rows affected (0.02 sec)

mysql>
mysql> INSERT INTO STUDENT_GROUP VALUES
    -> (101, 'Anu', 85, 'Chennai'),
    -> (102, 'Priya', 90, 'Madurai'),
    -> (103, 'Arun', 70, 'Salem'),
    -> (104, 'Kavin', 65, 'Chennai'),
    -> (105, 'Divya', 80, 'Madurai');
Query OK, 5 rows affected (0.01 sec)
Records: 5  Duplicates: 0  Warnings: 0
```

```
mysql> SELECT City, COUNT(*) AS Total_Students
    -> FROM STUDENT_GROUP
    -> GROUP BY City;
+---------+----------------+
| City    | Total_Students |
+---------+----------------+
| Chennai |              2 |
| Madurai |              2 |
| Salem   |              1 |
+---------+----------------+
3 rows in set (0.01 sec)

mysql> SELECT City, COUNT(*) AS Total_Students
    -> FROM STUDENT_GROUP
    -> GROUP BY City
    -> HAVING COUNT(*) > 1;
+---------+----------------+
| City    | Total_Students |
+---------+----------------+
| Chennai |              2 |
| Madurai |              2 |
+---------+----------------+
2 rows in set (0.01 sec)

mysql> SELECT * FROM STUDENT_GROUP
    -> ORDER BY Marks DESC;
+-------+-------+-------+---------+
| RegNo | Name  | Marks | City    |
+-------+-------+-------+---------+
|   102 | Priya |    90 | Madurai |
|   101 | Anu   |    85 | Chennai |
|   105 | Divya |    80 | Madurai |
|   103 | Arun  |    70 | Salem   |
|   104 | Kavin |    65 | Chennai |
+-------+-------+-------+---------+
5 rows in set (0.01 sec)
```