Global Electrical Solutions BV



Badweg 28| 8401 BL/ Gorredijk T +31 (0) 513 3229701 I E info@globalelectricalsolutions.nl KVK-nummer: 72554908 BTW-nummer: NL859151244B01 Bank: NL20RAB00356500594

Datum 13-09-2024

Ouotation,

This quotation is made on request from BioSea. The scope of supply is based on the received documentation and discussions between Global Electrical Solutions and BioSea, and concerns the fabrication and delivery of one (1) By-Pass Valve Cabinet (16 PCS of Valves).

This quotation is for budgetary purposes, and free of engagement.

1 Scope of Supply BioSea valve cabinet 16 valves – delivery of components: System consists of;

- 16 Bypass valves
- 1 Transfer button

Price:

1. Materials:

Item	Description	QTY	Price each in EURO	Total Amount in Euro
1	BioSea valve cabinet 16 Bypass valves	1	€ 4.574,-	€ 4.574,-
2	Transfer Button	1	€ 340,-	€ 340,-
	Total			€ 4.914,-

NOTE

- 1. With the transfer button you will be able to transfer ballast water internally with by-pass valve(s) opened.
- 2. In the installation manual of Bio-Sea they mention that BIO-SEA control cabinet accepts three dry contact inputs (24Vdc) to receive information from the vessel valves:
 - One input for all the ship valves by-passing the system (normal operation and stripping). Any opening of by-pass valve triggers an alarm and a record on the datalog.
 - One input for all the valves involved in internal transfers between ballast tanks (no treatment required). Any opening of transfer valve triggers a record on the datalog.

One input for the ship valves involved in stripping operation. Any opening
of ship stripping valve during a stripping operation triggers an alarm and
a record on the datalog. These inputs use positive security, so, for each
input, corresponding contact should be open when at leastone of the
corresponding valves is open and close when all the corresponding valves
are closed.

Taking this instruction into account, we have quoted a 16 valve cabinet, which will use the one input on the control cabinet.

3. As Global Electrical Solution, we recommend the fail safe method. This means that a closed valve gives a closed contact to the plc. In case of a cable rupture the plc will signal an open valve, which is a fail safe. Also in case of no bypass BWT (no alarm) the system should give a closed contact to the Bio Sea installation. (also fail safe)

Offered prices are based on the following information, received:

- Email; P1482 JP88 STORK / BWTS / BIO-UV September 13th
- GSPL-P1482-PI-0007 Valve Configuration list for Bypass R.A.

Process Signal Input 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 26 27 28 29 30 31 32 33 34 35 36 36 36 36 36 36 36																																				
Granty Filling Through Sechest -Condition-3		Valve ID	Valve BV1	Valve BV2	Valve BV3	Valve BV4	Valve BVS	Valve BV6	Valve BV8	Valve BV9	Valve BV10	Valve BAV03	Valve BAV04	Valve		Valve	Valve																			
Gravity Discharges Filling Through Searcheast - Condition-2 Configuration 2 Configuration 2 Configuration 3 Configuration 3 Configuration 3 Configuration 4 Configuration 4 Configuration 4 Configuration 5 Configuration 5 Configuration 5 Configuration 5 Configuration 6 Configuration 6 Configuration 7 Configuration 7 Configuration 7 Configuration 7 Configuration 8 Configuration 9 Configuration 10 Configuration 10 Configuration 10 Configuration 10 Configuration 11 Configuration 12 Configuration 13 Configuration 14 Configuration 15 Configuration	Process	Signal Input			3	4	5	5 7	8	9	10	11	12	13	14	15	16	17	18	19	20 2	21 2	22 2	3 2	4 2	25 2	26 2	6 2	7 28	29	30	31	32	33	34 3	5 36
Configuration 3	Gravity Filling Through Seacheast -Condition-1	Configuration 1	0	0			Т		Т							П	П		Т	П				Т	Т	Т		Т							Т	
System Byposs To Overboard-Condition-1 Configuration 4 0	Gravity Filling Through Seacheast -Condition-2	Configuration 2			0	0																														
System Byposs To Overboard Condition-2 Configuration 5 0											0														\perp											
System Bypass To Overboard-Condition-3 Configuration 6 O O System Bypass To Overboard-Condition-4 Configuration 7 O O System Bypass Through Fire Pydrants-1 Configuration 8 O O O System Bypass Through Fire Pydrants-2 Configuration 9 O O O O System Bypass Through Emergency Cooling-1 Configuration 10 O O O O System Bypass Through Emergency Cooling-2 Configuration 11 O O O O	System Bypass To Overboard-Condition-1	Configuration 4								C)	0	0	0														Т							\top	
System Byposs To Overboard Condition 4 Configuration 7 0 0 System Byposs Through Fire Indiants-1 Configuration 8 0 0 0 System Byposs Through Fire Indiants-2 Configuration 9 0 0 0 System Byposs Through Emergency Cooling-1 Configuration 10 0 0 0 System Byposs Through Emergency Cooling-2 Configuration 11 0 0 0	System Bypass To Overboard-Condition-2	Configuration 5						0				0	0	0																						
System Byposs Through Fire hydronts-1 Configuration 8 O O O System Byposs Through Fire hydronts-2 Configuration 9 O O O System Byposs Through Emergency Cooling-1 Configuration 10 O O O System Byposs Through Emergency Cooling-2 Configuration 11 O O O															0																					
System Byposs Through Fire hydrants-2 Configuration 9 0 0 0 System Byposs Through Fire hydrants-2 Configuration 10 0 0 0 System Byposs Through Emergency Cooling-2 Configuration 11 0 0 0	System Bypass To Overboard-Condition-4	Configuration 7														0																				
System Bypass Through Emergency Cooling-1 Configuration 10 O O O System Bypass Through Emergency Cooling-2 Configuration 11 O O O	System Bypass Through Fire hydrants-1	Configuration 8			0		0									0																				
System Byposs Through Emergency Cooling-2 Configuration 11 0 0 0 0							- (0																					
	System Bypass Through Emergency Cooling-1	Configuration 10		0				0	0)																										
System Byposs Configuration 12 0					0				0	0)								\Box	\Box					Т										\top	
	System Bypass	Configuration 12															0																			
																				\perp																
									I												\perp	_[
																			\perp	\perp																
									\perp										\perp	\perp					\perp			\perp								
																						_												\perp T		

Any deviation from the information provided will be offered as additional work. The offer is for the delivery of 1 units

Excluded in the offer.

- Waiting time not caused by GES, waiting time will be charged on service rate.
- V.A.T.
- Costs for Class surveyor's attendance and Classification costs
- Class approval of drawings
- Commissioning of installations
- Transportation
- Other works as specified herein

Delivery time.

- Delivery time materials on stock, subject unsold,
- Estimated fabrication time 1 working week, assuming we can continue to work without interruptions after received of written Purchase Order

Payment.

- 100% After order confirmation as immediate down payment upon official PO

Shipment is EXW Gorredijk, The Netherands All prices are excluding VAT.
This offer is valet until 31 October 2024

Confidentiality

This offer remains the property of Global Electrical Solutions and may without the written permission of the owner not be multiplied, be used for third parties or be given to third parties for perusal. Confident we issue a complete offer as per your expectations and awaiting your prompt reply / order confirmation

We would be happy to explain our quotation in more detail in a personal meeting. If you have any questions about the quote, please do not hesitate to contact us

Kind regards, Global Electrical Solutions BV

Greetings Global Electrical Solutions BV

R.C.Wesseling

Offer accepted signature.

Sales Manager