

Group functions, also called multiple-row functions, return one result per group of rows processed. Multiple-row functions covered in this chapter include SUM, AVG, COUNT, MIN, and MAX. This chapter also explains using the GROUP BY clause to identify groups of records to process and the HAVING clause to restrict groups returned in the query results.

When using the GROUP BY clause, remember the following:

- If a group function is used in the SELECT clause, any single (non-aggregate) columns listed in the SELECT clause must also be listed in the GROUP BY clause.
- Columns used to group data in the GROUP BY clause don't have to be listed in the SELECT clause. They're included in the SELECT clause only to have these groups identified in the output. Column aliases can't be used in the GROUP BY clause.
- Results returned from a SELECT statement that includes a GROUP BY clause are displayed in ascending order of the columns listed in the GROUP BY clause.

To have a different sort sequence, use the ORDER BY clause. When a SELECT statement includes all three clauses, the order in which they're evaluated is as follows:

- The WHERE clause
  - The GROUP BY clause
  - The HAVING clause
- In essence, the WHERE clause filters the data before grouping, and the HAVING clause filters the groups after the grouping occurs.

## 8.1 Group by examples

```
DELETE FROM patient;
```

```
INSERT INTO patient values (111,'john','Wei','m','11-FEB-1978',25000, 'Davis','CA');
```

```
INSERT INTO patient values (114,'billy','Bob','f','05-MAY-1985',60000,'Davis','NV');
```

```
INSERT INTO patient values (115,'dove','Grime','f','04-JUN-1960',20000,'Sacramento','CA');
```

```
INSERT INTO patient values (199,'john','Dali','m','11-FEB-1978',25000, 'Davis','CA');
```

```
INSERT INTO patient values (112,'john','Smith','m','01-MAR-1981',40000, 'Davis','CA');
```

```
INSERT INTO patient values (978,'john','Doe','m','11-FEB-1978',25000,NULL,'CA');
```

```
INSERT INTO patient values (113,'jill','Crane','m','12-APR-1999',50000,'Reno','NV');
```

111	john	Wei	m	11-FEB-1978	25000	Davis	CA
114	billy	Bob	f	05-MAY-1985	60000	Davis	NV
115	dove	Grime	f	04-JUN-1960	20000	Sacramento	CA
199	john	Dali	m	11-FEB-1978	25000	Davis	CA
112	john	Smith	m	01-MAR-1981	40000	Davis	CA
978	john	Doe	m	11-FEB-1978	25000	NULL	CA
113	jill	Crane	m	12-APR-1999	50000	Reno	NV
SELECT SUM(salary) FROM patient;							
<b>Group by city</b>							
111	john	Wei	m	11-FEB-1978	25000	Davis	CA
114	billy	Bob	f	05-MAY-1985	60000	Davis	NV
199	john	Dali	m	11-FEB-1978	25000	Davis	CA
112	john	Smith	m	01-MAR-1981	40000	Davis	CA
115	dove	Grime	f	04-JUN-1960	20000	Sacramento	CA
978	john	Doe	m	11-FEB-1978	25000	NULL	CA
113	jill	Crane	m	12-APR-1999	50000	Reno	NV
SELECT city, SUM(salary) FROM patient GROUP BY city;							
<b>Group by state</b>							
111	john	Wei	m	11-FEB-1978	25000	Davis	CA
199	john	Dali	m	11-FEB-1978	25000	Davis	CA
112	john	Smith	m	01-MAR-1981	40000	Davis	CA
978	john	Doe	m	11-FEB-1978	25000	NULL	CA

**RESULT**

245000

**RESULT**

Davis            150000

Sacramento    20000

NULL            25000

Reno            50000

**RESULT**

CA            135000

115 dove Grime f 04-JUN-1960 20000 Sacramento CA	NV 110000
114 billy Bob f 05-MAY-1985 60000 Davis NV	
113 jill Crane m 12-APR-1999 50000 Reno NV	
SELECT state, SUM(salary) FROM patient GROUP BY state;	
<b><u>Group by gender</u></b>	<b><u>RESULT</u></b>
111 john Wei m 11-FEB-1978 25000 Davis CA	
199 john Dali m 11-FEB-1978 25000 Davis CA	
112 john Smith m 01-MAR-1981 40000 Davis CA	
978 john Doe m 11-FEB-1978 25000 NULL CA	m 165000
113 jill Crane m 12-APR-1999 50000 Reno NV	f 80000
114 billy Bob f 05-MAY-1985 60000 Davis NV	
115 dove Grime f 04-JUN-1960 20000 Sacramento CA	
SELECT gender, SUM(salary) FROM patient GROUP BY gender;	
<b><u>Group by city and gender</u></b>	<b><u>RESULT</u></b>
111 john Wei m 11-FEB-1978 25000 Davis CA	
199 john Dali m 11-FEB-1978 25000 Davis CA	
112 john Smith m 01-MAR-1981 40000 Davis CA	
	Davis m 90000
114 billy Bob f 05-MAY-1985 60000 Davis NV	Davis f 60000
	Sacramento f 20000
115 dove Grime f 04-JUN-1960 20000 Sacramento CA	NULL m 25000
	Reno m 50000
978 john Doe m 11-FEB-1978 25000 NULL CA	

113 jill Crane m 12-APR-1999 50000 Reno NV	
SELECT city, gender, SUM(salary) FROM patient GROUP BY city, gender;	
<b><u>Group by state and gender</u></b>	<b><u>RESULT</u></b>
111 john Wei m 11-FEB-1978 25000 Davis CA	
199 john Dali m 11-FEB-1978 25000 Davis CA	
112 john Smith m 01-MAR-1981 40000 Davis CA	
978 john Doe m 11-FEB-1978 25000 NULL CA	CA m 115000
	CA f 20000
115 dove Grime f 04-JUN-1960 20000 Sacramento CA	NV f 60000
	NV m 50000
114 billy Bob f 05-MAY-1985 60000 Davis NV	
113 jill Crane m 12-APR-1999 50000 Reno NV	
SELECT state, gender, SUM(salary) FROM patient GROUP BY state, gender;	
<b><u>Group by fname and city</u></b>	<b><u>RESULT</u></b>
111 john Wei m 11-FEB-1978 25000 Davis CA	
199 john Dali m 11-FEB-1978 25000 Davis CA	
112 john Smith m 01-MAR-1981 40000 Davis CA	
	John Davis 90000
978 john Doe m 11-FEB-1978 25000 NULL CA	John NULL 25000
	Jill Reno 60000
113 jill Crane m 12-APR-1999 50000 Reno NV	Billy Davis 60000

114 billy Bob f 05-MAY-1985 60000 Davis NV	Dove Sacramento 20000
115 dove Grime f 04-JUN-1960 20000 Sacramento CA	
SELECT fname, city, SUM(salary) FROM patient GROUP BY fname, city;	

## 8.2 SUM

The SUM function is used to calculate the total amount stored in a numeric field for a group of records. The syntax of the SUM function is SUM([( DISTINCT| ALL] n), where n is a column containing numeric data.

```
SELECT salary from patient;
```

--The result is a single number that is the summation of all the salaries.

```
SELECT SUM (salary) FROM patient;
```

--All is implied as in the above statement.

```
SELECT SUM (ALL salary) FROM patient;
```

--The result is a single number that is the summation of all the distinct salaries, which

--means it suppresses the duplicates before doing a summation.

```
SELECT SUM (DISTINCT salary) FROM patient;
```

```
SQL> SELECT salary from patient;
```

```
      SALARY
-----
      25000
      60000
      20000
      40000
      25000
```

6 rows selected.

```
SQL> --The result is a single number that is the summation of all the salaries
SQL> SELECT SUM (salary) FROM patient;
```

```
SUM(SALARY)
-----
      170000
```

```
SQL> --All is implied as in the above statement
SQL> SELECT SUM (ALL salary) FROM patient;
```

```
SUM(ALLSALARY)
-----
      170000
```

```
SQL> --The result is a single number that is the summation of all the distinct salaries which means
```

```
SQL> --it suppresses the duplicates before doing a summation
SQL> SELECT SUM (DISTINCT salary) FROM patient;
```

```
SUM(DISTINCTSALARY)
-----
      145000
```

--Error: how do we align the single summation number with all the cities?

```
SELECT city, SUM(salary) FROM patient;
```

```
SQL> --This is problematic because how do we align the single summation number with all the cities
```

```
SQL> SELECT city, SUM(salary) FROM patient;
SELECT city, SUM(salary) FROM patient
```

```
      *
ERROR at line 1:
ORA-00937: not a single-group group function
```

--Creates a grouping for each city, which means that it suppresses the duplicates in each group and --and then comes up with a summation for each group order by is the last clause.

```
SELECT city, SUM(salary) FROM patient GROUP BY city ORDER BY 1;
```

--Creates a group for each of the states and gives a summation for each state.

```
SELECT state, SUM(salary) FROM patient GROUP BY state;
```

--Creates combination of fname, city categories and provides a summation for each group.

```
SELECT fname,city, SUM(salary) FROM patient GROUP BY fname,city;
```

```

SQL> --Creates a grouping for each city which means
SQL> --that it suppresses the duplicates in each group and
SQL> --and then comes up with a summation for each group
SQL> --order by is the last clause.
SQL> SELECT city, SUM(salary) FROM patient GROUP BY city ORDER BY 1;

```

CITY	SUM(SALARY)
Davis	65000
Las Vegas	60000
Reno	20000
Sacramento	25000

```

SQL> --Creates a group for each of the states and gives a summation for each state
SQL> SELECT state, SUM(salary) FROM patient GROUP BY state;

```

STATE	SUM(SALARY)
CA	110000
NV	60000

```

SQL> --Creates combination of fname, city categories and provides a summation for each group
SQL> SELECT fname,city, SUM(salary) FROM patient GROUP BY fname,city;

```

FNAME	CITY	SUM(SALARY)
billy	Las Vegas	60000
dove	Sacramento	20000
john	Davis	65000
john	Davis	65000
jill	Reno	25000

--First the where clause filters. Then it does a grouping with the data that is left over. It --groups the different cities and then for each city group, it comes up with a summation.

```

SELECT city, SUM(salary) FROM patient WHERE UPPER(city) <> 'RENO'
GROUP BY city ORDER BY 1;

```

```

SQL> SELECT city, SUM(salary) FROM patient WHERE UPPER(city) <> 'RENO' GROUP
city ORDER BY 1;

```

CITY	SUM(SALARY)
Davis	65000
Las Vegas	60000
Sacramento	20000

--First the where clause filters. Then it does a grouping with the data that is left over. It --groups the different cities and then for each city group, it comes up with a summation.

```

SELECT city, SUM(salary) FROM patient WHERE UPPER(city) != 'RENO' or
city is NULL GROUP BY city ORDER BY 1;

```

```

SQL> --First the where clause filters. Then it does a grouping with the data that
is left over. It groups
SQL> --the different cities and for each city group it comes up with a summation

SQL> SELECT city, SUM(salary) FROM patient WHERE UPPER(city) != 'RENO' or city
is NULL GROUP BY city ORDER BY 1;

```

CITY	SUM(SALARY)
Davis	65000
Las Vegas	60000
Sacramento	20000

## 8.3 DISTINCT

The optional DISTINCT keyword instructs Oracle to include only unique numeric values in its calculation. The ALL keyword instructs Oracle to include multiple occurrences of numeric values when totaling a field. If the DISTINCT or ALL keywords aren't included when using the SUM function, Oracle assumes the ALL keyword by default and uses all the numeric values in the field when the query is executed.

```

--ALL is implied and is not needed.
SELECT SUM (ALL salary) FROM patient;

--Suppresses the duplicates and gives a summation.
SELECT SUM (DISTINCT salary) FROM patient;

--Suppresses duplicates and gives a summation for each city category.
SELECT city, SUM(DISTINCT salary) FROM patient GROUP BY city ;

--Does not suppress the duplicates for salary and gives a summation for each city category.
SELECT city, SUM(ALL salary) FROM patient GROUP BY city;

```



```

SQL> --ALL is implied and is not needed
SQL> SELECT SUM (ALL salary) FROM patient;

SUM(ALLSALARY)
-----
      170000

SQL> --Suppresses the duplicates and gives a summation
SQL> SELECT SUM (DISTINCT salary) FROM patient;

SUM(DISTINCTSALARY)
-----
      145000

SQL> --suppresses duplicates and gives a summation for each city category
SQL> SELECT city, SUM(DISTINCT salary) FROM patient GROUP BY city ;

CITY                SUM(DISTINCTSALARY)
-----
Las Vegas            25000
Davis                60000
Sacramento           65000
Reno                 20000

SQL> --Does not suppress the duplicates for salary and gives a summation for each city category
SQL> SELECT city, SUM(ALL salary) FROM patient GROUP BY city;

CITY                SUM(ALLSALARY)
-----
Las Vegas            25000
Davis                60000
Sacramento           65000
Reno                 20000

```

```

--Just like the above; however, there is an additional filtering with the having clause. It
-- includes only groups that have a sum greater than 25000.
SELECT city, SUM(ALL salary) FROM patient GROUP BY city HAVING sum(salary)>25000;

SQL> SELECT city, SUM(ALL salary) FROM patient GROUP BY city HAVING sum(salary)>
25000;

CITY                SUM(ALLSALARY)
-----
Las Vegas            60000
Davis                65000

SQL>

```

## 8.4 AVG

The AVG function calculates the average of numeric values in a specified column. The syn-tax of the AVG function is `AVG([ DISTINCT| ALL] n)`, where n is a column containing numeric data.

```
SELECT salary FROM patient;
```

```
SQL> SELECT salary FROM patient;
```

```
      SALARY
```

```
-----  
      25000  
      60000  
      20000  
      40000  
      25000
```

```
6 rows selected.
```

--Gives a single average for all the salaries.

```
SELECT AVG (salary) FROM patient;
```

--Same as above

```
SELECT AVG (ALL salary) FROM patient;
```

--Suppresses duplicates and then gives an average.

```
SELECT AVG (DISTINCT salary) FROM patient;
```

--Invalid: Does not know how to display the one single average salary with all the cities.

```
SELECT city, AVG (salary) FROM patient;
```

--Displays the average salary for each city category.

```
SELECT city, AVG (salary) FROM patient GROUP BY city ORDER BY 1;
```

```

SQL> --Gives a single average for all the salaries
SQL> SELECT AVG (salary) FROM patient;

AVG(SALARY)
-----
      34000

SQL> --Same as above
SQL> SELECT AVG (ALL salary) FROM patient;

AVG(ALLSALARY)
-----
      34000

SQL> --Suppresses duplicates and then gives an average
SQL> SELECT AVG (DISTINCT salary) FROM patient;

AVG(DISTINCTSALARY)
-----
      36250

SQL> --Invalid: Does not know how to display the one single average salary with
all the cities
SQL> SELECT city, AVG (salary) FROM patient;
SELECT city, AVG (salary) FROM patient
*
ERROR at line 1:
ORA-00937: not a single-group group function

SQL> --Displays the average salary for each city category
SQL> SELECT city, AVG (salary) FROM patient GROUP BY city ORDER BY 1;

CITY                AVG(SALARY)
-----
Davis                32500
Las Vegas            60000
Reno                 20000
Sacramento           25000

```

--First it filters the data based on the where clause. Then it takes the left over records and  
--does a grouping for each of the cities and provides an average for each grouping.

```

SELECT city, AVG (salary) FROM patient WHERE UPPER(city) <> 'RENO' GROUP BY
city ORDER BY 1;

```

--First it filters the data based on the where clause. Then it takes the left over records and  
--does a grouping for each of the cities and provides an average for each grouping. If there is a  
--city group that does not have a salary, which means that it is NULL, then it will replace it with a  
--zero. There is additional filtering using the having clause after all the grouping is done.

```

SELECT city, AVG (nvl(salary,0)) FROM patient WHERE UPPER(city) <> 'RENO'
GROUP BY city HAVING AVG(salary)>20000 ORDER BY 1;

```

```

SQL> --First it filters the data based on the where clause. Then it takes the left
over records and does a
SQL> --grouping for each of the cities and provides an average for each grouping
SQL> SELECT city, AVG (salary) FROM patient WHERE UPPER(city) <> 'RENO' GROUP BY
city ORDER BY 1;

```

CITY	AVG(SALARY)
Davis	32500
Las Vegas	60000
Sacramento	20000

```

SQL> --First it filters the data based on the where clause. Then it takes the left
over records and does a
SQL> --grouping for each of the cities and provides an average for each grouping
. If there is a city group that
SQL> --does not have a salary which means that it is null, then it will replace
it with a zero
SQL> SELECT city, AVG (nvl(salary,0)) FROM patient WHERE UPPER(city) <> 'RENO'
GROUP BY city HAVING AVG(salary)>20000 ORDER BY 1;

```

CITY	AVG(NVL(SALARY,0))
Davis	32500
Las Vegas	60000

## 8.5 COUNT

Depending on the argument used, the COUNT function can count the records having non- NULL values in a specified field or count the total records meeting a specific condition, including those containing NULL values. The syntax of the COUNT function is COUNT(\* [ DISTINCT| ALL] c), where c represents a numeric or non-numeric column.

```
SELECT fname,lname,city FROM patient;
```

--Counts the number of rows.

```
SELECT COUNT (*) FROM patient;
```

--Counts the number rows based on the contents of the city. If the city for a given row contains

--a NULL, then it will not be counted.

```
SELECT COUNT (city) FROM patient;
```

--Same as above

```
SELECT COUNT (ALL city) FROM patient;
```

--Invalid: Does not know how to display a single number with the six different cities.

```
SELECT city, COUNT (*) FROM patient;
```

```
SQL> SELECT fname,lname,city FROM patient;
```

FNAME	LNAME	CITY
john	Wei	Davis
billy	Bob	Las Vegas
dove	Grime	Sacramento
john	Smith	Davis
john	Doe	
jill	Crane	Reno

6 rows selected.

```
SQL> --Counts the number of rows
SQL> SELECT COUNT (*) FROM patient;
```

```
  COUNT(*)
-----
         6
```

```
SQL> --Counts the number rows based on the contents of the city. If the city for
a given row contains
```

```
SQL> --a null then it will not be counted
```

```
SQL> SELECT COUNT (city) FROM patient;
```

```
  COUNT(CITY)
-----
         5
```

```
SQL> --Same as above
```

```
SQL> SELECT COUNT (ALL city) FROM patient;
```

```
  COUNT(ALLCITY)
-----
         5
```

```
SQL> --Invalid: Does not know how to display a single number with the six differ
ent cities
```

```
SQL> SELECT city, COUNT (*) FROM patient;
```

```
SELECT city, COUNT (*) FROM patient
```

```
      *
```

```
ERROR at line 1:
```

```
ORA-00937: not a single-group group function
```

--Create a group for each of the different cities and do a count for each category. NULL cities are  
--excluded from the count.

```
SELECT city, COUNT (city) FROM patient GROUP BY city;
```

--Same as above but the NULLs are not excluded.

```
SELECT city, COUNT (*) FROM patient GROUP BY city;
```

--After it has come up with the count per grouping, there is an additional filtering, which includes only those  
--records where the count is greater than 1.

```
SELECT city, COUNT (*) FROM patient GROUP BY city HAVING COUNT(*) >1;
```

```

SQL> --Create a group for each of the different cities and do a count for each c
category. Null cities are excluded
SQL> --from the count
SQL> SELECT city, COUNT (city) FROM patient GROUP BY city;

```

CITY	COUNT(CITY)
	0
Las Vegas	1
Davis	2
Sacramento	1
Reno	1

```

SQL> --Same as above but the nulls are not excluded
SQL> SELECT city, COUNT (*) FROM patient GROUP BY city;

```

CITY	COUNT(*)
	1
Las Vegas	1
Davis	2
Sacramento	1
Reno	1

```

SQL> --After it has come up with the count per grouping, there is an additional
filtering which only includes
SQL> --those where the count is greater than 1.
SQL> SELECT city, COUNT (*) FROM patient GROUP BY city HAVING COUNT(*) > 1;

```

CITY	COUNT(*)
Davis	2

## 8.6 MAX

The MAX function returns the largest value stored in the specified column. The syntax of the MAX function is MAX([ DISTINCT| ALL] c), where c can represent any numeric, character, or date column.

```

SELECT salary FROM patient;

--The highest salary is displayed.
SELECT MAX (salary) FROM patient;

--same as above
SELECT MAX (ALL salary) FROM patient;

```

```
SQL> SELECT salary FROM patient;

SALARY
-----
25000
60000
20000
40000
25000

6 rows selected.

SQL> --The highest salary
SQL> SELECT MAX (salary) FROM patient;

MAX(SALARY)
-----
60000

SQL> --same as above
SQL> SELECT MAX (ALL salary) FROM patient;

MAX(ALLSALARY)
-----
60000
```

--Invalid: the highest salary is a single number and cannot be associated with all cities.

```
SELECT city, MAX (salary) FROM patient;
```

--Displays highest salary for each city.

```
SELECT city, MAX (salary) FROM patient GROUP BY city;
```

```
SQL> --Invalid: the highest salary is a single number and cannot be associated with all cities
SQL> SELECT city, MAX (salary) FROM patient;
SELECT city, MAX (salary) FROM patient
*
ERROR at line 1:
ORA-00937: not a single-group group function
```

```
SQL> -- highest salary for each city
SQL> SELECT city, MAX (salary) FROM patient GROUP BY city;

CITY                MAX(SALARY)
-----
Las Vegas           25000
Davis               60000
Sacramento         40000
Reno               20000
```

--Given the fname, city combination, display the the number of records and the highest salary

--for each of those combination categories.

```
SELECT fname, city, COUNT(*), AVG (salary), MAX(salary) FROM patient GROUP BY
fname, city;
```

--Same as above except that after the final result, do some additional filtering based on the count.

```
SELECT fname, city, COUNT(*), AVG (salary), MAX(salary) FROM patient GROUP BY
fname, city HAVING COUNT(*) > 2;
```

```

SQL> --Given the fname, city combination, display the the number of records, and
the highest salary
SQL> --for each of those combination categories
SQL> SELECT fname, city, COUNT(*), AVG (salary), MAX(salary) FROM patient GROUP
BY fname, city;

```

FNAME	CITY	COUNT(*)	AVG(SALARY)	MAX(SALARY)
billy	Las Vegas	1	60000	60000
dove	Sacramento	1	20000	20000
john	Davis	2	32500	40000
john		1	25000	25000
jill	Reno	1		

```

SQL> --Same as above except that after the final result do some additional filtering based on the count

```

```

SQL> SELECT fname, city, COUNT(*), AVG (salary), MAX(salary) FROM patient GROUP
BY fname, city HAVING COUNT(*) > 2;

```

```

no rows selected

```



## 8.7 MIN

In contrast to the MAX function, the MIN function returns the smallest value in a specified column. As with the MAX function, the MIN function works with any numeric, character, or date column. The syntax of the MIN function is MIN([ DISTINCT| ALL] c), where c represents any character, numeric, or date column. The MIN function uses the same logic as the MAX function for numeric and character data, except it returns the smallest value rather than the largest value.

```
SELECT salary FROM patient;
```

--The lowest salary is displayed.

```
SELECT MIN (salary) FROM patient;
```

--Invalid: cannot display a single number with six cities.

```
SELECT city, MIN(salary) FROM patient;
```

--Display the lowest salary for each city category and display the number of records in each group.

```
SELECT city, MIN (salary), COUNT(*) FROM patient GROUP BY city;
```

```
SQL> SELECT salary FROM patient;
```

```
      SALARY
-----
      25000
      60000
      20000
      40000
      25000
```

6 rows selected.

```
SQL> --The lowest salary
SQL> SELECT MIN (salary) FROM patient;
```

```
MIN(SALARY)
-----
      20000
```

SQL> --Invalid: cannot display a single number with six cities

```
SQL> SELECT city, MIN(salary) FROM patient;
SELECT city, MIN(salary) FROM patient
*
```

ERROR at line 1:  
ORA-00937: not a single-group group function

SQL> --the lowest salary for each city category and display the number of records in each group

```
SQL> SELECT city, MIN (salary), COUNT(*) FROM patient GROUP BY city;
```

CITY	MIN(SALARY)	COUNT(*)
	25000	1
Las Vegas	60000	1
Davis	25000	2
Sacramento	20000	1
Reno		1

--Filters with the where clause. Then given the remaining records, it groups by city and finds the  
--lowest salary for each city category. Given the result set, it only includes the ones where  
--there are more than two records for each group. The results are sorted by city.

```
SELECT city, MIN (salary) FROM patient WHERE city IS NOT NULL GROUP BY city HAVING count(*)  
>1 ORDER BY 1 DESC;
```

```
SQL> --Filters with the where clause, then given the remaining records, groups b  
y city and finds the lowest  
SQL> --salary for each city category. Given the result set, it only includes the  
ones where there are more than  
SQL> --Two records for each group. Order by city  
SQL> SELECT city, MIN (salary) FROM patient WHERE city IS NOT NULL GROUP BY cit  
y HAVING count(*) > 1 ORDER BY 1 DESC;
```

CITY	MIN(SALARY)
Davis	25000

## 8.8 Dates and group functions

--Displays oldest person, youngest person, the number of records (excludes all those that have a NULL in  
--DOB), and number of records (Suppresses duplicate DOB).

```
SELECT min(DOB), max (DOB), count(DOB), count (DISTINCT DOB) FROM patient;
```

--Invalid: Cannot apply AVG to date formats. Use months\_between to convert it into a number  
--and then do an average.

```
SELECT AVG(DOB) FROM patient;
```

--Invalid: can do a sum on date formats.

```
SELECT SUM(DOB) FROM patient;
```

```

SQL> --Oldest person, youngest person, the number of records (excludes all those
that have a null in dob),
SQL> --number of records (Suppresses duplicate dob)
SQL> SELECT min(dob), max (dob), count(dob), count (DISTINCT dob) FROM patient;

MIN(DOB)    MAX(DOB)    COUNT(DOB) COUNT(DISTINCTDOB)
-----
04-JUN-60 12-APR-99          6              5

SQL> --Invalid: Cannot apply avg to date formats. Use months_between to convert
it into a number and then
SQL> --do an average
SQL> SELECT avg(dob) FROM patient;
SELECT avg(dob) FROM patient
*
ERROR at line 1:
ORA-00932: inconsistent datatypes: expected NUMBER got DATE

SQL> --Invalid: can do a sum on date formats
SQL> SELECT SUM(dob) FROM patient;
SELECT SUM(dob) FROM patient
*
ERROR at line 1:
ORA-00932: inconsistent datatypes: expected NUMBER got DATE

```

## ✓ CHECK 8A

1. Display the count of all people who make less than 10000 for each of the different personality types.
2. Display the average age and maximum salary for each personality type. Display both the average age and personality types.
3. What is wrong with the following:
  - SELECT \* FROM patient WHERE salary > AVG(salary);
  - SELECT fname AS firstname, SUM (salary) summation FROM patient  
WHERE firstname='john'  
HAVING summation > 10000