

Catalogue Module API Specification

Platform: SalaryNeeds Backend • **Base URL:** https://salary.hinchmart.com • **Roles:** Admin, User, Worker • **Version:** 1.0.0

1. System Architecture & Hierarchy

The catalogue system implements a unified 3-tier hierarchy representing a single source of truth across all roles:

Hierarchy: Category (Tier 1) → Subcategory / Service (Tier 2) → Optional Variant (Tier 3)

Single Source of Truth: Admin manages the catalogue. Both User and Worker applications read from the **same database tables** (categories, services, variants). No duplicate records are created for User or Worker.

2. Authentication & Role Authorization

Role	Header Passed	Permissions & Access
ADMIN	X-Role: ADMIN	Full CRUD access to /api/admin/**, plus read access to all catalogue views.
USER	X-Role: USER	Read-only access to active catalogue via /api/user/**. Cannot access Admin APIs (403 Forbidden).
WORKER	X-Role: WORKER	Read-only access to active catalogue via /api/worker/**. Cannot access Admin APIs (403 Forbidden).

3. Admin Catalogue APIs (Management)

Admin endpoints allow creating, updating, activating, and deleting categories, subcategories, and variants.

POST Create Category (with Image Upload)

`https://salary.hinchmart.com/api/admin/categories`

Content-Type: multipart/form-data

Form-Data Parameters:

- name (Text, Required): Category name (e.g. Home Cleaning)
- description (Text, Optional): Category description
- amount (Number, Optional): Base amount (default 0.00)
- discount (Number, Optional): Discount value (default 0.00)
- displayOrder (Number, Optional): Sort order (default 0)
- status (Text, Optional): ACTIVE or INACTIVE
- image (File, Optional): Direct image file upload (.png, .jpg, .webp)

POST Create Subcategory (with Image Upload)

`https://salary.hinchmart.com/api/admin/subcategories`

Content-Type: multipart/form-data

Form-Data Parameters:

- categoryId (Text, Required): Parent Category UUID
- name (Text, Required): Subcategory name (e.g. Kitchen Cleaning)
- description (Text, Optional): Detailed description
- amount (Number, Required): Base price (e.g. 1500.00)
- discount (Number, Optional): Discount (e.g. 10.00)
- status (Text, Optional): ACTIVE or INACTIVE
- image (File, Optional): Subcategory image file

POST Create Optional Variant (with Image Upload)

`https://salary.hinchmart.com/api/admin/subcategories/{subcategoryId}/variants`

Content-Type: multipart/form-data

Form-Data Parameters:

- **name** (Text, Required): Variant name (e.g. 1 BHK, 2 BHK)
- **description** (Text, Optional): Specific description
- **amount** (Number, Required): Variant price (e.g. 1500.00)
- **discount** (Number, Optional): Discount value (e.g. 10.00)
- **status** (Text, Optional): ACTIVE or INACTIVE
- **image** (File, Optional): Variant image file

4. User Catalogue APIs (Customer View)

All User APIs require X-Role: USER and return only active catalogue records.

GET 1. Get Active Categories

`https://salary.hinchmart.com/api/user/categories`

```
{
  "success": true,
  "message": "Active categories retrieved successfully",
  "data": [
    {
      "id": "176d03c0-7791-44f2-96fc-f0654a2af739",
      "name": "home cleaning",
      "description": "Professional home cleaning services",
      "amount": 0.00,
      "discount": 0.00,
      "finalAmount": 0.00,
      "image": "https://salary.hinchmart.com/uploads/categories/home.jpg",
      "status": "ACTIVE",
      "isActive": true
    }
  ]
}
```

GET 2. Get Active Subcategories by Category ID

`https://salary.hinchmart.com/api/user/categories/{categoryId}/subcategories`

```
{
  "success": true,
  "message": "Active subcategories retrieved successfully",
  "data": [
    {
      "id": 10,
      "categoryId": "176d03c0-7791-44f2-96fc-f0654a2af739",
      "categoryName": "home cleaning",
      "name": "kitchen cleaning",
      "description": "Kitchen deep cleaning with oil removal",
      "amount": 1500.00,
      "discount": 10.00,
      "finalAmount": 1350.00,
      "image": "https://salary.hinchmart.com/uploads/subcategories/kitchen.jpg",
      "status": "ACTIVE",
      "isActive": true
    }
  ]
}
```

GET 3. Get Active Variants for Subcategory

<https://salary.hinchmart.com/api/user/subcategories/{subcategoryId}/variants>

```
{
  "success": true,
  "message": "Active variants retrieved successfully",
  "data": [
    {
      "id": 100,
      "subcategoryId": 10,
      "name": "1 bhk",
      "description": "Kitchen cleaning for 1 BHK",
      "amount": 1500.00,
      "discount": 10.00,
      "finalAmount": 1350.00,
      "image": "https://salary.hinchmart.com/uploads/variants/1bhk.jpg",
      "status": "ACTIVE"
    },
    {
      "id": 101,
      "subcategoryId": 10,
      "name": "2 bhk",
      "description": "Kitchen cleaning for 2 BHK",
      "amount": 2000.00,
      "discount": 10.00,
      "finalAmount": 1800.00,
      "image": "https://salary.hinchmart.com/uploads/variants/2bhk.jpg",
      "status": "ACTIVE"
    }
  ]
}
```

Note: When a subcategory has no variants, data returns empty array [].

5. Worker Catalogue APIs (Worker View)

All Worker APIs require X-RoLe: WORKER and read the identical active catalogue dataset from the same database.

Method	Endpoint	Description
GET	/api/worker/categories	Retrieve all active categories for worker partner app.
GET	/api/worker/categories/{categoryId}/subcategories	Retrieve all active subcategories under selected category.
GET	/api/worker/subcategories/{subcategoryId}	Retrieve full details of a specific subcategory.
GET	/api/worker/subcategories/{subcategoryId}/variants	Retrieve active variants (returns [] if none exist).

6. Complete Fields Dictionary

Field Name	Type	Tier	Description
id	UUID / Long	All	Primary Key identifier
name	String	All	Normalized lowercase item title
description	String	All	Service / item description
amount	Decimal	All	Base price before discount
discount	Decimal	All	Discount value (% or flat)
finalAmount	Decimal	All	Server-calculated final price
image / imageUrl	String	All	Public URL of the uploaded image
status	String	All	ACTIVE or INACTIVE
displayOrder	Integer	Category	Sorting order
categoryId	UUID	Subcategory	Foreign key to parent Category
subcategoryId	Long	Variant	Foreign key to parent Subcategory