D O O R & W I N D O W E L E V A T I O N S









[redacted]	[redacted]	SINGLE SWING DOOR WITH ALUMINUM [redacted] FIXED WINDOW & AWNING WINDOWS
DW 1	[redacted]	TYPE 1 & 3
	NUMBER OF SETS	[redacted]
	LOCATION	GF-LIVING AREA

TAG	DESCRIPTION	PVC
D 1	SPECIFICATION	TYPE 4
	NUMBER OF SETS	1
	LOCATION	T & B

TAG	DESCRIPTION	AWNING WINDOW
W 1	SPECIFICATION	TYPE 2
	NUMBER OF SETS	2
	LOCATION	GF-GUEST ROOM T & B

TAG	DESCRIPTION	AWNING & FIXED WINDOW
W 2	SPECIFICATION	TYPE 1
	NUMBER OF SETS	1
	LOCATION	GF-MAIN KITCHEN AREA

D O O R & W I N D O W S C H E D U L E

TAG	DESCRIPTION	DIMENSION(mm) WIDTH	DIMENSION(mm) HEIGHT	NO. OF PANELS	NO. OF SETS	REMARKS
[redacted]	SINGLE SWING DOOR WITH ALUMINUM [redacted]	1800	2150	3	1	[redacted], BY SUPPLIER OR MANUFACTURER
D-1	PVC DOOR	700	2150	1	1	HEAVY TRACK, , HEAVY DUTY DOOR HANDLE & LOCK, DOOR STOPPER, VERIFY SUPPLIER
W-1	AWNING WINDOW	650	650	1	1	[redacted]
W-2	AWNING & FIXED WINDOW	1600	1300	2	1	[redacted]

GENERAL NOTES

1. [redacted] AND QUANTITY PRIOR TO FABRICATION OF ALL WINDOWS.
2. REFER TO FLOOR PLANS FOR WINDOW MARKS.
3. CORRELATE WITH SPECIFICATIONS REGARDING MATERIALS AND [redacted].
4. MEASURE WINDOW WIDTH AND HEIGHT FROM THE ROOM [redacted].
5. ALL ALUMINUM WINDOWS IN CONTACT WITH CONCRETE, SHALL BE PROVIDED WITH RUBBER VINYL STRIPPING.
6. [redacted] AND INSTALLATION DRAWINGS TO BE APPROVED BY THE ARCHITECT.
7. APPLY SILICON WATER SEALANT FOR ALL EXPOSED WINDOWS.
8. PROVIDE COMPLETE WEATHER STRIPPING FOR ALL DOORS.
9. ALL ALUMINUM SECTIONS OF WINDOWS SHALL BE OF APPROVED ALUMINUM SECTIONS.
10. [redacted] (MOCK-UP) OF [redacted], FOR ARCHITECT'S APPROVAL.

WINDOW SPECS

[redacted]

USE 10MM THK. CLEAR TEMPERED GLASS ON 50MM X 100MM ALUMINUM [redacted], 50MM X 100MM ALUMINUM PERIMETER [redacted], COLOR BY ARCHITECT. COMPLETE [redacted] BY MANUFACTURER.

2-AWNING WINDOW

USE 10MM THK. CLEAR TEMPERED GLASS ON 50MM X 100MM ALUMINUM [redacted] IN POWDERCOAT FINISH. COLOR BY ARCHITECT. COMPLETE [redacted] BY MANUFACTURER.

DOORS SPECS

3-SINGLE SWING PANEL DOOR

USE SOLID WOOD PANEL DOOR OR EQUIVALENT, WITH [redacted] FROM 2"x6" [redacted], ALL SURFACES SHALL BE IN DUCO PAINT FINISH.

USE SUNKEN FLAT HEAD SCREWS FOR ATTACHMENT. USE 4 [redacted] BA2F 4 X 4 X 3mm 2BALL BEARING STAINLESS STEEL HINGES, 1 SET DL6 STUTGART CYLINDRICAL LEVERSET PRIVACY FUNCTION ANSI GRADE 1 AND 1 SET TS90 [redacted] PARALLEL ARM DOOR CLOSER BY DORMA OR EQUIVALENT.

4-SLIDING DOOR (SOLID WOOD PANEL)

USE SOLID WOOD PANEL DOOR OR EQUIVALENT, WITH [redacted] FROM 2"x6" [redacted], ALL SURFACES SHALL BE IN DUCO PAINT FINISH.

FOR ACCESORY VERIFY SUPPLIER/MANUFACTURER

REPUBLIC OF THE PHILIPPINES
DEPARTMENT OF SOCIAL WELFARE AND DEVELOPMENT
PRK. [redacted], BRGY.ZONE III,
KORONADAL CITY, SOUTH COTABATO, FO XII

PREPARED BY:
[redacted]
TECHNICAL FACILITATOR
[redacted] BY:
ENGR. [redacted]

RA 9266 SECTION 33

Drawings and specifications and other contract documents duly signed, stamped or sealed, as instruments of service, are the intellectual property and documents of the architect, whether the object for which they are made is executed or not. It shall be unlawful for any person to duplicate or make copies of said documents for use in the repetition of and for other projects or buildings, whether executed partly or in whole, without the written consent of the architect or author of said documents.

REVIEWED AND VERIFIED BY:
ENGR. ROLLY A. TEOFILO
PDO IV FOR INFRA

PROJECT TITLE:
CONSTRUCTION OF 2-UNITS ISOLATION BUIDLING (11-ROOMS)
LOCATION:
[redacted] BRGY. BUKAY PAIT, [redacted] SOUTH COTABATO

APPROVED BY:
CEZARIO JOEL C. ESPEJO
REGIONAL DIRECTOR
[redacted]

SHEET CONTENT
DOOR & WINDOW SCHEDULE

REVISIONS

MARK	DATE	

DRAWN BY :	CEB
DESIGNED BY :	
DATE :	--
CHECKED BY :	FCE

PROJECT NO.

SHEET NO.
A-500

SCALE A3 AS SHOWN
A1