

EXPERIMENT 3

(A)

You are given with the Employee schema; the task is to find the highest score for each respective department.

For eg: department D1 have the highest score as 5.28. Hence in the output, final updated score for D1 should be 5.28.

Same with the other departments i.e., D2, D3 and D4.

CODE:

```
CREATE TABLE Employee
```

```
(
```

```
    EID INT PRIMARY KEY,
```

```
    DEPT VARCHAR(10),
```

```
    SCORES DECIMAL(5,2)
```

```
);
```

```
INSERT INTO Employee (EID, DEPT, SCORES)
```

```
VALUES
```

```
(1, 'D1', 1.00),
```

```
(2, 'D1', 5.28),
```

```
(3, 'D1', 4.00),
```

```
(4, 'D2', 8.00),
```

```
(5, 'D1', 2.50),
```

```
(6, 'D2', 7.00),
```

```
(7, 'D3', 9.00),
```

```
(8, 'D4', 10.20);
```

```
update Employee as e
```

```
set scores=(
```

```

select max(scores)
from employee
where dept=E.dept
);
select * from employee;

```

	eid [PK] integer	dept character varying (10)	scores numeric (5,2)
1	1	D1	5.28
2	2	D1	5.28
3	3	D1	5.28
4	4	D2	8.00
5	5	D1	5.28
6	6	D2	8.00
7	7	D3	9.00
8	8	D4	10.20

(B) A company maintains employee salary records for different departments. The management wants to prepare a report containing employees whose salaries fall among the top three highest distinct salary values within their respective departments. If multiple employees receive the same qualifying salary, all such employees must be included in the final report. Display the department name, employee name, and salary for every qualifying employee.

CODE:

```

SELECT
    D.NAME AS DEPARTMENT,
    E.NAME AS EMPLOYEE,
    E.SALARY AS SALARY
FROM
    EMPLOYEE AS E
JOIN
    DEPARTMENT AS D
ON
    E.departmentId = D.ID

```

WHERE

(

SELECT COUNT(DISTINCT E2.SALARY)

FROM EMPLOYEE AS E2

WHERE E2.departmentId = E.departmentId

AND

E2.SALARY > E.SALARY

) < 3

ORDER BY D.NAME;

	department character varying (50) 🔒	employee character varying (50) 🔒	salary integer 🔒
1	IT	Joe	85000
2	IT	Max	90000
3	IT	Randy	85000
4	IT	Will	70000
5	Sales	Henry	80000
6	Sales	Sam	60000

(C) SALES ANALYSIS PART 1

A company maintains records of products sold by different salespersons. The management wants to prepare a sales performance report by identifying the salesperson(s) who generated the highest overall sales revenue. If multiple salespersons have the same highest total sales amount, all of them must be included in the final report. Return the seller ID(s) satisfying this condition.

CODE:

SELECT SELLER_ID

FROM ORDERS

GROUP BY SELLER_ID

HAVING SUM(AMOUNT) =

(

SELECT MAX(MAX_AMT)

FROM

24BAI70068

```
(  
SELECT SELLER_ID, SUM(AMOUNT) AS MAX_AMT  
FROM ORDERS  
GROUP BY SELLER_ID  
)  
)
```

	seller_id integer	
1		3