

**Alberto Andrés Valdés González.**

**Degree:** Mathematical Engineer.

**Work position:** ML-Engineer.

**Mail:** [anvaldes@uc.cl](mailto:anvaldes@uc.cl)/[alberto.valdes.gonzalez.96@gmail.com](mailto:alberto.valdes.gonzalez.96@gmail.com)


**Location:** Santiago, Chile.

---

## Oversampling


---

**Step 0:** We have imbalanced datasets.




---


**Step 1:** We take the bigger dataset and we going to iterate with the other datasets.




**Step 2:** Repeat and sample the smaller dataset till get the same size of the bigger dataset.




**Step 3:** We iterate with the other dataset.



**Step 4:** Repeat and sample the smaller dataset till get the same size of the bigger dataset.




**Step 5:** We finally have the final datasets.




# Undersampling

---


**Step 0:** We have imbalanced datasets.




**Step 1:** We take the smaller dataset and we going to iterate with the other datasets.




**Step 2:** Sample the bigger dataset till get the same size of the smaller dataset.




**Step 3:** We iterate with the other dataset.



**Step 4:** Sample the bigger dataset till get the same size of the smaller dataset.



**Step 5:** We finally have the final datasets.



# SMOTE

---

We can use this method only for structured data and we only have to apply the same strategy of **Oversampling**.

---