

AOS-CX 10.13 Quality of Service Guide

4100i, 6000, 6100 Switch Series



Hewlett Packard
Enterprise

Published: November 2023

Version: 1

Copyright Information

© Copyright 2024 Hewlett Packard Enterprise Development LP.

This product includes code licensed under certain open source licenses which require source compliance. The corresponding source for these components is available upon request. This offer is valid to anyone in receipt of this information and shall expire three years following the date of the final distribution of this product version by Hewlett Packard Enterprise Company. To obtain such source code, please check if the code is available in the HPE Software Center at <https://myenterpriselicense.hpe.com/cwp-ui/software> but, if not, send a written request for specific software version and product for which you want the open source code. Along with the request, please send a check or money order in the amount of US \$10.00 to:

Hewlett Packard Enterprise Company
Attn: General Counsel
WW Corporate Headquarters
1701 E Mossy Oaks Rd Spring, TX 77389
United States of America.



Notices

The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Confidential computer software. Valid license from Hewlett Packard Enterprise required for possession, use, or copying. Consistent with FAR 12.211 and 12.212, Commercial Computer Software, Computer Software Documentation, and Technical Data for Commercial Items are licensed to the U.S. Government under vendor's standard commercial license.

Links to third-party websites take you outside the Hewlett Packard Enterprise website. Hewlett Packard Enterprise has no control over and is not responsible for information outside the Hewlett Packard Enterprise website.

Acknowledgments

Intel®, Itanium®, Optane™, Pentium®, Xeon®, Intel Inside®, and the Intel Inside logo are trademarks of Intel Corporation in the U.S. and other countries.

Microsoft® and Windows® are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

Adobe® and Acrobat® are trademarks of Adobe Systems Incorporated.

Java® and Oracle® are registered trademarks of Oracle and/or its affiliates.

UNIX® is a registered trademark of The Open Group.

All third-party marks are property of their respective owners.

Contents

About this document	7
Applicable products	7
Latest version available online	7
Command syntax notation conventions	7
About the examples	8
Identifying switch ports and interfaces	8
QoS overview	10
End-to-end QoS behavior	10
Best effort service	10
Class of Service	10
Differentiated services	11
QoS on the switch	12
QoS trust	14
Dynamic QoS trust mode	15
Port rate limiting	15
Queue profiles	16
Schedule profiles	16
Egress queue shaping	17
Terms	17
QoS configuration	19
Configuring QoS	19
Configuring expedited forwarding for VoIP traffic	20
Configuring rate limiting	22
Configuring egress queue shaping	23
Configuring threshold profiles	24
Supporting Ethernet 802.1D Class of Service	24
Monitoring queue operation	25
QoS commands	27
apply qos	27
map queue	29
min-bandwidth	30
name queue	31
qos cos	32
qos dscp	33
qos dscp-map	34
qos queue-profile	36
qos schedule-profile	37
qos threshold-profile	39
qos trust	40
queue action	42
rate-limit	43
show interface queues	46
show interface qos	47
show qos dscp-map	49
show qos queue-profile	50
show qos schedule-profile	51

show qos threshold-profile	52
show qos trust	53
strict queue	54

Support and Other Resources 57

Accessing Aruba Support	57
Accessing Updates	58
Aruba Support Portal	58
My Networking	58
Warranty Information	58
Regulatory Information	58
Documentation Feedback	59

This document describes features of the AOS-CX network operating system. It is intended for administrators responsible for installing, configuring, and managing Aruba switches on a network.

Applicable products

This document applies to the following products:

- Aruba 4100i Switch Series (JL817A, JL818A)
- Aruba 6000 Switch Series (R8N85A, R8N86A, R8N87A, R8N88A, R8N89A, R9Y03A)
- Aruba 6100 Switch Series (JL675A, JL676A, JL677A, JL678A, JL679A)

Latest version available online

Updates to this document can occur after initial publication. For the latest versions of product documentation, see the links provided in [Support and Other Resources](#).

Command syntax notation conventions

Convention	Usage
<code>example-text</code>	Identifies commands and their options and operands, code examples, filenames, pathnames, and output displayed in a command window. Items that appear like the example text in the previous column are to be entered exactly as shown and are required unless enclosed in brackets ([]).
example-text	In code and screen examples, indicates text entered by a user.
Any of the following: ■ <code><example-text></code> ■ <code><example-text></code> ■ <i>example-text</i> ■ <i>example-text</i>	Identifies a placeholder—such as a parameter or a variable—that you must substitute with an actual value in a command or in code: ■ For output formats where italic text cannot be displayed, variables are enclosed in angle brackets (<code>< ></code>). Substitute the text—including the enclosing angle brackets—with an actual value. ■ For output formats where italic text can be displayed, variables might or might not be enclosed in angle brackets. Substitute the text including the enclosing angle brackets, if any, with an actual value.
	Vertical bar. A logical OR that separates multiple items from which you can choose only one. Any spaces that are on either side of the vertical bar are included for readability and are not a required part of the command syntax.

Convention	Usage
{ }	Braces. Indicates that at least one of the enclosed items is required.
[]	Brackets. Indicates that the enclosed item or items are optional.
... or ...	Ellipsis: ■ In code and screen examples, a vertical or horizontal ellipsis indicates an omission of information. ■ In syntax using brackets and braces, an ellipsis indicates items that can be repeated. When an item followed by ellipses is enclosed in brackets, zero or more items can be specified.

About the examples

Examples in this document are representative and might not match your particular switch or environment.

The slot and port numbers in this document are for illustration only and might be unavailable on your switch.

Understanding the CLI prompts

When illustrating the prompts in the command line interface (CLI), this document uses the generic term **switch**, instead of the host name of the switch. For example:

```
switch>
```

The CLI prompt indicates the current command context. For example:

```
switch>
```

Indicates the operator command context.

```
switch#
```

Indicates the manager command context.

switch(CONTEXT-NAME)#

Indicates the configuration context for a feature. For example:

```
switch(config-if) #
```

Identifies the **interface** context.

Variable information in CLI prompts

In certain configuration contexts, the prompt may include variable information. For example, when in the VLAN configuration context, a VLAN number appears in the prompt:

```
switch(config-vlan-100) #
```

When referring to this context, this document uses the syntax:

```
switch(config-vlan-<VLAN-ID>) #
```

Where <VLAN-ID> is a variable representing the VLAN number.

Identifying switch ports and interfaces

Physical ports on the switch and their corresponding logical software interfaces are identified using the format:

```
member/slot/port
```

On the 4100i Switch Series

- *member*: Always 1. VSF is not supported on this switch.
- *slot*: Always 1. This is not a modular switch, so there are no slots.
- *port*: Physical number of a port on the switch.

For example, the logical interface **1/1/4** in software is associated with physical port 4 on the switch.

On the 6000 and 6100 Switch Series

- *member*: Always 1. VSF is not supported on this switch.
- *slot*: Always 1. This is not a modular switch, so there are no slots.
- *port*: Physical number of a port on the switch.

For example, the logical interface **1/1/4** in software is associated with physical port 4 on the switch.

Quality of Service (QoS) enables network administrators to customize how different types of traffic are serviced on a network, taking into account the unique characteristics of each traffic type and its importance within an organization's infrastructure. QoS ensures uniform and efficient traffic handling, keeping the most important traffic moving at an acceptable speed, regardless of current bandwidth usage. It also provides methods for administrators to control the priority settings of inbound traffic arriving at each network device.

End-to-end QoS behavior

The QoS settings on each network device must be aligned to achieve the desired end-to-end QoS behavior for a network. Three service types can be used to categorize and prioritize network traffic:

- Best Effort Service
- Ethernet Class of Service (CoS)
- Internet Differentiated Services (DiffServ)

For a network as a whole, it is best to select one service type to use as the primary end-to-end behavior, and then use the other two service types as needed.

Best effort service

This is the simplest service type. All traffic is treated equally in a first-come, first-served manner. If the traffic load is low in relation to the capacity of the network links, then there is no need for the administrative complexity and costs of maintaining a more complex end-to-end policy. This is sometimes called over-provisioning, as all link speeds are much higher than peak loads on the network.

Class of Service

Class of Service (CoS) is a method for classifying network traffic at layer 2 by marking 802.1Q VLAN Ethernet frames with one of eight service classes.

CoS	Traffic type	Example protocols
7	Network Control	STP, PVST
6	Internetwork Control	BGP, OSPF, PIM
5	Voice (<10ms latency)	VoIP(UDP)
4	Video (<100ms latency)	RTP
3	Critical Applications	SQL RPC, SNMP

CoS	Traffic type	Example protocols
2	Excellent Effort	NFS, SMB
0	Best Effort	HTTP, TELNET
1	Background	SMTP, IMAP

CoS 1 is deliberately set as the lowest CoS. This enables a traffic service level below the default (best effort) traffic level to be specified.

The 3-bit Priority Code Point (PCP) field within the 16-bit Ethernet VLAN tag is used to mark the CoS.




Differentiated services

Differentiated services (DiffServ) is a method for classifying network traffic at layer 3 by marking packets with one of 64 different service classes. Services classes are identified by the Differentiated services Code Point (DSCP) value. Some common DSCP values are:

DSCP	Name	Service class	RFC
48	CS6	Network Control	2474
46	EF	Telephony	3246
40	CS5	Signaling	2474
34, 36, 38	AF41, AF42, AF43	Multimedia Conferencing	2597
32	CS4	Real-Time Interactive	2474
26, 28, 30	AF31, AF32, AF33	Multimedia Streaming	2597
24	CS3	Broadcast Video	2474
18, 20, 22	AF21, AF22, AF23	Low-Latency Data	2597
16	CS2	OAM	2474
00	CS0,BE,DF	Best Effort	2474
10, 12, 14	AF11, AF12, AF13	Bulk Data	2597
08	CS1	Low-Priority Data	3662

DSCP CS1 (08) CoS 1 is deliberately set as the lowest priority. This enables a traffic service level below the standard (best effort or default forwarding) level to be specified.

The DSCP value is carried within the IPv4 DSCP field or the upper 6-bits of the 8-bit IPv6 Traffic Class (TC) field.



QoS on the switch

There are five key stages a packet passes through when traversing a switch: ingress, prioritization, destination determination, egress queuing, and transmission.




Switches with at least 52 ports will experience negative performance if a flood occurs where at least 42 ports are members of the same VLAN and all 52 ports have QoS rules applied to them.

Ingress	Prioritization	Classification	Queueing	Transmission
Packets arrive at switch interface (port).	An initial cos value is assigned to the packet based on VLAN CoS or IP DSCP.	Packets cos value and code points can be remarked, and rates policed, based on many packet header fields. <i>(see ACL & Policy Guide)</i>	Packets are queued based on the destination interface and cos value of the packet.	A scheduler defines the order in which packets are selected from queues to be transmitted from the interface.
rate-limit Rate limiting can control ingress flow by packet type: broadcast, multicast, unknown-unicast, or ICMP.	qos trust {cos dscp none} Assigns which packet values are used to determine initial local-priority either globally for all interfaces, or to specific interface(s). qos dscp-map Defines how IP DSCP values are mapped to cos values. qos cos Remarks egress CoS value. qos dscp Remarks egress DSCP value.	class {ip ipv6 mac} NAME match TERMS [count] ignore TERMS [count] Creates an ordered list of rules to identify packets to match the class. policy NAME class NAME ACTIONS Creates an ordered list of classes to which traffic is evaluated, and the actions to be taken on matching packets: remarking, policing etc apply policy NAME Assigns the policy to evaluate all traffic inbound or outbound globally, or on specific interfaces or VLANs.	qos queue-profile Creates a profile that defines transmit queues. map queue Assigns a cos value to a queue. Packets with a matching cos value are placed in the queue. name queue Assigns a name to a queue. apply qos Assigns queue, schedule, or threshold profiles globally to all interfaces, or schedule or threshold profiles to a specific interface(s).	qos schedule-profile Creates a profile that defines the order in which packets are selected from the queues for transmission. strict queue Assigns the strict priority algorithm, with optional max-bandwidth, to a queue. min-bandwidth queue Assigns the guaranteed minimum bandwidth algorithm to a queue. qos shape Assigns the maximum rate for traffic to be transmitted by the interface.

Ingress	Prioritization	Classification	Queueing	Transmission
Packets arrive at switch interface (port).	An initial cos value is assigned to the packet based on VLAN CoS or IP DSCP.	Packets local-priority and code points can be remarked, and rates policed, based on many packet header fields. (see <i>ACL & Policy Guide</i>)	Packets are queued based on the destination interface and cos of the packet.	A scheduler defines the order in which packets are selected from queues to be transmitted from the interface.
	show int IFNAME qos Displays all the QoS settings configured on an interface: - Profiles - Rate-limits - CoS or DSCP remarks - Egress shape - Trust show qos dscp-map Displays the content of the DSCP Map table. show qos trust Display the current default trust mode.	show class {ip ipv6 mac} Displays the ordered list of the match and ignore statements in the class. show policy Displays the order list of classes in the policy. show policy hitcounts Displays the ordered list of classes in the policy. For each class the number of times that each match or ignore statement in the class matched a packet.	show int IFNAME queues Displays the per-queue counts of packets transmitted, packets dropped, and bytes transmitted. show qos queue-profile Displays the definition of queue profiles.	show qos schedule-profile Displays the definition of schedule profiles.

The following diagram shows how different packets might traverse a switch. It also shows how QoS configuration settings apply at each stage.



QoS trust

Traffic priorities for networks can be carried in VLAN tags using the CoS Priority Code Point (PCP), or in IP packet headers using the Differentiated Services Code Point (DSCP). Whether these priorities affect how traffic is serviced depends on how the QoS trust mode is configured on the switch. The QoS trust mode specifies how the switch assigns values to ingress packets and can be set globally for all interfaces or individually for each interface. By default the trust mode is set to `cos`, meaning the existing QoS information in the packet will be trusted. The priority values of DSCP packets are mapped to corresponding CoS values. If the trust mode is set to `none` the CoS value in the incoming packet will be marked as zero.


For example:

When QoS trust mode = CoS



DSCP Map

When QoS trust mode = DSCP



When QoS trust mode = None



Dynamic QoS trust mode

The device profile feature can dynamically set the QoS trust mode on an interface based on the LLDP information exchanged with a link partner. The device profile's trust mode temporarily overrides the static trust mode configured for an interface. The override remains in place as long as that link partner is connected and its link state is **up**. Use command `show interface IFNAME qos` to view the current QoS trust mode for an interface.

Port rate limiting

Port rate limiting helps control undesirable traffic. Its purpose is to allow enough unicast, broadcast, multicast, and ICMP traffic for the network to function properly, while preventing flooding and traffic storms.

Some amount of each traffic type is required for normal network operation. For example, broadcast packets may include ARP and DHCP traffic. Video streams and certain types of network protocol packets are multicast traffic. Unknown-unicast packets may be intended for devices whose addresses have temporarily aged out of network forwarding caches. Configuring rate limits can help provide balance between necessary and flooded traffic.

The amount of permitted traffic (the rate limit) can be specified in kilobits-per-second (kbps) or as a percentage of link bandwidth (percent).

Please note that rate limits are enforced separately on each individual member of a LAG, not on the LAG as a whole. When limits are in kilobits-per-second (kbps), larger limits may be needed on high speed ports in order to allow normal network functionality. Conversely, limits configured as a percentage of link bandwidth may result in too much undesired traffic on high- speed ports.

Queue profiles

A queue profile defines the queues that are associated with an interface to control the transmission of packets. Each profile supports up to eight queues, numbered 0 to 7. The larger the queue number, the higher its priority during transmission scheduling. Packets are assigned to a queue based on their local priority value (0 to 7). A queue profile must map all eight local priority values to whatever queues are being used on the switch, and a schedule profile must specify the configuration for those same queues. A queue without a local priority value assigned to it is not used to store packets. Packets are assigned to the queue based on CoS value. The queue profile defines queue number to CoS mapping. The `factory-default` map cross maps the 0 and 1 values.

```
switch# show qos queue-profile factory-default
queue_num cos          name
-----
0          1          Scavenger_and_backup_data
1          0
2          2
3          3
4          4
5          5
6          6
7          7
```

Commonly used commands for working with QoS queues are as follows:

- `qos queue-profile`: Creates an empty queue-profile and enters the profile configuration context.
- `name queue`: Assigns a descriptive name to a queue.
- `map queue`: Maps queue to CoS.
- `apply qos queue-profile`: Applies a queue-profile globally to all interfaces.

Schedule profiles

A schedule profile determines the order in which queues are selected for transmission, and the amount of service available for each queue. A schedule profile must be configured on every interface at all times. A schedule profile can be applied globally to all interfaces, or only to specific interfaces. The switch described in this guide supports Guaranteed Minimum Bandwidth (GMB), Strict, and Strict EQS scheduling.

The switch described in this guide supports 8 queues.

```
switch# show qos schedule-profile
profile_status profile_name
-----
applied        factory-default
complete       strict
```



```
switch# show qos schedule-profile factory-default
queue_num algorithm      percent max-bandwidth_kbps
-----
0          min-bandwidth  2
1          min-bandwidth  3
2          min-bandwidth 30
3          min-bandwidth 10
4          min-bandwidth 10
5          min-bandwidth 10
6          min-bandwidth 15
7          min-bandwidth 20
```

Egress queue shaping

Egress queue shaping limits the amount of traffic transmitted per strict output and guaranteed minimum bandwidth queues. The buffer associated with each egress queue stores excess traffic to absorb bursts and smooths the output rate. For example, an administrator might limit strict-priority or min-bandwidth queue traffic to prevent low-priority queue starvation in the event that a device inappropriately sends too many higher-priority packets.

Egress queue shaping can be configured on an Ethernet port or on a link aggregation group (LAG). To configure egress queue shaping, define a schedule profile with the strict priority algorithm assigned to each queue.

Terms

Class

For networking, a set of packets sharing a common characteristic. For example, all IPv4 packets.

Code point

The name of a packet header field, or the value carried within a packet header field:

- Example 1: Priority code point (PCP) is the name of a field in the IEEE 802.1Q VLAN tag.
- Example 2: Differentiated services code point (DSCP) is the name of a field carried within the DS field of an IP packet header.

Class of service (CoS)

A 3-bit value used to mark packets with one of eight classes (levels of priority). It is carried within the priority code point (PCP) field of the IEEE 802.1Q VLAN tag.

Differentiated services code point (DSCP)

A 6-bit value used to mark packets for different per-hop behavior as originally defined by IETF RFC 2474. It is carried within the differentiated services (DS) field of the IPv4 or IPv6 header.

Metadata

Information labels associated with each packet in the switch, separate from the packet headers and data. These labels are used by the switch in its handling of the packet. For example: arrival port, egress port, VLAN membership, and local priority.

Priority code point (PCP)

The name of a 3-bit field in the IEEE 802.1Q VLAN tag. It carries the CoS value to mark a packet with one of eight classes (priority levels).

Quality of service (QoS)

General term used when describing or measuring performance. For networking, it means how different classes of packets are treated when traversing a network or device.

Traffic class (TC)

General term for a set of packets sharing a common characteristic. It used to be the name of an 8-bit field in the IPv6 header originally defined by IETF RFC 2460. This field name was changed to differentiated services by IETF RFC 2474.

Type of service (ToS)

General term when there are different levels of treatment (fare class). It used to be the name of an 8-bit field in the IPv4 header originally defined by IETF RFC 791. This field name was changed to differentiated services by IETF RFC 2474.

Configuring QoS

Procedure

1. Configure how values are assigned to ingress packets with the commands `qos dscp-map`, and `qos trust`.
2. Optionally, add a rate limit for ingress traffic on one or more interfaces with the command `rate-limit`.
3. If you do not want to use the default QoS queue profile for queue mapping, create one or more custom queue profiles with the command `qos queue-profile`. For each queue in a custom queue profile:
 - a. Assign a CoS value mapping with the command `map queue`.
 - b. Optionally, define a descriptive name with the command `name queue`. All queues must be mapped to a CoS value, and the queues selected for use must be in contiguous order starting at 0.
4. If you do not want to use the default QoS schedule profile to determine the order in which queues are selected to transmit a packet, create one or more custom schedule profiles with the command `qos schedule-profile`. For each queue in a custom schedule queue profile, define scheduling priority with the commands `strict queue` and `min-bandwidth`.
5. Optionally for strict queues, configure egress queue shaping to limit egress bandwidth on an interface to a value that is less than its line rate. Use the `max-bandwidth` parameter of the `strict queue` command.
6. Activate QoS settings with the command `apply qos`. This command lets you apply a queue profile and schedule profile globally to all interfaces, or a schedule profile override to individual interfaces.
7. View QoS configuration settings with the provided `show` commands.

Examples

The following example creates a queue profile named Q1 and assigns queue to CoS value mapping:

Queue	CoS Value
0	0
1	1
2	2
3	3

Queue	CoS Value
4	4
5	5
6	6
7	7

Creates a schedule profile named S1 and assigns minimum bandwidth for each queue with a corresponding percentage value:

Queue	Minimum bandwidth (percentage)
0	5
1	5
2	10
3	10
4	20
5	20
6	10
7	20

Applies **Q1** and **S1** to all interfaces that do not have a QoS override applied.

```
switch(config)# qos trust cos
switch(config)# qos queue-profile Q1
switch(config-queue)# map queue 0 cos 0
switch(config-queue)# map queue 1 cos 1
switch(config-queue)# map queue 2 cos 2
switch(config-queue)# map queue 3 cos 3
switch(config-queue)# map queue 4 cos 4
switch(config-queue)# map queue 5 cos 5
switch(config-queue)# map queue 6 cos 6
switch(config-queue)# map queue 7 cos 7
switch(config)# qos schedule-profile S1
switch(config-schedule)# min-bandwidth queue 0 percent 5
switch(config-schedule)# min-bandwidth queue 1 percent 5
switch(config-schedule)# min-bandwidth queue 2 percent 10
switch(config-schedule)# min-bandwidth queue 3 percent 10
switch(config-schedule)# min-bandwidth queue 4 percent 20
switch(config-schedule)# min-bandwidth queue 5 percent 20
switch(config-schedule)# min-bandwidth queue 6 percent 10
switch(config-schedule)# min-bandwidth queue 7 percent 20
switch(config-schedule)# apply qos queue-profile Q1 schedule-profile S1
```

Configuring expedited forwarding for VoIP traffic

Voice over IP (VoIP) traffic is delay and jitter sensitive. For optimum transmission of VoIP traffic, dwell time in network devices must be kept to a minimum and all network devices in the data path must have identical per-hop behaviors. To configure a dedicated queue on the switch to handle VoIP traffic with priority service before all other queues, follow these steps.

Prerequisites

This scenario assumes that VoIP packets are uniquely identified using DiffServ code point 46, Expedited Forwarding (EF).

Procedure

1. Map DSCP EF packets exclusively to CoS value 6. The default DSCP map has eight code points (40 through 47), that are mapped to CoS value 5. To reserve CoS value 6 for VoIP traffic, the other code points must be reassigned. In this scenario, CoS value 6 is used for all reassignments, including for code point 40, Call Signaling protocol (CS5).

```
switch(config)# qos dscp-map 40 cos 6 name CS5
switch(config)# qos dscp-map 41 cos 6
switch(config)# qos dscp-map 42 cos 6
switch(config)# qos dscp-map 43 cos 6
switch(config)# qos dscp-map 44 cos 6
switch(config)# qos dscp-map 45 cos 6
```

2. Queue 7 is the highest priority queue, so for best throughput, create a queue profile that maps CoS to queue 7.

```
switch(config)# qos queue-profile ef_priority
switch(config-queue)# name queue 7 Voice_Priority_Queue
switch(config-queue)# map queue 7 cos 5
switch(config-queue)# map queue 6 cos 7
switch(config-queue)# map queue 5 cos 6
switch(config-queue)# map queue 4 cos 4
switch(config-queue)# map queue 3 cos 3
switch(config-queue)# map queue 2 cos 2
switch(config-queue)# map queue 1 cos 1
switch(config-queue)# map queue 0 cos 0
```

3. Create a schedule profile that services queue 7 using strict priority (SP), and the remaining queues with minimum bandwidth. This scenario defines queue 7 as strict and gives queues 0-6 an equal minimum bandwidth.

```
switch(config)# qos schedule-profile voip
switch(config-schedule)# strict queue 7
switch(config-schedule)# min-bandwidth queue 6 percent 10
switch(config-schedule)# min-bandwidth queue 5 percent 10
switch(config-schedule)# min-bandwidth queue 4 percent 10
switch(config-schedule)# min-bandwidth queue 3 percent 10
switch(config-schedule)# min-bandwidth queue 2 percent 10
switch(config-schedule)# min-bandwidth queue 1 percent 10
switch(config-schedule)# min-bandwidth queue 0 percent 10
```

4. Apply the profiles to all interfaces.


```
switch(config)# apply qos queue-profile ef_priority schedule-profile voip
```

5. Configure DSCP trust mode on all ports

```
switch(config)# qos trust dscp
```

Configuring rate limiting

This scenario illustrates how to use rate limiting to manage the traffic from various devices connected to a switch. The physical topology of the network looks like this:



A certain amount of broadcast traffic is necessary to maintain healthy network operation, particularly from routers and across service boundaries. In this scenario, both the service cloud and the router connections limit this traffic to 1 Gbps. The server has a smaller limit, as it does not require as much network protocol traffic as the service cloud and router.

A multicast server needs to be able to stream multicast traffic to clients, so a multicast rate limit may not be helpful. A computer, however, should not be generating large amounts of multicast traffic (it may be receiving streams, but typically not sending them). In this example, the computer is configured with a multicast rate limit to prevent malicious traffic from taking up network bandwidth.

Finally, while the service cloud and router may need to send traffic for unknown unicast addresses to resolve address forwarding, the server and computer should send very little of this type of traffic. Rate limiting unknown unicast traffic on those two devices enforces that.

Procedure

1. Configure broadcast and multicast rate limiting for the service cloud connection.

```
switch# config  
switch(config)# interface 1/1/1  
switch(config-if)# rate-limit broadcast 1000000 kbps  
switch(config-if)# rate-limit multicast 2000000 kbps  
switch(config-if)# exit
```

2. Configure broadcast rate limiting for the router connection.

```
switch(config-if) # interface 1/1/2
switch(config-if) # rate-limit broadcast 1000000 kbps
switch(config-if) # exit
```

3. Configure broadcast rate limiting for the server connection.

```
switch(config-if) # interface 1/1/5
switch(config-if) # rate-limit broadcast 200000 kbps
switch(config-if) # exit
```

4. Configure broadcast, and multicast rate limiting for the computer connection.

```
switch(config-if) # interface 1/1/10
switch(config-if) # rate-limit broadcast 1000 kbps
switch(config-if) # rate-limit multicast 500 kbps
```

Configuring egress queue shaping

This example shows how to apply egress queue shaping to an interface. First, a schedule profile is created that has per-queue bandwidth limits set on all queues with **strict** as the scheduling algorithm. Next, this profile is applied to an interface or LAG.

The following example creates a schedule profile named **EQSExample**, which services all queues using **strict** priority. This profile configures queues 1, 4, and 7 with a bandwidth limit of 10 Gbps, 20 Gbps, and 30 Gbps respectively. The **apply qos schedule-profile** command is then used to apply the **EQSExample** profile to interface **1/1/1**. The actual bandwidth configured on an interface can be found by using the **show interface <IF-NAME> qos** command.

```
switch(config) # qos schedule-profile EQSExample
switch(config-schedule) # strict queue 0
switch(config-schedule) # strict queue 1 max-bandwidth 10000000 kbps
switch(config-schedule) # strict queue 2
switch(config-schedule) # strict queue 3
switch(config-schedule) # strict queue 4 max-bandwidth 20000000 kbps
switch(config-schedule) # strict queue 5
switch(config-schedule) # strict queue 6
switch(config-schedule) # strict queue 7 max-bandwidth 30000000 kbps
switch(config-schedule) # exit
switch(config) # interface 1/1/1
switch(config-if) # apply qos schedule-profile EQSExample
```

The following example creates a schedule profile named **EQSExample** which services all queues using **strict** priority. This profile configures queues 1, 4 and 7 with a bandwidth limit of 10%, 20%, and 30% of link bandwidth respectively. The **apply qos schedule-profile** command is then used to apply the **EQSExample** profile to the port. The actual burst and bandwidth configured on an interface can be found by using the **show interface <IF-NAME> qos** command.

```
(config) # qos schedule-profile EQSExample
(config-schedule) # strict queue 0
```

```
(config-schedule)# strict queue 1 max-bandwidth 10 percent
(config-schedule)# strict queue 2
(config-schedule)# strict queue 3
(config-schedule)# strict queue 4 max-bandwidth 20 percent
(config-schedule)# strict queue 5
(config-schedule)# strict queue 6
(config-schedule)# strict queue 7 max-bandwidth 30 percent
```

Configuring threshold profiles

The threshold profile is an optional configuration that specifies a per-packet action to be taken for each port queue when the queue utilization reaches or exceeds the configured threshold. The per-queue configuration within the threshold profile is optional, which means any number of queues may be configured. An unconfigured queue means that no threshold action behavior will occur. Also, an empty threshold profile is valid and can be applied.

Use the `apply qos threshold-profile <THRESHOLD-NAME>` command in the global context to configure all ports to use the profile, or in the interface context to configure the interface to use the profile. No threshold profiles are created or configured by default.

In an environment where congestion management features are required in order to reduce latency and responsive transport protocols are in use, ECN can be configured on queues carrying delay-sensitive traffic. The desired result is that a network device's port-queue utilization is actively managed, resulting in ECN-capable transport (ECT) packets being Congestion Encountered (CE) marked when queue utilization reaches or exceeds a configured threshold.

Procedure

Supporting Ethernet 802.1D Class of Service

IEEE 802.1Q is the most current Ethernet standard for Class of Service (CoS). It superseded an earlier standard, 802.1D, in 2005. IEEE 802.1Q slightly changed the ordering of the classes of service from its predecessor IEEE 802.1D for CoS 2 and CoS 0:

CoS 802.1Q	CoS 802.1D
7 Network Control	7 Network Control
6 Internetwork Control	6 Voice (<10ms latency)
5 Voice (<10ms latency)	5 Video (<100ms latency)
4 Video (<100ms latency)	4 Controlled Load
3 Critical Applications	3 Excellent Effort
2 Excellent	0 Best Effort

Effort

0 Best Effort	2 Spare
---------------	---------

1 Background	1 Background
--------------	--------------

In 802.1D, both CoS 2 and CoS 1 are below CoS 0 (Best Effort).

When a switch is installed in a network of devices following 802.1D Class of Service, the QoS to queue mapping must be reconfigured to follow the 802.1D standard by swapping the assignments of CoS 0 and 2:

1. Create a new queue profile with the desired queue to CoS mapping changes.
2. Apply the created queue profile, using the `apply qos` command.

```
switch# config
switch(config)# queue-profile newProfile
switch(config-queue)# map queue 0 cos 1
switch(config-queue)# map queue 2 cos 0
switch(config-queue)# map queue 1 cos 2
switch(config-queue)# map queue 3 cos 3
switch(config-queue)# map queue 4 cos 4
switch(config-queue)# map queue 5 cos 5
switch(config-queue)# map queue 6 cos 6
switch(config-queue)# map queue 7 cos 7

switch# show qos queue-profile newProfile
queue_num      cos      name
-----
0              1
1              2
2              0
3              3
4              4
5              5
6              6
7              7
```

Monitoring queue operation

Use the `show interface queues` command to display the traffic transmitted per queue, and the number of packets dropped due to the queue being full. (Tx Bytes is available on the 6000 and 6100 Switch Series.) For example:

```
switch# show interface 1/1/1 queues
Interface 1/1/1 is (Administratively down)
Admin state is down
State information: admin_down
      Tx Packets      Tx Bytes      Tx Drops
Q0          100          8000           0
Q1       1234567      12345678908           5
Q2           0           0           0
Q3           0           0           0
Q4           0           0           0
```

Q5	0	0	0
Q6	0	0	0
Q7	0	0	0

Tx Bytes: Total bytes transmitted. The byte count may include packet headers and internal metadata that are removed before the packet is transmitted. Packet headers added when the packet is transmitted may not be included.

Tx Packets: Total packets transmitted.

Tx Drops: The number of packets dropped by a queue before it was sent. When traffic cannot be forwarded out an egress interface, it backs up at ingress. The more servicing assigned to a queue by a schedule profile, the less likely traffic destined for that queue will back up and be dropped. Tx Drops shows the sum of packets that were dropped across all line modules (due to insufficient capacity) by the ingress Virtual Output Queues (VOQs) destined for the egress port.

apply qos

```
apply qos [queue-profile <QUEUE-NAME>] schedule-profile <SCHEDULE-NAME>
no apply qos [queue-profile <QUEUE-NAME>] schedule-profile <SCHEDULE-NAME>
```

Description

Applies a queue profile and schedule profile globally to all Ethernet and LAG interfaces on the switch, or applies a schedule profile to a specific interface. When applied globally, the specified schedule profile is configured only on Ethernet interfaces and LAGs that do not already have their own schedule profile.

The same profile can be applied both globally and locally to an interface. This guarantees that an interface always uses the specified profile, even if the global profile is changed.

The **no** form of this command removes the specified schedule profile from an interface and the interface uses the global schedule profile. This is the only way to remove a schedule profile override from the interface.



Interfaces may shut down briefly during reconfiguration.

Parameter	Description
<code>queue-profile <QUEUE-NAME></code>	Specifies the name of the queue profile to apply. Range: 1 to 64 alphanumeric characters, including period (.), underscore (_), and hyphen (-). This parameter is not supported in the config-if context.
<code>schedule-profile <SCHEDULE-NAME></code>	Specifies the name of the schedule profile to apply. Range: 1 to 64 alphanumeric characters, including period (.), underscore (_), and hyphen (-).

Usage

- The switch must always have a globally-applied queue and schedule profile. To stop using a given profile, apply a different profile.
- For a queue profile to be complete and ready to be applied, all eight CoS values must be mapped to a queue.
- For a schedule profile to be complete and ready to be applied, it must define all queues specified in the queue profile. All queues must use the same algorithm, except for the highest numbered queue, which can be **strict**.
- Both the queue profile and the schedule profile must specify the same number of queues.
- Schedule profiles can be modified while applied, but only in ways where a single command will not result in the profile becoming invalid. For example, queue 7 can have the algorithm changed, and weighted queues can have their weights changed.

- Queues must be consecutively defined starting at queue number zero. For example, a four-queue profile with priority values defined for queues 0, 1, 2, 3 is valid, but a four-queue profile which defines priority values for queues 1, 3, 5, and 7 is not.
- There can be only 2, 4, or 8 queues in a queue profile configuration and the queues must be consecutively numbered starting at zero.
- All queues must use the same algorithm except for the highest numbered queue, which may be strict.

If the number of queues was changed from the previous queue profile to the new one, any Ethernet or LAG interfaces with locally applied schedule profiles will program the newly applied global schedule-profile. The *show running-config interface* command will list the existing *apply qos schedule-profile* command with a comment describing the actual profile applied:

Examples

The following commands illustrate a valid configuration where every CoS value is assigned to a queue and all assigned queues are defined:

```
switch(config)# qos trust cos
switch(config)# qos queue-profile Q1
switch(config)# map queue 0 cos 0
switch(config)# map queue 1 cos 1
switch(config)# map queue 2 cos 2
switch(config)# map queue 3 cos 3
switch(config)# map queue 4 cos 4
switch(config)# map queue 5 cos 5
switch(config)# map queue 6 cos 6
switch(config)# map queue 7 cos 7
switch(config)# qos schedule-profile S1
switch(config)# min-bandwidth queue 0 percent 5
switch(config)# min-bandwidth queue 1 percent 5
switch(config)# min-bandwidth queue 2 percent 10
switch(config)# min-bandwidth queue 3 percent 10
switch(config)# min-bandwidth queue 4 percent 20
switch(config)# min-bandwidth queue 5 percent 20
switch(config)# min-bandwidth queue 6 percent 10
switch(config)# min-bandwidth queue 7 percent 20
```

The following commands illustrate an invalid configuration because CoS 2 is not assigned to a queue:

```
switch(config)# qos trust cos
switch(config)# qos queue-profile Q1
switch(config)# map queue 0 cos 0
switch(config)# map queue 1 cos 1
switch(config)# map queue 3 cos 3
switch(config)# map queue 4 cos 4
switch(config)# map queue 5 cos 5
switch(config)# map queue 6 cos 6
switch(config)# map queue 7 cos 7
switch(config)# qos schedule-profile S1
switch(config)# min-bandwidth queue 0 percent 5
switch(config)# min-bandwidth queue 1 percent 5
switch(config)# min-bandwidth queue 3 percent 10
switch(config)# min-bandwidth queue 4 percent 20
switch(config)# min-bandwidth queue 5 percent 20
switch(config)# min-bandwidth queue 6 percent 10
switch(config)# min-bandwidth queue 7 percent 20
```

Applying the QoS profile **Q1** and the schedule profile **S1** to all interfaces that do not have an applied interface-specific schedule profile:

```
switch(config)# apply qos queue-profile Q1 schedule-profile S1
```

Command History

Release	Modification
10.07 or earlier	--

Command Information

Platforms	Command context	Authority
All platforms	config config-if config-lag-if	Administrators or local user group members with execution rights for this command.

map queue

```
map queue <QUEUE-NUMBER> cos <PRIORITY-NUMBER>  
no map queue <QUEUE-NUMBER> [cos <PRIORITY-NUMBER>]
```

Description

Assigns a CoS value to a queue in a queue profile. By default, the larger the queue number the higher its priority. A queue without a CoS value assigned to it is not used to store packets. The same queue can be assigned multiple CoS values.

The **no** form of this command removes the specified cos value from a specific queue. If no CoS value is specified, then all CoS values are removed from the queue.

Parameter	Description
<QUEUE-NUMBER>	Specifies the queue number. Range: 0 to 7.
<PRIORITY-NUMBER>	Specifies the CoS value. Range: 0 to 7, where 0 is the lowest priority and 7 is the highest.

Usage

The following commands illustrate a valid configuration, where every local priority value is assigned to a queue:

```
map queue 0 local-priority 0  
map queue 1 local-priority 1  
map queue 1 local-priority 2  
map queue 3 local-priority 3  
map queue 4 local-priority 4  
map queue 5 local-priority 5  
map queue 5 local-priority 6  
map queue 5 local-priority 7
```

The following commands illustrate an invalid configuration, because local priority 2 is not assigned to a queue:

```
map queue 0 local-priority 0
map queue 1 local-priority 1
map queue 2 local-priority 3
map queue 3 local-priority 4
map queue 4 local-priority 5
map queue 5 local-priority 6
map queue 5 local-priority 7
```

Examples

Assigning priority **7** to queue **7** in profile **myprofile**:

```
switch(config)# qos queue-profile myprofile
switch(config-queue)# map queue 7 local-priority 7
```

Removing priority **7** from queue **7** in profile **myprofile**:

```
switch(config)# qos queue-profile myprofile
switch(config-queue)# no map queue 7 local-priority 7
```

Command History

Release	Modification
10.07 or earlier	--

Command Information

Platforms	Command context	Authority
All platforms	config-queue	Administrators or local user group members with execution rights for this command.

min-bandwidth

```
min-bandwidth queue <QUEUE-NUMBER> percent <PERCENTAGE>
no min-bandwidth queue <QUEUE-NUMBER>
```

Description

Assigns the Guaranteed Minimum Bandwidth (GMB) algorithm and a percentage of bandwidth to a queue. GMB allocates available bandwidth among all non-empty queues in relation to their configured minimum bandwidth. Non-empty queues are serviced first in strict order up to their minimum bandwidth. If there is any remaining bandwidth, the scheduler will strictly service any remaining non-empty queues.

The **no** form of this command only clears the algorithm for a queue if GMB has been assigned.

Occasionally, the following errors may occur:

- *The schedule profile total sum of GMB percentages must not exceed 100.*

This error occurs when attempting to apply a schedule profile with sum of GMB percentages of queues exceed 100 percentage. The solution is to configure GMB percentage for queues, so that the sum of percentage must not exceed 100.

Parameter	Description
<QUEUE-NUMBER>	Specifies the queue number. Range: 0 to 7.
<PERCENTAGE>	Specifies bandwidth percentage used for GMB scheduling. Range: 0 to 100.

Examples

Assigning queue **0** of schedule profile **S1** the GMB scheduling algorithm with minimum bandwidth of **5 percent**:

```
switch(config)# qos schedule-profile S1
switch(config-schedule)# min-bandwidth queue 0 percent 5
```

Removing GMB from queue 0:

```
switch(config)# qos schedule-profile s1
switch(config-schedule)# no min-bandwidth queue 0
```

Command History

Release	Modification
10.07 or earlier	--

Command Information

Platforms	Command context	Authority
4100i 6000 6100	config-schedule-<NAME>	Administrators or local user group members with execution rights for this command.

name queue

```
name queue <QUEUE-NUMBER> <DESCRIPTION>
no name queue <QUEUE-NUMBER>
```

Description

Assigns a description to a queue in a queue profile. This is for identification purposes and has no effect on configuration.

The **no** form of this command removes the description associated with a queue.

Parameter	Description
<QUEUE-NUMBER>	Specifies the queue number. Range: 0 to 7.
<DESCRIPTION>	Specifies a queue description for identification purposes. Range: 1 to 64 alphanumeric characters, including period (.), underscore (_), and hyphen (-).

Examples

Assigning the description **priority-traffic** to queue **7**:

```
switch(config)# qos queue-profile myprofile
switch(config-queue)# name queue 7 priority-traffic
```

Removing the description from queue **7**:

```
switch(config)# qos queue-profile myprofile
switch(config-queue)# no name queue 7
```

Command History

Release	Modification
10.07 or earlier	--

Command Information

Platforms	Command context	Authority
All platforms	config-queue	Administrators or local user group members with execution rights for this command.

qos cos

```
qos cos <CODE-POINT>
no qos cos
```

Description

Configures a CoS PCP remark for an Ethernet or LAG interface. Packets that ingress on the interface are remarked at egress using the configured CoS PCP value.

The remark only occurs when QoS trust mode on the interface is set to **none**.

If QoS trust mode is not set to **none**, then the remark is ignored, and the following commands will show the CoS remark status as **ignored (incompatible Port Access Trust configuration)** or **not applied' (incompatible QoS global/port Trust configuration)**:

- show running-configuration
- show interface <PORT-NUM>
- show interface <PORT-NUM> qos

The **no** form of this command removes a CoS remark on an interface.

Parameter	Description
<code><CODE-POINT></code>	Specifies an 802.1 VLAN priority CoS value. Range: 0 to 7.

Examples

Configuring a CoS remark of **3** on interface **1/1/1**:

```
switch(config)# interface 1/1/1
switch(config-if)# qos trust none
switch(config-if)# qos cos 3
```

Deleting a CoS remark of **3** on interface **1/1/1**:

```
switch(config)# interface 1/1/1
switch(config-if)# no qos cos
```

Command History

Release	Modification
10.07 or earlier	--

Command Information

Platforms	Command context	Authority
4100i 6000 6100	config-if	Administrators or local user group members with execution rights for this command.

qos dscp

```
qos dscp <CODE-POINT>
no qos dscp
```

Description

Configures a differentiated services code point (DSCP) remark for an Ethernet or LAG interface. IPV4 and IPV6 packets that ingress on the interface are remarked at egress using the configured DSCP value.

The remark only occurs when QoS trust mode on the interface is set to **none**. If a DSCP remark is configured and then trust mode is subsequently set to **cos** or **dscp**, then the DSCP remark is ignored.

The following commands will show the remark status as *ignored* (incompatible Port Access Trust configuration) or *not applied* (incompatible QoS global or port trust configuration):

- **show running-configuration**
- **show interface <INTERFACE-NAME>**
- **show interface <INTERFACE-NAME> qos**

The **no** form of this command removes a CoS remark on an interface.

Parameter	Description
<code><CODE-POINT></code>	Specifies an IP differentiated services code point value. Range: 0 to 63.

Usage

Order of operation for arriving IPv4 or IPv6 packets:

1. The CoS metadata is assigned from the DSCP map entry indexed by the DSCP remark value.
2. If a CoS remark is also configured along with the DSCP remark, the CoS remark value will be assigned to the packet's CoS metadata.
3. The CoS metadata and queue profile are then used to determine the queue for the packet. If the packet is transmitted with an 802.1Q VLAN tag, the PCP will be remarked to match the CoS metadata.

For arriving non-IP packets:

The CoS metadata is assigned from the DSCP map entry indexed by the DSCP remark value. This CoS value and the queue profile are used to select the queue for packet scheduling. The PCP of tagged non-IP packets will be remarked to this CoS value.

Examples

Configuring a DSCP remark of **43** on interface **1/1/1**:

```
switch(config)# interface 1/1/1
switch(config-if)# qos trust none
switch(config-if)# qos dscp 43
```

Deleting a DSCP remark of **43** on interface **1/1/1**:

```
switch(config)# interface 1/1/1
switch(config-if)# no dscp 43
```

Command History

Release	Modification
10.07 or earlier	--

Command Information

Platforms	Command context	Authority
4100i 6000 6100	config-if config-lag-if	Administrators or local user group members with execution rights for this command.

qos dscp-map

```
qos dscp-map <CODE-POINT> [color <COLOR>] [cos <COS-VALUE>] [name <DESCRIPTION>]
no qos dscp-map <CODE-POINT>
```

Description

Defines the CoS value color assigned to incoming packets for a specific IP differentiated services code point (DSCP) value. The DSCP map values are used to prioritize incoming packets when QoS trust mode is set to **dscp**.

The **no** form of this command restores the assignments for a code point to the default setting.



The color *<COLOR>* parameter is supported only in 4100i Switch Series.

Use **show qos dscp-map** to view the current settings. To see the default DSCP map settings, use the following command:

```
switch# show qos dscp-map default
DSCP      code_point  cos  color  name
-----
000000    0           0   green  CS0
000001    1           0   green
000010    2           0   green
000011    3           0   green
000100    4           0   green
000101    5           0   green
...
101101    45          5   green
101110    46          5   green  EF
101111    47          5   green
110000    48          6   green  CS6
...
111101    61          7   green
111110    62          7   green
111111    63          7   green
```

```
switch# show qos dscp-map default
DSCP      code_point  cos  name
-----
000000    0           0   CS0
000001    1           0
000010    2           0
000011    3           0
000100    4           0
000101    5           0
...
101101    45          5
101110    46          5   EF
101111    47          5
110000    48          6   CS6
...
111100    60          7
111101    61          7
111110    62          7
111111    63          7
```

Parameter

Description

<CODE-POINT>

Specifies an IP differentiated services code point. Range: 0 to 63. Default: 0.

color *<COLOR>*

Configures the QoS CoS map color. The supported colors are

Parameter	Description
	green, red, and yellow. The default color is green.
<code>cos <COS-VALUE></code>	Specifies an 802.1p VLAN priority CoS remark value. Range: 0 to 7. Default 0.
<code>cos <PCP-VALUE></code>	Specifies an optional 802.1p VLAN Priority Code Point remark value. Range: 0 to 7. Default: No remark.
<code>name <DESCRIPTION></code>	Specifies a description for the DSCP setting. The name is used for identification only, and has no effect on queue configuration. Range: 1 to 64 alphanumeric characters, including period (.), underscore (_), and hyphen (-).

Examples

Setting code point **46** to a Cos of **7** and CoS map color as **yellow**:

```
switch(config)# qos dscp-map 46 cos 7 name new color yellow
```

Setting code point **41** to a CoS of **6**:

```
switch(config)# qos dscp-map 41 cos 6
```

Setting code point **41** to the default value:

```
switch(config)# no qos dscp-map 41
```

Command History

Release	Modification
10.13	Added <COLOR> parameters.
10.07 or earlier	--

Command Information

Platforms	Command context	Authority
4100i 6000 6100	config	Administrators or local user group members with execution rights for this command.

qos queue-profile

```
qos queue-profile <NAME>
no qos queue-profile <NAME>
```

Description

Creates a new QoS queue profile and switches to the **config-queue** context for the profile. Or, if the specified QoS queue profile exists, this command switches to the **config-queue** context for the profile. . A queue profile maps queues to CoS values. Each profile has two, four, or eight queues numbered 0 to 7. The larger the queue number, the higher its priority during transmission scheduling.

The **no** form of this command removes the specified QoS queue profile. Only profiles that are not currently applied can be removed.

Parameter	Description
<code><NAME></code>	Specifies the name of the QoS queue profile to create or configure. Range: 1 to 64 alphanumeric characters, including period (.), underscore (_), and hyphen (-).

Examples

Creating the profile **myprofile**:

```
switch(config)# qos queue-profile myprofile
switch(config-queue)#
```

Deleting the profile **myprofile**:

```
switch(config)# no qos queue-profile myprofile
```

Command History

Release	Modification
10.07 or earlier	--

Command Information

Platforms	Command context	Authority
All platforms	config	Administrators or local user group members with execution rights for this command.

qos schedule-profile

```
qos schedule-profile <NAME>
no qos schedule-profile <NAME>
```

Description

Creates a QoS schedule profile and switches to the **config-schedule** context for the profile. If the specified schedule profile exists, this command switches to the **config-schedule** context for the profile. The schedule profile determines the order in which queues are selected to transmit a packet, and the amount of service defined for each queue.

Parameter	Description
<NAME>	Specifies the name of the QoS queue profile to create or configure. Range: 1 to 64 alphanumeric characters, including period (.), underscore (_), and hyphen (-).

Usage

Queues in a schedule profile are numbered consecutively starting from zero. Queue zero is the lowest priority queue. The larger the queue number, the higher priority the queue has in scheduling algorithms.

A profile named **factory-default** is defined by default and applied to all interfaces. It cannot be edited or deleted. To see its settings, use the command:

```
switch# show qos schedule-profile factory-default
queue_num algorithm      percent max-bandwidth_kbps
-----
0          min-bandwidth  2
1          min-bandwidth  3
2          min-bandwidth 30
3          min-bandwidth 10
4          min-bandwidth 10
5          min-bandwidth 10
6          min-bandwidth 15
7          min-bandwidth 20
```

A profile named **strict** is predefined and cannot be edited or deleted. The strict profile services all queues of the queue profile to which it is applied, using the strict priority algorithm.

A schedule profile must be defined on all interfaces at all times.

There are two permitted configurations for a schedule profile:

1. All queues use the same scheduling algorithm (for example, GMB).
2. The highest queue number uses strict priority, and all remaining (lower) queues use the same algorithm (for example, GMB). This supports priority scheduling behavior necessary for the IETF RFC 3246 Expedited Forwarding specification (<https://tools.ietf.org/html/rfc3246>).

Only limited changes can be made to an applied schedule profile:

- The percentage of a GMB queue.
- The bandwidth of a strict queue or a min-bandwidth queue.
- The algorithm of the highest numbered queue can be swapped between GMB and strict, and vice versa.

Applicable to REST: Any other changes will result in an unusable schedule profile, and the switch will revert to the **factory-default** profile until the profile is corrected.

The **no** form of this command removes the specified QoS schedule profile when it is not applied. Only profiles that are not currently applied to an interface can be removed.

Examples

Creating the schedule profile **MySchedule**:

```
switch(config)# qos schedule-profile MySchedule
switch(config-schedule)#
```

Deleting the schedule profile **MySchedule**:

```
switch(config)# no qos schedule-profile MySchedule
```

Command History

Release	Modification
10.07 or earlier	--

Command Information

Platforms	Command context	Authority
All platforms	config	Administrators or local user group members with execution rights for this command.

qos threshold-profile

```
qos threshold-profile <NAME>
no qos threshold-profile <NAME>
```

Description

Creates a QoS threshold profile and switches to the **config-threshold** context for the profile. If the specified threshold profile exists, this command switches to the **config-threshold** context for the existing profile. The threshold profile determines the action to take when a threshold is exceeded for each queue.

A threshold profile is composed of up to . Each queue defines the action to take when buffer utilization exceeds a specific threshold.

Configure queues with the command **queue**.

The **no** form of this command removes the specified QoS threshold profile. Only profiles that are not currently applied to an interface can be removed.



In 4100i Switch Series, only one profile can be created.

Parameter	Description
<NAME>	Specifies the name of the QoS threshold profile to create or configure. Range: 1 to 64 alphanumeric characters, including period (.), underscore (_), and hyphen (-).

Usage

Queues in a threshold profile can be any valid queue number, although it is also valid to create a threshold profile with no queues specified. Queue zero is the minimum allowed queue number. The maximum allowed queue number may vary by product. For products supporting eight queues, the

largest queue number is seven. If an applied threshold profile specifies configuration of a queue number that is not in use based on the configured queue profile, the threshold configuration of that unused queue is ignored.

Examples

Creating the threshold profile **mythreshold**:

```
switch(config)# qos threshold-profile mythreshold
switch(config-threshold)#
```

Deleting the threshold profile **MySchedule**:

```
switch(config)# no qos threshold-profile mythreshold
```

Command History

Release	Modification
10.13	Command enabled on 4100i Switch Series.
10.07 or earlier	--

Command Information

Platforms	Command context	Authority
4100i	config	Administrators or local user group members with execution rights for this command.

qos trust

```
qos trust {none|cos|dscp}
no qos trust
```

Description

Configures one of three modes that are applied globally on all Ethernet interfaces and LAGs that have not applied their own trust mode. Trust mode determines whether VLAN or IP headers are used to assign CoS

values to ingress packets.

In the **config** context:

- This command sets the trust mode that is globally applied to all interfaces that do not have a trust mode configured.
- The **no** form of this command restores all interfaces that do not currently have a trust mode configured to the default setting.

In the **config-if** context:

- This command sets the trust mode override for a specific interface.
- The **no** form of this command clears a trust mode override. The interface then uses the global setting. This is the only way to remove a trust mode override.

Parameter	Description
none	Ignores all packet headers. Ingress packets are assigned CoS value zero.
cos	For 802.1 VLAN-tagged packets, use the priority code point field from the outermost VLAN header to assign the CoS value. For untagged packets, the CoS value is assigned to zero. Default.
dscp	For IP packets, use the DSCP as the index into the DSCP Map table to obtain the CoS value for the packet. For non-IP packets, the CoS value is assigned to zero.

Example

Setting the global trust mode to **dscp**, which is applied to all interfaces that do not already have an individual trust mode configured. An override is then applied to interface **2/2/2**, and LAG 100, setting trust mode to **cos**:

```
switch(config)# qos trust dscp
switch(config)# interface 2/2/2
switch(config-if)# qos trust cos
switch(config-if)# interface lag 100
switch(config-if)# qos trust cos
```



WARNING: QoS port remark configurations are not applied when the QoS trust mode is *mode*. This warning message is seen if a port trust command other than *trust none* is attempted when there is already a remark configuration on the port. To restore the old remark configuration, configure the port trust mode to *none*.



WARNING: QoS port remark configurations are not applied when the global QoS trust mode is *mode*. This warning message is seen if a port *no qos trust* command is attempted when there is already a remark configuration on the port and the global trust mode is not *none*. To re-apply the remark configuration, set the port trust mode to *none*.

Command History

Release	Modification
10.07 or earlier	--

Command Information

Platforms	Command context	Authority
All platforms	config config-if config-lag-if	Administrators or local user group members with execution rights for this command.

queue action

WRED

4100i Switch Series

```
queue <0-7> action wred { green | yellow | red } min-threshold <WRED-MIN-LIMIT> percent
max-threshold <WRED-MAX-LIMIT> percent
```

Description

Defines the threshold settings and action for a specified queue in a threshold-profile. For ECN, when queue utilization exceeds the threshold value, ECT (ECN-Capable Transport) packets will be CE (Congestion Encountered) marked when transmitted.

For WRED, when queue utilization exceeds the threshold value, WRED action will randomly early-drop packets to signal congestion. More than one WRED action can be configured on a single queue for different packet colors.

The **no** form of this command removes the settings for a queue.



- Threshold-profile actions are only supported for traffic arriving on interfaces configured in the trust dscp mode.
- ECN is not supported in 4100i Switch Series.

Parameter	Description
<0-7>	Specifies the queue number. Range: 0 to 7.
<WRED-MIN-LIMIT>	Specifies the queue minimum utilization threshold value for WRED to probabilistically start dropping packets.
<WRED-MAX-LIMIT>	Specifies the queue maximum utilization threshold value for WRED, after which every packet is dropped.

Examples

Applicable only on the 4100i Switch Series

Configuring a WRED action on queue 2 for red, yellow, and green colored packets:

```
switch(config)# qos threshold-profile threshprofile
switch(config-threshold)# queue 4 action wred green min-threshold 50 percent max-
threshold 100 percent
switch(config-threshold)# queue 4 action wred yellow min-threshold 30 percent max-
threshold 50 percent
```

```
switch(config-threshold)# queue 4 action wred red min-threshold 20 percent max-threshold 30 percent
```

Removing a threshold from queue **7** in profile **mythreshold**:

```
switch(config)# qos threshold-profile mythreshold  
switch(config-threshold)# no queue 7
```

Command History

Release	Modification
10.13	Command enabled on 4100i Switch Series.
10.07 or earlier	--

Command Information

Platforms	Command context	Authority
4100i	config-threshold	Administrators or local user group members with execution rights for this command.

rate-limit

```
rate-limit {broadcast|multicast|unknown-unicast|icmp {ip-all|ipv4|ipv6}} <RATE>  
{kbps|percent}  
no rate-limit {broadcast|multicast|unknown-unicast|icmp}
```

Description

Sets the amount of traffic of a specific type that can ingress on an Ethernet interface, or on each port of a LAG interface. Rate limits are enforced separately on each individual member of a LAG, not on the LAG as a whole.

The **no** form of this command removes the traffic limit for the specified traffic type.

Parameter	Description
{broadcast multicast unknown-unicast icmp {ip-all ipv4 ipv6}}	Specifies the type of ingress traffic to which the rate limit applies: broadcast, multicast, unknown-unicast, or ICMP. The multicast rate limit affects multicast and broadcast traffic. The broadcast rate limit only affects broadcast traffic. When both types are applied to the same interface, broadcast packets are limited to the lower of the two rate

Parameter	Description
	values. Layer 2 BPDU packets, like spanning tree, are also included in the multicast rate limit. Unknown-unicast packets may be intended for devices whose addresses have temporarily aged out of network forwarding caches. Configuring rate limits can help provide balance between necessary and flooded traffic. The ICMP rate limit can be configured to apply to IPv4, IPv6, or all IP traffic. Only one ICMP rate-limit can be configured at a time. Applying a new ICMP rate-limit replaces any previous ICMP rate-limit.
<code><RATE> {kbps percent}</code>	Specifies the rate limit in kilobits-per-second or as a percentage of link bandwidth. Range: 64 to 10000000 kbps (in steps of 64 kbps), or 1-100 percent. The actual rate limit will be approximately equivalent to the minimum of the two 64-kbps step values that are closest to the configured (or kbps-converted) rate. The actual applied rate limit can be verified using the show interface <IF-NAME> qos command. For percentage mode, rate-limits may be shown as "not applied" until after link-up has occurred on the configured port or LAG.

Examples

Limiting broadcast traffic to **1024kbps** on interface **1/1/3**:

```
switch(config)# interface 1/1/3
switch(config-if)# rate-limit broadcast 1024 kbps
```

Limiting all ICMP IPv4 traffic to **10000kbps** on interface **1/1/3**:

```
switch(config)# interface 1/1/3
switch(config-if)# rate-limit icmp ipv4 1024 kbps
```

Configuring a multicast rate-limit as a percentage of link bandwidth:

```
switch(config)# interface 1/1/3  
switch(config-if)# rate-limit multicast 1 percent
```

Viewing the results of the previous configuration settings:

```
switch# show interface 1/1/3 qos  
Interface 1/1/3 is up  
Admin state is up  
qos trust cos (global)  
qos queue-profile factory-default (global)  
qos schedule-profile factory-default (global)  
rate-limit unknown-unicast 1024 kbps (1024 actual)  
rate-limit broadcast 1024 kbps (1100 actual)  
rate-limit multicast 1 percent (10000 actual)  
rate-limit icmp ip-all 1024 kbps (1024 actual)  
  
switch# show interface 1/1/3  
  
Interface 1/1/3 is up  
Admin state is up  
Link state: up for 3 minutes (since Thu Nov 26 17:56:14 UTC 2020)  
Link transitions: 1  
Description:  
Hardware: Ethernet, MAC Address: f8:60:f0:c9:21:bc  
MTU 1500  
Type 1GbT  
Full-duplex  
qos trust cos  
rate-limit unknown-unicast 1024 kbps (1024 actual)  
rate-limit broadcast 1024 kbps (1100 actual)  
rate-limit multicast 1 percent (10000 actual)  
rate-limit icmp ip-all 1024 kbps (1024 actual)  
Speed 1000 Mb/s  
Auto-negotiation is on  
Energy-Efficient Ethernet is disabled  
Flow-control: off  
Error-control: off  
MDI mode: MDIX  
VLAN Mode: access  
Access VLAN: 1  
Rx  
0 total packets  
0 unicast packets  
0 multicast packets  
0 broadcast packets  
0 errors  
0 CRC/FCS  
0 total bytes  
0 dropped  
0 pause  
Tx  
1057962 total packets  
0 unicast packets  
0 multicast packets  
1058039 broadcast packets  
0 errors  
0 collision  
366066962 total bytes  
0 dropped  
0 pause
```

Command History

Release	Modification
10.13	Added percent parameter.
10.07 or earlier	--

Command Information

Platforms	Command context	Authority
4100i 6000 6100	config-if	Administrators or local user group members with execution rights for this command.

show interface queues

show interface <INTERFACE-NAME> queues

Description

Displays interface-level queue statistics.

Parameter	Description
<INTERFACE-NAME>	Specifies the name of an Ethernet port or LAG on the switch. Format: member/slot/port or lag number .

Usage

Statistics include:

- **Tx Bytes:** Total bytes transmitted. The byte count may include packet headers and internal metadata that are removed before the packet is transmitted. Packet headers added when the packet is transmitted may not be included. The byte count includes any packets subsequently dropped by an egress ACL .
- **Tx Packets:** Total packets transmitted. The count includes packets subsequently dropped by an egress ACL .
- **Tx Drops:** Total packets dropped by an egress queue due to insufficient capacity.

Examples

Showing queue statistics for interface **1/1/5**:

```
switch# show interface 1/1/5 queues
Interface 1/1/5 is down
Admin state is up
```

	Tx Bytes	Tx Packets	Tx Drops
Q0	0	0	3
Q1	15356	73	0
Q2	0	0	0
Q3	0	0	0
Q4	0	0	0
Q5	0	0	0
Q6	0	0	0

Q7	0	0	0
----	---	---	---

Showing queue statistics for interface **lag 1**:

```
switch# show interface lag 1 queues
Aggregate-name lag1
Aggregated-interfaces :
1/1/6 1/1/7
Speed 20000 Mb/s
      Tx Bytes      Tx Packets      Tx Drops
Q0              0             0             0
Q1              0             0             0
Q2              0             0             0
Q3              0             0             0
Q4              0             0             0
Q5              0             0             0
Q6              0             0             0
Q7            3450             25             0
```

Command History

Release	Modification
10.07 or earlier	--

Command Information

Platforms	Command context	Authority
All platforms	Operator (>) or Manager (#)	Operators or Administrators or local user group members with execution rights for this command. Operators can execute this command from the operator context (>) only.

show interface qos

show interface <INTERFACE-NAME> qos

Description

Shows various QoS settings for a specific interface.

Parameter	Description
<INTERFACE-NAME>	Specifies the name of an interface on the switch. Format: member/slot/port or lag number .

Examples

Showing QoS settings for interface **1/1/5**:

```
switch# show interface 1/1/5 qos
Interface 1/1/5 is up
Admin state is up
```

```

qos trust cos (global)
qos queue-profile factory-default (global)
qos schedule-profile factory-default (global)
qos threshold-profile test (override)
qos cos 5
qos dscp 47
rate-limit unknown-unicast 1 percent (10000 actual)
rate-limit broadcast 40000 kbps (40000 actual)
rate-limit icmp ip-all 10000 kbps (10000 actual)

```

Showing QoS settings for a two-member lag:

```

switch# show interface lag1 qos
Aggregate-name lag1
Admin state is up
qos trust cos (global)
qos queue-profile factory-default (global)
qos schedule-profile test (override)
qos threshold-profile test (override)
qos cos 5
qos dscp 47
rate-limit unknown-unicast 1 percent (10000 actual)
rate-limit broadcast 40000 kbps (40000 actual)
rate-limit icmp ip-all 10000 kbps (10000 actual)

```

Per Interface Status

Queue	Maximum Bandwidth	Bandwidth Units
Q1	20000	kbps
Q4	30000	kbps
Q7	40000	kbps

Showing QoS settings for interface **1/1/5**:

```

switch# show interface 1/1/5 qos
Interface 1/1/5 is up
Admin state is up
qos trust cos (global)
qos queue-profile factory-default (global)
qos schedule-profile factory-default (global)
qos cos 5
qos dscp 47
rate-limit unknown-unicast 1 percent (10000 actual)
rate-limit broadcast 40000 kbps (40000 actual)
rate-limit icmp ip-all 10000 kbps (10000 actual)

```

Command History

Release	Modification
10.07 or earlier	--

Command Information

Platforms	Command context	Authority
All platforms	Operator (>) or Manager (#)	Operators or Administrators or local user group members with execution rights for this command. Operators can execute this command from the operator context (>) only.

show qos dscp-map

show qos dscp-map [default]

Description

Displays the current or default global QoS dscp-map.

Parameter	Description
default	Shows the factory default DSCP code point settings.

Examples

Showing the current QoS DSCP map:

```
switch# show qos dscp-map
DSCP      code_point cos  name
-----
000000    0          0    CS0
000001    1          0
000010    2          0
000011    3          0
000100    4          0
000101    5          0
...
101101    45         5
101110    46         6    new
101111    47         5
110000    48         6    CS6
...
111101    61         7
111110    62         7
111111    63         7
```

Showing the default QoS DSCP map:

```
switch# show qos dscp-map default
DSCP      code_point cos  name
-----
000000    0          0    CS0
000001    1          0
000010    2          0
000011    3          0
000100    4          0
000101    5          0
...
101101    45         5
101110    46         5
101111    47         5
110000    48         6    CS6
```

```
...
111100 60 7
111101 61 7
111110 62 7
111111 63 7
```

Command History

Release	Modification
10.07 or earlier	--

Command Information

Platforms	Command context	Authority
All platforms	Operator (>) or Manager (#)	Operators or Administrators or local user group members with execution rights for this command. Operators can execute this command from the operator context (>) only.

show qos queue-profile

```
show qos queue-profile [<NAME> | factory-default]
```

Description

Shows the status of all queue profiles, or a specific queue profile.

Parameter	Description
<NAME>	Specifies the name of a queue profile. Range 1 to 64 alphanumeric characters, including period (.), underscore (_), and hyphen (-).
[factory-default]	Specifies the factory default queue profile.

Usage

The status of a queue profile can be:

- Applied - The profile is actively being used by the switch.
- Complete - The profile meets the criteria to be applied.
- Incomplete - The profile does not meet the criteria to be applied.

For a queue profile to be complete and ready to be applied:

- All eight cos values must be mapped to some queue.
- There can be only 2, 4, or 8 queues.
- The queues must be consecutively numbered starting at zero.

Examples

Showing the settings of the factory default queue profile:

```
switch# show qos queue-profile factory-default
queue_num cos name
-----
0          1
1          0
2          2
3          3
4          4
5          5
6          6
7          7
```

Command History

Release	Modification
10.07 or earlier	--

Command Information

Platforms	Command context	Authority
All platforms	Operator (>) or Manager (#)	Operators or Administrators or local user group members with execution rights for this command. Operators can execute this command from the operator context (>) only.

show qos schedule-profile

show qos schedule-profile [<NAME> | factory-default | strict]

Description

Shows the status of all schedule profiles, or a specific schedule profile.

Parameter	Description
<NAME>	Specifies the name of a queue or schedule profile. Range: 1 to 64 alphanumeric characters, including period (.), underscore (_), and hyphen (-).
[factory-default]	Specifies the factory default queue profile.

Usage

The status of a schedule profile can be:

- Applied - The profile is actively being used by one or more ports.
- Complete - The profile meets the criteria to be applied.
- Incomplete - The profile does not meet the criteria to be applied.

For a schedule profile to be complete and ready to be applied it must have:

- An algorithm for each queue defined by the applied queue profile.
- All queues must use the same algorithm except for the highest numbered queue, which may be strict.

Example

Showing the status of all schedule profiles:

```
switch# show qos schedule-profile
profile_status profile_name
-----
applied        MySchedule
complete       factory-default
complete       Test
```

Showing the configuration of factory default schedule profile:

```
switch# show qos schedule-profile factory-default
Queue
Number  Algorithm      Percent  Maximum  Bandwidth
-----  -
0       min-bandwidth  2        Bandwidth
1       min-bandwidth  3        Units
2       min-bandwidth  30
3       min-bandwidth  10
4       min-bandwidth  10
5       min-bandwidth  10
6       min-bandwidth  15
7       min-bandwidth  20
```

Command History

Release	Modification
10.07 or earlier	--

Command Information

Platforms	Command context	Authority
All platforms	Operator (>) or Manager (#)	Operators or Administrators or local user group members with execution rights for this command. Operators can execute this command from the operator context (>) only.

show qos threshold-profile

```
show qos threshold-profile [<NAME>]
```

Description

Shows the status of all threshold profiles, or a specific threshold profile.

Parameter	Description
<NAME>	Specifies the name of a threshold profile. Range: 1 to 64 alphanumeric characters, including period (.), underscore (_), and hyphen (-).

Usage

Status fields are:

- applied: The threshold profile is applied to all configured ports.
- partially applied: The threshold profile is applied to some configured ports but failed on other configured ports.
- not applied: The threshold profile could not be applied to any configured ports.
- blank field: The threshold profile is not applied in the configuration (globally or as a port override).



For the 4100i Switch Series, you cannot apply threshold profile at the global level. Also, the threshold profile cannot be applied on 10G ports.

Examples

Showing the status of the threshold profile:

```
switch# show qos threshold-profile
profile_status      profile_name
-----
applied             threshprofile
```

Command History

Release	Modification
10.13	Command enabled on 4100i Switch Series.
10.07 or earlier	--

Command Information

Platforms	Command context	Authority
4100i	Operator (>) or Manager (#)	Operators or Administrators or local user group members with execution rights for this command. Operators can execute this command from the operator context (>) only.

show qos trust

```
show qos trust [default]
```

Description

Shows the global QoS trust settings, or the factory default settings.

Parameter	Description
default	Shows the factory default QoS trust settings.

Examples

Showing the current QoS trust settings:

```
switch# show qos trust
qos trust cos
```

Showing the default QoS trust settings:

```
switch# show qos trust default
qos trust cos
```

Command History

Release	Modification
10.07 or earlier	--

Command Information

Platforms	Command context	Authority
All platforms	Operator (>) or Manager (#)	Operators or Administrators or local user group members with execution rights for this command. Operators can execute this command from the operator context (>) only.

strict queue

```
strict queue <0-7> [max-bandwidth <RATE> [kbps|percent]]
no strict queue <0-7> [max-bandwidth <RATE> [kbps|percent]]
```

Description

Assigns the strict priority algorithm to a queue. Strict priority services all packets waiting in a queue, before servicing the packets in lower priority queues.

Egress queue shaping can be configured using the **max-bandwidth** option to limit the amount of traffic transmitted per output queue. The buffer associated with each egress queue stores the excess traffic to smooth the output rate. Sustained rates of traffic above the maximum bandwidth will eventually fill the output queue, causing tail drops. Use **show interface <IF-NAME> queues** to determine if any tail-drop errors have occurred.

The **no** form of this command removes the queue configuration from the schedule profile. To remove only egress queue shaping, re-enter the strict queue command without the **max-bandwidth** parameter.

Parameter	Description
<QUEUE-NUMBER>	Specifies the number of the queue. Range: 0 to 7.
max-bandwidth <BANDWIDTH>	Specifies the maximum bandwidth allowed on the queue in Kbps. Range: 468 to 100000000. Alternatively, the maximum bandwidth rate can also be configured on the queue as a percentage of the port shape or link bandwidth if a port shape is not configured. The allowed range is 1-100.

Usage

Either all the queues of the schedule profile can be *strict* or just the highest numbered queue. When applied to a LAG, each member Ethernet port independently schedules its egress transmissions using the strict settings. Only limited changes can be made to a *strict* queue that is part of an applied schedule profile:

- The max-bandwidth settings.
- The highest numbered queue can be swapped between *strict* and *min-bandwidth*

Any other changes or removing a queue (**no strict queue**) will result in an unusable schedule profile. If that schedule profile is applied in the interface context, the switch will revert to the schedule profile applied in the global context until the profile is corrected. If that schedule profile is applied in the global context, the switch will revert to using the factory-default profile until the profile is corrected.

It is possible for the following errors to occur:

- **The max-bandwidth cannot be greater than 100 percent.**

This error occurs when a max-bandwidth value greater than 100 percent is configured on a queue.

- **The max-bandwidth cannot be less than <NUM> kbps.**

This error occurs when a kbps max-bandwidth value less than the supported minimum kbps shape value is configured on a queue. The supported minimum kbps shape value can be retrieved using the **show capacities** command.

Examples

Assigning strict priority to queue **7** in the schedule profile **MySchedule**:

```
switch(config)# qos schedule-profile MySchedule
switch(config-schedule)# strict queue 7
```

Deleting strict priority from queue **7** in the schedule profile **MySchedule**:

```
switch(config)# qos schedule-profile MySchedule
switch(config-schedule)# no strict queue 7
```

Assigning strict priority to queue **7** in the schedule profile **MySchedule** with a maximum bandwidth of 10000 Kbps:

```
switch(config)# qos schedule-profile MySchedule
switch(config-schedule)# strict queue 7 max-bandwidth 10000 kbps
```

Command History

Release	Modification
10.13	Added the kbps and percent parameters.
10.07 or earlier	--

Command Information

Platforms	Command context	Authority
All platforms	config-schedule- <i><NAME></i>	Administrators or local user group members with execution rights for this command.

Accessing Aruba Support

Aruba Support Services	https://www.arubanetworks.com/support-services/
AOS-CX Switch Software Documentation Portal	https://www.arubanetworks.com/techdocs/AOS-CX/help_portal/Content/home.htm
Aruba Support Portal	https://asp.arubanetworks.com/
North America telephone	1-800-943-4526 (US & Canada Toll-Free Number) +1-408-754-1200 (Primary - Toll Number) +1-650-385-6582 (Backup - Toll Number - Use only when all other numbers are not working)
International telephone	https://www.arubanetworks.com/support-services/contact-support/

Be sure to collect the following information before contacting Support:

- Technical support registration number (if applicable)
- Product name, model or version, and serial number
- Operating system name and version
- Firmware version
- Error messages
- Product-specific reports and logs
- Add-on products or components
- Third-party products or components

Other useful sites

Other websites that can be used to find information:

Airheads social forums and Knowledge Base	https://community.arubanetworks.com/
AOS-CX Switch Software Documentation Portal	https://www.arubanetworks.com/techdocs/AOS-CX/help_portal/Content/home.htm
Aruba Hardware Documentation	https://www.arubanetworks.com/techdocs/hardware/DocumentationPortal/Content/home.htm

Aruba software	https://asp.arubanetworks.com/downloads
Software licensing	https://lms.arubanetworks.com/
End-of-Life information	https://www.arubanetworks.com/support-services/end-of-life/
Aruba Developer Hub	https://developer.arubanetworks.com/

Accessing Updates

You can access updates from the Aruba Support Portal or the HPE My Networking Website.

Aruba Support Portal

<https://asp.arubanetworks.com/downloads>

If you are unable to find your product in the Aruba Support Portal, you may need to search My Networking, where older networking products can be found:

My Networking

<https://www.hpe.com/networking/support>

To view and update your entitlements, and to link your contracts and warranties with your profile, go to the Hewlett Packard Enterprise Support Center **More Information on Access to Support Materials** page:

<https://support.hpe.com/portal/site/hpsc/aae/home/>

Access to some updates might require product entitlement when accessed through the Hewlett Packard Enterprise Support Center. You must have an HP Passport set up with relevant entitlements.

Some software products provide a mechanism for accessing software updates through the product interface. Review your product documentation to identify the recommended software update method.

To subscribe to eNewsletters and alerts:

<https://asp.arubanetworks.com/notifications/subscriptions> (requires an active Aruba Support Portal (ASP) account to manage subscriptions). Security notices are viewable without an ASP account.

Warranty Information

To view warranty information for your product, go to <https://www.arubanetworks.com/support-services/product-warranties/>.

Regulatory Information

To view the regulatory information for your product, view the *Safety and Compliance Information for Server, Storage, Power, Networking, and Rack Products*, available at <https://www.hpe.com/support/Safety-Compliance-EnterpriseProducts>

Additional regulatory information

Aruba is committed to providing our customers with information about the chemical substances in our products as needed to comply with legal requirements, environmental data (company programs, product recycling, energy efficiency), and safety information and compliance data, (RoHS and WEEE). For more information, see <https://www.arubanetworks.com/company/about-us/environmental-citizenship/>.

Documentation Feedback

Aruba is committed to providing documentation that meets your needs. To help us improve the documentation, send any errors, suggestions, or comments to Documentation Feedback (docsfeedback-switching@hpe.com). When submitting your feedback, include the document title, part number, edition, and publication date located on the front cover of the document. For online help content, include the product name, product version, help edition, and publication date located on the legal notices page.