



AOS-CX Job Scheduler Guide (All Switch Series)

AOS-CX Job Scheduler Guide (All Switch Series)

Published: May 2026

© Copyright 2026 – Hewlett Packard Enterprise Development LP

Notices

The information provided here is subject to change without notice. Hewlett Packard Enterprise's products and services are covered only by the express warranty statements that come with them. This document does not constitute an additional warranty. Hewlett Packard Enterprise is not responsible for any technical or editorial errors or omissions in this document.

Confidential computer software. You must have a valid license from Hewlett Packard Enterprise to possess, use, or copy the software. In accordance with FAR 12.211 and 12.212, Commercial Computer Software, Computer Software Documentation, and Technical Data for Commercial Items are licensed to the U.S. Government under the vendor's standard commercial license.

Links to third-party websites will take you outside of the Hewlett Packard Enterprise website. Hewlett Packard Enterprise has no control over and is not responsible for the information outside the Hewlett Packard Enterprise website.

Open source code

This product includes code licensed under certain open source licenses which require source compliance. The corresponding source for these components is available upon request. This offer is valid to anyone in receipt of this information and shall expire three years following the date of the final distribution of this product version by Hewlett Packard Enterprise Company. To obtain such source code, please check if the code is available in the HPE Software Center at <https://myenterpriselicense.hpe.com/cwp-ui/software> but, if not, send a written request for specific software version and product for which you want the open source code. Along with the request, please send a check or money order in the amount of US \$10.00 to:

Hewlett Packard Enterprise Company

Attn: General Counsel

WW Corporate Headquarters

1701 E Mossy Oaks Rd, Spring, TX 77389

United States of America.



Legal disclaimer

The resource assets in this document may include abbreviated and/or legacy terminology for products. See [**www.arubanetworks.com**](http://www.arubanetworks.com) for current and complete product lines and names.

Table of contents

About this document.....	5
Applicable products.....	5
Latest version available online.....	6
Command syntax notation conventions.....	6
About the examples.....	7
Identifying switch ports and interfaces.....	8
Identifying modular switch components.....	10
Job Scheduler.....	11
Working with Job Scheduler.....	11
Job Scheduler commands.....	14
job	15
reload	18
schedule	22
show job	26
show capacities (job, schedule)	29
show reload	30
show running-config (job, schedule)	32
show schedule	34
Support and Other Resources.....	36
Accessing HPE Aruba Networking Support.....	36
Accessing Updates.....	38
Warranty Information.....	38
Regulatory Information.....	38
Documentation Feedback.....	39

About this document

This document describes features of the AOS-CX network operating system. It is intended for administrators responsible for installing, configuring, and managing HPE Aruba Networking switches on a network.

Subtopics

Applicable products

Latest version available online

Command syntax notation conventions

About the examples

Identifying switch ports and interfaces

Identifying modular switch components

Applicable products

This document applies to the following products:

- HPE Aruba Networking 4100i Switch Series (JL817A, JL818A)
- HPE Aruba Networking 6000 Switch Series (R8N85A, R8N86A, R8N87A, R8N88A, R8N89A, R9Y03A)
- HPE Aruba Networking 6100 Switch Series (JL675A, JL676A, JL677A, JL678A, JL679A)
- HPE Aruba Networking 5420 Switch Series (S0U67A, S0U55A, S0U63A, S0U64A, S0U65A, S0U75A, S0U72A, S0U78A, S0U58A, S0U73A, S0U74A, S0U71A, S0U76A, S0U70A, S0U77A, S0U60A, S0U61A, S0U62A, S0U66A, S0U68A)
- HPE Aruba Networking 6200 Switch Series (JL724A, JL725A, JL726A, JL727A, JL728A, R8Q67A, R8Q68A, R8Q69A, R8Q70A, R8Q71A, R8V08A, R8V09A, R8V10A, R8V11A, R8V12A, R8Q72A, JL724B, JL725B, JL726B, JL727B, JL728B, S0M81A, S0M82A, S0M83A, S0M84A, S0M85A, S0M86A, S0M87A, S0M88A, S0M89A, S0M90A, S0G13A, S0G14A, S0G15A, S0G16A, S0G17A)
- HPE Aruba Networking 6300 Switch Series (JL658A, JL659A, JL660A, JL661A, JL662A, JL663A, JL664A, JL665A, JL666A, JL667A, JL668A, JL762A, R8S89A, R8S90A, R8S91A, R8S92A, S0E91A, S0X44A, S3L75A, S3L76A, S3L77A)
- HPE Aruba Networking 6400 Switch Series (R0X31A, R0X38B, R0X38C, R0X39B, R0X39C, R0X40B, R0X40C, R0X41A, R0X41C, R0X42A, R0X42C, R0X43A, R0X43C, R0X44A, R0X44C, R0X45A, R0X45C, R0X26A, R0X27A, JL741A, S0E48A, S0E48A #0D1, S1T83A, S1T83A #0D1)
- HPE Aruba Networking 8100 Switch Series (R9W94A, R9W95A, R9W96A, R9W97A)

- HPE Aruba Networking 8320 Switch Series (JL479A, JL579A, JL581A)
- HPE Aruba Networking 8325 Switch Series (JL624A, JL625A, JL626A, JL627A)
- HPE Aruba Networking 8325H Switch Series (S4B20A, S4B21A, S4B22A, S4B23A, S2T42A, S2T46A, S2T47A, S2T48A)
- HPE Aruba Networking 8325P Switch Series (S0G12A, S4A48A)
- HPE Aruba Networking 8360 Switch Series (JL700A, JL701A, JL702A, JL703A, JL706A, JL707A, JL708A, JL709A, JL710A, JL711A, JL700C, JL701C, JL702C, JL703C, JL706C, JL707C, JL708C, JL709C, JL710C, JL711C, JL704C, JL705C, JL719C, JL718C, JL717C, JL720C, JL722C, JL721C)
- HPE Aruba Networking 8400 Switch Series (JL366A, JL363A, JL687A)
- HPE Aruba Networking 9300 Switch Series (R9A29A, R9A30A, R8Z96A, S0F81A, S0F82A, S0F83A)
- HPE Aruba Networking 9300S Switch Series (S0F81A, S0F82A, S0F83A, S0F84A, S0F85A, S0F86A, S0F88A, S0F95A, S0F96A)
- HPE Aruba Networking 10000 Switch Series (R8P13A, R8P14A)

Latest version available online

Updates to this document can occur after initial publication. For the latest versions of product documentation, see the links provided in [Support and Other Resources](#).

Command syntax notation conventions

Convention	Usage
example - text	Identifies commands and their options and operands , code examples, filenames, pathnames, and output displayed in a command window. Items that appear like the example text in the previous column are to be entered exactly as shown and are required unless enclosed in brackets ([]).
example - text	In code and screen examples, indicates text entered by a user.

Convention	Usage
Any of the following: • <code><example - text></code> • <code><example - text></code> • <code>example - text</code> • <code>example - text</code>	Identifies a placeholder—such as a parameter or a variable—that you must substitute with an actual value in a command or in code: • For output formats where italic text cannot be displayed, variables are enclosed in angle brackets (<code>< ></code>). Substitute the text—including the enclosing angle brackets—with an actual value. • For output formats where italic text can be displayed, variables might or might not be enclosed in angle brackets. Substitute the text including the enclosing angle brackets, if any, with an actual value.
	Vertical bar. A logical OR that separates multiple items from which you can choose only one. Any spaces that are on either side of the vertical bar are included for readability and are not a required part of the command syntax.
{ }	Braces. Indicates that at least one of the enclosed items is required.
[]	Brackets. Indicates that the enclosed item or items are optional.
... or ...	Ellipsis: • In code and screen examples, a vertical or horizontal ellipsis indicates an omission of information. • In syntax using brackets and braces, an ellipsis indicates items that can be repeated. When an item followed by ellipses is enclosed in brackets, zero or more items can be specified.

About the examples

Examples in this document are representative and might not match your particular switch or environment.

The slot and port numbers in this document are for illustration only and might be unavailable on your switch.

Understanding the CLI prompts

When illustrating the prompts in the command line interface (CLI), this document uses the generic term **switch**, instead of the host name of the switch. For example:

```
switch>
```

The CLI prompt indicates the current command context. For example:

```
switch>
```

Indicates the operator command context.

```
switch#
```

Indicates the manager command context.

```
switch(CONTEXT-NAME) #
```

Indicates the configuration context for a feature. For example:

```
switch(config-if) #
```

Identifies the **interface** context.

Variable information in CLI prompts

In certain configuration contexts, the prompt may include variable information. For example, when in the VLAN configuration context, a VLAN number appears in the prompt:

```
switch(config-vlan-100) #
```

When referring to this context, this document uses the syntax:

```
switch(config-vlan-<VLAN-ID>) #
```

Where <VLAN-ID> is a variable representing the VLAN number.

Identifying switch ports and interfaces

Physical ports on the switch and their corresponding logical software interfaces are identified using the format: **member/slot/port**.

On the HPE Aruba Networking 4100i Switch Series

- member: Always 1. VSF is not supported on this switch.
- slot: Always 1. This is not a modular switch, so there are no slots.
- port: Physical number of a port on the switch.

For example, the logical interface **1/1/4** in software is associated with physical port 4 on the switch.

On the HPE Aruba Networking 6000 and 6100 Switch Series

- member: Always 1. VSF is not supported on this switch.

- slot: Always 1. This is not a modular switch, so there are no slots.
- port: Physical number of a port on the switch.

For example, the logical interface **1/1/4** in software is associated with physical port 4 on the switch.

On the HPE Aruba Networking 6200 Switch Series

- member: Member number of the switch in a Virtual Switching Framework (VSF) stack. Range: 1 to 8. The primary switch is always member 1. If the switch is not a member of a VSF stack, then member is 1.
- slot: Always 1. This is not a modular switch, so there are no slots.
- port: Physical number of a port on the switch.

For example, the logical interface **1/1/4** in software is associated with physical port 4 in slot 1 on member 1.

On the HPE Aruba Networking 6300 Switch Series

- member: Member number of the switch in a Virtual Switching Framework (VSF) stack. Range: 1 to 10. The primary switch is always member 1. If the switch is not a member of a VSF stack, then member is 1.
- slot: Always 1. This is not a modular switch, so there are no slots.
- port: Physical number of a port on the switch.

For example, the logical interface **1/1/4** in software is associated with physical port 4 on member 1.

On the HPE Aruba Networking 6400 and 5420 Switch Series

- member: Always 1. VSF is not supported on this switch.
- slot: Specifies physical location of a module in the switch chassis.
 - Management modules are on the front of the switch in slots 1/1 and 1/2.
 - Line modules are on the front of the switch starting in slot 1/3.
- port: Physical number of a port on a line module.

For example, the logical interface **1/3/4** in software is associated with physical port 4 in slot 3 on member 1.

On the HPE Aruba Networking 8xxx, 9300/9300S, and 10000 Switch Series

- member: Always 1. VSF is not supported on this switch.
- slot: Always 1. This is not a modular switch, so there are no slots.
- port: Physical number of a port on the switch.

For example, the logical interface **1/1/4** in software is associated with physical port 4 on the switch.



NOTE

If using breakout cables, the port designation changes to x:y, where x is the physical port and y is the lane when split. For example, the logical interface 1/1/4:2 in software is associated with lane 2 on physical port 4 in slot 1 on member 1.

On the HPE Aruba Networking 8400 Switch Series

- member: Always 1. VSF is not supported on this switch.
- slot: Specifies physical location of a module in the switch chassis.
 - Management modules are on the front of the switch in slots 1/5 and 1/6.
 - Line modules are on the front of the switch in slots 1/1 through 1/4, and 1/7 through 1/10.
- port: Physical number of a port on a line module

For example, the logical interface **1/1/4** in software is associated with physical port 4 in slot 1 on member 1.

Identifying modular switch components

- Power supplies are on the front of the switch behind the bezel above the management modules. Power supplies are labeled in software in the format: member/power supply:
 - member: 1.
 - power supply: 1 to 4.
- Fans are on the rear of the switch and are labeled in software as: member/tray/fan:
 - member: 1.
 - tray: 1 to 4.
 - fan: 1 to 4.
- Fabric modules are not labeled on the switch but are labeled in software in the format: member/module:
 - member: 1.
 - member: 1 or 2.
- The display module on the rear of the switch is not labeled with a member or slot number.

Job Scheduler

- The Job Scheduler enables you to execute batches of CLI commands on a user-configured schedule or interval. Job Scheduler can be used, for example, to schedule activities such as port toggles, switch reboots, QoS policy changes, system health status checks, statistics clearing, clean-up, and saving the running configuration.
- Schedules can trigger jobs based on calendar date and time or at periodic intervals.
- Jobs can be scheduled to execute as frequently as once every thirty minutes.
- When executed, commands with simple (y/n) prompts (such as `boot system`) will be automatically confirmed with "y." Other commands requiring more complex user input (such as password change) cannot be used.

Subtopics

Working with Job Scheduler

Job Scheduler commands

Working with Job Scheduler

To help understand how to work with the Job Scheduler, several basic examples are presented, followed by detailed descriptions of the commands involved under [Job scheduler commands](#).

Port toggle example

This example creates a port toggle job and then schedules the job for execution on Monday and Friday night at 11:45 PM.

Creating a port toggle job named **PTog1**:

```
switch(config)# job PTog1
switch(config-job-PTog1)# desc Toggle port 1/1/1
switch(config-job-PTog1)# 10 cli config
switch(config-job-PTog1)# 20 cli interface 1/1/1
switch(config-job-PTog1)# 30 cli shutdown
switch(config-job-PTog1)# 40 delay 10 cli no shutdown
switch(config-job-PTog1)# 50 cli end
switch(config-job-PTog1)# exit
```

Creating a schedule named **PT2xW** that runs the port toggle job **PTog1** on Mondays and Fridays at 11:45 PM, starting on August 2 2021, with a one-year duration:

```
switch(config)# schedule PT2xW
switch(config-schedule-PT2xW)# desc Monday & Friday 11:45 PM port toggles
switch(config-schedule-PT2xW)# 10 job PTog1
switch(config-schedule-PT2xW)# trigger on 23:45 weekly 2,6 count 104 start
2021-08-02
switch(config-schedule-PT2xW)# exit
```

Showing the port toggle job information after first execution:

```
switch# show job PTog1
Job Name : PTog1
  Enabled           : Yes
  Description       : Toggle port 1/1/1
  Status           : waiting
  Number of commands : 5
  Total execution count : 1
  Failed execution count : 0
  Job execution history
  -----
  Instance number   : 1
  Execution status   : success
  Execution start time : Mon Aug 2 23:45:00 2021
  Execution duration : 10s
  Job CLI commands
  -----
  10 cli config
  20 cli interface 1/1/1
  30 cli shutdown
  40 delay 10 cli no shutdown
  50 cli end
```

Showing the port toggle job schedule information after first execution:

```
switch# show schedule PT2xW
Schedule Name: PT2xW
  Schedule config
  -----
  Description       : Monday & Friday 11:45 PM port toggles
  Enabled          : Yes
  Trigger type     : calendar
  Transient        : No
  Max trigger count : 104
```

```

Trigger start date   : 2021-08-02 23:45
Schedule Status
-----
Trigger status      : active
Next trigger time   : Fri Aug  6 23:45:00 2021
Triggered count     : 1
Scheduled Jobs
-----
10   : PTog1

```

Showing the port toggle job most recent execution output:

```

switch# show job PTog1 execution-output 1
=====
=====
Command: config
time: Mon Aug  2 23:45:00 2021
=====
=====
=====
=====
Command: interface 1/1/1
time: Mon Aug  2 23:45:00 2021
=====
=====
=====
=====
Command: shutdown
time: Mon Aug  2 23:45:00 2021
=====
=====
=====
=====
Command: cli no shutdown
time: Mon Aug  2 23:45:10 2021
=====
=====
=====
=====
Command: end
time: Mon Aug  2 23:45:10 2021
=====
=====

```

Switch reboot example

This example creates a switch reboot job and then schedules the job for execution on the last day of every month at 3:00 AM.

Creating a job named **Reboot_sw1** that saves the running configuration and then reboots the switch:

```
switch(config)# job Reboot_sw1
switch(config-job-Reboot_sw1)# desc Save config then reboot switch
switch(config-job-Reboot_sw1)# 10 cli config
switch(config-job-Reboot_sw1)# 20 cli write mem
switch(config-job-Reboot_sw1)# 30 cli boot system
switch(config-job-Reboot_sw1)# exit
switch(config)#
```

Creating a schedule named **RB_LDM** that runs the switch reboot job **Reboot_sw1** on the last day of the month at 3:00 AM, starting on January 31 2022, with a two-year duration:

```
switch(config)# schedule RB_LDM
switch(config-schedule-RB_LDM)# desc Monthly reboot 3:00 AM
switch(config-schedule-RB_LDM)# 10 job Reboot_sw1
switch(config-schedule-RB_LDM)# trigger on 3:00 monthly 31 count 24 start
2022-01-31
switch(config-schedule-RB_LDM)# exit
switch(config)#
```

After the **RB_LDM** schedule triggers the reboot job **Reboot_sw1**, the `show events` command is available to show schedule triggering (`<MODEL>` represents the switch model number):

```
switch# show events -a -d schedulerd
-----
Event logs from previous boots
-----
...
2022-01-31T03:00:14.405135+00:00 <MODEL> schedulerd[2054]: Event|12202|
LOG_INFO|AMM|1/1|Schedule RB_LDM triggered, trigger_count: 1
-----
Event logs from current boot
-----
switch#
```

Job Scheduler commands

Select a command from the list in the left navigation menu.

Subtopics

job
reload
schedule
show job
show capacities (job, schedule)
show reload
show running-config (job, schedule)
show schedule

job

Syntax

In the config context:

```
job <JOB-NAME>  
no job [<JOB-NAME>]
```

Subcommands available In the job config context (`config-job`):

```
[no] enable  
[no] desc <DESCRIPTION>  
[no] [<SEQ-NUM>] [delay <DELAY>] cli <COMMAND>  
resequence <START-SEQ-NUM>  
          <INCREMENT>
```

Description

If <JOB-NAME> does not exist, this command creates a job and then enters its context.

The no form of this command deletes the specified job. If no job is specified, all jobs are deleted.



NOTE

Deleting a job also removes it from any schedule that uses the job, preventing further attempts to execute the job.

If <JOB-NAME> exists, this command enters the **config-job- <NAME>** context for the specified job.

Parameter	Description
	Specifies the job name. Range 1 to 64 characters (alphanumeric and "_" (underscore))

Parameter	Description
<code><JOB-NAME></code>	

Subcommands

These subcommands are available within the **config-job-** `<NAME>` context for configuring the job:

enable

Enables the job (the default). **no enable** disables the job.

```
[no] desc <DESCRIPTION>
```

Specifies a user-defined job description. **no desc** removes the description. Range: 1 to 128 characters. For example:

```
switch(config-job-PTog1) # desc Toggle port 1/1/1
    [no] [
    <SEQ-NUM>
    ] [delay
    <DELAY>
    ] cli
    <COMMAND>
```

Adds a CLI command to the job. The no form removes the command from the job. When executed, commands with simple (y/n) prompts (such as **boot system**) will be automatically confirmed with "y." Other commands requiring more complex user input (such as password change) cannot be used.

<SEQ-NUM> specifies the job CLI command sequence number to facilitate ordering of commands within a job. When omitted, a sequence number that is 10 greater the highest existing sequence number is auto-assigned. The first auto-assigned sequence number is 10. Range: 1 to 4294967295.

[delay `<DELAY>`] specifies the delay in seconds before this CLI command is executed. The cumulative delay for all commands in a job must be no more than 300 seconds. Range 1 to 300.

cli `<COMMAND>` specifies the CLI command to be executed. Range 1 to 4096 characters.

These commands must not be used in a job: **copy, repeat, show boot-history, show core-dump, show events, show job, show tech, sleep, terminal-monitor.**

For example, adding a command as line 18 to a job:

```
switch(config-job-PTog1) # 18 cli interface 1/1/1
resequence <START-SEQ-NUM>
           <INCREMENT>
```


Resequences the CLI command line sequence numbers. Both **<START-SEQ-NUM>** and **<INCREMENT>** default to 10. For example, resequencing the CLI command list to start at 10 with an increment of 5.

```
switch(config-job-PTog1)# resequence 10 5
switch(config-job-PTog1)# show job PTog1
Job Name : PTog1
...
    Job CLI commands
    -----
    10 cli config
    15 cli interface 1/1/1
    20 cli shutdown
...
```

Usage

- A maximum of 20 commands can be used in a job.
- To see the maximum number of jobs and job execution output preserved instances for your particular switch, use command **show capacities job**.
- Jobs must complete execution in under five minutes and are force-stopped after five minutes if they do not.

Examples

Creating a port toggle job named **PTog1**:

```
switch(config)# job PTog1
switch(config-job-PTog1)# desc Toggle port 1/1/1
switch(config-job-PTog1)# 10 cli config
switch(config-job-PTog1)# 20 cli interface 1/1/1
switch(config-job-PTog1)# 30 cli shutdown
switch(config-job-PTog1)# 40 delay 10 cli no shutdown
switch(config-job-PTog1)# 50 cli end
switch(config-job-PTog1)# exit
switch(config)#
```

Creating a job named **Reboot_sw1** that saves the running configuration and then reboots the switch:

```
switch(config)# job Reboot_Sw1
switch(config-job-Reboot_sw1)# desc Save config then reboot switch
switch(config-job-Reboot_Sw1)# 10 cli config
switch(config-job-Reboot_Sw1)# 20 cli write mem
switch(config-job-Reboot_Sw1)# 30 cli boot system
switch(config-job-Reboot_Sw1)# exit
switch(config)#
```

Command History

Release	Modification
10.08	Command introduced.

Command Information

Platforms	Command context	Authority
All platforms	<code>config</code> <code>config-job-</code> <code><NAME></code>	Administrators or local user group members with execution rights for this command.

reload

Syntax

```
reload
<1-10> {at YYYY-MM-DD HH:MM:SS}|{after DD:HH:MM}
active|standby {at YYYY-MM-DD HH:MM:SS}|{after DD:HH:MM}
at YYYY-MM-DD HH:MM:SS
after DD:HH:MM
cancel
```

Description

Reboot the switch, stack, or chassis at a specific date and time up to 99 days in the future, or after a specified time period has elapsed. Reload information is not persistent after the reboot. The **reload** commands trigger a reload of the default image, which is defined using the **boot set-default** command. The **reload cancel** command cancels a scheduled reload operation.



NOTE

The **reload** command cannot be issued if an In-Service Software Update (ISSU) is in progress.

Parameter	Description
<code><1 - 10></code>	On 6200, and 6300M/F Switch series, specify a VSF member ID to reload that VSF member.
<code>at YYYY-MM-DD HH:MM:SS</code>	On 6200, and 6300M/F Switch series, specify the timestamp for the scheduled VSF member reload, where: • YYYY represents the year. • MM represents the month, from 01 (January) to 12 (December). • DD represents the day (01 to 31). • HH represents the hour, in 24 - hour clock format, 00 - 23. • MM represents the minute, 00 - 59. • SS represents the seconds, 00 - 59.
<code>after DD:HH:MM</code>	On 6200, and 6300M/F Switch series, specify how much time should elapse before the scheduled VSF member reload, where: • DD represents the number of days before the reload • HH represents the number of hours before the reload • MM represents the number of minutes before the reload.
<code>(active standby)</code>	On 6400 and 8400 Switch series, use the active and standby options to reload the active or standby management module.
<code>at YYYY-MM-DD HH:MM:SS</code>	On 6400 and 8400 Switch series, specify the timestamp for the scheduled management module reload, where: • YYYY represents the year. • MM represents the month, from 01 (January) to 12 (December). • DD represents the day (01 to 31). • HH represents the hour, in 24 - hour clock format, 00 - 23. • MM represents the minute, 00 - 59. • SS represents the seconds, 00 - 59.
<code>after DD:HH:MM</code>	On 6400 and 8400 Switch series, specify how much time should elapse before the scheduled management module reload, where: • DD represents the number of days before the reload • HH represents the number of hours before the reload • MM represents the number of minutes before the reload.

Parameter	Description
<code>at YYYY-MM-DD HH:MM:SS</code>	On 4100i, 5420, 6000, 6100, 6300M/F, 6300L, 6400, 8100, 8320, 8325/8325H/8325P, 8360, 9300/9300S and 10000 switch series, specify the timestamp for the scheduled reload, where • YYYY represents the year. • MM represents the month, from 01 (January) to 12 (December). • DD represents the day (01 to 31). • HH represents the hour, in 24 - hour clock format, 00 - 23. • MM represents the minute, 00 - 59. • SS represents the seconds, 00 - 59.
<code>after DD:HH:MM</code>	On 4100i, 5420, 6000, 6100, 6300, 6400, 8100, 8320, 8325/8325H/8325P, 8360, 9300/9300S and 10000 switch series, specify how much time should elapse before the scheduled management module reload, where: • DD represents the number of days before the reload • HH represents the number of hours before the reload • MM represents the number of minutes before the reload.
<code>cancel</code>	Cancel any scheduled reload operations.

Usage

Configuring the reload feature will use one job scheduler space and reduce the number of available job scheduler configurations.

Examples

Scheduling a system reload on 4100i, 5420, 6000, 6100, 6300, 6400, 8100, 8320, 8325/8325H/8325P, 8360, 9300/9300S or 10000 switch series at a specific date and time:

```
switch# reload at 2025-08-12 12:01:00
Reload scheduled at 12:01:00 08/12/2025 (in 10 days, 15 hours, 17 minutes,
12 seconds)
The system will be rebooted at the scheduled time from the secondary image.
Continue (y/n)? y
Warning! Any change in configuration may be lost during the scheduled
reboot.
Please remember to save the changes before the scheduled reboot happens.
Configuring reload feature will reduce one job configuration.
```

Scheduling a system reload on 4100i, 5420, 6000, 6100, 6300, 6400, 8100, 8320, 8325/8325H/8325P, 8360, 9300/9300S or 10000 switch series in one day and one hour from the current time:

```
switch# reload after 01:01:00
Reload scheduled in 1 days, 1 hours, 0 minutes
The system will be rebooted at the scheduled time from the secondary image.
Continue (y/n)? y
Warning! Any change in configuration may be lost during the scheduled
reboot.
Please remember to save the changes before the scheduled reboot happens.
Configuring reload feature will reduce one job configuration.
```

Scheduling a reload of an active management module on a 6400 or 8400 Switch series at a specified date and time:

```
switch# reload active at 2025-08-12 12:01:00
Reload scheduled at 12:01:00 08/12/2025 (in 10 days, 15 hours, 17 minutes,
12 seconds)
The system will be rebooted at the scheduled time from the primary image.
Continue (y/n)? y
Warning! Any change in configuration may be lost during the scheduled
reboot.
Please remember to save the changes before the scheduled reboot happens.
Configuring reload feature will reduce one job configuration.
```

Scheduling a reload of an active management module on a 6400 or 8400 Switch series in one hour and one day from the current time:

```
switch# reload standby after 01:01:00
Reload scheduled in 1 days, 1 hours, 0 minutes
The system will be rebooted at the scheduled time from the secondary image.
Continue (y/n)? y
Warning! Any change in configuration may be lost during the scheduled
reboot.
Please remember to save the changes before the scheduled reboot happens.
Configuring reload feature will reduce one job configuration.
```

Scheduling a reload of VSF member 4 on a 6300M/F or 6200 Switch series at a specified date and time.

```
Switch# reload 4 at 2025-08-12 12:01:00
Reload scheduled at 12:01:00 08/12/2025 (in 10 days, 15 hours, 17 minutes,
12 seconds)
The system will be rebooted at the scheduled time from the primary image.
Continue (y/n)? y
Warning! Any change in configuration may be lost during the scheduled
reboot.
Please remember to save the changes before the scheduled reboot happens.
Configuring reload feature will reduce one job configuration.
```

Scheduling a reload of VSF member 4 on a 6300M/F or 6200 Switch series, one day and one hour after the current time.

```

switch# reload 4 after 01:01:00
Reload scheduled in 1 days, 1 hours, 0 minutes
The system will be rebooted at the scheduled time from the secondary image.
Continue (y/n)? y
Warning! Any change in configuration may be lost during the scheduled
reboot.
Please remember to save the changes before the scheduled reboot happens.
Configuring reload feature will reduce one job configuration.

```

Command History

Release	Modification
10.16.1000	Command introduced.

Command Information

Platforms	Command context	Authority
All platforms	config config-job- <NAME>	Administrators or local user group members with execution rights for this command.

schedule

Syntax

In the config context:

```

schedule <SCHEDULE-NAME> [transient]
no schedule [<SCHEDULE-NAME>]

```

Subcommands available In the schedule config context (`config-schedule`):

```

[no] enable
[no] desc <DESCRIPTION>
[no] [<SEQ-NUM>] job <JOB-NAME>
resequence <START-SEQ-NUM>
        <INCREMENT>
[no] trigger on HH:MM {daily | weekly <1-7> | monthly <1-31>}

```

```

    [count <1-1000>] [start YYYY-MM-DD]
[no] trigger every {days <1-365> | hours <1-8760> | minutes <30-525600>}
    [count <1-1000> ] [start HH:MM [YYYY-MM-DD]]
[no] trigger at HH:MM [YYYY-MM-DD]

```

Description

If <SCHEDULE-NAME> does not exist, this command creates a job schedule and then enters its context.

The **no** form of this command deletes the specified schedule. If no schedule is specified, all schedules are deleted.

If <SCHEDULE-NAME> exists, this command enters the **config-schedule-** <NAME> context for the specified job schedule.

Parameter	Description
<SCHEDULE-NAME>	Specifies the schedule name. Range 1 to 64 characters (alphanumeric and "_" (underscore)).
[transient]	Causes the schedule to be cleared upon switch reboot. By default, schedules are maintained after switch reboots.

Subcommands

These subcommands are available within the `config-schedule-<NAME>` context for scheduling jobs and controlling the order in which the jobs are executed:

enable

Enables the schedule (the default). `no enable` disables the schedule.

```
[no] desc <DESCRIPTION>
```

Specifies a user-defined schedule description. `no desc` removes the description. Range: 1 to 128 characters. For example:

```

switch(config-schedule-Monthly)# desc Monthly schedule
    [no] [
    <SEQ-NUM>
    ] job
    <JOB-NAME>

```

Associates an existing job with this schedule. The no form removes the job from the schedule.

<JOB-NAME> specifies an existing job name. Range: 1 to 64 characters (alphanumeric and "_" (underscore)).

<SEQ-NUM> specifies the job name sequence number to facilitate ordering of jobs within a schedule. When omitted, a sequence number that is 10 greater the highest existing sequence number is auto-assigned. The first auto-assigned sequence number is 10.

For example, associating two jobs with the selected schedule:

```
switch(config-schedule-Monthly) # 10 job PTog1
switch(config-schedule-Monthly) # 20 job PTog2
resequence <START-SEQ-NUM>
           <INCREMENT>
```

Resequences the job name sequence numbers in the schedule. Both **<START-SEQ-NUM>** and **<INCREMENT>** default to 10. For example, resequencing the job list to start at 5 with an increment of 10.

```
switch(config-schedule-Monthly) # resequence 5 10
switch(config-schedule-Monthly) # show schedule Monthly
Schedule Name: Monthly
...
    Scheduled Jobs
    -----
    5      : PTog1
    15     : PTog2
[no] trigger on HH:MM {daily | weekly <1-7> | monthly <1-31>}
           [count <1-1000>] [start YYYY-MM-DD]
```

Sets the job to trigger at a specific time. The no form removes the trigger.

HH:MM selects the time using a 24-hour clock (switch local time). Range: 00:00 to 23:59.

daily selects daily.

weekly <1-7> selects specific days of week or days-of-week ranges (with comma or hyphen separators) using numeric day-of-week numbers with Sunday equal 1. For example: **1, 3, 5-7** for Sunday, Tuesday, Thursday, Friday, Saturday.

monthly <1-31> selects specific days of month or days of month ranges (with comma or hyphen separators) using numeric day-of-month numbers. For example: **5, 14-21, 25, 31**. For months with fewer days than the specified day number, the last day of the month is selected.

count <1-1000> selects the number of times the job will be executed. When omitted, job execution triggering is indefinite.

start YYYY-MM-DD selects the schedule first trigger date. When omitted, today's date is used for times at least 5 minutes into the future, otherwise tomorrow is selected as the first trigger date.

For example, setting the schedule to trigger monthly on the 15th, at 11:45 PM, starting on August 15, with an execution limit of 200:

```
switch(config-schedule-M) # trigger on 23:45 monthly 15 count 200 start
2021-08-15
```



```
[no] trigger every {days <1-365> | hours <1-8760> | minutes  
<30-525600>}  
[count <1-1000>] [start HH:MM [YYYY-MM-DD]]
```

Sets the job trigger to a specific periodic interval. The no form removes the trigger. By default, the schedule is activated within 5 minutes from the configuration time. If the start time is specified, then the job is executed beginning at the specified start time and thereafter at the specified interval.

days <1-365> selects the interval in days. Range: 1 to 365.

hours <1-8760> selects the interval in minutes. Range: 1 to 8760.

minutes <30-525600> selects the interval in seconds. Range: 30 to 525600.

count <1-1000> selects the number of times the job will be executed. When omitted, job execution triggering is indefinite.

start HH:MM [YYYY-MM-DD] selects the schedule first trigger time and date.

For example, setting the schedule to trigger once every 14 days, starting on January 1, with an execution limit of 500:

```
switch(config-schedule-Ev14D) # trigger every days 14 count 500 start  
2022-01-01  
[no] trigger at HH:MM [YYYY-MM-DD]
```

Sets the job to trigger one time only on a specific date and time. When the date is omitted, today's date is used for times at least 5 minutes into the future, otherwise tomorrow is selected. The no form removes the trigger.

For example, setting the schedule to trigger once only on August 26 at midnight:

```
switch(config-schedule-Aug26) # trigger at 00:00 2021-08-26
```

Usage

- A job can be used only once per schedule.
- To see the maximum number of schedules and jobs per schedule for your particular switch, use command **show capacities schedule**.
- Configure the jobs to be executed (using the **job** command) before configuring a schedule.
- Jobs must complete execution in under five minutes and are force-stopped after five minutes if they do not.
- A job must be scheduled to execute at least five minutes after its previous execution. If the same job is scheduled to be executed again within less than five minutes, the execution is skipped.

Examples

Creating a schedule named **PT2xW** that runs the port toggle job **PTog1** on Mondays and Fridays at 11:45 PM, starting on August 2 2021, with a one-year duration:

```
switch(config)# schedule PT2xW
switch(config-schedule-PT2xW)# desc Monday & Friday 11:45 PM port toggles
switch(config-schedule-PT2xW)# 10 job PTog1
switch(config-schedule-PT2xW)# trigger on 23:45 weekly 2,6 count 104 start
2021-08-02
switch(config-schedule-PT2xW)# exit
switch(config)#
```

Creating a schedule named **RB_LDM** that runs the switch reboot job on the last day of the month at 3:00 AM, starting on January 31 2022, with a two-year duration:

```
switch(config)# schedule RB_LDM
switch(config-schedule-RB_LDM)# desc Monthly reboot 3:00 AM
switch(config-schedule-RB_LDM)# 10 job Reboot_sw1
switch(config-schedule-RB_LDM)# trigger on 3:00 monthly 31 count 24 start
2022-01-31
switch(config-schedule-RB_LDM)# exit
```

Command History

Release	Modification
10.08	Command introduced.

Command Information

Platforms	Command context	Authority
All platforms	config config- schedule- <i><NAME></i>	Administrators or local user group members with execution rights for this command.

show job

Syntax

```
show job [<JOB-NAME>] [execution-output <INSTANCE-ID>]
```

Description

Shows information about a specific job or every job. Optionally shows the job execution output log.

Parameter	Description
<JOB-NAME>	Specifies an existing job name. When omitted, information is shown for every job. Range: 1 to 64 characters (alphanumeric and "_" (underscore)).
<INSTANCE-ID>	Selects the job execution output instance with 1 selecting the most recent. To see the maximum number of job execution output instances for your particular switch, use command show capacities job .

Usage

Job execution statistics such as execution counts are reset to zero upon switch reboot.

Examples

Showing port toggle job information before execution has occurred:

```
switch# show job PTog1
Job Name : PTog1
  Enabled           : Yes
  Description       : Toggle port 1/1/1
  Status           : waiting
  Number of commands : 5
  Total execution count : 0
  Failed execution count : 0
  Job CLI commands
  -----
  10 cli config
  20 cli interface 1/1/1
  30 cli shutdown
  40 delay 10 cli no shutdown
  50 cli end
```

Showing port toggle job information after execution has occurred:

```

switch# show job PTog1
Job Name : PTog1
  Enabled           : Yes
  Description       : Toggle port 1/1/1
  Status           : waiting
  Number of commands : 5
  Total execution count : 1
  Failed execution count : 0
  Job execution history
  -----
  Instance number   : 1
  Execution status   : success
  Execution start time : Mon Aug 2 23:45:00 2021
  Execution duration : 10s
  Job CLI commands
  -----
  10 cli config
  20 cli interface 1/1/1
  30 cli shutdown
  40 delay 10 cli no shutdown
  50 cli end

```

Showing port toggle job most recent execution output:

```

switch# show job PTog1 execution-output 1
=====
=====
Command: config
time: Mon Aug 2 23:45:00 2021
=====
=====
=====
=====
Command: interface 1/1/1
time: Mon Aug 2 23:45:00 2021
=====
=====
=====
=====
Command: shutdown
time: Mon Aug 2 23:45:00 2021
=====
=====
=====

```

```

=====
Command: cli no shutdown
time: Mon Aug  2 23:45:10 2021
=====
=====
=====
Command: end
time: Mon Aug  2 23:45:10 2021
=====
=====

```

Command History

Release	Modification
10.08	Command introduced.

Command Information

Platforms	Command context	Authority
All platforms	Operator (>) or Manager (#)	Operators or Administrators or local user group members with execution rights for this command. Operators can execute this command from the operator context (>) only.

show capacities (job, schedule)

Syntax

```
show capacities {job | schedule}
```

Description

Shows either job or schedule capacities information for your switch model.

Examples

Showing job capacities information (8320 example shown):

```

switch# show capacities job
System Capacities: Filter Job

```

Capacities	
Name	Value

Maximum number of job execution output preserved per job	10
Maximum number of jobs configurable in a system	32

Showing schedule capacities information (8320 example shown):

switch# show capacities Schedule	
System Capacities: Filter Schedule	
Capacities	
Name	Value

Maximum number of jobs configurable in a schedule	10
Maximum number of schedules configurable in a system	32

Command History

Release	Modification
10.08	Command introduced.

Command Information

Platforms	Command context	Authority
All platforms	Operator (>) or Manager (#)	Operators or Administrators or local user group members with execution rights for this command. Operators can execute this command from the operator context (>) only.

show reload

Syntax

```
show reload
```

Description

Display the configuration defined using the `reload` command.

Examples

Displaying the reload configuration on a 4100i, 5420, 6000, 6100, 6300, 6400, 8100, 8320, 8325/8325H/8325P, 8360, 9300/9300S or 10000 switch series:

```
switch# show reload
-----
Reload Configuration
-----
Module           :  Chassis
Reboot after     :  2 days, 8 hours, 10 minutes
-----
```

Displaying the reload configuration on an active management module on a 6400 or 8400 Switch series:

```
switch# show reload
-----
Reload Configuration
-----
Module           :  AMM
Reboot after     :  2 days, 8 hours, 08 minutes
-----
```

Displaying the reload configuration on a standby management module on a 6400 or 8400 Switch series:

```
switch# show reload
-----
Reload Configuration
-----
Module           :  SMM
Reboot after     :  2 days, 8 hours, 10 minutes
-----
```

Displaying the reload configuration on a 6300M/F or 6200 Switch series.

```
switch# show reload
-----
Reload Configuration
-----
Module           :  Stack
VSF member       :  2
Reboot at        :  2025-04-12 12:01:00
-----
```

Command History

Release	Modification
10.16.1000	Command introduced.

Command Information

Platforms	Command context	Authority
All platforms	config config-job- <NAME>	Administrators or local user group members with execution rights for this command.

show running-config (job, schedule)

Syntax

```
show running-config [current-context]
```

Description

Shows the entire running configuration for the switch, including configuration details for the Job Scheduler job and schedule configuration.

Parameter	Description
current-context	When included from within the Job Scheduler job or schedule context, shows only the job or schedule configuration information for the selected job or schedule.

Examples

Showing the running configuration information for all jobs and schedules with unrelated configuration information omitted for clarity (omitted portions represented by ellipses("...")):

```
switch# show running-config
Current configuration:
...
```



```

!
job PTog1
  desc Toggle port 1/1/1
  10 cli config
  20 cli interface 1/1/1
  30 cli shutdown
  40 delay 10 cli no shutdown
  50 cli end
job Reboot_sw1
  desc Save config then reboot switch
  10 cli config
  20 cli write mem
  30 cli boot system
schedule PT2xW
  desc Monday & Friday 11:45 PM port toggles
  trigger on 23:45 weekly 2,6 count 104 start 2021-08-02
  10 job PTog1
schedule RB_LDM
  desc Monthly reboot 3:00 AM
  trigger on 3:00 monthly 31 count 24 start 2022-01-31
  10 job Reboot_sw1
...

```

From within the job **PTog1** context, showing the running configuration information for the job:

```

switch(config-job-PTog1)# show running-config current-context
Current configuration:
job PTog1
  desc Toggle port 1/1/1
  10 cli config
  20 cli interface 1/1/1
  30 cli shutdown
  40 delay 10 cli no shutdown
  50 cli end

```

From within the schedule **PT2xW** context, showing the running configuration information for the schedule:

```

switch(config-schedule-PT2xW)# show running-config current-context
Current configuration:
schedule PT2xW
  desc Monday & Friday 11:45 PM port toggles
  trigger on 23:45 weekly 2,6 count 104 start 2021-08-02
  10 job PTog1

```

Command History

Release	Modification
10.08	Command introduced.

Command Information

Platforms	Command context	Authority
All platforms	Operator (>) or Manager (#) <pre>config-job- <NAME> config- schedule- <NAME></pre>	Operators or Administrators or local user group members with execution rights for this command. Operators can execute this command from the operator context (>) only.

show schedule

Syntax

```
show schedule [<SCHEDULE-NAME>]
```

Description

Shows information about a specific schedule or every schedule.

Parameter	Description
<pre><SCHEDULE-NAME></pre>	Specifies an existing job schedule name. When omitted, information is shown for every schedule. Range: 1 to 64 characters (alphanumeric and "_" (underscore)).

Usage

Schedule statistics such as **Triggered count** are reset to zero upon switch reboot.

Examples

Showing port toggle job schedule information before execution has occurred:

```
switch# show schedule PT2xW
Schedule Name: PT2xW
Schedule config
-----
Description      : Monday & Friday 11:45 PM port toggles
Enabled          : Yes
Trigger type     : calendar
Transient        : No
Max trigger count : 104
Trigger start date : 2021-08-02 23:45
Schedule Status
-----
Trigger status   : active
Next trigger time : Mon Aug  2 23:45:00 2021
Scheduled Jobs
-----
10  : PTog1
```

Showing port toggle job schedule information after execution has occurred:

```
switch# show schedule PT2xW
Schedule Name: PT2xW
Schedule config
-----
Description      : Monday & Friday 11:45 PM port toggles
Enabled          : Yes
Trigger type     : calendar
Transient        : No
Max trigger count : 104
Trigger start date : 2021-08-02 23:45
Schedule Status
-----
Trigger status   : active
Next trigger time : Fri Aug  6 23:45:00 2021
Triggered count  : 1
Scheduled Jobs
-----
10  : PTog1
```

Command History

Release	Modification
10.08	Command introduced.

Command Information

Platforms	Command context	Authority
All platforms	Operator (>) or Manager (#)	Operators or Administrators or local user group members with execution rights for this command. Operators can execute this command from the operator context (>) only.

Support and Other Resources

Access HPE Aruba Networking support and updates, and view warranty and regulatory information

Subtopics

[Accessing HPE Aruba Networking Support](#)

[Accessing Updates](#)

[Warranty Information](#)

[Regulatory Information](#)

[Documentation Feedback](#)

Accessing HPE Aruba Networking Support

HPE Aruba Networking Support Services

<https://www.hpe.com/us/en/networking/hpe-aruba-networking-support-services.html>

AOS - CX Switch Software Documentation Portal

HPE Aruba Networking Support Portal

<https://networkingsupport.hpe.com/home>

North America telephone	1 - 800 - 943 - 4526 (US & Canada Toll - Free Number) +1 - 650 - 750 - 0350 (Backup—Toll Number)
International telephone	https://www.hpe.com/psnow/doc/a50011948enw

Be sure to collect the following information before contacting Support:

- Technical support registration number (if applicable)
- Product name, model or version, and serial number
- Operating system name and version
- Firmware version
- Error messages
- Product-specific reports and logs
- Add-on products or components
- Third-party products or components

Other useful sites

Other websites that can be used to find information:

HPE Aruba Networking Developer Hub	https://developer.arubanetworks.com/hpe - aruba - networking - aoscx/docs/about
Airheads social forums and Knowledge Base	https://community.arubanetworks.com/
AOS - CX Software Technical Update channel on YouTube.	Videos on new features introduced in this release : https://www.youtube.com/playlist?list=PLsYGHuNuBZcbWPEjjHuVMqP - Q_UL3CskS
HPE Aruba Networking Hardware Documentation and Translations Portal	
HPE Aruba Networking software	https://networkingsupport.hpe.com/downloads https://networkingsupport.hpe.com/downloads
Software licensing and Feature Packs	https://licensemanagement.hpe.com/

Accessing Updates

You can access updates from the HPE Aruba Networking Support Portal at <https://networkingsupport.hpe.com>.

Some software products provide a mechanism for accessing software updates through the product interface. Review your product documentation to identify the recommended software update method.

To subscribe to eNewsletters and alerts:

<https://networkingsupport.hpe.com/notifications/subscriptions> (requires an active HPE Aruba Networking Support Portal account to manage subscriptions). Security notices are viewable without an HPE Aruba Networking Support Portal account.

Warranty Information

To view warranty information for your product, go to <https://www.arubanetworks.com/support-services/product-warranties/>.

Regulatory Information

To view the regulatory information for your product, view the Safety and Compliance Information for Server, Storage, Power, Networking, and Rack Products, available at <https://www.hpe.com/support/Safety-Compliance-EnterpriseProducts>

Additional regulatory information

HPE Aruba Networking is committed to providing our customers with information about the chemical substances in our products as needed to comply with legal requirements, environmental data (company programs, product recycling, energy efficiency), and safety information and compliance data, (RoHS and WEEE). For more information, see <https://www.arubanetworks.com/company/about-us/environmental-citizenship/>.

Documentation Feedback

HPE Aruba Networking is committed to providing documentation that meets your needs. To help us improve the documentation, send any errors, suggestions, or comments to Documentation Feedback ([**docsfeedback-switching@hpe.com**](mailto:docsfeedback-switching@hpe.com)). When submitting your feedback, include the document title, part number, edition, and publication date located on the front cover of the document. For online help content, include the product name, product version, help edition, and publication date located on the legal notices page.