

AOS-CX 10.07 SNMP/MIB Guide

**6100, 6200, 6300, 6400, 8320, 8325, 8360,
8400 Switch Series**



a Hewlett Packard
Enterprise company

Copyright Information

© Copyright 2021 Hewlett Packard Enterprise Development LP.

Open Source Code

This product includes code licensed under the GNU General Public License, the GNU Lesser General Public License, and/or certain other open source licenses. A complete machine-readable copy of the source code corresponding to such code is available upon request. This offer is valid to anyone in receipt of this information and shall expire three years following the date of the final distribution of this product version by Hewlett Packard Enterprise Company. To obtain such source code, send a check or money order in the amount of US \$10.00 to:

Hewlett Packard Enterprise Company
6280 America Center Drive
San Jose, CA 95002
USA

Notices

The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Confidential computer software. Valid license from Hewlett Packard Enterprise required for possession, use, or copying. Consistent with FAR 12.211 and 12.212, Commercial Computer Software, Computer Software Documentation, and Technical Data for Commercial Items are licensed to the U.S. Government under vendor's standard commercial license.

Links to third-party websites take you outside the Hewlett Packard Enterprise website. Hewlett Packard Enterprise has no control over and is not responsible for information outside the Hewlett Packard Enterprise website.

Contents	3
About this Document	5
Applicable products	5
Latest version available online	5
Command syntax notation conventions	5
About the examples	6
Identifying switch ports and interfaces	7
Identifying modular switch components	8
SNMP	9
SNMP write: PoE write capabilities	9
SNMP traps	9
Configuring SNMP	10
SNMP commands	11
event-trap-enable	11
lldp trap enable	12
rmon alarm	14
rmon alarm {enable disable} {index all}	15
show rmon alarm	16
show snmp agent-port	17
show snmp community	18
show snmp system	18
show snmp trap	19
show snmp vrf	19
show snmpv3 context	20
show snmpv3 engine-id	21
show snmpv3 security-level	21
show snmpv3 users	21
snmp-server agent-port	22
SNMP server community commands	23
snmp-server community	23
access-level	23
access-list	24
snmp-server historical-counters-monitor	25
snmp-server host	25
snmp-server system-contact	27
snmp-server system-description	28
snmp-server system-location	29
snmp-server vrf	29
snmp-server trap-source interface vrf	30
snmp-server trap	31
snmp-server trap vsx	32
snmpv3 context	33
snmpv3 engine-id	34
snmpv3 security-level	35
snmpv3 user	36
Entity MIB support	38

Location of the MIB files on the web	38
Newly introduced MIBs and Traps for 10.07	38
PoE	38
PORT-ACCESS	39
RPVST	39
VSX	39
OIDs that supports SNMP write	40
Support and Other Resources	41
Accessing Aruba Support	41
Accessing Updates	41
Aruba Support Portal	41
My Networking	42
Warranty Information	42
Regulatory Information	42
Documentation Feedback	42

This document describes features of the AOS-CX SNMP MIB. It is intended for administrators responsible for installing, configuring, and managing Aruba switches on a network.

Applicable products

This document applies to the following products:

- Aruba 6100 Switch Series (JL675A, JL676A, JL677A, JL678A, JL679A)
- Aruba 6200 Switch Series (JL724A, JL725A, JL726A, JL727A, JL728A)
- Aruba 6300 Switch Series (JL658A, JL659A, JL660A, JL661A, JL662A, JL663A, JL664A, JL665A, JL666A, JL667A, JL668A, JL762A)
- Aruba 6400 Switch Series (JL741A, R0X26A, R0X27A, R0X29A, R0X30A)
- Aruba 8320 Switch Series (JL479A, JL579A, JL581A)
- Aruba 8325 Switch Series (JL624A, JL625A, JL626A, JL627A)
- Aruba 8360 Switch Series (JL700A, JL701A, JL702A, JL703A, JL706A, JL707A, JL708A, JL709A, JL710A, JL711A)
- Aruba 8400 Switch Series (JL375A, JL376A)

Latest version available online

Updates to this document can occur after initial publication. For the latest versions of product documentation, see the links provided in [Support and Other Resources](#).

Command syntax notation conventions

Convention	Usage
<code>example-text</code>	Identifies commands and their options and operands, code examples, filenames, pathnames, and output displayed in a command window. Items that appear like the example text in the previous column are to be entered exactly as shown and are required unless enclosed in brackets ([]).
example-text	In code and screen examples, indicates text entered by a user.

Convention	Usage
Any of the following: ■ <code><example-text></code> ■ <code><example-text></code> ■ <i>example-text</i> ■ <i>example-text</i>	Identifies a placeholder—such as a parameter or a variable—that you must substitute with an actual value in a command or in code: ■ For output formats where italic text cannot be displayed, variables are enclosed in angle brackets (< >). Substitute the text—including the enclosing angle brackets—with an actual value. ■ For output formats where italic text can be displayed, variables might or might not be enclosed in angle brackets. Substitute the text including the enclosing angle brackets, if any, with an actual value.
	Vertical bar. A logical OR that separates multiple items from which you can choose only one. Any spaces that are on either side of the vertical bar are included for readability and are not a required part of the command syntax.
{ }	Braces. Indicates that at least one of the enclosed items is required.
[]	Brackets. Indicates that the enclosed item or items are optional.
... or ...	Ellipsis: ■ In code and screen examples, a vertical or horizontal ellipsis indicates an omission of information. ■ In syntax using brackets and braces, an ellipsis indicates items that can be repeated. When an item followed by ellipses is enclosed in brackets, zero or more items can be specified.

About the examples

Examples in this document are representative and might not match your particular switch or environment. The slot and port numbers in this document are for illustration only and might be unavailable on your switch.

Understanding the CLI prompts

When illustrating the prompts in the command line interface (CLI), this document uses the generic term `switch`, instead of the host name of the switch. For example:

```
switch>
```

The CLI prompt indicates the current command context. For example:

```
switch>
```

Indicates the operator command context.

```
switch#
```

Indicates the manager command context.

```
switch (CONTEXT-NAME)#
```

Indicates the configuration context for a feature. For example:

```
switch (config-if) #
```

Identifies the `interface` context.

Variable information in CLI prompts

In certain configuration contexts, the prompt may include variable information. For example, when in the VLAN configuration context, a VLAN number appears in the prompt:

```
switch(config-vlan-100) #
```

When referring to this context, this document uses the syntax:

```
switch(config-vlan-<VLAN-ID>) #
```

Where *<VLAN-ID>* is a variable representing the VLAN number.

Identifying switch ports and interfaces

Physical ports on the switch and their corresponding logical software interfaces are identified using the format:

member/slot/port

On the 6100 Switch Series

- *member*: Always 1. VSF is not supported on this switch.
- *slot*: Always 1. This is not a modular switch, so there are no slots.
- *port*: Physical number of a port on the switch.

For example, the logical interface 1/1/4 in software is associated with physical port 4 on the switch.

On the 6200 Switch Series

- *member*: Member number of the switch in a Virtual Switching Framework (VSF) stack. Range: 1 to 8. The primary switch is always member 1. If the switch is not a member of a VSF stack, then member is 1.
- *slot*: Always 1. This is not a modular switch, so there are no slots.
- *port*: Physical number of a port on the switch.

For example, the logical interface 1/1/4 in software is associated with physical port 4 in slot 1 on member 1.

On the 6300 Switch Series

- *member*: Member number of the switch in a Virtual Switching Framework (VSF) stack. Range: 1 to 10. The primary switch is always member 1. If the switch is not a member of a VSF stack, then member is 1.
- *slot*: Always 1. This is not a modular switch, so there are no slots.
- *port*: Physical number of a port on the switch.

For example, the logical interface 1/1/4 in software is associated with physical port 4 on member 1.

On the 6400 Switch Series

- *member*: Always 1. VSF is not supported on this switch.
- *slot*: Specifies physical location of a module in the switch chassis.
 - Management modules are on the front of the switch in slots 1/1 and 1/2.
 - Line modules are on the front of the switch starting in slot 1/3.
- *port*: Physical number of a port on a line module.

For example, the logical interface 1/3/4 in software is associated with physical port 4 in slot 3 on member 1.

On the 83xx Switch Series

- *member*: Always 1. VSF is not supported on this switch.
- *slot*: Always 1. This is not a modular switch, so there are no slots.
- *port*: Physical number of a port on the switch.

For example, the logical interface 1/1/4 in software is associated with physical port 4 on the switch.



If using breakout cables, the port designation changes to x:y, where x is the physical port and y is the lane when split to 4 x 10G or 4 x 25G. For example, the logical interface 1/1/4:2 in software is associated with lane 2 on physical port 4 in slot 1 on member 1.

On the 8400 Switch Series

- *member*: Always 1. VSF is not supported on this switch.
- *slot*: Specifies physical location of a module in the switch chassis.
 - Management modules are on the front of the switch in slots 1/5 and 1/6.
 - Line modules are on the front of the switch in slots 1/1 through 1/4, and 1/7 through 1/10.
- *port*: Physical number of a port on a line module

For example, the logical interface 1/1/4 in software is associated with physical port 4 in slot 1 on member 1.

Identifying modular switch components

- Power supplies are on the front of the switch behind the bezel above the management modules. Power supplies are labeled in software in the format: *member/power supply*:
 - *member*: 1.
 - *power supply*: 1 to 4.
- Fans are on the rear of the switch and are labeled in software as: *member/tray/fan*:
 - *member*: 1.
 - *tray*: 1 to 4.
 - *fan*: 1 to 4.
- Fabric modules are not labeled on the switch but are labeled in software in the format: *member/module*:
 - *member*: 1.
 - *member*: 1 or 2.
- The display module on the rear of the switch is not labeled with a member or slot number.

Simple Network Management Protocol (SNMP) is an Internet-standard protocol used for managing and monitoring the devices connected to a network by collecting, organizing and modifying information about managed devices on IP networks.

SNMP write: PoE write capabilities

PoE enable

The PoE enable is requested through SNMP to enable the PoE interface. The `admin_disable` SNMP value is updated to enable the PoE interface.

PoE disable

The PoE disable is requested through SNMP to disable the PoE interface. The `admin_disable` SNMP value is updated to disable the PoE interface.

PoE cycle

The PoE cycle is a feature where you can request a PoE port reset with a timeout ranging from 1 to 60 seconds. The PoE cycle is requested through the SNMP server to disable and enable a PoE interface with an input timeout of 1 to 60 seconds. The PoE handles the PoE disable and enable events when the SNMP value is updated for `admin_disable` correspondingly. The value of timeout ranges from 1-60 seconds. It is a one-time operation.

SNMP traps

Event log traps

When SNMP is configured, interface daemons event log messages for link-up and link-down events will be sent as traps.

Event log trap OID: 1.3.6.1.4.1.47196.4.1.1.3.4.1.1

Parameter	OID	Description
<code>sysUpTimeInstance</code>	1.3.6.1.2.1.1.3.0	Contains the uptime for the system in centiseconds
<code>snmpTrapOID</code>	1.3.6.1.6.3.1.1.4.1	Contains the OID for the event log trap
<code>eventIndex</code>	1.3.6.1.2.1.16.9.1.1.1	Contains an index that uniquely identifies an event
<code>eventDescription</code>	1.3.6.1.2.1.16.9.1.1.2	Contains the event log message

Link-up and link-down traps

Standard IF-MIB link-up and link-down traps will be sent on link-state change when an interface is configured using `trap link-status` or when `user_config:link_state_snmp_trap` is set to true. The trap sends the current information for ifindex, admin status, operational status, and interface name.

Link up trap OID: 1.3.6.1.6.3.1.1.5.4

Link down trap OID: 1.3.6.1.6.3.1.1.5.3

Parameter	OID	Description
sysUpTimeInstance	1.3.6.1.2.1.1.3.0	Contains the uptime for the system in centiseconds
snmpTrapOID	1.3.6.1.6.3.1.1.4.1	Contains the OID for the link up or linkdown trap
ifIndex	1.3.6.1.2.1.2.2.1.1.X	Contains the ifindex for the interface
ifAdminStatus	1.3.6.1.2.1.2.2.1.7.X	Contains the admin status for the interface
ifOperStatus	1.3.6.1.2.1.2.2.1.8.X	Contains the operational status for the interface
ifDescr	1.3.6.1.2.1.2.2.1.2.X	Contains the name for the interface

Configuring SNMP

SNMP agent provides read-write access for specific OIDs. Refer [OIDs that supports SNMP write](#) for the list of OIDs that supports write operations.

Procedure

1. SNMP is not enabled on the switch by default, unless the user enables it over any available VRF or with the default/mgmt VRF using the command `snmp-server vrf <NAME>`. For example, use the command `snmp-server vrf mgmt` to enable SNMP on the management interface. Use the command `snmp-server vrf default` to enable SNMP on the default VRF. Use the command `snmp-server vrf <USERDEFINED_VRF_NAME>` to enable SNMP on the user created VRF.

2. Set the system contact, location, and description for the switch with the following commands:

- `snmp-server system-contact`
- `snmp-server system-location`
- `snmp-server system-description`

You can also set the system location and system contact values using SNMP.

3. If required, change the default SNMP port on which the agent listens for requests with the command `snmp-server agent-port`.
4. By default, the agent uses the community string **public** to protect access through SNMPv1/v2c. Set a new community string with the command `snmp-server community`.
5. Configure the trap receivers to which the SNMP agent will send trap notifications with the command `snmp-server host`.
6. Create an SNMPv3 context and associate it with any available SNMPv3 user to perform context specific v3 MIB polling using the command `snmpv3 user <V3_USERNAME> context <CONTEXT_NAME>`.

7. Create an SNMPv3 context and associate it with an available SNMPv1/v2c community string to perform context specific v1/v2c MIB polling using the command `snmpv3 context <CONTEXT_NAME> vrf <VRF_NAME> community <COMMUNITY_NAME>`.
8. Review your SNMP configuration settings with the following commands:
 - `show snmp agent-port`
 - `show snmp community`
 - `show snmp system`
 - `show snmpv3 context`
 - `show snmp trap`
 - `show snmp vrf`
 - `show snmpv3 users`
 - `show tech snmp`

Example 1

This example creates the following configuration:

- Enables SNMP on the out-of-band management interface (VRF **mgmt**).
- Sets the contact, location, and description for the switch to: **JaniceM, Building2, LabSwitch**.
- Sets the community string to **Lab8899X**.

```
switch(config)# snmp-server vrf mgmt
switch(config)# snmp-server system-contact JaniceM
switch(config)# snmp-server system-location Building2
switch(config)# snmp-server system-description LabSwitch
switch(config)# snmp-server community Lab8899X
```

Example 2

This example creates the following configuration:

- Creates an SNMPv3 user named **Admin** using **sha** authentication with the plaintext password **mypassword** and using **des** security with the plaintext password **myprivpass**.
- Associates the SNMPv3 user `Admin` with a context named `newContext`.

```
switch(config)# snmpv3 user Admin auth sha auth-pass plaintext mypassword priv des
priv-pass plaintext myprivpass
switch(config)# snmpv3 user Admin context newContext
```

SNMP commands

event-trap-enable

Syntax

`event-trap-enable`

`no event-trap-enable`

Description

Enables the notification of events to be sent as traps to the SNMP management stations. It is enabled by default.

The `no` form of this command disables the event traps.

Command context

`config`

Authority

Administrators or local user group members with execution rights for this command.

Examples

Enabling the event traps:

```
switch(config)# event-trap-enable
```

Disabling the event traps:

```
switch(config)# no event-trap-enable
```

lldp trap enable

Syntax

```
lldp trap enable
```

```
no lldp trap enable
```

Description

Enables sending SNMP traps for LLDP related events from a particular interface. LLDP trap generation is enabled by default on all the interfaces and has to be disabled for interfaces on which traps are not required to be generated.

The `no` form of this command disables the LLDP trap generation.



LLDP trap generation is disabled by default at the global level and must be enabled before any LLDP traps are sent.

Command context

`config` and `config-if`

Authority

Administrators or local user group members with execution rights for this command.

Examples

Enabling LLDP trap generation on global level:

```
switch(config)# lldp trap enable
```

Enabling LLDP trap generation on interface level:

```
switch(config-if)# lldp trap enable
```

Disabling LLDP trap generation on global level:

```
switch(config)# no lldp trap enable
```

Disabling LLDP trap generation on interface level:

```
switch(config-if)# no lldp trap enable
```

Displaying LLDP global configuration:

```
switch# show lldp configuration
```

LLDP Global Configuration

=====

```
LLDP Enabled           : No
LLDP Transmit Interval : 30
LLDP Hold Time Multiplier : 4
LLDP Transmit Delay Interval : 2
LLDP Reinit Timer Interval : 2
LLDP Trap Enabled      : No
```

TLVs Advertised

=====

```
Management Address
Port Description
Port VLAN-ID
System Description
System Name
```

LLDP Port Configuration

=====

PORT	TX-ENABLED	RX-ENABLED	INTF-TRAP-ENABLED
1/1/1	Yes	Yes	Yes
1/1/2	Yes	Yes	Yes
1/1/3	Yes	Yes	Yes
1/1/4	Yes	Yes	Yes
1/1/5	Yes	Yes	Yes
1/1/6	Yes	Yes	Yes
.....			
.....			
mgmt	Yes	Yes	Yes

Displaying LLDP Configuration for the interface:

```
switch# show lldp configuration 1/1/1
```

LLDP Global Configuration

=====

```
LLDP Enabled           : Yes
LLDP Transmit Interval : 30
LLDP Hold Time Multiplier : 4
```

```
LLDP Transmit Delay Interval : 2
LLDP Reinit Timer Interval   : 2
LLDP Trap Enabled            : No
```

LLDP Port Configuration

PORT	TX-ENABLED	RX-ENABLED	INTF-TRAP-ENABLED
1/1/1	Yes	Yes	Yes

Displaying LLDP Configuration for the management interface:

```
switch# show lldp configuration mgmt
```

LLDP Global Configuration

```
LLDP Enabled           : Yes
LLDP Transmit Interval : 30
LLDP Hold Time Multiplier : 4
LLDP Transmit Delay Interval : 2
LLDP Reinit Timer Interval : 2
LLDP Trap Enabled      : Yes
```

LLDP Port Configuration

PORT	TX-ENABLED	RX-ENABLED	INTF-TRAP-ENABLED
mgmt	Yes	Yes	Yes

rmon alarm

Syntax

```
rmon alarm index <INDEX> snmp-oid <SNMP-OID> rising-threshold <RISING-THRESHOLD>
    falling-threshold <FALLING-THRESHOLD> [sample-interval <SAMPLE-INTERVAL>] [sample-type
<ABSOLUTE|DELTA>]
```

```
no rmon alarm [index <INDEX>]
```

Description

Stores configuration entries in an alarm table that defines the sample interval, sample-type, and threshold parameters for an SNMP MIB object. Only the SNMP MIB objects that resolve to an ASN.1 primitive type of INTEGER (INTEGER, Integer32, Counter32, Counter64, Gauge32, or TimeTicks) will be monitored.

The `no` form of this command removes all RMON alarms and allows you to specify an index to remove a particular RMON alarm.

Command context

```
config
```

Parameters

```
index <INDEX>
```

Specifies the RMON alarm index. Range: 1 to 20.

```
snmp-oid <SNMP-OID>
```

Specifies the SNMP MIB object to be monitored by RMON.

rising-threshold <RISING-THRESHOLD>

Specifies the upper threshold value for the RMON alarm.

falling-threshold <FALLING-THRESHOLD>

Specifies the falling threshold value for the RMON alarm. The falling threshold must be less than the rising threshold.

sample-interval <SAMPLE-INTERVAL>

Sample interval in seconds. Default: 30.

sample-type <ABSOLUTE|DELTA>

Specifies the method of sampling of the SNMP MIB object. Default: Absolute.

Authority

Administrators or local user group members with execution rights for this command.

Examples

Configuring RMON for the MIB object **ifOutErrors.15** with an index **1**, rising threshold of **2147483647** and falling threshold of **-2134** using **absolute** sampling for a sample interval of **100** seconds:

```
switch(config)# rmon alarm index 1 snmp-oid ifOutErrors.15 rising-threshold
2147483647
falling-threshold -2134 sample-type absolute sample-interval 100
```

Removing RMON alarm with the index 5:

```
switch(config)# no rmon alarm index 5
```

rmon alarm {enable | disable} {index | all}

Syntax

```
rmon alarm {enable | disable} {index <INDEX> | all}
```

Description

Enables and disables the RMON alarm and its index. RMON alarm is enabled by default.

Command context

config

Parameters

enable

Enables the RMON alarm index

disable

Disables the RMON alarm index.

index <INDEX>

Specifies the RMON alarm index. Range: 1 to 20.

all

Specifies all the RMON alarms.

Authority

Administrators or local user group members with execution rights for this command.

Examples

Enabling or disabling all the RMON alarm:

```
switch(config)# rmon alarm enable all
switch(config)# rmon alarm disable all
```

Enabling or disabling RMON alarm by index:

```
switch(config)# rmon alarm enable index 1
switch(config)# rmon alarm disable index 1
```

show rmon alarm

Syntax

```
show rmon alarm [index <INDEX>]
```

Description

Displays the RMON alarm configurations.

Command context

config

Parameters

index <INDEX>

Specifies the RMON alarm index. Range: 1 to 20.

Authority

Administrators or local user group members with execution rights for this command.

Examples

Showing all RMON alarm configurations:

```
switch# show rmon alarm
Index          : 1
Enabled        : true
Status         : valid
MIB object     : ifOutErrors.15
Sample type    : delta
Sampling interval : 6535 seconds
Rising threshold : 100
Falling threshold : 10
Last sampled value : 0
Last sample time : 2020-09-21 05:58:11

Index          : 3
Enabled        : true
Status         : invalid
MIB object     : IF-MIB::ifDescr.19
Sample type    : absolute
Sampling interval : 10000 seconds
Rising threshold : 4000
```



```
Falling threshold : 10
Last sampled value : 0
```

Showing RMON alarm with alarm index 1:

```
switch# show rmon alarm index 1
Index          : 1
Enabled        : true
Status         : valid
MIB object     : ifOutErrors.15
Sample type    : delta
Sampling interval : 6535 seconds
Rising threshold : 100
Falling threshold : 10
Last sampled value : 0
Last sample time : 2020-06-21 05:58:11
```

Showing disabled RMON alarm information:

```
switch# show rmon alarm
Index          : 1
Enabled        : false
Status         : valid
MIB object     : ifOutErrors.15
Sample type    : delta
Sampling interval : 6535 seconds
Rising threshold : 100
Falling threshold : 10
Last sampled value : 0
Last sample time : 2020-09-21 05:58:11

Index          : 3
Enabled        : false
Status         : invalid
MIB object     : IF-MIB::ifDescr.19
Sample type    : absolute
Sampling interval : 10000 seconds
Rising threshold : 4000
Falling threshold : 10
Last sampled value : 0
```

show snmp agent-port

Syntax

```
show snmp agent-port
```

Description

Displays SNMP agent UDP port number.

Command context

Operator (>) or Manager (#)

Authority

Operators or Administrators or local user group members with execution rights for this command.
Operators can execute this command from the operator context (>) only.

Example

Displaying SNMP agent UDP port number:

```
switch# show snmp agent-port
SNMP agent port : 161
```

show snmp community

Syntax

```
show snmp community
```

Description

Displays a list of all configured SNMPv1/v2c communities.

Command context

Manager (#)

Authority

Administrators or local user group members with execution rights for this command.

Usage

When a user creates a custom community before enabling an SNMP agent, AOS-CX automatically removes the default `public` community from the system.

Example

Displaying a list of all configured SNMPv1/v2c communities:

Before any community is created by user

```
switch# show snmp community
-----
SNMP communities
-----
public
```

After community is created by user

```
switch#show snmp community
-----
SNMP communities
-----
private
private2
```

show snmp system

Syntax

```
show snmp system
```

Description

Displays SNMP description, location, and contact information.

Command context

Operator (>) or Manager (#)

Authority

Operators or Administrators or local user group members with execution rights for this command.
Operators can execute this command from the operator context (>) only.

Example

Displaying SNMP description, location, and contact information:

```
switch# show snmp system
SNMP system information
-----
System description : Aggregation router
System location   : Main lab
System contact    : John Smith, Lab Admin
```

show snmp trap

Syntax

```
show snmp trap
```

Description

Displays all configured SNMP traps/informs receivers.

Command context

Operator (>) or Manager (#)

Authority

Operators or Administrators or local user group members with execution rights for this command.
Operators can execute this command from the operator context (>) only.

Example

Displaying all configured SNMP trap and informs receivers:

```
switch# show snmp trap
HOST                                PORT  TYPE    VER  COMMUNITY/USER NAME  VRF
-----
10.10.10.10                        162   trap    v1   public                default
10.10.10.10                        162   inform  v2c  public                default
10.10.10.10                        162   inform  v3   name                  default
```

show snmp vrf

Syntax

```
show snmp vrf
```

Description

Displays the VRF on which the SNMP agent service is running.

Command context

Operator (>) or Manager (#)

Authority

Operators or Administrators or local user group members with execution rights for this command.
Operators can execute this command from the operator context (>) only.

Example

Displaying SNMP services enabled on VRF:

```
switch#show snmp vrf
SNMP enabled VRF
-----
mgmt
default
```

show snmpv3 context

Syntax

```
show snmpv3 context
```

Description

Displays all configured SNMP contexts.

Command context

Operator (>) or Manager (#)

Authority

Operators or Administrators or local user group members with execution rights for this command.
Operators can execute this command from the operator context (>) only.

Examples

Displaying all configured SNMP contexts:

```
switch# show snmpv3 context
-----
name                                vrf                                community
-----
contextA                           default                           private
contextB          vrf_A            public
```

```
switch# show snmpv3 context
-----
Name          vrf          Community          ype[Instance_id]
-----
A              default      public             vrf
switch#
```

show snmpv3 engine-id

Syntax

```
show snmpv3 engine-id
```

Description

Displays the configured SNMPv3 snmp engine-id.

If the SNMPv3 engine-id is not configured, by default a unique engine-id is created by the switch using a combination of the enterprise OID value and the switch's mac address.

Command context

Operator (>) or Manager (#)

Authority

Operators or Administrators or local user group members with execution rights for this command. Operators can execute this command from the operator context (>) only.

Example

Displaying the configured SNMPv3 engine-id:

```
switch# show snmpv3 engine-id
SNMP engine-id : 80:00:B8:5C:08:00:09:1d:de:a5
```

show snmpv3 security-level

Syntax

```
show snmpv3 security-level
```

Description

Displays the configured SNMPv3 security level.

Command context

Operator (>) or Manager (#)

Authority

Operators or Administrators or local user group members with execution rights for this command. Operators can execute this command from the operator context (>) only.

Examples

Displaying the configured SNMPv3 security level:

```
switch# show snmpv3 security-level
SNMPv3 security-level : auth
```

show snmpv3 users

Syntax

```
show snmpv3 users
```

Description

Displays all configured SNMPv3 users.

For more details on the user enabled status, see [snmpv3 security-level](#).

Command context

Operator (>) or Manager (#)

Authority

Operators or Administrators or local user group members with execution rights for this command. Operators can execute this command from the operator context (>) only.

Example

Displaying all configured SNMPv3 users:

```
switch# show snmpv3 users
-----
User                               AuthMode  PrivMode  Context  Enabled
-----
name                               md5       none      none     False
name2                              sha       aes       none     True
```

snmp-server agent-port

Syntax

```
snmp-server agent-port <PORT>
```

```
no snmp-server agent-port [<PORT>]
```

Description

Sets the UDP port number that the SNMP master agent uses to communicate. UDP port 161 is the default port.

The `no` form of this command sets the SNMP master agent port to the default value.

Command context

config

Parameters

<PORT>

Specifies the UDP port number that the SNMP master agent will use. Range: 1 to 65535. Default: 161.

Authority

Administrators or local user group members with execution rights for this command.

Examples

Setting the SNMP master agent port to **2000**:

```
switch(config)# snmp-server agent-port 2000
```

Resetting the SNMP master agent port to the default value:

```
switch(config-schedule)# no snmp-server agent-port 2000
```

SNMP server community commands

snmp-server community

Syntax

```
snmp-server community <STRING>
```

```
no snmp-server community <STRING>
```

Description

Adds an SNMPv1/SNMPv2c community string. A community string is a password that controls read access to the SNMP agent. A network management program must supply this name when attempting to get SNMP information from the switch. A maximum of 10 community strings are supported. Once you create your own community string, the default community string (`public`) is deleted.

The `no` form of this command removes the specified SNMPv1/SNMPv2c community string. When no community string exists, a default community string with the value `public` is automatically defined.

Command context

config

Parameters

<STRING>

Specifies the SNMPv1/SNMPv2c community string. Range: 1 to 32 printable ASCII characters, excluding space and question mark.

Authority

Administrators or local user group members with execution rights for this command.

Examples

Setting the SNMPv1/SNMPv2c community string to **private**:

```
switch(config)# snmp-server community private
```

Removing SNMPv1/SNMPv2c community string **private**:

```
switch(config)# no snmp-server community private
```

access-level

Syntax

```
access-level <ro|rw>
```

```
no access-level <ro|rw>
```

Description

Changes the access level of the SNMP community. The default access level is read-only (`ro`).

The `no` form of this command changes the access level of the community to default.

Command context

`config-community`

Parameters

`ro`

Specifies Read-Only access with the SNMP community.

`rw`

Specifies Read-Write access with the SNMP community.

Authority

Administrators or local user group members with execution rights for this command.

Examples

Enabling the SNMP community:

```
switch(config)# snmp-server community my_community
switch(config-community)#
```

Configuring the access level for the SMNP community:

```
switch(config-community)# access-level rw
```

Changing the access level of the SNMP community to default:

```
switch(config-community)# no access-level rw
```

access-list

Syntax

```
access-list <ACL-NAME>
```

```
no access-list <ACL-NAME>
```

Description

Associates an ACL with the SNMP community. If an ACL is not associated with the SNMP community, the default access is allowed for all the hosts.

The `no` form of this command removes association of the ACL with the SNMP community.

Command context

`config-community`

Parameters

`<ACL-NAME>`

Specifies the ACL name. It supports a maximum of 64 characters.

Authority

Administrators or local user group members with execution rights for this command.

Examples

Enabling the SNMP community:

```
switch(config)# snmp-server community my_community  
switch(config-community)#
```

Associating an ACL with the SMNP community:

```
switch(config-community)# access-list my_acl
```

Removing the associated ACL with the SNMP community:

```
switch(config-community)# no access-list my_acl
```



hitcounts for SNMP ACL will not be incremented.

Example: `show access-list hitcounts ip all` will not show the hit count of SNMP ACL.

snmp-server historical-counters-monitor

Syntax

```
snmp-server historical-counters-monitor
```

```
no snmp-server historical-counters-monitor
```

Description

Enables the Remote Network Monitoring agent (`rmond`) to start collecting historical interface statistics. The `no` form of this command stops the historical interface statistics collection.

Command context

Operator (>) or Manager (#)

Authority

Operators or Administrators or local user group members with execution rights for this command. Operators can execute this command from the operator context (>) only.

Example

Enabling the `rmond` agent to start historical interface statistics collection:

```
switch(config)# snmp-server historical-counters-monitor
```

Disabling the `rmond` agent to stop historical interface statistics collection:

```
switch(config)# no snmp-server historical-counters-monitor
```

snmp-server host

Syntax

```
snmp-server host <IPv4-ADDR | IPv6-ADDR> trap version <VERSION> [community <STRING>]
[port <UDP-PORT>] [<VRF-NAME>]
```

```
no snmp-server host <IPv4-ADDR | IPv6-ADDR> trap version <VERSION> [community <STRING>]
[port <UDP-PORT>] [<VRF-NAME>]
```

```
snmp-server host <IPv4-ADDR | IPv6-ADDR> inform version v2c [community <STRING>]
[port <UDP-PORT>] [<VRF-NAME>]
```

```
no snmp-server host <IPv4-ADDR | IPv6-ADDR> inform version v2c [community <STRING>]
[port <UDP-PORT>] [<VRF-NAME>]
```

```
snmp-server host <IPv4-ADDR | IPv6-ADDR> [trap version v3 | inform version v3] user <NAME>
[port <UDP-PORT>] [<VRF-NAME>]
```

```
no snmp-server host <IPv4-ADDR | IPv6-ADDR> [trap version v3 | inform version v3] user
<NAME>
[port <UDP-PORT>] [<VRF-NAME>]
Description
```

Configures a trap/informs receiver to which the SNMP agent can send SNMP v1/v2c/v3 traps or v2c informs. A maximum of 30 SNMP traps/informs receivers can be configured.

The `no` form of this command removes the specified trap/inform receiver.

Command context

config

Parameters

<IPv4-ADDR>

Specifies the IP address of a trap receiver in IPv4 format (x.x.x.x), where x is a decimal number from 0 to 255. You can remove leading zeros. For example, the address 192.169.005.100 becomes 192.168.5.100.

<IPv6-ADDR>

Specifies the IP address of a trap receiver in IPv6 format (x:x::x:x).

trap version <VERSION>

Specifies the trap notification type for SNMPv1, v2c or v3. Available options are: v1, v2c or v3.

inform version v2c

Specifies the inform notification type for SNMPv2c.

trap version v3

Specifies the trap notification type for SNMPv3.

user <NAME>

Specifies the SNMPv3 user name to be used in the SNMP trap notifications.

community <STRING>

Specifies the name of the community string to use when sending trap notifications. Range: 1 - 32 printable ASCII characters, excluding space and question mark. Default: public.

<UDP-PORT>

Specifies the UDP port on which notifications are sent. Range: 1 - 65535. Default: 162.

<VRF-NAME>

Specifies the VRF on which the SNMP agent listens for incoming requests.

Authority

Administrators or local user group members with execution rights for this command.

Examples

```

switch(config)# snmp-server host 10.10.10.10 trap version v1
switch(config)# no snmp-server host 10.10.10.10 trap version v1
switch(config)# snmp-server host a:b::c:d trap version v1
switch(config)# no snmp-server host a:b::c:d trap version v1
switch(config)# snmp-server host 10.10.10.10 trap version v2c community public
switch(config)# no snmp-server host 10.10.10.10 trap version v2c community public
switch(config)# snmp-server host a:b::c:d trap version v2c community public
switch(config)# no snmp-server host a:b::c:d trap version v2c community public
switch(config)# snmp-server host 10.10.10.10 trap version v2c community public port
5000
switch(config)# no snmp-server host 10.10.10.10 trap version v2c community public
port 5000
switch(config)# snmp-server host 10.10.10.10 trap version v2c community public port
5000 vrf default
switch(config)# no snmp-server host 10.10.10.10 trap version v2c community public
port 5000 vrf default
switch(config)# snmp-server host a:b::c:d trap version v2c community public port
5000
switch(config)# no snmp-server host a:b::c:d trap version v2c community public port
5000
switch(config)# snmp-server host 10.10.10.10 inform version v2c community public
switch(config)# no snmp-server host 10.10.10.10 inform version v2c community public
switch(config)# snmp-server host a:b::c:d inform version v2c community public
switch(config)# no snmp-server host a:b::c:d inform version v2c community public
switch(config)# snmp-server host 10.10.10.10 inform version v2c community public
port 5000
switch(config)# no snmp-server host 10.10.10.10 inform version v2c community public
port 5000
switch(config)# snmp-server host 10.10.10.10 inform version v2c community public
port 5000 vrf default
switch(config)# no snmp-server host 10.10.10.10 inform version v2c community public
port 5000 vrf default
switch(config)# snmp-server host a:b::c:d inform version v2c community public port
5000
switch(config)# no snmp-server host a:b::c:d inform version v2c community public
port 5000
switch(config)# snmp-server host 10.10.10.10 trap version v3 user Admin
switch(config)# no snmp-server host 10.10.10.10 trap version v3 user Admin
switch(config)# snmp-server host a:b::c:d trap version v3 user Admin
switch(config)# no snmp-server host a:b::c:d trap version v3 user Admin
switch(config)# snmp-server host 10.10.10.10 trap version v3 user Admin port 2000
switch(config)# no snmp-server host 10.10.10.10 trap version v3 user Admin port 2000
switch(config)# snmp-server host a:b::c:d trap version v3 user Admin port 2000
switch(config)# no snmp-server host a:b::c:d trap version v3 user Admin port 2000

```

snmp-server system-contact

Syntax

```
snmp-server system-contact <INFO>
```

```
no snmp-server system-contact [<INFO>]
```

Description

Sets SNMP contact information.

The no form of this command removes the SNMP contact information.

Command context

config

Parameters

<INFO>

Specifies SNMP contact information. Range: 1 to 128 printable ASCII characters, except for question mark (?).

Authority

Administrators or local user group members with execution rights for this command.

Examples

Defines SNMP contact information to be **John Smith, Lab Admin**:

```
switch(config)# snmp-server system-contact John Smith, Lab Admin
```

Removes SNMP contact information:

```
switch(config)# no snmp-server system-contact
```

snmp-server system-description

Syntax

```
snmp-server system-description <DESCRIPTION>
```

```
no snmp-server system-description
```

Description

Sets the SNMP system description.

The `no` form of this command removes the SNMP system description.

Command context

config

Parameters

<DESCRIPTION>

Specifies the SNMP system description. Typical content to include would be the full name and version of the following:

- Hardware type of the system
- Software operating system
- Networking software

Range: 1 to 64 printable ASCII characters, except for the question mark (?).

Authority

Administrators or local user group members with execution rights for this command.

Examples

Defines the SNMP system description to be **mainSwitch**:

```
switch(config)# snmp-server system-description mainSwitch
```

Removes the SNMP system description:

```
switch(config)# no snmp-server system-description mainSwitch
```

snmp-server system-location

Syntax

```
snmp-server system-location <INFO>
```

```
no snmp-server system-location
```

Description

Sets the SNMP location information.

The `no` form of this command removes the SNMP location information.

Command context

config

Parameters

<INFO>

Specifies the SNMP location information. Range: 1 to 128 printable ASCII characters, except for the question mark (?).

Authority

Administrators or local user group members with execution rights for this command.

Examples

Defines the SNMP location information to be **Main Lab**:

```
switch(config)# snmp-server system-location Main Lab
```

Removes the SNMP location information:

```
switch(config)# no snmp-server system-location
```

snmp-server vrf

Syntax

```
snmp-server vrf <VRF-NAME>
```

```
no snmp-server vrf <VRF-NAME>
```

Description

Configures a VRF on which the SNMP agent listens for incoming requests. By default, the SNMP agent does not listen on any VRF. 6100 only supports default VRF. The SNMP agent can listen on multiple VRFs.

The `no` form of this command stops the SNMP agent from listening for incoming requests on the specified VRF.

Command context

config

Parameters

<VRF-NAME>

Specifies the name of a VRF.

Authority

Administrators or local user group members with execution rights for this command.

Examples

Configuring the SNMP agent to listen on VRF `default`.

```
switch(config)# snmp-server vrf default
```

Configuring the SNMP agent to listen on VRF `mgmt`.

```
switch(config)# snmp-server vrf mgmt
```

Configuring the SNMP agent to listen on used-defined VRF `myvrf`.

```
switch(config)# snmp-server vrf myvrf
```

Stopping the SNMP agent from listening on VRF `default`.

```
switch(config)# no snmp-server vrf default
```

snmp-server trap-source interface vrf

Syntax

```
snmp-server trap-source {interface <IF-NAME> | <IPv4-Address> | <IPv6-Address>} [vrf <VRF-NAME>]
```

```
no snmp-server trap-source {interface <IF-NAME> | <IPv4-Address> | <IPv6-Address>} [vrf <VRF-NAME>]
```

Description

Configures SNMP trap source interface or IP address for a VRF.

The `no` form of this command removes the SNMP `trap-source` configuration for a VRF.

Command context

config

Parameters

<IF-NAME>

Specifies the source interface name. Interface name can be physical interface, loopback interface, LAG interface, or VLAN interface.

<IPv4-Address>

Specifies the IPv4 address of source interface for the SNMP trap.

<IPv6-Address>

Specifies the IPv6 address of source interface for the SNMP trap.

<VRF-NAME>

Specifies the name of a VRF associated to the source interface for the SNMP trap.

Authority

Administrators or local user group members with execution rights for this command.

Examples

Configuring SNMP trap source interface for a VRF.

```
switch(config)# snmp-server trap-source interface 1/1/12 vrf sample
switch(config)# snmp-server trap-source interface loopback10 vrf sample
switch(config)# snmp-server trap-source interface vlan23 vrf sample
```

Configuring SNMP trap source IP address for a VRF.

```
switch(config)# snmp-server trap-source 10.0.0.1 vrf red
switch(config)# snmp-server trap-source 1001::1 vrf red
```

snmp-server trap

Syntax

```
snmp-server trap {cpu-utilization | memory-utilization | rmon-events}
no snmp-server trap {cpu-utilization | memory-utilization | rmon-events}
```

Description

Enables the SNMP traps. The SNMP traps are enabled by default.

The `no` form of this command disables the SNMP traps.

Command context

config

Parameters

cpu-utilization

Enables the CPU utilization traps.

memory-utilization

Enables the memory utilization traps.

rmon-events

Enables the RMON event traps.

Authority

Administrators or local user group members with execution rights for this command.

Examples

Enabling the SNMP traps:

```
switch(config)# snmp-server trap cpu-utilization
switch(config)# snmp-server trap memory-utilization
switch(config)# snmp-server trap rmon-events
```

Disabling the SNMP traps:

```
switch(config)# no snmp-server trap cpu-utilization
switch(config)# no snmp-server trap memory-utilization
switch(config)# no snmp-server trap rmon-events
```

Displaying the SNMP trap configuration:

```
switch(config)# show running-config all | inc snmp
snmp-server trap rmon-events
snmp-server trap cpu-utilization
snmp-server trap memory-utilization
```

Displaying CPU and Memory usage:

```
switch(config)# show system
Hostname           : XXXX
System Description : XX.10.07.0001CI
System Contact     :
System Location    :
Vendor             : Aruba
Product Name       : JLXXXX XXXX Base Chassis/3xFT/18xFans/Cbl Mgr/X462 Bundle
Chassis Serial Nbr : SG6Z009068
Base MAC Address   : f40343-806400
ArubaOS-CX Version : XX.10.07.0001CI
Time Zone          : UTC
Up Time            : 8 minutes
CPU Util (%)       : 1
Memory Usage (%)   : 10
```

snmp-server trap vsx

Syntax

```
snmp-server trap vsx
```

```
no snmp-server trap vsx
```

Description

Enables sending the SNMP traps for VSX related events. VSX trap generation is disabled by default.

The `no` form of this command disables sending the SNMP traps for VSX related events.

The trap support is available for the following VSX events:

- ISL up and down
- KA up and down
- MCLAG up and down

Command context

config

Parameters

vsx

Specifies SNMP traps for VSX events.

Authority

Administrators or local user group members with execution rights for this command.

Examples

Enabling the VSX traps:

```
switch(config)# snmp-server trap vsx
```

```
switch(config)# show vsx configuration trap
SNMP traps : Enabled
```

Disabling the VSX traps:

```
switch(config)# no snmp-server trap vsx
```

```
switch(config)# show vsx configuration trap
SNMP traps : Disabled
```

snmpv3 context

Syntax

```
snmpv3 context <NAME> vrf <VRF-NAME> [community <STRING>]
```

```
no snmpv3 context <NAME> [vrf <VRF-NAME>]
```

Description

Creates an SNMPv3 context on the specified VRF.

The `no` form of this command removes the specified SNMP context.

Command context

config

Parameters

<NAME>

Specifies the name of the context. Range: 1 to 32 printable ASCII characters, excluding space and question mark (?).

vrf <VRF-NAME>

Specifies the VRF associated with the context. Default: default.

community <STRING>

Specifies the SNMP community string associated with the context. Range: 1 to 32 printable ASCII characters, excluding space and question mark. Default: public.

Authority

Administrators or local user group members with execution rights for this command.

Examples

Creating an SNMPv3 context named **newContext**:

```
switch(config)# snmpv3 context newContext
```

Creating an SNMPv3 context named **newContext** on VRF **myVrf** and with community string **private**.

```
switch(config)# snmpv3 context newContext vrf myVrf community private
```

Removing the SNMPv3 context named **newContext** on VRF **myVrf**:

```
switch(config)# no snmpv3 context newContext vrf myVrf
```

snmpv3 engine-id

Syntax

```
snmpv3 engine-id <ENGINE-ID>
```

```
no snmpv3 engine-id <ENGINE-ID>
```

Description

Configures the SNMPv3 SNMP engine-id allowing an administrator to configure a unique SNMP engine-id for the switch. This engine-id is used by the NMS management tool to identify and distinguish multiple switches on the same network.

The **no** form of this command restores the default engine-id, created by the switch using a combination of the enterprise OID value and the switch's mac address.

Command context

```
config
```

Parameters

<ENGINE-ID>

SNMPv3 SNMP engine-id in colon separated hexadecimal notation.

Authority

Administrators or local user group members with execution rights for this command.

Examples

Configuring the SNMPv3 engine-id:

```
switch(config)#  
switch(config)# snmpv3 engine-id  
WORD SNMPv3 snmp engine-id in colon seperated hexadecimal notation  
switch(config)# snmpv3 engine-id 01:23:45:67:89:ab:cd:ef:01:23:45:67
```

Restoring the default SNMPv3 engine-id:

```
switch(config)# no snmpv3 engine-id
```

snmpv3 security-level

Syntax

```
snmpv3 security-level {auth | auth-privacy}  
no snmpv3 security-level {auth | auth-privacy}
```

Description

Configures the SNMPv3 security level. The security level determines which SNMPv3 users defined by the command `snmpv3 user` are able to connect.

The `no` form of this command changes the security level as follows:

- `no snmpv3 security-level auth`: Sets the security level to `auth-privacy`.
- `no snmpv3 security-level auth-privacy`: Sets the security level to no authentication or privacy, allowing any SNMP user to connect.

Command context

config

Parameters

`auth`

SNMPv3 users that support authentication, or authentication and privacy are allowed.

`auth-privacy`

Only SNMPv3 users with both authentication and privacy are allowed. This is the highest level of SNMPv3 security. Default.

Authority

Administrators or local user group members with execution rights for this command.

Examples

Setting the SNMPv3 security level to authentication and privacy:

```
switch(config)# snmpv3 security-level auth-privacy
```

Setting the SNMPv3 security level to authentication only:

```
switch(config)# snmpv3 security-level auth
```

Setting the SNMPv3 security level to no authentication and no privacy:

```
switch(config)# no snmpv3 security-level auth-privacy
```

Restoring the default SNMPv3 security level to authentication and privacy:

```
switch(config)# no snmpv3 security-level auth
```

snmpv3 user

Syntax

```
snmpv3 user <NAME>
    [auth <AUTH-PROTO> auth-pass [{plaintext | ciphertext} <AUTH-PASS>]]
    [priv <PRIV-PROTO> priv-pass [{plaintext | ciphertext} <PRIV-PASS>]]
no snmpv3 user <NAME>
    [auth <AUTH-PROTO> auth-pass [{plaintext | ciphertext} <AUTH-PASS>]]
    [priv <PRIV-PROTO> priv-pass [{plaintext | ciphertext} <PRIV-PASS>]]
```

Description

Creates an SNMPv3 user and adds it to an SNMPv3 context. The SNMPv3 security level (set with command `snmpv3 security-level`) determines which users are allowed to authenticate.

The `no` form of this command removes the specified SNMPv3 user.

Command context

config

Parameters

<NAME>

Specifies the SNMPv3 username. Range 1 to 32 printable ASCII characters, excluding space and question mark (?).

auth <AUTH-PROTO>

Selects the authentication protocol used to validate user logins: `md5` or `sha1`.

auth-pass [{plaintext | ciphertext} <AUTH-PASS>]

Specifies the SNMPv3 user authentication password. Range for `plaintext` is 8 to 32 printable ASCII characters, excluding space and question mark (?). Range for `ciphertext` is 1 to 256 printable ASCII characters. Ciphertext is used when copying user configuration settings between switches.

priv <PRIV-PROTO>

Selects the SNMPv3 privacy protocol (encryption method): `aes` or `des`.

priv-pass [{plaintext | ciphertext} <PRIV-PASS>]

Specifies the SNMPv3 user privacy encryption password. Range for `plaintext` is 8 to 32 printable ASCII characters, excluding space and question mark (?). Range for `ciphertext` is 1 to 256 printable ASCII characters. Ciphertext is used when copying user configuration settings between switches.



When the authentication password is not provided on the command line, plaintext authentication password prompting occurs upon pressing Enter, followed by privacy encryption protocol prompting, and finally plaintext encryption password prompting. The entered password characters are masked with asterisks.



When the authentication type and password plus the privacy protocol (encryption method) are provided on the command line but the encryption password is not provided, plaintext encryption password prompting occurs upon pressing Enter. The entered password characters are masked with asterisks.

Authority

Administrators or local user group members with execution rights for this command.

Examples

Defining SNMPv3 user **Admin1** using **sha** authentication and **des** privacy encryption with provided plaintext passwords:

```
switch(config)# snmpv3 user Admin1 auth sha auth-pass plaintext F82#450h
priv des priv-pass plaintext F82#4eva
```

Defining SNMPv3 user **Admin2** using **MD5** authentication and **AES** privacy encryption with provided authentication password and privacy encryption type but prompted encryption password:

```
switch(config)# snmpv3 user Admin2 auth md5 auth-pass plaintext F82#450h
priv aes priv-pass
Enter the privacy encryption key: *****
Re-Enter the privacy encryption key: *****
```

Defining SNMPv3 user **Admin2** using **MD5** authentication and **AES** privacy encryption with plaintext password prompting and privacy encryption selection:

```
switch(config)# snmpv3 user Admin2 auth md5 auth-pass
Enter the authentication password: *****
Re-Enter the authentication password: *****

Configure the privacy protocol (y/n)? y
Enter the privacy protocol (aes/des)? aes

Enter the privacy encryption key: *****
Re-Enter the privacy encryption key: *****
```

Removing SNMPv3 user **Admin1**:

```
switch(config)# no snmpv3 user Admin1
```

Creating an SNMP user on switch 1 and then creating the same user on switch 2 by copying from the switch 1 configuration:

On switch 1, configure a user named **Admin3**, and then use the `show running-config` command to display switch configuration. Save a copy of the full `snmpv3 user` command (shown by `show running-config`). This saved command is used on switch 2.

```
switch1(config)# snmpv3 user Admin3 auth sha auth-pass plaintext F82#450h
priv des priv-pass plaintext F82#4eva
switch1(config)# exit
switch1# show running-config
Current configuration:
!
!Version ArubaOS-CX xx.xx.xx.xxxxxx
!
snmpv3 user Admin3 auth sha auth-pass ciphertext AQBaf2d...FJVcZ3o=
priv des priv-pass ciphertext AQBah2p...2jftFwQ=
ssh server vrf mgmt
!
interface mgmt
 no shutdown
 ip dhcp
```

```
vlan 1
```

On switch 2, execute the `snmpv3 user` command that you saved from switch 1 (as shown by `show running-config`). This creates the user on switch 2 with the same configuration.

```
switch2(config)# snmpv3 user Admin3 auth sha auth-pass ciphertext AQBaf2d...FJVcZ3o=  
priv des priv-pass ciphertext AQBah2p...2jFTFwQ=
```

Entity MIB support

The Entity MIB, rfc 6933, allows network managers to retrieve physical containment and logical relationships for devices in the network. The `entConfigChange` trap is sent to configured SNMP-server hosts when a change occurs. The trap is configured to send notifications no more than once every 5 seconds. We will be supporting the Entity MIB for read-only.

Physical components that are supported include:

- Stack
- Chassis
- Fabric cards
- Fan trays
- Fans
- Line cards and their interfaces
- Management modules and the intake temperature sensor
- Power supplies

The slots for any removable component are also represented.

The logical table of the Entity MIB represents configured VLANs and the associated ports.

`entConfigChange` trap/notification is sent to configured snmp-server hosts.

Location of the MIB files on the web

The MIB files for Aruba switches can be found on the [Aruba Service Portal](#). You can apply the various filters to filter by product series, software versions, and software release types.

Newly introduced MIBs and Traps for 10.07

The following list contains the newly introduced MIBs and Traps for each software feature. Software is provided along with the MIB and Traps supported name.

PoE

MIB file

ARUBAWIRED-POE-MIB

Implemented MIB objects:

- `arubaWiredPoePethPsePortPoECycle`

PORT-ACCESS

MIB file

ARUBAWIRED-PORT-ACCESS-MIB.mib

Implemented MIB objects

■ arubaWiredPortAccessClientTable

- arubaWiredPacPortName
- arubaWiredPacMac
- arubaWiredPacUserName
- arubaWiredPacAppliedRole
- arubaWiredPacAppliedRoleType
- arubaWiredPacOnboardedMethods
- arubaWiredPacAuthState
- arubaWiredPacAuthFailureReason
- arubaWiredPacVlanId

■ arubaWiredPortAccessRoleTable

- arubaWiredParName
- arubaWiredParOrigin
- arubaWiredParUbtGatewayRole
- arubaWiredParUbtGatewayClearpassRole
- arubaWiredParGatewayZone
- arubaWiredParVlanId
- arubaWiredParVlanMode

RPVST

MIB file

ARUBAWIRED-RPVST-MIB

Implemented MIB objects

- arubaWiredRpvstCurrentVportCount
- arubaWiredRpvstMstpInterconnectVlan

VSX

MIB file

ARUBAWIRED-VSX-MIB.mib

Traps supported

- mclagLocalUpPeerUp
- mclagLocalUpPeerDown
- mclagLocalDownPeerUp
- mclagLocalDownPeerDown

OIDs that supports SNMP write

The following table contains the OIDs that supports SNMP write:

Software Feature	MIB File	OID
SNMPv2 System	SNMPv2-MIB.mib	■ sysContact ■ sysName ■ sysLocation
PoE	■ ARUBAWIRED-POE.mib ■ POWER-ETHERNET-MIB	■ arubaWiredPoePethPsePortPoECycle ■ pethPsePortAdminEnable

Accessing Aruba Support

Aruba Support Services	https://www.arubanetworks.com/support-services/
Aruba Support Portal	https://asp.arubanetworks.com/
North America telephone	1-800-943-4526 (US & Canada Toll-Free Number) +1-408-754-1200 (Primary - Toll Number) +1-650-385-6582 (Backup - Toll Number - Use only when all other numbers are not working)
International telephone	https://www.arubanetworks.com/support-services/contact-support/

Be sure to collect the following information before contacting Support:

- Technical support registration number (if applicable)
- Product name, model or version, and serial number
- Operating system name and version
- Firmware version
- Error messages
- Product-specific reports and logs
- Add-on products or components
- Third-party products or components

Other useful sites

Other websites that can be used to find information:

Airheads social forums and Knowledge Base	https://community.arubanetworks.com/
Software licensing	https://lms.arubanetworks.com/
End-of-Life information	https://www.arubanetworks.com/support-services/end-of-life/
Aruba software and documentation	https://asp.arubanetworks.com/downloads

Accessing Updates

You can access updates from the Aruba Support Portal or the HPE My Networking Website.

Aruba Support Portal

<https://asp.arubanetworks.com/downloads>

If you are unable to find your product in the Aruba Support Portal, you may need to search My Networking, where older networking products can be found:

My Networking

<https://www.hpe.com/networking/support>

To view and update your entitlements, and to link your contracts and warranties with your profile, go to the Hewlett Packard Enterprise Support Center **More Information on Access to Support Materials** page:

<https://support.hpe.com/portal/site/hpsc/aae/home/>

Access to some updates might require product entitlement when accessed through the Hewlett Packard Enterprise Support Center. You must have an HP Passport set up with relevant entitlements.

Some software products provide a mechanism for accessing software updates through the product interface. Review your product documentation to identify the recommended software update method.

To subscribe to eNewsletters and alerts:

<https://asp.arubanetworks.com/notifications/subscriptions> (requires an active Aruba Support Portal (ASP) account to manage subscriptions). Security notices are viewable without an ASP account.

Warranty Information

To view warranty information for your product, go to <https://www.arubanetworks.com/support-services/product-warranties/>.

Regulatory Information

To view the regulatory information for your product, view the *Safety and Compliance Information for Server, Storage, Power, Networking, and Rack Products*, available at <https://www.hpe.com/support/Safety-Compliance-EnterpriseProducts>

Additional regulatory information

Aruba is committed to providing our customers with information about the chemical substances in our products as needed to comply with legal requirements, environmental data (company programs, product recycling, energy efficiency), and safety information and compliance data, (RoHS and WEEE). For more information, see <https://www.arubanetworks.com/company/about-us/environmental-citizenship/>.

Documentation Feedback

Aruba is committed to providing documentation that meets your needs. To help us improve the documentation, send any errors, suggestions, or comments to Documentation Feedback (docsfeedback-switching@hpe.com). When submitting your feedback, include the document title, part number, edition, and publication date located on the front cover of the document. For online help content, include the product name, product version, help edition, and publication date located on the legal notices page.