

# Webhooks: wire SendKit events into your stack

Webhooks push SendKit events to your own endpoint the moment they happen, so your stack does not have to poll the API. Everything below is available through `sendkit webhooks` in the CLI.

## Managing webhooks from the CLI

| Command                                                                                            | What it does                                                                                         |
|----------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------|
| <code>sendkit webhooks list</code>                                                                 | Lists webhooks on the active workspace, paginated.                                                   |
| <code>sendkit webhooks get &lt;id&gt;</code>                                                       | Shows the details of one webhook.                                                                    |
| <code>sendkit webhooks create --name &lt;name&gt; --url &lt;url&gt; --events &lt;events&gt;</code> | Creates a webhook pointed at your endpoint, subscribed to a comma-separated list of event types.     |
| <code>sendkit webhooks update &lt;id&gt; --status &lt;status&gt;</code>                            | Updates a webhook's name, URL, event list, or status.                                                |
| <code>sendkit webhooks test &lt;id&gt;</code>                                                      | Sends a test event to a webhook so you can confirm your endpoint is receiving and handling payloads. |
| <code>sendkit webhooks delete &lt;id&gt;</code>                                                    | Removes a webhook.                                                                                   |

## Wiring one up

### 01 Point it at your endpoint

Give `create` a name, the URL that should receive events, and the events to subscribe to as a comma-separated list.

### 02 Send a test event

Run `webhooks test <id>` before you wire anything downstream, so you confirm your endpoint responds correctly to a real payload shape.

### 03 Verify the signature on your end

SendKit signs webhook payloads, so your endpoint can verify a request actually came from SendKit before acting on it, rather than trusting any POST that arrives at the URL.

KEEPING IT HEALTHY

Use `webhooks get <id>` to check status and event list any time your integration seems to have gone quiet, and `update` to change the URL or event list without deleting and recreating the webhook.

The CLI's own help does not enumerate the specific event type names; confirm the exact list available to subscribe to inside your workspace before building against it.

### Create your first webhook

Run `sendkit webhooks create` with your endpoint URL, then `sendkit webhooks test` to confirm it is receiving real payloads.

Create your first webhook