

1. Write a scala program which produces all values from an array after removing duplicates.

```
def main(args: Array[String]): Unit = {  
  
    val arr = Array(6, 2, 3, 7, 4, 1, 5)  
  
    val unique = arr.distinct  
  
    println("Array after removing duplicates:")  
    for (i <- unique) {  
        println(i)  
    }  
  
}
```

2. Create a map of prices for a number of shopping items you want. Now create another map from it with the same key

```
val items = Map("orange" -> 50, "grapes" -> 40, "apple" -> 35, "tomato" -> 60)
```

3. Write a function minmax(value:Array[Int]) which returns a pair of minimum and maximum values of an array passed to it

```
def minmax(value: Array[Int]): (Int, Int) = {  
    var min = value(0)  
    var max = value(0)  
  
    for (v <- value) {  
        if (v < min) {  
            min = v  
        }  
        if (v > max) {  
            max = v  
        }  
    }  
    (min, max)  
}
```

```
val arr = Array(10, 5, 8, 20, 3)
```

```
val result = minmax(arr)
```

```
println("Minimum value: " + result._1)  
println("Maximum value: " + result._2)
```

4. Repeat the above exercise as a procedure which prints the min and max values of an array

```
def minmax(value: Array[Int]): Unit = {  
  
    var min = value(0)  
    var max = value(0)
```

```
for (v <- value) {  
  if (v < min) {  
    min = v  
  }  
  if (v > max) {  
    max = v  
  }  
}  
  
println("Minimum value: " + min)  
println("Maximum value: " + max)  
}  
  
val arr = Array(10, 5, 8, 20, 3)  
  
minmax(arr)
```