



Lecture 33-34

Code Optimizations

Awanish Pandey

Department of Computer Science and Engineering
Indian Institute of Technology
Roorkee

April 25, 2025

Data Flow Analysis

- Global optimizations are based on dataflow analysis

Data Flow Analysis

- Global optimizations are based on dataflow analysis
- These are algorithms to gather data about a program

Data Flow Analysis

- Global optimizations are based on dataflow analysis
- These are algorithms to gather data about a program
- Specify some property that must hold every time an instruction is executed

Data Flow Analysis

- Global optimizations are based on dataflow analysis
- These are algorithms to gather data about a program
- Specify some property that must hold every time an instruction is executed
- The analysis differs in the properties they compute

Data Flow Analysis

- Global optimizations are based on dataflow analysis
- These are algorithms to gather data about a program
- Specify some property that must hold every time an instruction is executed
- The analysis differs in the properties they compute
- Example: constant propagation

Data Flow Analysis

- Global optimizations are based on dataflow analysis
- These are algorithms to gather data about a program
- Specify some property that must hold every time an instruction is executed
- The analysis differs in the properties they compute
- Example: constant propagation
 - ▶ computes for each point in the program

Data Flow Analysis

- Global optimizations are based on dataflow analysis
- These are algorithms to gather data about a program
- Specify some property that must hold every time an instruction is executed
- The analysis differs in the properties they compute
- Example: constant propagation
 - ▶ computes for each point in the program
 - ▶ for each variable used by the program

Data Flow Analysis

- Global optimizations are based on dataflow analysis
- These are algorithms to gather data about a program
- Specify some property that must hold every time an instruction is executed
- The analysis differs in the properties they compute
- Example: constant propagation
 - ▶ computes for each point in the program
 - ▶ for each variable used by the program
 - ▶ whether variable has a unique constant value at that point

Data Flow Analysis

- Global optimizations are based on dataflow analysis
- These are algorithms to gather data about a program
- Specify some property that must hold every time an instruction is executed
- The analysis differs in the properties they compute
- Example: constant propagation
 - ▶ computes for each point in the program
 - ▶ for each variable used by the program
 - ▶ whether variable has a unique constant value at that point
 - ▶ replace variable reference by a constant value

Data Flow Abstraction

- Find data flow value at each program point.

Data Flow Abstraction

- Find data flow value at each program point.
- $IN[s]$ and $OUT[s]$

Data Flow Abstraction

- Find data flow value at each program point.
- $IN[s]$ and $OUT[s]$
- Transfer function: defines the relation between data flow values before and after the program point

Data Flow Abstraction

- Find data flow value at each program point.
- $IN[s]$ and $OUT[s]$
- Transfer function: defines the relation between data flow values before and after the program point
- Forward and Backward Analysis

Data Flow Abstraction

- Find data flow value at each program point.
- $IN[s]$ and $OUT[s]$
- Transfer function: defines the relation between data flow values before and after the program point
- Forward and Backward Analysis
 - ▶ $OUT[s] = f_s(IN[s])$

Data Flow Abstraction

- Find data flow value at each program point.
- $IN[s]$ and $OUT[s]$
- Transfer function: defines the relation between data flow values before and after the program point
- Forward and Backward Analysis
 - ▶ $OUT[s] = f_s(IN[s])$
 - ▶ $IN[s] = f_s(OUT[s])$

Data Flow Abstraction

- Find data flow value at each program point.
- $IN[s]$ and $OUT[s]$
- Transfer function: defines the relation between data flow values before and after the program point
- Forward and Backward Analysis
 - ▶ $OUT[s] = f_s(IN[s])$
 - ▶ $IN[s] = f_s(OUT[s])$
- What if we can reach a program point from two locations?

Data Flow Abstraction

- Find data flow value at each program point.
- $IN[s]$ and $OUT[s]$
- Transfer function: defines the relation between data flow values before and after the program point
- Forward and Backward Analysis
 - ▶ $OUT[s] = f_s(IN[s])$
 - ▶ $IN[s] = f_s(OUT[s])$
- What if we can reach a program point from two locations?
 - ▶ $IN[B] = \cup_{P \text{ is predecessor of } B} OUT[P]$ in case of forward analysis

Data Flow Abstraction

- Find data flow value at each program point.
- $IN[s]$ and $OUT[s]$
- Transfer function: defines the relation between data flow values before and after the program point
- Forward and Backward Analysis
 - ▶ $OUT[s] = f_s(IN[s])$
 - ▶ $IN[s] = f_s(OUT[s])$
- What if we can reach a program point from two locations?
 - ▶ $IN[B] = \cup_{P \text{ is predecessor of } B} OUT[P]$ in case of forward analysis
 - ▶ $OUT[B] = \cup_{S \text{ is successor of } B} IN[S]$ in case of backward analysis

Reaching Definitions

- Where in the program each variable may have been defined when control reaches each point

Reaching Definitions

- Where in the program each variable may have been defined when control reaches each point
- d reaches a point p if there is a path from d to p and d is not killed along that path.

Reaching Definitions

- Where in the program each variable may have been defined when control reaches each point
- d reaches a point p if there is a path from d to p and d is not killed along that path.
- Possible use case?

Reaching Definitions

- Where in the program each variable may have been defined when control reaches each point
- d reaches a point p if there is a path from d to p and d is not killed along that path.
- Possible use case?
 - ▶ Variable used before assignment.

Reaching Definitions

- Where in the program each variable may have been defined when control reaches each point
- d reaches a point p if there is a path from d to p and d is not killed along that path.
- Possible use case?
 - ▶ Variable used before assignment.
 - ▶ How to detect it?

Reaching Definitions

- Where in the program each variable may have been defined when control reaches each point
- *d reaches a point p* if there is a path from d to p and d is not killed along that path.
- Possible use case?
 - ▶ Variable used before assignment.
 - ▶ How to detect it?
 - ▶ Assign a dummy definition to each variable; if any dummy definition is used, then the variable is used without a definition.

Reaching Definitions

- Where in the program each variable may have been defined when control reaches each point
- *d reaches a point p* if there is a path from d to p and d is not killed along that path.
- Possible use case?
 - ▶ Variable used before assignment.
 - ▶ How to detect it?
 - ▶ Assign a dummy definition to each variable; if any dummy definition is used, then the variable is used without a definition.
- $OUT[B] = gen_B \cup (IN[B] - kill_B)$

Reaching Definitions

- Where in the program each variable may have been defined when control reaches each point
- *d reaches a point p* if there is a path from d to p and d is not killed along that path.
- Possible use case?
 - ▶ Variable used before assignment.
 - ▶ How to detect it?
 - ▶ Assign a dummy definition to each variable; if any dummy definition is used, then the variable is used without a definition.
- $OUT[B] = gen_B \cup (IN[B] - kill_B)$
- $IN[B] = \bigcup_{P \text{ is predecessor of } B} OUT[P]$

Reaching Definitions

- Where in the program each variable may have been defined when control reaches each point
- *d reaches a point p* if there is a path from d to p and d is not killed along that path.
- Possible use case?
 - ▶ Variable used before assignment.
 - ▶ How to detect it?
 - ▶ Assign a dummy definition to each variable; if any dummy definition is used, then the variable is used without a definition.
- $OUT[B] = gen_B \cup (IN[B] - kill_B)$
- $IN[B] = \bigcup_{P \text{ is predecessor of } B} OUT[P]$
- Solve till the fix point is reached.

Live Variable Analysis

- Whether the value of x could be used at program point p or not.

Live Variable Analysis

- Whether the value of x could be used at program point p or not.
- def_B set of variables defined in B prior to any use of that variable in B

Live Variable Analysis

- Whether the value of x could be used at program point p or not.
- def_B set of variables defined in B prior to any use of that variable in B
- use_B Value may be used in B prior to any definition of the variable

Live Variable Analysis

- Whether the value of x could be used at program point p or not.
- def_B set of variables defined in B prior to any use of that variable in B
- use_B Value may be used in B prior to any definition of the variable
- $IN[EXIT] = \phi$

Live Variable Analysis

- Whether the value of x could be used at program point p or not.
- def_B set of variables defined in B prior to any use of that variable in B
- use_B Value may be used in B prior to any definition of the variable
- $IN[EXIT] = \phi$
- $IN_B = use_B \cup (OUT[B] - def_B)$

Live Variable Analysis

- Whether the value of x could be used at program point p or not.
- def_B set of variables defined in B prior to any use of that variable in B
- use_B Value may be used in B prior to any definition of the variable
- $IN[EXIT] = \phi$
- $IN_B = use_B \cup (OUT[B] - def_B)$
- $OUT[B] = \cup_{S \text{ is successor of } B} IN[S]$

Available Expression

- An expression is *available* at a point p if every path from the entry node to p evaluates that expression and its operands are not modified between the path.

Available Expression

- An expression is *available* at a point p if every path from the entry node to p evaluates that expression and its operands are not modified between the path.
- $OUT[ENTRY] = \phi$

Available Expression

- An expression is *available* at a point p if every path from the entry node to p evaluates that expression and its operands are not modified between the path.
- $OUT[ENTRY] = \phi$
- $OUT[B] = gen_B \cup (IN[B] - kill_B)$

Available Expression

- An expression is *available* at a point p if every path from the entry node to p evaluates that expression and its operands are not modified between the path.
- $OUT[ENTRY] = \phi$
- $OUT[B] = gen_B \cup (IN[B] - kill_B)$
- $IN[B] = \cap_{P \text{ is predecessor of } B} OUT[P]$

Constant Propagation