



Lecture 5

Lexical Analysis

Awanish Pandey

Department of Computer Science and Engineering
Indian Institute of Technology
Roorkee

January 29, 2025

Takeaways from the last class

- Difference between **lexeme** and **token**

Takeaways from the last class

- Difference between **lexeme** and **token**
- Approaches for implementing lexical analyzer

there are three approaches -
Assembly languages, High level
languages and Generator tools

Takeaways from the last class

- Difference between **lexeme** and **token**
- Approaches for implementing lexical analyzer
- Difficulties while doing lexical analysis

Takeaways from the last class

- Difference between **lexeme** and **token**
- Approaches for implementing lexical analyzer
- Difficulties while doing lexical analysis
- Impact on symbol table while doing lexical analysis

Takeaways from the last class

- Difference between **lexeme** and **token**
- Approaches for implementing lexical analyzer
- Difficulties while doing lexical analysis
- Impact on symbol table while doing lexical analysis
- Partitioning input into tokens.

Takeaways from the last class

- Difference between **lexeme** and **token**
- Approaches for implementing lexical analyzer
- Difficulties while doing lexical analysis
- Impact on symbol table while doing lexical analysis
- Partitioning input into tokens.
- **Maximal Munch**

Extended Regular Expression

Extended Regular Expression

- One or more instances

Extended Regular Expression

- One or more instances

$$r^+ = rr^*$$

Extended Regular Expression

- One or more instances

$$r^+ = rr^*$$

- Zero or one instance

Extended Regular Expression

- One or more instances

$$r^+ = rr^*$$

- Zero or one instance

$$r^?$$

Extended Regular Expression

- One or more instances

$$r^+ = rr^*$$

- Zero or one instance

$$r^?$$

- Character classes

Extended Regular Expression

- One or more instances

$$r^+ = rr^*$$

- Zero or one instance

$$r^?$$

- Character classes

$$[a_1 a_2 \dots a_n]$$

Extended Regular Expression

- One or more instances

$$r^+ = rr^*$$

- Zero or one instance

$$r^?$$

- Character classes

$$[a_1 a_2 \dots a_n]$$

- Any character

Extended Regular Expression

- One or more instances

$$r^+ = rr^*$$

- Zero or one instance

$$r^?$$

- Character classes

$$[a_1 a_2 \dots a_n]$$

- Any character

.

Extended Regular Expression

- One or more instances

$$r^+ = rr^*$$

- Zero or one instance

$$r^?$$

- Character classes

$$[a_1 a_2 \dots a_n]$$

- Any character

.

- Beginning of the line

Extended Regular Expression

- One or more instances

$$r^+ = rr^*$$

- Zero or one instance

$$r^?$$

- Character classes

$$[a_1 a_2 \dots a_n]$$

- Any character

.

- Beginning of the line

^

Extended Regular Expression

- One or more instances

$$r^+ = rr^*$$

- Zero or one instance

$$r^?$$

- Character classes

$$[a_1 a_2 \dots a_n]$$

- Any character

.

- Beginning of the line

^

- End of the line

Extended Regular Expression

- One or more instances

$$r^+ = rr^*$$

- Zero or one instance

$$r^?$$

- Character classes

$$[a_1 a_2 \dots a_n]$$

- Any character

.

- Beginning of the line

^

- End of the line

\$

Extended Regular Expression

- One or more instances

$$r^+ = rr^*$$

- Zero or one instance

$$r^?$$

- Character classes

$$[a_1 a_2 \dots a_n]$$

- Any character

$$\cdot$$

- Beginning of the line

$$\wedge$$

- End of the line

$$\$$$

- Between m and n occurrence

Extended Regular Expression

- One or more instances

$$r^+ = rr^*$$

- Zero or one instance

$$r^?$$

- Character classes

$$[a_1 a_2 \dots a_n]$$

- Any character

.

- Beginning of the line

^

- End of the line

\$

- Between m and n occurrence

$$r\{m,n\}$$

Lexical analyzer generator

- Input to the generator

Lexical analyzer generator

- Input to the generator
 - ▶ List of regular expressions in priority order

Lexical analyzer generator

- Input to the generator
 - ▶ List of regular expressions in priority order
 - ▶ Associated actions for each of regular expression (generates kind of token and other bookkeeping information)

Lexical analyzer generator

- Input to the generator
 - ▶ List of regular expressions in priority order
 - ▶ Associated actions for each of regular expression (generates kind of token and other bookkeeping information)
- Output of the generator

Lexical analyzer generator


- Input to the generator
 - ▶ List of regular expressions in priority order
 - ▶ Associated actions for each of regular expression (generates kind of token and other bookkeeping information)
- Output of the generator
 - ▶ Program that reads input character stream and breaks that into tokens

Lexical analyzer generator

- Input to the generator
 - ▶ List of regular expressions in priority order
 - ▶ Associated actions for each of regular expression (generates kind of token and other bookkeeping information)
- Output of the generator
 - ▶ Program that reads input character stream and breaks that into tokens
 - ▶ Reports lexical errors (unexpected characters), if any

Lexical analyzer generator

- Input to the generator
 - ▶ List of regular expressions in priority order
 - ▶ Associated actions for each of regular expression (generates kind of token and other bookkeeping information)
- Output of the generator
 - ▶ Program that reads input character stream and breaks that into tokens
 - ▶ Reports lexical errors (unexpected characters), if any



Sample Lex File

File Format

declaration

%%

transition rules

%%

auxiliary functions

Sample Lex File

File Format

declaration

%%

transition rules

%%

auxiliary functions

Declaration

- Variables which is going to be used in the rules must be defined in this section.

Sample Lex File

File Format

declaration

%%

transition rules

%%

auxiliary functions

Declaration

- Variables which is going to be used in the rules must be defined in this section.
D [0-9]

Sample Lex File

File Format

declaration

%%

transition rules

%%

auxiliary functions

Declaration

- Variables which is going to be used in the rules must be defined in this section.
D [0-9]
- Section enclosed in `%{ %}` delimiter lines are copied to the lex.yy.c file.

Sample Lex File

File Format

declaration

%%

transition rules

%%

auxiliary functions

Declaration

- Variables which is going to be used in the rules must be defined in this section.
D [0-9]

- Section enclosed in %{%} delimiter lines are copied to the lex.yy.c file.

%{

include < math.h >

int count;

%}

Sample Lex file

Transition Rule

Pattern { *Action* }

Sample Lex file

Transition Rule

Pattern {*Action*}

Auxiliary Functions

C Code, going directly into `lex.yy.c`

Sample Lex file

Transition Rule

Pattern {*Action*}

Auxiliary Functions

C Code, going directly into `lex.yy.c`

Important functions/variables

- `yyin`

Sample Lex file

Transition Rule

Pattern {*Action*}

Auxiliary Functions

C Code, going directly into `lex.yy.c`

Important functions/variables

- `yyin`
- `yylex`

Sample Lex file

Transition Rule

Pattern {*Action*}

Auxiliary Functions

C Code, going directly into `lex.yy.c`

Important functions/variables

- `yyin`
- `yylex`
- `yytext`

Sample Lex file

Transition Rule

Pattern {*Action*}

Auxiliary Functions

C Code, going directly into `lex.yy.c`

Important functions/variables

- `yyin`
- `yylex`
- `yytext`
- `yyerror`

Sample Lex file

Transition Rule

Pattern {*Action*}

Auxiliary Functions

C Code, going directly into `lex.yy.c`

Important functions/variables

- `yyin`
- `yylex`
- `yytext`
- `yyerror`
- `yylen`

Sample Lex file

Transition Rule

Pattern {*Action*}

Auxiliary Functions

C Code, going directly into `lex.yy.c`

Important functions/variables

- `yyin` input stream to take the source program
- `yylex` a function called to perform lexical analysis
- `yytext` lexeme that matches pattern
- `yyerror` It is a function ; It is used for explicit error flagging in the code.
- `yylen` length of `yytext` or lexeme
- `yylineno` line number tracking

How lex works?

- Regular expressions describe the languages that can be recognized by finite automata

How lex works?

- Regular expressions describe the languages that can be recognized by finite automata
- Translate each token regular expression into a non-deterministic finite automaton

How lex works?

- Regular expressions describe the languages that can be recognized by finite automata
- Translate each token regular expression into a non-deterministic finite automaton
- Convert the NFA into an equivalent DFA

How lex works?

- Regular expressions describe the languages that can be recognized by finite automata
- Translate each token regular expression into a non-deterministic finite automaton
- Convert the NFA into an equivalent DFA
- Minimize the DFA to reduce number of states

How lex works?

- Regular expressions describe the languages that can be recognized by finite automata
- Translate each token regular expression into a non-deterministic finite automaton
- Convert the NFA into an equivalent DFA
- Minimize the DFA to reduce number of states
- Emit code driven by the DFA tables

How to break up text

- How to tokenize $e/\text{sex} = 0$

How to break up text

- How to tokenize $elsex = 0$
 - ▶ $else\ x = 0$
 - ▶ $elsex = 0$
- Regular expressions alone are not enough

How to break up text

- How to tokenize $elsex = 0$
 - ▶ $else\ x = 0$
 - ▶ $elsex = 0$
- Regular expressions alone are not enough
- the longest match wins

How to break up text

- How to tokenize $elsex = 0$
 - ▶ $else\ x = 0$
 - ▶ $elsex = 0$
- Regular expressions alone are not enough
- the longest match wins
- Ties are resolved by prioritizing tokens

How to break up text

- How to tokenize $elsex = 0$

- ▶ $else\ x = 0$
- ▶ $elsex = 0$

for implementation, all the three are required.


- Regular expressions alone are not enough
- the longest match wins
- Ties are resolved by prioritizing tokens

- Lexical definitions consist of **regular definitions, priority rules, and maximal munch principle**

How to break up text

- How to tokenize $elsex = 0$
 - ▶ $else\ x = 0$
 - ▶ $elsex = 0$
- Regular expressions alone are not enough
- the longest match wins
- Ties are resolved by prioritizing tokens
- Lexical definitions consist of **regular definitions**, **priority rules**, and **maximal munch principle**
- Construct an analyzer that will return $\langle \text{token}, \text{lexeme} \rangle$ pairs

Transition Diagram for Relational Operator



Correctness check

- The lexeme for a given token must be the longest possible

Correctness check

- The lexeme for a given token must be the longest possible
- Assume input to be 12.34E56

Correctness check

- The lexeme for a given token must be the longest possible
- Assume input to be 12.34E56
- It can be matched as $\langle \text{int}, 12 \rangle$

Correctness check

- The lexeme for a given token must be the longest possible
- Assume input to be 12.34E56
- It can be matched as $\langle \text{int}, 12 \rangle$
- the matching should always start with the first transition diagram

Correctness check

- The lexeme for a given token must be the longest possible
- Assume input to be 12.34E56
- It can be matched as $\langle \text{int}, 12 \rangle$
- the matching should always start with the first transition diagram
- If failure occurs in one transition diagram, then retract the forward pointer to the start state and activate the next diagram

Correctness check

- The lexeme for a given token must be the longest possible
- Assume input to be 12.34E56
- It can be matched as $\langle \text{int}, 12 \rangle$
- the matching should always start with the first transition diagram
- If failure occurs in one transition diagram, then retract the forward pointer to the start state and activate the next diagram
- If failure occurs in all diagrams, then a lexical error has occurred

Correctness check

- The lexeme for a given token must be the longest possible
- Assume input to be 12.34E56
- It can be matched as $\langle \text{int}, 12 \rangle$
- the matching should always start with the first transition diagram
- If failure occurs in one transition diagram, then retract the forward pointer to the start state and activate the next diagram
- If failure occurs in all diagrams, then a lexical error has occurred
- This can be implemented using **lots of** switch-cases in C programming language.

see book

Interface to other passes

