



Fundamentals of Object Oriented Programming

CSN- 103

Dr. R. Balasubramanian

Associate Professor

Department of Computer Science and Engineering

Indian Institute of Technology Roorkee

Roorkee 247 667

balarfcs@iitr.ac.in

<https://sites.google.com/site/balaiiitr/>



Identifiers

- When more than one words are used in a name
 - dayTemperature
 - firstDayOfMonth
 - totalMarks ✓
- All **private** and **local variables** use only lowercase letters combined with underscores
 - length
 - batch_strength
- All **classes** and **interfaces** start with a leading uppercase letter
 - Student
 - HelloJava
 - Vehicle
 - MotorCycle

total Marks X

Identifiers

- Variables that represent **Constant Values** use uppercase letters and underscores
 - TOTAL
 - F_MAX
 - PRINCIPAL_AMOUNT



Literals

- Integer
- Floating_Point
- Character
- String
- Boolean



Separators

- `()` Encloses arguments in method definitions and calling; adjusts precedence in arithmetic expressions; surrounds cast types and delimits test expressions in flow control statements
- `{ }` defines blocks of code and automatically initializes arrays
- `[]` declares array types and dereferences array values
- `;` terminates statements
- `,` separates successive identifiers in variable declarations; chains statements in the test, expression of a for loop
- `.` Selects a field or method from an object; separates package names from sub-package and class names
- `:` Used after loop labels

Java Statements

- Empty Statement
- Labelled Statement

hackit:

```
while (Some condition) {  
    if ( a specific condition )  
        break hackit;           //Usage with Label  
    else  
        normal business goes here..  
}
```

- Expression Statement

- Assignment, Pre-Increment, Pre-Decrement, Post-Increment, Post-Decrement, Method Call and Allocation Expression
 - `double d = new double(8.9473);`



Java Statements

- Selection statement
 - if, if-else and switch
- Iteration Statement
 - while, do and for
- Jump Statement
 - break, continue, return and throw
- Guarding statement
 - try, catch and finally

Constants, Variables and Data Types

- Constants

- Constants in Java refers to fixed values that do not change during the execution of a program
 - Integer constants
 - Real constants
 - Single character constants
 - String constants
 - Backslash character constants

- Integer Constants

- decimal, octal and hexadecimal

- Decimal

➤ 123 -456 0 76543

- Octal

➤ 037 0 0234 0661

hexadecimal

- Hexadecimal

➤ 0X2 0X9F 0xbcd 0x



 edit  fork  download

```
1.  /* package whatever; // don't place package name! */
2.
3.  import java.util.*;
4.  import java.lang.*;
5.  import java.io.*;
6.
7.  /* Name of the class has to be "Main" only if the class is public. */
8.  class Ideone
9.  {
10.     public static void main (String[] args) throws java.lang.Exception
11.     {
12.         int a;
13.         a=03467;
14.         System.out.println(a);
15.     }
16. }
```

Success #stdin #stdout 0.05s 27620KB

 stdin

Standard input is empty

 stdout

1847

<https://ideone.com/INYb7I>



edit fork download

```
1.  /* package whatever; // don't place package name! */
2.
3.  import java.util.*;
4.  import java.lang.*;
5.  import java.io.*;
6.
7.  /* Name of the class has to be "Main" only if the class is public. */
8.  class Ideone
9.  {
10.     public static void main (String[] args) throws java.lang.Exception
11.     {
12.         int b;
13.         b=0x23ef;
14.         System.out.println(b); // your code goes here
15.     }
16. }
```

Success #stdin #stdout 0.1s 27712KB

stdin

Standard input is empty

stdout

9199

<https://ideone.com/s885ef>
