Lecture 9-10 13-14.2.2025

## Today's agenda:

## Church numerals, successor function, primitive recursive functions

Church numerals

```
0 = \lambda f. \lambda y. y
1 = \lambda f. \lambda y. f y
2 = \lambda f. \lambda y. f (f y)
n = \lambda f. \lambda y. f (f....(f y))...) n times
```

Successor is defined as: succ =  $S = \lambda n$ .  $\lambda f \cdot \lambda y \cdot f(n f y)$ 

Now we want to design the successor function. How did we get the term for successor function?

Suppose that it is correct. We shall work out for SO and S1 to get the insight.

```
S0 = (\lambda n.\lambda f.\lambda y. f(n f y))(\lambda f.\lambda y.y)
= (\lambda n.\lambda f.\lambda y. f(n f y))(\lambda u.\lambda v.v) [by renaming]
= \lambda f.\lambda y.f ((\lambda u.\lambda v.v) f y)
= \lambda f.\lambda y.f ((\lambda u.\lambda v.v) f) y) [by left associative]
= \lambda f.\lambda y.f ((\lambda v.v) y)
= \lambda f.\lambda y.f y corresponds to numeral 1
```

Since n is an argument of S so we add  $\lambda n$ .

Now succ of n is n' = n+1; now n' is represented as  $\lambda f.\lambda y$ . (something)

Where the (something) is < f (the body of n) >. Let us call it f M. when M is applied to n we get the body of n. So n must occur in M. Now n would be replaced by the actual parameter n.

But the actual parameter contains  $\lambda f$  and  $\lambda y$ . So in order to get rid of them, supply the corresponding parameters. Thus in doing so, we get only the body of n.

```
S1 = (\lambda n. \lambda f. \lambda y. f(n f y))(\lambda f. \lambda y. fy)

= \lambda f. \lambda y. f((\lambda f. \lambda y. fy)fy))

= \lambda f. \lambda y. f((\lambda y. fy)y)

= \lambda f. \lambda y. f(fy)
```

However, designing the lambda term for predecessor function is hard (invented by Kleene during a visit to a dentist!).



End of lecture

Stephen Kleene (1909-1994) Church's student and a pioneer of LC. He invented regular expressions. Kleene star (Kleene closure) is named after him. His works helped to provide the foundations of theoretical computer science.

```
primitive recursive functions:
                          add(m, n+1) = succ(add(m,n))
add(m, 0) = m
multiply(m,1) = m multiply(m,n+1) = add(m, multiply(m,n))
exponent(m,0) = 1 exponent(m,n+1) = multiply(m, exponent(m,n))
Successor function: succ = \lambda n. \lambda f \cdot \lambda y. f(n f y)
generalize the successor function to adding m. so we have plus = λm. λn.λf. λy. m f(n f y)
Recall the factorial function: f = IF (iszero n) SO n^* f (pred n)
now we have a pure lambda term for f. the components are (i) IF (ii) 0 (iii) S (iv) iszero n (v) * (vi) pred
Design of iszero function: iszero = \lambdan. n (\lambdax. false) true
iszero = \lambda n. n (\lambda x. false) true true = \lambda f. \lambda y. f
                                                                                 false = \lambda f. \lambda y. y
          <del>λn.</del>n
          [λf. λy. y...( ) ......true..... ]
                                                          beta reduction true or false
        = (\lambda y. y) true
        = true
iszero 0 = (\lambda n. n (\lambda x. false) true) 0
          = (\lambda n. n (\lambda x. false) true) \lambda f. \lambda y. y
          = ((\lambda f. \lambda y. y) (\lambda x. false)) true
          = (\lambda y. y) true
          = true
iszero 1 = (\lambda n. n (\lambda x. false) true) 1
          = (\lambda n. n (\lambda x. false) true) (\lambda f. \lambda y. fy)
          = (\lambda f. \lambda y. f y) (\lambda x. false) true
          = ((\lambda f. \lambda y. f y) (\lambda x. false))true
          = (\lambda y. ((\lambda x. false) y)) true
          = (\lambda y. false) true
          = false
```