



Lecture 4

Lexical Analysis

Awanish Pandey

Department of Computer Science and Engineering
Indian Institute of Technology
Roorkee

January 28, 2025

Lexical Analysis

- Recognize tokens and ignore white spaces and comments

Lexical Analysis

- Recognize tokens and ignore white spaces and comments
- Error reporting

Lexical Analysis

- Recognize tokens and ignore white spaces and comments
- Error reporting
- Model using regular expressions

Lexical Analysis

- Recognize tokens and ignore white spaces and comments
- Error reporting
- Model using regular expressions
- Recognize using Finite State Automata

Lexical Analysis

- Recognize tokens and ignore white spaces and comments
- Error reporting
- Model using regular expressions
- Recognize using Finite State Automata
- Sentences consist of a string of **tokens** (a syntactic category), for example, number, identifier, keyword, string

Lexical Analysis

- Recognize tokens and ignore white spaces and comments
- Error reporting
- Model using regular expressions
- Recognize using Finite State Automata
- Sentences consist of a string of **tokens** (a syntactic category), for example, number, identifier, keyword, string
- Sequences of characters in a token is a **lexeme** for example, 100.01, counter, const, "How are you?"

Lexical Analysis

- Recognize tokens and ignore white spaces and comments
- Error reporting
- Model using regular expressions
- Recognize using Finite State Automata
- Sentences consist of a string of **tokens** (a syntactic category), for example, number, identifier, keyword, string
- Sequences of characters in a token is a **lexeme** for example, 100.01, counter, const, "How are you?"

After lexical analysis of `a = b + c`

Lexical Analysis

- Recognize tokens and ignore white spaces and comments
- Error reporting
- Model using regular expressions
- Recognize using Finite State Automata
- Sentences consist of a string of **tokens** (a syntactic category), for example, number, identifier, keyword, string
- Sequences of characters in a token is a **lexeme** for example, 100.01, counter, const, "How are you?"

After lexical analysis of `a = b + c`

tokens	id	ASSIGN	id	ADDOP	ID
lexeme	a	=	b	+	c

Approaches to Implement

Approaches to Implement

- Use Assembly language

Approaches to Implement

- Use Assembly language
Most efficient but most difficult to implement

Approaches to Implement

- Use Assembly language
Most efficient but most difficult to implement
- Use high-level languages like C

Approaches to Implement

- Use Assembly language
Most efficient but most difficult to implement
- Use high-level languages like C
Efficient but difficult to implement

Approaches to Implement

- Use Assembly language
Most efficient but most difficult to implement
- Use high-level languages like C
Efficient but difficult to implement
- Use tools like `lex`, `flex`

Approaches to Implement

- Use Assembly language
Most efficient but most difficult to implement
- Use high-level languages like C
Efficient but difficult to implement
- Use tools like `lex`, `flex`
Easy to implement but not as efficient as the first two cases

A simple lexical analyzer

A simple lexical analyzer

Allow white spaces, numbers, and arithmetic operators in an expression

A simple lexical analyzer

Allow white spaces, numbers, and arithmetic operators in an expression

```
1 #include <stdio.h>
2 #include <ctype.h>
3 int lineno = 1;
4 int tokenval = NONE;
5 int lex() {
6     int t;
7     while (1) {
8         t = getchar ();
9         if (t == ' ' || t == '\t');
10        else if (t == '\n')
11            lineno = lineno + 1;
12        else if (isdigit (t) ) {
13            tokenval = t - '0';
14            t = getchar ();
15            while (isdigit(t)) {
16                tokenval=tokenval * 10 + t - '0';
17                t = getchar();
18            }
19            ungetc(t,stdin);
20            return num;
21        }
22        else { tokenval = NONE; return t; }
23    }
24 }
```

A simple lexical analyzer

Allow white spaces, numbers, and arithmetic operators in an expression

```
1 #include <stdio.h>
2 #include <ctype.h>
3 int lineno = 1;
4 int tokenval = NONE;
5 int lex() {
6     int t;
7     while (1) {
8         t = getchar ();
9         if (t == ' ' || t == '\t');
10        else if (t == '\n')
11            lineno = lineno + 1;
12        else if (isdigit (t) ) {
13            tokenval = t - '0';
14            t = getchar ();
15            while (isdigit(t)) {
16                tokenval=tokenval * 10 + t - '0';
17                t = getchar();
18            }
19            ungetc(t,stdin);
20            return num;
21        }
22        else { tokenval = NONE; return t; }
23    }
24 }
```

- Header files and global variable declaration

A simple lexical analyzer

Allow white spaces, numbers, and arithmetic operators in an expression

```
1 #include <stdio.h>
2 #include <ctype.h>
3 int lineno = 1;
4 int tokenval = NONE;
5 int lex() {
6     int t;
7     while (1) {
8         t = getchar ();
9         if (t == ' ' || t == '\t');
10        else if (t == '\n')
11            lineno = lineno + 1;
12        else if (isdigit (t) ) {
13            tokenval = t - '0'
14            t = getchar ();
15            while (isdigit(t)) {
16                tokenval=tokenval * 10 + t - '0'
17                t = getchar();
18            }
19            ungetc(t,stdin);
20            return num;
21        }
22        else { tokenval = NONE; return t; }
23    }
24 }
```

- Header files and global variable declaration
- A global variable tokenval is set to the value of the number

A simple lexical analyzer

Allow white spaces, numbers, and arithmetic operators in an expression

```
1 #include <stdio.h>
2 #include <ctype.h>
3 int lineno = 1;
4 int tokenval = NONE;
5 int lex() {
6     int t;
7     while (1) {
8         t = getchar ();
9         if (t == ' ' || t == '\t');
10        else if (t == '\n')
11            lineno = lineno + 1;
12        else if (isdigit (t) ) {
13            tokenval = t - '0';
14            t = getchar ();
15            while (isdigit(t)) {
16                tokenval=tokenval * 10 + t - '0';
17                t = getchar();
18            }
19            ungetc(t,stdin);
20            return num;
21        }
22        else { tokenval = NONE; return t; }
23    }
24 }
```

- Header files and global variable declaration
- A global variable tokenval is set to the value of the number
- Check for the whitespace

A simple lexical analyzer

Allow white spaces, numbers, and arithmetic operators in an expression

```
1 #include <stdio.h>
2 #include <ctype.h>
3 int lineno = 1;
4 int tokenval = NONE;
5 int lex() {
6     int t;
7     while (1) {
8         t = getchar ();
9         if (t == ' ' || t == '\t');
10        else if (t == '\n')
11            lineno = lineno + 1;
12        else if (isdigit (t) ) {
13            tokenval = t - '0';
14            t = getchar ();
15            while (isdigit(t)) {
16                tokenval=tokenval * 10 + t - '0';
17                t = getchar();
18            }
19            ungetc(t,stdin);
20            return num;
21        }
22        else { tokenval = NONE; return t; }
23    }
24 }
```

- Header files and global variable declaration
- A global variable tokenval is set to the value of the number
- Check for the whitespace
- Check for the new line

A simple lexical analyzer

Allow white spaces, numbers, and arithmetic operators in an expression

```
1 #include <stdio.h>
2 #include <ctype.h>
3 int lineno = 1;
4 int tokenval = NONE;
5 int lex() {
6     int t;
7     while (1) {
8         t = getchar ();
9         if (t == ' ' || t == '\t');
10        else if (t == '\n')
11            lineno = lineno + 1;
12        else if (isdigit (t) ) {
13            tokenval = t - '0';
14            t = getchar ();
15            while (isdigit(t)) {
16                tokenval=tokenval * 10 + t - '0';
17                t = getchar();
18            }
19            ungetc(t,stdin);
20            return num;
21        }
22        else { tokenval = NONE; return t; }
23    }
24 }
```

- Header files and global variable declaration
- A global variable tokenval is set to the value of the number
- Check for the whitespace
- Check for the new line
- Check for digit

A simple lexical analyzer

Allow white spaces, numbers, and arithmetic operators in an expression

```
1 #include <stdio.h>
2 #include <ctype.h>
3 int lineno = 1;
4 int tokenval = NONE;
5 int lex() {
6     int t;
7     while (1) {
8         t = getchar ();
9         if (t == ' ' || t == '\t');
10        else if (t == '\n')
11            lineno = lineno + 1;
12        else if (isdigit (t) ) {
13            tokenval = t - '0';
14            t = getchar ();
15            while (isdigit(t)) {
16                tokenval=tokenval * 10 + t - '0';
17                t = getchar();
18            }
19            ungetc(t,stdin);
20            return num;
21        }
22        else { tokenval = NONE; return t; }
23    }
24 }
```

- Header files and global variable declaration
- A global variable tokenval is set to the value of the number
- Check for the whitespace
- Check for the new line
- Check for digit
- Else return the scanned character

Problems

Problems

- Scans text character by character

Problems

- Scans text character by character
- The lookahead character determines what kind of token to read and when the current token ends

Problems

- Scans text character by character
- The lookahead character determines what kind of token to read and when the current token ends
- The first character cannot determine what kind of token we are going to read

Symbol Table

Symbol Table

- Stores information for subsequent phases

Symbol Table

- Stores information for subsequent phases
- Interface to the symbol table

Symbol Table

- Stores information for subsequent phases
- Interface to the symbol table
 - ▶ `Insert(s,t)`: save lexeme `s` and token `t` and return pointer

Symbol Table

- Stores information for subsequent phases
- Interface to the symbol table
 - ▶ $\text{Insert}(s, t)$: save lexeme s and token t and return pointer
 - ▶ $\text{Lookup}(s)$: return index of entry for lexeme s or 0 if s is not found

Symbol Table

- Stores information for subsequent phases
- Interface to the symbol table
 - ▶ `Insert(s,t)`: save lexeme `s` and token `t` and return pointer
 - ▶ `Lookup(s)`: return index of entry for lexeme `s` or 0 if `s` is not found

Implementation of Symbol Table

Symbol Table

- Stores information for subsequent phases
- Interface to the symbol table
 - ▶ $\text{Insert}(s, t)$: save lexeme s and token t and return pointer
 - ▶ $\text{Lookup}(s)$: return index of entry for lexeme s or 0 if s is not found

Implementation of Symbol Table


Token	Lexeme

Symbol Table

- Stores information for subsequent phases
- Interface to the symbol table
 - ▶ Insert(s,t): save lexeme s and token t and return pointer
 - ▶ Lookup(s): return index of entry for lexeme s or 0 if s is not found

Implementation of Symbol Table

Token	Lexeme



Handling Keyword

Handling Keyword

- Consider tokens INT and CHAR with lexemes int and char.

Handling Keyword

- Consider tokens INT and CHAR with lexemes int and char.
- Initialize symbol table with `insert("int" , INT)` and `insert("char" , CHAR)`.

Handling Keyword

- Consider tokens INT and CHAR with lexemes int and char.
- Initialize symbol table with `insert("int" , INT)` and `insert("char" , CHAR)`.
- Any subsequent lookup returns a nonzero value, therefore, cannot be used as an identifier.

Handling Keyword

- Consider tokens INT and CHAR with lexemes int and char.
- Initialize symbol table with `insert("int" , INT)` and `insert("char" , CHAR)`.
- Any subsequent lookup returns a nonzero value, therefore, cannot be used as an identifier.
- Not an error at lexical analysis phase.

Difficulties in designing the lexical analyzer

Difficulties in designing the lexical analyzer

- Looks simple. Right?

Difficulties in designing the lexical analyzer

- Looks simple. Right?
- Lexemes in a fixed position. Fix format (python) vs. free format languages (C).

Difficulties in designing the lexical analyzer

- Looks simple. Right?
- Lexemes in a fixed position. Fix format (python) vs. free format languages (C).
- Handling the whitespaces

Difficulties in designing the lexical analyzer

- Looks simple. Right?
- Lexemes in a fixed position. Fix format (python) vs. free format languages (C).
- Handling the whitespaces
 - ▶ In Fortran counter and co unter are same.

Difficulties in designing the lexical analyzer

- Looks simple. Right?
- Lexemes in a fixed position. Fix format (python) vs. free format languages (C).
- Handling the whitespaces
 - ▶ In Fortran `counter` and `co unter` are same.
 - ▶ `D0 10 I = 1.25`
 - ▶ `D0 10 I = 1,25`

Difficulties in designing the lexical analyzer

- Looks simple. Right?
- Lexemes in a fixed position. Fix format (python) vs. free format languages (C).
- Handling the whitespaces
 - ▶ In Fortran `counter` and `co unter` are same.
 - ▶ `D0 10 I = 1.25`
 - ▶ `D0 10 I = 1,25`
 - ▶ Due to punch cards and errors in punching

Difficulties in designing the lexical analyzer

- Looks simple. Right?
- Lexemes in a fixed position. Fix format (python) vs. free format languages (C).
- Handling the whitespaces
 - ▶ In Fortran `counter` and `co unter` are same.
 - ▶ `D0 10 I = 1.25`
 - ▶ `D0 10 I = 1,25`
 - ▶ Due to punch cards and errors in punching
- Are keywords reserve word?

Difficulties in designing the lexical analyzer

- Looks simple. Right?
- Lexemes in a fixed position. Fix format (python) vs. free format languages (C).
- Handling the whitespaces
 - ▶ In Fortran `counter` and `co unter` are same.
 - ▶ `D0 10 I = 1.25`
 - ▶ `D0 10 I = 1,25`
 - ▶ Due to punch cards and errors in punching
- Are keywords reserve word?
`if then then then = else else else = then // valid in PL/1`

Difficulties in designing the lexical analyzer

- Looks simple. Right?
- Lexemes in a fixed position. Fix format (python) vs. free format languages (C).
- Handling the whitespaces
 - ▶ In Fortran counter and co unter are same.
 - ▶ `D0 10 I = 1.25`
 - ▶ `D0 10 I = 1,25`
 - ▶ Due to punch cards and errors in punching
- Are keywords reserve word?
 - `if then then then = else else else = then // valid in PL/1`
- Requires arbitrary lookahead and very large buffers. Worse, the buffers may have to be reloaded.
 - `Declare(arg1,arg2,arg3,.....,argn)`
 - `Declare(arg1,arg2,arg3,.....,argn) = 0`

Difficulties in designing the lexical analyzer

- Looks simple. Right?
- Lexemes in a fixed position. Fix format (python) vs. free format languages (C).
- Handling the whitespaces
 - ▶ In Fortran `counter` and `co unter` are same.
 - ▶ `D0 10 I = 1.25`
 - ▶ `D0 10 I = 1,25`
 - ▶ Due to punch cards and errors in punching
- Are keywords reserve word?
 - `if then then then = else else else = then // valid in PL/1`
- Requires arbitrary lookahead and very large buffers. Worse, the buffers may have to be reloaded.
 - `Declare(arg1,arg2,arg3,.....,argn)`
 - `Declare(arg1,arg2,arg3,.....,argn) = 0`
- Even today `Foo<Bar<Bazz>>`

What are we looking for?

- How to describe tokens

What are we looking for?

- How to describe tokens
- How to break text into token

What are we looking for?

- How to describe tokens
- How to break text into token
`if(x==0) a = x << 1;`

What are we looking for?

- How to describe tokens
- How to break text into token
 - `if(x==0) a = x << 1;`
 - `iff(x==0) a = x < 1;`

What are we looking for?

- How to describe tokens
- How to break text into token
 - $\text{if}(x==0) \ a = x \ll 1;$
 - $\text{iff}(x==0) \ a = x < 1;$
- How to break the input into tokens efficiently

What are we looking for?

- How to describe tokens
- How to break text into token
 - $\text{if}(x==0) a = x \ll 1;$
 - $\text{iff}(x==0) a = x < 1;$
- How to break the input into tokens efficiently
 - ▶ Tokens may have similar prefixes.

What are we looking for?

- How to describe tokens
- How to break text into token
 - $\text{if}(x==0) \ a = x \ll 1;$
 - $\text{iff}(x==0) \ a = x < 1;$
- How to break the input into tokens efficiently
 - ▶ Tokens may have similar prefixes.
 - ▶ Each character should be looked at only once.

How to describe token

How to describe token

- By regular languages

How to describe token

- By regular languages
- Regular languages

How to describe token

- By regular languages
- Regular languages
 - ▶ Are easy to understand

How to describe token

- By regular languages
- Regular languages
 - ▶ Are easy to understand
 - ▶ There is a well-understood and useful theory

How to describe token

- By regular languages
- Regular languages
 - ▶ Are easy to understand
 - ▶ There is a well-understood and useful theory
 - ▶ They have efficient implementation

How to describe token

- By regular languages
- Regular languages
 - ▶ Are easy to understand
 - ▶ There is a well-understood and useful theory
 - ▶ They have efficient implementation
- Let r_i be a regular expression and d_i be a distinct name

How to describe token

- By regular languages
- Regular languages
 - ▶ Are easy to understand
 - ▶ There is a well-understood and useful theory
 - ▶ They have efficient implementation
- Let r_i be a regular expression and d_i be a distinct name
- Regular definition is a sequence of definitions of the form

How to describe token

- By regular languages
- Regular languages
 - ▶ Are easy to understand
 - ▶ There is a well-understood and useful theory
 - ▶ They have efficient implementation
- Let r_i be a regular expression and d_i be a distinct name
- Regular definition is a sequence of definitions of the form
$$\begin{array}{l}d_1 \rightarrow r_1 \\d_2 \rightarrow r_2 \\d_3 \rightarrow r_3 \\ \dots\dots\dots \\d_n \rightarrow r_n\end{array}$$

How to describe token

- By regular languages
- Regular languages
 - ▶ Are easy to understand
 - ▶ There is a well-understood and useful theory
 - ▶ They have efficient implementation
- Let r_i be a regular expression and d_i be a distinct name
- Regular definition is a sequence of definitions of the form
$$\begin{array}{l}d_1 \rightarrow r_1 \\d_2 \rightarrow r_2 \\d_3 \rightarrow r_3 \\ \dots\dots\dots \\d_n \rightarrow r_n\end{array}$$
- Where each r_i is a regular expression over $\sum \cup d_1 \cup d_2 \cup \dots \cup d_{i-1}$

Regular expressions in specifications

- Regular expressions are only specifications; implementation is still required.

Regular expressions in specifications

- Regular expressions are only specifications; implementation is still required.
- Given a string s and a regular expression R , does $s \in L(R)$?

Regular expressions in specifications

- Regular expressions are only specifications; implementation is still required.
- Given a string s and a regular expression R , does $s \in L(R)$?
- Solution to this problem is the basis of the lexical analyzers.

Regular expressions in specifications

- Regular expressions are only specifications; implementation is still required.
- Given a string s and a regular expression R , does $s \in L(R)$?
- Solution to this problem is the basis of the lexical analyzers.
- Just the yes/no answer is not important.

Regular expressions in specifications

- Regular expressions are only specifications; implementation is still required.
- Given a string s and a regular expression R , does $s \in L(R)$?
- Solution to this problem is the basis of the lexical analyzers.
- Just the yes/no answer is not important.
- **Goal: Partition the input into tokens.**

Regular expressions in specifications

- Regular expressions are only specifications; implementation is still required.
- Given a string s and a regular expression R , does $s \in L(R)$?
- Solution to this problem is the basis of the lexical analyzers.
- Just the yes/no answer is not important.
- **Goal: Partition the input into tokens.**

Algorithm

- 1 Construct R merging all the regular expressions
 $R = R_1 + R_2 + R_3 + \dots$

Regular expressions in specifications

- Regular expressions are only specifications; implementation is still required.
- Given a string s and a regular expression R , does $s \in L(R)$?
- Solution to this problem is the basis of the lexical analyzers.
- Just the yes/no answer is not important.
- **Goal: Partition the input into tokens.**

Algorithm

- 1 Construct R merging all the regular expressions
 $R = R_1 + R_2 + R_3 + \dots$
- 2 Let input be $x_1 \dots x_n$ then task is for $1 \leq i \leq n$ check $x_1 \dots x_i \in L(R)$

Regular expressions in specifications

- Regular expressions are only specifications; implementation is still required.
- Given a string s and a regular expression R , does $s \in L(R)$?
- Solution to this problem is the basis of the lexical analyzers.
- Just the yes/no answer is not important.
- **Goal: Partition the input into tokens.**

Algorithm

- 1 Construct R merging all the regular expressions
 $R = R_1 + R_2 + R_3 + \dots$
- 2 Let input be $x_1 \dots x_n$ then task is for $1 \leq i \leq n$ check $x_1 \dots x_i \in L(R)$
- 3 $x_1 \dots x_i \in L(R) \rightarrow x_1 \dots x_i \in L(R_j)$ for some j . smallest such j is token class of $x_1 \dots x_i$

Regular expressions in specifications

- Regular expressions are only specifications; implementation is still required.
- Given a string s and a regular expression R , does $s \in L(R)$?
- Solution to this problem is the basis of the lexical analyzers.
- Just the yes/no answer is not important.
- **Goal: Partition the input into tokens.**

Algorithm

- 1 Construct R merging all the regular expressions
 $R = R_1 + R_2 + R_3 + \dots$
- 2 Let input be $x_1 \dots x_n$ then task is for $1 \leq i \leq n$ check $x_1 \dots x_i \in L(R)$
- 3 $x_1 \dots x_i \in L(R) \rightarrow x_1 \dots x_i \in L(R_j)$ for some j . smallest such j is token class of $x_1 \dots x_i$
- 4 Remove $x_1 \dots x_i$ from input; go to (2)

Cont...

- The algorithm gives priority to tokens listed earlier

Cont...

- The algorithm gives priority to tokens listed earlier
Treats `if` as a keyword and not an identifier

Cont...

- The algorithm gives priority to tokens listed earlier
Treats `if` as a keyword and not an identifier
- How much input is used? What if
 - ▶ $x_1 \dots x_i \in L(R)$
 - ▶ $x_1 \dots x_j \in L(R)$

Cont...

- The algorithm gives priority to tokens listed earlier
Treats `if` as a keyword and not an identifier
- How much input is used? What if
 - ▶ $x_1 \dots x_i \in L(R)$
 - ▶ $x_1 \dots x_j \in L(R)$
 - ▶ Pick up the longest possible string in $L(R)$

Cont...

- The algorithm gives priority to tokens listed earlier
Treats `if` as a keyword and not an identifier
- How much input is used? What if
 - ▶ $x_1 \dots x_i \in L(R)$
 - ▶ $x_1 \dots x_j \in L(R)$
 - ▶ Pick up the longest possible string in $L(R)$
 - ▶ The principle of **maximal munch**
- Regular expressions provide a concise and useful notation for string patterns

Cont...

- The algorithm gives priority to tokens listed earlier
Treats `if` as a keyword and not an identifier
- How much input is used? What if
 - ▶ $x_1 \dots x_i \in L(R)$
 - ▶ $x_1 \dots x_j \in L(R)$
 - ▶ Pick up the longest possible string in $L(R)$
 - ▶ The principle of **maximal munch**
- Regular expressions provide a concise and useful notation for string patterns
- Good algorithms require a single pass over the input