



Lecture 30

Code Generation

Awanish Pandey

Department of Computer Science and Engineering
Indian Institute of Technology
Roorkee

April 11, 2025

Rearranging order of the code

- $a + e * (c + d)$

Rearranging order of the code

- $a + e * (c + d)$
- Minimum registers required for correct execution?

Rearranging order of the code

- $a + e * (c + d)$
 - Minimum registers required for correct execution?
- 1 $R_0 = a$

Rearranging order of the code

- $a + e * (c + d)$
 - Minimum registers required for correct execution?
- 1 $R_0 = a$
 - 2 $R_1 = c$

Rearranging order of the code

- $a + e * (c + d)$
 - Minimum registers required for correct execution?
- 1 $R_0 = a$
 - 2 $R_1 = c$
 - 3 $R_2 = d$

Rearranging order of the code

- $a + e * (c + d)$
- Minimum registers required for correct execution?

① $R_0 = a$

② $R_1 = c$

③ $R_2 = d$

④ $R_1 = R_1 + R_2$

Rearranging order of the code

- $a+e*(c+d)$
- Minimum registers required for correct execution?

① $R_0 = a$

② $R_1 = c$

③ $R_2 = d$

④ $R_1 = R_1 + R_2$

⑤ $R_2 = e$

Rearranging order of the code

- $a + e * (c + d)$
- Minimum registers required for correct execution?

① $R_0 = a$

② $R_1 = c$

③ $R_2 = d$

④ $R_1 = R_1 + R_2$

⑤ $R_2 = e$

⑥ $R_2 = R_2 * R_1$

Rearranging order of the code

- $a + e * (c + d)$
- Minimum registers required for correct execution?

① $R_0 = a$

② $R_1 = c$

③ $R_2 = d$

④ $R_1 = R_1 + R_2$

⑤ $R_2 = e$

⑥ $R_2 = R_2 * R_1$

⑦ $R_0 = R_0 + R_2$

Rearranging order of the code

- $a + e * (c + d)$
- Minimum registers required for correct execution?

① $R_0 = a$

② $R_1 = c$

③ $R_2 = d$

④ $R_1 = R_1 + R_2$

⑤ $R_2 = e$

⑥ $R_2 = R_2 * R_1$

⑦ $R_0 = R_0 + R_2$

① $R_0 = c$

Rearranging order of the code

- $a + e * (c + d)$
- Minimum registers required for correct execution?

① $R_0 = a$

② $R_1 = c$

③ $R_2 = d$

④ $R_1 = R_1 + R_2$

⑤ $R_2 = e$

⑥ $R_2 = R_2 * R_1$

⑦ $R_0 = R_0 + R_2$

① $R_0 = c$

② $R_1 = d$

Rearranging order of the code

- $a+e*(c+d)$
- Minimum registers required for correct execution?

① $R_0 = a$

② $R_1 = c$

③ $R_2 = d$

④ $R_1 = R_1 + R_2$

⑤ $R_2 = e$

⑥ $R_2 = R_2 * R_1$

⑦ $R_0 = R_0 + R_2$

① $R_0 = c$

② $R_1 = d$

③ $R_0 = R_0 + R_1$

Rearranging order of the code

- $a + e * (c + d)$
- Minimum registers required for correct execution?

① $R_0 = a$

② $R_1 = c$

③ $R_2 = d$

④ $R_1 = R_1 + R_2$

⑤ $R_2 = e$

⑥ $R_2 = R_2 * R_1$

⑦ $R_0 = R_0 + R_2$

① $R_0 = c$

② $R_1 = d$

③ $R_0 = R_0 + R_1$

④ $R_1 = e$

Rearranging order of the code

- $a + e * (c + d)$
- Minimum registers required for correct execution?

① $R_0 = a$

② $R_1 = c$

③ $R_2 = d$

④ $R_1 = R_1 + R_2$

⑤ $R_2 = e$

⑥ $R_2 = R_2 * R_1$

⑦ $R_0 = R_0 + R_2$

① $R_0 = c$

② $R_1 = d$

③ $R_0 = R_0 + R_1$

④ $R_1 = e$

⑤ $R_1 = R_1 * R_0$

Rearranging order of the code

- $a + e * (c + d)$
- Minimum registers required for correct execution?

① $R_0 = a$

② $R_1 = c$

③ $R_2 = d$

④ $R_1 = R_1 + R_2$

⑤ $R_2 = e$

⑥ $R_2 = R_2 * R_1$

⑦ $R_0 = R_0 + R_2$

① $R_0 = c$

② $R_1 = d$

③ $R_0 = R_0 + R_1$

④ $R_1 = e$

⑤ $R_1 = R_1 * R_0$

⑥ $R_0 = a$

Rearranging order of the code

- $a + e * (c + d)$
- Minimum registers required for correct execution?

① $R_0 = a$

② $R_1 = c$

③ $R_2 = d$

④ $R_1 = R_1 + R_2$

⑤ $R_2 = e$

⑥ $R_2 = R_2 * R_1$

⑦ $R_0 = R_0 + R_2$

① $R_0 = c$

② $R_1 = d$

③ $R_0 = R_0 + R_1$

④ $R_1 = e$

⑤ $R_1 = R_1 * R_0$

⑥ $R_0 = a$

⑦ $R_0 = R_0 + R_1$

Register allocation

- When should we do?

Register allocation

- When should we do?
 - ▶ Instruction Selection

Register allocation

- When should we do?
 - ▶ Instruction Selection
 - ▶ Instruction Reordering

Register allocation

- When should we do?
 - ▶ Instruction Selection
 - ▶ Instruction Reordering
- Type of allocator

Register allocation

- When should we do?
 - ▶ Instruction Selection
 - ▶ Instruction Reordering
- Type of allocator
 - ▶ Using usages count

Register allocation

- When should we do?
 - ▶ Instruction Selection
 - ▶ Instruction Reordering
- Type of allocator
 - ▶ Using usages count
 - ▶ Graph coloring based (Near optimal/ Build interference graph)

Register allocation

- When should we do?
 - ▶ Instruction Selection
 - ▶ Instruction Reordering
- Type of allocator
 - ▶ Using usages count
 - ▶ Graph coloring based (Near optimal/ Build interference graph)
 - ▶ linear scan (Fast)

Register allocation

- When should we do?
 - ▶ Instruction Selection
 - ▶ Instruction Reordering
- Type of allocator
 - ▶ Using usages count
 - ▶ Graph coloring based (Near optimal/ Build interference graph)
 - ▶ linear scan (Fast)
 - ▶ Local register allocation

Problem in Simple Code Generator

Problem in Simple Code Generator

- Visibility of only current instruction.

Problem in Simple Code Generator

- Visibility of only current instruction.
- DAG of the basic block will give more visibility

Problem in Simple Code Generator

- Visibility of only current instruction.
- DAG of the basic block will give more visibility
 - ▶ It stores data dependencies

Problem in Simple Code Generator

- Visibility of only current instruction.
- DAG of the basic block will give more visibility
 - ▶ It stores data dependencies
 - ▶ Helps in common sub-expression elimination

Problem in Simple Code Generator

- Visibility of only current instruction.
- DAG of the basic block will give more visibility
 - ▶ It stores data dependencies
 - ▶ Helps in common sub-expression elimination
 - ▶ Useful in identifying code generation order

Problem in Simple Code Generator

- Visibility of only current instruction.
- DAG of the basic block will give more visibility
 - ▶ It stores data dependencies
 - ▶ Helps in common sub-expression elimination
 - ▶ Useful in identifying code generation order
 - ▶ Useful in instruction reordering

Problem in Simple Code Generator

- Visibility of only current instruction.
- DAG of the basic block will give more visibility
 - ▶ It stores data dependencies
 - ▶ Helps in common sub-expression elimination
 - ▶ Useful in identifying code generation order
 - ▶ Useful in instruction reordering
- Code generation based on DAG

Problem in Simple Code Generator

- Visibility of only current instruction.
- DAG of the basic block will give more visibility
 - ▶ It stores data dependencies
 - ▶ Helps in common sub-expression elimination
 - ▶ Useful in identifying code generation order
 - ▶ Useful in instruction reordering
- Code generation based on DAG
 - ▶ Perform topological numbering for the DAG nodes

Problem in Simple Code Generator

- Visibility of only current instruction.
- DAG of the basic block will give more visibility
 - ▶ It stores data dependencies
 - ▶ Helps in common sub-expression elimination
 - ▶ Useful in identifying code generation order
 - ▶ Useful in instruction reordering
- Code generation based on DAG
 - ▶ Perform topological numbering for the DAG nodes
 - ▶ Generate code for nodes in reverse topological ordering

Problem in Simple Code Generator

- Visibility of only current instruction.
- DAG of the basic block will give more visibility
 - ▶ It stores data dependencies
 - ▶ Helps in common sub-expression elimination
 - ▶ Useful in identifying code generation order
 - ▶ Useful in instruction reordering
- Code generation based on DAG
 - ▶ Perform topological numbering for the DAG nodes
 - ▶ Generate code for nodes in reverse topological ordering
 - ▶ Optimal code generation is NP-hard

Optimal Code Generation in case of tree (assuming sufficient registers)

Optimal Code Generation in case of tree (assuming sufficient registers)

- Ershov Numbers: Numbers of registers needed to evaluate a node without storing any temporaries.

Optimal Code Generation in case of tree (assuming sufficient registers)

- Ershov Numbers: Numbers of registers needed to evaluate a node without storing any temporaries.
 - ▶ Label all leaves as 1.

Optimal Code Generation in case of tree (assuming sufficient registers)

- Ershov Numbers: Numbers of registers needed to evaluate a node without storing any temporaries.
 - ▶ Label all leaves as 1.
 - ▶ The label of an interior node with one child is the label of its child

Optimal Code Generation in case of tree (assuming sufficient registers)

- Ershov Numbers: Numbers of registers needed to evaluate a node without storing any temporaries.
 - ▶ Label all leaves as 1.
 - ▶ The label of an interior node with one child is the label of its child
 - ▶ The label of an interior node with two children

Optimal Code Generation in case of tree (assuming sufficient registers)

- Ershov Numbers: Numbers of registers needed to evaluate a node without storing any temporaries.
 - ▶ Label all leaves as 1.
 - ▶ The label of an interior node with one child is the label of its child
 - ▶ The label of an interior node with two children
 - ★ Larger of the label of its children if those labels are different.

Optimal Code Generation in case of tree (assuming sufficient registers)

- Ershov Numbers: Numbers of registers needed to evaluate a node without storing any temporaries.
 - ▶ Label all leaves as 1.
 - ▶ The label of an interior node with one child is the label of its child
 - ▶ The label of an interior node with two children
 - ★ Larger of the label of its children if those labels are different.
 - ★ One plus the label of its children if both the labels are same.

Optimal Code Generation in case of tree (assuming sufficient registers)

- Ershov Numbers: Numbers of registers needed to evaluate a node without storing any temporaries.
 - ▶ Label all leaves as 1.
 - ▶ The label of an interior node with one child is the label of its child
 - ▶ The label of an interior node with two children
 - ★ Larger of the label of its children if those labels are different.
 - ★ One plus the label of its children if both the labels are same.
- Recursive algo, start from root node. If a node is labelled as k then only k registers will be used

Optimal Code Generation in case of tree (assuming sufficient registers)

- Ershov Numbers: Numbers of registers needed to evaluate a node without storing any temporaries.
 - ▶ Label all leaves as 1.
 - ▶ The label of an interior node with one child is the label of its child
 - ▶ The label of an interior node with two children
 - ★ Larger of the label of its children if those labels are different.
 - ★ One plus the label of its children if both the labels are same.
- Recursive algo, start from root node. If a node is labelled as k then only k registers will be used
- There is a "base" $b \geq 1$ for registers use. so that actual registers used are $R_b, R_{b+1}, \dots, R_{b+k-1}$ and the result always appears in R_{b+k-1}

Optimal Code Generation in case of tree (assuming sufficient registers)

- Ershov Numbers: Numbers of registers needed to evaluate a node without storing any temporaries.
 - ▶ Label all leaves as 1.
 - ▶ The label of an interior node with one child is the label of its child
 - ▶ The label of an interior node with two children
 - ★ Larger of the label of its children if those labels are different.
 - ★ One plus the label of its children if both the labels are same.
- Recursive algo, start from root node. If a node is labelled as k then only k registers will be used
- There is a "base" $b \geq 1$ for registers use. so that actual registers used are $R_b, R_{b+1}, \dots, R_{b+k-1}$ and the result always appears in R_{b+k-1}
- For a leaf operand x , if base is b generate the instruction LD R_b, x