

Vietnam–Korea University of Information and Communication Technology

VKU_TLE_WA_CE

Vo Nguyen Hoang An, Nguyen Tung Lam, Nguyen Van Phung

The ICPC 2026 - Vietnam Central Provincial Contest

Oct 25, 2026

1 Contest 1

2 Mathematics 1

3 Data structures 2

4 Numerical 5

5 Number theory 6

6 Combinatorial 9

7 Graph 10

8 Geometry 15

9 Strings 17

10 Various 18

Contest (1)

template.cpp

```cpp
#include <bits/stdc++.h>
using namespace std;
#define rep(i, a, b) for (int i = a; i < (b); ++i)
#define sz(x) (int)(x).size()
#define all(x) begin(x), end(x)
#define rall(x) rbegin(x), rend(x)
#define nl "\n"
typedef long long ll;
typedef pair<int, int> pii;
typedef vector<int> vi;
int main() {
    cin.tie(0)->sync_with_stdio(0);
    cin.exceptions(cin.failbit);
}
```

template.py

```python
import sys
sys.setrecursionlimit(10000000)
from collections import deque, Counter, defaultdict
from bisect import bisect_left, bisect_right, insort
from heapq import (
    heapify, heappush, heappop,
    heappushpop, heapreplace,
    nlargest, nsmallest
)
from itertools import (
    accumulate, permutations, combinations,
    combinations_with_replacement,
    product, groupby, chain
)
from functools import lru_cache, cmp_to_key, reduce
from operator import itemgetter, mul, xor
# Only need when problem state
from fractions import Fraction
from decimal import Decimal, getcontext
from array import array
```

.bashrc

```
alias c='g++ -Wall -Wconversion -Wfatal-errors -g -std=c++17 -
    fsanitize=undefined,address'
alias co='g++ -O2 -std=c++17'
ulimit -s unlimited
xmodmap -e 'clear lock' -e 'keycode 66 = Control_L' -e 'add
    Control = Control_L'
setxkbmap -option ctrl:nocaps
gsettings set org.gnome.desktop.input-sources xkb-options "['
    ctrl:nocaps']"
```

.vimrc

```
set cin aw ai is ts=4 sw=4 tm=50 nu noeb bg=dark ru cul
sy on | im jk <esc> | im kj <esc> | no ; :
" Select region and then type :Hash to hash your selection.
ca Hash w !cpp -dD -P -fpreprocessed \| tr -d '[:space:]' \|
    md5sum \| cut -c-6
nnoremap <F1> :w<CR>:!g++ -Wall -Wconversion -Wfatal-errors -g
    -std=c++17 -fsanitize=undefined,address % -o %:r && ./%:r<
    CR>
```

hash.sh

```
# Hashes a file, ignoring all whitespace and comments. Use for
# verifying that code was correctly typed.
cpp -dD -P -fpreprocessed | tr -d '[:space:]'| md5sum |cut -c-6
```

troubleshoot.txt

```
- Pre-submit:
Write a few simple test cases if sample is not enough.
Are time limits close? If so, generate max cases.
Is the memory usage fine?
Could anything overflow?
Make sure to submit the right file.
- Wrong answer:
Print your solution! Print debug output, as well.
Are you clearing all data structures between test cases?
Can your algorithm handle the whole range of input?
Read the full problem statement again.
Do you handle all corner cases correctly?
Have you understood the problem correctly?
Any uninitialized variables?
Any overflows?
Confusing N and M, i and j, etc.?
Are you sure your algorithm works?
What special cases have you not thought of?
Are you sure the STL functions you use work as you think?
Add some assertions, maybe resubmit.
Create some testcases to run your algorithm on.
Go through the algorithm for a simple case.
Go through this list again.
Explain your algorithm to a teammate.
Ask the teammate to look at your code.
Go for a small walk, e.g. to the toilet.
Is your output format correct? (including whitespace)
Rewrite your solution from the start or let a teammate do it.
- Runtime error:
Have you tested all corner cases locally?
Any uninitialized variables?
Are you reading or writing outside the range of any vector?
Any assertions that might fail?
Any possible division by 0? (mod 0 for example)
Any possible infinite recursion?
Invalidated pointers or iterators?
Are you using too much memory?
Debug with resubmits (e.g. remapped signals, see Various).
- Time limit exceeded:
Do you have any possible infinite loops?
What is the complexity of your algorithm?
Are you copying a lot of unnecessary data? (References)
How big is the input and output? (consider scanf)
Avoid vector, map. (use arrays/unordered_map)
What do your teammates think about your algorithm?
- Memory limit exceeded:
What is the max amount of memory your algorithm should need?
Are you clearing all data structures between test cases?
```

Mathematics (2)

2.1 Equations

$$ax^2 + bx + c = 0 \Rightarrow x = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}$$

The extremum is given by $x = -b/2a$.

$$\begin{aligned} ax + by &= e \\ cx + dy &= f \end{aligned} \Rightarrow \begin{aligned} x &= \frac{ed - bf}{ad - bc} \\ y &= \frac{af - ec}{ad - bc} \end{aligned}$$

In general, given an equation $Ax = b$, the solution to a variable x_i is given by

$$x_i = \frac{\det A_i'}{\det A}$$

where A_i' is A with the i'th column replaced by b.

2.2 Recurrences

If $a_n = c_1 a_{n-1} + \cdots + c_k a_{n-k}$, and $r_1, \ldots, r_k$ are distinct roots of $x^k - c_1 x^{k-1} - \cdots - c_k$, there are $d_1, \ldots, d_k$ s.t.

$$a_n = d_1 r_1^n + \cdots + d_k r_k^n.$$

Non-distinct roots r become polynomial factors, e.g. $a_n = (d_1 n + d_2) r^n$.

2.3 Trigonometry

$$a\cos x + b\sin x = r\cos(x - \phi)$$
$$a\sin x + b\cos x = r\sin(x + \phi)$$

where $r = \sqrt{a^2 + b^2}, \phi = \operatorname{atan2}(b, a)$.

2.4 Geometry

2.4.1 Triangles

Side lengths: a, b, c

Semiperimeter: $p = \frac{a + b + c}{2}$

Area: $A = \sqrt{p(p-a)(p-b)(p-c)}$

Circumradius: $R = \frac{abc}{4A}$

Inradius: $r = \frac{A}{p}$

Length of median (divides triangle into two equal-area triangles): $m_a = \frac{1}{2}\sqrt{2b^2 + 2c^2 - a^2}$

Length of bisector (divides angles in two):

$$s_a = \sqrt{bc\left[1 - \left(\frac{a}{b+c}\right)^2\right]}$$

Law of sines: $\frac{\sin\alpha}{a} = \frac{\sin\beta}{b} = \frac{\sin\gamma}{c} = \frac{1}{2R}$

Law of cosines: $a^2 = b^2 + c^2 - 2bc\cos\alpha$

Law of tangents: $\frac{a+b}{a-b} = \frac{\tan\frac{\alpha+\beta}{2}}{\tan\frac{\alpha-\beta}{2}}$

2.4.2 Quadrilaterals

With side lengths a, b, c, d, diagonals e, f, diagonals angle θ, area A and magic flux $F = b^2 + d^2 - a^2 - c^2$:

$$4A = 2ef \cdot \sin\theta = F\tan\theta = \sqrt{4e^2f^2 - F^2}$$

For cyclic quadrilaterals the sum of opposite angles is $180°$, $ef = ac + bd$, and $A = \sqrt{(p-a)(p-b)(p-c)(p-d)}$.

2.4.3 Pick's Theorem

For a simple polygon with integer coordinates:

$$A = I + \frac{B}{2} - 1 \iff I = \frac{2A - B + 2}{2}$$

I: Number of integer lattice points strictly **inside** the polygon.
B: Number of integer lattice points on the **boundary** (including vertices):
A: Area of the polygon.

$$B = \sum_{i=0}^{n-1} \gcd(|x_i - x_{(i+1)\%n}|, |y_i - y_{(i+1)\%n}|)$$

Implementation Notes:
Avoid floats: Use `polygonArea2` directly to get $2A = |$`polygonArea2(pts)`$|$, then compute $I = (2A - B + 2)/2$ via integer arithmetic.
Orientation: Wrap `polygonArea2` with `abs()` since clockwise vertex ordering produces a negative signed area.
Overflow: Cast coordinates to `Point<long long>`; cross products overflow 32-bit signed integers when coordinates $\geq 10^5$.
Ordering: Vertices must appear in sequential order around the polygon boundary (e.g., from input or output of `convexHull`).

2.5 Sums

$$c^a + c^{a+1} + \cdots + c^b = \frac{c^{b+1} - c^a}{c-1}, c \neq 1$$

$$1 + 2 + 3 + \cdots + n = \frac{n(n+1)}{2}$$

$$1^2 + 2^2 + 3^2 + \cdots + n^2 = \frac{n(2n+1)(n+1)}{6}$$

$$1^3 + 2^3 + 3^3 + \cdots + n^3 = \frac{n^2(n+1)^2}{4}$$

$$1^4 + 2^4 + 3^4 + \cdots + n^4 = \frac{n(n+1)(2n+1)(3n^2+3n-1)}{30}$$

2.6 Stars and Bars

Number of ways to distribute n identical items into k distinct bins (or number of integer solutions to $x_1 + x_2 + \cdots + x_k = n$):
Non-negative integers ($x_i \geq 0$, empty bins allowed):

$$\binom{n+k-1}{k-1} = \binom{n+k-1}{n}$$

Positive integers ($x_i \geq 1$, each bin has at least 1 item, $n \geq k$):

$$\binom{n-1}{k-1}$$

Arbitrary lower bounds ($x_i \geq c_i$): Let $n' = n - \sum_{i=1}^{k} c_i$. If $n' \geq 0$:

$$\binom{n'+k-1}{k-1}$$

Upper bounds ($x_i \leq u_i$): Apply the Principle of Inclusion-Exclusion by negating constraints ($x_i \geq u_i + 1$).

2.6.1 Geometric Series Modulo Arbitrary M

To compute $S(n) = \sum_{i=0}^{n} a^i = 1 + a + a^2 + \cdots + a^n \pmod M$ in $\mathcal{O}(\log^2 n)$ (or $\mathcal{O}(\log n)$) without requiring modular inverse (valid for composite M): If $n = 0$: $S(0) = 1$.
If n is odd ($n+1$ terms is even):

$$S(n) = \left(1 + a^{\frac{n+1}{2}}\right) S\left(\frac{n-1}{2}\right) \pmod M$$

If n is even ($n+1$ terms is odd):

$$S(n) = 1 + a \cdot S(n-1) \pmod M$$

```
ll geomSeries(ll a, ll n, ll m) {
  if (n == 0) return 1 % m;
  if (n % 2) {
    ll half = geomSeries(a, (n - 1) / 2, m);
    ll p = modpow(a, (n + 1) / 2, m);
    return (__int128)(1 + p) * half % m;
  }
  return (1 + (__int128)(a % m) * geomSeries(a, n - 1, m)) % m;
}
```

2.7 Probability theory

Let X be a discrete random variable with probability $p_X(x)$ of assuming the value x. It will then have an expected value (mean) $\mu = \mathbb{E}(X) = \sum_x x p_X(x)$ and variance $\sigma^2 = V(X) = \mathbb{E}(X^2) - (\mathbb{E}(X))^2 = \sum_x (x - \mathbb{E}(X))^2 p_X(x)$ where σ is the standard deviation. If X is instead continuous it will have a probability density function $f_X(x)$ and the sums above will instead be integrals with $p_X(x)$ replaced by $f_X(x)$.

Expectation is linear:

$$\mathbb{E}(aX + bY) = a\mathbb{E}(X) + b\mathbb{E}(Y)$$

For independent X and Y,

$$V(aX + bY) = a^2V(X) + b^2V(Y).$$

2.7.1 Discrete distributions

Binomial distribution

The number of successes in n independent yes/no experiments, each which yields success with probability p is $\text{Bin}(n, p)$, $n = 1, 2, \ldots, 0 \leq p \leq 1$.

$$p(k) = \binom{n}{k} p^k (1-p)^{n-k}$$

$$\mu = np,\ \sigma^2 = np(1-p)$$

$\text{Bin}(n, p)$ is approximately $\text{Po}(np)$ for small p.

First success distribution

The number of trials needed to get the first success in independent yes/no experiments, each which yields success with probability p is $\text{Fs}(p)$, $0 \leq p \leq 1$.

$$p(k) = p(1-p)^{k-1},\ k = 1, 2, \ldots$$

$$\mu = \frac{1}{p},\ \sigma^2 = \frac{1-p}{p^2}$$

Data structures (3)

OrderStatisticTree.h
Description: A set (not multiset!) with support for finding the n'th element, and finding the index of an element. To get a map, change `null_type`.
Time: $\mathcal{O}(\log N)$ 782797, 16 lines

```
#include <bits/extc++.h>
using namespace __gnu_pbds;

template<class T>
using Tree = tree<T, null_type, less<T>, rb_tree_tag,
    tree_order_statistics_node_update>;

void example() {
  Tree<int> t, t2; t.insert(8);
```

```
  auto it = t.insert(10).first;
  assert(it == t.lower_bound(9));
  assert(t.order_of_key(10) == 1);
  assert(t.order_of_key(11) == 2);
  assert(*t.find_by_order(0) == 8);
  t.join(t2); // assuming T < T2 or T > T2, merge t2 into t
}
```

HashMap.h

Description: Hash map with mostly the same API as unordered_map, but ~3x faster. Uses 1.5x memory. Initial capacity must be a power of 2 (if provided).

d77092, 7 lines

```
#include <bits/extc++.h>
// To use most bits rather than just the lowest ones:
struct chash { // large odd number for C
  const uint64_t C = ll(4e18 * acos(0)) | 71;
  ll operator()(ll x) const { return __builtin_bswap64(x*C); }
};
__gnu_pbds::gp_hash_table<ll,int,chash> h({},{},{},{},{1<<16});
```

SegmentTree.h

Description: Zero-indexed max-tree. Bounds are inclusive to the left and exclusive to the right. Can be changed by modifying T, f and unit.
Time: $\mathcal{O}(\log N)$

0f4bdb, 19 lines

```
struct Tree {
  typedef int T;
  static constexpr T unit = INT_MIN;
  T f(T a, T b) { return max(a, b); } // (any associative fn)
  vector<T> s; int n;
  Tree(int n = 0, T def = unit) : s(2*n, def), n(n) {}
  void update(int pos, T val) {
    for (s[pos += n] = val; pos /= 2;)
      s[pos] = f(s[pos * 2], s[pos * 2 + 1]);
  }
  T query(int b, int e) { // query [b, e)
    T ra = unit, rb = unit;
    for (b += n, e += n; b < e; b /= 2, e /= 2) {
      if (b % 2) ra = f(ra, s[b++]);
      if (e % 2) rb = f(s[--e], rb);
    }
    return f(ra, rb);
  }
};
```

LazySegmentTree.h

Description: Segment tree with ability to add or set values of large intervals, and compute max of intervals. Can be changed to other things. Use with a bump allocator for better performance, and SmallPtr or implicit indices to save memory.
Usage: `Node* tr = new Node(v, 0, sz(v));`
Time: $\mathcal{O}(\log N)$.

"../various/BumpAllocator.h" 34ecf5, 50 lines

```
const int inf = 1e9;
struct Node {
  Node *l = 0, *r = 0;
  int lo, hi, mset = inf, madd = 0, val = -inf;
  Node(int lo,int hi):lo(lo),hi(hi){} // Large interval of -inf
  Node(vi& v, int lo, int hi) : lo(lo), hi(hi) {
    if (lo + 1 < hi) {
      int mid = lo + (hi - lo)/2;
      l = new Node(v, lo, mid); r = new Node(v, mid, hi);
      val = max(l->val, r->val);
    }
    else val = v[lo];
  }
  int query(int L, int R) {
    if (R <= lo || hi <= L) return -inf;
    if (L <= lo && hi <= R) return val;
    push();
    return max(l->query(L, R), r->query(L, R));
  }
  void set(int L, int R, int x) {
    if (R <= lo || hi <= L) return;
    if (L <= lo && hi <= R) mset = val = x, madd = 0;
    else {
      push(), l->set(L, R, x), r->set(L, R, x);
      val = max(l->val, r->val);
    }
  }
  void add(int L, int R, int x) {
    if (R <= lo || hi <= L) return;
    if (L <= lo && hi <= R) {
      if (mset != inf) mset += x;
      else madd += x;
      val += x;
    }
    else {
      push(), l->add(L, R, x), r->add(L, R, x);
      val = max(l->val, r->val);
    }
  }
  void push() {
    if (!l) {
      int mid = lo + (hi - lo)/2;
      l = new Node(lo, mid); r = new Node(mid, hi);
    }
    if (mset != inf)
      l->set(lo,hi,mset), r->set(lo,hi,mset), mset = inf;
    else if (madd)
      l->add(lo,hi,madd), r->add(lo,hi,madd), madd = 0;
  }
};
```

UnionFindRollback.h

Description: Disjoint-set data structure with undo. If undo is not needed, skip st, time() and rollback().
Usage: `int t = uf.time(); ...; uf.rollback(t);`
Time: $\mathcal{O}(\log(N))$

de4ad0, 21 lines

```
struct RollbackUF {
  vi e; vector<pii> st;
  RollbackUF(int n) : e(n, -1) {}
  int size(int x) { return -e[find(x)]; }
  int find(int x) { return e[x] < 0 ? x : find(e[x]); }
  int time() { return sz(st); }
  void rollback(int t) {
    for (int i = time(); i --> t;)
      e[st[i].first] = st[i].second;
    st.resize(t);
  }
  bool join(int a, int b) {
    a = find(a), b = find(b);
    if (a == b) return false;
    if (e[a] > e[b]) swap(a, b);
    st.push_back({a, e[a]});
    st.push_back({b, e[b]});
    e[a] += e[b]; e[b] = a;
    return true;
  }
};
```

SubMatrix.h

Description: Calculate submatrix sums quickly, given upper-left and lower-right corners (half-open).
Usage: `SubMatrix<int> m(matrix);`
`m.sum(0, 0, 2, 2); // top left 4 elements`
Time: $\mathcal{O}\left(N^2 + Q\right)$

c59ada, 13 lines

```
template<class T>
struct SubMatrix {
  vector<vector<T>> p;
  SubMatrix(vector<vector<T>>& v) {
    int R = sz(v), C = sz(v[0]);
    p.assign(R+1, vector<T>(C+1));
    rep(r,0,R) rep(c,0,C)
      p[r+1][c+1] = v[r][c] + p[r][c+1] + p[r+1][c] - p[r][c];
  }
  T sum(int u, int l, int d, int r) {
    return p[d][r] - p[d][l] - p[u][r] + p[u][l];
  }
};
```

Matrix.h

Description: Basic operations on square matrices.
Usage: `Matrix<int, 3> A;`
`A.d = {{{{1,2,3}}, {{4,5,6}}, {{7,8,9}}}};`
`array<int, 3> vec = {1,2,3};`
`vec = (A^N) * vec;`

<cassert> 4da5a2, 26 lines

```
template<class T, int N> struct Matrix {
  typedef Matrix M;
  array<array<T, N>, N> d{};
  M operator*(const M& m) const {
    M a;
    rep(i,0,N) rep(j,0,N)
      rep(k,0,N) a.d[i][k] += d[i][j] * m.d[j][k];
    return a;
  }
  array<T, N> operator*(const array<T, N>& vec) const {
    array<T, N> ret{};
    rep(i,0,N) rep(j,0,N) ret[i] += d[i][j] * vec[j];
    return ret;
  }
  M operator^(ll p) const {
    assert(p >= 0);
    M a, b(*this);
    rep(i,0,N) a.d[i][i] = 1;
    while (p) {
      if (p&1) a = a*b;
      b = b*b;
      p >>= 1;
    }
    return a;
  }
};
```

LineContainer.h

Description: Container where you can add lines of the form kx+m, and query maximum values at points x. Useful for dynamic programming ("convex hull trick").
Time: $\mathcal{O}(\log N)$

<cassert> 8ec1c7, 30 lines

```
struct Line {
  mutable ll k, m, p;
  bool operator<(const Line& o) const { return k < o.k; }
  bool operator<(ll x) const { return p < x; }
};

struct LineContainer : multiset<Line, less<>> {
  // (for doubles, use inf = 1/.0, div(a,b) = a/b)
  static const ll inf = LLONG_MAX;
  ll div(ll a, ll b) { // floored division
    return a / b - ((a ^ b) < 0 && a % b); }
  bool isect(iterator x, iterator y) {
```

```
    if (y == end()) return x->p = inf, 0;
    if (x->k == y->k) x->p = x->m > y->m ? inf : -inf;
    else x->p = div(y->m - x->m, x->k - y->k);
    return x->p >= y->p;
  }
  void add(ll k, ll m) {
    auto z = insert({k, m, 0}), y = z++, x = y;
    while (isect(y, z)) z = erase(z);
    if (x != begin() && isect(--x, y)) isect(x, y = erase(y));
    while ((y = x) != begin() && (--x)->p >= y->p)
      isect(x, erase(y));
  }
  ll query(ll x) {
    assert(!empty());
    auto l = *lower_bound(x);
    return l.k * x + l.m;
  }
};
```

FenwickTree.h

Description: Computes partial sums a[0] + a[1] + ... + a[pos - 1], and updates single elements a[i], taking the difference between the old and new value.
Time: Both operations are $\mathcal{O}(\log N)$.

e62fac, 22 lines

```
struct FT {
  vector<ll> s;
  FT(int n) : s(n) {}
  void update(int pos, ll dif) { // a[pos] += dif
    for (; pos < sz(s); pos |= pos + 1) s[pos] += dif;
  }
  ll query(int pos) { // sum of values in [0, pos)
    ll res = 0;
    for (; pos > 0; pos &= pos - 1) res += s[pos-1];
    return res;
  }
  int lower_bound(ll sum) {// min pos st sum of [0, pos] >= sum
    // Returns n if no sum is >= sum, or -1 if empty sum is.
    if (sum <= 0) return -1;
    int pos = 0;
    for (int pw = 1 << 25; pw; pw >>= 1) {
      if (pos + pw <= sz(s) && s[pos + pw-1] < sum)
        pos += pw, sum -= s[pos-1];
    }
    return pos;
  }
};
```

FenwickTree2d.h

Description: Computes sums a[i,j] for all i<I, j<J, and increases single elements a[i,j]. Requires that the elements to be updated are known in advance (call fakeUpdate() before init()).
Time: $\mathcal{O}\left(\log^2 N\right)$. (Use persistent segment trees for $\mathcal{O}(\log N)$.)

"FenwickTree.h" 157f07, 22 lines

```
struct FT2 {
  vector<vi> ys; vector<FT> ft;
  FT2(int limx) : ys(limx) {}
  void fakeUpdate(int x, int y) {
    for (; x < sz(ys); x |= x + 1) ys[x].push_back(y);
  }
  void init() {
    for (vi& v : ys) sort(all(v)), ft.emplace_back(sz(v));
  }
  int ind(int x, int y) {
    return (int)(lower_bound(all(ys[x]), y) - ys[x].begin()); }
  void update(int x, int y, ll dif) {
    for (; x < sz(ys); x |= x + 1)
      ft[x].update(ind(x, y), dif);
  }
  ll query(int x, int y) {
    ll sum = 0;
    for (; x; x &= x - 1)
      sum += ft[x-1].query(ind(x-1, y));
    return sum;
  }
};
```

RMQ.h

Description: Range Minimum Queries on an array. Returns min(V[a], V[a + 1], ... V[b - 1]) in constant time.
Usage: `RMQ rmq(values);`
`rmq.query(inclusive, exclusive);`
Time: $\mathcal{O}(|V| \log |V| + Q)$

<cassert> 510c32, 16 lines

```
template<class T>
struct RMQ {
  vector<vector<T>> jmp;
  RMQ(const vector<T>& V) : jmp(1, V) {
    for (int pw = 1, k = 1; pw * 2 <= sz(V); pw *= 2, ++k) {
      jmp.emplace_back(sz(V) - pw * 2 + 1);
      rep(j,0,sz(jmp[k]))
        jmp[k][j] = min(jmp[k - 1][j], jmp[k - 1][j + pw]);
    }
  }
  T query(int a, int b) {
    assert(a < b); // or return inf if a == b
    int dep = 31 - __builtin_clz(b - a);
    return min(jmp[dep][a], jmp[dep][b - (1 << dep)]);
  }
};
```

BinaryTrie.h

Description: Binary Trie (0-1 Trie) for dynamic insertion, deletion, and bitwise XOR queries (maximum, minimum, and count <= k) on non-negative integers.
Usage: `BinaryTrie tr;`
`tr.insert(x); tr.erase(x);`
`tr.maxXor(x); // returns max (x ^ y) for y in trie`
`tr.minXor(x); // returns min (x ^ y) for y in trie`
`tr.countLeq(x, k); // count y in trie such that (x ^ y) <= k`
Time: $\mathcal{O}(B)$ per operation, where B is the bit length (B = 30 for <= 1e9).

<cassert> 35c8cd, 68 lines

```
struct BinaryTrie {
  static const int B = 30; // 30 bits for values < 2^30 (~1e9)
  struct Node {
    int ch[2] = {0, 0};
    int cnt = 0;
  };
  vector<Node> t = {Node()};
  void insert(int x, int v = 1) { // v = -1 to erase
    int u = 0;
    t[u].cnt += v;
    for (int i = B - 1; i >= 0; --i) {
      int b = (x >> i) & 1;
      if (!t[u].ch[b]) {
        t[u].ch[b] = sz(t);
        t.emplace_back();
      }
      u = t[u].ch[b];
      t[u].cnt += v;
    }
  }
  void erase(int x) { insert(x, -1); }
  int maxXor(int x) {
    assert(t[0].cnt > 0);
    int u = 0, res = 0;
    for (int i = B - 1; i >= 0; --i) {
      int b = (x >> i) & 1;
      if (t[u].ch[!b] && t[t[u].ch[!b]].cnt > 0) {
        res |= (1 << i);
        u = t[u].ch[!b];
      } else {
        u = t[u].ch[b];
      }
    }
    return res;
  }
  int minXor(int x) {
    assert(t[0].cnt > 0);
    int u = 0, res = 0;
    for (int i = B - 1; i >= 0; --i) {
      int b = (x >> i) & 1;
      if (t[u].ch[b] && t[t[u].ch[b]].cnt > 0) {
        u = t[u].ch[b];
      } else {
        res |= (1 << i);
        u = t[u].ch[!b];
      }
    }
    return res;
  }
  // Count number of elements y in trie such that (x ^ y) <= k
  int countLeq(int x, int k) {
        if (k < 0) return 0;
        if (k >= (1 << B)) return t[0].cnt;

        int u = 0, ans = 0;
        for (int i = B - 1; i >= 0; --i) {
            int bx = (x >> i) & 1, bk = (k >> i) & 1;
            if (bk) {
                if (t[u].ch[bx]) ans += t[t[u].ch[bx]].cnt;
                u = t[u].ch[!bx];
            } else {
                u = t[u].ch[bx];
            }
            if (!u) return ans;
        }
        return ans + t[u].cnt;
    }
};
```

MoQueries.h

Description: Answer interval or tree path queries by finding an approximate TSP through the queries, and moving from one query to the next by adding/removing points at the ends. If values are on tree edges, change `step` to add/remove the edge (a, c) and remove the initial `add` call (but keep `in`).
Time: $\mathcal{O}\left(N\sqrt{Q}\right)$

a12ef4, 49 lines

```
void add(int ind, int end) { ... } // add a[ind] (end = 0 or 1)
void del(int ind, int end) { ... } // remove a[ind]
int calc() { ... } // compute current answer

vi mo(vector<pii> Q) {
  int L = 0, R = 0, blk = 350; // ~N/sqrt(Q)
  vi s(sz(Q)), res = s;
#define K(x) pii(x.first/blk, x.second ^ -(x.first/blk & 1))
  iota(all(s), 0);
  sort(all(s), [&](int s, int t){ return K(Q[s]) < K(Q[t]); });
  for (int qi : s) {
    pii q = Q[qi];
    while (L > q.first) add(--L, 0);
    while (R < q.second) add(R++, 1);
    while (L < q.first) del(L++, 0);
    while (R > q.second) del(--R, 1);
    res[qi] = calc();
  }
```

```
  return res;
}

vi moTree(vector<array<int, 2>> Q, vector<vi>& ed, int root=0){
  int N = sz(ed), pos[2] = {}, blk = 350; // ~N/sqrt(Q)
  vi s(sz(Q)), res = s, I(N), L(N), R(N), in(N), par(N);
  add(0, 0), in[0] = 1;
  auto dfs = [&](int x, int p, int dep, auto& f) -> void {
    par[x] = p;
    L[x] = N;
    if (dep) I[x] = N++;
    for (int y : ed[x]) if (y != p) f(y, x, !dep, f);
    if (!dep) I[x] = N++;
    R[x] = N;
  };
  dfs(root, -1, 0, dfs);
#define K(x) pii(I[x[0]] / blk, I[x[1]] ^ -(I[x[0]] / blk & 1))
  iota(all(s), 0);
  sort(all(s), [&](int s, int t){ return K(Q[s]) < K(Q[t]); });
  for (int qi : s) rep(end,0,2) {
    int &a = pos[end], b = Q[qi][end], i = 0;
#define step(c) { if (in[c]) { del(a, end); in[a] = 0; } \
                  else { add(c, end); in[c] = 1; } a = c; }
    while (!(L[b] <= L[a] && R[a] <= R[b]))
      I[i++] = b, b = par[b];
    while (a != b) step(par[a]);
    while (i--) step(I[i]);
    if (end) res[qi] = calc();
  }
  return res;
}
```

Numerical (4)

4.1 Optimization

GoldenSectionSearch.h

Description: Finds the argument minimizing the function f in the interval $[a, b]$ assuming f is unimodal on the interval, i.e. has only one local minimum and no local maximum. The maximum error in the result is *eps*. Works equally well for maximization with a small change in the code. See TernarySearch.h in the Various chapter for a discrete version.
Usage: `double func(double x) { return 4+x+.3*x*x; }`
`double xmin = gss(-1000,1000,func);`
Time: $\mathcal{O}(\log((b-a)/\epsilon))$

31d45b, 14 lines

```
double gss(double a, double b, double (*f)(double)) {
  double r = (sqrt(5)-1)/2, eps = 1e-7;
  double x1 = b - r*(b-a), x2 = a + r*(b-a);
  double f1 = f(x1), f2 = f(x2);
  while (b-a > eps)
    if (f1 < f2) { //change to > to find maximum
      b = x2; x2 = x1; f2 = f1;
      x1 = b - r*(b-a); f1 = f(x1);
    } else {
      a = x1; x1 = x2; f1 = f2;
      x2 = a + r*(b-a); f2 = f(x2);
    }
  return a;
}
```

4.2 Matrices

IntDeterminant.h

Description: Calculates determinant using modular arithmetics. Modulos can also be removed to get a pure-integer version.
Time: $\mathcal{O}(N^3)$

3313dc, 18 lines

```
const ll mod = 12345;
ll det(vector<vector<ll>>& a) {
  int n = sz(a); ll ans = 1;
  rep(i,0,n) {
    rep(j,i+1,n) {
      while (a[j][i] != 0) { // gcd step
        ll t = a[i][i] / a[j][i];
        if (t) rep(k,i,n)
          a[i][k] = (a[i][k] - a[j][k] * t) % mod;
        swap(a[i], a[j]);
        ans *= -1;
      }
    }
    ans = ans * a[i][i] % mod;
    if (!ans) return 0;
  }
  return (ans + mod) % mod;
}
```

SolveLinear.h

Description: Solves $A * x = b$. If there are multiple solutions, an arbitrary one is returned. Returns rank, or -1 if no solutions. Data in A and b is lost.
Time: $\mathcal{O}(n^2 m)$

<cassert> 44c9ab, 38 lines

```
typedef vector<double> vd;
const double eps = 1e-12;

int solveLinear(vector<vd>& A, vd& b, vd& x) {
  int n = sz(A), m = sz(x), rank = 0, br, bc;
  if (n) assert(sz(A[0]) == m);
  vi col(m); iota(all(col), 0);

  rep(i,0,n) {
    double v, bv = 0;
    rep(r,i,n) rep(c,i,m)
      if ((v = fabs(A[r][c])) > bv)
        br = r, bc = c, bv = v;
    if (bv <= eps) {
      rep(j,i,n) if (fabs(b[j]) > eps) return -1;
      break;
    }
    swap(A[i], A[br]);
    swap(b[i], b[br]);
    swap(col[i], col[bc]);
    rep(j,0,n) swap(A[j][i], A[j][bc]);
    bv = 1/A[i][i];
    rep(j,i+1,n) {
      double fac = A[j][i] * bv;
      b[j] -= fac * b[i];
      rep(k,i+1,m) A[j][k] -= fac*A[i][k];
    }
    rank++;
  }

  x.assign(m, 0);
  for (int i = rank; i--;) {
    b[i] /= A[i][i];
    x[col[i]] = b[i];
    rep(j,0,i) b[j] -= A[j][i] * b[i];
  }
  return rank; // (multiple solutions if rank < m)
}
```

SolveLinearBinary.h

Description: Solves $Ax = b$ over $\mathbb{F}_2$. If there are multiple solutions, one is returned arbitrarily. Returns rank, or -1 if no solutions. Destroys A and b.
Time: $\mathcal{O}(n^2 m)$

<cassert> fa2d7a, 34 lines

```
typedef bitset<1000> bs;
int solveLinear(vector<bs>& A, vi& b, bs& x, int m) {
  int n = sz(A), rank = 0, br;
  assert(m <= sz(x));
  vi col(m); iota(all(col), 0);
  rep(i,0,n) {
    for (br=i; br<n; ++br) if (A[br].any()) break;
    if (br == n) {
      rep(j,i,n) if(b[j]) return -1;
      break;
    }
    int bc = (int)A[br]._Find_next(i-1);
    swap(A[i], A[br]);
    swap(b[i], b[br]);
    swap(col[i], col[bc]);
    rep(j,0,n) if (A[j][i] != A[j][bc]) {
      A[j].flip(i); A[j].flip(bc);
    }
    rep(j,i+1,n) if (A[j][i]) {
      b[j] ^= b[i];
      A[j] ^= A[i];
    }
    rank++;
  }

  x = bs();
  for (int i = rank; i--;) {
    if (!b[i]) continue;
    x[col[i]] = 1;
    rep(j,0,i) b[j] ^= A[j][i];
  }
  return rank; // (multiple solutions if rank < m)
}
```

MatrixInverse.h

Description: Invert matrix A. Returns rank; result is stored in A unless singular (rank < n). Can easily be extended to prime moduli; for prime powers, repeatedly set $A^{-1} = A^{-1}(2I - AA^{-1}) \pmod{p^k}$ where A^{-1} starts as the inverse of A mod p, and k is doubled in each step.
Time: $\mathcal{O}(n^3)$

ebfff6, 35 lines

```
int matInv(vector<vector<double>>& A) {
  int n = sz(A); vi col(n);
  vector<vector<double>> tmp(n, vector<double>(n));
  rep(i,0,n) tmp[i][i] = 1, col[i] = i;

  rep(i,0,n) {
    int r = i, c = i;
    rep(j,i,n) rep(k,i,n)
      if (fabs(A[j][k]) > fabs(A[r][c]))
        r = j, c = k;
    if (fabs(A[r][c]) < 1e-12) return i;
    A[i].swap(A[r]); tmp[i].swap(tmp[r]);
    rep(j,0,n)
      swap(A[j][i], A[j][c]), swap(tmp[j][i], tmp[j][c]);
    swap(col[i], col[c]);
    double v = A[i][i];
    rep(j,i+1,n) {
      double f = A[j][i] / v;
      A[j][i] = 0;
      rep(k,i+1,n) A[j][k] -= f*A[i][k];
      rep(k,0,n) tmp[j][k] -= f*tmp[i][k];
    }
    rep(j,i+1,n) A[i][j] /= v;
    rep(j,0,n) tmp[i][j] /= v;
    A[i][i] = 1;
  }

  for (int i = n-1; i > 0; --i) rep(j,0,i) {
```

```
    double v = A[j][i];
    rep(k,0,n) tmp[j][k] -= v*tmp[i][k];
  }

  rep(i,0,n) rep(j,0,n) A[col[i]][col[j]] = tmp[i][j];
  return n;
}
```

4.3 Fourier transforms

FastFourierTransform.h

Description: fft(a) computes $\hat{f}(k) = \sum_x a[x] \exp(2\pi i \cdot kx/N)$ for all k. N must be a power of 2. Useful for convolution: `conv(a, b) = c`, where $c[x] = \sum a[i]b[x-i]$. For convolution of complex numbers or more than two vectors: FFT, multiply pointwise, divide by n, reverse(start+1, end), FFT back. Rounding is safe if $(\sum a_i^2 + \sum b_i^2) \log_2 N < 9 \cdot 10^{14}$ (in practice 10^{16}; higher for random inputs). Otherwise, use NTT/FFTMod.
Time: $\mathcal{O}(N \log N)$ with $N = |A| + |B|$ ($\sim 1s$ for $N = 2^{22}$)

00ced6, 35 lines

```
typedef complex<double> C;
typedef vector<double> vd;
void fft(vector<C>& a) {
  int n = sz(a), L = 31 - __builtin_clz(n);
  static vector<complex<long double>> R(2, 1);
  static vector<C> rt(2, 1);  // (^ 10% faster if double)
  for (static int k = 2; k < n; k *= 2) {
    R.resize(n); rt.resize(n);
    auto x = polar(1.0L, acos(-1.0L) / k);
    rep(i,k,2*k) rt[i] = R[i] = i&1 ? R[i/2] * x : R[i/2];
  }
  vi rev(n);
  rep(i,0,n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
  rep(i,0,n) if (i < rev[i]) swap(a[i], a[rev[i]]);
  for (int k = 1; k < n; k *= 2)
    for (int i = 0; i < n; i += 2 * k) rep(j,0,k) {
      C z = rt[j+k] * a[i+j+k]; // (25% faster if hand-rolled)
      a[i + j + k] = a[i + j] - z;
      a[i + j] += z;
    }
}
vd conv(const vd& a, const vd& b) {
  if (a.empty() || b.empty()) return {};
  vd res(sz(a) + sz(b) - 1);
  int L = 32 - __builtin_clz(sz(res)), n = 1 << L;
  vector<C> in(n), out(n);
  copy(all(a), begin(in));
  rep(i,0,sz(b)) in[i].imag(b[i]);
  fft(in);
  for (C& x : in) x *= x;
  rep(i,0,n) out[i] = in[-i & (n - 1)] - conj(in[i]);
  fft(out);
  rep(i,0,sz(res)) res[i] = imag(out[i]) / (4 * n);
  return res;
}
```

FastFourierTransformMod.h

Description: Higher precision FFT, can be used for convolutions modulo arbitrary integers as long as $N \log_2 N \cdot \text{mod} < 8.6 \cdot 10^{14}$ (in practice 10^{16} or higher). Inputs must be in $[0, \text{mod})$.
Time: $\mathcal{O}(N \log N)$, where $N = |A| + |B|$ (twice as slow as NTT or FFT)

"FastFourierTransform.h" b82773, 22 lines

```
typedef vector<ll> vl;
template<int M> vl convMod(const vl &a, const vl &b) {
  if (a.empty() || b.empty()) return {};
  vl res(sz(a) + sz(b) - 1);
  int B=32-__builtin_clz(sz(res)), n=1<<B, cut=int(sqrt(M));
  vector<C> L(n), R(n), outs(n), outl(n);
  rep(i,0,sz(a)) L[i] = C((int)a[i] / cut, (int)a[i] % cut);
  rep(i,0,sz(b)) R[i] = C((int)b[i] / cut, (int)b[i] % cut);
  fft(L), fft(R);
  rep(i,0,n) {
    int j = -i & (n - 1);
    outl[j] = (L[i] + conj(L[j])) * R[i] / (2.0 * n);
    outs[j] = (L[i] - conj(L[j])) * R[i] / (2.0 * n) / 1i;
  }
  fft(outl), fft(outs);
  rep(i,0,sz(res)) {
    ll av = ll(real(outl[i])+.5), cv = ll(imag(outs[i])+.5);
    ll bv = ll(imag(outl[i])+.5) + ll(real(outs[i])+.5);
    res[i] = ((av % M * cut + bv) % M * cut + cv) % M;
  }
  return res;
}
```

NumberTheoreticTransform.h

Description: ntt(a) computes $\hat{f}(k) = \sum_x a[x] g^{xk}$ for all k, where $g = \text{root}^{(mod-1)/N}$. N must be a power of 2. Useful for convolution modulo specific nice primes of the form $2^a b + 1$, where the convolution result has size at most 2^a. For arbitrary modulo, see FFTMod. `conv(a, b) = c`, where $c[x] = \sum a[i]b[x-i]$. For manual convolution: NTT the inputs, multiply pointwise, divide by n, reverse(start+1, end), NTT back. Inputs must be in $[0, \text{mod})$.
Time: $\mathcal{O}(N \log N)$

617d6f, 49 lines

```
const ll NTT_MOD = (119 << 23) + 1, NTT_ROOT = 62; // =
    998244353
// For p < 2^30 there is also e.g. 5 << 25, 7 << 26, 479 << 21
// and 483 << 21 (same root). The last two are > 10^9.
typedef vector<ll> vl;

namespace ntt_impl {
ll modpow(ll b, ll e, ll m = NTT_MOD) {
  ll ans = 1; b %= m;
  for (; e; b = b * b % m, e /= 2)
    if (e & 1) ans = ans * b % m;
  return ans;
}
}

void ntt(vl &a) {
  using ntt_impl::modpow;
  const ll mod = NTT_MOD, root = NTT_ROOT;
  int n = sz(a), L = 31 - __builtin_clz(n);
  static vl rt(2, 1);
  for (static int k = 2, s = 2; k < n; k *= 2, s++) {
    rt.resize(n);
    ll z[] = {1, modpow(root, mod >> s)};
    rep(i,k,2*k) rt[i] = rt[i / 2] * z[i & 1] % mod;
  }
  vi rev(n);
  rep(i,0,n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
  rep(i,0,n) if (i < rev[i]) swap(a[i], a[rev[i]]);
  for (int k = 1; k < n; k *= 2)
    for (int i = 0; i < n; i += 2 * k) rep(j,0,k) {
      ll z = rt[j + k] * a[i + j + k] % mod, &ai = a[i + j];
      a[i + j + k] = ai - z + (z > ai ? mod : 0);
      ai += (ai + z >= mod ? z - mod : z);
    }
}
vl conv(const vl &a, const vl &b) {
  using ntt_impl::modpow;
  const ll mod = NTT_MOD;
  if (a.empty() || b.empty()) return {};
  int s = sz(a) + sz(b) - 1, B = 32 - __builtin_clz(s),
      n = 1 << B;
  ll inv = modpow(n, mod - 2);
  vl L(a), R(b), out(n);
  L.resize(n), R.resize(n);
  ntt(L), ntt(R);
  rep(i,0,n)
    out[-i & (n - 1)] = (ll)L[i] * R[i] % mod * inv % mod;
  ntt(out);
  return {out.begin(), out.begin() + s};
}
```

FastSubsetTransform.h

Description: Transform to a basis with fast convolutions of the form $c[z] = \sum_{z=x \oplus y} a[x] \cdot b[y]$, where $\oplus$ is one of AND, OR, XOR. The size of a must be a power of two.
Time: $\mathcal{O}(N \log N)$

464cf3, 16 lines

```
void FST(vi& a, bool inv) {
  for (int n = sz(a), step = 1; step < n; step *= 2) {
    for (int i = 0; i < n; i += 2 * step) rep(j,i,i+step) {
      int &u = a[j], &v = a[j + step]; tie(u, v) =
        inv ? pii(v - u, u) : pii(v, u + v); // AND
        inv ? pii(v, u - v) : pii(u + v, u); // OR
        pii(u + v, u - v);                   // XOR
    }
  }
  if (inv) for (int& x : a) x /= sz(a); // XOR only
}
vi conv(vi a, vi b) {
  FST(a, 0); FST(b, 0);
  rep(i,0,sz(a)) a[i] *= b[i];
  FST(a, 1); return a;
}
```

Number theory (5)

5.1 Modular arithmetic

ModularArithmetic.h

Description: Operators for modular arithmetic. You need to set `mod` to some number first and then you can use the structure.

<cassert>, "euclid.h" ea1ac7, 19 lines

```
const ll mod = 17; // change to something else
struct Mod {
  ll x;
  Mod(ll y) : Mod(y%mod+mod,0){}
  Mod(ll y,int) : x(y<mod?y:y-mod){}
  Mod operator+(Mod b) { return {x + b.x,0}; }
  Mod operator-(Mod b) { return {x - b.x + mod,0}; }
  Mod operator*(Mod b) { return {x * b.x % mod,0}; }
  Mod operator/(Mod b) { return *this * invert(b); }
  Mod invert(Mod a) {
    ll x, y, g = euclid(a.x, mod, x, y);
    assert(g == 1); return x;
  }
  Mod operator^(ll e) {
    if (!e) return 1;
    Mod r = *this ^ (e / 2); r = r * r;
    return e&1 ? *this * r : r;
  }
};
```

ModInverse.h

Description: O(logM)

<cassert>, "euclid.h" 6e98db, 15 lines

```
// Case 1: M is prime.
ll modinvPrime(ll a, ll M) {
  ll r = 1, e = M - 2;
  a %= M; if (a < 0) a += M;
  for (; e; a = a * a % M, e >>= 1)
    if (e & 1) r = r * a % M;
```

```
  return r;
}
// Case 2: M is arbitrary. Need gcd(a, M) == 1
ll modinv(ll a, ll M) {
  a = (a % M + M) % M;
  ll x, y, g = euclid(a, M, x, y);
  assert(g == 1); // g != 1 => no inverse
  return (x % M + M) % M;
}
```

ModPow.h

b83e45, 8 lines

```
const ll mod = 1000000007; // faster if const

ll modpow(ll b, ll e) {
  ll ans = 1;
  for (; e; b = b * b % mod, e /= 2)
    if (e & 1) ans = ans * b % mod;
  return ans;
}
```

ModLog.h

Description: Returns the smallest $x > 0$ s.t. $a^x = b \pmod m$, or -1 if no such x exists. modLog(a,1,m) can be used to calculate the order of a.
Time: $\mathcal{O}\left(\sqrt{m}\right)$

c040b8, 11 lines

```
ll modLog(ll a, ll b, ll m) {
  ll n = (ll) sqrt(m) + 1, e = 1, f = 1, j = 1;
  unordered_map<ll, ll> A;
  while (j <= n && (e = f = e * a % m) != b % m)
    A[e * b % m] = j++;
  if (e == b % m) return j;
  if (__gcd(m, e) == __gcd(m, b))
    rep(i,2,n+2) if (A.count(e = e * f % m))
      return n * i - A[e];
  return -1;
}
```

ModSum.h

Description: Sums of mod'ed arithmetic progressions.
modsum(to, c, k, m) $= \sum_{i=0}^{to-1} (ki + c)\%m$. divsum is similar but for floored division.
Time: $\log(m)$, with a large constant.

5c5bc5, 16 lines

```
typedef unsigned long long ull;
ull sumsq(ull to) { return to / 2 * ((to-1) | 1); }

ull divsum(ull to, ull c, ull k, ull m) {
  ull res = k / m * sumsq(to) + c / m * to;
  k %= m; c %= m;
  if (!k) return res;
  ull to2 = (to * k + c) / m;
  return res + (to - 1) * to2 - divsum(to2, m-1 - c, m, k);
}

ll modsum(ull to, ll c, ll k, ll m) {
  c = ((c % m) + m) % m;
  k = ((k % m) + m) % m;
  return to * c + k * sumsq(to) - m * divsum(to, c, k, m);
}
```

ModMulLL.h

Description: Calculate $a \cdot b \bmod c$ (or $a^b \bmod c$) for $0 \le a, b \le c \le 7.2 \cdot 10^{18}$.
Time: $\mathcal{O}(1)$ for modmul, $\mathcal{O}(\log b)$ for modpow

bbbd8f, 11 lines

```
typedef unsigned long long ull;
ull modmul(ull a, ull b, ull M) {
  ll ret = a * b - M * ull(1.L / M * a * b);
  return ret + M * (ret < 0) - M * (ret >= (ll)M);
}
ull modpow(ull b, ull e, ull mod) {
  ull ans = 1;
  for (; e; b = modmul(b, b, mod), e /= 2)
    if (e & 1) ans = modmul(ans, b, mod);
  return ans;
}
```

ModSqrt.h

Description: Tonelli-Shanks algorithm for modular square roots. Finds x s.t. $x^2 = a \pmod p$ ($-x$ gives the other solution).
Time: $\mathcal{O}\left(\log^2 p\right)$ worst case, $\mathcal{O}(\log p)$ for most p

<cassert> cbbeb4, 35 lines

```
// Local modpow that takes explicit modulus (ModPow.h's version
    uses global const ll mod)
namespace modsqrt_impl {
ll mpow(ll b, ll e, ll m) {
  ll ans = 1; b %= m;
  for (; e; b = b * b % m, e /= 2)
    if (e & 1) ans = ans * b % m;
  return ans;
}
}

ll sqrt(ll a, ll p) {
  using modsqrt_impl::mpow;
  a %= p; if (a < 0) a += p;
  if (a == 0) return 0;
  assert(mpow(a, (p-1)/2, p) == 1); // else no solution
  if (p % 4 == 3) return mpow(a, (p+1)/4, p);
  // a^(n+3)/8 or 2^(n+3)/8 * 2^(n-1)/4 works if p % 8 == 5
  ll s = p - 1, n = 2;
  int r = 0, m;
  while (s % 2 == 0)
    ++r, s /= 2;
  while (mpow(n, (p - 1) / 2, p) != p - 1) ++n;
  ll x = mpow(a, (s + 1) / 2, p);
  ll b = mpow(a, s, p), g = mpow(n, s, p);
  for (;; r = m) {
    ll t = b;
    for (m = 0; m < r && t != 1; ++m)
      t = t * t % p;
    if (m == 0) return x;
    ll gs = mpow(g, 1LL << (r - m - 1), p);
    g = gs * gs % p;
    x = x * gs % p;
    b = b * g % p;
  }
}
```

5.2 Primality

FastEratosthenes.h

Description: Prime sieve for generating all primes smaller than LIM.
Time: LIM=1e9 $\approx$ 1.5s

6b2912, 20 lines

```
const int LIM = 1e6;
bitset<LIM> isPrime;
vi eratosthenes() {
  const int S = (int)round(sqrt(LIM)), R = LIM / 2;
  vi pr = {2}, sieve(S+1); pr.reserve(int(LIM/log(LIM)*1.1));
  vector<pii> cp;
  for (int i = 3; i <= S; i += 2) if (!sieve[i]) {
    cp.push_back({i, i * i / 2});
    for (int j = i * i; j <= S; j += 2 * i) sieve[j] = 1;
  }
  for (int L = 1; L <= R; L += S) {
    array<bool, S> block{};
    for (auto &[p, idx] : cp)
      for (int i=idx; i < S+L; idx = (i+=p)) block[i-L] = 1;
    rep(i,0,min(S, R - L))
      if (!block[i]) pr.push_back((L + i) * 2 + 1);
  }
  for (int i : pr) isPrime[i] = 1;
  return pr;
}
```

MillerRabin.h

Description: Deterministic Miller-Rabin primality test. Guaranteed to work for numbers up to $7 \cdot 10^{18}$; for larger numbers, use Python and extend A randomly.
Time: 7 times the complexity of $a^b \mod c$.

"ModMulLL.h" 60dcd1, 12 lines

```
bool isPrime(ull n) {
  if (n < 2 || n % 6 % 4 != 1) return (n | 1) == 3;
  ull A[] = {2, 325, 9375, 28178, 450775, 9780504, 1795265022},
      s = __builtin_ctzll(n-1), d = n >> s;
  for (ull a : A) {   // ^ count trailing zeroes
    ull p = modpow(a%n, d, n), i = s;
    while (p != 1 && p != n - 1 && a % n && i--)
      p = modmul(p, p, n);
    if (p != n-1 && i != s) return 0;
  }
  return 1;
}
```

Factor.h

Description: Pollard-rho randomized factorization algorithm. Returns prime factors of a number, in arbitrary order (e.g. 2299 -> {11, 19, 11}).
Time: $\mathcal{O}\left(n^{1/4}\right)$, less for numbers with small factors.

"ModMulLL.h", "MillerRabin.h" d8d98d, 18 lines

```
ull pollard(ull n) {
  ull x = 0, y = 0, t = 30, prd = 2, i = 1, q;
  auto f = [&](ull x) { return modmul(x, x, n) + i; };
  while (t++ % 40 || __gcd(prd, n) == 1) {
    if (x == y) x = ++i, y = f(x);
    if ((q = modmul(prd, max(x,y) - min(x,y), n))) prd = q;
    x = f(x), y = f(f(y));
  }
  return __gcd(prd, n);
}
vector<ull> factor(ull n) {
  if (n == 1) return {};
  if (isPrime(n)) return {n};
  ull x = pollard(n);
  auto l = factor(x), r = factor(n / x);
  l.insert(l.end(), all(r));
  return l;
}
```

5.3 Divisibility

euclid.h

Description: Finds two integers x and y, such that $ax + by = \gcd(a, b)$. If you just need gcd, use the built in __gcd instead. If a and b are coprime, then x is the inverse of $a \pmod b$.

33ba8f, 5 lines

```
ll euclid(ll a, ll b, ll &x, ll &y) {
  if (!b) return x = 1, y = 0, a;
  ll d = euclid(b, a % b, y, x);
  return y -= a/b * x, d;
}
```

CRT.h

Description: Chinese Remainder Theorem.
crt(a, m, b, n) computes x such that $x \equiv a \pmod m$, $x \equiv b \pmod n$. If $|a| < m$ and $|b| < n$, x will obey $0 \le x < \text{lcm}(m, n)$. Assumes $mn < 2^{62}$.

Time: $\log(n)$

<assert>, "euclid.h" 04d93a, 7 lines

```
ll crt(ll a, ll m, ll b, ll n) {
  if (n > m) swap(a, b), swap(m, n);
  ll x, y, g = euclid(m, n, x, y);
  assert((a - b) % g == 0); // else no solution
  x = (b - a) % n * x % n / g * m + a;
  return x < 0 ? x + m*n/g : x;
}
```

5.3.1 Bézout's identity

For $a \neq, b \neq 0$, then $d = gcd(a, b)$ is the smallest positive integer for which there are integer solutions to

$$ax + by = d$$

If (x, y) is one solution, then all solutions are given by

$$\left(x + \frac{kb}{\gcd(a,b)}, y - \frac{ka}{\gcd(a,b)}\right), \quad k \in \mathbb{Z}$$

phiFunction.h

Description: *Euler's* ϕ function is defined as $\phi(n) := \#$ of positive integers $\leq n$ that are coprime with n. $\phi(1) = 1$, p prime $\Rightarrow \phi(p^k) = (p-1)p^{k-1}$, m, n coprime $\Rightarrow \phi(mn) = \phi(m)\phi(n)$. If $n = p_1^{k_1}p_2^{k_2}...p_r^{k_r}$ then $\phi(n) = (p_1-1)p_1^{k_1-1}...(p_r-1)p_r^{k_r-1}$. $\phi(n) = n \cdot \prod_{p|n}(1-1/p)$.
$\sum_{d|n}\phi(d) = n$, $\sum_{1\leq k\leq n, \gcd(k,n)=1} k = n\phi(n)/2, n > 1$
Euler's thm: a, n coprime $\Rightarrow a^{\phi(n)} \equiv 1 \pmod{n}$.
Fermat's little thm: p prime $\Rightarrow a^{p-1} \equiv 1 \pmod{p}$ $\forall a$.

cf7d6d, 8 lines

```
const int LIM = 5000000;
int phi[LIM];

void calculatePhi() {
  rep(i,0,LIM) phi[i] = i&1 ? i : i/2;
  for (int i = 3; i < LIM; i += 2) if(phi[i] == i)
    for (int j = i; j < LIM; j += i) phi[j] -= phi[j] / i;
}
```

5.4 Combinatorics modulo M

Combinatorics.h

Description: Factorials, inverse factorials and nCr modulo a prime M. Call initFact() once before using nCr.
Time: $\mathcal{O}(MAXN)$ precomputation, $\mathcal{O}(1)$ per query

"ModInverse.h" c5d503, 13 lines

```
const ll mod = 1000000007;
const int MAXN = 1000001;
ll fact[MAXN], invfact[MAXN];
void initFact() {
  fact[0] = 1;
  rep(i,1,MAXN) fact[i] = fact[i-1] * i % mod;
  invfact[MAXN-1] = modinvPrime(fact[MAXN-1], mod);
  for (int i = MAXN-1; i > 0; i--) invfact[i-1] = invfact[i] *
      i % mod;
}
ll nCr(int n, int r) {
  if (r < 0 || r > n) return 0;
  return fact[n] * invfact[r] % mod * invfact[n-r] % mod;
}
```

nCrAny.h

Description: nCr mod an arbitrary M. Splits M into prime powers p^k, computes nCr mod each p^k (n! with factors of p removed, times p^e), then combines with CRT. Every p^k of M must be at most about 1e7 (table of size p^k), and M must be factorizable by trial division (M at most about 1e12). For a large prime M use nCr from Combinatorics.h.
Time: $\mathcal{O}\left(sump^k + log_p n\right)$ per query

"euclid.h", "CRT.h", "ModInverse.h" e7ce2d, 38 lines

```
ll powmod(ll b, ll e, ll m) {
  ll r = 1 % m; b %= m;
  for (; e; b = b * b % m, e >>= 1) if (e & 1) r = r * b % m;
  return r;
}
// n! with all factors of p removed, mod pk
ll factNoP(ll n, ll p, ll pk, const vector<ll>& f) {
  ll res = 1;
  while (n) {
    res = res * powmod(f[pk-1], n / pk, pk) % pk * f[n % pk] %
        pk;
    n /= p;
  }
  return res;
}
ll nCrPk(ll n, ll r, ll p, ll k, ll pk) {
  ll e = 0;
  for (ll t = n; t; ) t /= p, e += t;
  for (ll t = r; t; ) t /= p, e -= t;
  for (ll t = n-r; t; ) t /= p, e -= t;
  if (e >= k) return 0;
  vector<ll> f(pk);
  f[0] = 1;
  rep(i,1,pk) f[i] = i % p ? f[i-1] * i % pk : f[i-1];
  ll num = factNoP(n, p, pk, f);
  ll den = factNoP(r, p, pk, f) * factNoP(n-r, p, pk, f) % pk;
  return num * modinv(den, pk) % pk * powmod(p, e, pk) % pk;
}
ll nCrAny(ll n, ll r, ll M) {
  if (r < 0 || r > n) return 0;
  ll ans = 0, m = 1, x = M;
  for (ll p = 2; p * p <= x; p++) if (x % p == 0) {
    ll k = 0, pk = 1;
    while (x % p == 0) x /= p, k++, pk *= p;
    ans = crt(ans, m, nCrPk(n, r, p, k, pk), pk); m *= pk;
  }
  if (x > 1) { ans = crt(ans, m, nCrPk(n, r, x, 1, x), x); m *=
      x; }
  return ans % M;
}
```

5.5 Floor blocks

FloorBlocks.h

Description: Iterates over maximal blocks [l, r] on which floor(n / i) is constant.
Time: $\mathcal{O}(sqrt(n))$

88ed1f, 4 lines

```
for (ll l = 1, r; l <= n; l = r + 1) {
  r = n / (n / l);
  // for every i in [l, r]: n / i == n / l
}
```

5.6 Fractions

ContinuedFractions.h

Description: Given N and a real number $x \geq 0$, finds the closest rational approximation p/q with $p, q \leq N$. It will obey $|p/q - x| \leq 1/qN$.
For consecutive convergents, $p_{k+1}q_k - q_{k+1}p_k = (-1)^k$. ($p_k/q_k$ alternates between $> x$ and $< x$.) If x is rational, y eventually becomes ∞; if x is the root of a degree 2 polynomial the a's eventually become cyclic.
Time: $\mathcal{O}(\log N)$

dd6c5e, 21 lines

```
typedef double d; // for N ~ 1e7; long double for N ~ 1e9
pair<ll, ll> approximate(d x, ll N) {
  ll LP = 0, LQ = 1, P = 1, Q = 0, inf = LLONG_MAX; d y = x;
  for (;;) {
    ll lim = min(P ? (N-LP) / P : inf, Q ? (N-LQ) / Q : inf),
       a = (ll)floor(y), b = min(a, lim),
       NP = b*P + LP, NQ = b*Q + LQ;
    if (a > b) {
      // If b > a/2, we have a semi-convergent that gives us a
      // better approximation; if b = a/2, we *may* have one.
      // Return {P, Q} here for a more canonical approximation.
      return (abs(x - (d)NP / (d)NQ) < abs(x - (d)P / (d)Q)) ?
        make_pair(NP, NQ) : make_pair(P, Q);
    }
    if (abs(y = 1/(y - (d)a)) > 3*N) {
      return {NP, NQ};
    }
    LP = P; P = NP;
    LQ = Q; Q = NQ;
  }
}
```

FracBinarySearch.h

Description: Given f and N, finds the smallest fraction $p/q \in [0, 1]$ such that $f(p/q)$ is true, and $p, q \leq N$. You may want to throw an exception from f if it finds an exact solution, in which case N can be removed.
Usage: `fracBS([](Frac f) { return f.p>=3*f.q; }, 10); // {1,3}`
Time: $\mathcal{O}(\log(N))$

27ab3e, 25 lines

```
struct Frac { ll p, q; };

template<class F>
Frac fracBS(F f, ll N) {
  bool dir = 1, A = 1, B = 1;
  Frac lo{0, 1}, hi{1, 1}; // Set hi to 1/0 to search (0, N]
  if (f(lo)) return lo;
  assert(f(hi));
  while (A || B) {
    ll adv = 0, step = 1; // move hi if dir, else lo
    for (int si = 0; step; (step *= 2) >>= si) {
      adv += step;
      Frac mid{lo.p * adv + hi.p, lo.q * adv + hi.q};
      if (abs(mid.p) > N || mid.q > N || dir == !f(mid)) {
        adv -= step; si = 2;
      }
    }
    hi.p += lo.p * adv;
    hi.q += lo.q * adv;
    dir = !dir;
    swap(lo, hi);
    A = B; B = !!adv;
  }
  return dir ? hi : lo;
}
```

5.7 Pythagorean Triples

The Pythagorean triples are uniquely generated by

$$a = k \cdot (m^2 - n^2), \;\; b = k \cdot (2mn), \;\; c = k \cdot (m^2 + n^2),$$

with $m > n > 0$, $k > 0$, $m \perp n$, and either m or n even.

5.8 Primes

$p = 962592769$ is such that $2^{21} \mid p-1$, which may be useful. For hashing use 970592641 (31-bit number), 31443539979727 (45-bit), 3006703054056749 (52-bit). There are 78498 primes less than 1 000 000.

Primitive roots exist modulo any prime power p^a, except for $p = 2, a > 2$, and there are $\phi(\phi(p^a))$ many. For $p = 2, a > 2$, the group $\mathbb{Z}_{2^a}^\times$ is instead isomorphic to $\mathbb{Z}_2 \times \mathbb{Z}_{2^{a-2}}$.

5.9 Estimates

$\sum_{d|n} d = O(n \log\log n)$.

The number of divisors of n is at most around 100 for $n < 5e4$, 500 for $n < 1e7$, 2000 for $n < 1e10$, 200 000 for $n < 1e19$.

5.10 Mobius Function

$$\mu(n) = \begin{cases} 0 & n \text{ is not square free} \\ 1 & n \text{ has even number of prime factors} \\ -1 & n \text{ has odd number of prime factors} \end{cases}$$

Mobius Inversion:

$$g(n) = \sum_{d|n} f(d) \Leftrightarrow f(n) = \sum_{d|n} \mu(d) g(n/d)$$

Other useful formulas/forms:

$\sum_{d|n} \mu(d) = [n = 1]$ (very useful)

$g(n) = \sum_{n|d} f(d) \Leftrightarrow f(n) = \sum_{n|d} \mu(d/n) g(d)$

$g(n) = \sum_{1 \le m \le n} f(\lfloor \frac{n}{m} \rfloor) \Leftrightarrow f(n) = \sum_{1 \le m \le n} \mu(m) g(\lfloor \frac{n}{m} \rfloor)$

Combinatorial (6)

6.1 Permutations

6.1.1 Factorial

n	1	2	3	4	5	6	7	8	9	10
$n!$	1	2	6	24	120	720	5040	40320	362880	3628800
n	11	12	13	14	15	16	17			
$n!$	4.0e7	4.8e8	6.2e9	8.7e10	1.3e12	2.1e13	3.6e14			
n	20	25	30	40	50	100	150	171		
$n!$	2e18	2e25	3e32	8e47	3e64	9e157	6e262	>DBL_MAX		

IntPerm.h

Description: Permutation -> integer conversion. (Not order preserving.) Integer -> permutation can use a lookup table.

Time: $\mathcal{O}(n)$

044568, 6 lines

```
int permToInt(vi& v) {
  int use = 0, i = 0, r = 0;
  for(int x:v) r = r * ++i + __builtin_popcount(use & -(1<<x)),
    use |= 1 << x;                    // (note: minus, not ~!)
  return r;
}
```

6.1.2 Cycles

Let $g_S(n)$ be the number of n-permutations whose cycle lengths all belong to the set S. Then

$$\sum_{n=0}^{\infty} g_S(n) \frac{x^n}{n!} = \exp\left(\sum_{n \in S} \frac{x^n}{n}\right)$$

6.1.3 Derangements

Permutations of a set such that none of the elements appear in their original position.

$$D(n) = (n-1)(D(n-1) + D(n-2)) = nD(n-1) + (-1)^n = \left\lfloor \frac{n!}{e} \right\rceil$$

6.1.4 Burnside's lemma

Given a group G of symmetries and a set X, the number of elements of X *up to symmetry* equals

$$\frac{1}{|G|} \sum_{g \in G} |X^g|,$$

where X^g are the elements fixed by g ($g.x = x$).

If $f(n)$ counts "configurations" (of some sort) of length n, we can ignore rotational symmetry using $G = \mathbb{Z}_n$ to get

$$g(n) = \frac{1}{n} \sum_{k=0}^{n-1} f(\gcd(n,k)) = \frac{1}{n} \sum_{k|n} f(k) \phi(n/k).$$

6.2 Partitions and subsets

6.2.1 Partition function

Number of ways of writing n as a sum of positive integers, disregarding the order of the summands.

$$p(0) = 1,\ p(n) = \sum_{k \in \mathbb{Z} \setminus \{0\}} (-1)^{k+1} p(n - k(3k-1)/2)$$

$$p(n) \sim 0.145/n \cdot \exp(2.56\sqrt{n})$$

n	0	1	2	3	4	5	6	7	8	9	20	50	100
$p(n)$	1	1	2	3	5	7	11	15	22	30	627	~2e5	~2e8

6.2.2 Lucas' Theorem

Let n, m be non-negative integers and p a prime. Write $n = n_k p^k + ... + n_1 p + n_0$ and $m = m_k p^k + ... + m_1 p + m_0$. Then $\binom{n}{m} \equiv \prod_{i=0}^{k} \binom{n_i}{m_i} \pmod p$.

6.2.3 Binomials

multinomial.h

Description: Computes $\binom{k_1 + \cdots + k_n}{k_1, k_2, \ldots, k_n} = \frac{(\sum k_i)!}{k_1! k_2! \ldots k_n!}$.

a0a312, 5 lines

```
ll multinomial(vi& v) {
  ll c = 1, m = v.empty() ? 1 : v[0];
  rep(i,1,sz(v)) rep(j,0,v[i]) c = c * ++m / (j+1);
  return c;
}
```

6.3 General purpose numbers

6.3.1 Bernoulli numbers

EGF of Bernoulli numbers is $B(t) = \frac{t}{e^t - 1}$ (FFT-able).
$B[0, \ldots] = [1, -\frac{1}{2}, \frac{1}{6}, 0, -\frac{1}{30}, 0, \frac{1}{42}, \ldots]$

Sums of powers:

$$\sum_{i=1}^{n} n^m = \frac{1}{m+1} \sum_{k=0}^{m} \binom{m+1}{k} B_k \cdot (n+1)^{m+1-k}$$

Euler-Maclaurin formula for infinite sums:

$$\sum_{i=m}^{\infty} f(i) = \int_m^\infty f(x)dx - \sum_{k=1}^{\infty} \frac{B_k}{k!} f^{(k-1)}(m)$$

$$\approx \int_m^\infty f(x)dx + \frac{f(m)}{2} - \frac{f'(m)}{12} + \frac{f'''(m)}{720} + O(f^{(5)}(m))$$

6.3.2 Stirling numbers of the first kind

Number of permutations on n items with k cycles.

$$c(n,k) = c(n-1,k-1) + (n-1)c(n-1,k),\ c(0,0) = 1$$

$$\sum_{k=0}^{n} c(n,k) x^k = x(x+1)\ldots(x+n-1)$$

$c(8,k) = 8, 0, 5040, 13068, 13132, 6769, 1960, 322, 28, 1$
$c(n,2) = 0, 0, 1, 3, 11, 50, 274, 1764, 13068, 109584, \ldots$

6.3.3 Eulerian numbers

Number of permutations $\pi \in S_n$ in which exactly k elements are greater than the previous element. k j:s s.t. $\pi(j) > \pi(j+1)$, $k+1$ j:s s.t. $\pi(j) \ge j$, k j:s s.t. $\pi(j) > j$.

$$E(n,k) = (n-k)E(n-1,k-1) + (k+1)E(n-1,k)$$

$$E(n,0) = E(n,n-1) = 1$$

$$E(n,k) = \sum_{j=0}^{k} (-1)^j \binom{n+1}{j} (k+1-j)^n$$

6.3.4 Stirling numbers of the second kind

Partitions of n distinct elements into exactly k groups.

$$S(n,k) = S(n-1,k-1) + kS(n-1,k)$$

$$S(n,1) = S(n,n) = 1$$

$$S(n,k) = \frac{1}{k!} \sum_{j=0}^{k} (-1)^{k-j} \binom{k}{j} j^n$$

6.3.5 Bell numbers

Total number of partitions of n distinct elements. $B(n) = 1, 1, 2, 5, 15, 52, 203, 877, 4140, 21147, \ldots$. For p prime,

$$B(p^m + n) \equiv mB(n) + B(n+1) \pmod p$$

6.3.6 Labeled unrooted trees

on n vertices: n^{n-2}
on k existing trees of size n_i: $n_1 n_2 \cdots n_k n^{k-2}$
with degrees d_i: $(n-2)!/((d_1-1)!\cdots(d_n-1)!)$

6.3.7 Catalan numbers

$$C_n = \frac{1}{n+1}\binom{2n}{n} = \binom{2n}{n} - \binom{2n}{n+1} = \frac{(2n)!}{(n+1)!n!}$$

$$C_0 = 1,\ C_{n+1} = \frac{2(2n+1)}{n+2}C_n,\ C_{n+1} = \sum C_i C_{n-i}$$

$C_n = 1, 1, 2, 5, 14, 42, 132, 429, 1430, 4862, 16796, 58786, \ldots$

- sub-diagonal monotone paths in an $n \times n$ grid.
- strings with n pairs of parenthesis, correctly nested.
- binary trees with with $n+1$ leaves (0 or 2 children).
- ordered trees with $n+1$ vertices.
- ways a convex polygon with $n+2$ sides can be cut into triangles by connecting vertices with straight lines.
- permutations of $[n]$ with no 3-term increasing subseq.

Graph (7)

7.1 Fundamentals

BellmanFord.h

Description: Calculates shortest paths from s in a graph that might have negative edge weights. Unreachable nodes get dist = inf; nodes reachable through negative-weight cycles get dist = -inf. Assumes $V^2 \max|w_i| < \sim 2^{63}$.
Time: $\mathcal{O}(VE)$
830a8f, 23 lines

```
const ll inf = LLONG_MAX;
struct Ed { int a, b, w, s() { return a < b ? a : -a; }};
struct Node { ll dist = inf; int prev = -1; };

void bellmanFord(vector<Node>& nodes, vector<Ed>& eds, int s) {
  nodes[s].dist = 0;
  sort(all(eds), [](Ed a, Ed b) { return a.s() < b.s(); });

  int lim = sz(nodes) / 2 + 2; // /3+100 with shuffled vertices
  rep(i,0,lim) for (Ed ed : eds) {
    Node cur = nodes[ed.a], &dest = nodes[ed.b];
    if (abs(cur.dist) == inf) continue;
    ll d = cur.dist + ed.w;
    if (d < dest.dist) {
      dest.prev = ed.a;
      dest.dist = (i < lim-1 ? d : -inf);
    }
  }
  rep(i,0,lim) for (Ed e : eds) {
    if (nodes[e.a].dist == -inf)
      nodes[e.b].dist = -inf;
  }
}
```

FloydWarshall.h

Description: Calculates all-pairs shortest path in a directed graph that might have negative edge weights. Input is an distance matrix m, where $m[i][j] =$ `inf` if i and j are not adjacent. As output, $m[i][j]$ is set to the shortest distance between i and j, `inf` if no path, or `-inf` if the path goes through a negative-weight cycle.
Time: $\mathcal{O}(N^3)$
531245, 12 lines

```
const ll inf = 1LL << 62;
void floydWarshall(vector<vector<ll>>& m) {
  int n = sz(m);
  rep(i,0,n) m[i][i] = min(m[i][i], 0LL);
  rep(k,0,n) rep(i,0,n) rep(j,0,n)
    if (m[i][k] != inf && m[k][j] != inf) {
      auto newDist = max(m[i][k] + m[k][j], -inf);
      m[i][j] = min(m[i][j], newDist);
    }
  rep(k,0,n) if (m[k][k] < 0) rep(i,0,n) rep(j,0,n)
    if (m[i][k] != inf && m[k][j] != inf) m[i][j] = -inf;
}
```

TopoSort.h

Description: Topological sorting. Given is an oriented graph. Output is an ordering of vertices, such that there are edges only from left to right. If there are cycles, the returned list will have size smaller than n – nodes reachable from cycles will not be returned.
Time: $\mathcal{O}(|V| + |E|)$
d678d8, 8 lines

```
vi topoSort(const vector<vi>& gr) {
  vi indeg(sz(gr)), q;
  for (auto& li : gr) for (int x : li) indeg[x]++;
  rep(i,0,sz(gr)) if (indeg[i] == 0) q.push_back(i);
  rep(j,0,sz(q)) for (int x : gr[q[j]])
    if (--indeg[x] == 0) q.push_back(x);
  return q;
}
```

Dijkstra.h

Description: Calculates shortest paths from s in a graph with non-negative edge weights. Returns $\{dist, par\}$ where $dist[i]$ is the shortest distance (or inf if unreachable) and $par[i]$ is the parent on the shortest path.
Usage: `auto [dist, par] = dijkstra(s, adj);`
Time: $\mathcal{O}((V+E)\log V)$
98c27e, 20 lines

```
const ll inf = 1LL << 62;
pair<vector<ll>, vi> dijkstra(int s, const vector<vector<pair<
    int, ll>>>& adj) {
  int n = sz(adj);
  vector<ll> dist(n, inf);
  vi par(n, -1);
  priority_queue<pair<ll, int>, vector<pair<ll, int>>, greater<
      pair<ll, int>>> pq;
  dist[s] = 0;
  pq.push({0, s});
  while (!pq.empty()) {
    auto [d, u] = pq.top(); pq.pop();
    if (d != dist[u]) continue;
    for (auto [v, w] : adj[u])
      if (dist[u] + w < dist[v]) {
        dist[v] = dist[u] + w;
        par[v] = u;
        pq.push({dist[v], v});
      }
  }
  return {dist, par};
}
```

ShortestCycle.h

Description: Finds the length of the shortest cycle (girth) in an unweighted undirected graph. Returns -1 if the graph is acyclic.
Usage: `int len = shortestCycle(adj);`
Time: $\mathcal{O}(V(V+E))$
e29234, 19 lines

```
int shortestCycle(const vector<vi>& adj) {
  int n = sz(adj), ans = INT_MAX;
  rep(s,0,n) {
    vi dist(n, -1), par(n, -1), q = {s};
    dist[s] = 0;
    rep(qi,0,sz(q)) {
      int u = q[qi];
      for (int v : adj[u]) {
        if (dist[v] == -1) {
          dist[v] = dist[u] + 1;
          par[v] = u;
          q.push_back(v);
        } else if (par[u] != v)
          ans = min(ans, dist[u] + dist[v] + 1);
      }
    }
  }
  return ans == INT_MAX ? -1 : ans;
}
```

7.2 Network flow

PushRelabel.h

Description: Push-relabel using the highest label selection rule and the gap heuristic. Quite fast in practice. To obtain the actual flow, look at positive values only.
Time: $\mathcal{O}\left(V^2\sqrt{E}\right)$
0ae1d4, 48 lines

```
struct PushRelabel {
  struct Edge {
    int dest, back;
    ll f, c;
  };
  vector<vector<Edge>> g;
  vector<ll> ec;
  vector<Edge*> cur;
  vector<vi> hs; vi H;
  PushRelabel(int n) : g(n), ec(n), cur(n), hs(2*n), H(n) {}

  void addEdge(int s, int t, ll cap, ll rcap=0) {
    if (s == t) return;
    g[s].push_back({t, sz(g[t]), 0, cap});
    g[t].push_back({s, sz(g[s])-1, 0, rcap});
  }

  void addFlow(Edge& e, ll f) {
    Edge &back = g[e.dest][e.back];
    if (!ec[e.dest] && f) hs[H[e.dest]].push_back(e.dest);
    e.f += f; e.c -= f; ec[e.dest] += f;
    back.f -= f; back.c += f; ec[back.dest] -= f;
  }
  ll calc(int s, int t) {
    int v = sz(g); H[s] = v; ec[t] = 1;
    vi co(2*v); co[0] = v-1;
    rep(i,0,v) cur[i] = g[i].data();
    for (Edge& e : g[s]) addFlow(e, e.c);

    for (int hi = 0;;) {
      while (hs[hi].empty()) if (!hi--) return -ec[s];
      int u = hs[hi].back(); hs[hi].pop_back();
      while (ec[u] > 0)  // discharge u
        if (cur[u] == g[u].data() + sz(g[u])) {
          H[u] = 1e9;
          for (Edge& e : g[u]) if (e.c && H[u] > H[e.dest]+1)
            H[u] = H[e.dest]+1, cur[u] = &e;
          if (++co[H[u]], !--co[hi] && hi < v)
            rep(i,0,v) if (hi < H[i] && H[i] < v)
              --co[H[i]], H[i] = v + 1;
          hi = H[u];
        } else if (cur[u]->c && H[u] == H[cur[u]->dest]+1)
          addFlow(*cur[u], min(ec[u], cur[u]->c));
        else ++cur[u];
```

```
    }
  }
  bool leftOfMinCut(int a) { return H[a] >= sz(g); }
};
```

MinCostMaxFlow.h

Description: Min-cost max-flow. If costs can be negative, call setpi before maxflow, but note that negative cost cycles are not supported. To obtain the actual flow, look at positive values only.
Time: $\mathcal{O}\left(FE\log(V)\right)$ where F is max flow. $\mathcal{O}\left(VE\right)$ for setpi.

<cassert>, <bits/extc++.h> 135b73, 77 lines

```
const ll INF = numeric_limits<ll>::max() / 4;

struct MCMF {
  struct edge {
    int from, to, rev;
    ll cap, cost, flow;
  };
  int N;
  vector<vector<edge>> ed;
  vi seen;
  vector<ll> dist, pi;
  vector<edge*> par;

  MCMF(int N) : N(N), ed(N), seen(N), dist(N), pi(N), par(N) {}

  void addEdge(int from, int to, ll cap, ll cost) {
    if (from == to) return;
    ed[from].push_back(edge{ from,to,sz(ed[to]),cap,cost,0 });
    ed[to].push_back(edge{ to,from,sz(ed[from])-1,0,-cost,0 });
  }

  void path(int s) {
    fill(all(seen), 0);
    fill(all(dist), INF);
    dist[s] = 0; ll di;

    __gnu_pbds::priority_queue<pair<ll, int>> q;
    vector<decltype(q)::point_iterator> its(N);
    q.push({ 0, s });

    while (!q.empty()) {
      s = q.top().second; q.pop();
      seen[s] = 1; di = dist[s] + pi[s];
      for (edge& e : ed[s]) if (!seen[e.to]) {
        ll val = di - pi[e.to] + e.cost;
        if (e.cap - e.flow > 0 && val < dist[e.to]) {
          dist[e.to] = val;
          par[e.to] = &e;
          if (its[e.to] == q.end())
            its[e.to] = q.push({ -dist[e.to], e.to });
          else
            q.modify(its[e.to], { -dist[e.to], e.to });
        }
      }
    }
    rep(i,0,N) pi[i] = min(pi[i] + dist[i], INF);
  }

  pair<ll, ll> maxflow(int s, int t) {
    ll totflow = 0, totcost = 0;
    while (path(s), seen[t]) {
      ll fl = INF;
      for (edge* x = par[t]; x; x = par[x->from])
        fl = min(fl, x->cap - x->flow);

      totflow += fl;
      for (edge* x = par[t]; x; x = par[x->from]) {
        x->flow += fl;
        ed[x->to][x->rev].flow -= fl;
      }
    }
    rep(i,0,N) for(edge& e : ed[i]) totcost += e.cost * e.flow;
    return {totflow, totcost/2};
  }

  // If some costs can be negative, call this before maxflow:
  void setpi(int s) { // (otherwise, leave this out)
    fill(all(pi), INF); pi[s] = 0;
    int it = N, ch = 1; ll v;
    while (ch-- && it--)
      rep(i,0,N) if (pi[i] != INF)
        for (edge& e : ed[i]) if (e.cap)
          if ((v = pi[i] + e.cost) < pi[e.to])
            pi[e.to] = v, ch = 1;
    assert(it >= 0); // negative cost cycle
  }
};
```

EdmondsKarp.h

Description: Flow algorithm with guaranteed complexity $O(VE^2)$. To get edge flow values, compare capacities before and after, and take the positive values only.

<cassert> 482fe0, 36 lines

```
template<class T> T edmondsKarp(vector<unordered_map<int, T>>&
    graph, int source, int sink) {
  assert(source != sink);
  T flow = 0;
  vi par(sz(graph)), q = par;

  for (;;) {
    fill(all(par), -1);
    par[source] = 0;
    int ptr = 1;
    q[0] = source;

    rep(i,0,ptr) {
      int x = q[i];
      for (auto e : graph[x]) {
        if (par[e.first] == -1 && e.second > 0) {
          par[e.first] = x;
          q[ptr++] = e.first;
          if (e.first == sink) goto out;
        }
      }
    }
    return flow;
out:
    T inc = numeric_limits<T>::max();
    for (int y = sink; y != source; y = par[y])
      inc = min(inc, graph[par[y]][y]);

    flow += inc;
    for (int y = sink; y != source; y = par[y]) {
      int p = par[y];
      if ((graph[p][y] -= inc) <= 0) graph[p].erase(y);
      graph[y][p] += inc;
    }
  }
}
```

Dinic.h

Description: Flow algorithm with complexity $O(VE\log U)$ where $U = \max|\text{cap}|$. $O(\min(E^{1/2}, V^{2/3})E)$ if $U = 1$; $O(\sqrt{V}E)$ for bipartite matching.

d7f0f1, 42 lines

```
struct Dinic {
  struct Edge {
    int to, rev;
    ll c, oc;
    ll flow() { return max(oc - c, 0LL); } // if you need flows
  };
  vi lvl, ptr, q;
  vector<vector<Edge>> adj;
  Dinic(int n) : lvl(n), ptr(n), q(n), adj(n) {}
  void addEdge(int a, int b, ll c, ll rcap = 0) {
    adj[a].push_back({b, sz(adj[b]), c, c});
    adj[b].push_back({a, sz(adj[a]) - 1, rcap, rcap});
  }
  ll dfs(int v, int t, ll f) {
    if (v == t || !f) return f;
    for (int& i = ptr[v]; i < sz(adj[v]); i++) {
      Edge& e = adj[v][i];
      if (lvl[e.to] == lvl[v] + 1)
        if (ll p = dfs(e.to, t, min(f, e.c))) {
          e.c -= p, adj[e.to][e.rev].c += p;
          return p;
        }
    }
    return 0;
  }
  ll calc(int s, int t) {
    ll flow = 0; q[0] = s;
    rep(L,0,31) do { // 'int L=30' maybe faster for random data
      lvl = ptr = vi(sz(q));
      int qi = 0, qe = lvl[s] = 1;
      while (qi < qe && !lvl[t]) {
        int v = q[qi++];
        for (Edge e : adj[v])
          if (!lvl[e.to] && e.c >> (30 - L))
            q[qe++] = e.to, lvl[e.to] = lvl[v] + 1;
      }
      while (ll p = dfs(s, t, LLONG_MAX)) flow += p;
    } while (lvl[t]);
    return flow;
  }
  bool leftOfMinCut(int a) { return lvl[a] != 0; }
};
```

MinCut.h

Description: After running max-flow, the left side of a min-cut from s to t is given by all vertices reachable from s, only traversing edges with positive residual capacity.

GlobalMinCut.h

Description: Find a global minimum cut in an undirected graph, as represented by an adjacency matrix.
Time: $\mathcal{O}\left(V^3\right)$

8b0e19, 21 lines

```
pair<int, vi> globalMinCut(vector<vi> mat) {
  pair<int, vi> best = {INT_MAX, {}};
  int n = sz(mat);
  vector<vi> co(n);
  rep(i,0,n) co[i] = {i};
  rep(ph,1,n) {
    vi w = mat[0];
    size_t s = 0, t = 0;
    rep(it,0,n-ph) { // O(V^2) -> O(E log V) with prio. queue
      w[t] = INT_MIN;
      s = t, t = max_element(all(w)) - w.begin();
      rep(i,0,n) w[i] += mat[t][i];
    }
    best = min(best, {w[t] - mat[t][t], co[t]});
    co[s].insert(co[s].end(), all(co[t]));
    rep(i,0,n) mat[s][i] += mat[t][i];
```

```
    rep(i,0,n) mat[i][s] = mat[s][i];
    mat[0][t] = INT_MIN;
  }
  return best;
}
```

GomoryHu.h

Description: Given a list of edges representing an undirected flow graph, returns edges of the Gomory-Hu tree. The max flow between any pair of vertices is given by minimum edge weight along the Gomory-Hu tree path.
Time: $\mathcal{O}(V)$ Flow Computations

"PushRelabel.h" 0418b3, 13 lines

```
typedef array<ll, 3> Edge;
vector<Edge> gomoryHu(int N, vector<Edge> ed) {
  vector<Edge> tree;
  vi par(N);
  rep(i,1,N) {
    PushRelabel D(N); // Dinic also works
    for (Edge t : ed) D.addEdge(t[0], t[1], t[2], t[2]);
    tree.push_back({i, par[i], D.calc(i, par[i])});
    rep(j,i+1,N)
      if (par[j] == par[i] && D.leftOfMinCut(j)) par[j] = i;
  }
  return tree;
}
```

7.3 Matching

HopcroftKarp.h

Description: Fast bipartite matching algorithm. Graph g should be a list of neighbors of the left partition, and r should be a vector full of -1's of the same size as the right partition. Returns the size of the matching. $r[i]$ will be the match for vertex i on the right side, or -1 if it's not matched.
Time: $\mathcal{O}\left(E\sqrt{V}\right)$

731cfb, 20 lines

```
int hopcroftKarp(vector<vi>& g, vi& r) {
  int n = sz(g), res = 0;
  vi l(n, -1), q(n), d(n);
  auto dfs = [&](auto f, int u) -> bool {
    int t = exchange(d[u], 0) + 1;
    for (int v : g[u])
      if (r[v] == -1 || (d[r[v]] == t && f(f, r[v])))
        return l[u] = v, r[v] = u, 1;
    return 0;
  };
  for (int t = 0, f = 0;; t = f = 0, d.assign(n, 0)) {
    rep(i,0,n) if (l[i] == -1) q[t++] = i, d[i] = 1;
    rep(i,0,t) for (int v : g[q[i]]) {
      if (r[v] == -1) f = 1;
      else if (!d[r[v]]) d[r[v]] = d[q[i]] + 1, q[t++] = r[v];
    }
    if (!f) return res;
    rep(i,0,n) if (l[i] == -1) res += dfs(dfs, i);
  }
}
```

DFSMatching.h

Description: Simple bipartite matching algorithm. Graph g should be a list of neighbors of the left partition, and *btoa* should be a vector full of -1's of the same size as the right partition. Returns the size of the matching. $btoa[i]$ will be the match for vertex i on the right side, or -1 if it's not matched.
Usage: `vi btoa(m, -1); dfsMatching(g, btoa);`
Time: $\mathcal{O}(VE)$

522b98, 22 lines

```
bool find(int j, vector<vi>& g, vi& btoa, vi& vis) {
  if (btoa[j] == -1) return 1;
  vis[j] = 1; int di = btoa[j];
  for (int e : g[di])
    if (!vis[e] && find(e, g, btoa, vis)) {
      btoa[e] = di;
      return 1;
    }
  return 0;
}
int dfsMatching(vector<vi>& g, vi& btoa) {
  vi vis;
  rep(i,0,sz(g)) {
    vis.assign(sz(btoa), 0);
    for (int j : g[i])
      if (find(j, g, btoa, vis)) {
        btoa[j] = i;
        break;
      }
  }
  return sz(btoa) - (int)count(all(btoa), -1);
}
```

MinimumVertexCover.h

Description: Finds a minimum vertex cover in a bipartite graph. The size is the same as the size of a maximum matching, and the complement is a maximum independent set.

<cassert>, "DFSMatching.h" da4196, 20 lines

```
vi cover(vector<vi>& g, int n, int m) {
  vi match(m, -1);
  int res = dfsMatching(g, match);
  vector<bool> lfound(n, true), seen(m);
  for (int it : match) if (it != -1) lfound[it] = false;
  vi q, cover;
  rep(i,0,n) if (lfound[i]) q.push_back(i);
  while (!q.empty()) {
    int i = q.back(); q.pop_back();
    lfound[i] = 1;
    for (int e : g[i]) if (!seen[e] && match[e] != -1) {
      seen[e] = true;
      q.push_back(match[e]);
    }
  }
  rep(i,0,n) if (!lfound[i]) cover.push_back(i);
  rep(i,0,m) if (seen[i]) cover.push_back(n+i);
  assert(sz(cover) == res);
  return cover;
}
```

WeightedMatching.h

Description: Given a weighted bipartite graph, matches every node on the left with a node on the right such that no nodes are in two matchings and the sum of the edge weights is minimal. Takes cost[N][M], where cost[i][j] = cost for L[i] to be matched with R[j], and returns (min cost, match), where L[i] is matched with R[match[i]]. Negate costs for max cost. Requires $N \leq M$.
Time: $\mathcal{O}\left(N^2M\right)$

8f41c7, 24 lines

```
template<class T>
pair<T, vi> weightedMatching(vector<vector<T>> &C) {
  int i = sz(C), m = i ? sz(C[0]) : 0, c, s, r;
  vector<T> dist(m), pot(m);
  vi match(i), rev(m, -1), cols(m), prev(m);
  T d = 0, nd, cost = 0;
  while (i--) {
    rep(c,0,m) dist[c] = C[i][c], cols[c] = c, prev[c] = i;
    for (s = 0;;) {
      rep(j,s,m) {
        c = cols[j], nd = dist[c] - pot[c];
        if (j == s || d > nd) d = nd, swap(cols[s], cols[j]);
      }
      if ((r = rev[c = cols[s++]]) == -1) break;
      rep(j,0,m) if (dist[j] > (nd = C[r][j]-C[r][c]+dist[c]))
        dist[j] = nd, prev[j] = r;
    }
    cost += dist[c];
    while (s--) pot[cols[s]] = dist[cols[s]] - d;
    for (; r != i; swap(c, match[r]))
      r = rev[c] = prev[c];
  }
  return {cost, match};
}
```

GeneralMatching.h

Description: Matching for general graphs. Fails with probability N/mod.
Time: $\mathcal{O}\left(N^3\right)$

<cassert>, "../numerical/MatrixInverse-mod.h" cb1912, 40 lines

```
vector<pii> generalMatching(int N, vector<pii>& ed) {
  vector<vector<ll>> mat(N, vector<ll>(N)), A;
  for (pii pa : ed) {
    int a = pa.first, b = pa.second, r = rand() % mod;
    mat[a][b] = r, mat[b][a] = (mod - r) % mod;
  }

  int r = matInv(A = mat), M = 2*N - r, fi, fj;
  assert(r % 2 == 0);

  if (M != N) do {
    mat.resize(M, vector<ll>(M));
    rep(i,0,N) {
      mat[i].resize(M);
      rep(j,N,M) {
        int r = rand() % mod;
        mat[i][j] = r, mat[j][i] = (mod - r) % mod;
      }
    }
  } while (matInv(A = mat) != M);

  vi has(M, 1); vector<pii> ret;
  rep(it,0,M/2) {
    rep(i,0,M) if (has[i])
      rep(j,i+1,M) if (A[i][j] && mat[i][j]) {
        fi = i; fj = j; goto done;
      } assert(0); done:
    if (fj < N) ret.emplace_back(fi, fj);
    has[fi] = has[fj] = 0;
    rep(sw,0,2) {
      ll a = modpow(A[fi][fj], mod-2);
      rep(i,0,M) if (has[i] && A[i][fj]) {
        ll b = A[i][fj] * a % mod;
        rep(j,0,M) A[i][j] = (A[i][j] - A[fi][j] * b) % mod;
      }
      swap(fi,fj);
    }
  }
  return ret;
}
```

7.4 DFS algorithms

SCC.h

Description: Finds strongly connected components in a directed graph. If vertices u, v belong to the same component, we can reach u from v and vice versa.
Usage: `scc(graph, [&](vi& v) { ... })` visits all components in reverse topological order. `comp[i]` holds the component index of a node (a component only has edges to components with lower index). `ncomps` will contain the number of components.
Time: $\mathcal{O}(E+V)$

76b5c9, 24 lines

```
vi val, comp, z, cont;
int Time, ncomps;
template<class G, class F> int dfs(int j, G& g, F& f) {
  int low = val[j] = ++Time, x; z.push_back(j);
```

```
  for (auto e : g[j]) if (comp[e] < 0)
    low = min(low, val[e] ?: dfs(e,g,f));

  if (low == val[j]) {
    do {
      x = z.back(); z.pop_back();
      comp[x] = ncomps;
      cont.push_back(x);
    } while (x != j);
    f(cont); cont.clear();
    ncomps++;
  }
  return val[j] = low;
}
template<class G, class F> void scc(G& g, F f) {
  int n = sz(g);
  val.assign(n, 0); comp.assign(n, -1);
  Time = ncomps = 0;
  rep(i,0,n) if (comp[i] < 0) dfs(i, g, f);
}
```

BiconnectedComponents.h

Description: Finds all biconnected components in an undirected graph, and runs a callback for the edges in each. In a biconnected component there are at least two internally disjoint paths between any two nodes (a cycle exists through them). Note that a node can be in several components. An edge which is not in a component is a bridge, i.e., not part of any cycle.
Usage: `int eid = 0; ed.resize(N);`
`for each edge (a,b) {`
`ed[a].emplace_back(b, eid);`
`ed[b].emplace_back(a, eid++); }`
`bicomps([&](const vi& edgelist) {...});`
Time: $\mathcal{O}(E+V)$

c6b7c7, 32 lines

```
vi num, st;
vector<vector<pii>> ed;
int Time;
template<class F>
int dfs(int at, int par, F& f) {
  int me = num[at] = ++Time, top = me;
  for (auto [y, e] : ed[at]) if (e != par) {
    if (num[y]) {
      top = min(top, num[y]);
      if (num[y] < me)
        st.push_back(e);
    } else {
      int si = sz(st);
      int up = dfs(y, e, f);
      top = min(top, up);
      if (up == me) {
        st.push_back(e);
        f(vi(st.begin() + si, st.end()));
        st.resize(si);
      }
      else if (up < me) st.push_back(e);
      else { /* e is a bridge */ }
    }
  }
  return top;
}

template<class F>
void bicomps(F f) {
  num.assign(sz(ed), 0);
  rep(i,0,sz(ed)) if (!num[i]) dfs(i, -1, f);
}
```

2sat.h

Description: Calculates a valid assignment to boolean variables a, b, c,... to a 2-SAT problem, so that an expression of the type $(a||b)\&\&(!a||c)\&\&(d||!b)\&\&\ldots$ becomes true, or reports that it is unsatisfiable. Negated variables are represented by bit-inversions (~x).
Usage: `TwoSat ts(number of boolean variables);`
`ts.either(0, ~3); // Var 0 is true or var 3 is false`
`ts.setValue(2); // Var 2 is true`
`ts.atMostOne({0,~1,2}); // <= 1 of vars 0, ~1 and 2 are true`
`ts.solve(); // Returns true iff it is solvable`
`ts.values[0..N-1] holds the assigned values to the vars`
Time: $\mathcal{O}(N+E)$, where N is the number of boolean variables, and E is the number of clauses.

5f9706, 56 lines

```
struct TwoSat {
  int N;
  vector<vi> gr;
  vi values; // 0 = false, 1 = true

  TwoSat(int n = 0) : N(n), gr(2*n) {}

  int addVar() { // (optional)
    gr.emplace_back();
    gr.emplace_back();
    return N++;
  }

  void either(int f, int j) {
    f = max(2*f, -1-2*f);
    j = max(2*j, -1-2*j);
    gr[f].push_back(j^1);
    gr[j].push_back(f^1);
  }
  void setValue(int x) { either(x, x); }

  void atMostOne(const vi& li) { // (optional)
    if (sz(li) <= 1) return;
    int cur = ~li[0];
    rep(i,2,sz(li)) {
      int next = addVar();
      either(cur, ~li[i]);
      either(cur, next);
      either(~li[i], next);
      cur = ~next;
    }
    either(cur, ~li[1]);
  }

  vi val, comp, z; int time = 0;
  int dfs(int i) {
    int low = val[i] = ++time, x; z.push_back(i);
    for(int e : gr[i]) if (!comp[e])
      low = min(low, val[e] ?: dfs(e));
    if (low == val[i]) do {
      x = z.back(); z.pop_back();
      comp[x] = low;
      if (values[x>>1] == -1)
        values[x>>1] = x&1;
    } while (x != i);
    return val[i] = low;
  }

  bool solve() {
    values.assign(N, -1);
    val.assign(2*N, 0); comp = val;
    rep(i,0,2*N) if (!comp[i]) dfs(i);
    rep(i,0,N) if (comp[2*i] == comp[2*i+1]) return 0;
    return 1;
  }
};
```

EulerWalk.h

Description: Eulerian undirected/directed path/cycle algorithm. Input should be a vector of (dest, global edge index), where for undirected graphs, forward/backward edges have the same index. Returns a list of nodes in the Eulerian path/cycle with src at both start and end, or empty list if no cycle/path exists. To get edge indices back, add .second to s and ret.
Time: $\mathcal{O}(V+E)$

780b64, 15 lines

```
vi eulerWalk(vector<vector<pii>>& gr, int nedges, int src=0) {
  int n = sz(gr);
  vi D(n), its(n), eu(nedges), ret, s = {src};
  D[src]++; // to allow Euler paths, not just cycles
  while (!s.empty()) {
    int x = s.back(), y, e, &it = its[x], end = sz(gr[x]);
    if (it == end){ ret.push_back(x); s.pop_back(); continue; }
    tie(y, e) = gr[x][it++];
    if (!eu[e]) {
      D[x]--, D[y]++;
      eu[e] = 1; s.push_back(y);
    }}
  for (int x : D) if (x < 0 || sz(ret) != nedges+1) return {};
  return {ret.rbegin(), ret.rend()};
}
```

7.5 Coloring

EdgeColoring.h

Description: Given a simple, undirected graph with max degree D, computes a $(D+1)$-coloring of the edges such that no neighboring edges share a color. (D-coloring is NP-hard, but can be done for bipartite graphs by repeated matchings of max-degree nodes.)
Time: $\mathcal{O}(NM)$

e210e2, 31 lines

```
vi edgeColoring(int N, vector<pii> eds) {
  vi cc(N + 1), ret(sz(eds)), fan(N), free(N), loc;
  for (pii e : eds) ++cc[e.first], ++cc[e.second];
  int u, v, ncols = *max_element(all(cc)) + 1;
  vector<vi> adj(N, vi(ncols, -1));
  for (pii e : eds) {
    tie(u, v) = e;
    fan[0] = v;
    loc.assign(ncols, 0);
    int at = u, end = u, d, c = free[u], ind = 0, i = 0;
    while (d = free[v], !loc[d] && (v = adj[u][d]) != -1)
      loc[d] = ++ind, cc[ind] = d, fan[ind] = v;
    cc[loc[d]] = c;
    for (int cd = d; at != -1; cd ^= c ^ d, at = adj[at][cd])
      swap(adj[at][cd], adj[end = at][cd ^ c ^ d]);
    while (adj[fan[i]][d] != -1) {
      int left = fan[i], right = fan[++i], e = cc[i];
      adj[u][e] = left;
      adj[left][e] = u;
      adj[right][e] = -1;
      free[right] = e;
    }
    adj[u][d] = fan[i];
    adj[fan[i]][d] = u;
    for (int y : {fan[0], u, end})
      for (int& z = free[y] = 0; adj[y][z] != -1; z++);
  }
  rep(i,0,sz(eds))
    for (tie(u, v) = eds[i]; adj[u][ret[i]] != v;) ++ret[i];
  return ret;
}
```

7.6 Heuristics

MaximalCliques.h

Description: Runs a callback for all maximal cliques in a graph (given as a symmetric bitset matrix; self-edges not allowed). Callback is given a bitset representing the maximal clique.

Time: $\mathcal{O}\left(3^{n/3}\right)$, much faster for sparse graphs

b0d5b1, 12 lines

```
typedef bitset<128> B;
template<class F>
void cliques(vector<B>& eds, F f, B P = ~B(), B X={}, B R={}) {
  if (!P.any()) { if (!X.any()) f(R); return; }
  auto q = (P | X)._Find_first();
  auto cands = P & ~eds[q];
  rep(i,0,sz(eds)) if (cands[i]) {
    R[i] = 1;
    cliques(eds, f, P & eds[i], X & eds[i], R);
    R[i] = P[i] = 0; X[i] = 1;
  }
}
```

MaximumClique.h

Description: Quickly finds a maximum clique of a graph (given as symmetric bitset matrix; self-edges not allowed). Can be used to find a maximum independent set by finding a clique of the complement graph.

Time: Runs in about 1s for n=155 and worst case random graphs (p=.90). Runs faster for sparse graphs.

f7c0bc, 49 lines

```
typedef vector<bitset<200>> vb;
struct Maxclique {
  double limit=0.025, pk=0;
  struct Vertex { int i, d=0; };
  typedef vector<Vertex> vv;
  vb e;
  vv V;
  vector<vi> C;
  vi qmax, q, S, old;
  void init(vv& r) {
    for (auto& v : r) v.d = 0;
    for (auto& v : r) for (auto j : r) v.d += e[v.i][j.i];
    sort(all(r), [](auto a, auto b) { return a.d > b.d; });
    int mxD = r[0].d;
    rep(i,0,sz(r)) r[i].d = min(i, mxD) + 1;
  }
  void expand(vv& R, int lev = 1) {
    S[lev] += S[lev - 1] - old[lev];
    old[lev] = S[lev - 1];
    while (sz(R)) {
      if (sz(q) + R.back().d <= sz(qmax)) return;
      q.push_back(R.back().i);
      vv T;
      for(auto v:R) if (e[R.back().i][v.i]) T.push_back({v.i});
      if (sz(T)) {
        if (S[lev]++ / ++pk < limit) init(T);
        int j = 0, mxk = 1, mnk = max(sz(qmax) - sz(q) + 1, 1);
        C[1].clear(), C[2].clear();
        for (auto v : T) {
          int k = 1;
          auto f = [&](int i) { return e[v.i][i]; };
          while (any_of(all(C[k]), f)) k++;
          if (k > mxk) mxk = k, C[mxk + 1].clear();
          if (k < mnk) T[j++].i = v.i;
          C[k].push_back(v.i);
        }
        if (j > 0) T[j - 1].d = 0;
        rep(k,mnk,mxk + 1) for (int i : C[k])
          T[j].i = i, T[j++].d = k;
        expand(T, lev + 1);
      } else if (sz(q) > sz(qmax)) qmax = q;
      q.pop_back(), R.pop_back();
    }
  }
  vi maxClique() { init(V), expand(V); return qmax; }
  Maxclique(vb conn) : e(conn), C(sz(e)+1), S(sz(C)), old(S) {
    rep(i,0,sz(e)) V.push_back({i});
  }
};
```

MaximumIndependentSet.h

Description: To obtain a maximum independent set of a graph, find a max clique of the complement. If the graph is bipartite, see MinimumVertexCover.

7.7 Trees

BinaryLifting.h

Description: Calculate power of two jumps in a tree, to support fast upward jumps and LCAs. Assumes the root node points to itself.

Time: construction $\mathcal{O}(N \log N)$, queries $\mathcal{O}(\log N)$

bfce85, 25 lines

```
vector<vi> treeJump(vi& P){
  int on = 1, d = 1;
  while(on < sz(P)) on *= 2, d++;
  vector<vi> jmp(d, P);
  rep(i,1,d) rep(j,0,sz(P))
    jmp[i][j] = jmp[i-1][jmp[i-1][j]];
  return jmp;
}

int jmp(vector<vi>& tbl, int nod, int steps){
  rep(i,0,sz(tbl))
    if(steps&(1<<i)) nod = tbl[i][nod];
  return nod;
}

int lca(vector<vi>& tbl, vi& depth, int a, int b) {
  if (depth[a] < depth[b]) swap(a, b);
  a = jmp(tbl, a, depth[a] - depth[b]);
  if (a == b) return a;
  for (int i = sz(tbl); i--;) {
    int c = tbl[i][a], d = tbl[i][b];
    if (c != d) a = c, b = d;
  }
  return tbl[0][a];
}
```

LCA.h

Description: Data structure for computing lowest common ancestors in a tree (with 0 as root). C should be an adjacency list of the tree, either directed or undirected.

Time: $\mathcal{O}(N \log N + Q)$

"../data-structures/RMQ.h" 0f62fb, 21 lines

```
struct LCA {
  int T = 0;
  vi time, path, ret;
  RMQ<int> rmq;

  LCA(vector<vi>& C) : time(sz(C)), rmq((dfs(C,0,-1), ret)) {}
  void dfs(vector<vi>& C, int v, int par) {
    time[v] = T++;
    for (int y : C[v]) if (y != par) {
      path.push_back(v), ret.push_back(time[v]);
      dfs(C, y, v);
    }
  }

  int lca(int a, int b) {
    if (a == b) return a;
    tie(a, b) = minmax(time[a], time[b]);
    return path[rmq.query(a, b)];
  }
  //dist(a,b){return depth[a] + depth[b] - 2*depth[lca(a,b)];}
};
```

CompressTree.h

Description: Given a rooted tree and a subset S of nodes, compute the minimal subtree that contains all the nodes by adding all (at most $|S| - 1$) pairwise LCA's and compressing edges. Returns a list of (par, orig_index) representing a tree rooted at 0. The root points to itself.

Time: $\mathcal{O}(|S| \log |S|)$

<cassert>, "LCA.h" 9775a0, 21 lines

```
typedef vector<pair<int, int>> vpi;
vpi compressTree(LCA& lca, const vi& subset) {
  static vi rev; rev.resize(sz(lca.time));
  vi li = subset, &T = lca.time;
  auto cmp = [&](int a, int b) { return T[a] < T[b]; };
  sort(all(li), cmp);
  int m = sz(li)-1;
  rep(i,0,m) {
    int a = li[i], b = li[i+1];
    li.push_back(lca.lca(a, b));
  }
  sort(all(li), cmp);
  li.erase(unique(all(li)), li.end());
  rep(i,0,sz(li)) rev[li[i]] = i;
  vpi ret = {pii(0, li[0])};
  rep(i,0,sz(li)-1) {
    int a = li[i], b = li[i+1];
    ret.emplace_back(rev[lca.lca(a, b)], b);
  }
  return ret;
}
```

HLD.h

Description: Decomposes a tree into vertex disjoint heavy paths and light edges such that the path from any leaf to the root contains at most log(n) light edges. Code does additive modifications and max queries, but can support commutative segtree modifications/queries on paths and subtrees. Takes as input the full adjacency list. VALS_EDGES being true means that values are stored in the edges, as opposed to the nodes. All values initialized to the segtree default. Root must be 0.

Time: $\mathcal{O}\left((\log N)^2\right)$

<cassert>, "../data-structures/LazySegmentTree.h" 9547af, 46 lines

```
template <bool VALS_EDGES> struct HLD {
  int N, tim = 0;
  vector<vi> adj;
  vi par, siz, rt, pos;
  Node *tree;
  HLD(vector<vi> adj_)
    : N(sz(adj_)), adj(adj_), par(N, -1), siz(N, 1),
      rt(N),pos(N),tree(new Node(0, N)){ dfsSz(0); dfsHld(0); }
  void dfsSz(int v) {
    for (int& u : adj[v]) {
      adj[u].erase(find(all(adj[u]), v));
      par[u] = v;
      dfsSz(u);
      siz[v] += siz[u];
      if (siz[u] > siz[adj[v][0]]) swap(u, adj[v][0]);
    }
  }
  void dfsHld(int v) {
    pos[v] = tim++;
    for (int u : adj[v]) {
      rt[u] = (u == adj[v][0] ? rt[v] : u);
      dfsHld(u);
    }
```

```
  }
  template <class B> void process(int u, int v, B op) {
    for (;; v = par[rt[v]]) {
      if (pos[u] > pos[v]) swap(u, v);
      if (rt[u] == rt[v]) break;
      op(pos[rt[v]], pos[v] + 1);
    }
    op(pos[u] + VALS_EDGES, pos[v] + 1);
  }
  void modifyPath(int u, int v, int val) {
    process(u, v, [&](int l, int r) { tree->add(l, r, val); });
  }
  int queryPath(int u, int v) { // Modify depending on problem
    int res = -1e9;
    process(u, v, [&](int l, int r) {
        res = max(res, tree->query(l, r));
    });
    return res;
  }
  int querySubtree(int v) { // modifySubtree is similar
    return tree->query(pos[v] + VALS_EDGES, pos[v] + siz[v]);
  }
};
```

LinkCutTree.h

Description: Represents a forest of unrooted trees. You can add and remove edges (as long as the result is still a forest), and check whether two nodes are in the same tree.

Time: All operations take amortized $\mathcal{O}(\log N)$.

<cassert> 0fb462, 90 lines

```
struct Node { // Splay tree. Root's pp contains tree's parent.
  Node *p = 0, *pp = 0, *c[2];
  bool flip = 0;
  Node() { c[0] = c[1] = 0; fix(); }
  void fix() {
    if (c[0]) c[0]->p = this;
    if (c[1]) c[1]->p = this;
    // (+ update sum of subtree elements etc. if wanted)
  }
  void pushFlip() {
    if (!flip) return;
    flip = 0; swap(c[0], c[1]);
    if (c[0]) c[0]->flip ^= 1;
    if (c[1]) c[1]->flip ^= 1;
  }
  int up() { return p ? p->c[1] == this : -1; }
  void rot(int i, int b) {
    int h = i ^ b;
    Node *x = c[i], *y = b == 2 ? x : x->c[h], *z = b ? y : x;
    if ((y->p = p)) p->c[up()] = y;
    c[i] = z->c[i ^ 1];
    if (b < 2) {
      x->c[h] = y->c[h ^ 1];
      y->c[h ^ 1] = x;
    }
    z->c[i ^ 1] = this;
    fix(); x->fix(); y->fix();
    if (p) p->fix();
    swap(pp, y->pp);
  }
  void splay() {
    for (pushFlip(); p; ) {
      if (p->p) p->p->pushFlip();
      p->pushFlip(); pushFlip();
      int c1 = up(), c2 = p->up();
      if (c2 == -1) p->rot(c1, 2);
      else p->p->rot(c2, c1 != c2);
    }
  }
  Node* first() {
    pushFlip();
    return c[0] ? c[0]->first() : (splay(), this);
  }
};

struct LinkCut {
  vector<Node> node;
  LinkCut(int N) : node(N) {}

  void link(int u, int v) { // add an edge (u, v)
    assert(!connected(u, v));
    makeRoot(&node[u]);
    node[u].pp = &node[v];
  }
  void cut(int u, int v) { // remove an edge (u, v)
    Node *x = &node[u], *top = &node[v];
    makeRoot(top); x->splay();
    assert(top == (x->pp ?: x->c[0]));
    if (x->pp) x->pp = 0;
    else {
      x->c[0] = top->p = 0;
      x->fix();
    }
  }
  bool connected(int u, int v) { // are u, v in the same tree?
    Node* nu = access(&node[u])->first();
    return nu == access(&node[v])->first();
  }
  void makeRoot(Node* u) {
    access(u);
    u->splay();
    if(u->c[0]) {
      u->c[0]->p = 0;
      u->c[0]->flip ^= 1;
      u->c[0]->pp = u;
      u->c[0] = 0;
      u->fix();
    }
  }
  Node* access(Node* u) {
    u->splay();
    while (Node* pp = u->pp) {
      pp->splay(); u->pp = 0;
      if (pp->c[1]) {
        pp->c[1]->p = 0; pp->c[1]->pp = pp; }
      pp->c[1] = u; pp->fix(); u = pp;
    }
    return u;
  }
};
```

DirectedMST.h

Description: Finds a minimum spanning tree/arborescence of a directed graph, given a root node. If no MST exists, returns -1.

Time: $\mathcal{O}(E \log V)$

"../data-structures/UnionFindRollback.h" 39e620, 60 lines

```
struct Edge { int a, b; ll w; };
struct Node {
  Edge key;
  Node *l, *r;
  ll delta;
  void prop() {
    key.w += delta;
    if (l) l->delta += delta;
    if (r) r->delta += delta;
    delta = 0;
  }
  Edge top() { prop(); return key; }
};
Node *merge(Node *a, Node *b) {
  if (!a || !b) return a ?: b;
  a->prop(), b->prop();
  if (a->key.w > b->key.w) swap(a, b);
  swap(a->l, (a->r = merge(b, a->r)));
  return a;
}
void pop(Node*& a) { a->prop(); a = merge(a->l, a->r); }

pair<ll, vi> dmst(int n, int r, vector<Edge>& g) {
  RollbackUF uf(n);
  vector<Node*> heap(n);
  for (Edge e : g) heap[e.b] = merge(heap[e.b], new Node{e});
  ll res = 0;
  vi seen(n, -1), path(n), par(n);
  seen[r] = r;
  vector<Edge> Q(n), in(n, {-1,-1}), comp;
  deque<tuple<int, int, vector<Edge>>> cycs;
  rep(s,0,n) {
    int u = s, qi = 0, w;
    while (seen[u] < 0) {
      if (!heap[u]) return {-1,{}};
      Edge e = heap[u]->top();
      heap[u]->delta -= e.w, pop(heap[u]);
      Q[qi] = e, path[qi++] = u, seen[u] = s;
      res += e.w, u = uf.find(e.a);
      if (seen[u] == s) {
        Node* cyc = 0;
        int end = qi, time = uf.time();
        do cyc = merge(cyc, heap[w = path[--qi]]);
        while (uf.join(u, w));
        u = uf.find(u), heap[u] = cyc, seen[u] = -1;
        cycs.push_front({u, time, {&Q[qi], &Q[end]}});
      }
    }
    rep(i,0,qi) in[uf.find(Q[i].b)] = Q[i];
  }

  for (auto& [u,t,comp] : cycs) { // restore sol (optional)
    uf.rollback(t);
    Edge inEdge = in[u];
    for (auto& e : comp) in[uf.find(e.b)] = e;
    in[uf.find(inEdge.b)] = inEdge;
  }
  rep(i,0,n) par[i] = in[i].a;
  return {res, par};
}
```

7.8 Math

7.8.1 Number of Spanning Trees

Create an $N \times N$ matrix `mat`, and for each edge $a \to b \in G$, do `mat[a][b]--, mat[b][b]++` (and `mat[b][a]--, mat[a][a]++` if G is undirected). Remove the ith row and column and take the determinant; this yields the number of directed spanning trees rooted at i (if G is undirected, remove any row/column).

Geometry (8)

8.1 Geometric primitives

Point.h

Description: Class to handle points in the plane. T can be e.g. double or long long. (Avoid int.)

47ec0a, 28 lines

```
template <class T> int sgn(T x) { return (x > 0) - (x < 0); }
template<class T>
struct Point {
  typedef Point P;
  T x, y;
  explicit Point(T x=0, T y=0) : x(x), y(y) {}
  bool operator<(P p) const { return tie(x,y) < tie(p.x,p.y); }
  bool operator==(P p) const { return tie(x,y)==tie(p.x,p.y); }
  P operator+(P p) const { return P(x+p.x, y+p.y); }
  P operator-(P p) const { return P(x-p.x, y-p.y); }
  P operator*(T d) const { return P(x*d, y*d); }
  P operator/(T d) const { return P(x/d, y/d); }
  T dot(P p) const { return x*p.x + y*p.y; }
  T cross(P p) const { return x*p.y - y*p.x; }
  T cross(P a, P b) const { return (a-*this).cross(b-*this); }
  T dist2() const { return x*x + y*y; }
  double dist() const { return sqrt((double)dist2()); }
  // angle to x-axis in interval [-pi, pi]
  double angle() const { return atan2(y, x); }
  P unit() const { return *this/dist(); } // makes dist()=1
  P perp() const { return P(-y, x); } // rotates +90 degrees
  P normal() const { return perp().unit(); }
  // returns point rotated 'a' radians ccw around the origin
  P rotate(double a) const {
    return P(x*cos(a)-y*sin(a),x*sin(a)+y*cos(a)); }
  friend ostream& operator<<(ostream& os, P p) {
    return os << "(" << p.x << "," << p.y << ")"; }
};
```

sideOf.h

Description: Returns where p is as seen from s towards e. 1/0/-1 $\Leftrightarrow$ left/on line/right. If the optional argument eps is given 0 is returned if p is within distance eps from the line. P is supposed to be Point<T> where T is e.g. double or long long. It uses products in intermediate steps so watch out for overflow if using int or long long.

Usage: `bool left = sideOf(p1,p2,q)==1;`

"Point.h" ca4665, 9 lines

```
template<class P>
int sideOf(P s, P e, P p) { return sgn(s.cross(e, p)); }

template<class P>
int sideOf(P s, P e, P p, double eps) {
  auto a = (e-s).cross(p-s);
  double l = (e-s).dist()*eps;
  return (a > l) - (a < -l);
}
```

OnSegment.h


Description: Returns true iff p lies on the line segment from s to e. Use `(segDist(s,e,p)<=epsilon)` instead when using Point<double>.

"Point.h" c597e8, 3 lines

```
template<class P> bool onSegment(P s, P e, P p) {
  return p.cross(s, e) == 0 && (s - p).dot(e - p) <= 0;
}
```

lineDistance.h

Description:
Returns the signed distance between point p and the line containing points a and b. Positive value on left side and negative on right as seen from a towards b. a==b gives nan. P is supposed to be Point<T> or Point3D<T> where T is e.g. double or long long. It uses products in intermediate steps so watch out for overflow if using int or long long. Using Point3D will always give a non-negative distance. For Point3D, call .dist on the result of the cross product.




"Point.h" 53630a, 4 lines

```
template<class P>
double lineDist(P a, P b, P p) {
  return (double)(b-a).cross(p-a)/(b-a).dist();
}
```

SegmentDistance.h

Description:
Returns the shortest distance between point p and the line segment from point s to e.




Usage:
```
Point<double> a, b(2,2), p(1,1);
bool onSegment = segDist(a,b,p) < 1e-10;
```

"Point.h" d5f39f, 6 lines

```
typedef Point<double> P;
double segDist(P s, P e, P p) {
  if (s==e) return (p-s).dist();
  auto d = (e-s).dist2(), t = min(d,max(.0,(p-s).dot(e-s)));
  return ((p-s)*d-(e-s)*t).dist()/d;
}
```

lineIntersection.h

Description:
If a unique intersection point of the lines going through s1,e1 and s2,e2 exists {1, point} is returned. If no intersection point exists {0, (0,0)} is returned and if infinitely many exists {-1, (0,0)} is returned. The wrong position will be returned if P is Point<ll> and the intersection point does not have integer coordinates. Products of three coordinates are used in intermediate steps so watch out for overflow if using int or ll.




Usage:
```
auto res = lineInter(s1,e1,s2,e2);
if (res.first == 1)
cout << "intersection point at " << res.second << endl;
```

"Point.h" a01f81, 8 lines

```
template<class P>
pair<int, P> lineInter(P s1, P e1, P s2, P e2) {
  auto d = (e1 - s1).cross(e2 - s2);
  if (d == 0) // if parallel
    return {-(s1.cross(e1, s2) == 0), P(0, 0)};
  auto p = s2.cross(e1, e2), q = s2.cross(e2, s1);
  return {1, (s1 * p + e1 * q) / d};
}
```

SegmentIntersection.h

Description:
If a unique intersection point between the line segments going from s1 to e1 and from s2 to e2 exists then it is returned. If no intersection point exists an empty vector is returned. If infinitely many exist a vector with 2 elements is returned, containing the endpoints of the common line segment. The wrong position will be returned if P is Point<ll> and the intersection point does not have integer coordinates. Products of three coordinates are used in intermediate steps so watch out for overflow if using int or long long.



Usage:
```
vector<P> inter = segInter(s1,e1,s2,e2);
if (sz(inter)==1)
cout << "segments intersect at " << inter[0] << endl;
```


"Point.h", "OnSegment.h" 9d57f2, 13 lines

```
template<class P> vector<P> segInter(P a, P b, P c, P d) {
  auto oa = c.cross(d, a), ob = c.cross(d, b),
       oc = a.cross(b, c), od = a.cross(b, d);
  // Checks if intersection is single non-endpoint point.
  if (sgn(oa) * sgn(ob) < 0 && sgn(oc) * sgn(od) < 0)
    return {(a * ob - b * oa) / (ob - oa)};
  set<P> s;
  if (onSegment(c, d, a)) s.insert(a);
  if (onSegment(c, d, b)) s.insert(b);
  if (onSegment(a, b, c)) s.insert(c);
  if (onSegment(a, b, d)) s.insert(d);
  return {all(s)};
}
```

8.2 Circles

circumcircle.h

Description:
The circumcirle of a triangle is the circle intersecting all three vertices. ccRadius returns the radius of the circle going through points A, B and C and ccCenter returns the center of the same circle.



"Point.h" 6cffc5, 9 lines

```
typedef Point<double> P;
double ccRadius(P A, P B, P C) {
  return (B-A).dist()*(C-B).dist()*(A-C).dist()/
      abs((B-A).cross(C-A))/2;
}
P ccCenter(P A, P B, P C) {
  P b = C-A, c = B-A;
  return A + (b*c.dist2()-c*b.dist2()).perp()/b.cross(c)/2;
}
```

CircleIntersection.h

Description: Computes the pair of points at which two circles intersect. Returns false in case of no intersection.

<cassert>, "Point.h" 84d6d3, 11 lines

```
typedef Point<double> P;
bool circleInter(P a,P b,double r1,double r2,pair<P, P>* out) {
  if (a == b) { assert(r1 != r2); return false; }
  P vec = b - a;
  double d2 = vec.dist2(), sum = r1+r2, dif = r1-r2,
         p = (d2 + r1*r1 - r2*r2)/(d2*2), h2 = r1*r1 - p*p*d2;
  if (sum*sum < d2 || dif*dif > d2) return false;
  P mid = a + vec*p, per = vec.perp() * sqrt(fmax(0, h2) / d2);
  *out = {mid + per, mid - per};
  return true;
}
```

8.3 Polygons

PolygonArea.h

Description: Returns twice the signed area of a polygon. Clockwise enumeration gives negative area. Watch out for overflow if using int as T!

"Point.h" f12300, 6 lines

```
template<class T>
T polygonArea2(vector<Point<T>>& v) {
  T a = v.back().cross(v[0]);
  rep(i,0,sz(v)-1) a += v[i].cross(v[i+1]);
  return a;
}
```

InsidePolygon.h

Description: Returns true if p lies within the polygon. If strict is true, it returns false for points on the boundary. The algorithm uses products in intermediate steps so watch out for overflow.

Usage:
```
vector<P> v = {P{4,4}, P{1,2}, P{2,1}};
bool in = inPolygon(v, P{3, 3}, false);
```

Time: $\mathcal{O}(n)$

"Point.h", "OnSegment.h", "SegmentDistance.h" 2bf504, 11 lines

```
template<class P>
bool inPolygon(vector<P> &p, P a, bool strict = true) {
  int cnt = 0, n = sz(p);
  rep(i,0,n) {
    P q = p[(i + 1) % n];
    if (onSegment(p[i], q, a)) return !strict;
    //or: if (segDist(p[i], q, a) <= eps) return !strict;
    cnt ^= ((a.y<p[i].y) - (a.y<q.y)) * a.cross(p[i], q) > 0;
  }
  return cnt;
}
```

ConvexHull.h



Description:
Returns a vector of the points of the convex hull in counter-clockwise order. Points on the edge of the hull between two other points are not considered part of the hull.
Time: $\mathcal{O}(n \log n)$

"Point.h" 310954, 13 lines

```
typedef Point<ll> P;
vector<P> convexHull(vector<P> pts) {
  if (sz(pts) <= 1) return pts;
  sort(all(pts));
  vector<P> h(sz(pts)+1);
  int s = 0, t = 0;
  for (int it = 2; it--; s = --t, reverse(all(pts)))
    for (P p : pts) {
      while (t >= s + 2 && h[t-2].cross(h[t-1], p) <= 0) t--;
      h[t++] = p;
    }
  return {h.begin(), h.begin() + t - (t == 2 && h[0] == h[1])};
}
```

8.4 Misc. Point Set Problems

ClosestPair.h

Description: Finds the closest pair of points.
Time: $\mathcal{O}(n \log n)$

<cassert>, "Point.h" ac41a6, 17 lines

```
typedef Point<ll> P;
pair<P, P> closest(vector<P> v) {
  assert(sz(v) > 1);
  set<P> S;
  sort(all(v), [](P a, P b) { return a.y < b.y; });
  pair<ll, pair<P, P>> ret{LLONG_MAX, {P(), P()}};
  int j = 0;
  for (P p : v) {
    P d{1 + (ll)sqrt(ret.first), 0};
    while (v[j].y <= p.y - d.x) S.erase(v[j++]);
    auto lo = S.lower_bound(p - d), hi = S.upper_bound(p + d);
    for (; lo != hi; ++lo)
      ret = min(ret, {(*lo - p).dist2(), {*lo, p}});
    S.insert(p);
  }
  return ret.second;
}
```

Strings (9)

KMP.h

Description: pi[x] computes the length of the longest prefix of s that ends at x, other than s[0...x] itself (abacaba -> 0010123). Can be used to find all occurrences of a string.
Time: $\mathcal{O}(n)$

d4375c, 16 lines

```
vi pi(const string& s) {
  vi p(sz(s));
  rep(i,1,sz(s)) {
    int g = p[i-1];
    while (g && s[i] != s[g]) g = p[g-1];
    p[i] = g + (s[i] == s[g]);
  }
  return p;
}

vi match(const string& s, const string& pat) {
  vi p = pi(pat + '\0' + s), res;
  rep(i,sz(p)-sz(s),sz(p))
    if (p[i] == sz(pat)) res.push_back(i - 2 * sz(pat));
  return res;
}
```

Zfunc.h

Description: z[i] computes the length of the longest common prefix of s[i:] and s, except z[0] = 0. (abacaba -> 0010301)
Time: $\mathcal{O}(n)$

ee09e2, 12 lines

```
vi Z(const string& S) {
  vi z(sz(S));
  int l = -1, r = -1;
  rep(i,1,sz(S)) {
    z[i] = i >= r ? 0 : min(r - i, z[i - l]);
    while (i + z[i] < sz(S) && S[i + z[i]] == S[z[i]])
      z[i]++;
    if (i + z[i] > r)
      l = i, r = i + z[i];
  }
  return z;
}
```

Manacher.h

Description: For each position in a string, computes p[0][i] = half length of longest even palindrome around pos i, p[1][i] = longest odd (half rounded down).
Time: $\mathcal{O}(N)$

e7ad79, 13 lines

```
array<vi, 2> manacher(const string& s) {
  int n = sz(s);
  array<vi,2> p = {vi(n+1), vi(n)};
  rep(z,0,2) for (int i=0,l=0,r=0; i < n; i++) {
    int t = r-i+!z;
    if (i<r) p[z][i] = min(t, p[z][l+t]);
    int L = i-p[z][i], R = i+p[z][i]-!z;
    while (L>=1 && R+1<n && s[L-1] == s[R+1])
      p[z][i]++, L--, R++;
    if (R>r) l=L, r=R;
  }
  return p;
}
```

MinRotation.h

Description: Finds the lexicographically smallest rotation of a string.
Usage: rotate(v.begin(), v.begin()+minRotation(v), v.end());
Time: $\mathcal{O}(N)$

d07a42, 8 lines

```
int minRotation(string s) {
  int a=0, N=sz(s); s += s;
  rep(b,0,N) rep(k,0,N) {
    if (a+k == b || s[a+k] < s[b+k]) {b += max(0, k-1); break;}
    if (s[a+k] > s[b+k]) { a = b; break; }
  }
  return a;
}
```

SuffixArray.h

Description: Builds suffix array for a string. sa[i] is the starting index of the suffix which is i'th in the sorted suffix array. The returned vector is of size $n+1$, and sa[0] = n. The lcp array contains longest common prefixes for neighbouring strings in the suffix array: lcp[i] = lcp(sa[i], sa[i-1]), lcp[0] = 0. The input string must not contain any nul chars.
Time: $\mathcal{O}(n \log n)$

635552, 22 lines

```
struct SuffixArray {
  vi sa, lcp;
  SuffixArray(string s, int lim=256) { // or vector<int>
    s.push_back(0); int n = sz(s), k = 0, a, b;
    vi x(all(s)), y(n), ws(max(n, lim));
    sa = lcp = y, iota(all(sa), 0);
    for (int j = 0, p = 0; p < n; j = max(1, j * 2), lim = p) {
      p = j, iota(all(y), n - j);
      rep(i,0,n) if (sa[i] >= j) y[p++] = sa[i] - j;
      fill(all(ws), 0);
      rep(i,0,n) ws[x[i]]++;
      rep(i,1,lim) ws[i] += ws[i - 1];
      for (int i = n; i--;) sa[--ws[x[y[i]]]] = y[i];
      swap(x, y), p = 1, x[sa[0]] = 0;
      rep(i,1,n) a = sa[i - 1], b = sa[i], x[b] =
        (y[a] == y[b] && y[a + j] == y[b + j]) ? p - 1 : p++;
    }
    for (int i = 0, j; i < n - 1; lcp[x[i++]] = k)
      for (k && k--, j = sa[x[i] - 1];
          s[i + k] == s[j + k]; k++);
  }
};
```

SuffixTree.h

Description: Ukkonen's algorithm for online suffix tree construction. Each node contains indices [l, r) into the string, and a list of child nodes. Suffixes are given by traversals of this tree, joining [l, r) substrings. The root is 0 (has l = -1, r = 0), non-existent children are -1. To get a complete tree, append a dummy symbol – otherwise it may contain an incomplete path (still useful for substring matching, though).
Time: $\mathcal{O}(26N)$

aae0b8, 50 lines

```
struct SuffixTree {
  enum { N = 200010, ALPHA = 26 }; // N ~ 2*maxlen+10
  int toi(char c) { return c - 'a'; }
  string a; // v = cur node, q = cur position
  int t[N][ALPHA],l[N],r[N],p[N],s[N],v=0,q=0,m=2;

  void ukkadd(int i, int c) { suff:
    if (r[v]<=q) {
      if (t[v][c]==-1) { t[v][c]=m;  l[m]=i;
        p[m++]=v; v=s[v]; q=r[v];  goto suff; }
      v=t[v][c]; q=l[v];
    }
    if (q==-1 || c==toi(a[q])) q++; else {
      l[m+1]=i;  p[m+1]=m;  l[m]=l[v];  r[m]=q;
      p[m]=p[v];  t[m][c]=m+1;  t[m][toi(a[q])]=v;
      l[v]=q;  p[v]=m;  t[p[m]][toi(a[l[m]])]=m;
      v=s[p[m]];  q=l[m];
      while (q<r[m]) { v=t[v][toi(a[q])];  q+=r[v]-l[v]; }
      if (q==r[m])  s[m]=v;  else s[m]=m+2;
      q=r[v]-(q-r[m]);  m+=2;  goto suff;
    }
  }

  SuffixTree(string a) : a(a) {
    fill(r,r+N,sz(a));
    memset(s, 0, sizeof s);
    memset(t, -1, sizeof t);
    fill(t[1],t[1]+ALPHA,0);
    s[0] = 1; l[0] = l[1] = -1; r[0] = r[1] = p[0] = p[1] = 0;
    rep(i,0,sz(a)) ukkadd(i, toi(a[i]));
  }

  // example: find longest common substring (uses ALPHA = 28)
  pii best;
  int lcs(int node, int i1, int i2, int olen) {
    if (l[node] <= i1 && i1 < r[node]) return 1;
    if (l[node] <= i2 && i2 < r[node]) return 2;
    int mask = 0, len = node ? olen + (r[node] - l[node]) : 0;
    rep(c,0,ALPHA) if (t[node][c] != -1)
      mask |= lcs(t[node][c], i1, i2, len);
    if (mask == 3)
      best = max(best, {len, r[node] - len});
    return mask;
  }
```

```
  static pii LCS(string s, string t) {
    SuffixTree st(s + (char)('z' + 1) + t + (char)('z' + 2));
    st.lcs(0, sz(s), sz(s) + 1 + sz(t), 0);
    return st.best;
  }
};
```

Hashing.h

Description: Self-explanatory methods for string hashing. 2d2a67, 44 lines

```
// Arithmetic mod 2^64-1. 2x slower than mod 2^64 and more
// code, but works on evil test data (e.g. Thue-Morse, where
// ABBA... and BAAB... of length 2^10 hash the same mod 2^64).
// "typedef ull H;" instead if you think test data is random,
// or work mod 10^9+7 if the Birthday paradox is not a problem.
typedef uint64_t ull;
struct H {
  ull x; H(ull x=0) : x(x) {}
  H operator+(H o) { return x + o.x + (x + o.x < x); }
  H operator-(H o) { return *this + ~o.x; }
  H operator*(H o) { auto m = (__uint128_t)x * o.x;
    return H((ull)m) + (ull)(m >> 64); }
  ull get() const { return x + !~x; }
  bool operator==(H o) const { return get() == o.get(); }
  bool operator<(H o) const { return get() < o.get(); }
};
static const H C = (ll)1e11+3; // (order ~ 3e9; random also ok)

struct HashInterval {
  vector<H> ha, pw;
  HashInterval(string& str) : ha(sz(str)+1), pw(ha) {
    pw[0] = 1;
    rep(i,0,sz(str))
      ha[i+1] = ha[i] * C + str[i],
      pw[i+1] = pw[i] * C;
  }
  H hashInterval(int a, int b) { // hash [a, b)
    return ha[b] - ha[a] * pw[b - a];
  }
};

vector<H> getHashes(string& str, int length) {
  if (sz(str) < length) return {};
  H h = 0, pw = 1;
  rep(i,0,length)
    h = h * C + str[i], pw = pw * C;
  vector<H> ret = {h};
  rep(i,length,sz(str)) {
    ret.push_back(h = h * C + str[i] - pw * str[i-length]);
  }
  return ret;
}

H hashString(string& s){H h{}; for(char c:s) h=h*C+c;return h;}
```

AhoCorasick.h

Description: Aho-Corasick automaton, used for multiple pattern matching. Initialize with AhoCorasick ac(patterns); the automaton start node will be at index 0. find(word) returns for each position the index of the longest word that ends there, or -1 if none. findAll(−, word) finds all words (up to $N\sqrt{N}$ many if no duplicate patterns) that start at each position (shortest first). Duplicate patterns are allowed; empty patterns are not. To find the longest words that start at each position, reverse all input. For large alphabets, split each symbol into chunks, with sentinel bits for symbol boundaries.
Time: construction takes $\mathcal{O}(26N)$, where N = sum of length of patterns. find(x) is $\mathcal{O}(N)$, where N = length of x. findAll is $\mathcal{O}(NM)$.
<cassert> f35677, 66 lines

```
struct AhoCorasick {
  enum {alpha = 26, first = 'A'}; // change this!
  struct Node {
    // (nmatches is optional)
    int back, next[alpha], start = -1, end = -1, nmatches = 0;
    Node(int v) { memset(next, v, sizeof(next)); }
  };
  vector<Node> N;
  vi backp;
  void insert(string& s, int j) {
    assert(!s.empty());
    int n = 0;
    for (char c : s) {
      int& m = N[n].next[c - first];
      if (m == -1) { n = m = sz(N); N.emplace_back(-1); }
      else n = m;
    }
    if (N[n].end == -1) N[n].start = j;
    backp.push_back(N[n].end);
    N[n].end = j;
    N[n].nmatches++;
  }
  AhoCorasick(vector<string>& pat) : N(1, -1) {
    rep(i,0,sz(pat)) insert(pat[i], i);
    N[0].back = sz(N);
    N.emplace_back(0);

    queue<int> q;
    for (q.push(0); !q.empty(); q.pop()) {
      int n = q.front(), prev = N[n].back;
      rep(i,0,alpha) {
        int &ed = N[n].next[i], y = N[prev].next[i];
        if (ed == -1) ed = y;
        else {
          N[ed].back = y;
          (N[ed].end == -1 ? N[ed].end : backp[N[ed].start])
            = N[y].end;
          N[ed].nmatches += N[y].nmatches;
          q.push(ed);
        }
      }
    }
  }
  vi find(string word) {
    int n = 0;
    vi res; // ll count = 0;
    for (char c : word) {
      n = N[n].next[c - first];
      res.push_back(N[n].end);
      // count += N[n].nmatches;
    }
    return res;
  }
  vector<vi> findAll(vector<string>& pat, string word) {
    vi r = find(word);
    vector<vi> res(sz(word));
    rep(i,0,sz(word)) {
      int ind = r[i];
      while (ind != -1) {
        res[i - sz(pat[ind]) + 1].push_back(ind);
        ind = backp[ind];
      }
    }
    return res;
  }
};
```

Various (10)

10.1 Intervals

IntervalContainer.h

Description: Add and remove intervals from a set of disjoint intervals. Will merge the added interval with any overlapping intervals in the set when adding. Intervals are [inclusive, exclusive).
Time: $\mathcal{O}(\log N)$ edce47, 23 lines

```
set<pii>::iterator addInterval(set<pii>& is, int L, int R) {
  if (L == R) return is.end();
  auto it = is.lower_bound({L, R}), before = it;
  while (it != is.end() && it->first <= R) {
    R = max(R, it->second);
    before = it = is.erase(it);
  }
  if (it != is.begin() && (--it)->second >= L) {
    L = min(L, it->first);
    R = max(R, it->second);
    is.erase(it);
  }
  return is.insert(before, {L,R});
}

void removeInterval(set<pii>& is, int L, int R) {
  if (L == R) return;
  auto it = addInterval(is, L, R);
  auto r2 = it->second;
  if (it->first == L) is.erase(it);
  else (int&)it->second = L;
  if (R != r2) is.emplace(R, r2);
}
```

IntervalCover.h

Description: Compute indices of smallest set of intervals covering another interval. Intervals should be [inclusive, exclusive). To support [inclusive, inclusive], change (A) to add `|| R.empty()`. Returns empty set on failure (or if G is empty).
Time: $\mathcal{O}(N \log N)$ 9e9d8d, 19 lines

```
template<class T>
vi cover(pair<T, T> G, vector<pair<T, T>> I) {
  vi S(sz(I)), R;
  iota(all(S), 0);
  sort(all(S), [&](int a, int b) { return I[a] < I[b]; });
  T cur = G.first;
  int at = 0;
  while (cur < G.second) { // (A)
    pair<T, int> mx = make_pair(cur, -1);
    while (at < sz(I) && I[S[at]].first <= cur) {
      mx = max(mx, make_pair(I[S[at]].second, S[at]));
      at++;
    }
    if (mx.second == -1) return {};
    cur = mx.first;
    R.push_back(mx.second);
  }
  return R;
}
```

ConstantIntervals.h

Description: Split a monotone function on [from, to) into a minimal set of half-open intervals on which it has the same value. Runs a callback g for each such interval.
Usage: `constantIntervals(0, sz(v), [&](int x){return v[x];}, [&](int lo, int hi, T val){...});`
Time: $\mathcal{O}\left(k \log \frac{n}{k}\right)$ 753a4c, 19 lines

```
template<class F, class G, class T>
void rec(int from, int to, F& f, G& g, int& i, T& p, T q) {
  if (p == q) return;
  if (from == to) {
    g(i, to, p);
    i = to; p = q;
  } else {
    int mid = (from + to) >> 1;
    rec(from, mid, f, g, i, p, f(mid));
    rec(mid+1, to, f, g, i, p, q);
  }
}
template<class F, class G>
void constantIntervals(int from, int to, F f, G g) {
  if (to <= from) return;
  int i = from; auto p = f(i), q = f(to-1);
  rec(from, to-1, f, g, i, p, q);
  g(i, to, q);
}
```

10.2 Misc. algorithms

TernarySearch.h

Description: Find the smallest i in $[a, b]$ that maximizes $f(i)$, assuming that $f(a) < \ldots < f(i) \geq \cdots \geq f(b)$. To reverse which of the sides allows non-strict inequalities, change the < marked with (A) to <=, and reverse the loop at (B). To minimize f, change it to >, also at (B).
Usage: `int ind = ternSearch(0,n-1,[&](int i){return a[i];});`
Time: $\mathcal{O}(\log(b-a))$

<cassert> 9155b4, 11 lines

```
template<class F>
int ternSearch(int a, int b, F f) {
  assert(a <= b);
  while (b - a >= 5) {
    int mid = (a + b) / 2;
    if (f(mid) < f(mid+1)) a = mid; // (A)
    else b = mid+1;
  }
  rep(i,a+1,b+1) if (f(a) < f(i)) a = i; // (B)
  return a;
}
```

LIS.h

Description: Compute indices for the longest increasing subsequence.
Time: $\mathcal{O}(N \log N)$

2932a0, 17 lines

```
template<class I> vi lis(const vector<I>& S) {
  if (S.empty()) return {};
  vi prev(sz(S));
  typedef pair<I, int> p;
  vector<p> res;
  rep(i,0,sz(S)) {
    // change 0 -> i for longest non-decreasing subsequence
    auto it = lower_bound(all(res), p{S[i], 0});
    if (it == res.end()) res.emplace_back(), it = res.end()-1;
    *it = {S[i], i};
    prev[i] = it == res.begin() ? 0 : (it-1)->second;
  }
  int L = sz(res), cur = res.back().second;
  vi ans(L);
  while (L--) ans[L] = cur, cur = prev[cur];
  return ans;
}
```

FastKnapsack.h

Description: Given N non-negative integer weights w and a non-negative target t, computes the maximum S <= t such that S is the sum of some subset of the weights.
Time: $\mathcal{O}(N \max(w_i))$

b20ccc, 16 lines

```
int knapsack(vi w, int t) {
  int a = 0, b = 0, x;
  while (b < sz(w) && a + w[b] <= t) a += w[b++];
  if (b == sz(w)) return a;
  int m = *max_element(all(w));
  vi u, v(2*m, -1);
  v[a+m-t] = b;
  rep(i,b,sz(w)) {
    u = v;
    rep(x,0,m) v[x+w[i]] = max(v[x+w[i]], u[x]);
    for (x = 2*m; --x > m;) rep(j, max(0,u[x]), v[x])
      v[x-w[j]] = max(v[x-w[j]], j);
  }
  for (a = t; v[a+m-t] < 0; a--) ;
  return a;
}
```

10.3 Dynamic programming

KnuthDP.h

Description: When doing DP on intervals: $a[i][j] = \min_{i<k<j}(a[i][k] + a[k][j]) + f(i,j)$, where the (minimal) optimal k increases with both i and j, one can solve intervals in increasing order of length, and search $k = p[i][j]$ for $a[i][j]$ only between $p[i][j-1]$ and $p[i+1][j]$. This is known as Knuth DP. Sufficient criteria for this are if $f(b,c) \leq f(a,d)$ and $f(a,c) + f(b,d) \leq f(a,d) + f(b,c)$ for all $a \leq b \leq c \leq d$. Consider also: LineContainer (ch. Data structures), monotone queues, ternary search.
Time: $\mathcal{O}(N^2)$

DivideAndConquerDP.h

Description: Given $a[i] = \min_{lo(i)\leq k<hi(i)}(f(i,k))$ where the (minimal) optimal k increases with i, computes $a[i]$ for $i = L..R-1$.
Time: $\mathcal{O}((N + (hi - lo))\log N)$

d38d2b, 18 lines

```
struct DP { // Modify at will:
  int lo(int ind) { return 0; }
  int hi(int ind) { return ind; }
  ll f(int ind, int k) { return dp[ind][k]; }
  void store(int ind, int k, ll v) { res[ind] = pii(k, v); }

  void rec(int L, int R, int LO, int HI) {
    if (L >= R) return;
    int mid = (L + R) >> 1;
    pair<ll, int> best(LLONG_MAX, LO);
    rep(k, max(LO,lo(mid)), min(HI,hi(mid)))
      best = min(best, make_pair(f(mid, k), k));
    store(mid, best.second, best.first);
    rec(L, mid, LO, best.second+1);
    rec(mid+1, R, best.second, HI);
  }
  void solve(int L, int R) { rec(L, R, INT_MIN, INT_MAX); }
};
```

DigitDP.h

Description: Digit DP template to count numbers in range [0, N] satisfying certain conditions. For range [L, R], compute solve(R) - solve(L - 1).
Time: $\mathcal{O}(D * S * 10)$. D is number of digits, S is state size.

cb5eda, 38 lines

```
struct DigitDP {
  int memo[20][200]; // Change base on problem
  vi dig;
  int dfs(int pos, int st, bool tight, bool lz) {
    if (pos == sz(dig)) {
      return (st == 0); // Base case
    }
    if (!tight && !lz && memo[pos][st] != -1) {
      return memo[pos][st];
    }
    int lim = tight ? dig[pos] : 9;
    int res = 0;
    for (int d = 0; d <= lim; ++d) {
      bool nlz = lz && (d == 0);
      int nst = transition(st, d, nlz); // Change status function
      res += dfs(pos + 1, nst, tight && (d == lim), nlz);
    }
    if (!tight && !lz) {
      memo[pos][st] = res;
    }
    return res;
  }
  int transition(int st, int d, bool nlz) {
    // Customize the state transition formula according to the problem.
    // For example: calculate the digit sum, count occurrences of a specific digit, etc.
    if (nlz) return st; // If still processing leading zeros, keep the state unchanged.
    return st + d;
  }
  int solve(long long n) {
    if (n < 0) return 0;
    if (n == 0) return 1; // Adjust depending on whether zero should be counted as valid.
    dig.clear();
    for (; n > 0; n /= 10) dig.push_back(n % 10);
    reverse(all(dig));
    memset(memo, -1, sizeof(memo));
    return dfs(0, 0, true, true);
  }
};
```

10.4 Debugging tricks

- `signal(SIGSEGV, [](int) { _Exit(0); });` converts segfaults into Wrong Answers. Similarly one can catch SIGABRT (assertion failures) and SIGFPE (zero divisions). `_GLIBCXX_DEBUG` failures generate SIGABRT (or SIGSEGV on gcc 5.4.0 apparently).
- `feenableexcept(29);` kills the program on NaNs (1), 0-divs (4), infinities (8) and denormals (16).

10.5 Optimization tricks

`__builtin_ia32_ldmxcsr(40896);` disables denormals (which make floats 20x slower near their minimum value).

10.5.1 Bit hacks

- `x & -x` is the least bit in x.
- `for (int x = m; x; ) { --x &= m; ... }` loops over all subset masks of `m` (except `m` itself).
- `c = x&-x, r = x+c; (((r^x) >> 2)/c) | r` is the next number after x with the same number of bits set.
- `rep(b,0,K) rep(i,0,(1 << K)) if (i & 1 << b) D[i] += D[i^(1 << b)];` computes all sums of subsets.

10.5.2 Pragmas

- `#pragma GCC optimize ("Ofast")` will make GCC auto-vectorize loops and optimizes floating points better.
- `#pragma GCC target ("avx2")` can double performance of vectorized code, but causes crashes on old machines.
- `#pragma GCC optimize ("trapv")` kills the program on integer overflows (but is really slow).

FastMod.h

Description: Compute $a\%b$ about 5 times faster than usual, where b is constant but not known at compile time. Returns a value congruent to a (mod b) in the range $[0, 2b)$.

751a02, 8 lines

```
typedef unsigned long long ull;
struct FastMod {
  ull b, m;
  FastMod(ull b) : b(b), m(-1ULL / b) {}
  ull reduce(ull a) { // a % b + (0 or b)
    return a - (ull)((__uint128_t(m) * a) >> 64) * b;
  }
};
```

FastInput.h

Description: Read an integer from stdin. Usage requires your program to pipe in input from file.
Usage: `./a.out < input.txt`
Time: About 5x as fast as cin/scanf.

7b3c70, 17 lines

```
inline char gc() { // like getchar()
  static char buf[1 << 16];
  static size_t bc, be;
  if (bc >= be) {
    buf[0] = 0, bc = 0;
    be = fread(buf, 1, sizeof(buf), stdin);
  }
  return buf[bc++]; // returns 0 on EOF
}

int readInt() {
  int a, c;
  while ((a = gc()) < 40);
  if (a == '-') return -readInt();
  while ((c = gc()) >= 48) a = a * 10 + c - 480;
  return a - 48;
}
```

BumpAllocator.h

Description: When you need to dynamically allocate many objects and don't care about freeing them. "new X" otherwise has an overhead of something like 0.05us + 16 bytes per allocation.

<cassert> 745db2, 8 lines

```
// Either globally or in a single class:
static char buf[450 << 20];
void* operator new(size_t s) {
  static size_t i = sizeof buf;
  assert(s < i);
  return (void*)&buf[i -= s];
}
void operator delete(void*) {}
```

SmallPtr.h

Description: A 32-bit pointer that points into BumpAllocator memory.

"BumpAllocator.h" 2dd6c9, 10 lines

```
template<class T> struct ptr {
  unsigned ind;
  ptr(T* p = 0) : ind(p ? unsigned((char*)p - buf) : 0) {
    assert(ind < sizeof buf);
  }
  T& operator*() const { return *(T*)(buf + ind); }
  T* operator->() const { return &**this; }
  T& operator[](int a) const { return (&**this)[a]; }
  explicit operator bool() const { return ind; }
};
```

BumpAllocatorSTL.h

Description: BumpAllocator for STL containers.
Usage: `vector<vector<int, small<int>>> ed(N);`

bb66d4, 14 lines

```
char buf[450 << 20] alignas(16);
size_t buf_ind = sizeof buf;

template<class T> struct small {
  typedef T value_type;
  small() {}
  template<class U> small(const U&) {}
  T* allocate(size_t n) {
    buf_ind -= n * sizeof(T);
    buf_ind &= 0 - alignof(T);
    return (T*)(buf + buf_ind);
  }
  void deallocate(T*, size_t) {}
};
```

SIMD.h

Description: Cheat sheet of SSE/AVX intrinsics, for doing arithmetic on several numbers at once. Can provide a constant factor improvement of about 4, orthogonal to loop unrolling. Operations follow the pattern "_mm(256)?_name_(si(128|256)|epi(8|16|32|64)|pd|ps)". Not all are described here; grep for _mm_ in /usr/lib/gcc/*/4.9/include/ for more. If AVX is unsupported, try 128-bit operations, "emmintrin.h" and #define __SSE__ and __MMX__ before including it. For aligned memory use _mm_malloc(size, 32) or int buf[N] alignas(32), but prefer loadu/storeu.

c9ac08, 43 lines

```
#pragma GCC target ("avx2") // or sse4.1
#include "immintrin.h"

typedef __m256i mi;
#define L(x) _mm256_loadu_si256((mi*)&(x))

// High-level/specific methods:
// load(u)?_si256, store(u)?_si256, setzero_si256, _mm_malloc
// blendv_(epi8|ps|pd) (z?y:x), movemask_epi8 (hibits of bytes)
// i32gather_epi32(addr, x, 4): map addr[] over 32-b parts of x
// sad_epu8: sum of absolute differences of u8, outputs 4xi64
// maddubs_epi16: dot product of unsigned i7's, outputs 16xi15
// madd_epi16: dot product of signed i16's, outputs 8xi32
// extractf128_si256(, i) (256->128), cvtsi128_si32 (128->lo32)
// permute2f128_si256(x,x,1) swaps 128-bit lanes
// shuffle_epi32(x, 3*64+2*16+1*4+0) == x for each lane
// shuffle_epi8(x, y) takes a vector instead of an imm

// Methods that work with most data types (append e.g. _epi32):
// set1, blend (i8?x:y), add, adds (sat.), mullo, sub, and/or,
// andnot, abs, min, max, sign(1,x), cmp(gt|eq), unpack(lo|hi)

int sumi32(mi m) { union {int v[8]; mi m;} u; u.m = m;
  int ret = 0; rep(i,0,8) ret += u.v[i]; return ret; }
mi zero() { return _mm256_setzero_si256(); }
mi one() { return _mm256_set1_epi32(-1); }
bool all_zero(mi m) { return _mm256_testz_si256(m, m); }
bool all_one(mi m) { return _mm256_testc_si256(m, one()); }

ll example_filteredDotProduct(int n, short* a, short* b) {
  int i = 0; ll r = 0;
  mi zero = _mm256_setzero_si256(), acc = zero;
  while (i + 16 <= n) {
    mi va = L(a[i]), vb = L(b[i]); i += 16;
    va = _mm256_and_si256(_mm256_cmpgt_epi16(vb, va), va);
    mi vp = _mm256_madd_epi16(va, vb);
    acc = _mm256_add_epi64(_mm256_unpacklo_epi32(vp, zero),
      _mm256_add_epi64(acc, _mm256_unpackhi_epi32(vp, zero)));
  }
  union {ll v[4]; mi m;} u; u.m = acc; rep(i,0,4) r += u.v[i];
  for (;i<n;++i) if (a[i] < b[i]) r += a[i]*b[i]; // <- equiv
  return r;
}
```

Techniques (A)

techniques.txt 159 lines

```
Recursion
Divide and conquer
  Finding interesting points in N log N
Algorithm analysis
  Master theorem
  Amortized time complexity
Greedy algorithm
  Scheduling
  Max contiguous subvector sum
  Invariants
  Huffman encoding
Graph theory
  Dynamic graphs (extra book-keeping)
  Breadth first search
  Depth first search
  * Normal trees / DFS trees
  Dijkstra's algorithm
  MST: Prim's algorithm
  Bellman-Ford
  Konig's theorem and vertex cover
  Min-cost max flow
  Lovasz toggle
  Matrix tree theorem
  Maximal matching, general graphs
  Hopcroft-Karp
  Hall's marriage theorem
  Graphical sequences
  Floyd-Warshall
  Euler cycles
  Flow networks
  * Augmenting paths
  * Edmonds-Karp
  Bipartite matching
  Min. path cover
  Topological sorting
  Strongly connected components
  2-SAT
  Cut vertices, cut-edges and biconnected components
  Edge coloring
  * Trees
  Vertex coloring
  * Bipartite graphs (=> trees)
  * 3^n (special case of set cover)
  Diameter and centroid
  K'th shortest path
  Shortest cycle
Dynamic programming
  Knapsack
  Coin change
  Longest common subsequence
  Longest increasing subsequence
  Number of paths in a dag
  Shortest path in a dag
  Dynprog over intervals
  Dynprog over subsets
  Dynprog over probabilities
  Dynprog over trees
  3^n set cover
  Divide and conquer
  Knuth optimization
  Convex hull optimizations
  RMQ (sparse table a.k.a 2^k-jumps)
  Bitonic cycle
  Log partitioning (loop over most restricted)
Combinatorics
  Computation of binomial coefficients
  Pigeon-hole principle
  Inclusion/exclusion
  Catalan number
  Pick's theorem
Number theory
  Integer parts
  Divisibility
  Euclidean algorithm
  Modular arithmetic
  * Modular multiplication
  * Modular inverses
  * Modular exponentiation by squaring
  Chinese remainder theorem
  Fermat's little theorem
  Euler's theorem
  Phi function
  Frobenius number
  Quadratic reciprocity
  Pollard-Rho
  Miller-Rabin
  Hensel lifting
  Vieta root jumping
Game theory
  Combinatorial games
  Game trees
  Mini-max
  Nim
  Games on graphs
  Games on graphs with loops
  Grundy numbers
  Bipartite games without repetition
  General games without repetition
  Alpha-beta pruning
Probability theory
Optimization
  Binary search
  Ternary search
  Unimodality and convex functions
  Binary search on derivative
Numerical methods
  Numeric integration
  Newton's method
  Root-finding with binary/ternary search
  Golden section search
Matrices
  Gaussian elimination
  Exponentiation by squaring
Sorting
  Radix sort
Geometry
  Coordinates and vectors
  * Cross product
  * Scalar product
  Convex hull
  Polygon cut
  Closest pair
  Coordinate-compression
  Quadtrees
  KD-trees
  All segment-segment intersection
Sweeping
  Discretization (convert to events and sweep)
  Angle sweeping
  Line sweeping
  Discrete second derivatives
Strings
  Longest common substring
  Palindrome subsequences
  Knuth-Morris-Pratt
  Tries
  Rolling polynomial hashes
  Suffix array
  Suffix tree
  Aho-Corasick
  Manacher's algorithm
  Letter position lists
Combinatorial search
  Meet in the middle
  Brute-force with pruning
  Best-first (A*)
  Bidirectional search
  Iterative deepening DFS / A*
Data structures
  LCA (2^k-jumps in trees in general)
  Pull/push-technique on trees
  Heavy-light decomposition
  Centroid decomposition
  Lazy propagation
  Self-balancing trees
  Convex hull trick (wcipeg.com/wiki/Convex_hull_trick)
  Monotone queues / monotone stacks / sliding queues
  Sliding queue using 2 stacks
  Persistent segment tree
```