

Onek Mojar Contest

Team forming contest 5 - 2013 batch

1:50:27

5:00:00

Overview Problem Status Rank (93711)

A B C D E F G H I J

J - Eternal Victory

Time Limit:2000MS Memory Limit:262144KB 64bit IO Format:%I64d & %I64u

Submit

Status

Description

Valerian was captured by Shapur. The victory was such a great one that Shapur decided to carve a scene of Valerian's defeat on a mountain. So he had to find the best place to make his victory eternal!

He decided to visit all n cities of Persia to find the best available mountain, but after the recent war he was too tired and didn't want to traverse a lot. So he wanted to visit each of these n cities at least once with smallest possible traverse. Persian cities are connected with bidirectional roads. You can go from any city to any other one using these roads and there is a unique path between each two cities.

All cities are numbered 1 to n . Shapur is currently in the city 1 and he wants to visit all other cities with minimum possible traverse. He can finish his travels in any city.

Help Shapur find how much He should travel.

Input

First line contains a single natural number n ($1 \leq n \leq 10^5$) — the amount of cities.

Next $n - 1$ lines contain 3 integer numbers each x_i, y_i and w_i ($1 \leq x_i, y_i \leq n, 0 \leq w_i \leq 2 \times 10^4$). x_i and y_i are two ends of a road and w_i is the length of that road.

Output

A single integer number, the minimal length of Shapur's travel.

Please, do not use %lld specifier to read or write 64-bit integers in C++. It is preferred to use cout (also you may use %I64d).

Sample Input

Input

```
3
1 2 3
2 3 4
```

Output

7

Input

3

1 2 3

1 3 3

Output

9

[FAQ](#) | [About Virtual Judge](#) | [Forum](#) | [Discuss](#) | [Open Source Project](#)All Copyright Reserved ©2010-2014 [HUST ACM/ICPC TEAM](#)Anything about the OJ, please ask in the [forum](#), or contact author: [lsun](#), but NEVER contact [freefew@gmail.com](#), who is irrelevant to this site !!

Server Time: 2016-05-23 16:05:26