




NGN 2023 Conference

Evaluating U-Nets for Skull Stripping of Augmented T1-weighted MRI Scans

Anway Pimpalkar¹ **Dr. Rashmika Patole**¹ **Dr. Ketaki Kamble**² **Dr. Mahesh Shindikar**²

COEP Technological University, Pune IN

¹*Department of Electronics and Telecommunication*, ²*Department of Applied Sciences*





Neuroimaging Techniques

Computed
Tomography

Diffusion Tensor
Imaging

Magnetic
Resonance
Spectroscopy

Magnetization
Transfer
Imaging

Cerebral Perfusion
Imaging

Single Photon Emission
Computed Tomography

Magnetic
Resonance
Imaging

Positron Emission
Tomography

Electroencephalogram

Ultrasound
Imaging

Functional
Near-Infrared
Spectroscopy



Neuroimaging Techniques

Computed
Tomography

Diffusion Tensor
Imaging

Magnetic
Resonance
Spectroscopy

Magnetization
Transfer
Imaging

Cerebral Perfusion
Imaging

Single Photon Emission
Computed Tomography

**Magnetic
Resonance
Imaging**

Positron Emission
Tomography

Electroencephalogram

Ultrasound
Imaging

Functional
Near-Infrared
Spectroscopy

MRIs and Skull Stripping

- Information of both **brain and non-brain tissues**.
- **Only brain tissue required** for most studies of neuroanatomy, neurophysiology, and internal functions such as cognition and control.




Fig 1. Adapted from the work by Lee et al. (2011).

MRIs and Skull Stripping

- Information of both **brain and non-brain tissues**.
- **Only brain tissue required** for most studies of neuroanatomy, neurophysiology, and internal functions such as cognition and control.




Fig 1. Adapted from the work by Lee et al. (2011).

MRIs and Skull Stripping

- Information of both **brain and non-brain tissues**.
- Only **brain** tissue required for most studies of neuroanatomy, neurophysiology, and internal functions such as cognition and control.
- **Skull Stripping** is the separation of brain tissue, including grey and white matter from non-brain voxels such as the skull, scalp, and dura mater.





Fig 1. Adapted from the work by Lee et al. (2011).




Conventional Skull Stripping Methods






Conventional Skull Stripping Methods






Conventional Skull Stripping Methods



Conventional Skull Stripping Methods




Disadvantages:

- Require many user-dependent parameters.
- Susceptible to multi-scanner variability.



Advances in Skull Stripping



Advances in Skull Stripping



- Fuzzy Active Surface Model
- ROBEX

Deep Learning Based

- 3D-CNN
- VoxResNet
- U-Nets

- **U-Net architectures** are encoder-decoder networks for semantic segmentation.




Fig 2. U-Net architecture representation.
(Ronneberger et al., 2015)

Advances in Skull Stripping

- U-Net architectures are encoder-decoder networks for semantic segmentation.




Fig 2. U-Net architecture representation.
(Ronneberger et al., 2015)

Project Objective

- To evaluate the performance of three flavors of 2D U-Net architectures for Skull Stripping:
 - Vanilla
 - Residual
 - Dense
- Robustness to multi-scanner variance.

U-Net Architectures

- Encoder-decoder
- Two paths:
 - **Contractive:** Downsampling image to feature representation.
 - **Expansive:** Upsampling representation to segmentation map.
- 2D or 3D convolutions
- Skip connections




Fig 2. U-Net architecture representation.
(Ronneberger et al., 2015)




Fig 3. U-Net input and output.

U-Net Architectures

- Encoder-decoder
- Two paths:
 - **Contractive:** Downsampling image to feature representation.
 - **Expansive:** Upsampling representation to segmentation map.
- 2D or 3D convolutions
- Skip connections
- Based on connection density, we divide them into:
 - Vanilla U-Net
 - Residual U-Net
 - Dense U-Net




Fig 2. U-Net architecture representation.
(Ronneberger et al., 2015)





Fig 3. U-Net input and output.

U-Net Architectures for Skull Stripping



U-Net Architectures for Skull Stripping





Fig. 5


U-Net Architectures for Skull Stripping




Dense 2D U-Net Architecture

Fig. 6

U-Net Architectures for Skull Stripping




Training Methodology



- Source: NFBS Repository
- Manually Skull Stripped assisted by BEaST
- Total 125 scans, 110 used for training, 15 for test

Training Methodology




→ **Pre-processing**

- Intensity z - normalization


$$I_{z-norm}(x) = \frac{I(x) - \mu_{brain}}{\sigma_{brain}}$$

- Source: NFBS Repository
- Manually Skull Stripped assisted by BEaST
- Total 125 scans, 110 used for training, 15 for test


Training Methodology




- Source: NFBS Repository
- Manually Skull Stripped assisted by BEaST
- Total 125 scans, 110 used for training, 15 for test




Training Methodology




- Source: NFBS Repository
- Manually Skull Stripped assisted by BEaST
- Total 125 scans, 110 used for training, 15 for test



Skull Stripping using U-Nets



Skull Stripping using U-Nets




Implementation:


- Train/Validation split: 90/10 (Repeated Holdout).
- EarlyStopping callback to prevent overfitting.
- TensorFlow in Python.
- NVIDIA A100 Tensor Core GPU (40GB) Hardware Accelerator.

Results


- **Loss Function:** Binary Cross Entropy Loss Function
- **Metric:** Accuracy



(a) Vanilla U-Net



(b) Residual U-Net



(c) Dense U-Net

Fig 7. Training results.

Results

- **Loss Function:** Binary Cross Entropy Loss Function
- **Metric:** Accuracy

Table 2. 2D U-Net architecture training results.

| Architecture | Epochs | Batch Size | Training | | Validation | | Testing | |
|--------------|--------|------------|----------|----------|------------|----------|---------|----------|
| | | | Loss | Accuracy | Loss | Accuracy | Loss | Accuracy |
| Vanilla | 10 | 32 | 0.0066 | 99.72% | 0.0093 | 99.63% | 0.0065 | 99.73% |
| Residual | 9 | 32 | 0.0066 | 99.72% | 0.0092 | 99.63% | 0.0067 | 99.72% |
| Dense | 9 | 16 | 0.0053 | 99.77% | 0.0085 | 99.67% | 0.0062 | 99.75% |




Fig 8. (a) A sagittal 3D T1-w MRI slice from the NFBS repository and (b) corresponding Skull Stripped mask superimposed on the MRI scan.

Results

- **Loss Function:** Binary Cross Entropy Loss Function
- **Metric:** Accuracy

Table 2. 2D U-Net architecture training results.

| Architecture | Epochs | Batch Size | Training | | Validation | | Testing | |
|--------------|--------|------------|----------|----------|------------|----------|---------|----------|
| | | | Loss | Accuracy | Loss | Accuracy | Loss | Accuracy |
| Vanilla | 10 | 32 | 0.0066 | 99.72% | 0.0093 | 99.63% | 0.0065 | 99.73% |
| Residual | 9 | 32 | 0.0066 | 99.72% | 0.0092 | 99.63% | 0.0067 | 99.72% |
| Dense | 9 | 16 | 0.0053 | 99.77% | 0.0085 | 99.67% | 0.0062 | 99.75% |




Fig 8. (a) A sagittal 3D T1-w MRI slice from the NFBS repository and (b) corresponding Skull Stripped mask superimposed on the MRI scan.

Conclusion and Ongoing Work

- Dense 2D U-Net Architectures:
 - Better performance with same network depth.
 - Strengthen shallower models.
- Almost same output accuracies for all, need to dive deeper.
- Current work:
 - Test multi-variate scanning.
 - Expand number of architectures.




Fig 8. (a) A sagittal 3D T1-w MRI slice from the NFBS repository and (b) corresponding Skull Stripped mask superimposed on the MRI scan.



Acknowledgements

Dr. Rashmika Patole, Dr. Ketaki Kamble, and Dr. Mahesh Shindikar

Supervisors



Center of Excellence in Signal and Image Processing

Department of Electronics and Telecommunication
COEP Technological University

Reach out!

pimpalkaras19.extc@coep.ac.in