



5320 İS7ANBUL Sedef

Description

Acrylic emulsion based decorative interior paint with pearl effect.

Fields of Application

- On interiors suitably prepared new mineral surfaces such as mortar, concrete, cement panel, gypsum panel etc, on old painted surfaces, glass textile, putty and wall paper to create a decorative effect and on wood and metal surfaces for hobby purposes.

Properties

- Easily cleanable with its scrub resistance.
- High water vapour permeability.
- Pearl effect.
- Provides the possibility to create infinite number of patterns with respect to the used application tool, method and the imagination of the user.
- Solvent free and practically odourless.
- Water thinnable and ecologically compatible.

Application

- After brushing the loosely stuck flakes away, VİTRAY LAK should be applied, on VİTRAY FON and flake applied surfaces.
- The substrate must be cleaned from dust, dirt, oil and old blistered coatings that may prevent good adhesion. The surface should be made sound, clean and dry. New cementitious substrates must be cured at least 28 days before application.
- If necessary, fill the surface cracks and even the substrate with Kale İNCE AKRİLİK MACUN or Kale MACUNART.
- To have a fine, smooth texture, smoothen the entire surface by using Kale İNCE AKRİLİK MACUN or Kale MACUNART.
- Prime old painted, very dirty surfaces with Kale SİLASTER, new and porous surfaces with Kale ÜNİASTER or Kale MACUNART.
- Apply KALİA MAT, KALİA İPEK MAT or İS7ANBUL Sedef in 2 coats after the primer application.
- Apply İS7ANBUL Sedef by one of the following methods after the paint application:

- a) İS7ANBUL Sedef should be applied with roller or brush and desired patterns are created with decorative application tools before it dries.
 - b) Desired patterns are formed on the surface by padding İS7ANBUL Sedef with a sponge, paper or piece of cloth.
- Clean the tools with water.
 - Ensure that the air and surface temperatures are above +5 °C during the application and 24 hours following the application.

Storage

- Store between 5 – 35 °C.

Packaging

- 1, 2.5 and 15 kg pails.
- 1 kg and 2.5 kg packages packed together in 2s.



5320 İS7ANBUL Sedef

Technical Properties

(at 23°C and 50% RH)

General Data

Composition	Acrylic emulsion based
Thinner	Water
Density	Approx. 1.06 g/cm ³
Colours	9 colours in İS7ANBUL Efekt Colour Chart. Tintable by Renk Ustası

Application Data

Application Temperature Range	(+5°C) - (+35°C)
Drying Time	Tack-free time: 30 minutes. Thoroughly dry: After 24 hours. (Lower temperatures and/or higher relative humidity will lengthen the drying process.)
Consumption	Depending on the evenness and the porosity of the surface approx. 0.06 – 0.16 kg/m ² per coat.
Application Tools	Brush, Roller, Airless spraying equipment, decorative application tools (sponge, spatula, etc.)