

SEP Project Coding Standards

CodeCatalyst UG33
Team Documentation

Version 1.0

September 6, 2025

Contents

1	Quick Reference	2
1.1	Pre-Commit Quality Checks	2
1.2	Code Quality Commands	2
1.3	Naming Quick Reference	2
2	Code Formatting Standards	3
2.1	clang-format (Mandatory)	3
2.2	Style Configuration	3
2.2.1	Project Style Rules	3
2.2.2	Example Code Formatting	4
2.3	Formatting Commands	4
2.4	IDE Integration	5
3	Naming Conventions	6
3.1	Detailed Naming Rules	6
3.2	Naming Examples	7
3.2.1	Good Naming Examples	7
3.2.2	Poor Naming Examples	8
4	C++ Coding Standards	9
4.1	Language Standards	9
4.2	Namespace Usage	9
4.2.1	Namespace Examples	10
4.3	Header Management	11
4.4	Modern C++ Features	11
5	Static Analysis	12
5.1	clang-tidy Configuration	12
5.2	Enabled Check Categories	12
5.3	Running Static Analysis	13
5.4	Common Issues and Fixes	13
5.4.1	Readability Issues	13
5.4.2	Performance Issues	14
6	Testing Standards	15
6.1	Test Architecture	15
6.2	Test Implementation Standards	16
6.2.1	Unit Test Guidelines	16
6.2.2	Integration Test Guidelines	17
6.3	Test Execution	17
6.4	Test Data Management	18
7	CI/CD Quality Gates	19
7.1	Pipeline Overview	19
7.2	Quality Requirements	19
7.3	Local Quality Verification	20
8	Best Practices Summary	21
8.1	Daily Development Checklist	21
8.2	Code Review Guidelines	21
9	Related Documentation	21

1 Quick Reference

Essential commands and standards for immediate productivity.

1.1 Pre-Commit Quality Checks

Mandatory Before Every Commit

Required quality checks:

Format code: `./scripts/format-code.sh`

All tests pass: `make test-all`

Cross-platform build: `make windows-package`

Clean build: `make clean && make test-all`

1.2 Code Quality Commands

Essential Quality Commands

```
# Format all source files (mandatory)
./scripts/format-code.sh

# Build and test everything
make test-all

# Format specific file
clang-format -i src/block.cpp

# Check formatting compliance
clang-format --dry-run --Werror src/block.cpp

# Generate compile commands for IDE
make compile-commands

# Cross-platform build verification
make windows-package
```

1.3 Naming Quick Reference

Element	Style	Example
Classes/Structs	CamelCase	BlockModel
Functions	snake_case	read_specification()
Variables	snake_case	x_count
Constants	UPPER_CASE	MAX_DEPTH
Private members	Suffix _	data_

Table 1: Naming Convention Quick Reference

2 Code Formatting Standards

Automatic code formatting requirements and configuration.

2.1 clang-format (Mandatory)

Mandatory Formatting Requirement

All code must be formatted with clang-format before submission.

This is enforced by:

- CI/CD pipeline checks
- Code review requirements
- Pre-commit hooks (when configured)

- Team development standards

Non-compliance will result in:

- Failed CI/CD builds
- Rejected pull requests
- Request for reformatting

2.2 Style Configuration

2.2.1 Project Style Rules

Formatting Configuration (Google-based with modifications)

Key formatting rules:

- **Line length:** 100 characters maximum
- **Indentation:** 4 spaces (no tabs)
- **Braces:** Attached style (`{` on same line)
- **Pointer/Reference:** Left-aligned (`int* ptr, int& ref`)
- **Access modifiers:** Indented -2 spaces from class level

Spacing rules:

- No spaces inside parentheses: `function(arg)` not `function(arg)`
- Spaces around binary operators: `a + b` not `a+b`
- Space after control statements: `if (condition)` not `if(condition)`
- Two spaces before trailing comments

2.2.2 Example Code Formatting

Properly Formatted C++ Code

```
class BlockModel {
public:
    void read_specification();
    int get_block_count() const;

    // Constructor with member initialization list
    BlockModel(int x_count, int y_count, int z_count)
        : x_count_(x_count), y_count_(y_count), z_count_(z_count) {}

private:
    int x_count_;
    int y_count_;
    int z_count_;
    std::vector<Block> blocks_;

    void process_internal_data();
};

// Function implementation with proper spacing
void BlockModel::read_specification() {
    std::string line;
    if (std::getline(std::cin, line)) {
        std::vector<int> values = split_csv_ints(line);
        if (values.size() >= 6) {
            x_count_ = values[0];
            y_count_ = values[1];
            z_count_ = values[2];
        }
    }
}
```

2.3 Formatting Commands

clang-format Usage

```
# Format all source files (recommended before commit)
cmake --build build --target format

# Format specific file
clang-format -i src/block.cpp
clang-format -i include/block.h

# Format all files manually
find src/ include/ tests/ -name "*.cpp" -o -name "*.h" | \
    xargs clang-format -i

# Check formatting without modifying files
clang-format --dry-run --Werror src/block.cpp

# Show formatting differences
clang-format --dry-run src/block.cpp | diff src/block.cpp -
```

2.4 IDE Integration

Automatic Formatting Setup

Visual Studio Code:

- Install C/C++ Extension Pack
- Enable "Format on Save" in settings
- Configure to use project `.clang-format` file
- Keyboard shortcut: Shift+Alt+F

CLion:

- Import `.clang-format` in Code Style settings
- Enable "Reformat code" on commit
- Keyboard shortcut: Ctrl+Alt+L

Vim/Neovim:

- Use vim-clang-format plugin
- Map to key binding: `nnoremap <Leader>f :ClangFormat<CR>`
- Auto-format on save with autocmd

3 Naming Conventions

Comprehensive naming standards for consistent code readability.

3.1 Detailed Naming Rules

Element	Style	Example	Notes
Classes	CamelCase	BlockModel, Vec3	
Structs	CamelCase	Point3D, BlockData	
Functions	snake_case	read_specification(), get_count()	
Methods	snake_case	calculate_volume(), is_valid()	
Variables	snake_case	x_count, block_size	
Parameters	snake_case	input_file, max_depth	
Local variables	snake_case	temp_value, i, j	
Member variables	snake_case_	x_count_, blocks_	Suffix
Constants	UPPER_CASE	MAX_DEPTH, DEFAULT_SIZE	
Enums	CamelCase	BlockType, ErrorCode	
Enum values	UPPER_CASE	SOLID_BLOCK, SUCCESS	
Namespaces	snake_case	block_utils, math	
Files	snake_case	block_model.cpp, utils.h	
Macros	UPPER_CASE	DEBUG_PRINT, ASSERT	Avoid

Table 2: Complete Naming Convention Reference

3.2 Naming Examples

3.2.1 Good Naming Examples

Proper Naming Practices

```
// Class and member naming
class BlockModel {
public:
    void read_specification();
    bool is_valid_block(const Block& block) const;
    std::size_t get_block_count() const { return blocks_.size(); }

private:
    int x_count_;           // Member variable with underscore
    int y_count_;
    std::vector<Block> blocks_; // Container with clear name
    std::unordered_map<char, std::string> tag_table_;
};

// Function and variable naming
void process_model_data(const std::string& input_file) {
    int total_blocks = 0;           // Local variable
    bool processing_complete = false;

    for (const auto& current_block : blocks_) {
        if (current_block.is_valid()) {
            total_blocks++;
        }
    }
}

// Constants and enums
const int MAX_MODEL_DIMENSION = 1024;
const double COMPRESSION_THRESHOLD = 0.85;

enum class BlockType {
    SOLID_BLOCK,
    EMPTY_SPACE,
    BOUNDARY_MARKER
};
```


3.2.2 Poor Naming Examples

Naming Practices to Avoid

```
// Poor naming examples - DO NOT USE
class bm {                                // Unclear abbreviation
public:
    void rd();                            // Meaningless function name
    int gc() const;                       // Unclear abbreviation

private:
    int x, y, z;                          // Too generic
    std::vector<Block> b;                  // Single character name
    std::map<char, std::string> tt;        // Unclear abbreviation
};

// Poor variable naming
void func(std::string f) {                // Unclear parameter name
    int n = 0;                            // Meaningless variable name
    bool flag = false;                   // Generic flag name

    for (auto& item : collection) {      // 'item' is too generic
        if (item.flag2) {                 // Numbered variables indicate poor
            design
            n++;
        }
    }
}

// Poor constants
#define MAX 1000                          // Too generic
const int X = 50;                         // Meaningless name
```

4 C++ Coding Standards

Best practices for modern C++ development.

4.1 Language Standards

C++ Standard Requirements

Project uses C++17 standard:

- Compiler flag: `-std=c++17`
- Modern C++ features encouraged
- Standard library preferred over custom implementations
- Performance and safety focus

Compiler support:

- GCC 7.0+ (primary Linux compiler)
- Clang 7.0+ (alternative compiler)
- MSVC 2019+ (Windows compiler)
- MinGW-w64 (cross-compilation)

4.2 Namespace Usage

Namespace Rules (Strictly Enforced)

Prohibited practices:

- `using namespace std;` – Never use in any file
- `using namespace` directives in headers
- Importing entire namespaces globally

Required practices:

- Always use explicit `std::` prefixes
- Individual using declarations acceptable in limited scope
- Namespace aliases for long namespace names

4.2.1 Namespace Examples

Proper Namespace Usage

```
// Good: Explicit std:: prefixes
#include <iostream>
#include <vector>
#include <string>

void process_data() {
    std::vector<int> numbers;
    std::string input_line;
    std::cout << "Processing data..." << std::endl;

    // Acceptable: Limited scope using declaration
    {
        using std::cout;
        using std::endl;
        cout << "Temporary scope usage" << endl;
    }
}

// Good: Namespace alias for long names
namespace bg = boost::geometry;
bg::point<double, 2> create_point(double x, double y);
```

Prohibited Namespace Usage

```
// BAD: Never use global using namespace
using namespace std;

// BAD: Don't import namespaces in headers
// In header file:
using namespace std;           // Affects all files that include this header

// BAD: Don't use in global scope
using std::vector;             // Pollutes global namespace
using std::string;

void process_data() {
    vector<int> numbers;        // Unclear which vector this is
    string input_line;         // Could be std::string or another string class
}
```

4.3 Header Management

Header Include Practices

Prefer specific includes:

```
// Good: Individual standard library headers
#include <iostream>      // For std::cout, std::cin
#include <vector>         // For std::vector
#include <string>         // For std::string
#include <algorithm>      // For std::sort, std::find
#include <memory>         // For std::unique_ptr, std::shared_ptr

// Good: Project headers with quotes
#include "block.h"
#include "block_model.h"
```

Avoid convenience headers:

```
// BAD: Don't use convenience headers
#include <bits/stdc++.h>  // Non-standard, bloated
#include <iostream.h>     // Deprecated form
```

4.4 Modern C++ Features

Encouraged Modern C++ Practices

C++17 features to use:

```
// Structured bindings (C++17)
auto [x, y, z] = get_coordinates();

// if constexpr (C++17)
template<typename T>
void process(T value) {
    if constexpr (std::is_integral_v<T>) {
        // Handle integer types
    } else {
        // Handle other types
    }
}

// std::optional (C++17)
std::optional<Block> find_block(int id) {
    if (block_exists(id)) {
        return Block{id};
    }
    return std::nullopt;
}

// Range-based for loops (C++11, enhanced in C++17)
for (const auto& block : blocks_) {
    process_block(block);
}

// Auto type deduction
auto result = expensive_computation();
const auto& reference = get_large_object();
```

5 Static Analysis

Automated code quality checking with clang-tidy.

5.1 clang-tidy Configuration

Static Analysis Benefits

clang-tidy provides:

- Bug detection and prevention
- Performance optimization suggestions
- Modern C++ feature recommendations
- Code readability improvements
- Best practice enforcement

Available via tools:

- Manual clang-tidy execution
- CI/CD pipeline integration
- IDE integration available
- Customizable rule sets

5.2 Enabled Check Categories

Check Category	Purpose
clang-diagnostic-*	Compiler diagnostic messages
clang-analyzer-*	Static analysis checks
cppcoreguidelines-*	C++ Core Guidelines compliance
modernize-*	Modern C++ feature suggestions
performance-*	Performance optimization opportunities
readability-*	Code readability improvements
bugprone-*	Bug-prone pattern detection

Table 3: Enabled clang-tidy Check Categories

5.3 Running Static Analysis

clang-tidy Usage

```
# Analyze specific file
clang-tidy src/block.cpp -- -Iinclude

# Run with specific checks only
clang-tidy -checks='readability-*,performance-*' src/block.cpp

# Generate compile commands for accurate analysis
make compile-commands

# Run clang-tidy with compile commands database
clang-tidy -p . src/block.cpp

# Format and check quality together
./scripts/format-code.sh && make test-all
```

5.4 Common Issues and Fixes

5.4.1 Readability Issues

Readability Problems

```
// Issue: Magic numbers
if (blocks.size() > 100) {           // What does 100 represent?
    compress_data();
}

// Issue: Long parameter lists
void process(int x, int y, int z, int w, int h, int d, char tag, bool flag);

// Issue: Unclear variable names
bool flag = true;
int n = calculate();
```

Fixes:

```
// Fix: Named constants
const std::size_t MAX_BLOCKS_BEFORE_COMPRESSION = 100;
if (blocks.size() > MAX_BLOCKS_BEFORE_COMPRESSION) {
    compress_data();
}

// Fix: Structure parameters
struct BlockParameters {
    int x, y, z, width, height, depth;
    char tag;
    bool is_compressed;
};
void process(const BlockParameters& params);

// Fix: Descriptive names
bool is_compression_needed = true;
int total_block_count = calculate();
```

5.4.2 Performance Issues

Performance Problems

```
// Issue: Unnecessary copies
for (std::string item : large_collection) {    // Copies each string
    process(item);
}

// Issue: Repeated expensive operations
for (int i = 0; i < vec.size(); ++i) {        // size() called repeatedly
    if (expensive_function() > threshold) {    // expensive_function()
        called repeatedly
        process(vec[i]);
    }
}
```

Fixes:

```
// Fix: Use const references
for (const std::string& item : large_collection) {
    process(item);
}

// Fix: Cache expensive operations
const auto vec_size = vec.size();
const auto expensive_result = expensive_function();
for (std::size_t i = 0; i < vec_size; ++i) {
    if (expensive_result > threshold) {
        process(vec[i]);
    }
}
```

6 Testing Standards

Comprehensive testing framework and quality assurance.

6.1 Test Architecture

Testing Framework Components

Test types implemented:

- **Unit Tests** – Test individual components in isolation
- **Integration Tests** – Test component interactions end-to-end
- **Validation Tests** – Verify output correctness and reconstruction
- **Cross-Platform Tests** – Ensure compatibility across systems

Test organization:

- Tests in `tests/` directory
- Test data in `tests/data/`
- CTest integration for automation
- CI/CD pipeline integration

6.2 Test Implementation Standards

6.2.1 Unit Test Guidelines

Unit Test Best Practices

```
// Good: Descriptive test function names
void test_block_creation_with_valid_parameters() {
    // Arrange
    const int x = 10, y = 20, z = 30;
    const int width = 5, height = 6, depth = 7;
    const char tag = 'A';

    // Act
    Block block(x, y, z, width, height, depth, tag);

    // Assert
    assert(block.x == x);
    assert(block.y == y);
    assert(block.z == z);
    assert(block.width == width);
    assert(block.height == height);
    assert(block.depth == depth);
    assert(block.tag == tag);
}

void test_block_model_compression_algorithm() {
    // Arrange
    BlockModel model;
    // ... setup test data

    // Act
    model.read_specification();
    model.read_tag_table();
    model.read_model();

    // Assert - verify expected behavior
    // Check output format, block count, etc.
}
```

6.2.2 Integration Test Guidelines

Integration Test Structure

```
// Integration test: Full pipeline verification
void test_compression_and_validation_pipeline() {
    // Test the complete workflow:
    // Input -> Compression -> Output -> Validation -> Reconstruction

    // 1. Setup test input
    std::string test_input = load_test_case("case1.txt");

    // 2. Run compression
    std::ostringstream compressed_output;
    BlockModel model;
    // ... run compression algorithm

    // 3. Run validation
    std::istringstream validation_input(compressed_output.str());
    bool validation_passed = run_validation_test(validation_input);

    // 4. Assert results
    assert(validation_passed);
    assert(output_format_is_correct(compressed_output.str()));
}
```

6.3 Test Execution

Running Tests

```
# Run all tests (recommended)
make test-all

# Run specific test types
make test-compression-unit
make test-integration

# Run with sample data
make run-case1
make run-case2

# Validate output
make validate-case1
make validate-case2

# Clean build and test
make clean && make test-all
```

6.4 Test Data Management

Test Data Organization

Test data structure:

- `tests/data/case1.txt` – Smaller test case ($64 \times 8 \times 5$)
- `tests/data/case2.txt` – Larger test case ($64 \times 16 \times 5$)
- Test data follows project input format specification
- Data files version controlled for consistency

Test data guidelines:

- Include edge cases and boundary conditions
- Test both successful and failure scenarios
- Use representative real-world data
- Keep test data files reasonably sized

7 CI/CD Quality Gates

Automated quality assurance in the development pipeline.

7.1 Pipeline Overview

Quality Pipeline Structure

Quality gates implemented:

- **Code formatting** – clang-format compliance check
- **Static analysis** – clang-tidy warning detection
- **Build verification** – Cross-platform compilation
- **Test execution** – All tests must pass
- **Documentation** – Updates and consistency checks

Optimized workflow:

- Quick validation on every PR (3 minutes)
- Comprehensive validation on schedule/manual trigger
- Smart change detection to avoid redundant runs
- 75% reduction in CI resource usage

7.2 Quality Requirements

Merge Requirements

Before merging to main branch:

- All tests pass on primary platform (Ubuntu)
- Code formatting compliance verified
- No clang-tidy warnings introduced
- Documentation updated as needed
- PR review approval from team member

Comprehensive validation (scheduled):

- Multi-platform builds (Linux, macOS, Windows)
- Multiple compiler compatibility (GCC, Clang, MSVC)
- Cross-compilation verification
- Performance regression detection

7.3 Local Quality Verification

Pre-Commit Verification Script

```
#!/bin/bash
# Save as scripts/verify-quality.sh

echo "    Running pre-commit quality checks..."

# 1. Format check
echo "    Checking code formatting..."
if ! ./scripts/format-code.sh; then
    echo "    Code formatting failed"
    exit 1
fi

# 2. Build and test check
echo "    Building and testing project..."
if ! make test-all; then
    echo "    Build or tests failed"
    exit 1
fi

# 3. Cross-platform check (if on Linux)
if command -v x86_64-w64-mingw32-g++ &> /dev/null; then
    echo "    Checking Windows cross-compilation..."
    if ! make windows-package; then
        echo "    Windows cross-compilation failed"
        exit 1
    fi
fi

# 4. IDE support check
echo "    Updating IDE support..."
if command -v bear &> /dev/null; then
    make compile-commands > /dev/null
fi

echo "    All quality checks passed!"
```

8 Best Practices Summary

8.1 Daily Development Checklist

Developer Daily Checklist

Before starting work:

Pull latest changes: `git pull origin main`

Create feature branch: `git checkout -b UG33-XX-feature-name`

Verify build: `make test-all`

During development:

Format code regularly: `./scripts/format-code.sh`

Run relevant tests: `make test-compression-unit`

Test with sample data: `make run-case1`

Before committing:

All tests pass: `make test-all`

Code formatted: `./scripts/format-code.sh`

Clean build works: `make clean && make test-all`

Cross-platform build: `make windows-package`

Documentation updated if needed

Meaningful commit message (conventional commits)

8.2 Code Review Guidelines

Code Review Focus Areas

Technical review points:

- Correctness and logic validation
- Performance implications
- Memory management and resource handling
- Error handling and edge cases
- Test coverage adequacy

Style and maintainability:

- Naming convention compliance
- Code organization and structure
- Documentation and comments
- Consistent formatting (automated)
- Modern C++ feature usage

9 Related Documentation

- **development-environment.tex** – Complete environment setup guide
- **README.md** – Quick reference and essential commands
- **Git & Github Workflow.pdf** – Version control and collaboration
- **.clang-format** – Formatting configuration file

- **.clang-tidy** – Static analysis configuration file
- **Makefile** – Build system configuration