



PROJECT 05 / UNIFIED EVIDENCE PORTFOLIO

Web Exposure Review

Finding a website's weak spots, explaining the business risk and defining the ethical response.

Prepared by: Anyaugo Space-Tech Ltd.

Environment: Kali, Ubuntu and OWASP Juice Shop in a VirtualBox lab

Evidence: 24 lab screenshots and 3 revised training records

Report date: 24 September 2026 | **Revised:** 25 September 2026

Business question

What can an outsider discover, how serious is it, and what should the owner fix first?

Observed result

A crafted login returns an administrator-identity token. A directory listing exposes potentially sensitive filenames. Supporting captures show deployment, traffic, discovery and repeated HTTP responses.

Portfolio boundary

Controlled web-app training, not a client assessment. No cloud-platform testing or verified remediation is evidenced. Attacker scenarios and proposed client practices are labelled separately.

A website review with a business purpose

What this portfolio demonstrates

The question behind the work

If someone examined a website the way an attacker would, what could they find, how serious would it be, and what should be fixed first? Project 5 presents its documented scope, lab setup, traffic capture, discovery, findings and repeated-response checks in test order.

The environment and the result

The supplied evidence uses Kali at 10.77.5.10 and an Ubuntu target at 10.77.5.20, with OWASP Juice Shop served on port 3000. Ansible deployment succeeds; the application responds; a crafted login request returns a token whose decoded payload identifies the administrator. A web-accessible /ftp directory exposes a list of potentially sensitive filenames.

How the explanations work

Each stage states the concern, work performed and evidence limit. Attacker scenarios describe possible business consequences, not observed incidents. Ethical-hacker responses explain proportionate validation. Any client workflow is a hypothetical professional application, separate from the local training activity.

What is observed and what is hypothetical

Only the supplied captures are treated as observed lab results. Attacker scenarios are illustrative; they are not claims that data was stolen, a password vault was opened, or a company was compromised. Remediation and client workflows are proposals, not completed changes.

Scope of the evidence

The supplied evidence covers a local web application. No cloud account, IAM policy, storage permission review or cloud configuration test is evidenced. These would require a separately agreed scope.

Reader route

For a summary, read the cover and Test 08. For the technical trail, follow Tests 01-07. Test 09 covers responsible handling of lab evidence and AI-assisted work. The portfolio contains 24 original lab screenshot files and three revised prepared records, with source references and bookmarks.

Evidence Index

Original screenshots, revised records and page locations

Test	Section	Items	Page
01	Scope and Authorization	1	4
02	Lab Setup and Network Validation	7	6
03	Practice Application Setup	4	14
04	Web Traffic and Evidence Capture	4	19
05	Attack Surface Discovery	4	24
06	Web Application Findings	4	29
07	Findings Retest and Severity Review	2	35
08	Final Report and Professional Application	Report	38
09	Privacy and Responsible AI Use	1	42

Evidence first

The 27 source items are represented by 24 original lab screenshot files and 3 revised prepared records. Two repeated screenshot pairs are identified as reused evidence, not independent confirmations.

Use the PDF bookmarks for section navigation. Wide terminal captures use landscape pages. Revised records are labelled and linked to their source filenames. Read the captions for the meaning and limits of each capture.

Introduction - page 2

Provenance and reading limits - page 44

References - page 45

Scope and Authorization

Define the lab boundary before testing

Purpose and recorded scope

Project 5 is a hands-on web-security training exercise in Anyaugo Space-Tech's own VirtualBox practice lab. The supplied evidence shows Kali, Ubuntu and OWASP Juice Shop. Public practice platforms, cloud services and client systems are not part of the demonstrated assessment.

What the scope record establishes

The record defines the intended local targets, training activities and exclusions. Activities include observing web traffic, mapping paths, examining weaknesses in the designated lab application and documenting results. It is an internal training record, not evidence of a client agreement or third-party testing permission.

Illustrative attacker scenario

An attacker might follow any reachable lead, including a service owned by another organisation. A visible website or login page is not an invitation to test it. The training lesson is to distinguish technical reachability from the defined testing boundary.

Ethical-hacker response in this lab

Check the target address and application before each test. Use the designated practice accounts and synthetic data. Keep discovery and validation focused on the local application; pause if an unexpected target or sensitive non-lab information appears.

Professional application - hypothetical client engagement

In a future engagement, the system owner and assessor would document targets, permitted methods, timing, contacts and stop conditions before testing. An out-of-scope lead would need a separate decision. NIST SP 800-115 describes assessment planning and rules of engagement. [R1]

Evidence boundary

The revised record on the next page describes the intended lab scope. Its preparation date does not establish when the original scope was written. The screenshots document selected activities, not a complete audit of all testing. Branding identifies the publisher; it does not provide third-party permission.

Lab Scope and Authorization Record

Authorization date: 24 September 2026 | Revised training record

Purpose

Project 5 uses a deliberately vulnerable local web application to practise discovering, assessing and explaining website weaknesses. This revised record defines the intended targets, training activities and exclusions.

Lab ownership and scope

The project is described by its owner as Anyaugo Space-Tech's own VirtualBox practice lab. The evidenced targets are Kali at 10.77.5.10 and Ubuntu at 10.77.5.20, with OWASP Juice Shop on port 3000. This internal record does not grant access to any third-party system.

Intended training activities

Inspect lab HTTP exchanges; map application paths; examine weaknesses using practice accounts and synthetic data; record reproducible observations; assess severity and propose remedies. Registration of a practice account is an intentional lab-state change.

Exclusions

Client systems, production services, public practice platforms, cloud accounts and unrelated websites are outside the demonstrated work. Denial of service, social engineering and collection of real customer information are not part of this training scope.

Boundary checks and stop conditions

Verify the target before testing. Pause if a request reaches an unexpected system, exposes non-lab information or causes instability. The available network screenshots establish local connectivity, not complete isolation from all other networks.

Permission in a future engagement

Testing a third-party system would require its owner's permission and an explicit scope. Public reachability or company branding does not supply that permission. This is a training record, not a client authorization letter or legal certification. [R1]

Record status

Revised on 25 September 2026 from the supplied scope record. Original source retained separately. This record describes the intended boundary; it is not an independent audit of every action taken during the exercise.

Revised from: 1A-Scope-And-Authorization-Record.png

Lab Setup and Network Validation

A known environment makes evidence interpretable

Purpose and work performed

The captures show static lab addressing, bidirectional ping checks, hostname correction, network-profile troubleshooting and two VirtualBox snapshot entries. Kali uses 10.77.5.10/24; Ubuntu uses 10.77.5.20/24 in the final displayed checks.

What the evidence shows

The first Ubuntu sequence includes a duplicate profile and an incorrect .10 address in the additional command. Later output shows the intended .20 address and successful communication. The cleanup capture prints "Duplicate profile already removed" after a fallback command; it does not independently prove which earlier deletion succeeded.

Illustrative attacker scenario: why an attacker cares

Poorly separated test and production networks can turn a low-risk practice system into a route toward valuable services. Confusing addresses or unexpected adapters can also cause a tester to contact the wrong target. That possibility is a scenario, not a demonstrated pivot in this project.

Ethical-hacker response

Confirm identity, interfaces, routes and intended lab reachability before sending assessment traffic. Record mistakes and the resulting state. Where isolation matters, check hypervisor adapters and egress as well as local ping. A successful ping proves connectivity to one address, not absence of other paths.

Important evidence limit

The initial Kali capture shows eth1 connected with 10.0.3.15 and IPv6 addresses. Later images do not provide a complete adapter and routing audit. The captures therefore support local reachability, but do not establish that the lab could reach no other network.

Snapshots and hypothetical professional application

The snapshot images show named checkpoints, not a completed restoration or independent backup. In a hypothetical client exercise, the owner and assessor would check the rollback method before disruptive testing. Seven original screenshots follow.

TEST 02

2A | Kali addressing and reachability

Original lab screenshot

The lab profile activates on eth0 at 10.77.5.10/24 and receives replies from 10.77.5.20.

```
(project05-kali@kali)~  
$ nmcli device status  
ip -br addr  
DEVICE  TYPE      STATE      CONNECTION  
eth1     ethernet  connected  Wired connection 1  
lo       loopback  connected (externally)  lo  
eth0     ethernet  disconnected  --  
lo       UNKNOWN  127.0.0.1/8 ::1/128  
eth0     UP  
eth1     UP        10.0.3.15/24 fd17:625c:f037:3:606e:d353:8f0b:7d77/64 fd17:625c:f037:3:a00:27ff:fe51:801a/64 fe80::a00:27ff:fe51:801a/64  
  
(project05-kali@kali)~  
$ sudo nmcli con add type ethernet ifname eth0 con-name p05-lab ipv4.method manual ipv4.addresses 10.77.5.10/24 ipv6.m  
ethod disabled  
sudo nmcli con up p05-lab  
ip -br addr show eth0  
ping -c 3 10.77.5.20  
[sudo] password for project05-kali:  
Connection 'p05-lab' (273cd0e6-96dc-4252-8cb8-8d0fe3e51ee6) successfully added.  
Connection successfully activated (D-Bus active path: /org/freedesktop/NetworkManager/ActiveConnection/5)  
eth0     UP        10.77.5.10/24  
PING 10.77.5.20 (10.77.5.20) 56(84) bytes of data.  
64 bytes from 10.77.5.20: icmp_seq=1 ttl=64 time=7.11 ms  
64 bytes from 10.77.5.20: icmp_seq=2 ttl=64 time=1.47 ms  
64 bytes from 10.77.5.20: icmp_seq=3 ttl=64 time=1.39 ms
```

Evidence note: The earlier interface output also shows connected eth1 at 10.0.3.15. This image does not prove complete isolation.

Test-2A-kali-static-ip-eth0-ping-victim.png

TEST 02

2B | Ubuntu configuration and duplicate profile

Original lab screenshot

The capture records the intended .20 address, followed by another profile command using .10 and a duplicate-name warning.

```
lab-admin@project05-ubuntu-victim:~$ sudo nmcli con add type ethernet ifname enp0s3 con-name "P05-IR-Lab" ip4 10.77.5.20/24
sudo nmcli con up "P05-IR-Lab"
ip -br addr show enp0s3
[sudo] password for lab-admin:
Connection 'P05-IR-Lab' (57b75658-153f-43de-a397-b1d72b6a809d) successfully added.
Connection successfully activated (D-Bus active path: /org/freedesktop/NetworkManager/ActiveConnection/72)
enp0s3          UP          10.77.5.20/24 fe80::a70d:da54:f62:a324/64
lab-admin@project05-ubuntu-victim:~$ ip -br link
lo              UNKNOWN    00:00:00:00:00:00 <LOOPBACK,UP,LOWER_UP>
enp0s3          UP          08:00:27:81:b0:1e <BROADCAST,MULTICAST,UP,LOWER_UP>
enp0s8          UP          08:00:27:72:ed:95 <BROADCAST,MULTICAST,UP,LOWER_UP>
lab-admin@project05-ubuntu-victim:~$ sudo nmcli con add type ethernet ifname eth0 con-name "P05-IR-Lab" ip4 10.77.5.10/24
sudo nmcli con up "P05-IR-Lab"
Warning: There is another connection with the name 'P05-IR-Lab'. Reference the connection by its uuid 'a758111c-3193-4843-95bf-3ed841951aff'
Connection 'P05-IR-Lab' (a758111c-3193-4843-95bf-3ed841951aff) successfully added.
Connection successfully activated (D-Bus active path: /org/freedesktop/NetworkManager/ActiveConnection/73)
```

Evidence note: This is troubleshooting evidence. The later address and ping checks provide the clearer record of the resulting lab state.

Test-2B-ubuntu-static-ip-enp0s3-with-duplicate-profile-error.png

2C-1 | Profile cleanup and Ubuntu address

Original lab screenshot

The displayed profile list and interface output show Ubuntu at 10.77.5.20/24.

```
lab-admin@project05-ubuntu-victim:~$ printf '=== Project 5 Test 02: duplicate profile cleanup =
===\n'
date -u
hostname
whoami

printf '\n=== Remove stray duplicate profile (if still present) ===\n'
sudo nmcli con delete a758111c-3193-4843-95bf-3ed841951aff 2>/dev/null || echo 'Duplicate profi
le already removed.'

printf '\n=== Remaining network profiles ===\n'
nmcli -f NAME,UUID,DEVICE con show

printf '\n=== Lab interface address ===\n'
ip -br addr show enp0s3

printf '\n=== Reach Kali attacker inside lab ===\n'
ping -c 3 10.77.5.10
=== Project 5 Test 02: duplicate profile cleanup ===
Wed Sep 23 05:14:32 PM UTC 2026
project05-ubuntu-victim
lab-admin

=== Remove stray duplicate profile (if still present) ===
[sudo] password for lab-admin:
Duplicate profile already removed.

=== Remaining network profiles ===
NAME                UUID                                DEVICE
netplan-enp0s8      9a683faa-2cc7-384f-9230-8beaf91f9f29  enp0s8
P05-IR-Lab          57b75658-153f-43de-a397-b1d72b6a809d  enp0s3
lo                   0a6b51c0-229e-4b52-b53a-f3401004c714  lo
netplan-enp0s3      1eef7e45-3b9d-3043-bee3-fc5925c90273  --

=== Lab interface address ===
enp0s3                UP                10.77.5.20/24 fe80::a70d:da54:f62:a324/64
```

Evidence note: The fallback text says the duplicate was already removed; the visible command suppresses errors. The final address is the directly observable result.

Test-2C-1-ubuntu-duplicate-profile-removed.png

TEST 02

2C-2 | Ubuntu reaches Kali

Original lab screenshot

Three packets sent to 10.77.5.10 receive three replies, with 0% packet loss.

```
=== Lab interface address ===
enp0s3          UP          10.77.5.20/24 fe80::a70d:da54:f62:a324/64

=== Reach Kali attacker inside lab ===
PING 10.77.5.10 (10.77.5.10) 56(84) bytes of data.
64 bytes from 10.77.5.10: icmp_seq=1 ttl=64 time=2.06 ms
64 bytes from 10.77.5.10: icmp_seq=2 ttl=64 time=1.23 ms
64 bytes from 10.77.5.10: icmp_seq=3 ttl=64 time=1.25 ms

--- 10.77.5.10 ping statistics ---
3 packets transmitted, 3 received, 0% packet loss, time 2002ms
rtt min/avg/max/mdev = 1.225/1.509/2.056/0.386 ms
lab-admin@project05-ubuntu-victim:~$
```

Evidence note: This confirms the displayed internal connection at capture time. It is not an egress or segmentation audit.

Test-2C-2-ubuntu-ping-kali.png

2D | Kali identity and reciprocal connection

Original lab screenshot

The hostname and hosts entry identify project05-kali; eth0 has .10 and the .20 target returns three replies.

```
(project05-kali@project05-kali)-[~]
$ printf '=== Project 5 Test 02: Kali hostname corrected ===\n'
date -u
hostname
whoami
grep project05 /etc/hosts

printf '\n=== Lab interface and reach to Ubuntu victim ===\n'
ip -br addr show eth0
ping -c 3 10.77.5.20
=== Project 5 Test 02: Kali hostname corrected ===
Wed 23 Sep 2026 17:05:40 UTC
project05-kali
project05-kali
127.0.1.1      project05-kali

=== Lab interface and reach to Ubuntu victim ===
eth0          UP          10.77.5.10/24
PING 10.77.5.20 (10.77.5.20) 56(84) bytes of data.
64 bytes from 10.77.5.20: icmp_seq=1 ttl=64 time=1.48 ms
64 bytes from 10.77.5.20: icmp_seq=2 ttl=64 time=1.13 ms
64 bytes from 10.77.5.20: icmp_seq=3 ttl=64 time=1.28 ms

--- 10.77.5.20 ping statistics ---
3 packets transmitted, 3 received, 0% packet loss, time 2004ms
rtt min/avg/max/mdev = 1.130/1.295/1.480/0.143 ms

(project05-kali@project05-kali)-[~]
$
```


Evidence note: Together with 2C-2, this supports bidirectional lab reachability. Only the displayed interface is checked here.

Test-2D-kali-hostname-corrected-ping-victim.png

2E-1 | Ubuntu checkpoint recorded

Original lab screenshot

VirtualBox lists P05-Ubuntu-Test02-Network-Validated-v2 above the current state.



Evidence note: A snapshot name records an intended checkpoint. No snapshot restoration is shown.

Test-2E-1-ubuntu-test02-network-validated-v2-snapshot.png

2E-2 | Kali checkpoint recorded

Original lab screenshot

VirtualBox lists P05-Kali-Test02-Network-Validated-v2 above the current state.

 Details

 Snapshots

 Logs

 Resource Use

 File Manager

Name	Taken
  P05-Kali-Test02-Network-Validated-v2	23/09/2026 7:35 pm (3 mi
 Current State (changed)	

Evidence note: This is evidence of a listed checkpoint, not a tested recovery or independent backup.

Test-2E-2-kali-test02-network-validated-v2-snapshot.png

Practice Application Setup

Deploy the target and verify that it responds

Purpose and work performed

Kali uses Ansible against Ubuntu. The first capture reports a successful Ansible ping. The deployment playbook installs prerequisites and Docker, pulls Juice Shop and starts its container. The recap shows ok=6, changed=4, unreachable=0 and failed=0.

What the evidence shows

A request to `http://10.77.5.20:3000` receives HTTP 200 and a browser displays the Juice Shop storefront. Together these show deployment and basic application reachability at capture time. Ansible's ping checks its remote execution path; it is distinct from the network pings in Test 02.

Illustrative attacker scenario: automation access

A business may use automation to configure many servers consistently. If an attacker obtains that automation account or its secrets, the same access could be misused to change several systems. This scenario explains the importance of the channel; no stolen automation credentials or fleet compromise were demonstrated here.

Ethical-hacker response

In this lab, use the designated practice account and target. In a hypothetical client review, examine automation permissions, secret handling and change records within the documented scope. Recommend restricted access and reviewed deployment changes; a harmful fleet-wide action is unnecessary to establish access.

Evidence limit and repeatability

The screenshot shows a successful playbook run, but the playbook and inventory files themselves are not supplied. A fresh rebuild or recovery has not been demonstrated. The browser capture establishes the storefront, not the health of every feature or a secure deployment.

Business meaning

The test establishes a working target before assessing its weaknesses. OWASP Juice Shop is used here as the deliberately vulnerable practice application described in the project materials. Four images follow.

TEST 03

3A | Ansible remote execution succeeds

Original lab screenshot

The victim at 10.77.5.20 returns SUCCESS and ping: pong, with changed: false.

```
(project05-kali㉿project05-kali)-[~/project05-ansible]
$ ssh-keyscan -H 10.77.5.20 >> ~/.ssh/known_hosts
ansible -i inventory.ini victim -m ping --ask-pass
SSH password:
10.77.5.20 | SUCCESS => {
    "changed": false,
    "ping": "pong"
}

(project05-kali㉿project05-kali)-[~/project05-ansible]
$
```

Evidence note: This supports Ansible connectivity using supplied credentials. It does not demonstrate exploitation.

Test-3A-ansible-ping-victim-success.png

3B | Juice Shop deployment completes

Original lab screenshot

The visible playbook recap reports six successful tasks, four changes, no unreachable hosts and no failures.

```
(project05-kali@project05-kali)-[~/project05-ansible]
$ ansible-playbook -i inventory.ini deploy-juiceshop.yml --ask-pass --ask-become-pass
SSH password:
BECOME password[defaults to SSH password]:

PLAY [Deploy OWASP Juice Shop on the Project 5 victim] *****

TASK [Gathering Facts] *****
ok: [10.77.5.20]

TASK [Install prerequisite packages] *****
changed: [10.77.5.20]

TASK [Install Docker from Ubuntu repository] *****
changed: [10.77.5.20]

TASK [Ensure Docker service is running and enabled] *****
ok: [10.77.5.20]

TASK [Pull the Juice Shop image] *****
changed: [10.77.5.20]

TASK [Run the Juice Shop container] *****
changed: [10.77.5.20]

PLAY RECAP *****
10.77.5.20 : ok=6 changed=4 unreachable=0 failed=0 skipped=0 res
cued=0 ignored=0

(project05-kali@project05-kali)-[~/project05-ansible]
$
```

Evidence note: The run output is supplied; the playbook source and an independent rebuild test are not.

Test-3B-ansible-playbook-juiceshop-deployed.png

3C-1 | The web application responds

Original lab screenshot

curl receives HTTP 200 from the Ubuntu target on port 3000, with response headers and HTML content type.

```
(project05-kali@project05-kali)-[~/project05-ansible]
$ curl -I http://10.77.5.20:3000
HTTP/1.1 200 OK
Access-Control-Allow-Origin: *
X-Content-Type-Options: nosniff
X-Frame-Options: SAMEORIGIN
Feature-Policy: payment 'self'
X-Recruiting: /#/jobs
Accept-Ranges: bytes
Cache-Control: public, max-age=0
Last-Modified: Wed, 23 Sep 2026 23:56:21 GMT
ETag: W/"24b1-1a0d0b2e96b"
Content-Type: text/html; charset=UTF-8
Content-Length: 9393
Vary: Accept-Encoding
Date: Thu, 24 Sep 2026 00:08:41 GMT
Connection: keep-alive
Keep-Alive: timeout=5

(project05-kali@project05-kali)-[~/project05-ansible]
$ |
```


Evidence note: This verifies a response from the root page. It is not a full functional or security test.

Test-3C-1-juiceshop-reachable-from-kali.png

3C-2 | Storefront visible in the lab browser

Original lab screenshot

The browser displays the Juice Shop product catalogue at the lab address.



Evidence note: The visible browser page corroborates basic application availability. No real customer transaction is shown.

Test-3C-2-juiceshop-storefront-in-browser.png

Web Traffic and Evidence Capture

Read what the application actually sends

Purpose and recorded sequence

curl captures the root response, creates a practice account with HTTP 201, logs in with HTTP 200 and extracts a JWT payload. The customer token includes a password-hash field, role and account metadata. The screenshot contains lab credentials and tokens; they are not repeated in the report prose.

Illustrative attacker scenario: information exposed to the browser

An attacker who obtains a token can inspect a readable payload for useful account information. A password hash could assist offline guessing, but reading a token is not proof that it can be forged. For a business, unnecessary disclosure increases the consequences of a token leak.

Ethical-hacker response to token disclosure

Record the unnecessary field using a controlled account. Recommend retaining only claims needed by the application and removing password hashes. A later test should inspect newly issued tokens and separately check signature and authorisation enforcement. No signature bypass, token forgery or successful hash cracking is shown here. [R4]

Headers: observations before conclusions

The root response includes X-Content-Type-Options and X-Frame-Options, while CSP and HSTS are not visible. The test uses plain HTTP; an absent HSTS header here is not proof of an HTTPS-site configuration defect. A production review would assess HTTPS behaviour and an appropriate CSP in context. [R5]

Cross-origin policy

Access-Control-Allow-Origin: * is visible. This is an observation requiring endpoint-specific review, not proof of cross-origin account theft. Determine which data is intentionally public and restrict origins where cross-origin access is required for sensitive services. [R6]

Training lesson and evidence limit

These captures show how to turn traffic into verifiable observations. Test 06 demonstrates a separate SQL-injection login bypass; it does not establish exploitation of the token-disclosure observation. Four original screenshots follow.

4A | Request and response headers

Original lab screenshot

The verbose capture shows Kali connecting to the lab target, receiving HTTP 200 and displaying response headers.

```
(project05-kali@project05-kali)-[~/project05-ansible]
$ curl -v http://10.77.5.20:3000/ -o /dev/null
* Trying 10.77.5.20:3000...
* Established connection to 10.77.5.20 (10.77.5.20 port 3000) from 10.77.5.10 port 55342
  % Total    % Received % Xferd  Average Speed   Time    Time     Time  Current
                                 Dload  Upload   Total   Spent    Left   Speed
  0         0     0      0      0      0      0      0      0      0
> GET / HTTP/1.1
> Host: 10.77.5.20:3000
> User-Agent: curl/8.20.0
> Accept: */*
>
* Request completely sent off
< HTTP/1.1 200 OK
< Access-Control-Allow-Origin: *
< X-Content-Type-Options: nosniff
< X-Frame-Options: SAMEORIGIN
< Feature-Policy: payment 'self'
< X-Recruiting: /#/jobs
< Accept-Ranges: bytes
< Cache-Control: public, max-age=0
< Last-Modified: Wed, 23 Sep 2026 23:56:21 GMT
< ETag: W/"24b1-1a0d0b2e96b"
< Content-Type: text/html; charset=UTF-8
< Content-Length: 9393
< Vary: Accept-Encoding
< Date: Thu, 24 Sep 2026 11:07:28 GMT
< Connection: keep-alive
< Keep-Alive: timeout=5
<
{ [9393 bytes data]
100  9393 100  9393   0      0  91857      0      0
* Connection #0 to host 10.77.5.20:3000 left intact

(project05-kali@project05-kali)-[~/project05-ansible]
$
```

Evidence note: Some security headers are present. CSP and HSTS are not displayed; the request is HTTP, and wildcard CORS alone does not prove data theft.

Test-4A-curl-verbose-headers.png

4B-1 | Practice account creation

Original lab screenshot

The registration request receives HTTP 201 Created and a response identifying a customer account.

```
(project05-kali@project05-kali)-[~/project05-ansible]
$ curl -s -i -X POST http://10.77.5.20:3000/api/Users \
  -H "Content-Type: application/json" \
  -d '{"email":"[email protected]","password":"Anyaugo123!","passwordRepeat":"Anyaugo123!","securityQuestion":{"id":1},"securityAnswer":"lab"}' \
  | tee Test-4B-1-curl-register.txt
HTTP/1.1 201 Created
Access-Control-Allow-Origin: *
X-Content-Type-Options: nosniff
X-Frame-Options: SAMEORIGIN
Feature-Policy: payment 'self'
X-Recruiting: /#/jobs
Location: /api/Users/25
Content-Type: application/json; charset=utf-8
Content-Length: 308
ETag: W/"134-t8Z1tiNmNUA6mWFF7S7XUo/Zujs"
Vary: Accept-Encoding
Date: Thu, 24 Sep 2026 12:03:41 GMT
Connection: keep-alive
Keep-Alive: timeout=5

{"status":"success","data":{"username":"","role":"customer","deluxeToken":"","lastLoginIp":"0.0.0.0","profileImage":"/assets/public/images/uploads/default.svg","isActive":true,"id":25,"email":"[email protected]","updatedAt":"2026-09-24T12:03:41.359Z","createdAt":"2026-09-24T12:03:41.359Z","deletedAt":null}}

(project05-kali@project05-kali)-[~/project05-ansible]
$
```

Evidence note: This is controlled test-data creation. It is a deliberate application-state change, so the exercise should not be described as entirely read-only.

Test-4B-1-curl-register.png

4B-2 | Normal login returns a token

The practice account receives HTTP 200 and an authentication token.

Evidence note: This establishes the normal login baseline. The supplied screenshot is retained unchanged and includes lab authentication material.

Project 5 | Web Exposure Review | Controlled lab

TEST 04

4B-3 | Customer token payload

Original lab screenshot

The decoded payload shows the customer role and a password-hash field among account attributes.

```
(project05-kali@project05-kali)-[~/project05-ansible]
$ grep -o '"token":"[^"]*"' Test-4B-2-curl-login-token.txt | cut -d'"' -f4 | cut -d. -f2 | ba
se64 -d 2>/dev/null | tee Test-4B-3-jwt-decoded.txt; echo
```

REDACTED - credential hash in decoded payload

```
(project05-kali@project05-kali)-[~/project05-ansible]
$
```

Evidence note: Readable claims are not proof of forgery. The concern here is unnecessary sensitive content, not the mere presence of a role claim.

Test-4B-3-jwt-decoded.png

Attack Surface Discovery

Turn endpoint leads into validated observations

Purpose and work performed

ffuf probes common paths and filters responses of 9,393 bytes, matching the root page size shown earlier. The displayed results include /ftp, /robots.txt, redirects and several error responses. curl then retrieves robots.txt, and a local text-processing command lists names from the captured /ftp response.

What the evidence shows

The screenshots show the size filter in use and the resulting leads. The final ffuf status reaches 4,614 of 4,614 wordlist entries but reports 1,074 errors. The folder does not contain the raw JSON or text output referenced in the commands. These captures support discovery activity, not an exhaustive inventory.

Illustrative attacker scenario: following a public clue

A company might list an internal-looking path in robots.txt to discourage search indexing. An attacker could read that file, visit the path and look for sensitive material. Here, "Disallow: /ftp" is a useful lead; it is not an access restriction or proof of a weakness by itself.

Ethical-hacker response

Check response bodies and expected behaviour rather than treating every HTTP 200 or 500 as a confirmed endpoint or vulnerability. Define traffic limits for the lab, inspect failed requests and validate important leads manually. In a hypothetical client assessment, those limits and targets would be agreed with the owner.

The step from discovery to a finding

The /ftp filename list raises a specific concern because names include backups and a .kdbx file. An ethical tester would establish permitted access and sensitivity with the minimum necessary evidence before rating actual exposure. Further downloading or cracking is not demonstrated in this portfolio. [R3]

Evidence reuse

The robots.txt and filename-list images are reused byte-for-byte in Test 06. They appear in both sections to preserve the project sequence, but are not counted as independent confirmations. Four image files follow.

5A-1 | Size-filtered discovery

ffuf filters response size 9393 and returns leads including /ftp, /assets and /promotion.

Evidence note: A filtered result is a lead. HTTP status, response body and access behaviour need interpretation before declaring a finding.

Project 5 | Web Exposure Review | Controlled lab

TEST 05

5A-2 | Discovery completion and errors

Original lab screenshot

The final display reaches 4614/4614 entries and records 1074 errors.

```
promotion [Status: 200, Size: 5863, Words: 536, Lines: 180, Duration: 1669ms]
redirect [Status: 500, Size: 2531, Words: 219, Lines: 50, Duration: 417ms]
rest [Status: 500, Size: 2410, Words: 210, Lines: 50, Duration: 268ms]
restored [Status: 500, Size: 2418, Words: 210, Lines: 50, Duration: 255ms]
restore [Status: 500, Size: 2416, Words: 210, Lines: 50, Duration: 256ms]
restaurants [Status: 500, Size: 2424, Words: 210, Lines: 50, Duration: 265ms]
restricted [Status: 500, Size: 2422, Words: 210, Lines: 50, Duration: 255ms]
robots.txt [Status: 200, Size: 28, Words: 3, Lines: 2, Duration: 785ms]
seccode [Status: 200, Size: 0, Words: 1, Lines: 1, Duration: 950ms]
second [Status: 200, Size: 0, Words: 1, Lines: 1, Duration: 950ms]
secondary [Status: 200, Size: 0, Words: 1, Lines: 1, Duration: 949ms]
secret [Status: 200, Size: 0, Words: 1, Lines: 1, Duration: 946ms]
secrets [Status: 200, Size: 0, Words: 1, Lines: 1, Duration: 941ms]
section [Status: 200, Size: 0, Words: 1, Lines: 1, Duration: 937ms]
sections [Status: 200, Size: 0, Words: 1, Lines: 1, Duration: 1899ms]
:: Progress: [4614/4614] :: Job [1/1] :: 1 req/sec :: Duration: [0:10:08] :: Errors: 1074 ::

(project05-kali@project05-kali)-[~/project05-ansible]
$ |
```

Evidence note: The run is not an error-free inventory. Some apparent endpoints return errors or empty responses and require follow-up.


Test-5A-2-ffuf-attack-surface-endpoints.png

TEST 05

5B | robots.txt identifies /ftp

Original lab screenshot

The response contains User-agent: * and Disallow: /ftp.

A terminal window with a dark background. The prompt is (project05-kali@project05-kali)-[~/project05-ansible]. The command entered is \$ curl -s http://10.77.5.20:3000/robots.txt | tee Test-5B-robots-txt.txt. The output displayed is User-agent: * and Disallow: /ftp.

```
(project05-kali@project05-kali)-[~/project05-ansible]  
$ curl -s http://10.77.5.20:3000/robots.txt | tee Test-5B-robots-txt.txt  
User-agent: *  
Disallow: /ftp
```

Evidence note: This supplies a discovery lead. It does not deny HTTP access. The same image is reused as Test 6B-1.

Test-5B-robots-txt.png

TEST 05

5C | Filenames from the exposed directory

Original lab screenshot

The extracted list includes .bak files and incident-support.kdbx alongside other names.

```
(project05-kali@project05-kali)-[~/project05-ansible]
$ grep -oP 'title="\K[^"]+' Test-5C-ftp-directory-listing.txt | sort -u | tee Test-5C-ftp-files-only.txt
acquisitions.md
announcement_encrypted.md
coupons_2013.md.bak
eastere.gg
encrypt.pyc
incident-support.kdbx
legal.md
package.json.bak
package-lock.json.bak
quarantine
suspicious_errors.yml

(project05-kali@project05-kali)-[~/project05-ansible]
$
```

Evidence note: The capture shows filenames extracted from a saved listing. It does not show the contents or successful download of each file. Reused as Test 6B-2.

Test-5C-ftp-files-only.png

Administrator Login Bypass

Recorded severity: Critical | demonstrated in the lab

Observed evidence

In the local Juice Shop application, a crafted request to `/rest/user/login` receives HTTP 200 and an authentication token. The next capture decodes the returned token and displays id 1, `admin@juice-sh.op` and role `admin`. This supports issuance of an administrator-identity token without supplying that lab account's password.

Illustrative attacker scenario: the potential consequence

On a business website, bypassing login could allow an attacker to attempt privileged operations, view customer information or change records. The exact impact depends on which server-side actions the session can perform. No customer-data extraction, record change, persistence or operating-system takeover is demonstrated here.

How an ethical hacker would handle it

In the lab, retain the request, response and decoded identity as proof of the authentication failure. Further privilege checks would need a harmless, predefined test. In a hypothetical client engagement, report the finding through the agreed contact and obtain scope approval before accessing business records.

Proposed remedy and owner

For an application with this weakness, the developer should use parameterised queries and review related authentication queries. Restrict database-account privileges. This addresses a likely mechanism; no source-code review is supplied to confirm the exact implementation. These are proposed fixes, not changes completed in the lab. [R2]

What a meaningful retest would show

After an approved fix, the previous bypass input must not produce an authenticated session. A legitimate test account should still work. Capture the response body and session behaviour, and verify a harmless protected action if authorised. An HTTP status code alone is insufficient.

Rating and assurance boundary

Critical is the qualitative rating recorded in Test 7B, reflecting the potential impact of administrator authentication bypass. No CVSS vector was supplied. This report retains that rating with its evidence limits; it does not claim full system takeover or verified access to every administrative function.

Exposed Directory and Sensitive Filenames

Recorded severity: High | content access not fully evidenced

Observed evidence

The discovery output reports /ftp returning HTTP 200. robots.txt points to that path, and the supplied listing extraction includes coupons_2013.md.bak, package.json.bak, package-lock.json.bak and incident-support.kdbx. The two Test 6B images repeat the Test 05 captures.

Illustrative attacker scenario: following the filenames

An attacker could use a backup filename to seek configuration details or a password-vault file for attempted offline guessing. Exposure of a filename does not guarantee download access, valuable contents or a crackable vault. Those are possible follow-on risks, not completed actions shown here.

How an ethical hacker would handle it

In the lab, record the filename listing and the limits of what it demonstrates. Any further file check should be a defined training step using minimal data. In a hypothetical client engagement, obtain scope approval before retrieving sensitive contents or attempting offline analysis, and ask the owner to assess actual exposure.

Proposed remedy and owner

The application or hosting owner should remove backups and secret-bearing artifacts from web-served locations and enforce access control where files must remain available. Disabling directory indexing alone is insufficient if a known direct file URL still works. Review the deployment process that placed those files there. [R3]

What a meaningful retest would show

Check both directory browsing and authorised direct-file test cases from an unauthenticated session. If secret exposure is confirmed, the owner should assess credential rotation and relevant access records. No remedy, rotation, file download or vault opening is evidenced in this project.

Rating and assurance boundary

High is the original qualitative rating. The filename listing is shown, but content sensitivity and direct download access require further validation. This report presents High as provisional for potential sensitive-file exposure. Four source screenshots follow, including the two reused discovery images.

The displayed login request receives HTTP 200 and a token associated with the administrator email.

```
(project05-kali@project05-kali)-[~/project05-ansible]
```

31 / 45

TEST 06

6A-2 | Returned token identifies administrator

Original lab screenshot

The decoded payload displays the administrator account and role admin.

```
(project05-kali@project05-kali)-[~/project05-ansible]
$ grep -o '"token": "[^"]*"' Test-6A-sqli-login-bypass.txt | cut -d'"' -f4 | cut -d. -f2 | bas
e64 -d 2>/dev/null | tee Test-6A-2-sqli-admin-token-decoded.txt: echo
```

REDACTED - credential hash in decoded payload

```
(project05-kali@project05-kali)-[~/project05-ansible]
$
```

Evidence note: Together with 6A-1, this supports the login bypass. Decoding is not a signature-verification test or evidence of operating-system access.


Test-6A-2-sqli-admin-token-decoded.png

TEST 06

6B-1 | Public clue to the directory

Original lab screenshot

robots.txt explicitly names /ftp.

A terminal window with a dark background. The prompt is (project05-kali@project05-kali)-[~/project05-ansible]. The command is \$ curl -s http://10.77.5.20:3000/robots.txt | tee Test-5B-robots-txt.txt. The output is User-agent: * and Disallow: /ftp.

```
(project05-kali@project05-kali)-[~/project05-ansible]  
$ curl -s http://10.77.5.20:3000/robots.txt | tee Test-5B-robots-txt.txt  
User-agent: *  
Disallow: /ftp
```

Evidence note: This is byte-identical to Test 5B. It supports the same discovery lead and is not a new retest.

Test-6B-1-robots-disallow-ftp.png

TEST 06

6B-2 | Directory filename exposure

Original lab screenshot

The extracted directory names include backup-like files and a .kdbx filename.

```
(project05-kali@project05-kali)-[~/project05-ansible]
$ grep -oP 'title="\K[^"]+' Test-5C-ftp-directory-listing.txt | sort -u | tee Test-5C-ftp-files-only.txt
acquisitions.md
announcement_encrypted.md
coupons_2013.md.bak
eastere.gg
encrypt.pyc
incident-support.kdbx
legal.md
package.json.bak
package-lock.json.bak
quarantine
suspicious_errors.yml

(project05-kali@project05-kali)-[~/project05-ansible]
$
```

Evidence note: This is byte-identical to Test 5C. Individual file access, contents and password-vault compromise are not shown.

Test-6B-2-ftp-directory-exposed.png

Findings Retest and Severity Review

Separate repeated responses from a verified repair

Purpose and recorded result

The retest repeats the crafted login request and a request to /ftp/. Both display HTTP 200. The revised review distinguishes that limited response evidence from the original administrator-identity token capture. It retains the supplied severity categories with explicit qualifications.

What the retest actually establishes

The commands discard response bodies. The capture therefore shows repeated HTTP response status, but does not show a fresh token, decoded role, privileged action, directory content or individual file download. Test 06 remains the stronger evidence for administrator identity issuance.

Illustrative attacker scenario: why status-only checks can mislead

A business application can return a successful HTTP status while displaying an error or rejecting access in its response body. An attacker may investigate that difference; a professional assessor must also check actual behaviour before claiming either continued exploitation or successful repair.

Ethical-hacker response

Compare the post-change result against a defined acceptance criterion: no unauthorised session, no unintended file access and normal authorised use preserved. Record before-and-after evidence and any residual risk. This project contains no remediation deployment or successful fix verification.

How the ratings will be used

The prepared review uses impact and ease of exploitation as a qualitative guide, not a numeric CVSS calculation. This report preserves those supplied ratings while qualifying the evidence. The file-exposure impact remains provisional; header and CORS observations need deployment-specific context.

Remediation status

No patch, remediation deployment or fix verification is evidenced in this exercise. A deliberately vulnerable application can still be modified; its training purpose does not make correction impossible. The revised record states only the observed repeated responses and the further checks needed.

TEST 07

7A | Repeated HTTP responses

Original lab screenshot

The crafted login request and /ftp/ request both return HTTP 200 in the displayed retest.

```
(project05-kali@project05-kali)-[~/project05-ansible]
$ echo "=== RETEST 6A: SQLi admin login bypass ===" ; \
curl -s -o /dev/null -w "HTTP %{http_code}\n" -X POST http://10.77.5.20:3000/rest/user/login \
-H "Content-Type: application/json" \
-d '{"email":"' OR 1=1--","password":"x"}' ; \
echo "=== RETEST 6B: /ftp directory still exposed ===" ; \
curl -s -o /dev/null -w "HTTP %{http_code}\n" http://10.77.5.20:3000/ftp/ \
| tee Test-7A-findings-retest.txt
=== RETEST 6A: SQLi admin login bypass ===
HTTP 200
=== RETEST 6B: /ftp directory still exposed ===
HTTP 200

(project05-kali@project05-kali)-[~/project05-ansible]
$
```

Evidence note: Bodies are discarded. This supports repeated reachability and status, not independent confirmation of a new administrator session or file access.

Test-7A-findings-retest.png

Findings Retest and Severity Record

Revised training record | 25 September 2026

Retest evidence

Test 7A shows HTTP 200 for the repeated login and directory requests. Response bodies were discarded. It does not independently show a fresh administrator session, file contents or a successful fix.

Observation	Rating	Evidence and qualification
Administrator login bypass	Critical	Test 6A returns a token with administrator identity. Privileged functions and host access were not demonstrated.
Potential sensitive-file exposure	High, provisional	Directory filenames include backups and .kdbx. Individual download access and contents remain unverified.
Password-hash field in token	Medium	Field visible in decoded customer token. No hash cracking or token forgery demonstrated.
Header observations	Low, contextual	No CSP or HSTS displayed in sampled HTTP traffic. Some headers are present; HTTPS behaviour not assessed.
robots.txt names /ftp	Informational	A discovery lead. It does not itself enforce access control or prove sensitive content access.
Wildcard CORS	Low, contextual	Wildcard origin visible. No sensitive cross-origin response read demonstrated.

How to read the ratings

Categories retain the original qualitative assessment, with confidence limits made explicit. They are not CVSS scores or evidence that every observation was exploited. Business impact would need separate validation in a real environment.

Remediation status

No remediation is evidenced. Further verification would require response content and relevant session or access behaviour, followed by comparison after a documented change.

Final Report

What the portfolio supports and what remains open

Overall outcome

The portfolio demonstrates a working two-machine web lab, automated target deployment, command-line traffic capture, endpoint discovery and a documented administrator-login bypass. A directory listing exposes potentially sensitive filenames. The evidence supports a useful capability demonstration rather than assurance over any real company's systems.

Strongest finding

Test 6A records authentication data returned from a crafted login request, followed by a decoded administrator identity. This is the most direct demonstration of a security failure. Its potential business consequence justifies urgent attention in an equivalent authorised client environment.

Supporting observations

The captures also show a password-hash field in a customer token, wildcard CORS and the absence of some headers from sampled HTTP responses. These are distinct observations with different prerequisites and confidence levels. They should not all be described as independently exploited vulnerabilities.

What has not been established

No cloud security review, data theft, vault cracking, host compromise, comprehensive isolation audit or successful remediation is demonstrated. The scope, severity and privacy pages are prepared records. The scan reports errors; the final retest captures only status codes.

Tools evidenced

VirtualBox records the VM checkpoints; Kali and Ubuntu provide the lab systems; Ansible deploys the target through SSH; Docker runs the application; curl captures HTTP exchanges; ffuf discovers candidate paths; shell text processing and Base64 decoding expose selected response content. The supplied files do not demonstrate use of Burp Suite or mitmproxy.

Training priorities and professional application

For further training, prioritise authentication behaviour, then validate file access and sensitivity through predefined lab checks. No additional testing is performed by preparing this report. The following action register proposes remedies; the later client-workflow page is an explicitly hypothetical professional example.

Findings and Priorities

Supplied ratings retained; confidence and next steps made explicit

Observation / rating	Evidence and confidence	Proposed action / owner
6A Login bypass Critical	Token returned; decoded admin identity. Privileged functions not exercised.	Prioritise query repair and meaningful session retest. Application developer.
6B Directory exposure High, provisional	Listing and sensitive-looking filenames shown. Individual download and content unverified.	Validate permitted access; remove or protect sensitive artifacts. Hosting / application owner.
Token data Medium	Password-hash field visible in customer payload. No cracking or forgery shown.	Remove unnecessary sensitive claims; inspect new tokens. Identity / application developer.
Security headers Low, contextual	No CSP / HSTS in sampled HTTP response; some protective headers are present.	Review production HTTPS and browser policy. Application / platform owner.
robots.txt path Informational	/ftp disclosed. This is a lead, not access control.	Protect the resource itself; review disclosed paths. Application owner.
Wildcard CORS Low, contextual	Allow-Origin: * visible; sensitive cross-origin read not demonstrated.	Review each endpoint and intended origins. API owner.

Status: No remediation is evidenced for any item. The ratings are qualitative, not CVSS scores. This is a proposed training priority list. In a hypothetical client engagement, the owner would confirm impact, responsibility and deadlines.

Remediation guidance: SQL injection [R2]; web-served backup files [R3]; JWT claims [R4]; headers [R5]; CORS [R6].

From Discovery to an Approved Fix

Educational example only | no client engagement was performed

1 | Agree the engagement

Obtain written authority and agree targets, methods, timing, contacts and stop conditions. Include third-party and cloud boundaries explicitly. Confirm the evidence location and permitted AI use before handling restricted material. This is proposed client practice, not authority supplied by the lab record. [R1]

2 | Establish a reliable baseline

Verify target identity and expected access. Record the environment and normal login behaviour, preserve a baseline response, and confirm how to stop testing if the service is affected. Use controlled accounts and synthetic data where possible.

3 | Validate and report the loophole

Distinguish a scanner lead from a demonstrated issue. Capture enough evidence to show the affected boundary and explain potential business impact. For a serious authentication failure, notify the agreed contact promptly rather than waiting for the final report.

4 | Give the owner a concrete action

For each finding, record the affected function, evidence, confidence, impact, recommended correction and a responsible owner. The client decides change timing and risk acceptance. An assessor should not silently alter production just because a weakness was discovered.

5 | Retest the security outcome

After the owner confirms a change, repeat the approved case and inspect meaningful response content or behaviour. Check both the original failure and normal authorised use. Mark the result as resolved, partly resolved, unresolved or not retested, with supporting evidence.

6 | Close the engagement

Deliver the findings and limitations, remaining actions and any accepted risk. Close temporary access and manage evidence retention or deletion under the agreement. Keep the business owner's decisions distinguishable from the assessor's observations and recommendations.

Evidence Limits and Next Validation

A clear distinction between observed results and open questions

Area	Current evidence	Next validation
Lab boundary	Local addressing and successful ping; an additional Kali interface appears connected.	Review all adapters, routes and permitted egress.
Automation	Successful playbook recap and working storefront.	Review actual playbook and inventory; test a controlled lab rebuild if required.
Discovery	Size-filtered leads; 1,074 scan errors.	Review raw output and manually validate important and failed requests.
Authentication	Crafted login returns administrator identity in token.	Define a harmless lab privilege check and verify post-fix behaviour.
File exposure	Directory names include backups and a vault-like filename.	Validate authorised direct access and sensitivity; do not infer contents.
Retest	Two HTTP 200 responses; bodies discarded.	Capture session and access behaviour after a documented change.
Cloud exposure	No cloud-platform evidence supplied.	Agree a separate scope and collect cloud-specific evidence.
Privacy / AI	Revised training recommendations; implementation not audited.	Check the actual evidence-handling and AI workflow against the stated practices.

Claim supported: a documented web-application training exercise with an administrator-login bypass and directory filename exposure. Broader exploitation, production assurance and successful repair remain outside the demonstrated result.

Privacy and Responsible AI Use

Responsible handling of training evidence and AI-assisted work

Why this belongs in a training portfolio

Lab screenshots can contain usernames, passwords, session tokens and other reusable details. Responsible handling applies even when no client is involved. The practices below are recommendations; this portfolio is not an audit of their implementation.

1 | Define the workspace and purpose

Choose where evidence will be stored and which AI tools may assist drafting or analysis. Record the intended task and the information needed. For this project, keep the explanation grounded in local training evidence.

2 | Minimise information shared

Prefer synthetic examples or reviewed extracts. Check images and filenames as well as text for sensitive details. Keep originals separately; label any redacted sharing copies. Lab credentials and tokens visible in these screenshots should not be reused for real accounts.

3 | Control access and review provider handling

Limit access to the evidence workspace and review relevant storage, retention, deletion and AI-processing settings. A paid subscription or familiar brand is not proof of a particular data-handling guarantee. No provider-compliance assessment was performed here.

4 | Review AI-assisted output

A responsible reviewer should compare explanations with the captures. AI output must not invent findings, imply a client engagement or report a successful fix from HTTP status alone. NIST's Generative AI Profile supports attention to privacy and human oversight. [R7]

5 | Keep a record of revisions

Record material editorial changes and distinguish revised explanatory records from technical captures. Here, 24 lab screenshot files remain unchanged; the scope, severity and privacy records have been revised for consistent training wording.

Hypothetical client application

Future client work would require a separate agreement covering tools, permitted disclosures, access and evidence handling. Permission to test a system should not be assumed to include permission to disclose its data to an AI provider. No such client arrangement is claimed in this exercise.

Privacy and Responsible AI Use Record

Revised training record | 25 September 2026

Purpose

Recommendations for handling training evidence and AI-assisted explanations. These are proposed practices, not verified controls or a claim of a client engagement.

01 | Define the workspace

Choose the evidence location, intended AI task and information needed. Keep the project separate from unrelated work and define who may access its records.

02 | Limit what is shared

Use synthetic examples or reviewed extracts. Check screenshots for passwords, tokens and personal information. Preserve originals; label any sanitised copies. Do not reuse displayed lab credentials for real services.

03 | Control access

Limit access to the project workspace and use suitable account protection. Decide how evidence is stored, retained and removed. A written recommendation does not establish that these measures are implemented.

04 | Review and verify

Compare AI-assisted statements with the underlying captures. Distinguish a scan lead, a confirmed observation and a hypothetical consequence. Record test limitations and do not claim a fix without verification.

05 | Check provider handling

Review relevant AI-service terms and settings for retention, processing, training use and deletion before sharing restricted information. No specific provider guarantee or compliance review is claimed here. [R7]

06 | Keep an accountable record

Document material revisions and disclosures. If information is shared outside the intended boundary, stop further disclosure and follow the relevant response process. A future client engagement would need its own agreed data-handling arrangements.

Revised from: Test-9A-Privacy-And-AI-Use.png

Provenance and Reading Limits

Keep the evidence and the interpretation traceable

Source material

The project folder supplied 27 PNG files and READ-ME-FIRST.md. Test 08 was empty at initial review. The Project 4 unified report supplied the presentation reference and existing logo; Nunito was supplied in the project folder.

Evidence accounting

This edition contains all 24 original lab screenshot files and revised versions of the three prepared records: scope, severity and privacy. Two screenshot pairs are byte-identical, leaving 22 unique technical captures. Reused screenshots are identified in their captions.

Original captures and revised records

Technical screenshots are unchanged. The three prepared records have been rewritten as report pages to remove ambiguous scope, client and assurance claims. They are labelled as revised records and reference their original PNG filenames. Original source files remain separately preserved in the project folder.

Dates and verification limits

Some captures display 23-24 September 2026. The first report was prepared on 24 September and this editorial revision on 25 September 2026. The review did not verify capture authenticity, clock synchronisation or a complete chain of custody. Raw text logs, scan JSON and Ansible source files were not supplied.

Interpretation rules

Observed results are limited to the displayed captures. Recommendations describe future work; attacker scenarios are hypothetical. No claim is made of complete isolation, file-content retrieval, vault cracking, full system takeover or successful remediation. No new security tests were run for this editorial revision.

Publisher and classification

Anyaugo Space-Tech Ltd. | SECURITY TRAINING | LAB EVIDENCE. This is a training portfolio, not a client assessment or legal certification. The references inform professional examples and proposed remedies; they do not validate the lab results or grant third-party permission.

References

Primary sources checked on 24 September 2026

R1 | NIST SP 800-115

Technical Guide to Information Security Testing and Assessment (2008). Assessment planning, rules of engagement and reporting.

[Open primary source](#)

R2 | OWASP SQL Injection Prevention Cheat Sheet

Parameterised queries and least-privilege database access.

[Open primary source](#)

R3 | OWASP Web Security Testing Guide

Review Old Backup and Unreferenced Files for Sensitive Information. Web-served artifacts and configuration review.

[Open primary source](#)

R4 | OWASP JSON Web Token Cheat Sheet

Signed claims, confidentiality distinctions and token security.

[Open primary source](#)

R5 | OWASP HTTP Headers Cheat Sheet

Security headers and their appropriate application context.

[Open primary source](#)

R6 | OWASP REST Security Cheat Sheet

Endpoint access control and cross-origin policy.

[Open primary source](#)

R7 | NIST AI 600-1

Artificial Intelligence Risk Management Framework: Generative Artificial Intelligence Profile (2024). Privacy and human oversight.

[Open primary source](#)

References inform the recommendations; they do not certify the lab or grant testing permission. The project README, original screenshots and supplied Project 4 report are the local source materials. Nunito is used from the supplied font package.