

AI2611 CheatSheet

Haoyu Zhen

2022 年 6 月 11 日

Preface

Introduction

- My Machine Learning Lecture Notes (更丰富的版本, 适合学习这门课):
[Self-Learning/CS229/MyNotes/ML.pdf](#)
- \LaTeX code of the CheatSheet is available at:
[SJTU-Course-Stack/AI2611/CheatSheet](#)
- CheatSheet 为 2022 版 (非常少较草率, 当然有部分超纲, 不适合用于学习)。

Acknowledgement

- CS229, Stanford University. (Foundation, Kernel Method, GMM)
- CS231n, Stanford University. (Deep Learning)
- CS189, UC Berkeley. (Random Forest)
- Understanding Machine Learning, Cambridge University. (Linear Regression, KNN, SVM, K-means, PCA)
- AI2611, Shanghai Jiao Tong University. (中文部分, Spectral, Dimensionality Reduction)

§ Foundation

监督学习、无监督学习（聚类、降维）
独立同分布；最小化范化误差

Metric	Formula	Interpretation
准确率 (Accuracy)	$\frac{TP + TN}{TP + TN + FP + FN}$	Overall performance of model
查准率 (Precision)	$\frac{TP}{TP + FP}$	How accurate the positive predictions are
通过率、查全率 (Recall Sensitivity)	$\frac{TP}{TP + FN}$	Coverage of actual positive sample
假阳率 (FPR)	$\frac{FP}{TN + FP}$	
F1 score	$\frac{2TP}{\text{样例总数} + TP + TN}$	Hybrid metric useful for unbalanced classes
F_{β} score	$\frac{(1 + \beta^2) \times \text{Pre} \times \text{Rec}}{\beta^2 \times \text{Pre} + \text{Rec}}$	Precision and Recall

在不同的阈值下可以得到不同的 TPR 和 FPR 值，将它们在图中绘制出来，并依次连接起来就得到了 ROC 曲线，阈值取值越多，ROC 曲线越平滑。AUC：ROC 曲线下的面积

模型选择：留出法（hold-out，保持数据分布的一致性，多次重复划分取平均值）、交叉验证法（留一法，10-fold，更接近期望评估的模型，但计算量巨大；测试集只包含一个数据，无法分层采样，测试误差率区别较大；）、自助法（bootstrap，有放回采样，训练集中数据存在重复，适合小规模数据集）

误差-方差分解
 $E(f; D) = \text{bias}^2 + \text{variance} + \text{error}^2$
 $= (\bar{f}(x) - y)^2 + \mathbb{E}_D[f(x; D) - \bar{f}(x)] + \mathbb{E}_D[(y_D - y)^2]$

§ Linear Regression

Loss function: $\mathcal{L}_S(h) = \frac{1}{m} \sum_{i=1}^m (h(\mathbf{x}) - \mathbf{y})^2$. Solve $A\mathbf{w} = \mathbf{b}$ where $A \stackrel{\text{def}}{=} \sum \mathbf{x}_i \mathbf{x}_i^T = XX^T$ and $\mathbf{b} \stackrel{\text{def}}{=} \sum y_i \mathbf{x}_i = X^T \mathbf{y}$.

Theorem 1 $\omega = (X^T X)^{-1} X^T \mathbf{y}$. 优点: single-shot 算法; 易于实现; 缺点: 伪逆计算量大没可能导致数值不稳定（奇异矩阵）。

Theorem 2 Eigenvalue decomposition: $A = VD^+V^T$ where D is a diagonal matrix and V is an orthonormal matrix. Define D^+ to be the diagonal matrix: $D_{i,i}^+ = 0$ if $D_{i,i} = 0$ otherwise $D_{i,i}^+ = 1/D_{i,i}$. Then, $A\hat{\mathbf{w}} = \mathbf{b}$ where $\hat{\mathbf{w}} = VD^+V^T \mathbf{b}$.

Remark 1 Gradient Descent. 优点: 收敛快, 易于实现; 缺点: 批量更新, 可伸缩性问题。

概率解释: $y|x; \theta \sim \mathcal{N}(0, \sigma)$. Loss function 为最大似然的结果，分类器为 $E[y|x]$ 。

Ridge (岭) Regression

Regularization (w) $= \lambda \|w\|^2$ and $\mathbf{w} = (2\lambda m I + A)^{-1} \cdot \lambda$ 适当增大可以减少方差，但会提高误差。

Lasso (套索) Regression $R(w) = \lambda \|w\|_1$. SPARSE

§ KNN 超参数: k 和 $d(x_1, x_2)$. 计算量大, The “Curse of Dimensionality”, $m \geq (4c\sqrt{d}/\varepsilon)^{d+1}$. 低维度 + 边界非线性 + 密度高时使用。

§ 贝叶斯 先验: $\Pr(\omega_j)$, 后验: $\Pr(\omega_j|x)$, Likelihood: $\Pr(x|\omega_j)$ and Post = likely \times Prior/ $\Pr(x)$ where ω_j 表示类别, x 表示数据 (特征)。

最小化采取 α_i 行动的风险: $R(\alpha_i|x) = \sum_{j=1}^{j=c} \lambda(\alpha_i|\omega_j) \Pr(\omega_j|x)$, 其中 λ 表示在自然状态为 ω_j 的情况下因采取行动 α_i 而产生的损失。If $R(\alpha_1|x) < R(\alpha_2|x)$, then we adopt $\alpha_1 (\omega_1)$. Usually, $\lambda(\alpha_i, \omega_j) = 1 - \delta_{ij}$ and $R(\alpha_i|x) = 1 - \Pr(\omega_i|x)$

参数估计

$$\hat{\theta} = \arg \max_{\theta} \mathcal{L}(\theta) = \sum_{k=1}^n \log \Pr(x_k | \theta).$$

§ Random Forest

Definition 1 (Entropy)
$$H(Y) = - \sum_k \Pr(Y = k) \log \Pr(Y = k)$$
$$H(Y|X_j) = \Pr(X_j = 1) H(Y|X_j = 1) + \Pr(X_j = 0) H(Y|X_j = 0)$$

		Predicted class	
	+	TP True Positive	FN False Negative Type II error
Actual class	-	FP False Positive Type I error	TN True Negative

Mutual information between X_j and Y .
 $\max I(X_j; Y) \triangleq H(Y) - H(Y|X_j)$
Gini impurity/index: $G(Y) = 1 - \sum_k \Pr^2(Y = k)$

Random Forest
Ensemble method+randomized+reduce correlation

- bagging (bootstrap aggregating)**: sample some data points uniformly with replacement, and use these as the training set.
- feature randomization**: sample some number $k < d$ of features as candidates to be considered for this split.

§ LDA
类间 $d = |w^T \mu_1 - w^T \mu_2|$, 类内 $d_j = \sum_{i \in C_j} |w^T x_i - w^T \mu_j|$
从而 $d_w = d_1^2 + d_2^2 = w^T \Sigma w$.
Solve: $\max (d^2/d_w) = \max (w^T S_b w / w^T S_w w) \triangleq \lambda(w)$.

Theorem 3 $S_w^{-1} S_b w = \lambda w$, w 为最大特征值所对应的特征向量。

Remark 2 多类问题最多可以降低 $M - 1$ 维。
Calinski-Harabaz index:

$$S_b = \sum_{j=1}^M N_j (\mu_j - \mu) (\mu_j - \mu)^T$$
$$S_w = \sum_{j=1}^M \sum_{i \in C_j} (x_i - \mu_j) (x_i - \mu_j)^T$$

§ Kernel Method $K(x, z) \triangleq \langle \phi(x), \phi(z) \rangle$

Remark 3 Kernel is a corresponding to the feature map ϕ as a function that maps $\mathcal{X} \times \mathcal{X} \mapsto \mathbb{R}$.

Definition 2 (Gaussian kernel)
$$K(x, z) = \exp \left(- \frac{\|x - z\|^2}{2\sigma^2} \right).$$

The gaussian kernel is corresponding to an **infinite** dimensional feature mapping ϕ . Also, ϕ lives in Hilbert space.

§ SVM

$$\arg \max_{(w,b): \|w\|=1} \min_{i \in [m]} |w^T x^i + b| \quad \text{s.t. } \forall i, y^i (w^T x^i + b) \geq 1.$$
$$\arg \max_{(w,b): \|w\|=1} \min_{i \in [m]} y^i (w^T x^i + b) \tag{1}$$

$$(w_0, b_0) = \arg \min_{(w,b)} \frac{1}{2} \|w\|^2 \quad \text{s.t. } \forall i, y^i (w^T x^i + b) \geq 1.$$

Output: $\hat{w} = w_0 / \|w_0\|, \hat{b} = b_0 / \|w_0\|$

Support Vector: $g(x) = \pm 1$. $\gamma \sim \frac{1}{\|w\|}$
Soft-SVM and Norm Regularization

$$\min_{w,b,\xi} \left(\lambda \|w\|^2 + \frac{1}{m} \sum_{i=1}^m \xi_i \right)$$
$$\text{s.t. } \forall i, y^i (w^T x^i + b) \geq 1 - \xi_i \text{ and } \xi_i \geq 0$$

Output: w, b

Definition 3 (hinge loss)
 $l^{\text{hinge}}((w, b), (x, y)) = \max \{0, 1 - yw^T x + b\}.$

Now we just need to optimize $\lambda \|w\|^2 + \mathcal{L}^{\text{hinge}}(w, b)$. 松弛变量凡何意义: 对越界数据惩罚力度。
§ **K-means** 收敛: 递减 + 有下界。

前辈 将采样数据从某一分组分类到另一分组，目的是使得损失函数 $\min J = \sum_{i=1}^c J_i = \sum_{i=1}^c \sum_{x \in H_i} \|x - \mu_i\|^2$. \hat{x} 从类别 i 移至 j , 更新公式为: $m_j^* = m_j + \frac{\hat{x} - \mu_j}{n_j + 1}, J_j^* = J_j + \frac{n_j}{n_j + 1} \|\hat{x} - \mu_j\|^2$ and $J_i^* = J_i - \frac{n_i}{n_i - 1} \|\hat{x} - \mu_i\|^2$. Transer \hat{x} to H_k whose $J_k^* - J_l$ is smallest.

The Choice of k

- The Elbow Method: Calculate the Within Cluster Sum of Squared Errors for different values of k, and choose the k for which WSS becomes first starts to diminish.
- The Silhouette value: $a(i) = \frac{1}{|C_I|-1} \sum_{j \in C_I, j \neq i} d(i, j), b(i) = \min_{J \neq I} \frac{1}{|C_J|-1} \sum_{j \in C_J} d(i, j)$ and $s(i) = \frac{b-a}{\max[a,b]}$.
缺点: 样本数据发生很小的扰动, 那么样本的分类结果容易发生明显的改变.

Linkage-Based Clustering Algorithms aka **Agglomerative** Clustering which is trivial. Stopping criteria: numbers of clusters or current distance.

§ **GMM** $x|z \sim \mathcal{N}(\nu, \Sigma)$ where $z \sim \text{Mul}(\phi)$ is the latent variable

- E-step: Evaluate the **posterior** $\Pr: Q_i(z^i) = P(z^i|x^i; \theta)$.
- M-step: Use the posterior \Pr $Q_i(z^i)$ as cluster specific weights on data points x^i to separately re-estimate each cluster model:

$$\theta_i = \arg \max_{\theta} \sum_i \int_{z_i} Q_i(z^i) \log \left(\frac{P(x^i, z^i; \theta)}{Q_i(z^i)} \right) dz^i$$

Likelihood: $\mathcal{L}(\phi, \mu, \Sigma) = \sum_{i=1}^n \log \sum_{z^i=1}^k \Pr(x^i|z^i; \mu, \Sigma) \Pr(z^i|\phi)$

§ **Spectral** 对数据有很好的表征, 非凸数据; 但是拓展性不好。
Similarity: $W_{ij} = s(x_i, x_j) = \exp \left(- \frac{\|x_i - x_j\|^2}{2\sigma^2} \right)$
Graph Constructin: ϵ -neighborhood, fully connected and KNN.

Definition 4 Some useful definitions:
 $d_i = \sum_{j \in V} W_{ij}$
 $\text{cut}(A, B) = \sum_{i \in A, j \in B} W_{ij}$
 $\text{cut}(A_1, A_2, \dots, A_k) = \frac{1}{2} \sum_{i=1}^k \text{cut}(A_i, \bar{A}_i)$
 $\text{RatioCut}(A_1, A_2, \dots, A_k) = \frac{1}{2} \sum_{i=1}^k \text{cut}(A_i, \bar{A}_i) / |A_i|$
 $\text{Neut}(A_1, A_2, \dots, A_k) = \frac{1}{2} \sum_{i=1}^k \text{cut}(A_i, \bar{A}_i) / \text{vol}(A_i)$
Degree of the subgraph A: $\text{vol}(A) = d_A = \sum_{i,j \in A} W_{ij}$
Laplacian: $L = D - W$ where $W = \text{diag}(\sum_{i,j \in E} W_{ij})$

Theorem 4
 $\text{cut}(A, \bar{A}) = x^T L x$ and $\text{cut}(A_1, \dots, A_k) = \text{trace}(X^T L X)$
Proof: LHS $= \sum_{i \in A} d_i - \sum_{i,j \in A} W_{ij}$.

Theorem 5 Relaxation: $x \in \{0, 1\}^{|V|} \mapsto \mathbb{R}^{|V|}$.
 $\min \text{cut}(A, \bar{A}) \iff \min x^T L x = (x^T L x) / (x^T x)$ $\iff x$ 为 L 的最小非零特征值所对应的特征向量 (**Rayleigh quotient Theorem**).

Definition 5 Normalized Spectral Clustering:

- 对拉普拉斯矩阵进行标准化操作: $L \leftarrow D^{-0.5} L D^{-0.5}$
- 计算标准化操作后拉普拉斯矩阵最小的 k_1 个特征值对应的特征向量 F
- 将 F 组成的矩阵按行标准化, 组成 $n \times k_1$ 的特征矩阵 P .
- 对 P 中的每一行作为一个 k_1 维的样本, 用聚类方法进行聚类。

§ **PCA** Compressing matrix $W \in \mathbb{R}^{n,d}$ and recovering matrix $U \in \mathbb{R}^{d,n}$: $\arg \min_{W,U} \sum_{i=1}^n \|x_i - UWx_i\|^2$

Lemma 1 Let (U, W) be a solution of Equation above. Then $U^T U = I$ and $W = U^T$. (The columns of U are orthonormal.)

By the fact that $\|x - U U^T x\|^2 = \|x\|^2 - \text{trace}(U^T x x^T U)$
We could rewrite the Equation as follows:
$$\arg \max_{U \in \mathbb{R}^{d,n}: U^T U = I} \text{trace} \left[U^T \left(\sum_{i=1}^m x_i x_i^T \right) U \right]$$

Theorem 6 Let x_1, \dots, x_m be arbitrary vectors in \mathbb{R}^d , let $A = \sum_{i=1}^m x_i x_i^T$, and let u_1, \dots, u_n be n eigenvectors of the matrix A corresponding to the largest n eigenvalues of A . Then, the solution to the PCA optimization problem given in Equation is to set U to be the matrix whose columns are u_1, \dots, u_n and to set $W = U^T$. (More Intuition: **MathOverFlow**)

Proof 1 Let $V D V^T$ be the spectral decomposition of A (suppose that $D_{1,1} \geq \dots \geq D_{d,d}$) and let $B = V^T U$. We have

$$\text{trace}(U^T A U) = \text{trace}(B^T D B) = \sum_{j=1}^d D_{j,j} \sum_{i=1}^n B_{j,i}^2$$
$$\leq \max_{\beta \in [0,1]^d: \|\beta\| \leq n} \sum_{j=1}^d D_{j,j} \beta_j = \sum_{j=1}^n D_{j,j}$$

Nota Bene: $B^T B = I$ which entails $\sum_{j=1}^d \sum_{i=1}^n B_{j,i}^2 = n$.

§ **Dimensionality Reduction**
PCA 拟合了训练数据的长轴短轴, 使得映射后得到的低维度向量分布散射最大
MDS 找到映射方向使得在低维空间中高维样本间距离不变
 $\min \sum_{i < j} \|\hat{x}_i - \hat{x}_j\| - d_{ij}$

ISOMAP Geodesic 距离 ($d_{ij} \leftarrow$ shortest path) 能反映该数据的真正低维流形结构, 保留数据集的本征几何特征。
Locally Linear Embedding 从局部的线性结构关系, 恢复全局的非线性流形。假设: $\hat{x}_i = \sum_j W_{ij} x_j$ and $\sum_j W_{ij} = 1$.

$$\min \sum_i \left\| x_i - \sum_j W_{ij} x_j \right\|^2 \quad \text{s.t. } W_{ij} = 0 \text{ if } X_j \in \mathcal{N}(x_i)$$

ISOMAP VS LLE 都保留了邻接的几何结构; 都没有显式的映射函数, 故使用比较麻烦; LLE 需要更多的训练数据; ISOMAP 计算效率高, 实用性更高
§ **Deep Learning** Trivial.

CNN
$$N = \frac{W - F + 2P}{S} + 1.$$

RNN
$$h_{t+1} = \text{Tanh}(W_h h_t + W_x x_{t+1}).$$

Attention
$$y = \text{SoftMax} \left(\frac{QK^T}{\sqrt{D}} \right) V.$$

Weight Initialization
$$w \leftarrow \sqrt{2/n} \times \text{RandN}(0, 1)$$

Activate Function
$$\text{Sigmoid}(z) = \frac{1}{1 + \exp(-z)} \quad \text{and} \quad \text{Tanh}(z) = \frac{e^z - e^{-z}}{e^z + e^{-z}}$$

Batch Normalization (BP for BN is challenging)
Update:
$$\mu = \alpha \mu + (1 - \alpha) \hat{\mu} \quad \text{and} \quad \sigma^2 = \alpha \sigma^2 + (1 - \alpha) \hat{\sigma}^2.$$
Forward and Eval:
$$x_i \leftarrow \gamma \frac{x_i - \mu}{\sqrt{\sigma^2 + \varepsilon}} + \beta$$

Momentum
$$v \leftarrow \mu v - \alpha dx \quad \text{and} \quad x \leftarrow x + v$$

Adam
$$m \leftarrow \beta_1 m + (1 - \beta_1) dx \quad \text{and} \quad m_t \leftarrow m / (1 - \beta_1^t)$$
$$v \leftarrow \beta_2 v + (1 - \beta_2) dx^2 \quad \text{and} \quad v_t \leftarrow v / (1 - \beta_2^t)$$
$$x \leftarrow x - \frac{\alpha m_t}{\sqrt{v_t + \varepsilon}}$$