



macOS Security Compliance

macOS 26.0

***Security Configuration - Committee on National
Security Systems Instruction No. 1253 (Moderate)***

Tahoe Guidance, Revision 1.0 (2025-09-11)

Table of Contents

1. Foreword	1
2. Scope	2
3. Authors	3
4. Acronyms and Definitions	4
5. Applicable Documents.....	6
5.1. Government Documents.....	6
5.2. Non-Government Documents	6
6. Auditing	7
6.1. Configure Audit Log Files to Not Contain Access Control Lists	7
6.2. Configure Audit Log Folder to Not Contain Access Control Lists.....	7
6.3. Enable Security Auditing	8
6.4. Configure Audit Capacity Warning.....	9
6.5. Configure Audit_Control to Not Contain Access Control Lists	10
6.6. Configure Audit_Control Group to Wheel.....	10
6.7. Configure Audit_Control Owner to Mode 440 or Less Permissive	11
6.8. Configure Audit_Control Owner to Root	12
6.9. Configure System to Shut Down Upon Audit Failure.....	12
6.10. Configure Audit Log Files Group to Wheel.....	13
6.11. Configure Audit Log Files to Mode 440 or Less Permissive	13
6.12. Configure Audit Log Files to be Owned by Root	14
6.13. Configure System to Audit All Authorization and Authentication Events	15
6.14. Configure System to Audit All Administrative Action Events	16
6.15. Configure System to Audit All Failed Program Execution on the System.....	17
6.16. Configure System to Audit All Deletions of Object Attributes	17
6.17. Configure System to Audit All Changes of Object Attributes	18
6.18. Configure System to Audit All Failed Change of Object Attributes.....	19
6.19. Configure System to Audit All Failed Read Actions on the System.....	20
6.20. Configure System to Audit All Failed Write Actions on the System	21
6.21. Configure System to Audit All Log In and Log Out Events	22
6.22. Configure Audit Log Folders Group to Wheel	23
6.23. Configure Audit Log Folders to be Owned by Root	24
6.24. Configure Audit Log Folders to Mode 700 or Less Permissive.....	24
6.25. Configure Audit Retention to 7d	25
6.26. Configure Audit Failure Notification.....	26
7. Authentication	27
7.1. Enforce Multifactor Authentication for Login.....	27
7.2. Enforce Multifactor Authentication for the su Command	28
7.3. Enforce Multifactor Authentication for Privilege Escalation Through the sudo Command ..	29

7.4. Allow Smartcard Authentication	30
7.5. Set Smartcard Certificate Trust to High	31
7.6. Set Smartcard Certificate Trust to Moderate	32
7.7. Enforce Smartcard Authentication	33
7.8. Disable Password Authentication for SSH	34
8. iCloud	36
8.1. Disable iCloud Address Book	36
8.2. Disable the System Setting for Apple ID	37
8.3. Disable iCloud Bookmarks	37
8.4. Disable the iCloud Calendar Services	38
8.5. Disable iCloud Document Sync	39
8.6. Disable the iCloud Freeform Services	40
8.7. Disable iCloud Game Center	40
8.8. Disable iCloud Keychain Sync	41
8.9. Disable iCloud Mail	42
8.10. Disable iCloud Notes	43
8.11. Disable iCloud Photo Library	44
8.12. Disable iCloud Private Relay	44
8.13. Disable iCloud Reminders	45
8.14. Disable iCloud Desktop and Document Folder Sync	46
9. macOS	48
9.1. Disable AppleID and Internet Account Modifications	48
9.2. Disable AirDrop	49
9.3. Disable Apple ID Setup during Setup Assistant	49
9.4. Configure Apple System Log Files Owned by Root and Group to Wheel	50
9.5. Configure Apple System Log Files To Mode 640 or Less Permissive	51
9.6. Enable Authenticated Root	52
9.7. Disable Blank Blu Ray	53
9.8. Disable Blank CD	54
9.9. Disable Blank DVD	55
9.10. Enforce Blu Ray Read Only	56
9.11. Disable Bonjour Multicast	56
9.12. Disable Burn Support	57
9.13. Disable Calendar.app	58
9.14. Enforce CD Read Only	59
9.15. Issue or Obtain Public Key Certificates from an Approved Service Provider	60
9.16. Enforce Installation of XProtect Remediator and Gatekeeper Updates Automatically	61
9.17. Disable Installation of Configuration Profiles through the User Interface	62
9.18. Disable Dictation	62
9.19. Disable Disk Images	63
9.20. Disable DVD-RAM	64

9.21. Disable Erase Content and Settings	65
9.22. Access to External Storage Must Be Defined	66
9.23. Disable FaceTime.app	66
9.24. Disable FileVault Automatic Login	67
9.25. Control Connections to Other Systems via a Deny-All and Allow-by-Exception Firewall Policy	68
9.26. Enable Firmware Password	69
9.27. Enable Gatekeeper	70
9.28. Disable Genemoji AI Creation	71
9.29. Disable Handoff	72
9.30. Configure User's Home Folders to Apple's Default	72
9.31. Secure User's Home Folders	74
9.32. Disable the Built-in Web Server	74
9.33. Disable iCloud Storage Setup during Setup Assistant	75
9.34. Disable Apple Intelligence Image Playground	76
9.35. Configure Install.log Retention to 365	77
9.36. Disable iPhone Mirroring	77
9.37. Disable Infrared (IR) support	78
9.38. Prevent AdminHostInfo from Being Available at Login Window	79
9.39. Disable Mail App	80
9.40. Disable Apple Intelligence Mail Smart Replies	81
9.41. Disable Apple Intelligence Mail Summary	82
9.42. Enforce Enrollment in Mobile Device Management	83
9.43. Disable Messages App	84
9.44. Configure System Log Files Owned by Root and Group to Wheel	85
9.45. Configure System Log Files to Mode 640 or Less Permissive	86
9.46. Disable Network File System Service	86
9.47. Disable Apple Intelligence Notes Transcription	87
9.48. Disable Apple Intelligence Notes Transcription Summary	88
9.49. Enforce On Device Dictation	88
9.50. Enable Parental Controls	89
9.51. Disable Password Autofill	90
9.52. Remove Password Hint From User Accounts	91
9.53. Disable Proximity Based Password Sharing Requests	91
9.54. Disable Password Sharing	92
9.55. Disable Photos Enhanced Visual Search	93
9.56. Display Policy Banner at Login Window	94
9.57. Display Policy Banner at Remote Login	95
9.58. Enforce SSH to Display Policy Banner	97
9.59. Disable Power Nap	98
9.60. Disable Privacy Setup Services During Setup Assistant	99

9.61. Enforce Rapid Security Response Mechanism	99
9.62. Disable User Ability from Being Able to Undo Rapid Security Responses	100
9.63. Enable Recovery Lock	101
9.64. Disable Removable Storage Devices	101
9.65. Disable Root Login	103
9.66. Disable Apple Intelligence Safari Reader Summary	103
9.67. Enforce Screen Saver at Login Window	104
9.68. Ensure Secure Boot Level Set to Full	105
9.69. Enforce FileVault in Setup Assistant	105
9.70. Ensure System Integrity Protection is Enabled	106
9.71. Disable Siri Setup during Setup Assistant	107
9.72. Disable Apple Intelligence During Setup Assistant	108
9.73. Disable Screen Time Prompt During Setup Assistant	108
9.74. Disable Unlock with Apple Watch During Setup Assistant	109
9.75. Limit SSH to FIPS Compliant Connections	110
9.76. Set SSH Active Server Alive Maximum to 0	112
9.77. Configure SSH ServerAliveInterval option set to 900	114
9.78. Configure SSHD Channel Timeout to session:=900	115
9.79. Configure SSHD ClientAliveCountMax to 0	116
9.80. Configure SSHD ClientAliveInterval to 900	118
9.81. Limit SSHD to FIPS Compliant Connections	119
9.82. Set Login Grace Time to 30	121
9.83. Configure SSHD PerSourcePenalties	122
9.84. Disable Root Login for SSH	123
9.85. Configure SSHD Unused Connection Timeout to 900	124
9.86. Configure Sudo To Log Events	125
9.87. Configure Sudoers Timestamp Type	125
9.88. Ensure System Volume is Read Only	126
9.89. Disable Trivial File Transfer Protocol Service	127
9.90. Enable Time Synchronization Daemon	128
9.91. Disable TouchID Prompt during Setup Assistant	129
9.92. Disable Login to Other User's Active and Locked Sessions	129
9.93. Prohibit User Installation of Software into /Users/	131
9.94. Disable Unix-to-Unix Copy Protocol Service	132
9.95. Disable Apple Intelligence Writing Tools	133
10. Password Policy	134
10.1. Disable Accounts after 35 Days of Inactivity	134
10.2. Limit Consecutive Failed Login Attempts to 3	135
10.3. Set Account Lockout Time to 15 Minutes	136
10.4. Require Passwords Contain a Minimum of One Numeric Character	137
10.5. Require Passwords to Match the Defined Custom Regular Expression	138

10.6. Prohibit Password Reuse for a Minimum of 5 Generations	139
10.7. Require Passwords Contain a Minimum of One Lowercase Character	140
10.8. Restrict Maximum Password Lifetime to 60 Days	141
10.9. Require a Minimum Password Length of 15 Characters	142
10.10. Set Minimum Password Lifetime to 24 Hours	143
10.11. Prohibit Repeating, Ascending, and Descending Character Sequences	144
10.12. Require Passwords Contain a Minimum of One Special Character	145
10.13. Automatically Remove or Disable Temporary or Emergency User Accounts within 72 Hours	146
10.14. Require Passwords Contain a Minimum of One Uppercase Character	148
11. System Settings	151
11.1. Disable Airplay Receiver	151
11.2. Prevent Apple Watch from Terminating a Session Lock	152
11.3. Disable Unattended or Automatic Logon to the System	152
11.4. Enforce Auto Logout After 86400 Seconds of Inactivity	153
11.5. Disable Bluetooth When no Approved Device is Connected	154
11.6. Disable the Bluetooth System Settings Pane	155
11.7. Disable Bluetooth Sharing	156
11.8. Disable Content Caching Service	157
11.9. Enforce Critical Security Updates to be Installed	157
11.10. Disable Sending Diagnostic and Usage Data to Apple	158
11.11. Disable External Intelligence Integrations	159
11.12. Disable External Intelligence Integration Sign In	160
11.13. Enforce FileVault	161
11.14. Disable Find My Service	161
11.15. Enable macOS Application Firewall	163
11.16. Enable Firewall Stealth Mode	163
11.17. Apply Gatekeeper Settings to Block Applications from Unidentified Developers	164
11.18. Configure Gatekeeper to Disallow End User Override	166
11.19. Disable Guest Access to Shared SMB Folders	166
11.20. Disable the Guest Account	167
11.21. Disable Hot Corners	168
11.22. Secure Hot Corners	169
11.23. Disable Sending Audio Recordings and Transcripts to Apple	170
11.24. Disable Improve Search Information to Apple	171
11.25. Disable Improve Siri and Dictation Information to Apple	172
11.26. Disable the Internet Accounts System Preference Pane	172
11.27. Disable Internet Sharing	173
11.28. Disable Location Services	174
11.29. Configure Login Window to Prompt for Username and Password	175
11.30. Disable Media Sharing	176

11.31. Disable Password Hints	177
11.32. Disable Personalized Advertising	177
11.33. Disable Printer Sharing	178
11.34. Disable Remote Apple Events	179
11.35. Disable Remote Management	179
11.36. Disable Screen Sharing and Apple Remote Desktop	180
11.37. Enforce Session Lock After Screen Saver is Started	181
11.38. Enforce Screen Saver Password	182
11.39. Enforce Screen Saver Timeout	183
11.40. Enforce Automatic Installs of Available Security Updates using DDM	183
11.41. Disable Siri	184
11.42. Disable the System Settings Pane for Siri	185
11.43. Disable Server Message Block Sharing	186
11.44. Disable SSH Server for Remote Access Sessions	186
11.45. Enable SSH Server for Remote Access Sessions	187
11.46. Require Administrator Password to Modify System-Wide Preferences	188
11.47. Configure macOS to Use an Authorized Time Server	190
11.48. Enforce macOS Time Synchronization	191
11.49. Configure User Session Lock When a Smart Token is Removed	192
11.50. Disable the Touch ID System Settings Pane	192
11.51. Disable TouchID for Unlocking the Device	193
11.52. USB Devices Must be Authorized Before Allowing	194
11.53. Disable the System Settings Pane for Wallet and Apple Pay	195
11.54. Disable Wi-Fi Interface	196
12. Inherent	197
12.1. Audit Record Reduction and Report Generation	197
12.2. Allow Information Transfer with Other Operating Systems	197
12.3. Ensure Separate Execution Domain for Processes	198
12.4. Allow Administrators to Modify Security Settings and System Attributes	198
12.5. Enforce Access Restrictions	198
12.6. Allow Administrators to Promote Other Users to Administrator Status	199
12.7. Configure the System to Implement Approved Cryptography to Protect Information	199
12.8. Configure the System to Protect Memory from Unauthorized Code Execution	200
12.9. Limit Concurrent GUI Sessions to 10 for all Accounts	200
12.10. Enforce Approved Authorization for Logical Access	201
12.11. Display logoff capability and message to prevent exploitation	201
12.12. Ensure the System Implements Malicious Code Protection Mechanisms	202
12.13. Obscure Passwords	203
12.14. Must behave in predictable and documented manner	203
12.15. Prevent Software From Executing at Higher Privilege Levels than Users Executing The Software	204

12.16. Configure the System to Block Non-Privileged Users from Executing Privileged Functions	204
12.17. Configure the System to Prevent the Unauthorized Disclosure of Data via Shared Resources	205
12.18. Prohibit Remote Activation of Collaborative Computing Devices	205
12.19. Provide Ability to Disconnect or Disable Remote Access	206
12.20. Require users to reauthenticate for privilege escalation	206
12.21. Require users to reauthenticate when changing authenticators	206
12.22. Must remove all software components after updated versions installed	207
12.23. Ensure all Federal Laws, Executive Orders, Directives, Policies, Regulations, Standards, and Guidance for Authentication to a Cryptographic Module are Met	207
12.24. Protected Storage for Cryptographic Keys	207
12.25. Configure the System to Separate User and System Functionality	208
12.26. Encrypt Stored Passwords	208
12.27. Uniquely Identify Users and Processes	209
12.28. Verify remote disconnection of sessions	209
12.29. Automatically Remove or Disable Emergency Accounts within 72 Hours	209
12.30. Force Password Change at Next Logon	210
12.31. Automatically Remove or Disable Temporary User Accounts within 72 Hours	210
13. Permanent Findings	212
13.1. Off-Load Audit Records	212
13.2. Audit Record Reduction and Report Generation	212
13.3. Must Authenticate Before Establishing a Connection	212
13.4. Configure Automated Flaw Remediation	213
13.5. Limit Impact of Denial of Service Attacks	213
13.6. Protect Against Denial of Service Attacks by Ensuring Rate-Limiting Measures on Network Interfaces	214
13.7. Employ Automated Mechanisms for Account Management Functions	214
13.8. Require Devices to Reauthenticate when Changing Authenticators	214
13.9. Secure Name Address Resolution Service	215
13.10. Disable Wi-Fi When Connected to Ethernet	215
14. Not Applicable	216
14.1. Access Control for Mobile Devices	216
14.2. Configure the System to Uniquely Identify and Authenticate Non-Organizational Users	216
14.3. Information Input Validation	217
14.4. Managed Access Control Points	217
14.5. Non-Repudiation	218
14.6. Configure the System for Non-local Maintenance	218
15. Supplemental	219
15.1. Password Policy Supplemental	219

Chapter 1. Foreword

The macOS Security Compliance Project is an open source effort to provide a programmatic approach to generating security guidance. The configuration settings in this document were derived from National Institute of Standards and Technology (NIST) Special Publication (SP) 800-53, *Security and Privacy Controls for Information Systems and Organizations*, Revision 5.

This project can be used as a resource to easily create customized security baselines of technical security controls by leveraging a library of atomic actions which are mapped to the compliance requirements defined in NIST SP 800-53 (Rev. 5). It can also be used to develop customized guidance to meet the particular cybersecurity needs of any organization.

The objective of this effort was to simplify and radically accelerate the process of producing up-to-date macOS security guidance that is also accessible to any organization and tailorable to meet each organization's specific security needs.

Any and all risk based decisions to tailor the content produced by this project in order to meet the needs of a specific organization shall be approved by the responsible Information System Owner (ISO) and Authorizing Official (AO) and formally documented in their System Security Plan (SSP). While the project attempts to provide settings to meet compliance requirements, it is recommended that each rule be reviewed by your organization's Information System Security Officer (ISSO) prior to implementation.

Chapter 2. Scope

This guide describes the actions to take when securing a macOS 26.0 system against the Committee on National Security Systems Instruction No. 1253 (Moderate) security baseline.

Information System Security Officers and benchmark creators can use this catalog of settings in order to assist them in security benchmark creation. This list is a catalog, not a checklist or benchmark, and satisfaction of every item is not likely to be possible or sensible in many operational scenarios.

Chapter 3. Authors

macOS Security Compliance Project

Rob Lamb	Los Alamos National Laboratory
Ekkehard Koch	
Bob Gendler	National Institute of Standards and Technology

Chapter 4. Acronyms and Definitions

Table 1. Acronyms and Abbreviations

AES	Advanced Encryption Standard
ABM	Apple Business Manager
AFP	Apple Filing Protocol
ALF	Application Layer Firewall
AO	Authorizing Official
API	Application Programming Interface
ARD	Apple Remote Desktop
CA	Certificate Authority
CIS	Center for Internet Security
CMMC	Cybersecurity Maturity Model Certification
CNSSI	Committee on National Security Systems
CRL	Certificate Revocation List
DISA	Defense Information Systems Agency
DMA	Direct Memory Access
FISMA	Federal Information Security Modernization Act
FPKI	Federal Public Key Infrastructure
IR	Infrared
ISO	Information System Owner
ISSO	Information System Security Officer
MDM	Mobile Device Management
NASA	National Aeronautics and Space Administration
NFS	Network File System
NIST	National Institute of Standards and Technology
NSA	National Security Agency
OCSP	Online Certificate Status Protocol
ODV	Organization Defined Values
OS	Operating System
PF	Packet Filter
PIV	Personal Identity Verification
PIV-M	Personal Identity Verification Mandatory
PKI	Public Key Infrastructure
RBD	Risk Based Decision

SIP	System Integrity Protection
SMB	Server Message Block
SSH	Secure Shell
SSP	System Security Plan
STIG	Security Technical Implementation Guide
UAMDM	User Approved MDM
UUCP	Unix-to-Unix Copy Protocol

Table 2. Definitions

Baseline	A baseline is a predefined set of controls (also referred to as "a catalog" of settings) that address the protection needs of an organization's information systems. A baseline serves as a starting point for the creation of security benchmarks.
Benchmark	Benchmarks are a defined list of settings with values that an organization has defined.

Chapter 5. Applicable Documents

5.1. Government Documents

Table 3. National Institute of Standards and Technology (NIST)

Document Number or Descriptor	Document Title
NIST Special Publication 800-53 Rev 5	<i>NIST Special Publication 800-53 Rev 5.1.1</i>
NIST Special Publication 800-63	<i>NIST Special Publication 800-63</i>
NIST Special Publication 800-171	<i>NIST Special Publication 800-171 Rev 3</i>
NIST Special Publication 800-219	<i>NIST Special Publication 800-219 Rev 1</i>

Table 4. Defense Information Systems Agency (DISA)

Document Number or Descriptor	Document Title
STIG Ver 1, Rel 4	<i>Apple macOS 15 (Sequoia) STIG</i>

Table 5. Cybersecurity Maturity Model Certification (CMMC)

Document Number or Descriptor	Document Title
CMMC Model Overview v2.0	<i>Cybersecurity Maturity Model Certification (CMMC) Model Overview v2.0</i>

Table 6. Committee on National Security Systems (CNSS)

Document Number or Descriptor	Document Title
CNSSI No. 1253	<i>Security Categorization and Control Selection for National Security Systems</i>

5.2. Non-Government Documents

Table 7. Apple

Document Number or Descriptor	Document Title
Apple Platform Security Guide	<i>Apple Platform Security</i>
Apple Platform Deployment	<i>Apple Platform Deployment</i>
Apple Platform Certifications	<i>Apple Platform Certifications</i>
Profile-Specific Payload Keys	<i>Profile-Specific Payload Keys</i>

Table 8. Center for Internet Security

Document Number or Descriptor	Document Title
Apple macOS 15.0	<i>CIS Apple macOS 15.0 Benchmark version 1.1.0</i>

Chapter 6. Auditing

This section contains the configuration and enforcement of the OpenBSM settings.



The BSM Audit subsystem has been marked as deprecated by Apple.



The check/fix commands outlined in this section *MUST* be run with elevated privileges.

6.1. Configure Audit Log Files to Not Contain Access Control Lists

The audit log files *MUST* not contain access control lists (ACLs).

This rule ensures that audit information and audit files are configured to be readable and writable only by system administrators, thereby preventing unauthorized access, modification, and deletion of files.

To check the state of the system, run the following command(s):

```
/bin/ls -le $(/usr/bin/grep '^dir' /etc/security/audit_control | /usr/bin/awk -F: '{print $2}') | /usr/bin/awk '{print $1}' | /usr/bin/grep -c ":"
```

If the result is not **0**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/bin/chmod -RN /var/audit
```

ID	audit_acls_files_configure	
References	800-53r5	<ul style="list-style-type: none">AU-9
	CCE	<ul style="list-style-type: none">CCE-95101-2

6.2. Configure Audit Log Folder to Not Contain Access Control Lists

The audit log folder *MUST* not contain access control lists (ACLs).

Audit logs contain sensitive data about the system and users. This rule ensures that the audit

service is configured to create log folders that are readable and writable only by system administrators in order to prevent normal users from reading audit logs.

To check the state of the system, run the following command(s):

```
/bin/ls -lde /var/audit | /usr/bin/awk '{print $1}' | /usr/bin/grep -c ":"
```

If the result is not **0**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/bin/chmod -N /var/audit
```

ID	audit_acls_folders_configure	
References	800-53r5	<ul style="list-style-type: none">AU-9
	CCE	<ul style="list-style-type: none">CCE-95102-0

6.3. Enable Security Auditing

The information system *MUST* be configured to generate audit records.

Audit records establish what types of events have occurred, when they occurred, and which users were involved. These records aid an organization in their efforts to establish, correlate, and investigate the events leading up to an outage or attack.

The content required to be captured in an audit record varies based on the impact level of an organization's system. Content that may be necessary to satisfy this requirement includes, for example, time stamps, source addresses, destination addresses, user identifiers, event descriptions, success/fail indications, filenames involved, and access or flow control rules invoked.

The information system initiates session audits at system start-up.



Security auditing is NOT enabled by default on macOS Tahoe.

To check the state of the system, run the following command(s):

```
LAUNCHD_RUNNING=$(/bin/launchctl print system | /usr/bin/grep -c -E '\tcom.apple.auditd')
AUDITD_RUNNING=$(/usr/sbin/audit -c | /usr/bin/grep -c "AUC_AUDITING")
if [[ $LAUNCHD_RUNNING == 1 ]] && [[ -e /etc/security/audit_control ]] && [[
$AUDITD_RUNNING == 1 ]]; then
echo "pass"
```

```
else
    echo "fail"
fi
```

If the result is not **pass**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
if [[ ! -e /etc/security/audit_control ]] && [[ -e
/etc/security/audit_control.example ]];then
    /bin/cp /etc/security/audit_control.example /etc/security/audit_control
fi

/bin/launchctl enable system/com.apple.auditd
/bin/launchctl bootstrap system
/System/Library/LaunchDaemons/com.apple.auditd.plist
/usr/sbin/audit -i
```

ID	audit_audited_enabled	
References	800-53r5	<ul style="list-style-type: none">• AU-12, AU-12(1), AU-12(3)• AU-14(1)• AU-3, AU-3(1)• AU-8• CM-5(1)• MA-4(1)
CCE		<ul style="list-style-type: none">• CCE-95104-6

6.4. Configure Audit Capacity Warning

The audit service *MUST* be configured to notify the system administrator when the amount of free disk space remaining reaches an organization defined value.

This rule ensures that the system administrator is notified in advance that action is required to free up more disk space for audit logs.

To check the state of the system, run the following command(s):

```
/usr/bin/awk -F: '/^minfree/{print $2}' /etc/security/audit_control
```

If the result is not **25**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/usr/bin/sed -i.bak 's/.*minfree.*/minfree:25/' /etc/security/audit_control;  
/usr/sbin/audit -s
```

ID	audit_configure_capacity_notify	
References	800-53r5	<ul style="list-style-type: none">• AU-5(1)
	CCE	<ul style="list-style-type: none">• CCE-95105-3

6.5. Configure Audit_Control to Not Contain Access Control Lists

/etc/security/audit_control *MUST* not contain Access Control Lists (ACLs).

To check the state of the system, run the following command(s):

```
/bin/ls -le /etc/security/audit_control | /usr/bin/awk '{print $1}' | /usr/bin/grep -c ":"
```

If the result is not **0**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/bin/chmod -N /etc/security/audit_control
```

ID	audit_control_acls_configure	
References	800-53r5	<ul style="list-style-type: none">• AU-9
	CCE	<ul style="list-style-type: none">• CCE-95106-1

6.6. Configure Audit_Control Group to Wheel

/etc/security/audit_control *MUST* have the group set to wheel.

To check the state of the system, run the following command(s):

```
/bin/ls -dn /etc/security/audit_control | /usr/bin/awk '{print $4}'
```

If the result is not **0**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/usr/bin/chgrp wheel /etc/security/audit_control
```

ID	audit_control_group_configure	
References	800-53r5	<ul style="list-style-type: none">AU-9
	CCE	<ul style="list-style-type: none">CCE-95107-9

6.7. Configure Audit_Control Owner to Mode 440 or Less Permissive

`/etc/security/audit_control` *MUST* be configured so that it is readable only by the root user and group wheel.

To check the state of the system, run the following command(s):

```
/bin/ls -l /etc/security/audit_control | /usr/bin/awk '!/-r--[r-]-----\n|current|total/{print $1}' | /usr/bin/wc -l | /usr/bin/xargs
```

If the result is not **0**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/bin/chmod 440 /etc/security/audit_control
```

ID	audit_control_mode_configure	
References	800-53r5	<ul style="list-style-type: none">AU-9
	CCE	<ul style="list-style-type: none">CCE-95108-7

6.8. Configure Audit_Control Owner to Root

/etc/security/audit_control *MUST* have the owner set to root.

To check the state of the system, run the following command(s):

```
/bin/ls -dn /etc/security/audit_control | /usr/bin/awk '{print $3}'
```

If the result is not **0**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/usr/sbin/chown root /etc/security/audit_control
```

ID	audit_control_owner_configure	
References	800-53r5	<ul style="list-style-type: none">AU-9
	CCE	<ul style="list-style-type: none">CCE-95109-5

6.9. Configure System to Shut Down Upon Audit Failure

The audit service *MUST* be configured to shut down the computer if it is unable to audit system events.

Once audit failure occurs, user and system activity are no longer recorded, and malicious activity could go undetected. Audit processing failures can occur due to software/hardware errors, failures in the audit capturing mechanisms, and audit storage capacity being reached or exceeded.

To check the state of the system, run the following command(s):

```
/usr/bin/awk -F':|^policy| {print $NF} /etc/security/audit_control | /usr/bin/tr ',' '\n' | /usr/bin/grep -Ec 'ahlt'
```

If the result is not **1**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/usr/bin/sed -i.bak 's/^policy.*policy: ahlt,argv/' /etc/security/audit_control;
```

```
/usr/sbin/audit -s
```

ID	audit_failure_halt	
References	800-53r5	<ul style="list-style-type: none">• AU-5
	CCE	<ul style="list-style-type: none">• CCE-95111-1

6.10. Configure Audit Log Files Group to Wheel

Audit log files *MUST* have the group set to wheel.

The audit service *MUST* be configured to create log files with the correct group ownership to prevent normal users from reading audit logs.

Audit logs contain sensitive data about the system and users. If log files are set to be readable and writable only by system administrators, the risk is mitigated.

To check the state of the system, run the following command(s):

```
/bin/ls -n $(/usr/bin/grep '^dir' /etc/security/audit_control | /usr/bin/awk -F: '{print $2}') | /usr/bin/awk '{s+=$4} END {print s}'
```

If the result is not **0**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/usr/bin/chgrp -R wheel /var/audit/*
```

ID	audit_files_group_configure	
References	800-53r5	<ul style="list-style-type: none">• AU-9
	CCE	<ul style="list-style-type: none">• CCE-95112-9

6.11. Configure Audit Log Files to Mode 440 or Less Permissive

The audit service *MUST* be configured to create log files that are readable only by the root user and group wheel. To achieve this, audit log files *MUST* be configured to mode 440 or less permissive; thereby preventing normal users from reading, modifying or deleting audit logs.

To check the state of the system, run the following command(s):

```
/bin/ls -l $(/usr/bin/grep '^dir' /etc/security/audit_control | /usr/bin/awk -F: '{print $2}') | /usr/bin/awk '!/-r--r----|current|total/{print $1}' | /usr/bin/wc -l | /usr/bin/tr -d '\'
```

If the result is not **0**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/bin/chmod 440 /var/audit/*
```

ID	audit_files_mode_configure	
References	800-53r5	<ul style="list-style-type: none">• AU-9
	CCE	<ul style="list-style-type: none">• CCE-95113-7

6.12. Configure Audit Log Files to be Owned by Root

Audit log files *MUST* be owned by root.

The audit service *MUST* be configured to create log files with the correct ownership to prevent normal users from reading audit logs.

Audit logs contain sensitive data about the system and users. If log files are set to only be readable and writable by system administrators, the risk is mitigated.

To check the state of the system, run the following command(s):

```
/bin/ls -n $(/usr/bin/grep '^dir' /etc/security/audit_control | /usr/bin/awk -F: '{print $2}') | /usr/bin/awk '{s+=$3} END {print s}'
```

If the result is not **0**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/usr/sbin/chown -R root /var/audit/*
```

ID	audit_files_owner_configure	
References	800-53r5 CCE	<ul style="list-style-type: none"> AU-9 CCE-95114-5

6.13. Configure System to Audit All Authorization and Authentication Events

The auditing system *MUST* be configured to flag authorization and authentication (aa) events.

Authentication events contain information about the identity of a user, server, or client. Authorization events contain information about permissions, rights, and rules. If audit records do not include aa events, it is difficult to identify incidents and to correlate incidents to subsequent events.

Audit records can be generated from various components within the information system (e.g., via a module or policy filter).

To check the state of the system, run the following command(s):

```
/usr/bin/awk -F':|^/^flags/ { print $NF }' /etc/security/audit_control | /usr/bin/tr ',' '\n' | /usr/bin/grep -Ec 'aa'
```

If the result is not 1, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/usr/bin/grep -qE "^\$flags.*[^-]aa" /etc/security/audit_control || /usr/bin/sed -i.bak '/^\$flags/ s/$/,aa/' /etc/security/audit_control; /usr/sbin/audit -s
```

ID	audit_flags_aa_configure	
References	800-53r5 CCE	<ul style="list-style-type: none"> AC-2(12) AU-12 AU-2 CM-5(1) MA-4(1) CCE-95115-2

6.14. Configure System to Audit All Administrative Action Events

The auditing system *MUST* be configured to flag administrative action (ad) events.

Administrative action events include changes made to the system (e.g. modifying authentication policies). If audit records do not include ad events, it is difficult to identify incidents and to correlate incidents to subsequent events.

Audit records can be generated from various components within the information system (e.g., via a module or policy filter).

The information system audits the execution of privileged functions.



We recommend changing the line "43127:AUE_MAC_SYSCALL:mac_syscall(2):ad" to "43127:AUE_MAC_SYSCALL:mac_syscall(2):zz" in the file /etc/security/audit_event. This will prevent sandbox violations from being audited by the ad flag.

To check the state of the system, run the following command(s):

```
/usr/bin/awk -F':' '/^flags/ { print $NF }' /etc/security/audit_control | /usr/bin/tr ',' '\n' | /usr/bin/grep -Ec 'ad'
```

If the result is not 1, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/usr/bin/grep -qE "^flags.*[^-]ad" /etc/security/audit_control || /usr/bin/sed -i.bak '/^flags/ s/$/,ad/' /etc/security/audit_control; /usr/sbin/audit -s
```

ID	audit_flags_ad_configure	
References	800-53r5	<ul style="list-style-type: none">AC-2(12), AC-2(4)AC-6(9)AU-12AU-2CM-5(1)MA-4(1)
CCE		<ul style="list-style-type: none">CCE-95116-0

6.15. Configure System to Audit All Failed Program Execution on the System

The audit system *MUST* be configured to record enforcement actions of access restrictions, including failed program execute (-ex) attempts.

Enforcement actions are the methods or mechanisms used to prevent unauthorized access and/or changes to configuration settings. One common and effective enforcement action method is using program execution restrictions (e.g., denying users access to execute certain processes).

This configuration ensures that audit lists include events in which program execution has failed. Without auditing the enforcement of program execution, it is difficult to identify attempted attacks, as there is no audit trail available for forensic investigation.

To check the state of the system, run the following command(s):

```
/usr/bin/awk -F':' '/^flags/ { print $NF }' /etc/security/audit_control | /usr/bin/tr ',' '\n' | /usr/bin/grep -Ec '\-ex'
```

If the result is not 1, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/usr/bin/grep -qE "^flags.*-ex" /etc/security/audit_control || /usr/bin/sed -i.bak '^flags/ s/$/-ex/' /etc/security/audit_control; /usr/sbin/audit -s
```

ID	audit_flags_ex_configure	
References	800-53r5	<ul style="list-style-type: none">• AC-2(12)• AU-12• AU-2• CM-5(1)
	CCE	<ul style="list-style-type: none">• CCE-95117-8

6.16. Configure System to Audit All Deletions of Object Attributes

The audit system *MUST* be configured to record enforcement actions of attempts to delete file attributes (fd).

***Enforcement actions are the methods or mechanisms used to prevent unauthorized changes to

configuration settings. One common and effective enforcement action method is using access restrictions (i.e., denying modifications to a file by applying file permissions).

This configuration ensures that audit lists include events in which enforcement actions prevent attempts to delete a file.

Without auditing the enforcement of access restrictions, it is difficult to identify attempted attacks, as there is no audit trail available for forensic investigation.

To check the state of the system, run the following command(s):

```
/usr/bin/awk -F':' '/^flags/ { print $NF }' /etc/security/audit_control | /usr/bin/tr ',' '\n' | /usr/bin/grep -Ec '\-fd'
```

If the result is not **1**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/usr/bin/grep -qE "^flags.*-fd" /etc/security/audit_control || /usr/bin/sed -i.bak '/^flags/ s/$/-fd/' /etc/security/audit_control;/usr/sbin/audit -s
```

ID	audit_flags_fd_configure	
References	800-53r5	<ul style="list-style-type: none">• AC-2(12)• AU-12• AU-2• AU-9• CM-5(1)• MA-4(1)• CCE-95118-6
CCE		

6.17. Configure System to Audit All Changes of Object Attributes

The audit system *MUST* be configured to record enforcement actions of attempts to modify file attributes (fm).

Enforcement actions are the methods or mechanisms used to prevent unauthorized changes to configuration settings. One common and effective enforcement action method is using access restrictions (i.e., modifications to a file by applying file permissions).

This configuration ensures that audit lists include events in which enforcement actions attempts to modify a file.

Without auditing the enforcement of access restrictions, it is difficult to identify attempted attacks, as there is no audit trail available for forensic investigation.

To check the state of the system, run the following command(s):

```
/usr/bin/awk -F':|^flags/ { print $NF }' /etc/security/audit_control | /usr/bin/tr '\n' '' | /usr/bin/grep -Ec '^fm'
```

If the result is not 1, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/usr/bin/grep -qE "^flags.*fm" /etc/security/audit_control || /usr/bin/sed -i.bak '/^flags/ s/$/,fm/' /etc/security/audit_control;/usr/sbin/audit -s
```

ID	audit_flags_fm_configure	
References	800-53r5	<ul style="list-style-type: none">AC-2(12)AU-12AU-2AU-9CM-5(1)MA-4(1)
CCE		<ul style="list-style-type: none">CCE-95119-4

6.18. Configure System to Audit All Failed Change of Object Attributes

The audit system *MUST* be configured to record enforcement actions of failed attempts to modify file attributes (-fm).

Enforcement actions are the methods or mechanisms used to prevent unauthorized changes to configuration settings. One common and effective enforcement action method is using access restrictions (i.e., denying modifications to a file by applying file permissions).

This configuration ensures that audit lists include events in which enforcement actions prevent attempts to modify a file.

Without auditing the enforcement of access restrictions, it is difficult to identify attempted attacks, as there is no audit trail available for forensic investigation.

To check the state of the system, run the following command(s):

```
/usr/bin/awk -F':' '/^flags/ { print $NF }' /etc/security/audit_control | /usr/bin/tr ',' '\n' | /usr/bin/grep -Ec '\-fm'
```

If the result is not 1, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/usr/bin/grep -qE "^flags.*-fm" /etc/security/audit_control || /usr/bin/sed -i.bak '/^flags/ s/$/-fm/' /etc/security/audit_control;/usr/sbin/audit -s
```

ID	audit_flags_fm_failed_configure	
References	800-53r5	<ul style="list-style-type: none">AC-2(12)AU-12AU-2AU-9CM-5(1)MA-4(1)
CCE		<ul style="list-style-type: none">CCE-95120-2

6.19. Configure System to Audit All Failed Read Actions on the System

The audit system *MUST* be configured to record enforcement actions of access restrictions, including failed file read (-fr) attempts.

Enforcement actions are the methods or mechanisms used to prevent unauthorized access and/or changes to configuration settings. One common and effective enforcement action method is using access restrictions (e.g., denying access to a file by applying file permissions).

This configuration ensures that audit lists include events in which enforcement actions prevent attempts to read a file.

Without auditing the enforcement of access restrictions, it is difficult to identify attempted attacks, as there is no audit trail available for forensic investigation.

To check the state of the system, run the following command(s):

```
/usr/bin/awk -F':' '/^flags/ { print $NF }' /etc/security/audit_control | /usr/bin/tr ',' '\n' | /usr/bin/grep -Ec '\-fr'
```

If the result is not 1, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/usr/bin/grep -qE "^flags.*-fr" /etc/security/audit_control || /usr/bin/sed -i.bak '^flags/ s/$/-fr/' /etc/security/audit_control;/usr/sbin/audit -s
```

ID	audit_flags_fr_configure	
References	800-53r5	<ul style="list-style-type: none">AC-2(12)AU-12AU-2AU-9CM-5(1)MA-4(1)
CCE		• CCE-95121-0

6.20. Configure System to Audit All Failed Write Actions on the System

The audit system *MUST* be configured to record enforcement actions of access restrictions, including failed file write (-fw) attempts.

Enforcement actions are the methods or mechanisms used to prevent unauthorized access and/or changes to configuration settings. One common and effective enforcement action method is using access restrictions (e.g., denying users access to edit a file by applying file permissions).

This configuration ensures that audit lists include events in which enforcement actions prevent attempts to change a file.

Without auditing the enforcement of access restrictions, it is difficult to identify attempted attacks, as there is no audit trail available for forensic investigation.

To check the state of the system, run the following command(s):

```
/usr/bin/awk -F':' '/^flags/ { print $NF }' /etc/security/audit_control | /usr/bin/tr ',' '\n' | /usr/bin/grep -Ec '\-fw'
```

If the result is not **1**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/usr/bin/grep -qE "^flags.*-fw" /etc/security/audit_control || /usr/bin/sed -i.bak '/^flags/ s/$/-fw/' /etc/security/audit_control;/usr/sbin/audit -s
```

ID	audit_flags_fw_configure	
References	800-53r5	<ul style="list-style-type: none">AC-2(12)AU-12AU-2AU-9CM-5(1)MA-4(1)CCE-95122-8
	CCE	

6.21. Configure System to Audit All Log In and Log Out Events

The audit system *MUST* be configured to record all attempts to log in and out of the system (lo).

Frequently, an attacker that successfully gains access to a system has only gained access to an account with limited privileges, such as a guest account or a service account. The attacker must attempt to change to another user account with normal or elevated privileges in order to proceed. Auditing both successful and unsuccessful attempts to switch to another user account (by way of monitoring login and logout events) mitigates this risk.

The information system monitors login and logout events.

To check the state of the system, run the following command(s):

```
/usr/bin/awk -F':' '/^flags/ { print $NF }' /etc/security/audit_control | /usr/bin/tr ',' '\n' | /usr/bin/grep -Ec '^lo'
```

If the result is not **1**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/usr/bin/grep -qE "^flags.*[^-]lo" /etc/security/audit_control || /usr/bin/sed -i.bak '/^flags/ s/$/,lo/' /etc/security/audit_control; /usr/sbin/audit -s
```

ID	audit_flags_lo_configure	
References	800-53r5	<ul style="list-style-type: none">• AC-17(1)• AC-2(12)• AU-12• AU-2• MA-4(1)
CCE		• CCE-95123-6

6.22. Configure Audit Log Folders Group to Wheel

Audit log files *MUST* have the group set to wheel.

The audit service *MUST* be configured to create log files with the correct group ownership to prevent normal users from reading audit logs.

Audit logs contain sensitive data about the system and users. If log files are set to be readable and writable only by system administrators, the risk is mitigated.

To check the state of the system, run the following command(s):

```
/bin/ls -dn $(/usr/bin/grep '^dir' /etc/security/audit_control | /usr/bin/awk -F: '{print $2}') | /usr/bin/awk '{print $4}'
```

If the result is not **0**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/usr/bin/chgrp wheel /var/audit
```

ID	audit_folder_group_configure
----	------------------------------

References	800-53r5	• AU-9
	CCE	• CCE-95124-4

6.23. Configure Audit Log Folders to be Owned by Root

Audit log folders *MUST* be owned by root.

The audit service *MUST* be configured to create log folders with the correct ownership to prevent normal users from reading audit logs.

Audit logs contain sensitive data about the system and users. If log folders are set to only be readable and writable by system administrators, the risk is mitigated.

To check the state of the system, run the following command(s):

```
/bin/ls -dn $(/usr/bin/grep '^dir' /etc/security/audit_control | /usr/bin/awk -F: '{print $2}') | /usr/bin/awk '{print $3}'
```

If the result is not **0**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/usr/sbin/chown root /var/audit
```

ID	audit_folder_owner_configure	
References	800-53r5	• AU-9
	CCE	• CCE-95125-1

6.24. Configure Audit Log Folders to Mode 700 or Less Permissive

The audit log folder *MUST* be configured to mode 700 or less permissive so that only the root user is able to read, write, and execute changes to folders.

Because audit logs contain sensitive data about the system and users, the audit service *MUST* be configured to mode 700 or less permissive; thereby preventing normal users from reading, modifying or deleting audit logs.

To check the state of the system, run the following command(s):

```
/usr/bin/stat -f %A $(/usr/bin/grep '^dir' /etc/security/audit_control | /usr/bin/awk -F: '{print $2}')
```

If the result is not **700**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/bin/chmod 700 /var/audit
```

ID	audit_folders_mode_configure	
References	800-53r5	<ul style="list-style-type: none">• AU-9
	CCE	<ul style="list-style-type: none">• CCE-95126-9

6.25. Configure Audit Retention to 7d

The audit service *MUST* be configured to require records be kept for a organizational defined value before deletion, unless the system uses a central audit record storage facility.

When "expire-after" is set to "7d", the audit service will not delete audit logs until the log data criteria is met.

To check the state of the system, run the following command(s):

```
/usr/bin/awk -F: '/expire-after/{print $2}' /etc/security/audit_control
```

If the result is not **7d**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/usr/bin/sed -i.bak 's/^expire-after.*/expire-after:7d/' /etc/security/audit_control; /usr/sbin/audit -s
```

ID	audit_retention_configure
-----------	---------------------------

References	800-53r5	<ul style="list-style-type: none">• AU-11• AU-4
	CCE	<ul style="list-style-type: none">• CCE-95130-1

6.26. Configure Audit Failure Notification

The audit service *MUST* be configured to immediately print messages to the console or email administrator users when an auditing failure occurs.

It is critical for the appropriate personnel to be made aware immediately if a system is at risk of failing to process audit logs as required. Without a real-time alert, security personnel may be unaware of a potentially harmful failure in the auditing system's capability, and system operation may be adversely affected.

To check the state of the system, run the following command(s):

```
/usr/bin/grep -c "logger -s -p" /etc/security/audit_warn
```

If the result is not **1**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/usr/bin/sed -i.bak 's/logger -p/logger -s -p/' /etc/security/audit_warn;  
/usr/sbin/audit -s
```

ID	audit_settings_failure_notify	
References	800-53r5	<ul style="list-style-type: none">• AU-5, AU-5(2)
	CCE	<ul style="list-style-type: none">• CCE-95131-9

Chapter 7. Authentication

This section contains the configuration of authentication settings, including the enforcement of smartcard authentication.



See additional guidance in the Smartcard Supplemental.



The check/fix commands outlined in this section must be run with elevated privileges.

7.1. Enforce Multifactor Authentication for Login

The system *MUST* be configured to enforce multifactor authentication.

All users *MUST* go through multifactor authentication to prevent unauthenticated access and potential compromise to the system.



Modification of Pluggable Authentication Modules (PAM) now require user authorization, or use of a Privacy Preferences Policy Control (PPPC) profile from MDM that authorizes modifying system administrator files or full disk access.



/etc/pam.d/login will be automatically modified to its original state following any update or major upgrade to the operating system.

To check the state of the system, run the following command(s):

```
/usr/bin/grep -Ec  
'^(auth\s+sufficient\s+pam_smartcard.so|auth\s+required\s+pam_deny.so)'  
/etc/pam.d/login
```

If the result is not 2, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/bin/cat > /etc/pam.d/login << LOGIN_END  
# login: auth account password session  
auth      sufficient    pam_smartcard.so  
auth      optional     pam_krb5.so use_kcminit  
auth      optional     pam_ntlm.so try_first_pass  
auth      optional     pam_mount.so try_first_pass  
auth      required     pam_opendirectory.so try_first_pass  
auth      required     pam_deny.so  
account   required     pam_nologin.so
```

```
account    required    pam.opendirectory.so
password   required    pam.opendirectory.so
session    required    pam_launchd.so
session    required    pam_uwtmp.so
session    optional    pam_mount.so
LOGIN_END
```

```
/bin/chmod 644 /etc/pam.d/login
/usr/sbin/chown root:wheel /etc/pam.d/login
```

ID	auth_pam_login_smartcard_enforce	
References	800-53r5	<ul style="list-style-type: none">• IA-2(1), IA-2(2), IA-2(8)
	CCE	<ul style="list-style-type: none">• CCE-95132-7

7.2. Enforce Multifactor Authentication for the su Command

The system *MUST* be configured such that, when the `su` command is used, multifactor authentication is enforced.

All users *MUST* go through multifactor authentication to prevent unauthenticated access and potential compromise to the system.



Modification of Pluggable Authentication Modules (PAM) now require user authorization, or use of a Privacy Preferences Policy Control (PPPC) profile from MDM that authorizes modifying system administrator files or full disk access.



`/etc/pam.d/su` will be automatically modified to its original state following any update or major upgrade to the operating system.

To check the state of the system, run the following command(s):

```
/usr/bin/grep -Ec
'^(\bauth\b+s+sufficient\b+s+pam_smartcard.so\b|\bauth\b+s+required\b+s+pam_rootok.so\b)'
/etc/pam.d/su
```

If the result is not 2, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```

/bin/cat > /etc/pam.d/su << SU_END
# su: auth account password session
auth sufficient pam_smartcard.so
auth required pam_rootok.so
auth required pam_group.so no_warn group=admin,wheel ruser root_only
fail_safe
account required pam_permit.so
account required pam.opendirectory.so no_check_shell
password required pam.opendirectory.so
session required pam_launchd.so
SU_END

# Fix new file ownership and permissions
/bin/chmod 644 /etc/pam.d/su
/usr/sbin/chown root:wheel /etc/pam.d/su

```

ID	auth_pam_su_smartcard_enforce	
References	800-53r5	<ul style="list-style-type: none"> • IA-2(1), IA-2(2), IA-2(8)
	CCE	<ul style="list-style-type: none"> • CCE-95133-5

7.3. Enforce Multifactor Authentication for Privilege Escalation Through the sudo Command

The system *MUST* be configured to enforce multifactor authentication when the sudo command is used to elevate privilege.

All users *MUST* go through multifactor authentication to prevent unauthenticated access and potential compromise to the system.



Modification of Pluggable Authentication Modules (PAM) now require user authorization, or use of a Privacy Preferences Policy Control (PPPC) profile from MDM that authorizes modifying system administrator files or full disk access.



/etc/pam.d/sudo will be automatically modified to its original state following any update or major upgrade to the operating system.

To check the state of the system, run the following command(s):

```

/usr/bin/grep -Ec
'^(auth\s+sufficient\s+pam_smartcard.so|auth\s+required\s+pam_deny.so)'
/etc/pam.d/sudo

```

If the result is not 2, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/bin/cat > /etc/pam.d/sudo << SUDO_END
# sudo: auth account password session
auth      sufficient  pam_smartcard.so
auth      required    pam_opendirectory.so
auth      required    pam_deny.so
account   required    pam_permit.so
password  required    pam_deny.so
session   required    pam_permit.so
SUDO_END

/bin/chmod 444 /etc/pam.d/sudo
/usr/sbin/chown root:wheel /etc/pam.d/sudo
```

ID	auth_pam_sudo_smartcard_enforce	
References	800-53r5 CCE	<ul style="list-style-type: none">IA-2(1), IA-2(2), IA-2(8)CCE-95134-3

7.4. Allow Smartcard Authentication

Smartcard authentication *MUST* be allowed.

The use of smartcard credentials facilitates standardization and reduces the risk of unauthorized access.

When enabled, the smartcard can be used for login, authorization, and screen saver unlocking.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.security.smartcard')\
.objectForKey('allowSmartCard').js
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the

(com.apple.security.smartcard) payload type:

```
<key>allowSmartCard</key>
<true/>
```

ID	auth_smartcard_allow	
References	800-53r5	<ul style="list-style-type: none">• IA-2(1), IA-2(12), IA-2(2)
	CCE	<ul style="list-style-type: none">• CCE-95135-0

7.5. Set Smartcard Certificate Trust to High

The macOS system *MUST* be configured to block access to users who are no longer authorized (i.e., users with revoked certificates).

To prevent the use of untrusted certificates, the certificates on a smartcard card *MUST* meet the following criteria: its issuer has a system-trusted certificate, the certificate is not expired, its "valid-after" date is in the past, and it passes Certificate Revocation List (CRL) and Online Certificate Status Protocol (OCSP) checking.

By setting the smartcard certificate trust level to high, the system will execute a hard revocation, i.e., a network connection is required. A verified positive response from the OSCP/CRL server is required for authentication to succeed.



Before applying this setting, please see the smartcard supplemental guidance.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.security.smartcard')\
.objectForKey('checkCertificateTrust').js
EOS
```

If the result is not 3, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.security.smartcard) payload type:

```
<key>checkCertificateTrust</key>
<integer>3</integer>
```

ID	auth_smartcard_certificate_trust_enforce_high	
References	800-53r5	<ul style="list-style-type: none"> • IA-5(2) • SC-17 <p>CCE</p> <ul style="list-style-type: none"> • CCE-95136-8

7.6. Set Smartcard Certificate Trust to Moderate

The macOS system *MUST* be configured to block access to users who are no longer authorized (i.e., users with revoked certificates).

To prevent the use of untrusted certificates, the certificates on a smartcard card *MUST* meet the following criteria: its issuer has a system-trusted certificate, the certificate is not expired, its "valid-after" date is in the past, and it passes Certificate Revocation List (CRL) and Online Certificate Status Protocol (OCSP) checking.

By setting the smartcard certificate trust level to moderate, the system will execute a soft revocation, i.e., if the OCSP/CRL server is unreachable, authentication will still succeed.



Before applying this setting, please see the smartcard supplemental guidance.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.security.smartcard')\
.objectForKey('checkCertificateTrust').js
EOS
```

If the result is not 2, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.security.smartcard) payload type:

```
<key>checkCertificateTrust</key>
<integer>2</integer>
```

ID	auth_smartcard_certificate_trust_enforce_moderate
-----------	---

References	800-53r5	<ul style="list-style-type: none">• IA-5(2)• SC-17
	CCE	<ul style="list-style-type: none">• CCE-95137-6

7.7. Enforce Smartcard Authentication

Smartcard authentication *MUST* be enforced.

The use of smartcard credentials facilitates standardization and reduces the risk of unauthorized access.

When `enforceSmartCard` is set to "true", the smartcard must be used for login, authorization, and unlocking the screensaver.



`enforceSmartCard` will apply to the whole system. No users will be able to login with their password unless the profile is removed or a user is exempt from smartcard enforcement.



`enforceSmartcard` requires `allowSmartcard` to be set to true in order to work.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.security.smartcard')\
.objectForKey('enforceSmartCard').js
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.security.smartcard) payload type:

```
<key>enforceSmartCard</key>
<true/>
<key>allowSmartCard</key>
<true/>
```

ID	auth_smartcard_enforce
-----------	------------------------

References	800-53r5	<ul style="list-style-type: none"> • IA-2, IA-2(1), IA-2(12), IA-2(2), IA-2(6), IA-2(8) • IA-5(2)
	CCE	<ul style="list-style-type: none"> • CCE-95138-4

7.8. Disable Password Authentication for SSH

If remote login through SSH is enabled, password based authentication *MUST* be disabled for user login.

All users *MUST* go through multifactor authentication to prevent unauthenticated access and potential compromise to the system.



/etc/ssh/sshd_config will be automatically modified to its original state following any update or major upgrade to the operating system.

To check the state of the system, run the following command(s):

```
/usr/sbin/sshd -G | /usr/bin/grep -Ec
'^passwordauthentication\s+no|kbdinteractiveauthentication\s+no'
```

If the result is not 2, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
include_dir=$(./usr/bin/awk '/^Include/ {print $2}' /etc/ssh/sshd_config |
/usr/bin/tr -d '*')
if [[ -z $include_dir ]]; then
    /usr/bin/sed -i.bk "1s/>.*/Include \\\etc\\ssh\\sshd_config.d\\\*/"
/etc/ssh/sshd_config
fi
echo "passwordauthentication no" >> "${include_dir}01-mscp-sshd.conf"
echo "kbdinteractiveauthentication no" >> "${include_dir}01-mscp-sshd.conf"

for file in $(ls ${include_dir}); do
    if [[ "$file" == "100-macos.conf" ]]; then
        continue
    fi
    if [[ "$file" == "01-mscp-sshd.conf" ]]; then
        break
    fi
    /bin/mv ${include_dir}${file} ${include_dir}20-${file}
done
```

ID	auth_ssh_password_authentication_disable	
References	800-53r5	<ul style="list-style-type: none">• IA-2, IA-2(1), IA-2(2), IA-2(6), IA-2(8)• IA-5(2)• MA-4
	CCE	<ul style="list-style-type: none">• CCE-95139-2

Chapter 8. iCloud

This section contains the configuration and enforcement of iCloud and the Apple ID service settings.



The check/fix commands outlined in this section *MUST* be run by a user with elevated privileges.

8.1. Disable iCloud Address Book

The macOS built-in Contacts.app connection to Apple's iCloud service *MUST* be disabled.

Apple's iCloud service does not provide an organization with enough control over the storage and access of data, and, therefore, automated contact synchronization *MUST* be controlled by an organization approved service.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowCloudAddressBook').js
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowCloudAddressBook</key>
<false/>
```

ID	icloud_addressbook_disable	
References	800-53r5	<ul style="list-style-type: none">AC-20, AC-20(1)CM-7, CM-7(1)SC-7(10)
	CCE	<ul style="list-style-type: none">CCE-95140-0

8.2. Disable the System Setting for Apple ID

The system setting for Apple ID *MUST* be disabled.

Disabling the system setting prevents login to Apple ID and iCloud.

To check the state of the system, run the following command(s):

```
/usr/bin/profiles show -output stdout-xml | /usr/bin/xmllint --xpath  
'//key[text()="DisabledSystemSettings"]/following-sibling::*[1]' - | /usr/bin/grep -c  
"com.apple.systempreferences.AppleIDSettings"
```

If the result is not **1**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.systempreferences) payload type:

```
<key>DisabledSystemSettings</key>  
<array>  
    <string>com.apple.systempreferences.AppleIDSettings</string>  
</array>
```

ID	icloud_appleid_system_settings_disable	
References	800-53r5	<ul style="list-style-type: none">• AC-20, AC-20(1)• CM-7, CM-7(1)
	CCE	<ul style="list-style-type: none">• CCE-95141-8

8.3. Disable iCloud Bookmarks

The macOS built-in Safari.app bookmark synchronization via the iCloud service *MUST* be disabled.

Apple's iCloud service does not provide an organization with enough control over the storage and access of data and, therefore, automated bookmark synchronization *MUST* be controlled by an organization approved service.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS  
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\n.objectForKey('allowCloudBookmarks').js
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowCloudBookmarks</key>
<false/>
```

ID	icloud_bookmarks_disable	
References	800-53r5	<ul style="list-style-type: none"> • AC-20, AC-20(1) • CM-7, CM-7(1) • SC-7(10)
	CCE	<ul style="list-style-type: none"> • CCE-95142-6

8.4. Disable the iCloud Calendar Services

The macOS built-in Calendar.app connection to Apple's iCloud service *MUST* be disabled.

Apple's iCloud service does not provide an organization with enough control over the storage and access of data and, therefore, automated calendar synchronization *MUST* be controlled by an organization approved service.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowCloudCalendar').js
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowCloudCalendar</key>
<false/>
```

ID	icloud_calendar_disable	
References	800-53r5	<ul style="list-style-type: none">• AC-20, AC-20(1)• CM-7, CM-7(1)• SC-7(10)
CCE		<ul style="list-style-type: none">• CCE-95143-4

8.5. Disable iCloud Document Sync

The macOS built-in iCloud document synchronization service *MUST* be disabled to prevent organizational data from being synchronized to personal or non-approved storage.

Apple's iCloud service does not provide an organization with enough control over the storage and access of data and, therefore, automated document synchronization *MUST* be controlled by an organization approved service.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowCloudDocumentSync').js
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowCloudDocumentSync</key>
<false/>
```

ID	icloud_drive_disable
----	----------------------

References	800-53r5	<ul style="list-style-type: none"> • AC-20, AC-20(1) • CM-7, CM-7(1) • SC-7(10)
	CCE	<ul style="list-style-type: none"> • CCE-95144-2

8.6. Disable the iCloud Freeform Services

The macOS built-in Freeform.app connection to Apple's iCloud service *MUST* be disabled.

Apple's iCloud service does not provide an organization with enough control over the storage and access of data and, therefore, automated calendar synchronization *MUST* be controlled by an organization approved service.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowCloudFreeform').js
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowCloudFreeform</key>
<false/>
```

ID	icloud_freeform_disable	
References	800-53r5	<ul style="list-style-type: none"> • AC-20, AC-20(1) • CM-7, CM-7(1) • SC-7(10)
	CCE	<ul style="list-style-type: none"> • CCE-95145-9

8.7. Disable iCloud Game Center

This works only with supervised devices (MDM) and allows to disable Apple Game Center. The

rationale is Game Center is using Apple ID and will shared data on AppleID based services, therefore, Game Center *MUST* be disabled. This setting also prohibits functionality of adding friends to Game Center.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowGameCenter').js
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowGameCenter</key>
<false/>
```

ID	icloud_game_center_disable	
References	800-53r5	<ul style="list-style-type: none">• AC-20, AC-20(1)• CM-7, CM-7(1)• SC-7(10)• CCE-95146-7
	CCE	

8.8. Disable iCloud Keychain Sync

The macOS system's ability to automatically synchronize a user's passwords to their iCloud account *MUST* be disabled.

Apple's iCloud service does not provide an organization with enough control over the storage and access of data and, therefore, password management and synchronization *MUST* be controlled by an organization approved service.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowCloudKeychainSync').js
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowCloudKeychainSync</key>
<false/>
```

ID	icloud_keychain_disable	
References	800-53r5	<ul style="list-style-type: none"> • AC-20, AC-20(1) • CM-7, CM-7(1) • SC-7(10) • CCE-95147-5
	CCE	

8.9. Disable iCloud Mail

The macOS built-in Mail.app connection to Apple's iCloud service *MUST* be disabled.

Apple's iCloud service does not provide an organization with enough control over the storage and access of data and, therefore, automated mail synchronization *MUST* be controlled by an organization approved service.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowCloudMail').js
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowCloudMail</key>
<false/>
```

ID	icloud_mail_disable	
References	800-53r5	<ul style="list-style-type: none">• AC-20, AC-20(1)• CM-7, CM-7(1)• SC-7(10)
	CCE	<ul style="list-style-type: none">• CCE-95148-3

8.10. Disable iCloud Notes

The macOS built-in Notes.app connection to Apple's iCloud service *MUST* be disabled.

Apple's iCloud service does not provide an organization with enough control over the storage and access of data and, therefore, automated Notes synchronization *MUST* be controlled by an organization approved service.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowCloudNotes').js
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowCloudNotes</key>
<false/>
```

ID	icloud_notes_disable
----	----------------------

References	800-53r5	<ul style="list-style-type: none"> • AC-20, AC-20(1) • CM-7, CM-7(1) • SC-7(10)
	CCE	<ul style="list-style-type: none"> • CCE-95149-1

8.11. Disable iCloud Photo Library

The macOS built-in Photos.app connection to Apple's iCloud service *MUST* be disabled.

Apple's iCloud service does not provide an organization with enough control over the storage and access of data and, therefore, automated photo synchronization *MUST* be controlled by an organization approved service.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowCloudPhotoLibrary').js
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowCloudPhotoLibrary</key>
<false/>
```

ID	icloud_photos_disable	
References	800-53r5	<ul style="list-style-type: none"> • AC-20, AC-20(1) • CM-7, CM-7(1) • SC-7(10)
	CCE	<ul style="list-style-type: none"> • CCE-95150-9

8.12. Disable iCloud Private Relay

Enterprise networks may be required to audit all network traffic by policy, therefore, iCloud Private

Relay *MUST* be disabled.

Network administrators can also prevent the use of this feature by blocking DNS resolution of mask.icloud.com and mask-h2.icloud.com.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowCloudPrivateRelay').js
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowCloudPrivateRelay</key>
<false/>
```

ID	icloud_private_relay_disable	
References	800-53r5	<ul style="list-style-type: none">• AC-20, AC-20(1)• CM-7, CM-7(1)• SC-7(10)
	CCE	<ul style="list-style-type: none">• CCE-95151-7

8.13. Disable iCloud Reminders

The macOS built-in Reminders.app connection to Apple's iCloud service *MUST* be disabled.

Apple's iCloud service does not provide an organization with enough control over the storage and access of data and, therefore, automated reminders synchronization *MUST* be controlled by an organization approved service.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowCloudReminders').js
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowCloudReminders</key>
<false/>
```

ID	icloud_reminders_disable	
References	800-53r5 CCE	<ul style="list-style-type: none"> • AC-20, AC-20(1) • CM-7, CM-7(1) • SC-7(10) • CCE-95152-5

8.14. Disable iCloud Desktop and Document Folder Sync

The macOS system's ability to automatically synchronize a user's desktop and documents folder to their iCloud Drive *MUST* be disabled.

Apple's iCloud service does not provide an organization with enough control over the storage and access of data and, therefore, automated file synchronization *MUST* be controlled by an organization approved service.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowCloudDesktopAndDocuments').js
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowCloudDesktopAndDocuments</key>
<false/>
```

ID	icloud_sync_disable	
References	800-53r5	<ul style="list-style-type: none">• AC-20, AC-20(1)• CM-7, CM-7(1)• SC-7(10)
	CCE	<ul style="list-style-type: none">• CCE-95153-3

Chapter 9. macOS

This section contains the configuration and enforcement of operating system settings.



The check/fix commands outlined in this section *MUST* be run by a user with elevated privileges.

9.1. Disable AppleID and Internet Account Modifications

The system *MUST* disable account modification.

Account modification includes adding additional or modifying internet accounts in Apple Mail, Calendar, Contacts, in the Internet Account System Setting Pane, or the AppleID System Setting Pane.

This prevents the addition of unauthorized accounts.



Some organizations may allow the use and configuration of the built-in Mail.app, Calendar.app, and Contacts.app for organizational communication. Information System Security Officers (ISSOs) may make the risk-based decision not to disable the Internet Accounts System Preference pane to avoid losing this functionality, but they are advised to first fully weigh the potential risks posed to their organization.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowAccountModification').js
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowAccountModification</key>
<false/>
```

ID	os_account_modification_disable	
References	800-53r5 CCE	<ul style="list-style-type: none"> • AC-20, AC-20(1) • CM-7, CM-7(1) • CCE-95155-8

9.2. Disable AirDrop

AirDrop *MUST* be disabled to prevent file transfers to or from unauthorized devices. AirDrop allows users to share and receive files from other nearby Apple devices.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowAirDrop').js
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowAirDrop</key>
<false/>
```

ID	os_airdrop_disable	
References	800-53r5 CCE	<ul style="list-style-type: none"> • AC-20 • AC-3 • CM-7, CM-7(1) • CCE-95156-6

9.3. Disable Apple ID Setup during Setup Assistant

The prompt for Apple ID setup during Setup Assistant *MUST* be disabled.

macOS will automatically prompt new users to set up an Apple ID while they are going through Setup Assistant if this is not disabled, misleading new users to think they need to create Apple ID

accounts upon their first login.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript 2>/dev/null << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.SetupAssistant.managed')\
.objectForKey('SkipSetupItems').containsObject("AppleID")
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.SetupAssistant.managed) payload type:

```
<key>SkipSetupItems</key>
<array>
    <string>AppleID</string>
</array>
```

ID	os_appleid_prompt_disable	
References	800-53r5 CCE	<ul style="list-style-type: none">• AC-20• CCE-95159-0

9.4. Configure Apple System Log Files Owned by Root and Group to Wheel

The Apple System Logs (ASL) *MUST* be owned by root.

ASL logs contain sensitive data about the system and users. If ASL log files are set to only be readable and writable by system administrators, the risk is mitigated.

To check the state of the system, run the following command(s):

```
/usr/bin/stat -f '%Su:%Sg:%N' $(/usr/bin/grep -e '^>' /etc/asl.conf /etc/asl/* | \
/usr/bin/awk '{ print $2 }') 2>/dev/null | /usr/bin/awk '!/^root:wheel:{print $1}' | \
/usr/bin/wc -l | /usr/bin/tr -d ' '
```

If the result is not **0**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/usr/sbin/chown root:wheel $(/usr/bin/stat -f '%Su:%Sg:%N' $(/usr/bin/grep -e '^>' /etc/asl.conf /etc/asl/* | /usr/bin/awk '{ print $2 }') 2> /dev/null | /usr/bin/awk '!/^root:wheel:{print $1}' | /usr/bin/awk -F":\" !/^root:wheel:{print $3}'")
```

ID	os_asl_log_files_owner_group_configure	
References	800-53r5 CCE	<ul style="list-style-type: none">SI-11CCE-95161-6

9.5. Configure Apple System Log Files To Mode 640 or Less Permissive

The Apple System Logs (ASL) *MUST* be configured to be writable by root and readable only by the root user and group wheel. To achieve this, ASL log files *MUST* be configured to mode 640 permissive or less; thereby preventing normal users from reading, modifying or deleting audit logs. System logs frequently contain sensitive information that could be used by an attacker. Setting the correct permissions mitigates this risk.

To check the state of the system, run the following command(s):

```
/usr/bin/stat -f '%A:%N' $(/usr/bin/grep -e '^>' /etc/asl.conf /etc/asl/* | /usr/bin/awk '{ print $2 }') 2> /dev/null | /usr/bin/awk '!/640/{print $1}' | /usr/bin/wc -l | /usr/bin/tr -d '\n'
```

If the result is not **0**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/bin/chmod 640 $(/usr/bin/stat -f '%A:%N' $(/usr/bin/grep -e '^>' /etc/asl.conf /etc/asl/* | /usr/bin/awk '{ print $2 }') 2> /dev/null | /usr/bin/awk -F":\" '!/640/{print $2}')
```

ID	os_asl_log_files_permissions_configure
----	--

References	800-53r5	<ul style="list-style-type: none">• SI-11
	CCE	<ul style="list-style-type: none">• CCE-95162-4

9.6. Enable Authenticated Root

Authenticated Root *MUST* be enabled.

When Authenticated Root is enabled the macOS is booted from a signed volume that is cryptographically protected to prevent tampering with the system volume.



Authenticated Root is enabled by default on macOS systems.



If more than one partition with macOS is detected, the csrutil command will hang awaiting input.

To check the state of the system, run the following command(s):

```
/usr/libexec/mdmclient QuerySecurityInfo 2>/dev/null | /usr/bin/grep -c  
"AuthenticatedRootVolumeEnabled = 1;"
```

If the result is not **1**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/usr/bin/csrutil authenticated-root enable
```



To re-enable "Authenticated Root", boot the affected system into "Recovery" mode, launch "Terminal" from the "Utilities" menu, and run the command.

ID	os_authenticated_root_enable	
References	800-53r5	<ul style="list-style-type: none">• AC-3• CM-5• MA-4(1)• SC-34• SI-7, SI-7(6)
	CCE	<ul style="list-style-type: none">• CCE-95164-0

9.7. Disable Blank Blu Ray

Blank Blu Ray media *MUST* be disabled.



Some organizations rely on the use of removable media for storing and sharing data. Information System Security Officers (ISSOs) may make the risk-based decision not to disable external hard drives to avoid losing this functionality, but they are advised to first fully weigh the potential risks posed to their organization.



Apple has deprecated the use of [media mount controls](#), using these controls may not work as expected. Third party software may be required to fulfill the compliance requirements.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
ObjC.unwrap($.NSUserDefaults.alloc.initWithSuiteName('com.apple.systemuiserver')\
.objectForKey('mount-controls'))["blankbd"]
EOS
```

If the result is not **deny**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.systemuiserver) payload type:

```
<key>mount-controls</key>
<dict>
  <array>
    <string>alert</string>
    <string>eject</string>
  </array>
</dict>
```

ID	os_blank_bluray_disable	
References	800-53r5 CCE	<ul style="list-style-type: none">MP-7CCE-95165-7

9.8. Disable Blank CD

Blank CD media *MUST* be disabled.



Some organizations rely on the use of removable media for storing and sharing data. Information System Security Officers (ISSOs) may make the risk-based decision not to disable external hard drives to avoid losing this functionality, but they are advised to first fully weigh the potential risks posed to their organization.



Apple has deprecated the use of [media mount controls](#), using these controls may not work as expected. Third party software may be required to fulfill the compliance requirements.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
ObjC.unwrap($.NSUserDefaults.alloc.initWithSuiteName('com.apple.systemuiserver')\
.objectForKey('mount-controls'))["blanked"]
EOS
```

If the result is not **deny**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.systemuiserver) payload type:

```
<key>mount-controls</key>
<dict>
  <array>
    <string>alert</string>
    <string>eject</string>
  </array>
</dict>
```

ID	os_blank_cd_disable	
References	800-53r5 CCE	<ul style="list-style-type: none">MP-7CCE-95166-5

9.9. Disable Blank DVD

Blank DVD media *MUST* be disabled.



Some organizations rely on the use of removable media for storing and sharing data. Information System Security Officers (ISSOs) may make the risk-based decision not to disable external hard drives to avoid losing this functionality, but they are advised to first fully weigh the potential risks posed to their organization.



Apple has deprecated the use of [media mount controls](#), using these controls may not work as expected. Third party software may be required to fulfill the compliance requirements.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
ObjC.unwrap($.NSUserDefaults.alloc.initWithSuiteName('com.apple.systemuiserver')\
.objectForKey('mount-controls'))["blankdvd"]
EOS
```

If the result is not **deny**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.systemuiserver) payload type:

```
<key>mount-controls</key>
<dict>
  <array>
    <string>alert</string>
    <string>eject</string>
  </array>
</dict>
```

ID	os_blank_dvd_disable	
References	800-53r5 CCE	<ul style="list-style-type: none">MP-7CCE-95167-3

9.10. Enforce Blu Ray Read Only

Blu Ray media *MUST* be set to read only.



Some organizations rely on the use of removable media for storing and sharing data. Information System Security Officers (ISSOs) may make the risk-based decision not to disable external hard drives to avoid losing this functionality, but they are advised to first fully weigh the potential risks posed to their organization.



Apple has deprecated the use of [media mount controls](#), using these controls may not work as expected. Third party software may be required to fulfill the compliance requirements.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
ObjC.unwrap($.NSUserDefaults.alloc.initWithSuiteName('com.apple.systemuiserver')\
.objectForKey('mount-controls'))["bd"]
EOS
```

If the result is not **read-only**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.systemuiserver) payload type:

```
<key>mount-controls</key>
<dict>
  <array>
    <string>read-only</string>
  </array>
</dict>
```

ID	os.bluray.read_only_enforce	
References	800-53r5 CCE	<ul style="list-style-type: none">MP-7CCE-95168-1

9.11. Disable Bonjour Multicast

Bonjour multicast advertising *MUST* be disabled to prevent the system from broadcasting its

presence and available services over network interfaces.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.mDNSResponder')\
.objectForKey('NoMulticastAdvertisements').js
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.mDNSResponder) payload type:

```
<key>NoMulticastAdvertisements</key>
<true/>
```

ID	os_bonjour_disable	
References	800-53r5 CCE	<ul style="list-style-type: none">CM-7, CM-7(1)CCE-95169-9

9.12. Disable Burn Support

Burn support *MUST* be disabled.



Some organizations rely on the use of removable media for storing and sharing data. Information System Security Officers (ISSOs) may make the risk-based decision not to disable external hard drives to avoid losing this functionality, but they are advised to first fully weigh the potential risks posed to their organization.

To check the state of the system, run the following command(s):

```
/usr/bin/profiles -P -o stdout | /usr/bin/grep -Ec '(BurnSupport = off;|ProhibitBurn = 1;)'
```

If the result is not **2**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.finder) payload type:

```
<key>ProhibitBurn</key>
<true/>
```

Create a configuration profile containing the following keys in the (com.apple.DiscRecording) payload type:

```
<key>BurnSupport</key>
<string>off</string>
```

ID	os_burn_support_disable	
References	800-53r5 CCE	<ul style="list-style-type: none">• MP-7• CCE-95170-7

9.13. Disable Calendar.app

The macOS built-in Calendar.app *MUST* be disabled as this application can establish a connection to non-approved services. This rule is in place to prevent inadvertent data transfers.

 Some organizations allow the use of the built-in Calendar.app for organizational communication. Information System Security Officers (ISSOs) may make the risk-based decision not to disable the macOS built-in Calendar.app to avoid losing this functionality, but they are advised to first fully weigh the potential risks posed to their organization.

 Apple has deprecated the use of [application restriction controls](#), using these controls may not work as expected. Third party software may be required to fulfill the compliance requirements.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
function run() {
    let pref1 = ObjC.unwrap(
        $.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess.new')\
            .objectForKey('familyControlsEnabled'))
    let pathlist =
        $.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess.new')\
            .objectForKey('pathBlackList').js
    for ( let app in pathlist ) {
```

```

        if ( ObjC.unwrap(pathlist[app]) == "/Applications/Calendar.app" && pref1 == true
){
    return("true")
}
return("false")
}
EOS

```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess.new) payload type:

```

<key>familyControlsEnabled</key>
<true/>
<key>pathBlackList</key>
<array>
    <string>/Applications/Calendar.app</string>
</array>

```

ID	os_calendar_app_disable	
References	800-53r5 CCE	<ul style="list-style-type: none"> • AC-20 • CM-7, CM-7(1) • CCE-95171-5

9.14. Enforce CD Read Only

CD media *MUST* be set to read only.



Some organizations rely on the use of removable media for storing and sharing data. Information System Security Officers (ISSOs) may make the risk-based decision not to disable external hard drives to avoid losing this functionality, but they are advised to first fully weigh the potential risks posed to their organization.



Apple has deprecated the use of [media mount controls](#), using these controls may not work as expected. Third party software may be required to fulfill the compliance requirements.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
ObjC.unwrap($.NSUserDefaults.alloc.initWithSuiteName('com.apple.systemuiserver')\
.objectForKey('mount-controls'))["cd"]
EOS
```

If the result is not **read-only**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.systemuiserver) payload type:

```
<key>mount-controls</key>
<dict>
    <array>
        <string>read-only</string>
    </array>
</dict>
```

ID	os_cd_read_only_enforce	
References	800-53r5 CCE	<ul style="list-style-type: none">MP-7CCE-95173-1

9.15. Issue or Obtain Public Key Certificates from an Approved Service Provider

The organization *MUST* issue or obtain public key certificates from an organization-approved service provider and ensure only approved trust anchors are in the System Keychain.



This rule is marked as manual and may not be able to be automated. It is also excluded in the compliance scan and will not report any results.

To check the state of the system, run the following command(s):

```
/usr/bin/security dump-keychain /Library/Keychains/System.keychain | /usr/bin/awk -F'"' '/label/ {print $4}'
```

If the result is not **a list containing approved root certificates**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Obtain the approved certificates from the appropriate authority and install them to the System Keychain.

ID	os_certificate_authority_trust	
References	800-53r5 CCE	<ul style="list-style-type: none">• SC-17• CCE-95174-9

9.16. Enforce Installation of XProtect Remediator and Gatekeeper Updates Automatically

Software Update *MUST* be configured to update XProtect Remediator and Gatekeeper automatically.

This setting enforces definition updates for XProtect Remediator and Gatekeeper; with this setting in place, new malware and adware that Apple has added to the list of malware or untrusted software will not execute. These updates do not require the computer to be restarted.

<https://support.apple.com/en-us/HT207005>



Software update will automatically update XProtect Remediator and Gatekeeper by default in the macOS.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.SoftwareUpdate')\
.objectForKey('ConfigDataInstall').js
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.SoftwareUpdate) payload type:

```
<key>ConfigDataInstall</key>
<true/>
```

ID	os_config_data_install_enforce
-----------	--------------------------------

References	800-53r5	<ul style="list-style-type: none"> • SI-2(5) • SI-3
	CCE	<ul style="list-style-type: none"> • CCE-95176-4

9.17. Disable Installation of Configuration Profiles through the User Interface

Installation of configuration profiles through the user interface *MUST* be disabled and only be permitted through an authorized MDM server.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowUIConfigurationProfileInstallation').js
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowUIConfigurationProfileInstallation</key>
<false/>
```

ID	os_config_profile_ui_install_disable	
References	800-53r5	<ul style="list-style-type: none"> • CM-5
	CCE	<ul style="list-style-type: none"> • CCE-95177-2

9.18. Disable Dictation

Dictation *MUST* be disabled on Intel based Macs as the feature On Device Dictation is only available on Apple Silicon devices.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
```

```
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\n.objectForKey('allowDictation').js\nEOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowDictation</key>\n<false/>
```

ID	os_dictation_disable	
References	800-53r5	<ul style="list-style-type: none">AC-20CM-7, CM-7(1)SC-7(10)
	CCE	<ul style="list-style-type: none">CCE-95180-6

9.19. Disable Disk Images

Disk images *MUST* be disabled.



Some organizations rely on the use of removable media for storing and sharing data. Information System Security Officers (ISSOs) may make the risk-based decision not to disable external hard drives to avoid losing this functionality, but they are advised to first fully weigh the potential risks posed to their organization.



Apple has deprecated the use of [media mount controls](#), using these controls may not work as expected. Third party software may be required to fulfill the compliance requirements.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS\nObjC.unwrap($.NSUserDefaults.alloc.initWithSuiteName('com.apple.systemuiserver')\n.objectForKey('mount-controls'))["disk-image"]\nEOS
```

If the result is not **deny**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.systemuiserver) payload type:

```
<key>mount-controls</key>
<dict>
    <array>
        <string>alert</string>
        <string>eject</string>
    </array>
</dict>
```

ID	os_disk_image_disable	
References	800-53r5 CCE	<ul style="list-style-type: none">• MP-7• CCE-95182-2

9.20. Disable DVD-RAM

DVD-RAM media *MUST* be disabled.



Some organizations rely on the use of removable media for storing and sharing data. Information System Security Officers (ISSOs) may make the risk-based decision not to disable external hard drives to avoid losing this functionality, but they are advised to first fully weigh the potential risks posed to their organization.



Apple has deprecated the use of [media mount controls](#), using these controls may not work as expected. Third party software may be required to fulfill the compliance requirements.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
ObjC.unwrap($.NSUserDefaults.alloc.initWithSuiteName('com.apple.systemuiserver')\
.objectForKey('mount-controls'))["dvdrw"]
EOS
```

If the result is not **deny**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.systemuiserver) payload type:

```
<key>mount-controls</key>
<dict>
    <array>
        <string>alert</string>
        <string>eject</string>
    </array>
</dict>
```

ID	os_dvdram_disable	
References	800-53r5 CCE	<ul style="list-style-type: none">• MP-7• CCE-95183-0

9.21. Disable Erase Content and Settings

Erase Content and Settings *MUST* be disabled.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowEraseContentAndSettings').js
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowEraseContentAndSettings</key>
<false/>
```

ID	os_erase_content_and_settings_disable	
References	800-53r5 CCE	<ul style="list-style-type: none">CM-7, CM-7(1)CCE-95185-5

9.22. Access to External Storage Must Be Defined

Access to external storage *MUST* be managed.



Apple's built in method using declarative device management method only allows you to set external storage manament to Allowed, ReadOnly, and Disallowed.

To check the state of the system, run the following command(s):

```
/usr/bin/plutil -convert json  
/var/db/ManagedConfigurationFiles/DiskManagement/DiskManagement_Settings.plist -o - |  
/usr/bin/jq --raw-output '.Restrictions.ExternalStorage'
```

If the result is not **Allowed**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

This is implemented by Declarative Device Management (DDM).

ID	os_external_storage_access_defined	
References	800-53r5 CCE	<ul style="list-style-type: none">MP-7CCE-95188-9

9.23. Disable FaceTime.app

The macOS built-in FaceTime.app *MUST* be disabled.

The FaceTime.app establishes a connection to Apple's iCloud service, even when security controls have been put in place to disable iCloud access.



Apple has deprecated the use of [application restriction controls](#), using these controls may not work as expected. Third party software may be required to fulfill the compliance requirements.

To check the state of the system, run the following command(s):

```

/usr/bin/osascript -l JavaScript << EOS
function run() {
    let pref1 = ObjC.unwrap(
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess.new')\
.objectForKey('familyControlsEnabled'))
    let pathlist =
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess.new')\
.objectForKey('pathBlackList').js
    for ( let app in pathlist ) {
        if ( ObjC.unwrap(pathlist[app]) == "/Applications/FaceTime.app" && pref1 == true
){
            return("true")
        }
    }
    return("false")
}
EOS

```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess.new) payload type:

```

<key>familyControlsEnabled</key>
<true/>
<key>pathBlackList</key>
<array>
    <string>/Applications/FaceTime.app</string>
</array>

```

ID	os_facetime_app_disable	
References	800-53r5	<ul style="list-style-type: none"> • AC-20 • CM-7, CM-7(1)
	CCE	<ul style="list-style-type: none"> • CCE-95189-7

9.24. Disable FileVault Automatic Login

If FileVault is enabled, automatic login *MUST* be disabled, so that both FileVault and login window authentication are required.

The default behavior of macOS when FileVault is enabled is to automatically log in to the computer once successfully passing your FileVault credentials.



DisableFDEAutoLogin does not have to be set on Apple Silicon based macOS systems that are smartcard enforced as smartcards are available at pre-boot.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.loginwindow')\
.objectForKey('DisableFDEAutoLogin').js
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.loginwindow) payload type:

```
<key>DisableFDEAutoLogin</key>
<true/>
```

ID	os_filevault_autologin_disable	
References	800-53r5	<ul style="list-style-type: none">• AC-2(11)• AC-3• IA-5(13)
	CCE	<ul style="list-style-type: none">• CCE-95192-1

9.25. Control Connections to Other Systems via a Deny-All and Allow-by-Exception Firewall Policy

A deny-all and allow-by-exception firewall policy *MUST* be employed for managing connections to other systems.

Organizations *MUST* ensure the built-in packet filter firewall is configured correctly to employ the default deny rule.

Failure to restrict network connectivity to authorized systems permits inbound connections from malicious systems. It also permits outbound connections that may facilitate the exfiltration of data.

If you are using a third-party firewall solution, this setting does not apply.

 Configuring the built-in packet filter firewall to employ the default deny rule has the potential to interfere with applications on the system in an unpredictable manner. Information System Security Officers (ISSOs) may make the risk-based decision not to configure the built-in packet filter firewall to employ the default deny rule to avoid losing functionality, but they are advised to first fully weigh the potential risks posed to their organization.

To check the state of the system, run the following command(s):

```
/sbin/pfctl -a '*' -sr &> /dev/null | /usr/bin/grep -c "block drop in all"
```

If the result is not 1, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:



See the firewall supplemental which includes a script that has an example policy to implement this rule.

ID	os_firewall_default_deny_require		
References	800-53r5	• AC-4	• SC-7(5)
CCE		• CCE-95193-9	

9.26. Enable Firmware Password

A firmware password *MUST* be enabled and set.

Single user mode, recovery mode, the Startup Manager, and several other tools are available on macOS by holding the "Option" key down during startup. Setting a firmware password restricts access to these tools.

To set a firmware passcode use the following command:

```
/usr/sbin/firmwarepasswd -setpasswd
```



If firmware password or passcode is forgotten, the only way to reset the forgotten password is through the use of a machine specific binary generated and provided by Apple. Schedule a support call, and provide proof of purchase before the firmware binary will be generated.



Firmware passwords are not supported on Apple Silicon devices. This rule is only applicable to Intel devices.

To check the state of the system, run the following command(s):

```
/usr/sbin/firmwarepasswd -check | /usr/bin/grep -c "Password Enabled: Yes"
```

If the result is not **1**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:



See discussion on remediation and how to enable firmware password.

ID	os_firmware_password_require	
References	800-53r5	<ul style="list-style-type: none">• AC-6
	CCE	<ul style="list-style-type: none">• CCE-95194-7

9.27. Enable Gatekeeper

Gatekeeper *MUST* be enabled.

Gatekeeper is a security feature that ensures that applications are digitally signed by an Apple-issued certificate before they are permitted to run. Digital signatures allow the macOS host to verify that the application has not been modified by a malicious third party.

Administrator users will still have the option to override these settings on a case-by-case basis.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.systempolicy.control')\
.objectForKey('EnableAssessment').js
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.systempolicy.control) payload type:

```
<key>EnableAssessment</key>
<true/>
```

ID	os_gatekeeper_enable	
References	800-53r5	<ul style="list-style-type: none">• CM-14• CM-5• SI-3• SI-7(1), SI-7(15)
	CCE	<ul style="list-style-type: none">• CCE-95195-4

9.28. Disable Genemoji AI Creation

Apple Intelligence features such as Genemoji *MUST* be disabled.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowGenemoji').js
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowGenemoji</key>
<false/>
```

ID	os_genemoji_disable	
References	800-53r5	<ul style="list-style-type: none">• CM-7, CM-7(1)
	CCE	<ul style="list-style-type: none">• CCE-95196-2

9.29. Disable Handoff

Handoff *MUST* be disabled.

Handoff allows you to continue working on a document or project when the user switches from one Apple device to another. Disabling Handoff prevents data transfers to unauthorized devices.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowActivityContinuation').js
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowActivityContinuation</key>
<false/>
```

ID	os_handoff_disable		
References	800-53r5	• AC-20 • AC-3 • CM-7, CM-7(1)	CCE
		• CCE-95199-6	

9.30. Configure User's Home Folders to Apple's Default

The system *MUST* be configured to prevent access to other user's home folders.

Configuring the operating system to use the most restrictive permissions possible for user home directories helps to protect against inadvertent disclosures.



This rule is marked as manual and may not be able to be automated. It is also excluded in the compliance scan and will not report any results.

To check the state of the system, run the following command(s):

Verify the macOS system is configured so that permissions are set correctly on user home directories with the following commands:

```
/bin/ls -le /Users
```

This command will return a listing of the permissions of the root of every user account configured on the system. For each of the users, the permissions must be "drwxr-xr-x+", with the user listed as the owner and the group listed as \"staff\". The plus(+) sign indicates an associated Access Control List, which must be:

0: group:everyone deny delete

For every authorized user account, also run the following command:

```
/usr/bin/sudo /bin/ls -le /Users/userid
```

, where userid is an existing user.

This command will return the permissions of all the objects under the users' home directory. The permissions for each of the subdirectories must be:

drwx-----+

0: group:everyone deny delete

The exception is the \"Public\" directory, whose permissions must match the following:

drwxr-xr-x+

0: group:everyone deny delete

If the permissions returned by either of these checks differ from what is shown, this is a finding.

If the result is not N/A, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Configure the macOS system to set the appropriate permissions for each user on the system with the following command:

```
/usr/sbin/diskutil resetUserPermissions / DeviceNode UID
```

, where "DeviceNode UID" is the ID number for the user whose home directory permissions need to be repaired.

Using the `/usr/sbin/diskutil resetUserPermissions` command will only reset the permissions on the default folder set. Other folders in the home directory will not be affected.

ID	os_home_folders_default	
References	800-53r5	<ul style="list-style-type: none">• AC-6
	CCE	<ul style="list-style-type: none">• CCE-95202-8

9.31. Secure User's Home Folders

The system *MUST* be configured to prevent access to other user's home folders.

The default behavior of macOS is to allow all valid users access to the top level of every other user's home folder while restricting access only to the Apple default folders within.

To check the state of the system, run the following command(s):

```
/usr/bin/find /System/Volumes/Data/Users -mindepth 1 -maxdepth 1 -type d ! \(\ -perm 700 -o -perm 711 \) | /usr/bin/grep -v "Shared" | /usr/bin/grep -v "Guest" | /usr/bin/wc -l | /usr/bin/xargs
```

If the result is not **0**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
IFS=$'\n'  
for userDirs in $( /usr/bin/find /System/Volumes/Data/Users -mindepth 1 -maxdepth 1 -type d ! \(\ -perm 700 -o -perm 711 \) | /usr/bin/grep -v "Shared" | /usr/bin/grep -v "Guest" ); do  
    /bin/chmod og-rwx "$userDirs"  
done  
unset IFS
```

ID	os_home_folders_secure	
References	800-53r5 CCE	<ul style="list-style-type: none">AC-6CCE-95203-6

9.32. Disable the Built-in Web Server

The built-in web server which is managed by launchd is a non-essential service built into macOS and *MUST* be disabled and not running.



The built in web server service is disabled at startup by default macOS.

To check the state of the system, run the following command(s):

```
result="FAIL"  
enabled=$(/bin/launchctl print-disabled system | /usr/bin/grep '"org.apache.httpd" => enabled')  
running=$(/bin/launchctl print system/org.apache.httpd 2>/dev/null)
```

```

if [[ -z "$running" ]] && [[ -z "$enabled" ]]; then
    result="PASS"
elif [[ -n "$running" ]]; then
    result=result+" RUNNING"
elif [[ -n "$enabled" ]]; then
    result=result+" ENABLED"
fi
echo $result

```

If the result is not **PASS**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```

/usr/sbin/apachectl stop 2>/dev/null
/bin/launchctl disable system/org.apache.httpd

```

ID	os_httpd_disable		
References	800-53r5	• AC-17 • AC-3	
	CCE	• CCE-95204-4	

9.33. Disable iCloud Storage Setup during Setup Assistant

The prompt to set up iCloud storage services during Setup Assistant *MUST* be disabled.

The default behavior of macOS is to prompt new users to set up storage in iCloud. Disabling the iCloud storage setup prompt provides organizations more control over the storage of their data.

To check the state of the system, run the following command(s):

```

/usr/bin/osascript -l JavaScript 2>/dev/null << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.SetupAssistant.managed')\
.objectForKey('SkipSetupItems').containsObject("iCloudStorage")
EOS

```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.SetupAssistant.managed) payload type:

```
<key>SkipSetupItems</key>
<array>
    <string>iCloudStorage</string>
</array>
```

ID	os_icloud_storage_prompt_disable	
References	800-53r5 CCE	<ul style="list-style-type: none">• AC-20• CCE-95205-1

9.34. Disable Apple Intelligence Image Playground

Apple Intelligence features such as Image Playground *MUST* be disabled.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowImagePlayground').js
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowImagePlayground</key>
<false/>
```

ID	os_image_playground_disable	
References	800-53r5 CCE	<ul style="list-style-type: none">• CM-7, CM-7(1)• CCE-95207-7

9.35. Configure Install.log Retention to 365

The install.log *MUST* be configured to require records be kept for a organizational defined value before deletion, unless the system uses a central audit record storage facility.

To check the state of the system, run the following command(s):

```
/usr/sbin/aslmanager -dd 2>&1 | /usr/bin/awk '/\var\log\install.log$/ {count++}  
/Processing module com.apple.install/,/Finished/ { for (i=1;i<=NR;i++) { if ($i ==  
"TTL" && $(i+2) >= 365) { ttl="True" }; if ($i == "MAX") {max="True"} } } END{if (count  
> 1) { print "Multiple config files for /var/log/install, manually remove the extra  
files" } else if (max == "True") { print "all_max setting is configured, must be  
removed" } if (ttl != "True") { print "TTL not configured" } else { print "Yes" }}'
```

If the result is not **Yes**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/usr/bin/sed -i '' "s/* file \var\log\install.log.*/* file \var\log  
\install.log format='\$((Time))\$Z \$Host \$((Sender))\$((PID)):  
\$Message' rotate=utc compress file_max=50M size_only ttl=365/g"  
/etc/asl/com.apple.install
```



If there are multiple configuration files in /etc/asl that are set to process the file /var/log/install.log, these files will have to be manually removed.

ID	os_install_log_retention_configure		
References	800-53r5	• AU-11	• AU-4
	CCE	• CCE-95211-9	

9.36. Disable iPhone Mirroring

iPhone Mirroing *MUST* be disabled to prevent file transfers to or from unauthorized devices. Disabling iPhone Mirroring also prevents potentially unauthorized applications from appearing as if they are installed on the Mac.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS  
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
```

```
.objectForKey('allowiPhoneMirroring').js  
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowiPhoneMirroring</key>  
<false/>
```

ID	os_iphone_mirroring_disable		
References	800-53r5	<ul style="list-style-type: none">AC-20AC-3CM-7, CM-7(1)	CCE
		<ul style="list-style-type: none">CCE-95212-7	

9.37. Disable Infrared (IR) support

Infrared (IR) support *MUST* be disabled to prevent users from controlling the system with IR devices.

By default, if IR is enabled, the system will accept IR control from any remote device.



This is applicable only to models of Mac Mini systems earlier than Mac Mini8,1.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS  
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.driver.AppleIRController')\\  
.objectForKey('DeviceEnabled').js  
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:



The following settings are in the (com.apple.ManagedClient.preferences) payload. This payload requires the additional settings to be sub-payloads within, containing their defined payload types.

Create a configuration profile containing the following keys in the (com.apple.driver.AppleIRController) payload type:

```
<key>DeviceEnabled</key>
<false/>
```

ID	os_ir_support_disable		
References	800-53r5	• AC-18 • CM-7, CM-7(1)	CCE
		• CCE-95213-5	

9.38. Prevent AdminHostInfo from Being Available at Login Window

The system *MUST* be configured to not display sensitive information at the login window. If the key `AdminHostInfo` is configured with a string value, it will allow the HostName, IP Address, and operating system version and build to be displayed when clicking on the clock area of the login window.

Configuring this key to be an integer value, since it expects a string value, will effectively disable the behavior.



This configuration requires it to be deployed via Managed Preferences rather than directly to com.apple.loginwindow.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.loginwindow')\
.integerForKey('AdminHostInfo')
EOS
```

If the result is not **-1**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:



The following settings are in the (com.apple.ManagedClient.preferences) payload. This payload requires the additional settings to be sub-payloads within, containing their defined payload types.

Create a configuration profile containing the following keys in the (com.apple.loginwindow) payload type:

```
<key>AdminHostInfo</key>
<integer>-1</integer>
```

ID	os_loginwindow_adminhostinfo_disabled	
References	800-53r5	<ul style="list-style-type: none">AC-11(1)
	CCE	<ul style="list-style-type: none">CCE-95600-3

9.39. Disable Mail App

The macOS built-in Mail.app *MUST* be disabled.

The Mail.app contains functionality that can establish connections to Apple's iCloud, even when security controls to disable iCloud access have been put in place.



Some organizations allow the use of the built-in Mail.app for organizational communication. Information System Security Officers (ISSOs) may make the risk-based decision not to disable the macOS built-in Mail.app to avoid losing this functionality, but they are advised to first fully weigh the potential risks posed to their organization.



Apple has deprecated the use of [application restriction controls](#), using these controls may not work as expected. Third party software may be required to fulfill the compliance requirements.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
function run() {
    let pref1 = ObjC.unwrap(
        $.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess.new')\
            .objectForKey('familyControlsEnabled'))
    let pathlist =
        $.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess.new')\
            .objectForKey('pathBlackList').js
    for ( let app in pathlist ) {
        if ( ObjC.unwrap(pathlist[app]) == "/Applications/Mail.app" && pref1 == true ){
            return("true")
```

```
    }
}
return("false")
}
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess.new) payload type:

```
<key>familyControlsEnabled</key>
<true/>
<key>pathBlackList</key>
<array>
    <string>/Applications/Mail.app</string>
</array>
```

ID	os_mail_app_disable	
References	800-53r5 CCE	<ul style="list-style-type: none">AC-20CM-7, CM-7(1)CCE-95221-8

9.40. Disable Apple Intelligence Mail Smart Replies

Apple Intelligence features such as Mail Smart Replies that use off device AI *MUST* be disabled.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowMailSmartReplies').js
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowMailSmartReplies</key>
<false/>
```

ID	os_mail_smart_reply_disable	
References	800-53r5	<ul style="list-style-type: none">• AC-20, AC-20(1)• CM-7, CM-7(1)• SC-7(10)
	CCE	<ul style="list-style-type: none">• CCE-95222-6

9.41. Disable Apple Intelligence Mail Summary

Apple Intelligence features such as Apple Mail Summary that use off device AI *MUST* be disabled.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowMailSummary').js
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowMailSummary</key>
<false/>
```

ID	os_mail_summary_disable
----	-------------------------

References	800-53r5	<ul style="list-style-type: none"> • AC-20, AC-20(1) • CM-7, CM-7(1) • SC-7(10)
	CCE	<ul style="list-style-type: none"> • CCE-95223-4

9.42. Enforce Enrollment in Mobile Device Management

You *MUST* enroll your Mac in a Mobile Device Management (MDM) software.

User Approved MDM (UAMDM) enrollment or enrollment via Apple Business Manager (ABM)/Apple School Manager (ASM) is required to manage certain security settings. Currently these include:

- Allowed Kernel Extensions
- Allowed Approved System Extensions
- Privacy Preferences Policy Control Payload
- ExtensibleSingleSignOn
- FDEFFileVault

In macOS 11, UAMDM grants Supervised status on a Mac, unlocking the following MDM features, which were previously locked behind ABM:

- Activation Lock Bypass
- Access to Bootstrap Tokens
- Scheduling Software Updates
- Query list and delete local users

To check the state of the system, run the following command(s):

```
/usr/bin/profiles status -type enrollment | /usr/bin/awk -F: '/MDM enrollment/ {print $2}' | /usr/bin/grep -c "Yes (User Approved)"
```

If the result is not 1, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Ensure that system is enrolled via UAMDM.

ID	os_mdm_require
-----------	----------------

References	800-53r5	<ul style="list-style-type: none"> • CM-2 • CM-6
	CCE	<ul style="list-style-type: none"> • CCE-95227-5

9.43. Disable Messages App

The macOS built-in Messages.app *MUST* be disabled.

The Messages.app establishes a connection to Apple's iCloud service, even when security controls to disable iCloud access have been put in place.



Apple has deprecated the use of [application restriction controls](#), using these controls may not work as expected. Third party software may be required to fulfill the compliance requirements.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
function run() {
    let pref1 = ObjC.unwrap(
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess.new')\
.objectForKey('familyControlsEnabled'))
    let pathlist =
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess.new')\
.objectForKey('pathBlackList').js
    for ( let app in pathlist ) {
        if ( ObjC.unwrap(pathlist[app]) == "/Applications/Messages.app" && pref1 == true
){
            return("true")
        }
    }
    return("false")
}
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess.new) payload type:

```
<key>familyControlsEnabled</key>
<true/>
```

```

<key>pathBlackList</key>
<array>
    <string>/Applications/Messages.app</string>
</array>

```

ID	os_messages_app_disable	
References	800-53r5	<ul style="list-style-type: none"> • AC-20 • CM-7, CM-7(1)
	CCE	<ul style="list-style-type: none"> • CCE-95228-3

9.44. Configure System Log Files Owned by Root and Group to Wheel

The system log files *MUST* be owned by root.

System logs contain sensitive data about the system and users. If log files are set to only be readable and writable by system administrators, the risk is mitigated.

To check the state of the system, run the following command(s):

```

/usr/bin/stat -f '%Su:%Sg:%N' $(/usr/bin/grep -v '^#' /etc/newsyslog.conf |
/usr/bin/awk '{ print $1 }') 2> /dev/null | /usr/bin/awk '!/^root:wheel:{print $1}' |
/usr/bin/wc -l | /usr/bin/tr -d ' '

```

If the result is not **0**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```

/usr/sbin/chown root:wheel $(/usr/bin/stat -f '%Su:%Sg:%N' $(/usr/bin/grep -v '^#' /etc/newsyslog.conf |
/usr/bin/awk '{ print $1 }') 2> /dev/null | /usr/bin/awk '!/^root:wheel:{print $1}' |
F:" '!/^root:wheel:{print $3}')

```

ID	os_newsyslog_files_owner_group_configure	
References	800-53r5	<ul style="list-style-type: none"> • SI-11
	CCE	<ul style="list-style-type: none"> • CCE-95233-3

9.45. Configure System Log Files to Mode 640 or Less Permissive

The system logs *MUST* be configured to be writable by root and readable only by the root user and group wheel. To achieve this, system log files *MUST* be configured to mode 640 permissive or less; thereby preventing normal users from reading, modifying or deleting audit logs. System logs frequently contain sensitive information that could be used by an attacker. Setting the correct permissions mitigates this risk.

To check the state of the system, run the following command(s):

```
/usr/bin/stat -f '%A:%N' $(/usr/bin/grep -v '^#' /etc/newsyslog.conf | /usr/bin/awk '{ print $1 }') 2> /dev/null | /usr/bin/awk '!/640/{print $1}' | /usr/bin/wc -l | /usr/bin/tr -d '\n'
```

If the result is not **0**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/bin/chmod 640 $(/usr/bin/stat -f '%A:%N' $(/usr/bin/grep -v '^#' /etc/newsyslog.conf | /usr/bin/awk '{ print $1 }') 2> /dev/null | /usr/bin/awk '!/640/{print $1}' | awk -F ":" '!/640/{print $2}')
```

ID	os_newsyslog_files_permissions_configure	
References	800-53r5	<ul style="list-style-type: none">• SI-11
	CCE	<ul style="list-style-type: none">• CCE-95234-1

9.46. Disable Network File System Service

Support for Network File Systems (NFS) services is non-essential and, therefore, *MUST* be disabled.

To check the state of the system, run the following command(s):

```
isDisabled=$(/sbin/nfsd status | /usr/bin/awk '/nfsd service/ {print $NF}')
if [[ "$isDisabled" == "disabled" ]] && [[ -z $(/usr/bin/pgrep nfsd) ]]; then
    echo "pass"
else
    echo "fail"
fi
```

If the result is not **pass**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/bin/launchctl disable system/com.apple.nfsd  
/bin/rm -rf /etc/exports
```

The system may need to be restarted for the update to take effect.

ID	os_nfsd_disable	
References	800-53r5	<ul style="list-style-type: none">• AC-17• AC-3
	CCE	<ul style="list-style-type: none">• CCE-95235-8

9.47. Disable Apple Intelligence Notes Transcription

Apple Intelligence features such as Notes Transcription that use off device AI *MUST* be disabled.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS  
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\\  
.objectForKey('allowNotesTranscription').js  
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowNotesTranscription</key>  
<false/>
```

ID	os_notes_transcription_disable
-----------	--------------------------------

References	800-53r5	<ul style="list-style-type: none"> • AC-20, AC-20(1) • CM-7, CM-7(1) • SC-7(10)
	CCE	<ul style="list-style-type: none"> • CCE-95238-2

9.48. Disable Apple Intelligence Notes Transcription Summary

Apple Intelligence features such as Notes Transcription Summary that use off device AI *MUST* be disabled.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowNotesTranscriptionSummary').js
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowNotesTranscriptionSummary</key>
<false/>
```

ID	os_notes_transcription_summary_disable			
References	800-53r5	<ul style="list-style-type: none"> • AC-20, AC-20(1) • CM-7, CM-7(1) • SC-7(10) 	CCE	<ul style="list-style-type: none"> • CCE-95239-0

9.49. Enforce On Device Dictation

Dictation *MUST* be restricted to on device only to prevent potential data exfiltration.

The information system *MUST* be configured to provide only essential capabilities.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('forceOnDeviceOnlyDictation').js
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>forceOnDeviceOnlyDictation</key>
<true/>
```

ID	os_on_device_dictation_enforce		
References	800-53r5	<ul style="list-style-type: none">• AC-20• CM-7, CM-7(1)• SC-7(10)• CCE-95247-3	CCE

9.50. Enable Parental Controls

Parental Controls *MUST* be enabled.

Control of program execution is a mechanism used to prevent program execution of unauthorized programs, which is critical to maintaining a secure system baseline.

Parental Controls on the macOS consist of many different payloads, which are set individually depending on the type of control required. Enabling parental controls allows for further configuration of these restrictions.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess.new')\
.objectForKey('familyControlsEnabled').js
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess.new) payload type:

```
<key>familyControlsEnabled</key>
<true/>
```

ID	os_parental_controls_enable	
References	800-53r5 CCE	<ul style="list-style-type: none"> • CM-7(2) • CCE-95248-1

9.51. Disable Password Autofill

Password Autocomplete *MUST* be disabled.

macOS allows users to save passwords and use the Password Autocomplete feature in Safari and compatible apps. To protect against malicious users gaining access to the system, this feature *MUST* be disabled to prevent users from being prompted to save passwords in applications.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowPasswordAutoFill').js
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowPasswordAutoFill</key>
```

<false/>

ID	os_password_autofill_disable	
References	800-53r5	<ul style="list-style-type: none">• N/A
	CCE	<ul style="list-style-type: none">• CCE-95249-9

9.52. Remove Password Hint From User Accounts

User accounts *MUST* not contain password hints.

To check the state of the system, run the following command(s):

```
HINT=$(/usr/bin/dscl . -list /Users hint | /usr/bin/awk '{ print $2 }')

if [ -z "$HINT" ]; then
    echo "PASS"
else
    echo "FAIL"
fi
```

If the result is not **PASS**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
for u in $($(/usr/bin/dscl . -list /Users UniqueID | /usr/bin/awk '$2 > 500 {print
$1}'); do
    /usr/bin/dscl . -delete /Users/$u hint
done
```

ID	os_password_hint_remove	
References	800-53r5	<ul style="list-style-type: none">• IA-6
	CCE	<ul style="list-style-type: none">• CCE-95250-7

9.53. Disable Proximity Based Password Sharing Requests

Proximity based password sharing requests *MUST* be disabled.

The default behavior of macOS is to allow users to request passwords from other known devices

(macOS and iOS). This feature *MUST* be disabled to prevent passwords from being shared.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowPasswordProximityRequests').js
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowPasswordProximityRequests</key>
<false/>
```

ID	os_password_proximity_disable		
References	800-53r5	• IA-5	
	CCE	• CCE-95251-5	

9.54. Disable Password Sharing

Password Sharing *MUST* be disabled.

The default behavior of macOS is to allow users to share a password over Airdrop between other macOS and iOS devices. This feature *MUST* be disabled to prevent passwords from being shared.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowPasswordSharing').js
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowPasswordSharing</key>
<false/>
```

ID	os_password_sharing_disable	
References	800-53r5	<ul style="list-style-type: none">• IA-5
	CCE	<ul style="list-style-type: none">• CCE-95252-3

9.55. Disable Photos Enhanced Visual Search

Enhanced Visualized Search *MUST* be disabled in the Photos app.

The information system *MUST* be configured to provide only essential capabilities. Disabling Enhanced Visual Search will mitigate the risk of unwanted data being sent to Apple.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.photos.shareddefaults')\
.objectForKey('IPXDefaultEnhancedVisualSearchEnabled').js
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.photos.shareddefaults) payload type:

```
<key>IPXDefaultEnhancedVisualSearchEnabled</key>
<false/>
```

ID	os_photos_enhanced_search_disable
-----------	-----------------------------------

References	800-53r5	<ul style="list-style-type: none">• AC-20, AC-20(1)• CM-7, CM-7(1)• SC-7(10)
	CCE	<ul style="list-style-type: none">• CCE-95254-9

9.56. Display Policy Banner at Login Window

Displaying a standardized and approved use notification before granting access to the operating system ensures that users are provided with privacy and security notification verbiage that is consistent with applicable federal laws, Executive Orders, directives, policies, regulations, standards, and guidance.

System use notifications are required only for access via login interfaces with human users and are not required when such human interfaces do not exist.

The policy banner will show if a "PolicyBanner.rtf" or "PolicyBanner.rtfd" exists in the "/Library/Security" folder.

The banner text of the document *MUST* read:

You are accessing a U.S. Government information system, which includes: 1) this computer, 2) this computer network, 3) all Government-furnished computers connected to this network, and 4) all Government-furnished devices and storage media attached to this network or to a computer on this network. You understand and consent to the following: you may access this information system for authorized use only; unauthorized use of the system is prohibited and subject to criminal and civil penalties; you have no reasonable expectation of privacy regarding any communication or data transiting or stored on this information system at any time and for any lawful Government purpose, the Government may monitor, intercept, audit, and search and seize any communication or data transiting or stored on this information system; and any communications or data transiting or stored on this information system may be disclosed or used for any lawful Government purpose. This information system may contain Controlled Unclassified Information (CUI) that is subject to safeguarding or dissemination controls in accordance with law, regulation, or Government-wide policy. Accessing and using this system indicates your understanding of this warning.

To check the state of the system, run the following command(s):

```
/bin/ls -1d /Library/Security/PolicyBanner.rtf* | /usr/bin/wc -l | /usr/bin/tr -d ''
```

If the result is not 1, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```

bannerText="You are accessing a U.S. Government information system, which
includes: 1) this computer, 2) this computer network, 3) all Government-furnished
computers connected to this network, and 4) all Government-furnished devices and
storage media attached to this network or to a computer on this network. You
understand and consent to the following: you may access this information system
for authorized use only; unauthorized use of the system is prohibited and subject
to criminal and civil penalties; you have no reasonable expectation of privacy
regarding any communication or data transiting or stored on this information
system at any time and for any lawful Government purpose, the Government may
monitor, intercept, audit, and search and seize any communication or data
transiting or stored on this information system; and any communications or data
transiting or stored on this information system may be disclosed or used for any
lawful Government purpose. This information system may contain Controlled
Unclassified Information (CUI) that is subject to safeguarding or dissemination
controls in accordance with law, regulation, or Government-wide policy. Accessing
and using this system indicates your understanding of this warning."
/bin/mkdir /Library/Security/PolicyBanner.rtf
/usr/bin/textutil -convert rtf -output /Library/Security/PolicyBanner.rtf/TXT.rtf
-stdin <<EOF
$bannerText
EOF

```

ID	os_policy_banner_loginwindow_enforce	
References	800-53r5 <ul style="list-style-type: none"> • AC-8 CCE <ul style="list-style-type: none"> • CCE-95257-2 	

9.57. Display Policy Banner at Remote Login

Remote login service *MUST* be configured to display a policy banner at login.

Displaying a standardized and approved use notification before granting access to the operating system ensures that users are provided with privacy and security notification verbiage that is consistent with applicable federal laws, Executive Orders, directives, policies, regulations, standards, and guidance.

System use notifications are required only for access via login interfaces with human users and are not required when such human interfaces do not exist.

To check the state of the system, run the following command(s):

```

bannerText="You are accessing a U.S. Government (USG) Information System (IS) that is
provided for USG-authorized use only. By using this IS (which includes any device
attached to this IS), you consent to the following conditions:
-The USG routinely intercepts and monitors communications on this IS for purposes
including, but not limited to, penetration testing, COMSEC monitoring, network
operations and defense, personnel misconduct (PM), law enforcement (LE), and

```

counterintelligence (CI) investigations.

-At any time, the USG may inspect and seize data stored on this IS.

-Communications using, or data stored on, this IS are not private, are subject to routine monitoring, interception, and search, and may be disclosed or used for any USG authorized purpose.

-This IS includes security measures (e.g., authentication and access controls) to protect USG interests--not for your personal benefit or privacy.

-Notwithstanding the above, using this IS does not constitute consent to PM, LE or CI investigative searching or monitoring of the content of privileged communications, or work product, related to personal representation or services by attorneys, psychotherapists, or clergy, and their assistants. Such communications and work product are private and confidential. See User Agreement for details."

```
test "$(cat /etc/banner)" = "$bannerText" && echo "1" || echo "0"
```

If the result is not 1, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
bannerText="You are accessing a U.S. Government (USG) Information System (IS) that  
is provided for USG-authorized use only. By using this IS (which includes any  
device attached to this IS), you consent to the following conditions:
```

-The USG routinely intercepts and monitors communications on this IS for purposes including, but not limited to, penetration testing, COMSEC monitoring, network operations and defense, personnel misconduct (PM), law enforcement (LE), and counterintelligence (CI) investigations.

-At any time, the USG may inspect and seize data stored on this IS.

-Communications using, or data stored on, this IS are not private, are subject to routine monitoring, interception, and search, and may be disclosed or used for any USG authorized purpose.

-This IS includes security measures (e.g., authentication and access controls) to protect USG interests--not for your personal benefit or privacy.

-Notwithstanding the above, using this IS does not constitute consent to PM, LE or CI investigative searching or monitoring of the content of privileged communications, or work product, related to personal representation or services by attorneys, psychotherapists, or clergy, and their assistants. Such communications and work product are private and confidential. See User Agreement for details."

```
/bin/echo "${bannerText}" > /etc/banner
```

ID	os_policy_banner_ssh_configure	
References	800-53r5 CCE	<ul style="list-style-type: none">AC-8CCE-95258-0

9.58. Enforce SSH to Display Policy Banner

SSH *MUST* be configured to display a policy banner.

Displaying a standardized and approved use notification before granting access to the operating system ensures that users are provided with privacy and security notification verbiage that is consistent with applicable federal laws, Executive Orders, directives, policies, regulations, standards, and guidance.

System use notifications are required only for access via login interfaces with human users and are not required when such human interfaces do not exist



/etc/ssh/sshd_config will be automatically modified to its original state following any update or major upgrade to the operating system.

To check the state of the system, run the following command(s):

```
/usr/sbin/sshd -G | /usr/bin/grep -c "^banner /etc/banner"
```

If the result is not 1, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
include_dir=$( /usr/bin/awk '/^Include/ {print $2}' /etc/ssh/sshd_config |  
/usr/bin/tr -d '*' )  
  
if [[ -z $include_dir ]]; then  
    /usr/bin/sed -i.bk "1s/.*Include \\\\/etc\\\ssh\\\sshd_config.d\\\/*/"  
/etc/ssh/sshd_config  
fi  
  
/usr/bin/grep -qxF 'banner /etc/banner' "${include_dir}01-mscp-sshd.conf"  
2>/dev/null || echo "banner /etc/banner" >> "${include_dir}01-mscp-sshd.conf"  
  
for file in $(ls ${include_dir}); do  
    if [[ "$file" == "100-macos.conf" ]]; then  
        continue  
    fi  
    if [[ "$file" == "01-mscp-sshd.conf" ]]; then  
        break  
    fi  
    /bin/mv ${include_dir}${file} ${include_dir}20-${file}  
done
```

ID	os_policy_banner_ssh_enforce	
References	800-53r5 CCE	<ul style="list-style-type: none"> • AC-8 • CCE-95259-8

9.59. Disable Power Nap

Power Nap *MUST* be disabled.



Power Nap allows your Mac to perform actions while a Mac is asleep. This can interfere with USB power and may cause devices such as smartcards to stop functioning until a reboot and must therefore be disabled on all applicable systems.

The following Macs support Power Nap:

- MacBook (Early 2015 and later)
- MacBook Air (Late 2010 and later)
- MacBook Pro (all models with Retina display)
- Mac mini (Late 2012 and later)
- iMac (Late 2012 and later)
- Mac Pro (Late 2013 and later)

To check the state of the system, run the following command(s):

```
/usr/bin/pmset -g custom | /usr/bin/awk '/powernap/ { sum+=$2 } END {print sum}'
```

If the result is not **0**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/usr/bin/pmset -a powernap 0
```

ID	os_power_nap_disable	
References	800-53r5 CCE	<ul style="list-style-type: none"> • CM-7, CM-7(1) • CCE-95260-6

9.60. Disable Privacy Setup Services During Setup Assistant

The prompt for Privacy Setup services during Setup Assistant *MUST* be disabled.

Organizations *MUST* apply organization-wide configuration settings. The macOS Privacy Setup services prompt guides new users through enabling their own specific privacy settings; this is not essential and, therefore, *MUST* be disabled to prevent against the risk of individuals electing privacy settings with the potential to override organization-wide settings.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript 2>/dev/null << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.SetupAssistant.managed')\
.objectForKey('SkipSetupItems').containsObject("Privacy")
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.SetupAssistant.managed) payload type:

```
<key>SkipSetupItems</key>
<array>
    <string>Privacy</string>
</array>
```

ID	os_privacy_setup_prompt_disable	
References	800-53r5 CCE	<ul style="list-style-type: none">CM-7, CM-7(1)CCE-95267-1

9.61. Enforce Rapid Security Response Mechanism

Rapid security response mechanism *MUST* be enabled.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
```

```
.objectForKey('allowRapidSecurityResponseInstallation').js  
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowRapidSecurityResponseInstallation</key>  
<true/>
```

ID	os_rapid_security_response_allow	
References	800-53r5	<ul style="list-style-type: none">• SI-2, SI-2(5)• SI-3
	CCE	<ul style="list-style-type: none">• CCE-95272-1

9.62. Disable User Ability from Being Able to Undo Rapid Security Responses

Rapid security response (RSR) mechanism *MUST* be enabled and the ability for the user to disable RSR *MUST* be disabled.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS  
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\\  
.objectForKey('allowRapidSecurityResponseRemoval').js  
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowRapidSecurityResponseRemoval</key>
<false/>
```

ID	os_rapid_security_response_removal_disable	
References	800-53r5	<ul style="list-style-type: none">• SI-2, SI-2(5)• SI-3
	CCE	<ul style="list-style-type: none">• CCE-95273-9

9.63. Enable Recovery Lock

A recovery lock password *MUST* be enabled and set.

Single user mode, recovery mode, the Startup Manager, and several other tools are available on macOS by holding down specific key combinations during startup. Setting a recovery lock restricts access to these tools.



Recovery lock passwords are not supported on Intel devices. This rule is only applicable to Apple Silicon devices.

To check the state of the system, run the following command(s):

```
/usr/libexec/mdmclient QuerySecurityInfo 2>/dev/null | /usr/bin/grep -c
"IsRecoveryLockEnabled = 1"
```

If the result is not **1**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:



The SetRecoveryLock command can be used to set a Recovery Lock password and must be from your MDM.

ID	os_recovery_lock_enable	
References	800-53r5	<ul style="list-style-type: none">• AC-6
	CCE	<ul style="list-style-type: none">• CCE-95277-0

9.64. Disable Removable Storage Devices

Removable media, such as USB connected external hard drives, thumb drives, and optical media,

MUST be disabled for users.

Disabling removable storage devices reduces the risks and known vulnerabilities of such devices (e.g., malicious code insertion)



Some organizations rely on the use of removable media for storing and sharing data. Information System Security Officers (ISSOs) may make the risk-based decision not to disable external hard drives to avoid losing this functionality, but they are advised to first fully weigh the potential risks posed to their organization.



Apple has deprecated the use of [media mount controls](#), using these controls may not work as expected. Third party software may be required to fulfill the compliance requirements.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
ObjC.unwrap($.NSUserDefaults.alloc.initWithSuiteName('com.apple.systemuiserver')\
.objectForKey('mount-controls'))["harddisk-external"]
EOS
```

If the result is not **deny**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.systemuiserver) payload type:

```
<key>mount-controls</key>
<dict>
  <array>
    <string>alert</string>
    <string>eject</string>
  </array>
</dict>
```

ID	os_removable_media_disable	
References	800-53r5 CCE	<ul style="list-style-type: none">MP-7CCE-95279-6

9.65. Disable Root Login

To assure individual accountability and prevent unauthorized access, logging in as root at the login window *MUST* be disabled.

The macOS system *MUST* require individuals to be authenticated with an individual authenticator prior to using a group authenticator, and administrator users *MUST* never log in directly as root.

To check the state of the system, run the following command(s):

```
/usr/bin/dscl . -read /Users/root UserShell 2>&1 | /usr/bin/grep -c "/usr/bin/false"
```

If the result is not **1**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/usr/bin/dscl . -create /Users/root UserShell /usr/bin/false
```

ID	os_root_disable	
References	800-53r5	<ul style="list-style-type: none">IA-2, IA-2(5)
	CCE	<ul style="list-style-type: none">CCE-95282-0

9.66. Disable Apple Intelligence Safari Reader Summary

Apple Intelligence features such as Safari Reader Summary that use off device AI *MUST* be disabled.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowSafariSummary').js
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowSafariSummary</key>
<false/>
```

ID	os_safari_reader_summary_disable	
References	800-53r5	<ul style="list-style-type: none">• AC-20, AC-20(1)• CM-7, CM-7(1)• SC-7(10)
	CCE	<ul style="list-style-type: none">• CCE-95286-1

9.67. Enforce Screen Saver at Login Window

A default screen saver *MUST* be configured to display at the login window and *MUST* not display any sensitive information.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.screensaver')\
.objectForKey('moduleName').js
EOS
```

If the result is not **Tahoe**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.screensaver) payload type:

```
<key>moduleName</key>
<string>Tahoe</string>
```

ID	os_screensaver_loginwindow_enforce	
References	800-53r5	<ul style="list-style-type: none">• AC-11(1)
	CCE	<ul style="list-style-type: none">• CCE-95290-3

9.68. Ensure Secure Boot Level Set to Full

The Secure Boot security setting *MUST* be set to full.

Full security is the default Secure Boot setting in macOS. During startup, when Secure Boot is set to full security, the Mac will verify the integrity of the operating system before allowing the operating system to boot.



This will only return a proper result on a T2 or Apple Silicon Macs.

To check the state of the system, run the following command(s):

```
/usr/libexec/mdmclient QuerySecurityInfo 2>/dev/null | /usr/bin/grep -c  
"SecureBootLevel = full"
```

If the result is not **1**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:



Boot into Recovery Mode and enable Full Secure Boot

ID	os_secure_boot_verify		
References	800-53r5	• SI-6	• SI-7, SI-7(1), SI-7(5)
CCE		• CCE-95292-9	

9.69. Enforce FileVault in Setup Assistant

FileVault *MUST* be enforced in Setup Assistant.

The information system implements cryptographic mechanisms to protect the confidentiality and integrity of information stored on digital media during transport outside of controlled areas.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS  
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.MCX.FileVault2')\\  
.objectForKey('ForceEnableInSetupAssistant')  
EOS
```

If the result is not **1**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.MCX.FileVault2) payload type:

```
<key>ForceEnableInSetupAssistant</key>
<true/>
```

ID	os_setup_assistant_filevault_enforce	
References	800-53r5	<ul style="list-style-type: none">SC-28, SC-28(1)
	CCE	<ul style="list-style-type: none">CCE-95296-0

9.70. Ensure System Integrity Protection is Enabled

System Integrity Protection (SIP) *MUST* be enabled.

SIP is vital to protecting the integrity of the system as it prevents malicious users and software from making unauthorized and/or unintended modifications to protected files and folders; ensures the presence of an audit record generation capability for defined auditable events for all operating system components; protects audit tools from unauthorized access, modification, and deletion; restricts the root user account and limits the actions that the root user can perform on protected parts of the macOS; and prevents non-privileged users from granting other users direct access to the contents of their home directories and folders.



SIP is enabled by default in macOS.

To check the state of the system, run the following command(s):

```
/usr/bin/csrutil status | /usr/bin/grep -c 'System Integrity Protection status: enabled.'
```

If the result is not 1, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/usr/bin/csrutil enable
```



To reenable "System Integrity Protection", boot the affected system into

"Recovery" mode, launch "Terminal" from the "Utilities" menu, and run the command.

ID	os_sip_enable	
References	800-53r5	<ul style="list-style-type: none">• AC-3• AU-9, AU-9(3)• CM-5, CM-5(6)• SC-4• SI-2• SI-7
CCE		• CCE-95298-6

9.71. Disable Siri Setup during Setup Assistant

The prompt for Siri during Setup Assistant *MUST* be disabled.

Organizations *MUST* apply organization-wide configuration settings. The macOS Siri Assistant Setup prompt guides new users through enabling their own specific Siri settings; this is not essential and, therefore, *MUST* be disabled to prevent against the risk of individuals electing Siri settings with the potential to override organization-wide settings.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript 2>/dev/null << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.SetupAssistant.managed')\
.objectForKey('SkipSetupItems').containsObject("Siri")
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.SetupAssistant.managed) payload type:

```
<key>SkipSetupItems</key>
<array>
  <string>Siri</string>
</array>
```

ID	os_siri_prompt_disable	
References	800-53r5 CCE	<ul style="list-style-type: none"> • AC-20 • CM-7, CM-7(1) • CCE-95299-4

9.72. Disable Apple Intelligence During Setup Assistant

The prompt for setting up Apple Intelligence during Setup Assistant *MUST* be disabled.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript 2>/dev/null << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.SetupAssistant.managed')\
.objectForKey('SkipSetupItems').containsObject("Intelligence")
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.SetupAssistant.managed) payload type:

```
<key>SkipSetupItems</key>
<array>
    <string>Intelligence</string>
</array>
```

ID	os_skip_apple_intelligence_enable	
References	800-53r5 CCE	<ul style="list-style-type: none"> • AC-20 • AC-4 • CM-7 • CCE-95603-7

9.73. Disable Screen Time Prompt During Setup Assistant

The prompt for Screen Time setup during Setup Assistant *MUST* be disabled.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript 2>/dev/null << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.SetupAssistant.managed')\
.objectForKey('SkipSetupItems').containsObject("ScreenTime")
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.SetupAssistant.managed) payload type:

```
<key>SkipSetupItems</key>
<array>
    <string>ScreenTime</string>
</array>
```

ID	os_skip_screen_time_prompt_enable	
References	800-53r5	<ul style="list-style-type: none">• CM-7, CM-7(1)
	CCE	<ul style="list-style-type: none">• CCE-95300-0

9.74. Disable Unlock with Apple Watch During Setup Assistant

The prompt for Apple Watch unlock setup during Setup Assistant *MUST* be disabled.

Disabling Apple watches is a necessary step to ensuring that the information system retains a session lock until the user reestablishes access using an authorized identification and authentication procedures.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript 2>/dev/null << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.SetupAssistant.managed')\
.objectForKey('SkipSetupItems').containsObject("WatchMigration")
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.SetupAssistant.managed) payload type:

```
<key>SkipSetupItems</key>
<array>
    <string>WatchMigration</string>
</array>
```

ID	os_skip_unlock_with_watch_enable	
References	800-53r5 CCE	<ul style="list-style-type: none">AC-20CCE-95301-8

9.75. Limit SSH to FIPS Compliant Connections

SSH *MUST* be configured to limit the Ciphers, HostbasedAcceptedAlgorithms, HostKeyAlgorithms, KexAlgorithms, MACs, PubkeyAcceptedAlgorithms, CASignatureAlgorithms to algorithms that are FIPS 140 validated.

FIPS 140-3 is the current standard for validating that mechanisms used to access cryptographic modules utilize authentication that meet federal requirements.

Operating systems utilizing encryption *MUST* use FIPS validated mechanisms for authenticating to cryptographic modules.



For more information on FIPS compliance with the version of SSH included in the macOS, the manual page `apple_ssh_and_fips` has additional information.



On macOS 15.2 and higher the SSH configuration can be reset to the macOS default by running `/usr/libexec/reset-ssh-configuration`.

To check the state of the system, run the following command(s):

```
fips_ssh_config=( "Ciphers aes128-gcm@openssh.com" "HostbasedAcceptedAlgorithms ecdsa-sha2-nistp256,ecdsa-sha2-nistp256-cert-v01@openssh.com" "HostKeyAlgorithms ecdsa-sha2-nistp256-cert-v01@openssh.com,sk-ecdsa-sha2-nistp256-cert-v01@openssh.com,ecdsa-sha2-nistp256,sk-ecdsa-sha2-nistp256@openssh.com" "KexAlgorithms ecdh-sha2-nistp256" "MACs hmac-sha2-256-etm@openssh.com,hmac-sha2-256" "PubkeyAcceptedAlgorithms ecdsa-sha2-nistp256,ecdsa-sha2-nistp256-cert-v01@openssh.com,sk-ecdsa-sha2-nistp256-cert-v01@openssh.com" "CASignatureAlgorithms ecdsa-sha2-nistp256,sk-ecdsa-sha2-nistp256@openssh.com" )
```

```

total=0
ret="pass"
for config in $fips_ssh_config; do
    if [[ "$ret" == "fail" ]]; then
        break
    fi
    for u in $(/usr/bin/dscl . list /users shell | /usr/bin/egrep -v
'(^_)|(^root)|(/usr/bin/false)' | /usr/bin/awk '{print $1}'); do
        sshCheck=$((/usr/bin/sudo -u $u /usr/bin/ssh -G . | /usr/bin/grep -ci "$config")
        if [[ "$sshCheck" == "0" ]]; then
            ret="fail"
            break
        fi
    done
done
echo $ret

```

If the result is not **pass**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```

if [ -f /etc/ssh/crypto.conf ] && /usr/bin/grep -q "Include /etc/ssh/crypto.conf"
/etc/ssh/ssh_config.d/100-macos.conf 2>/dev/null; then
    /bin/ln -fs /etc/ssh/crypto/fips.conf /etc/ssh/crypto.conf
fi
include_dir=$((/usr/bin/awk '/^Include/ {print $2}' /etc/ssh/ssh_config |
/usr/bin/tr -d '*')

fips_ssh_config="Ciphers aes128-gcm@openssh.com "HostbasedAcceptedAlgorithms
ecdsa-sha2-nistp256,ecdsa-sha2-nistp256-cert-v01@openssh.com "HostKeyAlgorithms
ecdsa-sha2-nistp256-cert-v01@openssh.com,sk-ecdsa-sha2-nistp256-cert-
v01@openssh.com,ecdsa-sha2-nistp256,sk-ecdsa-sha2-nistp256@openssh.com"
"KexAlgorithms ecdh-sha2-nistp256" "MACs hmac-sha2-256-etm@openssh.com,hmac-sha2-
256" "PubkeyAcceptedAlgorithms ecdsa-sha2-nistp256,ecdsa-sha2-nistp256-cert-
v01@openssh.com,sk-ecdsa-sha2-nistp256-cert-v01@openssh.com"
"CASignatureAlgorithms ecdsa-sha2-nistp256,sk-ecdsa-sha2-nistp256@openssh.com")
for ssh_config in $fips_ssh_config; do
    ssh_setting=$(echo $ssh_config | /usr/bin/cut -d " " -f1)
    /usr/bin/grep -qEi "^\$ssh_setting" "${include_dir}01-mscp-ssh.conf" &&
/usr/bin/sed -i "" "s/^$ssh_setting.*/${ssh_config}/" "${include_dir}01-mscp-
ssh.conf" || echo "$ssh_config" >> "${include_dir}01-mscp-ssh.conf"
    for u in $(/usr/bin/dscl . list /users shell | /usr/bin/egrep -v
'(^_)|(^root)|(/usr/bin/false)' | /usr/bin/awk '{print $1}'); do
        config=$((/usr/bin/sudo -u $u /usr/bin/ssh -Gv . 2>&1)
        configfiles=$(echo "$config" | /usr/bin/awk '/Reading configuration data/
{print $NF}' | /usr/bin/tr -d '\r')
        configarray=( ${!(f)configfiles} )

```

```

if ! echo $config | /usr/bin/grep -q -i "$ssh_config" ; then
    for c in $configarray; do
        if [[ "$c" == "/etc/ssh/crypto.conf" ]]; then
            continue
        fi

        /usr/bin/sudo -u $u /usr/bin/grep -qEi "^\$ssh_setting" "$c" &&
/usr/bin/sed -i "" "s/^$ssh_setting.*/${ssh_config}/I" "$c"
        if [[ "$c" =~ ".ssh/config" ]]; then
            if /usr/bin/grep -qEi "$ssh_setting" "$c" 2> /dev/null; then
                old_file=$(cat ~$u/.ssh/config)
                echo "$ssh_config" > ~$u/.ssh/config
                echo "$old_file" >> ~$u/.ssh/config
            fi
        fi
    done
fi
done
done

```

ID	os_ssh_fips_compliant	
References	800-53r5 CCE	<ul style="list-style-type: none"> • AC-17(2) • IA-7 • SC-13 • SC-8(1) • CCE-95304-2

9.76. Set SSH Active Server Alive Maximum to 0

SSH *MUST* be configured with an Active Server Alive Maximum Count set to 0. Terminating an idle session within a short time period reduces the window of opportunity for unauthorized personnel to take control of a management session enabled on the console or console port that has been left unattended. In addition, quickly terminating an idle session or an incomplete login attempt will also free up resources committed by the managed network element.



/etc/ssh/ssh_config will be automatically modified to its original state following any update or major upgrade to the operating system.



On macOS 15.2 and higher the SSH configuration can be reset to the macOS default by running /usr/libexec/reset-ssh-configuration.

To check the state of the system, run the following command(s):

```
ret="pass"
```

```

for u in $(/usr/bin/dscl . -list /Users UniqueID | /usr/bin/awk '$2 > 500 {print $1}'
); do
    sshCheck=$(sudo -u $u /usr/bin/ssh -G . | grep -c
"ServerAliveCountMax 0")
    if [[ "$sshCheck" == "0" ]]; then
        ret="fail"
        break
    fi
done
/bin/echo $ret

```

If the result is not **pass**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```

include_dir=$(awk '/^Include/ {print $2}' /etc/ssh/ssh_config |
/usr/bin/tr -d '*')

ssh_config="ServerAliveCountMax 0"

ssh_setting=$(echo $ssh_config | cut -d " " -f1)
/usr/bin/grep -qEi "^$ssh_setting" "${include_dir}01-mscp-ssh.conf" &&
/usr/bin/sed -i "" "s/^$ssh_setting.*/${ssh_config}/" "${include_dir}01-mscp-
ssh.conf" || echo "$ssh_config" >> "${include_dir}01-mscp-ssh.conf"
for u in $(/usr/bin/dscl . list /users shell | egrep -v
'(^_)|(root)|(false)' | awk '{print $1}'); do
    config=$(sudo -u $u /usr/bin/ssh -Gv . 2>&1)
    configfiles=$(echo "$config" | awk '/Reading configuration data/ {print
$NF}' | tr -d '\r')
    configarray=( ${configfiles} )
    if ! echo $config | grep -q -i "$ssh_config" ; then
        for c in ${configarray}; do
            if [[ "$c" == "/etc/ssh/crypto.conf" ]]; then
                continue
            fi
            /usr/bin/sudo -u $u /usr/bin/grep -qEi "^$ssh_setting" "$c" && /usr/bin/sed
-i "" "s/^$ssh_setting.*/${ssh_config}/I" "$c"
            if [[ "$c" =~ ".ssh/config" ]]; then
                if /usr/bin/grep -qEi "$ssh_setting" "$c" 2> /dev/null; then
                    old_file=$(cat ~$u/.ssh/config)
                    echo "$ssh_config" > ~$u/.ssh/config
                    echo "$old_file" >> ~$u/.ssh/config
                fi
            fi
        done
    fi

```

done

ID	os_ssh_server_alive_count_max_configure	
References	800-53r5	• SC-10
	CCE	• CCE-95305-9

9.77. Configure SSH ServerAliveInterval option set to 900

SSH *MUST* be configured with an Active Server Alive Maximum Count set to 900.

Setting the Active Server Alive Maximum Count to 900 will log users out after a 900 seconds interval of inactivity.



/etc/ssh/ssh_config will be automatically modified to its original state following any update or major upgrade to the operating system.



On macOS 15.2 and higher the SSH configuration can be reset to the macOS default by running /usr/libexec/reset-ssh-configuration.

To check the state of the system, run the following command(s):

```
ret="pass"
for u in $(/usr/bin/dscl . -list /Users UniqueID | /usr/bin/awk '$2 > 500 {print $1}')
); do
    sshCheck=$(sudo -u $u /usr/bin/ssh -G . | grep -c "serveraliveinterval 900")
    if [[ "$sshCheck" == "0" ]]; then
        ret="fail"
        break
    fi
done
/bin/echo $ret
```

If the result is not **pass**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
include_dir=$(awk '/^Include/ {print $2}' /etc/ssh/ssh_config |
/usr/bin/tr -d '*')
```

```

ssh_config_string="ServerAliveInterval 900"
for ssh_config in $ssh_config_string; do
    ssh_setting=$(echo $ssh_config | /usr/bin/cut -d " " -f1)
    /usr/bin/grep -qEi "^$ssh_setting" "${include_dir}01-mscp-ssh.conf" &&
/usr/bin/sed -i "" "s/^$ssh_setting.*/${ssh_config}/" "${include_dir}01-mscp-
ssh.conf" || echo "$ssh_config" >> "${include_dir}01-mscp-ssh.conf"
    for u in $(/usr/bin/dscl . list /users shell | /usr/bin/egrep -v
'(^_)|(root)|(/usr/bin/false)' | /usr/bin/awk '{print $1}'); do
        config=$((/usr/bin/sudo -u $u /usr/bin/ssh -Gv . 2>&1))
        configfiles=$(echo "$config" | /usr/bin/awk '/Reading configuration data/
{print $NF}'| /usr/bin/tr -d '\r')
        configarray=( ${!(f)configfiles} )
        if ! echo $config | /usr/bin/grep -q -i "$ssh_config" ; then
            for c in $configarray; do
                if [[ "$c" == "/etc/ssh/crypto.conf" ]]; then
                    continue
                fi

                /usr/bin/sudo -u $u /usr/bin/grep -qEi "^$ssh_setting" "$c" &&
/usr/bin/sed -i "" "s/^$ssh_setting.*/${ssh_config}/I" "$c"
                if [[ "$c" =~ ".ssh/config" ]]; then
                    if /usr/bin/grep -qEi "$ssh_setting" "$c" 2> /dev/null; then
                        old_file=$(cat ~$u/.ssh/config)
                        echo "$ssh_config" > ~$u/.ssh/config
                        echo "$old_file" >> ~$u/.ssh/config
                    fi
                fi
            done
        fi
    done
done
done

```

ID	os_ssh_server_alive_interval_configure	
References	800-53r5	<ul style="list-style-type: none"> • AC-12 • SC-10
	CCE	<ul style="list-style-type: none"> • CCE-95306-7

9.78. Configure SSHD Channel Timeout to session:=*=900

If SSHD is enabled it *MUST* be configured with session ChannelTime out set to session:=*=900.

This will set the time out when the session is inactive.



/etc/ssh/sshd_config will be automatically modified to its original state following any update or major upgrade to the operating system.



On macOS 15.2 and higher the SSH configuration can be reset to the macOS default by running /usr/libexec/reset-ssh-configuration.

To check the state of the system, run the following command(s):

```
/usr/sbin/sshd -G | /usr/bin/awk '/channeltimeout/{print $2}'
```

If the result is not **session:=900***, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
include_dir=$(/usr/bin/awk '/^Include/ {print $2}' /etc/ssh/sshd_config | /usr/bin/tr -d '*')

if [[ -z $include_dir ]]; then
    /usr/bin/sed -i.bk "1s/.*/Include \\\`etc\\\`ssh\\\`sshd_config.d\\\`*/"
/etc/ssh/sshd_config
fi

/usr/bin/grep -qxF 'channeltimeout session:=900' "${include_dir}01-mscp-
sshd.conf" 2>/dev/null || echo "channeltimeout session:=900" >> "${include_dir}
01-mscp-sshd.conf"

for file in $(ls ${include_dir}); do
    if [[ "$file" == "100-macos.conf" ]]; then
        continue
    fi
    if [[ "$file" == "01-mscp-sshd.conf" ]]; then
        break
    fi
    /bin/mv ${include_dir}${file} ${include_dir}20-${file}
done
```

ID	os_sshd_channel_timeout_configure	
References	800-53r5	<ul style="list-style-type: none">AC-12SC-10
	CCE	<ul style="list-style-type: none">CCE-95307-5

9.79. Configure SSHD ClientAliveCountMax to 0

If SSHD is enabled it *MUST* be configured with the Client Alive Maximum Count set to 0.

This will set the number of client alive messages which may be sent without the SSH server receiving any messages back from the client. If this threshold is reached while client alive messages are being sent, the SSH server will disconnect the client, terminating the session. The client alive messages are sent through the encrypted channel and therefore will not be spoofable. The client alive mechanism is valuable when the client or server depend on knowing when a connection has become unresponsive.



This setting is not intended to manage idle user sessions where there is no input from the client. Its purpose is to monitor for interruptions in network connectivity and force the session to terminate after the connection appears to be broken.



On macOS 15.2 and higher the SSH configuration can be reset to the macOS default by running /usr/libexec/reset-ssh-configuration.

To check the state of the system, run the following command(s):

```
/usr/sbin/sshd -G | /usr/bin/awk '/clientalivecountmax/{print $2}'
```

If the result is not **0**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
include_dir=$(/usr/bin/awk '/^Include/ {print $2}' /etc/ssh/sshd_config | /usr/bin/tr -d '*')

if [[ -z $include_dir ]]; then
    /usr/bin/sed -i.bk "1s/.*/Include \\\`etc\\\`ssh\\\`sshd_config.d\\\`/*/" /etc/ssh/sshd_config
fi

/usr/bin/grep -qxF 'clientalivecountmax 0' "${include_dir}01-mscp-sshd.conf"
2>/dev/null || echo "clientalivecountmax 0" >> "${include_dir}01-mscp-sshd.conf"

for file in $(ls ${include_dir}); do
    if [[ "$file" == "100-macos.conf" ]]; then
        continue
    fi
    if [[ "$file" == "01-mscp-sshd.conf" ]]; then
        break
    fi
    /bin/mv ${include_dir}${file} ${include_dir}20-${file}
done
```

ID	os_sshd_client_alive_count_max_configure	
References	800-53r5 CCE	<ul style="list-style-type: none"> SC-10 CCE-95308-3

9.80. Configure SSHD ClientAliveInterval to 900

If SSHD is enabled then it *MUST* be configured with the Client Alive Interval set to 900.

Sets a timeout interval in seconds after which if no data has been received from the client, sshd(8) will send a message through the encrypted channel to request a response from the client.

This setting works in conjunction with ClientAliveCountMax to determine the termination of the connection after the threshold has been reached.



This setting is not intended to manage idle user sessions where there is no input from the client. Its purpose is to monitor for interruptions in network connectivity and force the session to terminate after the connection appears to be broken.



On macOS 15.2 and higher the SSH configuration can be reset to the macOS default by running /usr/libexec/reset-ssh-configuration.

To check the state of the system, run the following command(s):

```
/usr/sbin/sshd -G | /usr/bin/awk '/clientaliveinterval/{print $2}'
```

If the result is not **900**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
include_dir=$(/usr/bin/awk '/^Include/ {print $2}' /etc/ssh/sshd_config | /usr/bin/tr -d '*')

if [[ -z $include_dir ]]; then
    /usr/bin/sed -i.bk "1s/.*/Include \\/etc\\\/ssh\\\/sshd_config.d\\\/\\/*/" /etc/ssh/sshd_config
fi

/usr/bin/grep -qxF 'clientaliveinterval 900' "${include_dir}01-mscp-sshd.conf" 2>/dev/null || echo "clientaliveinterval 900" >> "${include_dir}01-mscp-sshd.conf"

for file in $(ls ${include_dir}); do
    if [[ "$file" == "100-macos.conf" ]]; then
        continue
    fi
done
```

```

fi
if [[ "$file" == "01-mscp-sshd.conf" ]]; then
    break
fi
/bin/mv ${include_dir}${file} ${include_dir}20-${file}
done

```

ID	os_sshd_client_alive_interval_configure		
References	800-53r5	<ul style="list-style-type: none"> • AC-12 • SC-10 	CCE

9.81. Limit SSHD to FIPS Compliant Connections

If SSHD is enabled then it *MUST* be configured to limit the Ciphers, HostbasedAcceptedAlgorithms, HostKeyAlgorithms, KexAlgorithms, MACs, PubkeyAcceptedAlgorithms, CASignatureAlgorithms to algorithms that are FIPS 140 validated.

FIPS 140-3 is the current standard for validating that mechanisms used to access cryptographic modules utilize authentication that meet federal requirements.

Operating systems utilizing encryption *MUST* use FIPS validated mechanisms for authenticating to cryptographic modules.



For more information on FIPS compliance with the version of SSHD included in the macOS, the manual page `apple_ssh_and_fips` has additional information.



On macOS 15.2 and higher the SSH configuration can be reset to the macOS default by running `/usr/libexec/reset-ssh-configuration`.

To check the state of the system, run the following command(s):

```

fips_sshd_config=( "Ciphers aes128-gcm@openssh.com" "HostbasedAcceptedAlgorithms ecdsa-sha2-nistp256,ecdsa-sha2-nistp256-cert-v01@openssh.com" "HostKeyAlgorithms ecdsa-sha2-nistp256-cert-v01@openssh.com,sk-ecdsa-sha2-nistp256-cert-v01@openssh.com,ecdsa-sha2-nistp256,sk-ecdsa-sha2-nistp256@openssh.com" "KexAlgorithms ecdh-sha2-nistp256" "MACs hmac-sha2-256-etm@openssh.com,hmac-sha2-256" "PubkeyAcceptedAlgorithms ecdsa-sha2-nistp256,ecdsa-sha2-nistp256-cert-v01@openssh.com,sk-ecdsa-sha2-nistp256-cert-v01@openssh.com" "CASignatureAlgorithms ecdsa-sha2-nistp256,sk-ecdsa-sha2-nistp256@openssh.com" )
total=0
for config in ${fips_sshd_config}; do
    total=$(expr $(/usr/sbin/sshd -G | /usr/bin/grep -i -c "$config") + $total)
done

```

```
echo $total
```

If the result is not 7, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
if [ -f /etc/ssh/crypto.conf ] && /usr/bin/grep -q "Include /etc/ssh/crypto.conf" /etc/ssh/sshd_config.d/100-macos.conf 2>/bin/null; then
    /bin/ln -fs /etc/ssh/crypto/fips.conf /etc/ssh/crypto.conf
fi

include_dir=$(/usr/bin/awk '/^Include/ {print $2}' /etc/ssh/sshd_config | /usr/bin/tr -d '*')

if [[ -z $include_dir ]]; then
    /usr/bin/sed -i.bk "1s/.*/Include \\\`etc\\\`ssh\\\`sshd_config.d\\\`/*/" /etc/ssh/sshd_config
fi

fips_sshd_config="Ciphers aes128-gcm@openssh.com" "HostbasedAcceptedAlgorithms ecdsa-sha2-nistp256,ecdsa-sha2-nistp256-cert-v01@openssh.com" "HostKeyAlgorithms ecdsa-sha2-nistp256-cert-v01@openSSH.com,sk-ecdsa-sha2-nistp256-cert-v01@openSSH.com,ecdsa-sha2-nistp256,sk-ecdsa-sha2-nistp256@openSSH.com" "KexAlgorithms ecdh-sha2-nistp256" "MACs hmac-sha2-256-etm@openSSH.com,hmac-sha2-256" "PubkeyAcceptedAlgorithms ecdsa-sha2-nistp256,ecdsa-sha2-nistp256-cert-v01@openSSH.com,sk-ecdsa-sha2-nistp256-cert-v01@openSSH.com"
"CASignatureAlgorithms ecdsa-sha2-nistp256,sk-ecdsa-sha2-nistp256@openSSH.com"
sshd_config=$(/usr/sbin/sshd -G)
for config in $fips_sshd_config; do
    if ! echo $sshd_config | /usr/bin/grep -q -i "$config" 2>/dev/null; then
        /usr/bin/grep -qxF "$config" "${include_dir}01-mscp-sshd.conf" 2>/dev/null ||
        echo "$config" >> "${include_dir}01-mscp-sshd.conf"
    fi
done

for file in $(ls ${include_dir}); do
    if [[ "$file" == "100-macos.conf" ]]; then
        continue
    fi
    if [[ "$file" == "01-mscp-sshd.conf" ]]; then
        break
    fi
    /bin/mv ${include_dir}${file} ${include_dir}20-${file}
done
```

ID	os_sshd_fips_compliant	
References	800-53r5	<ul style="list-style-type: none"> • AC-17(2) • IA-7 • SC-13 • SC-8(1)
	CCE	• CCE-95310-9

9.82. Set Login Grace Time to 30

If SSHD is enabled then it *MUST* be configured to wait only 30 seconds before timing out logon attempts.



On macOS 15.2 and higher the SSH configuration can be reset to the macOS default by running /usr/libexec/reset-ssh-configuration.

To check the state of the system, run the following command(s):

```
/usr/sbin/sshd -G | /usr/bin/awk '/logingracetime/{print $2}'
```

If the result is not **30**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
include_dir=$(/usr/bin/awk '/^Include/ {print $2}' /etc/ssh/sshd_config | /usr/bin/tr -d '*')
if [[ -z $include_dir ]]; then
    /usr/bin/sed -i.bk "1s/.*/Include \\\`etc\\\`ssh\\\`sshd_config.d\\\`/*/" /etc/ssh/sshd_config
fi

/usr/bin/grep -qxF 'logingracetime 30' "${include_dir}01-mscp-sshd.conf"
2>/dev/null || echo "logingracetime 30" >> "${include_dir}01-mscp-sshd.conf"

for file in $(ls ${include_dir}); do
    if [[ "$file" == "100-macos.conf" ]]; then
        continue
    fi
    if [[ "$file" == "01-mscp-sshd.conf" ]]; then
        break
    fi
    /bin/mv ${include_dir}${file} ${include_dir}20-${file}
```

done

ID	os_sshd_login_grace_time_configure	
References	800-53r5 CCE	<ul style="list-style-type: none">SC-10CCE-95311-7

9.83. Configure SSHD PerSourcePenalties

If SSHD is enabled then it *MUST* be configured with the Per Source Penalties configured.

Per Source Penalties controls penalties for various conditions that may represent attacks on sshd.

Penalties are enabled by default.



On macOS 15.2 and higher the SSH configuration can be reset to the macOS default by running /usr/libexec/reset-ssh-configuration.

To check the state of the system, run the following command(s):

```
/usr/sbin/sshd -G | /usr/bin/grep -q "persourcepenalties no" && echo "no" || echo "yes"
```

If the result is not yes, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
include_dir=$(./usr/bin/awk '/^Include/ {print $2}' /etc/ssh/sshd_config |  
/usr/bin/tr -d '*')  
  
if [[ -z $include_dir ]]; then  
    /usr/bin/sed -i.bk "1s/.*/Include \\\`/etc\\\`/ssh\\\`/sshd_config.d\\\`/*/"  
    /etc/ssh/sshd_config  
fi  
  
/usr/bin/grep -qxF 'persourcepenalties yes' "${include_dir}01-mscp-sshd.conf"  
2>/dev/null || echo "persourcepenalties yes" >> "${include_dir}01-mscp-sshd.conf"  
  
for file in $(ls ${include_dir}); do  
    if [[ "$file" == "100-macos.conf" ]]; then  
        continue  
    fi  
    if [[ "$file" == "01-mscp-sshd.conf" ]]; then  
        break  
    fi
```

```

fi
/bin/mv ${include_dir}${file} ${include_dir}20-${file}
done

```

ID	os_sshd_per_source_penalties_configure	
References	800-53r5 <ul style="list-style-type: none"> • SC-5 CCE <ul style="list-style-type: none"> • CCE-95312-5 	

9.84. Disable Root Login for SSH

If SSH is enabled to assure individual accountability and prevent unauthorized access, logging in as root via SSH *MUST* be disabled.

The macOS system *MUST* require individuals to be authenticated with an individual authenticator prior to using a group authenticator, and administrator users *MUST* never log in directly as root.



On macOS 15.2 and higher the SSH configuration can be reset to the macOS default by running /usr/libexec/reset-ssh-configuration.

To check the state of the system, run the following command(s):

```
/usr/sbin/sshd -G | /usr/bin/awk '/permitrootlogin/{print $2}'
```

If the result is not **no**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```

include_dir=$(/usr/bin/awk '/^Include/ {print $2}' /etc/ssh/sshd_config |
/usr/bin/tr -d '*')
if [[ -z $include_dir ]]; then
/usr/bin/sed -i.bk "1s/.*/Include \\\`/etc\\`/ssh\\`/sshd_config.d\\\`/*/" \
/etc/ssh/sshd_config
fi

/usr/bin/grep -qxF 'permitrootlogin no' "${include_dir}01-mscp-sshd.conf"
2>/dev/null || echo "permitrootlogin no" >> "${include_dir}01-mscp-sshd.conf"

for file in $(ls ${include_dir}); do
if [[ "$file" == "100-macos.conf" ]]; then
continue
fi

```

```

if [[ "$file" == "01-mscp-sshd.conf" ]]; then
    break
fi
/bin/mv ${include_dir}${file} ${include_dir}20-${file}
done

```

ID	os_sshd_permit_root_login_configure	
References	800-53r5	<ul style="list-style-type: none"> • IA-2(5)
	CCE	<ul style="list-style-type: none"> • CCE-95313-3

9.85. Configure SSHD Unused Connection Timeout to 900

If SSHD is enabled it *MUST* be configured with unused connection timeout set to 900.

This will set the time out when there are no open channels within an session.



On macOS 15.2 and higher the SSH configuration can be reset to the macOS default by running /usr/libexec/reset-ssh-configuration.

To check the state of the system, run the following command(s):

```
/usr/sbin/sshd -G | /usr/bin/awk '/unusedconnectiontimeout/{print $2}'
```

If the result is not **900**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```

include_dir=$(./usr/bin/awk '/^Include/ {print $2}' /etc/ssh/sshd_config |
/usr/bin/tr -d '*')

if [[ -z $include_dir ]]; then
    /usr/bin/sed -i.bk "1s/.*/Include \\\`etc\\\`ssh\\\`sshd_config.d\\\`*/"
/etc/ssh/sshd_config
fi

/usr/bin/grep -qxF 'unusedconnectiontimeout 900' "${include_dir}01-mscp-sshd.conf"
2>/dev/null || echo "unusedconnectiontimeout 900" >> "${include_dir}01-mscp-
sshd.conf"

for file in $(ls ${include_dir}); do
    if [[ "$file" == "100-macos.conf" ]]; then

```

```

        continue
    fi
    if [[ "$file" == "01-mscp-sshd.conf" ]]; then
        break
    fi
/bin/mv ${include_dir}${file} ${include_dir}20-${file}
done

```

ID	os_sshd_unused_connection_timeout_configure		
References	800-53r5	• AC-12	• SC-10
	CCE	• CCE-95314-1	

9.86. Configure Sudo To Log Events

Sudo *MUST* be configured to log privilege escalation.

To check the state of the system, run the following command(s):

```
/usr/bin/sudo /usr/bin/sudo -V | /usr/bin/grep -c "Log when a command is allowed by sudoers"
```

If the result is not **1**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```

/usr/bin/find /etc/sudoers* -type f -exec sed -i ''
'/^Defaults[[:blank:]]*!log_allowed/s/^/# /' '{}';
/bin/echo "Defaults log_allowed" >> /etc/sudoers.d/mscp

```

ID	os_sudo_log_enforce		
References	800-53r5	• AC-6(9)	
	CCE	• CCE-95316-6	

9.87. Configure Sudoers Timestamp Type

The file `/etc/sudoers` *MUST* be configured to not include a `timestamp_type` of `global` or `ppid` and be configured for timestamp record types of `tty`.

This rule ensures that the "sudo" command will prompt for the administrator's password at least once in each newly opened terminal window. This prevents a malicious user from taking advantage of an unlocked computer or an abandoned logon session by bypassing the normal password prompt requirement.

To check the state of the system, run the following command(s):

```
/usr/bin/sudo /usr/bin/sudo -V | /usr/bin/awk -F": " '/Type of authentication  
timestamp record/{print $2}'
```

If the result is not **tty**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/usr/bin/find /etc/sudoers* -type f -exec sed -i '' '/timestamp_type/d;  
!/tty_tickets/d' '{}' \;
```

ID	os_sudoers_timestamp_type_configure		
References	800-53r5	<ul style="list-style-type: none">CM-5(1)IA-11	
	CCE	<ul style="list-style-type: none">CCE-95318-2	

9.88. Ensure System Volume is Read Only

The System volume *MUST* be mounted as read-only in order to ensure that configurations critical to the integrity of the macOS have not been compromised. System Integrity Protection (SIP) will prevent the system volume from being mounted as writable.



The system volume is read only by default in macOS.

To check the state of the system, run the following command(s):

```
/usr/sbin/system_profiler SPStorageDataType | /usr/bin/awk '/Mount Point:  
\$/{x=NR+2}{NR==x}{print $2}'
```

If the result is not **No**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:



To remount the System volume as Read Only, rebooting the computer will mount it as Read Only.

ID	os_system_read_only	
References	800-53r5	<ul style="list-style-type: none">• MA-4(1)• SC-34• SI-7
	CCE	<ul style="list-style-type: none">• CCE-95319-0

9.89. Disable Trivial File Transfer Protocol Service

If the system does not require Trivial File Transfer Protocol (TFTP), support it is non-essential and *MUST* be disabled.

The information system *MUST* be configured to provide only essential capabilities. Disabling TFTP helps prevent the unauthorized connection of devices and the unauthorized transfer of information.



TFTP service is disabled at startup by default macOS.

To check the state of the system, run the following command(s):

```
result="FAIL"
enabled=$(/bin/launchctl print-disabled system | /usr/bin/grep '"com.apple.tftpd" =>
enabled')
running=$(/bin/launchctl print system/com.apple.tftpd 2>/dev/null)

if [[ -z "$running" ]] && [[ -z "$enabled" ]]; then
    result="PASS"
elif [[ -n "$running" ]]; then
    result=result+" RUNNING"
elif [[ -n "$enabled" ]]; then
    result=result+" ENABLED"
fi
echo $result
```

If the result is not **PASS**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/bin/launchctl bootout system/com.apple.tftpd
```

```
/bin/launchctl disable system/com.apple.tftpd
```

The system may need to be restarted for the update to take effect.

ID	os_tftpd_disable	
References	800-53r5	<ul style="list-style-type: none">• AC-17• AC-3• IA-5(1) CCE

9.90. Enable Time Synchronization Daemon

The macOS time synchronization daemon (`timed`) *MUST* be enabled for proper time synchronization to an authorized time server.



The time synchronization daemon is enabled by default on macOS.

To check the state of the system, run the following command(s):

```
/bin/launchctl print system | /usr/bin/grep -c -E '\tcom.apple.timed'
```

If the result is not **1**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/bin/launchctl load -w /System/Library/LaunchDaemons/com.apple.timed.plist
```



The service `timed` cannot be unloaded or loaded while System Integrity Protection (SIP) is enabled.

ID	os_time_server_enabled	
References	800-53r5	<ul style="list-style-type: none">• AU-12(1)• SC-45(1) CCE

9.91. Disable TouchID Prompt during Setup Assistant

The prompt for TouchID during Setup Assistant *MUST* be disabled.

macOS prompts new users through enabling TouchID during Setup Assistant; this is not essential and, therefore, *MUST* be disabled to prevent against the risk of individuals electing to enable TouchID to override organization-wide settings.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript 2>/dev/null << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.SetupAssistant.managed')\
.objectForKey('SkipSetupItems').containsObject("Biometric")
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.SetupAssistant.managed) payload type:

```
<key>SkipSetupItems</key>
<array>
    <string>Biometric</string>
</array>
```

ID	os_touchid_prompt_disable		
References	800-53r5 CCE	• CM-6 • CCE-95326-5	

9.92. Disable Login to Other User's Active and Locked Sessions

The ability to log in to another user's active or locked session *MUST* be disabled.

macOS has a privilege that can be granted to any user that will allow that user to unlock active user's sessions. Disabling the admins and/or user's ability to log into another user's active and locked session prevents unauthorized persons from viewing potentially sensitive and/or personal information.



Configuring this setting will change the user experience and disable TouchID from

unlocking the screensaver. A configuration profile will be generated to include the setting that restores the expected behavior. You can also apply the settings using

```
/usr/bin/sudo           /usr/bin/defaults      write  
/Library/Preferences/com.apple.loginwindow screenUnlockMode -int 1.
```



This rule may cause issues when platformSSO is configured.

To check the state of the system, run the following command(s):

```
RESULT="FAIL"  
SS_RULE=$(/usr/bin/security -q authorizationdb read system.login.screensaver 2>&1 |  
/usr/bin/xmllint --xpath "//dict/key[.='rule']/following-  
sibling::array[1]/string/text()" -)  
  
if [[ "${SS_RULE}" == "authenticate-session-owner" ]]; then  
    RESULT="PASS"  
else  
    PSSO_CHECK=$(/usr/bin/security -q authorizationdb read "$SS_RULE" 2>&1 |  
/usr/bin/xmllint --xpath '//key[.="rule"]/following-sibling::array[1]/string/text()' -)  
    if /usr/bin/grep -Fxq "authenticate-session-owner" <<<"$PSSO_CHECK"; then  
        RESULT="PASS"  
    fi  
fi  
  
echo $RESULT
```

If the result is not **PASS**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.loginwindow) payload type:

```
<key>screenUnlockMode</key>  
<integer>1</integer>
```

ID	os_unlock_active_user_session_disable	
References	800-53r5 CCE	<ul style="list-style-type: none">IA-2, IA-2(5)CCE-95328-1

9.93. Prohibit User Installation of Software into /Users/

Users *MUST* not be allowed to install software into /Users/.

Allowing regular users to install software, without explicit privileges, presents the risk of untested and potentially malicious software being installed on the system. Explicit privileges (escalated or administrative privileges) provide the regular user with explicit capabilities and control that exceeds the rights of a regular user.



Apple has deprecated the use of [application restriction controls](#), using these controls may not work as expected. Third party software may be required to fulfill the compliance requirements.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript <> EOS
function run() {
    let pref1 = ObjC.unwrap(
        $.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess.new')\
            .objectForKey('familyControlsEnabled'))
    let pathlist =
        $.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess.new')\
            .objectForKey('pathBlackList').js
    for ( let app in pathlist ) {
        if ( ObjC.unwrap(pathlist[app]) == "/Users/" && pref1 == true ){
            return("true")
        }
    }
    return("false")
}
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess.new) payload type:

```
<key>familyControlsEnabled</key>
<true/>
<key>pathBlackList</key>
<array>
    <string>/Users/</string>
</array>
```

ID	os_user_app_installation_prohibit	
References	800-53r5 CCE	<ul style="list-style-type: none">CM-11(2)CCE-95329-9

9.94. Disable Unix-to-Unix Copy Protocol Service

The system *MUST* not have the Unix-to-Unix Copy Protocol (UUCP) service active.

UUCP, a set of programs that enable the sending of files between different UNIX systems as well as sending commands to be executed on another system, is not essential and *MUST* be disabled in order to prevent the unauthorized connection of devices, transfer of information, and tunneling.



UUCP service is disabled at startup by default macOS.

To check the state of the system, run the following command(s):

```
result="FAIL"
enabled=$(/bin/launchctl print-disabled system | /usr/bin/grep '"com.apple.uucp" =>
enabled')
running=$(/bin/launchctl print system/com.apple.uucp 2>/dev/null)

if [[ -z "$running" ]] && [[ -z "$enabled" ]]; then
    result="PASS"
elif [[ -n "$running" ]]; then
    result=result+" RUNNING"
elif [[ -n "$enabled" ]]; then
    result=result+" ENABLED"
fi
echo $result
```

If the result is not **PASS**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/bin/launchctl bootout system/com.apple.uucp
/bin/launchctl disable system/com.apple.uucp
```

The system may need to be restarted for the update to take effect.

ID	os_uucp_disable
-----------	-----------------

References	800-53r5	<ul style="list-style-type: none"> • AC-17 • AC-3
	CCE	<ul style="list-style-type: none"> • CCE-95330-7

9.95. Disable Apple Intelligence Writing Tools

Apple Intelligence features such as writing tools that use off device AI *MUST* be disabled.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowWritingTools').js
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowWritingTools</key>
<false/>
```

ID	os_writing_tools_disable	
References	800-53r5	<ul style="list-style-type: none"> • AC-20, AC-20(1) • CM-7, CM-7(1) • SC-7(10)
	CCE	<ul style="list-style-type: none"> • CCE-95334-9

Chapter 10. Password Policy

This section contains the configuration and enforcement of settings pertaining to password policies in macOS.



The check/fix commands outlined in this section *MUST* be run by a user with elevated privileges.



The password policy recommendations in the NIST 800-53 (Rev 5) and NIST 800-63B state that complexity rules should be organizationally defined. The values defined are based off of common complexity values. But your organization may define its own password complexity rules.



The settings outlined in this section adhere to the recommendations provided in this document for systems that utilize passwords for local accounts. If systems are integrated with a directory service, local password policies should align with domain password policies to the fullest extent feasible.

10.1. Disable Accounts after 35 Days of Inactivity

The macOS *MUST* be configured to disable accounts after 35 days of inactivity.

This rule prevents malicious users from making use of unused accounts to gain access to the system while avoiding detection.

To check the state of the system, run the following command(s):

```
/usr/bin/pwpolicy -getaccountpolicies 2> /dev/null | /usr/bin/tail +2 |  
/usr/bin/xmllint --xpath '//dict/key[text()="policyAttributeInactiveDays"]/following-  
sibling::integer[1]/text()' -
```

If the result is not **35**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

This setting may be enforced using local policy or by a directory service.

To set local policy to disable an inactive user after 35 days, edit the current password policy to contain the following <dict> within the "policyCategoryAuthentication":

```
<dict>  
<key>policyContent</key>  
<string>policyAttributeLastAuthenticationTime &gt; policyAttributecurrentTime -  
(policyAttributeInactiveDays * 24 * 60 * 60)</string>
```

```
<key>policyIdentifier</key>
<string>Inactive Account</string>
<key>policyParameters</key>
<dict>
<key>policyAttributeInactiveDays</key>
<integer>35</integer>
</dict>
</dict>
```

After saving the file and exiting to the command prompt, run the following command to load the new policy file, substituting the path to the file in place of "\$pwpolicy_file".

```
/usr/bin/pwpolicy setaccountpolicies $pwpolicy_file
```



See the password policy supplemental on more information on how to implement password policies on macOS.

ID	pwpolicy_account_inactivity_enforce	
References	800-53r5 CCE	<ul style="list-style-type: none">AC-2(3)CCE-95336-4

10.2. Limit Consecutive Failed Login Attempts to 3

The macOS *MUST* be configured to limit the number of failed login attempts to a maximum of 3. When the maximum number of failed attempts is reached, the account *MUST* be locked for a period of time after.

This rule protects against malicious users attempting to gain access to the system via brute-force hacking methods.

To check the state of the system, run the following command(s):

```
/usr/bin/pwpolicy -getaccountpolicies 2> /dev/null | /usr/bin/tail +2 |
/usr/bin/xmllint --xpath
'//dict/key[text()="policyAttributeMaximumFailedAuthentications"]/following-
sibling::integer[1]/text()' - | /usr/bin/awk '{ if ($1 <= 3) {print "pass"} else
{print "fail"}}' | /usr/bin/uniq
```

If the result is not **pass**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.mobiledevice.passwordpolicy) payload type:

```
<key>maxFailedAttempts</key>
<integer>3</integer>
```

ID	pwpolicy_account_lockout_enforce	
References	800-53r5 CCE	<ul style="list-style-type: none">• AC-7• CCE-95337-2

10.3. Set Account Lockout Time to 15 Minutes

The macOS *MUST* be configured to enforce a lockout time period of at least 15 minutes when the maximum number of failed logon attempts is reached.

This rule protects against malicious users attempting to gain access to the system via brute-force hacking methods.

To check the state of the system, run the following command(s):

```
/usr/bin/pwpolicy -getaccountpolicies 2> /dev/null | /usr/bin/tail +2 |
/usr/bin/xmllint --xpath '//dict/key[text()="autoEnableInSeconds"]/following-
 sibling::integer[1]/text()' - | /usr/bin/awk '{ if ($1/60 >= 15 ) {print "pass"} else
{print "fail"}}' | /usr/bin/uniq
```

If the result is not **pass**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.mobiledevice.passwordpolicy) payload type:

```
<key>minutesUntilFailedLoginReset</key>
<integer>15</integer>
```

ID	pwpolicy_account_lockout_timeout_enforce	
References	800-53r5 CCE	<ul style="list-style-type: none">• AC-7• CCE-95338-0

10.4. Require Passwords Contain a Minimum of One Numeric Character

The macOS *MUST* be configured to require at least one numeric character be used when a password is created.

This rule enforces password complexity by requiring users to set passwords that are less vulnerable to malicious users.

To comply with Executive Order 14028, “Improving the Nation’s Cybersecurity”, OMB M-22-09, “Moving the U.S. Government Toward Zero Trust Cybersecurity Principles”, and NIST SP-800-63b, “Digital Identity Guidelines: Authentication and Lifecycle Management” federal, military, and intelligence communities must adopt the following configuration settings. Password policies must not require the use of complexity policies such as upper characters, lower characters, or special characters. Password policies must also not require the use of regular rotation. Password policies should define a minimum length. Multifactor authentication should be used where ever possible.



To check the state of the system, run the following command(s):

```
/usr/bin/pwpolicy -getaccountpolicies 2> /dev/null | /usr/bin/tail +2 |  
/usr/bin/xmllint --xpath '//dict/key[text()="policyIdentifier"]/following-  
sibling::*[1]/text()' - | /usr/bin/grep "requireAlphanumeric" -c
```

If the result is not 1, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.mobiledevice.passwordpolicy) payload type:

```
<key>requireAlphanumeric</key>  
<true/>
```

ID	pwpolicy_alpha_numeric_enforce	
References	800-53r5 CCE	<ul style="list-style-type: none">IA-5(1)CCE-95339-8

10.5. Require Passwords to Match the Defined Custom Regular Expression

The macOS *MUST* be configured to meet complexity requirements defined in `^(?=.*[A-Z])(?=.*[a-z])(?=.*[0-9]).$`.

This rule enforces password complexity by requiring users to set passwords that are less vulnerable to malicious users.

To comply with Executive Order 14028, “Improving the Nation’s Cybersecurity”, OMB M-22-09, “Moving the U.S. Government Toward Zero Trust Cybersecurity Principles”, and NIST SP-800-63b, “Digital Identity Guidelines: Authentication and Lifecycle Management” federal, military, and intelligence communities must adopt the following configuration settings. Password policies must not require the use of complexity policies such as upper characters, lower characters, or special characters. Password policies must also not require the use of regular rotation. Password policies should define a minimum length. Multifactor authentication should be used where ever possible.



The configuration profile generated must be installed from an MDM server.

To check the state of the system, run the following command(s):

```
/usr/bin/pwpolicy -getaccountpolicies 2> /dev/null | /usr/bin/tail +2 |  
/usr/bin/xmllint --xpath 'boolean(//*[contains(text(),"policyAttributePassword matches  
'\\''^(?=.*[A-Z])(?=.*[a-z])(?=.*[0-9]).*$'\\'''))' -
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.mobiledevice.passwordpolicy) payload type:

```
<key>customRegex</key>  
<dict>  
    <key>passwordContentRegex</key>  
    <string>^(?=.*[A-Z])(?=.*[a-z])(?=.*[0-9]).*$</string>  
    <key>passwordContentDescription</key>  
    <dict>  
        <key>default</key>  
        <string>Password must match custom regex.</string>  
    </dict>  
</dict>
```

ID	pwpolicy_custom_regex_enforce	
References	800-53r5 CCE	<ul style="list-style-type: none"> • IA-5(1) • CCE-95340-6

10.6. Prohibit Password Reuse for a Minimum of 5 Generations

The macOS *MUST* be configured to enforce a password history of at least 5 previous passwords when a password is created.

This rule ensures that users are not allowed to re-use a password that was used in any of the 5 previous password generations.

Limiting password reuse protects against malicious users attempting to gain access to the system via brute-force hacking methods.

 The guidance for password based authentication in NIST 800-53 (Rev 5) and NIST 800-63B state that complexity rules should be organizationally defined. The values defined are based off of common complexity values. But your organization may define its own password complexity rules.

To check the state of the system, run the following command(s):

```
/usr/bin/pwpolicy -getaccountpolicies 2> /dev/null | /usr/bin/tail +2 |
/usr/bin/xmllint --xpath
'//dict/key[text()="policyAttributePasswordHistoryDepth"]/following-
sibling::*[1]/text()' - | /usr/bin/awk '{ if ($1 >= 5 ) {print "pass"} else {print
"fail"}}' | /usr/bin/uniq
```

If the result is not **pass**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.mobiledevice.passwordpolicy) payload type:

```
<key>pinHistory</key>
<integer>5</integer>
```

ID	pwpolicy_history_enforce
-----------	--------------------------

References	800-53r5	• IA-5(1)
	CCE	• CCE-95343-0

10.7. Require Passwords Contain a Minimum of One Lowercase Character

The macOS *MUST* be configured to require at least one lower-case character be used when a password is created.

This rule enforces password complexity by requiring users to set passwords that are less vulnerable to malicious users.



To comply with Executive Order 14028, “Improving the Nation’s Cybersecurity”, OMB M-22-09, “Moving the U.S. Government Toward Zero Trust Cybersecurity Principles”, and NIST SP-800-63b, “Digital Identity Guidelines: Authentication and Lifecycle Management” federal, military, and intelligence communities must adopt the following configuration settings. Password policies must not require the use of complexity policies such as upper characters, lower characters, or special characters. Password policies must also not require the use of regular rotation. Password policies should define a minimum length. Multifactor authentication should be used where ever possible.



macOS 14 supports password policy complexity with custom regex deployed with a mobileconfig file. To use a mobileconfig file use **pwpolicy_custom_regex_enforce**.

To check the state of the system, run the following command(s):

```
/usr/bin/pwpolicy -getaccountpolicies 2> /dev/null | /usr/bin/tail +2 |  
/usr/bin/xmllint --xpath  
'//dict/key[text()="minimumAlphaCharactersLowerCase"]/following-  
sibling::integer[1]/text()' - | /usr/bin/awk '{ if ($1 >= 1) {print "pass"} else  
{print "fail"}}'
```

If the result is not **pass**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

This setting may be enforced using local policy or by a directory service.

To set local policy to require at least 1 lowercase letter, edit the current password policy to contain the following <dict> within the "policyCategoryPasswordContent":

```
<dict>
<key>policyContent</key>
<string>policyAttributePassword matches &apos;(.*[a-z].*){1,}+&apos;</string>
<key>policyIdentifier</key>
<string>Must have at least 1 lowercase letter</string>
<key>policyParameters</key>
<dict>
<key>minimumAlphaCharactersLowerCase</key>
<integer>1</integer>
</dict>
</dict>
```

After saving the file and exiting to the command prompt, run the following command to load the new policy file, substituting the path to the file in place of "\$pwpolicy_file".

```
/usr/bin/pwpolicy setaccountpolicies $pwpolicy_file
```



See the password policy supplemental on more information on how to implement password policies on macOS.

ID	pwpolicy_lower_case_character_enforce	
References	800-53r5 CCE	<ul style="list-style-type: none">IA-5(1)CCE-95344-8

10.8. Restrict Maximum Password Lifetime to 60 Days

The macOS *MUST* be configured to enforce a maximum password lifetime limit of at least 60 days.

This rule ensures that users are forced to change their passwords frequently enough to prevent malicious users from gaining and maintaining access to the system.

To comply with Executive Order 14028, “Improving the Nation’s Cybersecurity”, OMB M-22-09, “Moving the U.S. Government Toward Zero Trust Cybersecurity Principles”, and NIST SP-800-63b, “Digital Identity Guidelines: Authentication and Lifecycle Management” federal, military, and intelligence communities must adopt the following configuration settings. Password policies must not require the use of complexity policies such as upper characters, lower characters, or special characters. Password policies must also not require the use of regular rotation. Password policies should define a minimum length. Multifactor authentication should be used where ever possible.

To check the state of the system, run the following command(s):

```
/usr/bin/pwpolicy -getaccountpolicies 2> /dev/null | /usr/bin/tail +2 |
/usr/bin/xmllint --xpath
'//dict:key[text()="policyAttributeExpiresEveryNDays"]/following-sibling::*[1]/text()'
- | /usr/bin/awk '{ if ($1 <= 60 ) {print "pass"} else {print "fail"}}' |
/usr/bin/uniq
```

If the result is not **pass**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.mobiledevice.passwordpolicy) payload type:

```
<key>maxPINAgeInDays</key>
<integer>60</integer>
```

ID	pwpolicy_max_lifetime_enforce	
References	800-53r5 CCE	<ul style="list-style-type: none">IA-5CCE-95345-5

10.9. Require a Minimum Password Length of 15 Characters

The macOS *MUST* be configured to require a minimum of 15 characters be used when a password is created.

This rule enforces password complexity by requiring users to set passwords that are less vulnerable to malicious users.

To comply with Executive Order 14028, “Improving the Nation’s Cybersecurity”, OMB M-22-09, “Moving the U.S. Government Toward Zero Trust Cybersecurity Principles”, and NIST SP-800-63b, “Digital Identity Guidelines: Authentication and Lifecycle Management” federal, military, and intelligence communities must adopt the following configuration settings. Password policies must not require the use of complexity policies such as upper characters, lower characters, or special characters. Password policies must also not require the use of regular rotation. Password policies should define a minimum length. Multifactor authentication should be used where ever possible.

To check the state of the system, run the following command(s):

```
/usr/bin/pwpolicy -getaccountpolicies 2>/dev/null | tail +2 | grep -oE  
"policyAttributePassword matches '\.\{[0-9]+\}' | awk -F'[{,]' -v ODV=15 '{if ($2 > max)  
max=$2} END {print (max >= ODV) ? "pass" : "fail"}'
```

If the result is not **pass**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.mobiledevice.passwordpolicy) payload type:

```
<key>minLength</key>  
<integer>15</integer>
```

ID	pwpolicy_minimum_length_enforce	
References	800-53r5 CCE	<ul style="list-style-type: none">IA-5(1)CCE-95346-3

10.10. Set Minimum Password Lifetime to 24 Hours

The macOS *MUST* be configured to enforce a minimum password lifetime limit of 24 hours.

This rule discourages users from cycling through their previous passwords to get back to a preferred one.

To comply with Executive Order 14028, “Improving the Nation’s Cybersecurity”, OMB M-22-09, “Moving the U.S. Government Toward Zero Trust Cybersecurity Principles”, and NIST SP-800-63b, “Digital Identity Guidelines: Authentication and Lifecycle Management” federal, military, and intelligence communities must adopt the following configuration settings. Password policies must not require the use of complexity policies such as upper characters, lower characters, or special characters. Password policies must also not require the use of regular rotation. Password policies should define a minimum length. Multifactor authentication should be used where ever possible.



To check the state of the system, run the following command(s):

```
/usr/bin/pwpolicy -getaccountpolicies 2> /dev/null | /usr/bin/tail +2 |  
/usr/bin/xmllint --xpath  
'//dict/key[text()="policyAttributeMinimumLifetimeHours"]/following-  
sibling::integer[1]/text()' - | /usr/bin/awk '{ if ($1 >= 24 ) {print "pass"} else
```

```
{print "fail"}'
```

If the result is not **pass**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

This setting may be enforced using local policy or by a directory service.

To set local policy to require a minimum password lifetime, edit the current password policy to contain the following <dict> within the "policyCategoryPasswordContent":

```
<dict>
<key>policyContent</key>
<string>policyAttributeLastPasswordChangeTime < policyAttributecurrentTime - (policyAttributeMinimumLifetimeHours * 60 * 60)</string>
<key>policyIdentifier</key>
<string>Minimum Password Lifetime</string>
<key>policyParameters</key>
<dict>
<key>policyAttributeMinimumLifetimeHours</key>
<integer>24</integer>
</dict>
</dict>
```

After saving the file and exiting to the command prompt, run the following command to load the new policy file, substituting the path to the file in place of "\$pwpolicy_file".

```
/usr/bin/pwpolicy setaccountpolicies $pwpolicy_file
```



See the password policy supplemental on more information on how to implement password policies on macOS.

ID	pwpolicy_minimum_lifetime_enforce	
References	800-53r5	<ul style="list-style-type: none">• IA-5
	CCE	<ul style="list-style-type: none">• CCE-95347-1

10.11. Prohibit Repeating, Ascending, and Descending Character Sequences

The macOS *MUST* be configured to prohibit the use of repeating, ascending, and descending character sequences when a password is created.

This rule enforces password complexity by requiring users to set passwords that are less vulnerable to malicious users.



To comply with Executive Order 14028, “Improving the Nation’s Cybersecurity”, OMB M-22-09, “Moving the U.S. Government Toward Zero Trust Cybersecurity Principles”, and NIST SP-800-63b, “Digital Identity Guidelines: Authentication and Lifecycle Management” federal, military, and intelligence communities must adopt the following configuration settings. Password policies must not require the use of complexity policies such as upper characters, lower characters, or special characters. Password policies must also not require the use of regular rotation. Password policies should define a minimum length. Multifactor authentication should be used where ever possible.



`pwpolicy_simple_sequence_disable` prevents use of passwords which are regularly found in compromised password lists.

To check the state of the system, run the following command(s):

```
/usr/bin/pwpolicy -getaccountpolicies 2> /dev/null | /usr/bin/tail +2 |  
/usr/bin/xmllint --xpath '//dict/key[text()="policyIdentifier"]/following-  
sibling::*[1]/text()' - | /usr/bin/grep "allowSimple" -c
```

If the result is not **1**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.mobiledevice.passwordpolicy) payload type:

```
<key>allowSimple</key>  
<false/>
```

ID	pwpolicy_simple_sequence_disable	
References	800-53r5	<ul style="list-style-type: none">IA-5(1)
	CCE	<ul style="list-style-type: none">CCE-95349-7

10.12. Require Passwords Contain a Minimum of One Special Character

The macOS *MUST* be configured to require at least one special character be used when a password is created.

Special characters are those characters that are not alphanumeric. Examples include: ~ ! @ # \$ % ^ *.

This rule enforces password complexity by requiring users to set passwords that are less vulnerable to malicious users.



To comply with Executive Order 14028, “Improving the Nation’s Cybersecurity”, OMB M-22-09, “Moving the U.S. Government Toward Zero Trust Cybersecurity Principles”, and NIST SP-800-63b, “Digital Identity Guidelines: Authentication and Lifecycle Management” federal, military, and intelligence communities must adopt the following configuration settings. Password policies must not require the use of complexity policies such as upper characters, lower characters, or special characters. Password policies must also not require the use of regular rotation. Password policies should define a minimum length. Multifactor authentication should be used where ever possible.

To check the state of the system, run the following command(s):

```
/usr/bin/pwpolicy -getaccountpolicies 2>/dev/null | /usr/bin/tail -n +2 |  
/usr/bin/xmllint --xpath "//string[contains(text(), \"policyAttributePassword matches  
'(.*[^a-zA-Z0-9].*){\\\"})]\" - 2>/dev/null | /usr/bin/awk -F"\{|}" '{if ($2 >= 1) {print  
"pass"} else {print "fail"}}'
```

If the result is not **pass**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.mobiledevice.passwordpolicy) payload type:

```
<key>minComplexChars</key>  
<integer>1</integer>
```

ID	pwpolicy_special_character_enforce	
References	800-53r5 CCE	<ul style="list-style-type: none">IA-5(1)CCE-95350-5

10.13. Automatically Remove or Disable Temporary or Emergency User Accounts within 72 Hours

The macOS is able to be configured to set an automated termination for 72 hours or less for all

temporary or emergency accounts upon account creation.

Emergency administrator accounts are privileged accounts established in response to crisis situations where the need for rapid account activation is required. Therefore, emergency account activation may bypass normal account authorization processes. If these accounts are disabled, system maintenance during emergencies may not be possible, thus adversely affecting system availability.

Although the ability to create and use emergency administrator accounts is necessary for performing system maintenance during emergencies, these accounts present vulnerabilities to the system if they are not disabled and removed when they are no longer needed. Configuring the macOS to automatically remove or disable emergency accounts within 72 hours of creation mitigates the risks posed if one were to be created and accidentally left active once the crisis is resolved.

Emergency administrator accounts are different from infrequently used accounts (i.e., local logon accounts used by system administrators when network or normal logon is not available). Infrequently used accounts also remain available and are not subject to automatic termination dates. However, an emergency administrator account is normally a different account created for use by vendors or system maintainers.

To address access requirements, many operating systems can be integrated with enterprise-level authentication/access mechanisms that meet or exceed access control policy requirements.

If temporary or emergency user accounts remain active when no longer needed or for an excessive period, these accounts may be targeted by attackers to gain unauthorized access. To mitigate this risk, automated termination of all temporary or emergency accounts *MUST* be set to 72 hours (or less) when the temporary or emergency account is created.

If no policy is enforced by a directory service, a password policy can be set with the "pwpolicy" utility. The variable names may vary depending on how the policy was set.

If there are no temporary or emergency accounts defined on the system, this is Not Applicable.



This rule is marked as manual and may not be able to be automated. It is also excluded in the compliance scan and will not report any results.

To check the state of the system, run the following command(s):

Verify **if** a password policy is enforced by a directory service by asking the System Administrator (SA) or Information System Security Officer (ISSO).

If no policy is enforced by a directory service, a password policy can be **set** with the "**pwpolicy**" utility. The variable names may vary depending on how the policy was set.

If there are no temporary or emergency accounts defined on the system, this is Not Applicable.

To check **if** the password policy is configured to disable a temporary or emergency account after 72 hours, run the following **command** to output the password policy to the

screen, substituting the correct user name **in** place of username:

```
/usr/bin/pwpolicy -u username getaccountpolicies | tail -n +2
```

If there is no output, and password policy is not controlled by a directory service, this is a finding.

Otherwise, look **for** the line "**<key>policyCategoryAuthentication</key>**".

In the array that follows, there should be a **<dict>** section that contains a check **<string>** that allows **users** to log **in if "policyAttributeCurrentTime"** is less than the result of adding **"policyAttributeCreationTime"** to 72 hours (259299 seconds). The check might use a variable defined **in** its **"policyParameters"** section.

If the check does not exist or **if** the check adds too great an amount of **time** to **"policyAttributeCreationTime"**, this is a finding.

If the result is not **N/A**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

This setting may be enforced using local policy or by a directory service.

To set local policy to disable a temporary or emergency user, create a plain text file containing the following:

```
<dict> <key>policyCategoryAuthentication</key> <array> <dict> <key>policyContent</key>
<string>policyAttributeCurrentTime < > policyAttributeCreationTime+259299</string>
<key>policyIdentifier</key> <string>Disable Tmp Accounts </string> </dict> </array> </dict>
```

After saving the file and exiting to the command prompt, run the following command to load the new policy file, substituting the correct user name in place of "username" and the path to the file in place of "/path/to/file".

```
/usr/bin/pwpolicy -u username setaccountpolicies /path/to/file
```

ID	pwpolicy_temporary_or_emergency_accounts_disable	
References	800-53r5 CCE	<ul style="list-style-type: none">AC-2(2)CCE-95352-1

10.14. Require Passwords Contain a Minimum of One Uppercase Character

The macOS **MUST** be configured to require at least one uppercase character be used when a

password is created.

This rule enforces password complexity by requiring users to set passwords that are less vulnerable to malicious users.

To comply with Executive Order 14028, “Improving the Nation’s Cybersecurity”, OMB M-22-09, “Moving the U.S. Government Toward Zero Trust Cybersecurity Principles”, and NIST SP-800-63b, “Digital Identity Guidelines: Authentication and Lifecycle Management” federal, military, and intelligence communities must adopt the following configuration settings. Password policies must not require the use of complexity policies such as upper characters, lower characters, or special characters. Password policies must also not require the use of regular rotation. Password policies should define a minimum length. Multifactor authentication should be used where ever possible.

macOS 14 supports password policy complexity with custom regex deployed with a mobileconfig file. To use a mobileconfig file use **pwpolicy_custom_regex_enforce**.

To check the state of the system, run the following command(s):

```
/usr/bin/pwpolicy -getaccountpolicies 2> /dev/null | /usr/bin/tail +2 |  
/usr/bin/xmllint --xpath  
'//dict/key[text()="minimumAlphaCharactersUpperCase"]/following-  
sibling::integer[1]/text()' - | /usr/bin/awk '{ if ($1 >= 1) {print "pass"} else  
{print "fail"}}'
```

If the result is not **pass**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

This setting may be enforced using local policy or by a directory service.

To set local policy to require at least 1 lowercase letter, edit the current password policy to contain the following <dict> within the "policyCategoryPasswordContent":

```
<dict>  
<key>policyContent</key>  
<string>policyAttributePassword matches &apos;(.*[A-Z].*){1,}&apos;</string>  
<key>policyIdentifier</key>  
<string>Must have at least 1 uppercase letter</string>  
<key>policyParameters</key>  
<dict>  
<key>minimumAlphaCharactersUpperCase</key>  
<integer>1</integer>
```

```
</dict>  
</dict>
```

After saving the file and exiting to the command prompt, run the following command to load the new policy file, substituting the path to the file in place of "\$pwpolicy_file".

```
/usr/bin/pwpolicy setaccountpolicies $pwpolicy_file
```



See the password policy supplemental on more information on how to implement password policies on macOS.

ID	pwpolicy_upper_case_character_enforce	
References	800-53r5	<ul style="list-style-type: none">• IA-5(1)
	CCE	<ul style="list-style-type: none">• CCE-95353-9

Chapter 11. System Settings

This section contains the configuration and enforcement of the settings within the macOS System Settings application.



The check/fix commands outlined in this section *MUST* be run by a user with elevated privileges.

11.1. Disable Airplay Receiver

Airplay Receiver allows you to send content from another Apple device to be displayed on the screen as it's being played from your other device.

Support for Airplay Receiver is non-essential and *MUST* be disabled.

The information system *MUST* be configured to provide only essential capabilities.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowAirPlayIncomingRequests').js
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowAirPlayIncomingRequests</key>
<false/>
```

ID	system_settings_airplay_receiver_disable	
References	800-53r5	<ul style="list-style-type: none">CM-7, CM-7(1)
	CCE	<ul style="list-style-type: none">CCE-95354-7

11.2. Prevent Apple Watch from Terminating a Session Lock

Apple Watches are not an approved authenticator and their use *MUST* be disabled.

Disabling Apple watches is a necessary step to ensuring that the information system retains a session lock until the user reestablishes access using an authorized identification and authentication procedures.



Unlocking the system with an Apple Watch is not an approved authenticator for US Federal Government usage as it has not been verified to meet the strength requirements outlined in NIST SP 800-63.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowAutoUnlock').js
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowAutoUnlock</key>
<false/>
```

ID	system_settings_apple_watch_unlock_disable	
References	800-53r5 CCE	<ul style="list-style-type: none">IA-5CCE-95355-4

11.3. Disable Unattended or Automatic Logon to the System

Automatic logon *MUST* be disabled.

When automatic logons are enabled, the default user account is automatically logged on at boot time without prompting the user for a password. Even if the screen is later locked, a malicious user

would be able to reboot the computer and find it already logged in. Disabling automatic logons mitigates this risk.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.loginwindow')\
.objectForKey('com.apple.login.mcx.DisableAutoLoginClient').js
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.loginwindow) payload type:

```
<key>com.apple.login.mcx.DisableAutoLoginClient</key>
<true/>
```

ID	system_settings_automatic_login_disable	
References	800-53r5	<ul style="list-style-type: none">• IA-2• IA-5(13)
	CCE	<ul style="list-style-type: none">• CCE-95356-2

11.4. Enforce Auto Logout After 86400 Seconds of Inactivity

Auto logout *MUST* be configured to automatically terminate a user session and log out after 86400 seconds of inactivity.

NOTE: The maximum that macOS can be configured for autologoff is 86400 seconds.

 The automatic logout may cause disruptions to an organization's workflow and/or loss of data. Information System Security Officers (ISSOs) are advised to first fully weigh the potential risks posed to their organization before opting to disable the automatic logout setting.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
```

```
$.NSUserDefaults.alloc.initWithSuiteName('.GlobalPreferences')\n.objectForKey('com.apple.autologout.AutoLogOutDelay').js\nEOS
```

If the result is not **86400**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (.GlobalPreferences) payload type:

```
<key>com.apple.autologout.AutoLogOutDelay</key>\n<integer>86400</integer>
```

ID	system_settings_automatic_logout_enforce		
References	800-53r5	<ul style="list-style-type: none">AC-12AC-2(5)	
	CCE	<ul style="list-style-type: none">CCE-95357-0	

11.5. Disable Bluetooth When no Approved Device is Connected

The macOS system *MUST* be configured to disable Bluetooth unless there is an approved device connected.



Information System Security Officers (ISSOs) may make the risk-based decision not to disable Bluetooth, so as to maintain necessary functionality, but they are advised to first fully weigh the potential risks posed to their organization.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS\n$.NSUserDefaults.alloc.initWithSuiteName('com.apple.MCXBluetooth')\n.objectForKey('DisableBluetooth').js\nEOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:



The following settings are in the (com.apple.ManagedClient.preferences) payload. This payload requires the additional settings to be sub-payloads within, containing their defined payload types.

Create a configuration profile containing the following keys in the (com.apple.MCXBluetooth) payload type:

```
<key>DisableBluetooth</key>
<true/>
```

ID	system_settings_bluetooth_disable	
References	800-53r5	<ul style="list-style-type: none">• AC-18, AC-18(3)• SC-8
	CCE	<ul style="list-style-type: none">• CCE-95358-8

11.6. Disable the Bluetooth System Settings Pane

The Bluetooth System Setting pane *MUST* be disabled to prevent access to the bluetooth configuration.

To check the state of the system, run the following command(s):

```
/usr/bin/profiles show -output stdout-xml | /usr/bin/xmllint --xpath
'//key[text()="DisabledSystemSettings"]/following-sibling::*[1]' - | /usr/bin/grep -c
com.apple.BluetoothSettings
```

If the result is not 1, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.systempreferences) payload type:

```
<key>DisabledSystemSettings</key>
<array>
  <string>com.apple.BluetoothSettings</string>
</array>
```

ID	system_settings_bluetooth_settings_disable	
References	800-53r5 <ul style="list-style-type: none"> • CM-7, CM-7(1) CCE <ul style="list-style-type: none"> • CCE-95360-4 	

11.7. Disable Bluetooth Sharing

Bluetooth Sharing *MUST* be disabled.

Bluetooth Sharing allows users to wirelessly transmit files between the macOS and Bluetooth-enabled devices, including personally owned cellphones and tablets. A malicious user might introduce viruses or malware onto the system or extract sensitive files via Bluetooth Sharing. When Bluetooth Sharing is disabled, this risk is mitigated.

The check and fix are for the last logged in user. To get the last logged in user, run the following.



```
CURRENT_USER=$( /usr/bin/defaults read
/Library/Preferences/com.apple.loginwindow lastUserName )
```

To check the state of the system, run the following command(s):

```
/usr/bin/sudo -u "$CURRENT_USER" /usr/bin/defaults -currentHost read
com.apple.Bluetooth PrefKeyServicesEnabled
```

If the result is not **0**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/usr/bin/sudo -u "$CURRENT_USER" /usr/bin/defaults -currentHost write
com.apple.Bluetooth PrefKeyServicesEnabled -bool false
```

ID	system_settings_bluetooth_sharing_disable	
References	800-53r5 <ul style="list-style-type: none"> • AC-18(4) • AC-3 • CM-7, CM-7(1) CCE <ul style="list-style-type: none"> • CCE-95361-2 	

11.8. Disable Content Caching Service

Content caching *MUST* be disabled.

Content caching is a macOS service that helps reduce Internet data usage and speed up software installation on Mac computers. It is not recommended for devices furnished to employees to act as a caching server.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowContentCaching').js
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowContentCaching</key>
<false/>
```

ID	system_settings_content_caching_disable	
References	800-53r5 CCE	<ul style="list-style-type: none">CM-7, CM-7(1)CCE-95362-0

11.9. Enforce Critical Security Updates to be Installed

Ensure that security updates are installed as soon as they are available from Apple.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.SoftwareUpdate')\
.objectForKey('CriticalUpdateInstall').js
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.SoftwareUpdate) payload type:

```
<key>CriticalUpdateInstall</key>
<true/>
```

ID	system_settings_critical_update_install_enforce	
References	800-53r5	<ul style="list-style-type: none">SI-2
	CCE	<ul style="list-style-type: none">CCE-95363-8

11.10. Disable Sending Diagnostic and Usage Data to Apple

The ability to submit diagnostic data to Apple *MUST* be disabled.

The information system *MUST* be configured to provide only essential capabilities. Disabling the submission of diagnostic and usage information will mitigate the risk of unwanted data being sent to Apple.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
function run() {
let pref1 = $.NSUserDefaults.alloc.initWithSuiteName('com.apple.SubmitDiagInfo')\
.objectForKey('AutoSubmit').js
let pref2 = $.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowDiagnosticSubmission').js
if ( pref1 == false && pref2 == false ){
    return("true")
} else {
    return("false")
}
}
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.SubmitDiagInfo) payload type:

```
<key>AutoSubmit</key>
<false/>
```

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowDiagnosticSubmission</key>
<false/>
```

ID	system_settings_diagnostics_reports_disable		
References	800-53r5	<ul style="list-style-type: none">AC-20SC-7(10)SI-11	CCE
		<ul style="list-style-type: none">CCE-95364-6	

11.11. Disable External Intelligence Integrations

Integration with external intelligence systems *MUST* be disabled unless approved by the organization. Disabling external intelligence integration will mitigate the risk of data being sent to unapproved third party.

The information system *MUST* be configured to provide only essential capabilities.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowExternalIntelligenceIntegrations').js
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowExternalIntelligenceIntegrations</key>
<false/>
```

ID	system_settings_external_intelligence_disable	
References	800-53r5	<ul style="list-style-type: none">• AC-20• CM-7, CM-7(1)
	CCE	<ul style="list-style-type: none">• CCE-95365-3

11.12. Disable External Intelligence Integration Sign In

The ability to sign into an external intelligence systems *MUST* be disabled unless approved by the organization. Disabling external intelligence integration will mitigate the risk of data being sent to unapproved third party.

The information system *MUST* be configured to provide only essential capabilities.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowExternalIntelligenceIntegrationsSignIn').js
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowExternalIntelligenceIntegrationsSignIn</key>
<false/>
```

ID	system_settings_external_intelligence_sign_in_disable	
References	800-53r5	<ul style="list-style-type: none">• AC-20• CM-7, CM-7(1)
	CCE	<ul style="list-style-type: none">• CCE-95366-1

11.13. Enforce FileVault

FileVault *MUST* be enforced.

The information system implements cryptographic mechanisms to protect the confidentiality and integrity of information stored on digital media during transport outside of controlled areas.



See the FileVault supplemental to implement this rule.

To check the state of the system, run the following command(s):

```
dontAllowDisable=$(/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.MCX')\
.objectForKey('dontAllowFDEDisable').js
EOS
)
fileVault=$(/usr/bin/fdesetup status | /usr/bin/grep -c "FileVault is On.")
if [[ "$dontAllowDisable" == "true" ]]; then
    echo "1"
else
    echo "0"
fi
```

If the result is not 1, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.MCX) payload type:

```
<key>dontAllowFDEDisable</key>
<true/>
```

ID	system_settings_filevault_enforce	
References	800-53r5	<ul style="list-style-type: none">SC-28, SC-28(1)
	CCE	<ul style="list-style-type: none">CCE-95367-9

11.14. Disable Find My Service

The Find My service *MUST* be disabled.

A Mobile Device Management (MDM) solution *MUST* be used to carry out remote locking and

wiping instead of Apple's Find My service.

Apple's Find My service uses a personal AppleID for authentication. Organizations should rely on MDM solutions, which have much more secure authentication requirements, to perform remote lock and remote wipe.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
function run() {
    let pref1 = ObjC.unwrap(
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowFindMyDevice'))
    let pref2 = ObjC.unwrap(
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowFindMyFriends'))
    let pref3 = ObjC.unwrap(
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.icloud.managed')\
.objectForKey('DisableFMMiCloudSetting'))
    if ( pref1 == false && pref2 == false && pref3 == true ) {
        return("true")
    } else {
        return("false")
    }
}
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowFindMyDevice</key>
<false/>
<key>allowFindMyFriends</key>
<false/>
```

Create a configuration profile containing the following keys in the (com.apple.icloud.managed) payload type:

```
<key>DisableFMMiCloudSetting</key>
<true/>
```

ID	system_settings_find_my_disable	
References	800-53r5	<ul style="list-style-type: none"> • AC-20 • CM-7, CM-7(1)
	CCE	<ul style="list-style-type: none"> • CCE-95368-7

11.15. Enable macOS Application Firewall

The macOS Application Firewall is the built-in firewall that comes with macOS, and it *MUST* be enabled.

When the macOS Application Firewall is enabled, the flow of information within the information system and between interconnected systems will be controlled by approved authorizations.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.security.firewall')\
.objectForKey('EnableFirewall').js
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.security.firewall) payload type:

```
<key>EnableFirewall</key>
<true/>
```

ID	system_settings_firewall_enable	
References	800-53r5	<ul style="list-style-type: none"> • AC-4 • CM-7, CM-7(1) • SC-7, SC-7(12)
	CCE	<ul style="list-style-type: none"> • CCE-95369-5

11.16. Enable Firewall Stealth Mode

Firewall Stealth Mode *MUST* be enabled.

When stealth mode is enabled, the Mac will not respond to any probing requests, and only requests from authorized applications will still be authorized.



Enabling firewall stealth mode may prevent certain remote mechanisms used for maintenance and compliance scanning from properly functioning. Information System Security Officers (ISSOs) are advised to first fully weigh the potential risks posed to their organization before opting not to enable stealth mode.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.security.firewall')\
.objectForKey('EnableStealthMode').js
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.security.firewall) payload type:

```
<key>EnableStealthMode</key>
<true/>
<key>EnableFirewall</key>
<true/>
```

ID	system_settings_firewall_stealth_mode_enable	
References	800-53r5	<ul style="list-style-type: none">• CM-7, CM-7(1)• SC-7, SC-7(16)
	CCE	<ul style="list-style-type: none">• CCE-95370-3

11.17. Apply Gatekeeper Settings to Block Applications from Unidentified Developers

The information system implements cryptographic mechanisms to authenticate software prior to installation.

Gatekeeper settings must be configured correctly to only allow the system to run applications downloaded from the Mac App Store or applications signed with a valid Apple Developer ID code. Administrator users will still have the option to override these settings on a per-app basis.

Gatekeeper is a security feature that ensures that applications must be digitally signed by an Apple-issued certificate in order to run. Digital signatures allow the macOS to verify that the application has not been modified by a malicious third party.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
function run() {
    let pref1 = ObjC.unwrap(
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.systempolicy.control')\
.objectForKey('AllowIdentifiedDevelopers'))
    let pref2 = ObjC.unwrap(
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.systempolicy.control')\
.objectForKey('EnableAssessment'))
    if ( pref1 == true && pref2 == true ) {
        return("true")
    } else {
        return("false")
    }
}
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.systempolicy.control) payload type:

```
<key>AllowIdentifiedDevelopers</key>
<true/>
<key>EnableAssessment</key>
<true/>
```

ID	system_settings_gatekeeper_identified_developers_allowed	
References	800-53r5	<ul style="list-style-type: none">• CM-14• CM-5• SI-7(1), SI-7(15)
	CCE	<ul style="list-style-type: none">• CCE-95371-1

11.18. Configure Gatekeeper to Disallow End User Override

Gatekeeper *MUST* be configured with a configuration profile to prevent normal users from overriding its settings.

If users are allowed to disable Gatekeeper or set it to a less restrictive setting, malware could be introduced into the system.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.systempolicy.managed')\
.objectForKey('DisableOverride').js
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.systempolicy.managed) payload type:

```
<key>DisableOverride</key>
<true/>
```

ID	system_settings_gatekeeper_override_disallow		
References	800-53r5	<ul style="list-style-type: none">CM-5SI-7(15)	CCE

11.19. Disable Guest Access to Shared SMB Folders

Guest access to shared Server Message Block (SMB) folders *MUST* be disabled.

Turning off guest access prevents anonymous users from accessing files shared via SMB.

To check the state of the system, run the following command(s):

```
/usr/bin/defaults read /Library/Preferences/SystemConfiguration/com.apple.smb.server
```

AllowGuestAccess

If the result is not **0**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/usr/sbin/sysadminctl -smbGuestAccess off
```

ID	system_settings_guest_access_smb_disable	
References	800-53r5	<ul style="list-style-type: none">• AC-2, AC-2(9)
	CCE	<ul style="list-style-type: none">• CCE-95373-7

11.20. Disable the Guest Account

Guest access *MUST* be disabled.

Turning off guest access prevents anonymous users from accessing files.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
function run() {
    let pref1 = ObjC.unwrap($.NSUserDefaults.alloc.initWithSuiteName('com.apple.MCX')\
.objectForKey('DisableGuestAccount'))
    let pref2 = ObjC.unwrap($.NSUserDefaults.alloc.initWithSuiteName('com.apple.MCX')\
.objectForKey('EnableGuestAccount'))
    if ( pref1 == true && pref2 == false ) {
        return("true")
    } else {
        return("false")
    }
}
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.MCX) payload type:

```
<key>DisableGuestAccount</key>
<true/>
<key>EnableGuestAccount</key>
<false/>
```

ID	system_settings_guest_account_disable	
References	800-53r5	• AC-2, AC-2(9)
	CCE	• CCE-95374-5

11.21. Disable Hot Corners

Hot corners *MUST* be disabled.

The information system conceals, via the session lock, information previously visible on the display with a publicly viewable image. Although hot comers can be used to initiate a session lock or to launch useful applications, they can also be configured to disable an automatic session lock from initiating. Such a configuration introduces the risk that a user might forget to manually lock the screen before stepping away from the computer.

To check the state of the system, run the following command(s):

```
/usr/bin/profiles -P -o stdout | /usr/bin/grep -Ec '"wvous-bl-corner" = 0|"wvous-br-corner" = 0|"wvous-tl-corner" = 0|"wvous-tr-corner" = 0'
```

If the result is not 4, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:



The following settings are in the (com.apple.ManagedClient.preferences) payload. This payload requires the additional settings to be sub-payloads within, containing their defined payload types.

Create a configuration profile containing the following keys in the (com.apple.dock) payload type:

```
<key>wvous-bl-corner</key>
<integer>0</integer>
<key>wvous-br-corner</key>
<integer>0</integer>
<key>wvous-tr-corner</key>
<integer>0</integer>
<key>wvous-tl-corner</key>
```

<integer>0</integer>

ID	system_settings_hot_corners_disable	
References	800-53r5	• AC-11(1)
	CCE	• CCE-95375-2

11.22. Secure Hot Corners

Hot corners *MUST* be secured.

The information system conceals, via the session lock, information previously visible on the display with a publicly viewable image. Although hot comers can be used to initiate a session lock or to launch useful applications, they can also be configured to disable an automatic session lock from initiating. Such a configuration introduces the risk that a user might forget to manually lock the screen before stepping away from the computer.

The check and fix are for the last logged in user. To get the last logged in user, run the following.



```
CURRENT_USER=$( /usr/bin/defaults read  
/Library/Preferences/com.apple.loginwindow lastUserName )
```

To check the state of the system, run the following command(s):

```
bl_corner=$( /usr/bin/defaults read /Users/"$CURRENT_USER  
"/Library/Preferences/com.apple.dock wvous-bl-corner 2>/dev/null )  
tl_corner=$( /usr/bin/defaults read /Users/"$CURRENT_USER  
"/Library/Preferences/com.apple.dock wvous-tl-corner 2>/dev/null )  
tr_corner=$( /usr/bin/defaults read /Users/"$CURRENT_USER  
"/Library/Preferences/com.apple.dock wvous-tr-corner 2>/dev/null )  
br_corner=$( /usr/bin/defaults read /Users/"$CURRENT_USER  
"/Library/Preferences/com.apple.dock wvous-br-corner 2>/dev/null )  
  
if [[ "$bl_corner" != "6" ]] && [[ "$tl_corner" != "6" ]] && [[ "$tr_corner" != "6" ]]  
&& [[ "$br_corner" != "6" ]]; then  
    echo "0"  
fi
```

If the result is not 0, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/usr/bin/sudo -u "$CURRENT_USER" /usr/bin/defaults delete /Users/"$CURRENT_USER"  
"/Library/Preferences/com.apple.dock wvous-bl-corner 2>/dev/null  
/usr/bin/sudo -u "$CURRENT_USER" /usr/bin/defaults delete /Users/"$CURRENT_USER"  
"/Library/Preferences/com.apple.dock wvous-tl-corner 2>/dev/null  
/usr/bin/sudo -u "$CURRENT_USER" /usr/bin/defaults delete /Users/"$CURRENT_USER"  
"/Library/Preferences/com.apple.dock wvous-tr-corner 2>/dev/null  
/usr/bin/sudo -u "$CURRENT_USER" /usr/bin/defaults delete /Users/"$CURRENT_USER"  
"/Library/Preferences/com.apple.dock wvous-br-corner 2>/dev/null
```

ID	system_settings_hot_corners_secure	
References	800-53r5 CCE	<ul style="list-style-type: none">• AC-11(1)• CCE-95376-0

11.23. Disable Sending Audio Recordings and Transcripts to Apple

The ability for Apple to store and review audio of your audio recordings and transcripts of your vocal shortcuts and voice control interactions *MUST* be disabled. This will disable "Improve Assistive Voice Features" in Privacy & Security within System Settings.

The information system *MUST* be configured to provide only essential capabilities. Disabling the submission of this information will mitigate the risk of unwanted data being sent to Apple.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS  
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.Accessibility')\\  
.objectForKey('AXSAudioDonationSiriImprovementEnabled').js  
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.Accessibility) payload type:

```
<key>AXSAudioDonationSiriImprovementEnabled</key>  
<false/>
```

ID	system_settings_improve_assistive_voice_disable	
References	800-53r5	<ul style="list-style-type: none"> • AC-20 • CM-7, CM-7(1) • SC-7(10)
	CCE	<ul style="list-style-type: none"> • CCE-95377-8

11.24. Disable Improve Search Information to Apple

Sending data to Apple to help improve search *MUST* be disabled. This will disable "Improve Search" within Spotlight in System Settings.

The information system *MUST* be configured to provide only essential capabilities. Disabling the submission of search data will mitigate the risk of unwanted data being sent to Apple.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.assistant.support')\
.objectForKey('Search Queries Data Sharing Status').js
EOS
```

If the result is not 2, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.assistant.support) payload type:

```
<key>Search Queries Data Sharing Status</key>
<integer>2</integer>
```

ID	system_settings_improve_search_disable	
References	800-53r5	<ul style="list-style-type: none"> • AC-20 • CM-7, CM-7(1) • SC-7(10)
	CCE	<ul style="list-style-type: none"> • CCE-95378-6

11.25. Disable Improve Siri and Dictation Information to Apple

The ability for Apple to store and review audio of your Siri and Dictation interactions *MUST* be disabled.

The information system *MUST* be configured to provide only essential capabilities. Disabling the submission of Siri and Dictation information will mitigate the risk of unwanted data being sent to Apple.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.assistant.support')\
.objectForKey('Siri Data Sharing Opt-In Status').js
EOS
```

If the result is not 2, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.assistant.support) payload type:

```
<key>Siri Data Sharing Opt-In Status</key>
<integer>2</integer>
```

ID	system_settings_improve_siri_dictation_disable		
References	800-53r5	<ul style="list-style-type: none">AC-20CM-7, CM-7(1)SC-7(10)	
	CCE	<ul style="list-style-type: none">CCE-95379-4	

11.26. Disable the Internet Accounts System Preference Pane

The Internet Accounts System Setting *MUST* be disabled to prevent the addition of unauthorized internet accounts.



Some organizations may allow the use and configuration of the built-in Mail.app,

Calendar.app, and Contacts.app for organizational communication. Information System Security Officers (ISSOs) may make the risk-based decision not to disable the Internet Accounts System Preference pane to avoid losing this functionality, but they are advised to first fully weigh the potential risks posed to their organization.

To check the state of the system, run the following command(s):

```
/usr/bin/profiles show -output stdout-xml | /usr/bin/xmllint --xpath  
'//key[text()="DisabledSystemSettings"]/following-sibling::*[1]' - | /usr/bin/grep -c  
com.apple.Internet-Accounts-Settings.extension
```

If the result is not 1, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.systempreferences) payload type:

```
<key>DisabledSystemSettings</key>  
<array>  
    <string>com.apple.Internet-Accounts-Settings.extension</string>  
</array>
```

ID	system_settings_internet_accounts_disable		
References	800-53r5	• AC-20	• CM-7, CM-7(1), CM-7(5)
	CCE	• CCE-95381-0	

11.27. Disable Internet Sharing

If the system does not require Internet sharing, support for it is non-essential and *MUST* be disabled.

The information system *MUST* be configured to provide only essential capabilities. Disabling Internet sharing helps prevent the unauthorized connection of devices, unauthorized transfer of information, and unauthorized tunneling.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
```

```
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.MCX')\n.objectForKey('forceInternetSharingOff').js\nEOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.MCX) payload type:

```
<key>forceInternetSharingOff</key>\n<true/>
```

ID	system_settings_internet_sharing_disable		
References	800-53r5	• AC-20 • AC-4	
	CCE	• CCE-95382-8	

11.28. Disable Location Services

Location Services *MUST* be disabled.

The information system *MUST* be configured to provide only essential capabilities. Disabling Location Services helps prevent the unauthorized connection of devices, unauthorized transfer of information, and unauthorized tunneling.

To check the state of the system, run the following command(s):

```
/usr/bin/sudo -u _locationd /usr/bin/osascript -l JavaScript << EOS\n$.NSUserDefaults.alloc.initWithSuiteName('com.apple.locationd')\\n.objectForKey('LocationServicesEnabled').js\nEOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/usr/bin/defaults write
```

```
/var/db/locationd/Library/Preferences/ByHost/com.apple.locationd
LocationServicesEnabled -bool false;
pid=$(/bin/launchctl print system | /usr/bin/awk '/\tcom.apple.locationd/ {print
$1}')
kill -9 $pid
```

ID	system_settings_location_services_disable	
References	800-53r5	<ul style="list-style-type: none"> • CM-7, CM-7(1) • SC-7(10)
	CCE	<ul style="list-style-type: none"> • CCE-95383-6

11.29. Configure Login Window to Prompt for Username and Password

The login window *MUST* be configured to prompt all users for both a username and a password.

By default, the system displays a list of known users on the login window, which can make it easier for a malicious user to gain access to someone else's account. Requiring users to type in both their username and password mitigates the risk of unauthorized users gaining access to the information system.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.loginwindow')\
.objectForKey('SHOWFULLNAME').js
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.loginwindow) payload type:

```
<key>SHOWFULLNAME</key>
<true/>
```

ID	system_settings_loginwindow_prompt_username_password_enforce
-----------	--

References	800-53r5	• IA-2
	CCE	• CCE-95387-7

11.30. Disable Media Sharing

Media sharing *MUST* be disabled.

When Media Sharing is enabled, the computer starts a network listening service that shares the contents of the user's music collection with other users in the same subnet.

The information system *MUST* be configured to provide only essential capabilities. Disabling Media Sharing helps prevent the unauthorized connection of devices and the unauthorized transfer of information. Disabling Media Sharing mitigates this risk.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
function run() {
    let pref1 = ObjC.unwrap(
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowMediaSharing'))
    let pref2 = ObjC.unwrap(
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowMediaSharingModification'))
    if ( pref1 == false && pref2 == false ) {
        return("true")
    } else {
        return("false")
    }
}
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowMediaSharing</key>
<false/>
<key>allowMediaSharingModification</key>
<false/>
```

ID	system_settings_media_sharing_disabled	
References	800-53r5 CCE	<ul style="list-style-type: none"> • AC-17 • AC-3 • CCE-95388-5

11.31. Disable Password Hints

Password hints *MUST* be disabled.

Password hints leak information about passwords that are currently in use and can lead to loss of confidentiality.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.loginwindow')\
.objectForKey('RetriesUntilHint').js
EOS
```

If the result is not **0**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.loginwindow) payload type:

```
<key>RetriesUntilHint</key>
<integer>0</integer>
```

ID	system_settings_password_hints_disable	
References	800-53r5 CCE	<ul style="list-style-type: none"> • IA-6 • CCE-95389-3

11.32. Disable Personalized Advertising

Ad tracking and targeted ads *MUST* be disabled.

The information system *MUST* be configured to provide only essential capabilities. Disabling ad tracking ensures that applications and advertisers are unable to track users' interests and deliver targeted advertisements.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowApplePersonalizedAdvertising').js
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowApplePersonalizedAdvertising</key>
<false/>
```

ID	system_settings_personalized_advertising_disable		
References	800-53r5	<ul style="list-style-type: none">• AC-20• CM-7, CM-7(1)• SC-7(10)	
	CCE	<ul style="list-style-type: none">• CCE-95390-1	

11.33. Disable Printer Sharing

Printer Sharing *MUST* be disabled.

To check the state of the system, run the following command(s):

```
/usr/sbin/cupsctl | /usr/bin/grep -c "_share_printers=0"
```

If the result is not **1**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/usr/sbin/cupsctl --no-share-printers
/usr/bin/lpstat -p | awk '{print $2}' | /usr/bin/xargs -I{} lpadmin -p {} -o
```

printer-is-shared=false

ID	system_settings_printer_sharing_disable	
References	800-53r5	<ul style="list-style-type: none">• CM-7, CM-7(1)
	CCE	<ul style="list-style-type: none">• CCE-95391-9

11.34. Disable Remote Apple Events

If the system does not require Remote Apple Events, support for Apple Remote Events is non-essential and *MUST* be disabled.

The information system *MUST* be configured to provide only essential capabilities. Disabling Remote Apple Events helps prevent the unauthorized connection of devices, the unauthorized transfer of information, and unauthorized tunneling.

To check the state of the system, run the following command(s):

```
/bin/launchctl print-disabled system | /usr/bin/grep -c '"com.apple.AEserver" => disabled'
```

If the result is not 1, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/usr/sbin/systemsetup -setremoteappleevents off  
/bin/launchctl disable system/com.apple.AEserver
```



Systemsetup with -setremoteappleevents flag will fail unless you grant Full Disk Access to systemsetup or its parent process. Requires supervision.

ID	system_settings_rae_disable	
References	800-53r5	<ul style="list-style-type: none">• AC-17• AC-3
	CCE	<ul style="list-style-type: none">• CCE-95392-7

11.35. Disable Remote Management

Remote Management *MUST* be disabled.

To check the state of the system, run the following command(s):

```
/usr/libexec/mdmclient QuerySecurityInfo 2>/dev/null | /usr/bin/grep -c  
"RemoteDesktopEnabled = 0"
```

If the result is not 1, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/System/Library/CoreServices/RemoteManagement/ARDAgent.app/Contents/Resources/kick  
start -deactivate -stop
```

ID	system_settings_remote_management_disable	
References	800-53r5	<ul style="list-style-type: none">CM-7, CM-7(1)
	CCE	<ul style="list-style-type: none">CCE-95393-5

11.36. Disable Screen Sharing and Apple Remote Desktop

Support for both Screen Sharing and Apple Remote Desktop (ARD) is non-essential and *MUST* be disabled.

The information system *MUST* be configured to provide only essential capabilities. Disabling screen sharing and ARD helps prevent the unauthorized connection of devices, the unauthorized transfer of information, and unauthorized tunneling.

To check the state of the system, run the following command(s):

```
result="FAIL"  
enabled=$(/bin/launchctl print-disabled system | /usr/bin/grep  
'"com.apple.screensharing" => enabled')  
running=$(/bin/launchctl print system/com.apple.screensharing 2>/dev/null)  
  
if [[ -z "$running" ]] && [[ -z "$enabled" ]]; then  
    result="PASS"  
elif [[ -n "$running" ]]; then  
    result=result+" RUNNING"  
elif [[ -n "$enabled" ]]; then  
    result=result+" ENABLED"  
fi  
echo $result
```

If the result is not **PASS**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/bin/launchctl bootout system/com.apple.screensharing  
/bin/launchctl disable system/com.apple.screensharing
```

NOTE - This will apply to the whole system

ID	system_settings_screen_sharing_disable	
References	800-53r5	<ul style="list-style-type: none">• AC-17• AC-3
	CCE	<ul style="list-style-type: none">• CCE-95394-3

11.37. Enforce Session Lock After Screen Saver is Started

A screen saver *MUST* be enabled and the system *MUST* be configured to require a password to unlock once the screensaver has been on for a maximum of 5 seconds.

An unattended system with an excessive grace period is vulnerable to a malicious user.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
function run() {
    let delay = ObjC.unwrap(
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.screensaver')\
.objectForKey('askForPasswordDelay'))
    if ( delay <= 5 ) {
        return("true")
    } else {
        return("false")
    }
}
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.screensaver) payload type:

```
<key>askForPasswordDelay</key>
<integer>5</integer>
```

ID	system_settings_screensaver_ask_for_password_delay_enforce	
References	800-53r5	<ul style="list-style-type: none">• AC-11
	CCE	<ul style="list-style-type: none">• CCE-95395-0

11.38. Enforce Screen Saver Password

Users **MUST** authenticate when unlocking the screen saver.

The screen saver acts as a session lock and prevents unauthorized users from accessing the current user's account.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.screensaver')\
.objectForKey('askForPassword').js
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.screensaver) payload type:

```
<key>askForPassword</key>
<true/>
```

ID	system_settings_screensaver_password_enforce	
References	800-53r5	<ul style="list-style-type: none">• AC-11
	CCE	<ul style="list-style-type: none">• CCE-95396-8

11.39. Enforce Screen Saver Timeout

The screen saver timeout *MUST* be set to 1200 seconds or a shorter length of time.

This rule ensures that a full session lock is triggered within no more than 1200 seconds of inactivity.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
function run() {
    let timeout = ObjC.unwrap(
        $.NSUserDefaults.alloc.initWithSuiteName('com.apple.screensaver')\
        .objectForKey('idleTime'))
    if ( timeout <= 1200 ) {
        return("true")
    } else {
        return("false")
    }
}
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.screensaver) payload type:

```
<key>idleTime</key>
<integer>1200</integer>
```

ID	system_settings_screensaver_timeout_enforce		
References	800-53r5	• AC-11 • IA-11	CCE
		• CCE-95397-6	

11.40. Enforce Automatic Installs of Available Security Updates using DDM.

Ensure that available security updates are installed as soon as they are available from Apple and that the user cannot modify the setting within System Settings.

To check the state of the system, run the following command(s):

```
/usr/bin/plutil -convert json  
/var/db/softwareupdate/SoftwareUpdateDDMStatePersistence.plist -o - | /usr/bin/jq  
--raw-output  
. 'SUCorePersistedStatePolicyFields.SUCoreDDMDeclarationGlobalSettings.automaticallyInstallSystemAndSecurityUpdates'
```

If the result is not **1**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

This is implemented by Declarative Device Management (DDM).

ID	system_settings_security_update_install	
References	800-53r5	<ul style="list-style-type: none">SI-2
	CCE	<ul style="list-style-type: none">CCE-95602-9

11.41. Disable Siri

Support for Siri is non-essential and *MUST* be disabled.

The information system *MUST* be configured to provide only essential capabilities.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS  
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\n.objectForKey('allowAssistant').js\nEOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowAssistant</key>
```

<false/>

ID	system_settings_siri_disable	
References	800-53r5	<ul style="list-style-type: none">• AC-20• CM-7, CM-7(1)• SC-7(10)
	CCE	<ul style="list-style-type: none">• CCE-95398-4

11.42. Disable the System Settings Pane for Siri

The System Settings pane for Siri *MUST* be hidden.

Hiding the System Settings pane prevents the users from configuring Siri.



Disabling the Siri System Settings pane blocks the user from opting into Apple Intelligence.

To check the state of the system, run the following command(s):

```
/usr/bin/profiles show -output stdout-xml | /usr/bin/xmllint --xpath  
'//key[text()="DisabledSystemSettings"]/following-sibling::*[1]' - | /usr/bin/grep -c  
com.apple.Siri-Settings.extension
```

If the result is not 1, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.systempreferences) payload type:

```
<key>DisabledSystemSettings</key>  
<array>  
  <string>com.apple.Siri-Settings.extension</string>  
</array>
```

ID	system_settings_siri_settings_disable	
References	800-53r5	<ul style="list-style-type: none">• CM-7, CM-7(1), CM-7(5)
	CCE	<ul style="list-style-type: none">• CCE-95400-8

11.43. Disable Server Message Block Sharing

Support for Server Message Block (SMB) file sharing is non-essential and *MUST* be disabled.

The information system *MUST* be configured to provide only essential capabilities.

To check the state of the system, run the following command(s):

```
/bin/launchctl print-disabled system | /usr/bin/grep -c '"com.apple.smbd" => disabled'
```

If the result is not 1, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/bin/launchctl disable system/com.apple.smbd
```

The system may need to be restarted for the update to take effect.

ID	system_settings_smbd_disable		
References	800-53r5	• AC-17 • AC-3	
	CCE	• CCE-95401-6	

11.44. Disable SSH Server for Remote Access Sessions

SSH service *MUST* be disabled for remote access.

To check the state of the system, run the following command(s):

```
result="FAIL"
enabled=$(/bin/launchctl print-disabled system | /usr/bin/grep '"com.openssh.sshd" => enabled')
running=$(/bin/launchctl print system/com.openssh.sshd 2>/dev/null)

if [[ -z "$running" ]] && [[ -z "$enabled" ]]; then
    result="PASS"
elif [[ -n "$running" ]]; then
    result=result+" RUNNING"
elif [[ -n "$enabled" ]]; then
    result=result+" ENABLED"
fi
```

```
echo $result
```

If the result is not **PASS**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/usr/sbin/systemsetup -f -setremotelogin off >/dev/null  
/bin/launchctl disable system/com.openssh.sshd
```



Systemsetup with -setremotelogin flag will fail unless you grant Full Disk Access to systemsetup or its parent process. Requires supervision.

ID	system_settings_ssh_disable	
References	800-53r5	<ul style="list-style-type: none">AC-17CM-7, CM-7(1)
CCE		<ul style="list-style-type: none">CCE-95406-5

11.45. Enable SSH Server for Remote Access Sessions

Remote access sessions *MUST* use encrypted methods to protect unauthorized individuals from gaining access.

To check the state of the system, run the following command(s):

```
/bin/launchctl print-disabled system | /usr/bin/grep -c '"com.openssh.sshd" =>  
enabled'
```

If the result is not **1**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
/bin/launchctl enable system/com.openssh.sshd
```

ID	system_settings_ssh_enable
----	----------------------------

References	800-53r5	<ul style="list-style-type: none"> • AC-17 • AC-3 • CM-7, CM-7(1) • IA-2(8)
	CCE	<ul style="list-style-type: none"> • CCE-95407-3

11.46. Require Administrator Password to Modify System-Wide Preferences

The system *MUST* be configured to require an administrator password in order to modify the system-wide preferences in System Settings.

Some Preference Panes in System Settings contain settings that affect the entire system. Requiring a password to unlock these system-wide settings reduces the risk of a non-authorized user modifying system configurations.

To check the state of the system, run the following command(s):

```

authDBs=( "system.preferences" "system.preferences.energysaver"
"system.preferences.network" "system.preferences.printing"
"system.preferences.sharing" "system.preferences.softwareupdate"
"system.preferences.startupdisk" "system.preferences.timemachine")
result="1"
for section in ${authDBs[@]}; do
    if [[ $(/usr/bin/security -q authorizationdb read "$section" | /usr/bin/xmllint
-xpath 'name(//*[contains(text(), "shared")]/following-sibling::*[1])' -) != "false"
]]; then
        result="0"
    fi
    if [[ $(/usr/bin/security -q authorizationdb read "$section" | /usr/bin/xmllint
-xpath '//*[contains(text(), "group")]/following-sibling::*[1]/text()' - ) != "admin"
]]; then
        result="0"
    fi
    if [[ $(/usr/bin/security -q authorizationdb read "$section" | /usr/bin/xmllint
-xpath 'name(//*[contains(text(), "authenticate-user")]/following-sibling::*[1])' -)
!= "true" ]]; then
        result="0"
    fi
    if [[ $(/usr/bin/security -q authorizationdb read "$section" | /usr/bin/xmllint
-xpath 'name(//*[contains(text(), "session-owner")]/following-sibling::*[1])' -) !=
>false" ]]; then
        result="0"
    fi
done
echo $result

```

If the result is not 1, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

```
authDBs=("system.preferences" "system.preferences.energysaver"
"system.preferences.network" "system.preferences.printing"
"system.preferences.sharing" "system.preferences.softwareupdate"
"system.preferences.startupdisk" "system.preferences.timemachine")

for section in ${authDBs[@]}; do
/usr/bin/security -q authorizationdb read "$section" > "/tmp/$section.plist"

class_key_value=$((/usr/libexec/PlistBuddy -c "Print :class" "/tmp/
$section.plist" 2>&1)
if [[ "$class_key_value" == *"Does Not Exist"* ]]; then
/usr/libexec/PlistBuddy -c "Add :class string user" "/tmp/$section.plist"
else
/usr/libexec/PlistBuddy -c "Set :class user" "/tmp/$section.plist"
fi

key_value=$((/usr/libexec/PlistBuddy -c "Print :shared" "/tmp/$section.plist"
2>&1)
if [[ "$key_value" == *"Does Not Exist"* ]]; then
/usr/libexec/PlistBuddy -c "Add :shared bool false" "/tmp/$section.plist"
else
/usr/libexec/PlistBuddy -c "Set :shared false" "/tmp/$section.plist"
fi

auth_user_key=$((/usr/libexec/PlistBuddy -c "Print :authenticate-user"
"/tmp/$section.plist" 2>&1)
if [[ "$auth_user_key" == *"Does Not Exist"* ]]; then
/usr/libexec/PlistBuddy -c "Add :authenticate-user bool true" "/tmp/
$section.plist"
else
/usr/libexec/PlistBuddy -c "Set :authenticate-user true" "/tmp/$section.plist"
fi

session_owner_key=$((/usr/libexec/PlistBuddy -c "Print :session-owner"
"/tmp/$section.plist" 2>&1)
if [[ "$session_owner_key" == *"Does Not Exist"* ]]; then
/usr/libexec/PlistBuddy -c "Add :session-owner bool false" "/tmp/
$section.plist"
else
/usr/libexec/PlistBuddy -c "Set :session-owner false" "/tmp/$section.plist"
fi

group_key=$((/usr/libexec/PlistBuddy -c "Print :group" "/tmp/$section.plist"
2>&1)
```

```

if [[ "$group_key" == *"Does Not Exist"* ]]; then
    /usr/libexec/PlistBuddy -c "Add :group string admin" "/tmp/$section.plist"
else
    /usr/libexec/PlistBuddy -c "Set :group admin" "/tmp/$section.plist"
fi

/usr/bin/security -q authorizationdb write "$section" < "/tmp/$section.plist"
done

```

ID	system_settings_system_wide_preferences_configure	
References	800-53r5	<ul style="list-style-type: none"> • AC-6, AC-6(1), AC-6(2)
	CCE	<ul style="list-style-type: none"> • CCE-95408-1

11.47. Configure macOS to Use an Authorized Time Server

Approved time server *MUST* be the only server configured for use. As of macOS 10.13 only one time server is supported.

This rule ensures the uniformity of time stamps for information systems with multiple system clocks and systems connected over a network.

To check the state of the system, run the following command(s):

```

/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.MCX')\
.objectForKey('timeServer').js
EOS

```

If the result is not **time.nist.gov**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.MCX) payload type:

```

<key>timeServer</key>
<string>time.nist.gov</string>

```

ID	system_settings_time_server_configure
-----------	---------------------------------------

References	800-53r5	<ul style="list-style-type: none"> • AU-12(1) • SC-45(1)
	CCE	<ul style="list-style-type: none"> • CCE-95411-5

11.48. Enforce macOS Time Synchronization

Time synchronization *MUST* be enforced on all networked systems.

This rule ensures the uniformity of time stamps for information systems with multiple system clocks and systems connected over a network.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript <> EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.timed')\
.objectForKey('TMAutomaticTimeOnlyEnabled').js
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:



The following settings are in the (com.apple.ManagedClient.preferences) payload. This payload requires the additional settings to be sub-payloads within, containing their defined payload types.

Create a configuration profile containing the following keys in the (com.apple.timed) payload type:

```
<key>TMAutomaticTimeOnlyEnabled</key>
<true/>
```

ID	system_settings_time_server_enforce	
References	800-53r5	<ul style="list-style-type: none"> • AU-12(1) • SC-45(1)
	CCE	<ul style="list-style-type: none"> • CCE-95412-3

11.49. Configure User Session Lock When a Smart Token is Removed

The screen lock *MUST* be configured to initiate automatically when the smart token is removed from the system.

Session locks are temporary actions taken when users stop work and move away from the immediate vicinity of the information system but do not want to log out because of the temporary nature of their absences. While a session lock is not an acceptable substitute for logging out of an information system for longer periods of time, they prevent a malicious user from accessing the information system when a user has removed their smart token.

 Information System Security Officers (ISSOs) may make the risk-based decision not to enforce a session lock when a smart token is removed, so as to maintain necessary workflow capabilities, but they are advised to first fully weigh the potential risks posed to their organization.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.security.smartcard')\
.objectForKey('tokenRemovalAction').js
EOS
```

If the result is not **1**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.security.smartcard) payload type:

```
<key>tokenRemovalAction</key>
<integer>1</integer>
```

ID	system_settings_token_removal_enforce		
References	800-53r5 CCE	• AC-11 • CCE-95413-1	

11.50. Disable the Touch ID System Settings Pane

The System Settings pane for Touch ID *MUST* be disabled.

Disabling the System Settings pane prevents the users from configuring Touch ID.

To check the state of the system, run the following command(s):

```
/usr/bin/profiles show -output stdout-xml | /usr/bin/xmllint --xpath  
'//key[text()="DisabledSystemSettings"]/following-sibling::*[1]' - | /usr/bin/grep -c  
"com.apple.Touch-ID-Settings.extension"
```

If the result is not 1, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.systempreferences) payload type:

```
<key>DisabledSystemSettings</key>  
<array>  
  <string>com.apple.Touch-ID-Settings.extension</string>  
</array>
```

ID	system_settings_touch_id_settings_disable	
References	800-53r5	<ul style="list-style-type: none">CM-7, CM-7(1), CM-7(5)
	CCE	<ul style="list-style-type: none">CCE-95414-9

11.51. Disable TouchID for Unlocking the Device

TouchID enables the ability to unlock a Mac system with a user's fingerprint.

TouchID *MUST* be disabled for "Unlocking your Mac" on all macOS devices that are capable of using Touch ID.

The system *MUST* remain locked until the user establishes access using an authorized identification and authentication method.



TouchID is not an approved biometric authenticator for US Federal Government usage as it has not been verified to meet the strength requirements outlined in NIST SP 800-63.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS  
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
```

```
.objectForKey('allowFingerprintForUnlock').js  
EOS
```

If the result is not **false**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowFingerprintForUnlock</key>  
<false/>
```

ID	system_settings_touchid_unlock_disable	
References	800-53r5 CCE	<ul style="list-style-type: none">• IA-5• CCE-95415-6

11.52. USB Devices Must be Authorized Before Allowing

USB devices connected to a Mac *MUST* be authorized.



This feature is removed if a smartcard is paired or smartcard attribute mapping is configured.

To check the state of the system, run the following command(s):

```
/usr/bin/osascript -l JavaScript << EOS
function run() {
    let pref1 = ObjC.unwrap(
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.applicationaccess')\
.objectForKey('allowUSBRestrictedMode'))
    if ( pref1 == false ) {
        return("false")
    } else {
        return("true")
    }
}
EOS
```

If the result is not **true**, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.applicationaccess) payload type:

```
<key>allowUSBRestrictedMode</key>
<true/>
```

ID	system_settings_usb_restricted_mode	
References	800-53r5	<ul style="list-style-type: none">• MP-7• SC-41
	CCE	<ul style="list-style-type: none">• CCE-95416-4

11.53. Disable the System Settings Pane for Wallet and Apple Pay

The System Settings pane for Wallet and Apple Pay *MUST* be disabled.

Disabling the System Settings pane prevents the users from configuring Wallet and Apple Pay.

To check the state of the system, run the following command(s):

```
/usr/bin/profiles show -output stdout-xml | /usr/bin/xmllint --xpath
'//key[text()="DisabledSystemSettings"]/following-sibling::*[1]' - | /usr/bin/grep -c
"com.apple.WalletSettingsExtension"
```

If the result is not 1, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

Create a configuration profile containing the following keys in the (com.apple.systempreferences) payload type:

```
<key>DisabledSystemSettings</key>
<array>
    <string>com.apple.WalletSettingsExtension</string>
</array>
```

ID	system_settings_wallet_applepay_settings_disable	
References	800-53r5	<ul style="list-style-type: none"> CM-7, CM-7(1), CM-7(5)
	CCE	<ul style="list-style-type: none"> CCE-95418-0

11.54. Disable Wi-Fi Interface

The macOS system must be configured with Wi-Fi support software disabled if not connected to an authorized trusted network.

Allowing devices and users to connect to or from the system without first authenticating them allows untrusted access and can lead to a compromise or attack. Since wireless communications can be intercepted it is necessary to use encryption to protect the confidentiality of information in transit. Wireless technologies include for example microwave packet radio (UHF/VHF) 802.11x and Bluetooth. Wireless networks use authentication protocols (e.g. EAP/TLS PEAP) which provide credential protection and mutual authentication.



If the system requires Wi-Fi to connect to an authorized network, this is not applicable.



This rule is marked as manual and may not be able to be automated. It is also excluded in the compliance scan and will not report any results.

To check the state of the system, run the following command(s):

```
/usr/sbin/networksetup -listallnetworkservices | /usr/bin/grep -c "*Wi-Fi"
```

If the result is not 1, this is a finding.

Remediation Description

Perform the following to configure the system to meet the requirements:

To disable Wi-Fi on a macOS system, run the following command.

```
/usr/sbin/networksetup -setnetworkserviceenabled "Wi-Fi" off
```

ID	system_settings_wifi_disable	
References	800-53r5	<ul style="list-style-type: none"> AC-18, AC-18(1), AC-18(3) AC-4
	CCE	<ul style="list-style-type: none"> CCE-95419-8

Chapter 12. Inherent

This section reviews the controls that are built-in to macOS, and cannot be configured out of compliance.

12.1. Audit Record Reduction and Report Generation

The system *IS* configured with the ability provide and implement an audit record reduction and report generation capability.

Audit record reduction is a process that manipulates collected audit log information and organizes it into a summary format that is more meaningful to analysts. Audit record reduction and report generation capabilities do not always emanate from the same system or from the same organizational entities that conduct audit logging activities. The audit record reduction capability includes modern data mining techniques with advanced data filters to identify anomalous behavior in audit records. The report generation capability provided by the system can generate customizable reports. Time ordering of audit records can be an issue if the granularity of the timestamp in the record is insufficient.

Audit record reduction and report generation can be done with tools built into macOS such as auditreduce and praudit. These tools are protected by System Integrity Protection (SIP).

The technology supports this requirement and cannot be configured to be out of compliance. The technology inherently meets this requirement.

ID	audit_record_reduction_report_generation	
References	800-53r5	• AU-7

12.2. Allow Information Transfer with Other Operating Systems

The information system *IS* configured to allow the transfer of information to and from other operating systems and users.

The macOS is a UNIX 03-compliant operating system, which allows owners of object to have discretion over who should be authorized to access information.

<https://developer.apple.com/library/archive/documentation/Security/Conceptual/AuthenticationAndAuthorizationGuide/Permissions/Permissions.html>

The technology supports this requirement and cannot be configured to be out of compliance. The technology inherently meets this requirement.

ID	os_allow_info_passed	
References	800-53r5	• AC-3(4)

12.3. Ensure Separate Execution Domain for Processes

The inherent configuration of the macOS *IS* in compliance as Apple has implemented multiple features Mandatory access controls (MAC), System Integrity Protection (SIP), and application sandboxing.

<https://support.apple.com/guide/security/system-integrity-protection-secb7ea06b49/web>

<https://developer.apple.com/library/archive/documentation/Security/Conceptual/AppSandboxDesignGuide/AboutAppSandbox/AboutAppSandbox.html>

The technology supports this requirement and cannot be configured to be out of compliance. The technology inherently meets this requirement.

ID	os_application_sandboxing	
References	800-53r5	• SC-39

12.4. Allow Administrators to Modify Security Settings and System Attributes

The information system *IS* configured to allow administrators to modify security settings and system attributes.

The macOS is a UNIX 03-compliant operating system, which allows administrators of the system to change security settings and system attributes, including those which are kept within preference panes that are locked for standard users. .

<https://support.apple.com/guide/mac-help/change-permissions-for-files-folders-or-disks-mchlp1203/mac>

The technology supports this requirement and cannot be configured to be out of compliance. The technology inherently meets this requirement.

ID	os_change_security_attributes	
References	800-53r5	• AC-3(4)

12.5. Enforce Access Restrictions

The information system *IS* configured to enforce access restrictions and support auditing of the enforcement actions.

The inherent configuration of a macOS provides users with the ability to set their own permission settings to control who can view and alter files on the computer.

<https://support.apple.com/guide/mac-help/change-permissions-for-files-folders-or-disks-mchlp1203/mac>

The technology supports this requirement and cannot be configured to be out of compliance. The technology inherently meets this requirement.

ID	os_enforce_access_restrictions
References	800-53r5

12.6. Allow Administrators to Promote Other Users to Administrator Status

The information system *IS* configured to allow current administrators to promote standard users to administrator user status.

The macOS is a UNIX 03-compliant operating system which allows administrators of the system to grant privileges to other users.

<https://support.apple.com/guide/mac-help/set-up-other-users-on-your-mac-mtusr001/mac>

The technology supports this requirement and cannot be configured to be out of compliance. The technology inherently meets this requirement.

ID	os_grant_privs
References	800-53r5

12.7. Configure the System to Implement Approved Cryptography to Protect Information

The information system *IS* configured to implement approved cryptography to protect information.

Use of weak or untested encryption algorithms undermines the purposes of utilizing encryption to protect data. The operating system must implement cryptographic modules that adhere to the higher standards that have been tested, validated, and approved by the federal government.

Apple is committed to the FIPS validation process and historically has always submitted and validated the cryptographic modules in macOS. macOS Tahoe for Apple Silicon will be submitted for FIPS validation. macOS Tahoe for Intel based processors will *NOT* be submitted for FIPS validation.

<https://csrc.nist.gov/Projects/cryptographic-module-validation-program/validated-modules>

<https://support.apple.com/guide/sccc/welcome/web>

The technology supports this requirement and cannot be configured to be out of compliance. The technology inherently meets this requirement using FIPS Validated Cryptographic Modules.

ID	os_implement_cryptography
----	---------------------------

12.8. Configure the System to Protect Memory from Unauthorized Code Execution

The information system *IS* configured to implement non-executable data to protect memory from code execution.

Some adversaries launch attacks with the intent of executing code in non-executable regions of memory or in memory locations that are prohibited (e.g., buffer overflow attacks). Security safeguards (e.g., data execution prevention and address space layout randomization) can be employed to protect non-executable regions of memory. Data execution prevention safeguards can either be hardware-enforced or software-enforced; hardware-enforced methods provide the greater strength of mechanism.

macOS supports address space layout randomization (ASLR), position-independent executable (PIE), Stack Canaries, and NX stack and heap protection.

<https://developer.apple.com/library/archive/documentation/Darwin/Conceptual/64bitPorting/transition/transition.html>

https://developer.apple.com/library/archive/qa/qa1788/_index.html

<https://www.apple.com/macos/security/>

The technology supports this requirement and cannot be configured to be out of compliance. The technology inherently meets this requirement.

ID	os_implement_memory_protection	
References	800-53r5	• SI-16

12.9. Limit Concurrent GUI Sessions to 10 for all Accounts

The information system *IS* configured to limit the number of concurrent graphical user interface (GUI) sessions to a maximum of ten for all users.

Operating system management includes the ability to control the number of users and user sessions that utilize an operating system. Limiting the number of allowed users and sessions per user helps reduce the risks related to Denial-of-Service (DoS) attacks. This requirement addresses concurrent sessions for information system accounts and does not address concurrent sessions by single users via multiple system accounts. The maximum number of concurrent sessions should be defined based upon mission needs and the operational environment for each system.

The technology supports this requirement and cannot be configured to be out of compliance. The technology inherently meets this requirement.

ID	os_limit_gui_sessions	
References	800-53r5	• AC-10

12.10. Enforce Approved Authorization for Logical Access

The information system *IS* configured to enforce an approved authorization process before granting users logical access.

The inherent configuration of the macOS does not grant users logical access without authorization. Authorization is achieved on the macOS through permissions, which are controlled at many levels, from the Mach and BSD components of the kernel, through higher levels of the operating system and, for networked applications, through the networking protocols. Permissions can be granted at the level of directories, subdirectories, files or applications, or specific data within files or functions within applications.

<https://developer.apple.com/library/archive/documentation/Security/Conceptual/AuthenticationAndAuthorizationGuide/Permissions/Permissions.html>

The technology supports this requirement and cannot be configured to be out of compliance. The technology inherently meets this requirement.

ID	os_logical_access	
References	800-53r5	• AC-3

12.11. Display logoff capability and message to prevent exploitation

Provides a logout capability for user-initiated communications sessions whenever authentication is used to gain access to the system.

Displays an explicit logout message to users indicating the reliable termination of authenticated communications sessions.

The technology supports this requirement and cannot be configured to be out of compliance. The technology inherently meets this requirement.

ID	os_logoff_capability_and_message	
References	800-53r5	• AC-12(1), AC-12(2)

12.12. Ensure the System Implements Malicious Code Protection Mechanisms

The inherent configuration of the macOS IS in compliance as Apple has designed the system with three layers of protection against malware. Each layer of protection is comprised of one or more malicious code protection mechanisms, which are automatically implemented and which, collectively, meet the requirements of all applicable federal laws, Executive Orders, directives, policies, regulations, standards, and guidance for malicious code prevention.

1. This first layer of defense targets the distribution of malware; the aim is to prevent malware from ever launching. The following mechanisms are inherent to the macOS design and constitute the first layer of protection against malicious code:
 - The Apple App Store: the safest way to add new applications to a Mac is by downloading them from the App Store; all apps available for download from the App Store have been reviewed for signs of tampering and signed by Apple to indicate that the app meets security requirements and does not contain malware.
 - XProtect: a built-in, signature-based, anti-virus, anti-malware technology inherent to all Macs. XProtect automatically detects and blocks the execution of known malware.
 - In macOS 10.15 and all subsequent releases, XProtect checks for known malicious content when:
 - an app is first launched,
 - an app has been changed (in the file system), and
 - XProtect signatures are updated.
 - YARA: another built-in tool (inherent to all Macs), which conducts signature-based detection of malware. Apple updates YARA rules regularly.
 - Gatekeeper: a security feature inherent to all Macs; Gatekeeper scans apps to detect malware and/or revocations of a developer's signing certificate and prevents unsafe apps from running.
 - Notarization: Apple performs regular, automated scans to detect signs of malicious content and to verify developer ID-signed software; when no issues are found, Apple notarizes the software and delivers the results of scans to the system owner.
2. The second layer of defense targets malware that manages to appear on a Mac before it runs; the aim is to quickly identify and block any malware present on a Mac in order to prevent the malware from running and further spreading. The following mechanisms are inherent to the macOS design and constitute the second layer of protection against malicious code:
 - XProtect (defined above).
 - Gatekeeper (defined above).
 - Notarization (defined above).
3. The third layer of defense targets infected Mac system(s); the aim is to remediate Macs on which malware has managed to successfully execute. The following mechanism is inherent to the macOS design and constitutes the third layer of protection against malicious code:

- Apple’s XProtect: a technology included on all macOS systems. XProtect will remediate infections upon receiving updated information delivered and when infections are detected

<https://support.apple.com/guide/security/protecting-against-malware-sec469d47bd8/1/web/1>

<https://support.apple.com/guide/security/app-security-overview-sec35dd877d0/web>

The technology supports this requirement and cannot be configured to be out of compliance. The technology inherently meets this requirement.

ID	os_malicious_code_prevention	
References	800-53r5	<ul style="list-style-type: none"> • SI-3

12.13. Obscure Passwords

The information system *IS* configured to obscure feedback of authentication information during the authentication process to protect the information from possible exploitation by unauthorized individuals.

The inherent configuration of a macOS uses NSSecureTextField for any text field that receives a password, which automatically obscures text which is entered.

<https://developer.apple.com/documentation/appkit/nssecuretextfield>

The technology supports this requirement and cannot be configured to be out of compliance. The technology inherently meets this requirement.

ID	os_obscure_password	
References	800-53r5	<ul style="list-style-type: none"> • IA-5 • IA-6

12.14. Must behave in predictable and documented manner

The information system behaves in a predictable and documented manner that reflects organizational and system objectives when invalid inputs are received.

The technology supports this requirement and cannot be configured to be out of compliance. The technology inherently meets this requirement.

ID	os_predictable_behavior	
References	800-53r5	<ul style="list-style-type: none"> • SI-10(3)

12.15. Prevent Software From Executing at Higher Privilege Levels than Users Executing The Software

In certain situations, software applications/programs need to execute with elevated privileges to perform required functions. However, if the privileges required for execution are at a higher level than the privileges assigned to organizational users invoking such applications/programs, those users are indirectly provided with greater privileges than assigned by the organizations. Some programs and processes are required to operate at a higher privilege level and therefore should be excluded from the organization-defined software list after review.

The inherent configuration of the macOS does not allow for non-privileged users to be able to execute functions requiring privilege.

<https://developer.apple.com/library/archive/documentation/Security/Conceptual/AuthenticationAndAuthorizationGuide/Permissions/Permissions.html>

The technology supports this requirement and cannot be configured to be out of compliance. The technology inherently meets this requirement.

ID	os_prevent_priv_execution	
References	800-53r5	• AC-6(8)

12.16. Configure the System to Block Non-Privileged Users from Executing Privileged Functions

The information system *IS* configured to block standard users from executing privileged functions.

Privileged functions include disabling, circumventing, or altering implemented security safeguards and countermeasures.

The inherent configuration of the macOS does not allow for non-privileged users to be able to execute functions requiring privilege.

<https://developer.apple.com/library/archive/documentation/Security/Conceptual/AuthenticationAndAuthorizationGuide/Introduction/Introduction.html>

The technology supports this requirement and cannot be configured to be out of compliance. The technology inherently meets this requirement.

ID	os_prevent_priv_functions	
References	800-53r5	• AC-6(10)

12.17. Configure the System to Prevent the Unauthorized Disclosure of Data via Shared Resources

The information system *IS* configured to ensure that the unauthorized disclosure of data does not occur when resources are shared.

The inherent configuration of the macOS does not allow for resources to be shared between users without authorization.

<https://developer.apple.com/library/archive/documentation/Security/Conceptual/AuthenticationAndAuthorizationGuide/Permissions/Permissions.html>

The technology supports this requirement and cannot be configured to be out of compliance. The technology inherently meets this requirement.

ID	os_prevent_unauthorized_disclosure	
References	800-53r5	• SC-4

12.18. Prohibit Remote Activation of Collaborative Computing Devices

The inherent configuration of the macOS *IS* in compliance.

Apple has implemented a green light physically next to your camera that will glow when the camera is activated. There is an orange dot indicator by the Control Center pull down menu item to indicate when the system's microphone is listening or activated.

The macOS has built into the system, the ability to grant or deny access to the camera and microphone which requires the application to have an entitlement to use the device.

<https://support.apple.com/guide/mac-help/use-the-built-in-camera-mchlp2980/mac>

<https://support.apple.com/guide/mac-help/control-access-to-your-camera-mchlfd108da/mac>

<https://support.apple.com/guide/mac-help/control-access-to-your-microphone-on-mac-mchla1b1e1fe/12.0/mac/12.0>

The technology partially supports this requirement and cannot be configured to be in full compliance.

ID	os_prohibit_remote_activation_collab_devices	
References	800-53r5	• SC-15

12.19. Provide Ability to Disconnect or Disable Remote Access

Without the ability to immediately disconnect or disable remote access, an attack or other compromise taking place would not be immediately stopped. Operating system remote access functionality must have the capability to immediately disconnect current users remotely accessing the information system and/or disable further remote access. The speed of disconnect or disablement varies based on the criticality of missions functions and the need to eliminate immediate or future remote access to organizational information systems. The remote access functionality (e.g., SSH) may implement features such as automatic disconnect (or user-initiated disconnect) in case of adverse information based on an indicator of compromise or attack.

The technology supports this requirement and cannot be configured to be out of compliance. The technology inherently meets this requirement.

ID	os_provide_disconnect_remote_access	
References	800-53r5	• AC-17(9)

12.20. Require users to reauthenticate for privilege escalation

Without reauthentication, users may access resources or perform tasks for which they do not have authorization. When operating systems provide the capability to escalate a functional capability, it is critical the user reauthenticate.

The technology supports this requirement and cannot be configured to be out of compliance. The technology inherently meets this requirement.

ID	os_reauth_privilege	
References	800-53r5	• IA-11

12.21. Require users to reauthenticate when changing authenticators

Without reauthentication, users may access resources or perform tasks for which they do not have authorization. When operating systems provide the capability to change user authenticators, it is critical the user reauthenticate.

The technology supports this requirement and cannot be configured to be out of compliance. The technology inherently meets this requirement.

ID	os_reauth_users_change_authenticators	
References	800-53r5	• IA-11

12.22. Must remove all software components after updated versions installed

Previous versions of software components that are not removed from the information system after updates have been installed may be exploited by adversaries. Some information technology products may remove older versions of software automatically from the information system.

The technology supports this requirement and cannot be configured to be out of compliance. The technology inherently meets this requirement.

ID	os_remove_software_components_after_updates	
References	800-53r5	• SI-2(6)

12.23. Ensure all Federal Laws, Executive Orders, Directives, Policies, Regulations, Standards, and Guidance for Authentication to a Cryptographic Module are Met

The inherent configuration of the macOS *IS* in compliance by implementing mechanisms for authentication to a cryptographic module that meet the requirements of all applicable federal laws, Executive Orders, directives, policies, regulations, standards, and guidance for such authentication

macOS contains many open source projects that may use their own cryptographic libraries typically for the purposes of maintaining platform independence. These services are not covered by the Apple FIPS Validation of the CoreCrypto and CoreCrypto Kernel modules.

Apple is committed to the FIPS validation process and historically has always submitted and validated the cryptographic modules in macOS. macOS Tahoe for Apple Silicon will be submitted for FIPS validation. macOS Tahoe for Intel based processors will *NOT* be submitted for FIPS validation.

<https://csrc.nist.gov/Projects/cryptographic-module-validation-program/validated-modules>

<https://support.apple.com/guide/sccc/welcome/web>

The technology supports this requirement and cannot be configured to be out of compliance. The technology inherently meets this requirement.

ID	os_required_crypto_module	
References	800-53r5	• IA-7

12.24. Protected Storage for Cryptographic Keys

A system *IS* configured to provide protected storage for cryptographic keys either by hardware

protected key store or an organizationally defined safeguard.

Macs with Apple Silicon or T2 processors provide protected storage for cryptographic keys via the secure enclave.

<https://support.apple.com/guide/security/secure-enclave-sec59b0b31ff/1/web/1>



This will only return a proper result on a T2 or Apple Silicon Macs.

/usr/sbin/ioreg -w 0 -c AppleSEPManger | /usr/bin/grep -q 'AppleSEPManger'; /bin/echo \$?

ID	os_secure_enclave	
References	800-53r5	<ul style="list-style-type: none">• SC-28(3)

12.25. Configure the System to Separate User and System Functionality

The information system *IS* configured to separate user and system functionality.

Operating system management functionality includes functions necessary for administration and requires privileged user access. Allowing non-privileged users to access operating system management functionality capabilities increases the risk that non-privileged users may obtain elevated privileges. Operating system management functionality includes functions necessary to administer console, network components, workstations, or servers and typically requires privileged user access.

The inherent configuration of the macOS allows only privileged users to access operating system management functionalities.

<https://developer.apple.com/library/archive/documentation/MacOSX/Conceptual/BPSystemStartup/Chapters/DesigningDaemons.html>

The technology supports this requirement and cannot be configured to be out of compliance. The technology inherently meets this requirement.

ID	os_separate_functionality	
References	800-53r5	<ul style="list-style-type: none">• MA-4(1)• SC-2

12.26. Encrypt Stored Passwords

The information system *IS* configured to encrypt stored passwords.

Passwords need to be protected at all times, and encryption is the standard method for protecting passwords. If passwords are not encrypted, they can be plainly read (i.e., clear text) and easily compromised.

[https://developer.apple.com/documentation/opendirectory/
kodattributetypeauthenticationauthority](https://developer.apple.com/documentation/opendirectory/kodattributetypeauthenticationauthority)

The technology supports this requirement and cannot be configured to be out of compliance. The technology inherently meets this requirement.

ID	os_store_encrypted_passwords	
References	800-53r5	• IA-5(1), IA-5(1)(c)

12.27. Uniquely Identify Users and Processes

The macOS is a UNIX 03-compliant operating system. The system uniquely identifies and authenticates organizational users or processes.

The technology supports this requirement and cannot be configured to be out of compliance. The technology inherently meets this requirement.

ID	os_unique_identification	
References	800-53r5	• IA-4

12.28. Verify remote disconnection of sessions

The information system implements remote disconnect verification at the termination of non-local maintenance and diagnostic sessions.

The technology supports this requirement and cannot be configured to be out of compliance. The technology inherently meets this requirement.

ID	os_verify_remote_disconnection	
References	800-53r5	• MA-4(7)

12.29. Automatically Remove or Disable Emergency Accounts within 72 Hours

The macOS is able to be configured to automatically remove or disable emergency accounts within 72 hours or less.

Emergency administrator accounts are privileged accounts established in response to crisis situations where the need for rapid account activation is required. Therefore, emergency account activation may bypass normal account authorization processes. If these accounts are disabled, system maintenance during emergencies may not be possible, thus adversely affecting system availability.

Although the ability to create and use emergency administrator accounts is necessary for performing system maintenance during emergencies, these accounts present vulnerabilities to the

system if they are not disabled and removed when they are no longer needed. Configuring the macOS to automatically remove or disable emergency accounts within 72 hours of creation mitigates the risks posed if one were to be created and accidentally left active once the crisis is resolved.

Emergency administrator accounts are different from infrequently used accounts (i.e., local logon accounts used by system administrators when network or normal logon is not available). Infrequently used accounts also remain available and are not subject to automatic termination dates. However, an emergency administrator account is normally a different account created for use by vendors or system maintainers.

To address access requirements, many operating systems can be integrated with enterprise-level authentication/access mechanisms that meet or exceed access control policy requirements.

The technology supports this requirement and cannot be configured to be out of compliance. The technology inherently meets this requirement.

ID	pwpolicy_emergency_accounts_disable	
References	800-53r5	• AC-2(2)

12.30. Force Password Change at Next Logon

The macOS is able to be configured to force users to change their password at next logon.

Temporary passwords are often used for new users when accounts are created. However, once logged in to the system, users must be immediately prompted to change to a permanent password of their creation.

For a user to change their password at next logon, run the following command:

```
/usr/bin/pwpolicy -u [USER] -setpolicy "newPasswordRequired=1"
```



Replace [USER] with the username that must change the password at next logon

The technology supports this requirement and cannot be configured to be out of compliance. The technology inherently meets this requirement.

ID	pwpolicy_force_password_change	
References	800-53r5	• IA-5(1)

12.31. Automatically Remove or Disable Temporary User Accounts within 72 Hours

The macOS is able to be configured to set an automated termination for 72 hours or less for all temporary accounts upon account creation.

If temporary user accounts remain active when no longer needed or for an excessive period, these accounts may be targeted by attackers to gain unauthorized access. To mitigate this risk, automated termination of all temporary accounts *MUST* be set to 72 hours (or less) when the temporary account is created.

If no policy is enforced by a directory service, a password policy can be set with the "pwpolicy" utility. The variable names may vary depending on how the policy was set.

If there are no temporary accounts defined on the system, this is Not Applicable.

The technology supports this requirement and cannot be configured to be out of compliance. The technology inherently meets this requirement.

ID	pwpolicy_temporary_accounts_disable	
References	800-53r5	• AC-2(2)

Chapter 13. Permanent Findings

This section contains the controls that are defined in NIST 800-53 revision 5 but are unable to be configured natively within macOS. It is recommended to implement a third-party solution to meet the controls in this section.

13.1. Off-Load Audit Records

Audit records should be off-loaded onto a different system or media from the system being audited.

Information stored in only one location is vulnerable to accidental or incidental deletion or alteration. Off-loading is a common process in information systems with limited audit storage capacity.

To secure audit records by off-loading, many operating systems can be integrated with enterprise-level auditing mechanisms that meet or exceed this requirement.

The technology does not support this requirement. This is an applicable-does not meet finding.

ID	audit_off_load_records
References	800-53r5 <ul style="list-style-type: none">• AU-4(1)

13.2. Audit Record Reduction and Report Generation

The macOS should be configured to provide and implement the capability to process, sort, and search audit records for events of interest based on organizationally defined fields.

Events of interest can be identified by the content of audit records, including system resources involved, information objects accessed, identities of individuals, event types, event locations, event dates and times, Internet Protocol addresses involved, or event success or failure. Organizations may define event criteria to any degree of granularity required, such as locations selectable by a general networking location or by specific system component.

The technology does not support this requirement. This is an applicable-does not meet finding.

ID	audit_records_processing
References	800-53r5 <ul style="list-style-type: none">• AU-7(1)

13.3. Must Authenticate Before Establishing a Connection

Organizational devices requiring unique device-to-device identification and authentication may be defined by type, by device, or by a combination of type/device. Information systems typically use either shared known information (e.g., Media Access Control [MAC] or Transmission Control Protocol/Internet Protocol [TCP/IP] addresses) for device identification or organizational

authentication solutions (e.g., IEEE 802.1x and Extensible Authentication Protocol [EAP], Radius server with EAP-Transport Layer Security [TLS] authentication, Kerberos) to identify/authenticate devices on local and/or wide area networks. Organizations determine the required strength of authentication mechanisms by the security categories of information systems. Because of the challenges of applying this control on large scale, organizations are encouraged to only apply the control to those limited number (and type) of devices that truly need to support this capability.

The technology does support this requirement, however, third party solutions are required to implement at an infrastructure level.

ID	os_auth_peripherals	
References	800-53r5	• IA-3

13.4. Configure Automated Flaw Remediation

The macOS system *MUST* be configured to determine the state of system components with regard to flaw remediation.

The technology does not support this requirement. This is an applicable-does not meet finding.

ID	os_continuous_monitoring	
References	800-53r5	• SI-2(2)

13.5. Limit Impact of Denial of Service Attacks

The macOS should be configured to limit the impact of Denial of Service (DoS) attacks.

DoS attacks leave authorized users unable to access information systems, devices, or other network resources due to the actions of a malicious cyber threat actor. When this occurs, the organization must operate at degraded capacity; often resulting in an inability to accomplish its mission.

To limit the impact of DoS attacks, organizations may choose to employ increased capacity and service redundancy, which has the potential to reduce systems' susceptibility to some DoS attacks. Managing excess capacity may include, for example, establishing selected usage priorities, quotas, or partitioning. Many operating systems can be integrated with enterprise-level firewalls and networking equipment that meet or exceed this requirement.

The technology does not support this requirement. This is an applicable-does not meet finding.

ID	os_limit_dos_attacks	
References	800-53r5	• SC-5(2)

13.6. Protect Against Denial of Service Attacks by Ensuring Rate-Limiting Measures on Network Interfaces

The macOS should be configured to prevent Denial of Service (DoS) attacks by enforcing rate-limiting measures on network interfaces.

DoS attacks leave authorized users unable to access information systems, devices, or other network resources due to the actions of a malicious cyber threat actor. When this occurs, the organization must operate at degraded capacity; often resulting in an inability to accomplish its mission.

To prevent DoS attacks by ensuring rate-limiting measures on network interfaces, many operating systems can be integrated with enterprise-level firewalls and networking equipment that meet or exceed this requirement.

The technology does not support this requirement. This is an applicable-does not meet finding.

ID	os_protect_dos_attacks	
References	800-53r5	• SC-5

13.7. Employ Automated Mechanisms for Account Management Functions

The organization should employ automated mechanisms to support the management of information system accounts.

The use of automated mechanisms prevents against human error and provide a faster and more efficient means of relaying time-sensitive information and account management.

To employ automated mechanisms for account management functions, many operating systems can be integrated with an enterprise-level directory service that meets or exceeds this requirement.

The technology does not support this requirement. This is an applicable-does not meet finding.

ID	os_provide_automated_account_management	
References	800-53r5	• AC-2(1)

13.8. Require Devices to Reauthenticate when Changing Authenticators

The macOS should be configured to require users to reauthenticate when the device authenticator is changed.

Without reauthentication, users may access resources or perform tasks for which they are not

authorization. When operating systems provide the capability to change device authenticators, it is critical the device reauthenticate.

The technology does not support this requirement. This is an applicable-does not meet finding.

ID	os_reauth_devices_change_authenticators	
References	800-53r5	<ul style="list-style-type: none">• IA-11

13.9. Secure Name Address Resolution Service

The information system requests and performs data origin authentication and data integrity verification on the name/address resolution responses the system receives from authoritative sources.



macOS supports encrypted DNS settings with the com.apple.dnsSettings.managed payload, however, the system must be integrated with a DNS server that supports encrypted DNS. <https://developer.apple.com/documentation/devicemanagement/dnssettings>

The technology does not support this requirement. This is an applicable-does not meet finding.

ID	os_secure_name_resolution	
References	800-53r5	<ul style="list-style-type: none">• SC-21

13.10. Disable Wi-Fi When Connected to Ethernet

The macOS should be configured to automatically disable Wi-Fi when connected to ethernet.

The use of Wi-Fi to connect to unauthorized networks may facilitate the exfiltration of mission data. Therefore, wireless networking capabilities internally embedded within information system components should be disabled when not intended to be used.



If the system requires Wi-Fi to connect to an authorized network, this is not applicable.

The technology does not support this requirement. This is an applicable-does not meet finding.

ID	system_settings_wifi_disable_when_connected_to_ethernet	
References	800-53r5	<ul style="list-style-type: none">• AC-18(1), AC-18(3)• AC-4

Chapter 14. Not Applicable

This section contains the controls that are defined in the NIST 800-53 revision 5 but are not applicable when configuring a macOS system.

14.1. Access Control for Mobile Devices

A mobile device is a computing device that has a small form factor such that it can easily be carried by a single individual; is designed to operate without a physical connection; possesses local, non-removable or removable data storage; and includes a self-contained power source. Mobile device functionality may also include voice communication capabilities, on-board sensors that allow the device to capture information, and/or built-in features for synchronizing local data with remote locations. Examples include smart phones and tablets. Mobile devices are typically associated with a single individual. The processing, storage, and transmission capability of the mobile device may be comparable to or merely a subset of notebook/desktop systems, depending on the nature and intended purpose of the device. Protection and control of mobile devices is behavior or policy-based and requires users to take physical action to protect and control such devices when outside of controlled areas. Controlled areas are spaces for which organizations provide physical or procedural controls to meet the requirements established for protecting information and systems.

Due to the large variety of mobile devices with different characteristics and capabilities, organizational restrictions may vary for the different classes or types of such devices. Usage restrictions and specific implementation guidance for mobile devices include configuration management, device identification and authentication, implementation of mandatory protective software, scanning devices for malicious code, updating virus protection software, scanning for critical software updates and patches, conducting primary operating system (and possibly other resident software) integrity checks, and disabling unnecessary hardware.

Usage restrictions and authorization to connect may vary among organizational systems. For example, the organization may authorize the connection of mobile devices to its network and impose a set of usage restrictions, while a system owner may withhold authorization for mobile device connection to specific applications or impose additional usage restrictions before allowing mobile device connections to a system.

The technology does not support this requirement. This is an applicable-does not meet finding.

ID	os_access_control_mobile_devices	
References	800-53r5	• AC-19

14.2. Configure the System to Uniquely Identify and Authenticate Non-Organizational Users

The information system uniquely identifies and authenticates non-organizational users (or processes acting on behalf of non-organizational users).

This requirement is NA for this technology.

ID	os_identify_non-org_users	
References	800-53r5	• IA-8

14.3. Information Input Validation

Check the validity of the following information inputs: organization-defined information inputs to the systems.

Checking the valid syntax and semantics of system inputs—including character set, length, numerical range, and acceptable values—verifies that inputs match specified definitions for format and content. For example, if the organization specifies that numerical values between 1-100 are the only acceptable inputs for a field in a given application, inputs of "387," "abc," or "%K%" are invalid inputs and are not accepted as input to the system. Valid inputs are likely to vary from field to field within a software application. Applications typically follow well-defined protocols that use structured messages (i.e., commands or queries) to communicate between software modules or system components. Structured messages can contain raw or unstructured data interspersed with metadata or control information. If software applications use attacker-supplied inputs to construct structured messages without properly encoding such messages, then the attacker could insert malicious commands or special characters that can cause the data to be interpreted as control information or metadata. Consequently, the module or component that receives the corrupted output will perform the wrong operations or otherwise interpret the data incorrectly. Prescreening inputs prior to passing them to interpreters prevents the content from being unintentionally interpreted as commands. Input validation ensures accurate and correct inputs and prevents attacks such as cross-site scripting and a variety of injection attacks.

This requirement is NA for this technology.

ID	os_information_validation	
References	800-53r5	• SI-10

14.4. Managed Access Control Points

Route remote accesses through authorized and managed network access control points.

Organizations consider the Trusted Internet Connections (TIC) initiative requirements for external network connections since limiting the number of access control points for remote access reduces attack surfaces.

This requirement is NA for this technology.

ID	os_managed_access_control_points	
References	800-53r5	• AC-17(3)

14.5. Non-Repudiation

Provide irrefutable evidence that an individual (or process acting on behalf of an individual) has performed organization-defined actions to be covered by non-repudiation.

Types of individual actions covered by non-repudiation include creating information, sending and receiving messages, and approving information. Non-repudiation protects against claims by authors of not having authored certain documents, senders of not having transmitted messages, receivers of not having received messages, and signatories of not having signed documents. Non-repudiation services can be used to determine if information originated from an individual or if an individual took specific actions (e.g., sending an email, signing a contract, approving a procurement request, or receiving specific information). Organizations obtain non-repudiation services by employing various techniques or mechanisms, including digital signatures and digital message receipts.

This requirement is NA for this technology.

ID	os_non_reputation	
References	800-53r5	• AU-10

14.6. Configure the System for Non-local Maintenance

Non-local maintenance and diagnostic activities are those activities conducted by individuals communicating through a network, either an external network or an internal network.

This requirement is NA for this technology.

ID	os_nonlocal_maintenance	
References	800-53r5	• MA-4

Chapter 15. Supplemental

This section provides additional information to support the guidance provided by the baselines.

15.1. Password Policy Supplemental

To comply with Executive Order 14028, “Improving the Nation’s Cybersecurity”, OMB M-22-09, “Moving the U.S. Government Toward Zero Trust Cybersecurity Principles”, and NIST SP-800-63b, “Digital Identity Guidelines: Authentication and Lifecycle Management” federal, military, and intelligence communities must adopt the following configuration settings:

- Password policies must not require the use of complexity policies such as upper characters, lower characters, or special characters.
- Password policies must also not require the use of regular rotation.

In accordance with these requirements, the following rules, while they remain on specific benchmarks, have been removed from any of the NIST 800-53r5 baselines as recommendations.

- pwpolicy_alpha_numeric_enforce
- pwpolicy_custom_regex_enforce
- pwpolicy_lower_case_character_enforce.yaml
- pwpolicy_max_lifetime_enforce
- pwpolicy_minimum_lifetime_enforce
- pwpolicy_prevent_dictionary_words
- pwpolicy_simple_sequence_disable
- pwpolicy_special_character_enforce
- pwpolicy_upper_case_character_enforce.yaml

If an organization has requirements to implement additional password policies, the remainder of this supplemental discusses the following password policy rules:

- pwpolicy_lower_case_character_enforce
- pwpolicy_upper_case_character_enforce
- pwpolicy_account_inactivity_enforce
- pwpolicy_minimum_lifetime_enforce

Password policies should be enforced as much as possible via Configuration Profiles. However, the following policies are currently not enforceable via Configuration Profiles, and must therefore be enabled using the `pwpolicy` command:

- Enforcing at least 1 lowercase character
- Enforcing at least 1 uppercase character
- Disabling an account after 35 days of inactivity

- Password minimum lifetime

To set the local policy to meet these requirements, save the following XML password policy to a file.

```

<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE plist PUBLIC "-//Apple//DTD PLIST 1.0//EN"
"http://www.apple.com/DTDs/PropertyList-1.0.dtd">
<plist version="1.0">
<dict>
  <key>policyCategoryAuthentication</key>
  <array>
    <dict>
      <key>policyContent</key>
      <string>policyAttributeLastAuthenticationTime &gt; policyAttributeCurrentTime
- (policyAttributeInactiveDays * 24 * 60 * 60)</string>
      <key>policyIdentifier</key>
      <string>Inactive Account</string>
      <key>policyParameters</key>
      <dict>
        <key>policyAttributeInactiveDays</key>
        <integer>35</integer>
      </dict>
    </dict>
  </array>
  <key>policyCategoryPasswordContent</key>
  <array>
    <dict>
      <key>policyContent</key>
      <string>policyAttributePassword matches '(.*[A-Z].*){1,}+'</string>
      <key>policyIdentifier</key>
      <string>Must have at least 1 uppercase letter</string>
      <key>policyParameters</key>
      <dict>
        <key>minimumAlphaCharactersUpperCase</key>
        <integer>1</integer>
      </dict>
    </dict>
  </array>
  <dict>
    <key>policyContent</key>
    <string>policyAttributePassword matches '(.*[a-z].*){1,}+'</string>
    <key>policyIdentifier</key>
    <string>Must have at least 1 lowercase letter</string>
    <key>policyParameters</key>
    <dict>
      <key>minimumAlphaCharactersLowerCase</key>
      <integer>1</integer>
    </dict>
  </dict>
  <dict>
    <key>policyContent</key>
  
```

```
<string>policyAttributeLastPasswordChangeTime &lt; policyAttributecurrentTime  
- (policyAttributeMinimumLifetimeHours * 60 * 60)</string>  
    <key>policyIdentifier</key>  
    <string>Minimum Password Lifetime</string>  
    <key>policyParameters</key>  
    <dict>  
        <key>policyAttributeMinimumLifetimeHours</key>  
        <integer>24</integer>  
    </dict>  
    </dict>  
    </array>  
  </dict>  
</plist>
```

Run the following command to load the new policy file, substituting the path to the file in place of "\$pwpolicy_file".

```
/usr/bin/pwpolicy setaccountpolicies $pwpolicy_file
```



If directory services is being utilized, password policies should come from the domain.



In order to apply any password policy, the `allowPasscodeModification` setting in `com.apple.applicationaccess` must not be set to `false`.