


Introduction to Algorithms

Lecture 4: Quicksort

Prof. Charles E. Leiserson and Prof. Erik Demaine
Massachusetts Institute of Technology

March 4, 2025

Introduction to Algorithms



Content has been extracted from *Introduction to Algorithms*, Fourth Edition, by Cormen, Leiserson, Rivest, and Stein. MIT Press. 2022.

Visit <https://mitpress.mit.edu/9780262046305/introduction-to-algorithms/>.

Original slides from *Introduction to Algorithms* 6.046J/18.401J, Fall 2005 Class by Prof. Charles Leiserson and Prof. Erik Demaine. MIT OpenCourseWare Initiative available at <https://ocw.mit.edu/courses/6-046j-introduction-to-algorithms-sma-5503-fall-2005/>.

Plan

Quicksort

Divide & Conquer

Partitioning

Worst-case Analysis

Intuition

Randomized Quicksort

Analysis

Quicksort

- ▶ Proposed by C.A.R. Hoare in 1962.
- ▶ Divide-and-conquer algorithm.
- ▶ Sorts ‘in place’ (like insertion sort, but not like merge sort).
- ▶ Very practical (with tuning).

Plan

Quicksort

Divide & Conquer

Partitioning

Worst-case Analysis

Intuition

Randomized Quicksort

Analysis

Divide and Conquer

Quicksort an n -element array:

1. **Divide:** Partition the array into two subarrays around a **pivot** x such that elements in lower subarray $\leq x \leq$ elements in upper subarray.



2. **Conquer:** Recursively sort the two subarrays.
3. **Combine:** Trivial.

Key:

Linear-time partitioning subroutine.

Plan

Quicksort

Divide & Conquer

Partitioning

Worst-case Analysis

Intuition

Randomized Quicksort


Analysis

Partitioning Subroutine


```
1: procedure PARTITION( $A, p, q$ )
2:    $x \leftarrow A[p]$ 
3:    $i \leftarrow p$ 
4:   for  $j \leftarrow p + 1$  to  $q$  do
5:     if  $A[j] \leq x$  then
6:        $i \leftarrow i + 1$ 
7:       exchange  $A[i] \leftrightarrow A[j]$ 
8:     end if
9:   end for
10:  exchange  $A[p] \leftrightarrow A[i]$ 
11:  return  $i$ 
12: end procedure
```

Running time:
 $O(n)$ for n elements.


Invariant:



Example of partitioning




Example of partitioning




Example of partitioning




Example of partitioning




Example of partitioning




Example of partitioning




Example of partitioning




Example of partitioning






Example of partitioning



Example of partitioning








Example of partitioning



i

→ j

Example of partitioning



i

Pseudocode for Quicksort

```
1: procedure QUICKSORT( $A, p, r$ )
2:   if  $p < r$  then
3:      $q \leftarrow \text{PARTITION}(A, p, r)$ 
4:     QUICKSORT( $A, p, q - 1$ )
5:     QUICKSORT( $A, q + 1, r$ )
6:   end if
7: end procedure
```

Initial call:

QUICKSORT($A, 1, n$)

Analysis of Quicksort

- ▶ Assume all input elements are distinct.
- ▶ In practice, there are better partitioning algorithms for when duplicate input elements may exist.
- ▶ Let $T(n) =$ worst-case running time on an array of n elements.

Plan

Quicksort

Divide & Conquer

Partitioning

Worst-case Analysis

Intuition

Randomized Quicksort

Analysis

Worst-case of Quicksort

- ▶ Input sorted or reverse sorted.
- ▶ Partition around min or max element.
- ▶ One side of partition always has no elements.

$$\begin{aligned}T(n) &= T(0) + T(n - 1) + \Theta(n) \\&= \Theta(1) + T(n - 1) + \Theta(n) \\&= T(n - 1) + \Theta(n) \\&= \Theta(n^2)\end{aligned}$$

Worst-case of Quicksort

- ▶ Input sorted or reverse sorted.
- ▶ Partition around min or max element.
- ▶ One side of partition always has no elements.

$$\begin{aligned}T(n) &= T(0) + T(n - 1) + \Theta(n) \\&= \Theta(1) + T(n - 1) + \Theta(n) \\&= T(n - 1) + \Theta(n) \\&= \Theta(n^2)\end{aligned}$$

Arithmetic Series!

Worst-case Recursion Tree

$$T(n) = T(0) + T(n - 1) + cn$$

Recurrence relation for worst-case recursion tree


Worst-case Recursion Tree

$$T(n) = T(0) + T(n - 1) + cn$$

$$T(n)$$


Worst-case Recursion Tree

$$T(n) = T(0) + T(n - 1) + cn$$




Worst-case Recursion Tree

$$T(n) = T(0) + T(n - 1) + cn$$




Worst-case Recursion Tree

$$T(n) = T(0) + T(n - 1) + cn$$




Worst-case Recursion Tree

$$T(n) = T(0) + T(n-1) + cn$$



Worst-case Recursion Tree

$$T(n) = T(0) + T(n-1) + cn$$



Plan

Quicksort

Divide & Conquer

Partitioning

Worst-case Analysis

Intuition

Randomized Quicksort

Analysis

Best-case Analysis

For intuition only!

If we're lucky, PARTITION splits the array evenly:

$$\begin{aligned} T(n) &= 2T\left(\frac{n}{2}\right) + \Theta(n) \\ &= \Theta(n \lg n) \quad (\text{same as merge-sort}) \end{aligned}$$

What if the split is always $\frac{1}{10} : \frac{9}{10}$?

$$T(n) = T\left(\frac{1}{10}n\right) + T\left(\frac{9}{10}n\right) + \Theta(n)$$

What is the solution to this recurrence?


Analysis of “Almost-best” Case

$$T(n)$$


Analysis of “Almost-best” Case

$$\begin{array}{c} cn \\ / \quad \backslash \\ T\left(\frac{1}{10}n\right) \quad T\left(\frac{9}{10}n\right) \end{array}$$


Analysis of “Almost-best” Case



Analysis of “Almost-best” Case



Analysis of “Almost-best” Case



More Intuition

Suppose we alternate lucky, unlucky, lucky, unlucky, lucky, ...

$$\begin{aligned} L(n) &= 2U\left(\frac{n}{2}\right) + \Theta(n) && \textcolor{red}{lucky} \\ U(n) &= L(n-1) + \Theta(n) && \textcolor{red}{unlucky} \end{aligned}$$

Solving:

$$\begin{aligned} L(n) &= 2 \left(L\left(\frac{n}{2} - 1\right) + \Theta\left(\frac{n}{2}\right) \right) + \Theta(n) \\ &= 2L\left(\frac{n}{2} - 1\right) + \Theta(n) \\ &= \Theta(n \lg n) && \textcolor{red}{Lucky!} \end{aligned}$$

How can we make sure we are usually lucky?

Plan

Quicksort

Divide & Conquer

Partitioning

Worst-case Analysis

Intuition

Randomized Quicksort

Analysis

Randomized Quicksort

IDEA:

Partition around a **random** element.

- ▶ Running time is independent of the input order.
- ▶ No assumptions need to be made about the input distribution.
- ▶ No specific input elicits the worst-case behavior.
- ▶ The worst case is determined only by the output of a random-number generator.

Plan

Quicksort

Divide & Conquer

Partitioning

Worst-case Analysis

Intuition

Randomized Quicksort

Analysis

Randomized Quicksort Analysis

Let $T(n) =$ the random variable for the running time of randomized quicksort on an input of size n , assuming random numbers are independent.

For $k = 0, 1, \dots, n - 1$, define the **indicator random variable**.

$$X_k = \begin{cases} 1 & \text{if PARTITION generates a } k : n - k - 1 \text{ split,} \\ 0 & \text{otherwise.} \end{cases}$$

$E[X_k] = \Pr\{X_k = 1\} = \frac{1}{n}$, since all splits are equally likely, assuming elements are distinct.

Analysis (Cont.)

$$T(n) = \begin{cases} T(0) + T(n-1) + \Theta(n) & \text{if } 0 : n-1 \text{ split,} \\ T(1) + T(n-2) + \Theta(n) & \text{if } 1 : n-2 \text{ split,} \\ \vdots \\ T(n-1) + T(0) + \Theta(n) & \text{if } n-1 : 0 \text{ split.} \end{cases}$$
$$= \sum_{k=0}^{n-1} X_k(T(k) + T(n-k-1) + \Theta(n))$$

Calculating expectation

Take expectations of both sides.

$$E[T(n)] = E \left[\sum_{k=0}^{n-1} X_k (T(k) + T(n-k-1) + \Theta(n)) \right]$$

Calculating expectation

Linearity of expectation.

$$\begin{aligned} E[T(n)] &= E \left[\sum_{k=0}^{n-1} X_k (T(k) + T(n-k-1) + \Theta(n)) \right] \\ &= \sum_{k=0}^{n-1} E [X_k (T(k) + T(n-k-1) + \Theta(n))] \end{aligned}$$

Calculating expectation

Independence of X_k from other random choices.

$$\begin{aligned} E[T(n)] &= E \left[\sum_{k=0}^{n-1} X_k(T(k) + T(n-k-1) + \Theta(n)) \right] \\ &= \sum_{k=0}^{n-1} E [X_k(T(k) + T(n-k-1) + \Theta(n))] \\ &= \sum_{k=0}^{n-1} E[X_k] \cdot E[T(k) + T(n-k-1) + \Theta(n)] \end{aligned}$$

Calculating expectation

Linearity of expectation: $E[X_k] = \frac{1}{n}$.

$$\begin{aligned} E[T(n)] &= E \left[\sum_{k=0}^{n-1} X_k (T(k) + T(n-k-1) + \Theta(n)) \right] \\ &= \sum_{k=0}^{n-1} E [X_k (T(k) + T(n-k-1) + \Theta(n))] \\ &= \sum_{k=0}^{n-1} E[X_k] \cdot E[T(k) + T(n-k-1) + \Theta(n)] \\ &= \frac{1}{n} \sum_{k=0}^{n-1} E[T(k)] + \frac{1}{n} \sum_{k=0}^{n-1} E[T(n-k-1)] + \frac{1}{n} \sum_{k=0}^{n-1} \Theta(n) \end{aligned}$$

Calculating expectation

Summations have identical terms.

$$\begin{aligned} E[T(n)] &= E \left[\sum_{k=0}^{n-1} X_k (T(k) + T(n-k-1) + \Theta(n)) \right] \\ &= \sum_{k=0}^{n-1} E [X_k (T(k) + T(n-k-1) + \Theta(n))] \\ &= \sum_{k=0}^{n-1} E[X_k] \cdot E[T(k) + T(n-k-1) + \Theta(n)] \\ &= \frac{1}{n} \sum_{k=0}^{n-1} E[T(k)] + \frac{1}{n} \sum_{k=0}^{n-1} E[T(n-k-1)] + \frac{1}{n} \sum_{k=0}^{n-1} \Theta(n) \\ &= \frac{2}{n} \sum_{k=0}^{n-1} E[T(k)] + \Theta(n) \end{aligned}$$

Hairy recurrence

$$E[T(n)] = \frac{2}{n} \sum_{k=2}^{n-1} E[T(k)] + \Theta(n)$$

(The $k = 0, 1$ terms can be absorbed in the $\Theta(n)$.)

Prove:

$$E[T(n)] \leq an \lg n \text{ for constant } a > 0.$$

- ▶ Choose a large enough so that $an \lg n$ dominates $E[T(n)]$ for sufficiently small $n \geq 2$.

Use fact:

$$\sum_{k=2}^{n-1} k \lg k \leq \frac{1}{2}n^2 \lg n - \frac{1}{8}n^2 \text{ (exercise).}$$

Substitution method

Substitute inductive hypothesis.

$$E[T(n)] \leq \frac{2}{n} \sum_{k=2}^{n-1} ak \lg k + \Theta(n)$$

Substitution method

Use fact.

$$\begin{aligned} E[T(n)] &\leq \frac{2}{n} \sum_{k=2}^{n-1} ak \lg k + \Theta(n) \\ &\leq \frac{2a}{n} \left(\frac{1}{2} n^2 \lg n - \frac{1}{8} n^2 \right) + \Theta(n) \end{aligned}$$

Substitution method

$$\begin{aligned} E[T(n)] &\leq \frac{2}{n} \sum_{k=2}^{n-1} ak \lg k + \Theta(n) \\ &\leq \frac{2a}{n} \left(\frac{1}{2} n^2 \lg n - \frac{1}{8} n^2 \right) + \Theta(n) \\ &= an \lg n - \left(\frac{an}{4} - \Theta(n) \right) \\ &\leq an \lg n, \end{aligned}$$

if a is chosen large enough so that

$\frac{an}{4}$ dominates the $\Theta(n)$.

Quicksort in practice

- ▶ Quicksort is a great general-purpose sorting algorithm.
- ▶ Quicksort is typically over twice as fast as merge sort.
- ▶ Quicksort can benefit substantially from **code tuning**.
- ▶ Quicksort behaves well even with caching and virtual memory.

End of Lecture 4.

TDT5FTOTTC



Top 5 Fundamental Takeaways

Top 5 Fundamental Takeaways

- 5 **Quicksort is a Divide-and-Conquer Algorithm** – It recursively partitions an array around a pivot and sorts the subarrays efficiently.

Top 5 Fundamental Takeaways

- 5 **Quicksort is a Divide-and-Conquer Algorithm** – It recursively partitions an array around a pivot and sorts the subarrays efficiently.
- 4 **Partitioning is the Core of Quicksort** – The partitioning step ensures elements are correctly placed around the pivot in $O(n)$ time.

Top 5 Fundamental Takeaways

- 5 **Quicksort is a Divide-and-Conquer Algorithm** – It recursively partitions an array around a pivot and sorts the subarrays efficiently.
- 4 **Partitioning is the Core of Quicksort** – The partitioning step ensures elements are correctly placed around the pivot in $O(n)$ time.
- 3 **Best-case and Worst-case Analysis** – Quicksort runs in $O(n \log n)$ in the best case but can degrade to $O(n^2)$ if poorly partitioned.


Top 5 Fundamental Takeaways

- 5 **Quicksort is a Divide-and-Conquer Algorithm** – It recursively partitions an array around a pivot and sorts the subarrays efficiently.
- 4 **Partitioning is the Core of Quicksort** – The partitioning step ensures elements are correctly placed around the pivot in $O(n)$ time.
- 3 **Best-case and Worst-case Analysis** – Quicksort runs in $O(n \log n)$ in the best case but can degrade to $O(n^2)$ if poorly partitioned.
- 2 **Randomized Quicksort Helps Avoid Worst-case Behavior** – Choosing a random pivot prevents consistently bad splits and ensures an expected $O(n \log n)$ runtime.

Top 5 Fundamental Takeaways

- 5 **Quicksort is a Divide-and-Conquer Algorithm** – It recursively partitions an array around a pivot and sorts the subarrays efficiently.
- 4 **Partitioning is the Core of Quicksort** – The partitioning step ensures elements are correctly placed around the pivot in $O(n)$ time.
- 3 **Best-case and Worst-case Analysis** – Quicksort runs in $O(n \log n)$ in the best case but can degrade to $O(n^2)$ if poorly partitioned.
- 2 **Randomized Quicksort Helps Avoid Worst-case Behavior** – Choosing a random pivot prevents consistently bad splits and ensures an expected $O(n \log n)$ runtime.
- 1 **Quicksort is Highly Efficient in Practice** – It outperforms merge sort in most cases and benefits from hardware optimizations.

Introduction to Algorithms



Content has been extracted from *Introduction to Algorithms*, Fourth Edition, by Cormen, Leiserson, Rivest, and Stein. MIT Press. 2022.

Visit <https://mitpress.mit.edu/9780262046305/introduction-to-algorithms/>.

Original slides from *Introduction to Algorithms* 6.046J/18.401J, Fall 2005 Class by Prof. Charles Leiserson and Prof. Erik Demaine. MIT OpenCourseWare Initiative available at <https://ocw.mit.edu/courses/6-046j-introduction-to-algorithms-sma-5503-fall-2005/>.