

Databases

Lab 02

Andrés Calderón, Ph.D.

February 14, 2025

1 Introduction

In the first part of the lab, we will practice some relational algebra expressions using the **radb** software with a simple sample database. To do so, we will explain how to install **radb** and demonstrate its basic usage. Then, we will go through a set of examples that implement relational algebra expressions to solve the proposed queries. Once you are familiar with this, you will be asked to solve a new set of queries on a different database.

Go ahead!

2 **radb** Tutorial

2.1 Verify Python Installation

Ensure that Python 3.5 or a later version is installed on your system. You can check your Python version by running:

```
python --version
```

If Python 3 is not the default version on your system, you may need to use **python3** instead.

```
python3 --version
```

If your system does not have Python installed, we recommend following this [tutorial](#) to install Miniconda, a minimal yet powerful Python distribution.

2.2 Install **radb**

Use **pip** to install the **radb** package. If **pip** is not associated with Python 3 on your system, use **pip3** instead.

```
pip install radb
```

Or, if necessary:

```
pip3 install radb
```

3 Set Up a Sample Database

To practice using **radb**, set up a sample database as follows:

- Download the [applications.db](#) file, which contains the sample database.
- Run the following command in a terminal console to start the **radb** interpreter with the sample database **applications.db**. First, navigate to the directory where the database is located:

```
radb applications.db
```

If your system cannot find the **radb** command, it might be installed in a directory that is not included in your system's **PATH**. On Linux, for example, it may be located in `~/local/bin/`. You can run it by specifying the full path:

```
~/local/bin/radb applications.db
```

Alternatively, you can add the directory to your **PATH** to avoid typing the full path each time. To find out where **pip** installed **radb**, run:

```
pip show -f radb
```

4 Run **radb** commands on the Sample Database

At the **ra>** prompt, you can execute commands such as:

- List all relations in the database. If everything is running correctly, you should see a list of three relations.

```
\list;
```

- Exit the **radb** interpreter:

```
\quit;
```

For more detailed information and additional commands, refer to the official **radb** documentation section **Advanced Use** at: <https://users.cs.duke.edu/~junyang/radb/advance.html>.

5 Practice Relational Algebra in a Sample Database

5.1 The Applications Database

The **applications.db** database is extremely simple and will help us understand the format of the relational algebra expressions covered in class, as well as how to use them in the **radb** software for practice.

The **applications.db** database contains dummy data about a group of students applying to different colleges or universities. It consists of only three relations and models the following attributes:

- student(sID, sName, GPA, sizeHS)
- college(cName, state, enrollment)
- apply(sID, cName, major, decision)

5.2 Relational algebra operations

5.2.1 Simplest relational algebra expresion

Let's list the content of the database. Go back to the `radb` interpreter, and when you see the `ra>` prompt again, type the name of each relation and see what happens.

```
student;
```

```
college;
```

```
apply;
```

How many tuples does each relation have?

5.2.2 Selection (σ)

The selection operation retrieves tuples from a relation that satisfy a specified condition.

Syntax:

```
\select_{condition} input_relation;
```

Examples:

- Students with GPA greater than 4.0.
- $\sigma_{GPA > 4.0} \text{ student}$.

```
\select_{GPA > 4.0} student;
```

- Students with GPA greater than 4.0 and the size of their high school greater than 2000.
- $\sigma_{GPA > 4.0 \wedge sizeHS > 2000} \text{ student}$.

```
\select_{GPA > 4.0 and sizeHS > 2000} student;
```

- Applications to the program of 'Sistemas' at the 'PUJ'.
- $\sigma_{major=Sistemas \wedge cName=PUJ} \text{ apply}$.

```
\select_{major = 'Sistemas' and cName = 'PUJ'} apply;
```

5.2.3 Projection (Π)

Projection creates a new relation by selecting specific attributes from an existing relation.

Syntax:

```
\project_{attr_list} input_relation;
```

Examples:

- Student ID and decision for all applications.
- $\Pi_{sID, decision} \text{ apply}$.

```
\project_{sID, decision} apply;
```

- ID and name of students with GPA greater than 3.5 (it is a composed query).
- $\Pi_{sID, sName} (\sigma_{GPA > 3.5} \text{ student})$.

```
\project_{sID, sName} ( \select_{GPA > 3.5} student );
```

5.2.4 Cartesian Product (\times)

Perform Cartesian product over the tuples of two relations.

Syntax:

```
input_relation_1 \cross input_relation_2;
```

Examples:

- Find the Cartesian product between the students and the applications.
- $\text{student} \times \text{apply}$.

```
student \cross apply;
```

- Name and GPA of students which applied to 'Sistemas'.
- $\Pi_{sName, GPA} (\sigma_{\text{student.sID}=\text{apply.sID} \wedge \text{major}=\text{Sistemas}} (\text{student} \times \text{apply}))$.

```
\project_{sName, GPA}( \select_{student.sID = apply.sID and major = 'Sistemas'}( student \cross apply ) );
```

5.2.5 Natural Join (\bowtie)

Natural join will automatically equate all pairs of identically named attributes from its inputs.

Syntax:

```
input_relation_1 \join input_relation_2;
```

Examples:

- Name and GPA of students which applied to ‘Sistemas’.
- $\Pi_{sName, GPA} (\sigma_{major=Sistemas} (student \bowtie apply))$.

```
\project_{sName, GPA}( \select_{major = 'Sistemas'}( student \join apply ) );
```

- Name, GPA, and college of students which applied to ‘Medicina’ at institutions with enrollment greater than 20000.
- $\Pi_{sName, GPA, cName} (\sigma_{major=Medicina \wedge enrollment > 20000} (student \bowtie apply \bowtie college))$.

```
\project_{sName, GPA, cName}(
  \select_{major = 'Medicina' and enrollment > 20000}(
    student \join ( apply \join college )
  )
);
```

Note that you can also use a multi-line format to write relational expressions. The expression will be evaluated only when the ; is entered.

5.2.6 Theta Join (\bowtie_{θ})

Theta join will equate pairs of attributes from its inputs based on a particular condition. It is particularly useful when the attributes in the relations to be joined have different names.

Syntax:

```
input_relation_1 \join_{cond} input_relation_2;
```

6 Independent Work

6.1 Beer Database

The `beer.db` database models drinkers, bars, beers, and drinking preferences among a group of people. The data model of the database is as follows:

- `bar(name, address)`
- `beer(name, brewer)`
- `drinker(name, address)`
- `frequents(drinker, bar, times_a_week)`
- `likes(drinker, beer)`
- `serves(bar, beer, price)`

You will use this database to practice additional relational algebra queries by following the Basic Use reference available in the `radb` documentation (<https://users.cs.duke.edu/~junyang/radb/basic.html>).

Your task is to connect to the `beer.db` database in the same way as with `applications.db` and follow the guide by running all the examples provided. Pay particular attention to the last three operations: Set union, difference, and intersection; Rename; and Aggregation and Grouping.

For each expression in the guide (those with a gray background), you will capture the results and present them in a well-formatted report, along with their corresponding relational algebra expressions.

6.2 Pizza Database

The `pizza.db` database has the following data model:

- `Person (name, age, gender)`
- `Frequents (name, pizzeria)`
- `Eats (name, pizza)`
- `Serves (pizzeria, pizza, price)`

You will use the `pizza.db` database to answer the following queries. For each query, you must provide the corresponding relational algebra expression and the `radb` code, along with your response.

1. Find the unique person who does not frequent pizzerias that sell supreme pizza.
2. Find the pizzerias and pizzas that are more expensive than those sold by Little Caesars.
3. How old is the only woman who eats pizza that costs less than \$7.75?
4. What is the most popular pizzeria among people between 20 and 30 years old?
5. What is the average age of men who eat pepperoni pizza?

Finally, you will propose your own query for the `pizza.db` database (just one). Based on the queries above, you will create a new query from scratch, write its corresponding relational algebra expression, and provide the `radb` code to answer it.

We expect you to submit a well-structured report in PDF format, containing the requested information outlined in Sections 6.1 and 6.2. Additionally, include the `radb` code with the answers to the queries in a ZIP file. The submission deadline is **February 28, 2025**.

Happy Hacking ☺!