

Towards Parallel Detection of Moving Flock Patterns in Large Spatio-temporal Datasets

Final report

Andres Calderon

December 8, 2016

1 Introduction

Spatio-temporal data is ubiquitous nowadays. Thanks to new technologies and location devices (such as Internet of Things, Remote Sensing, Smart phones, GPS, RFID, etc.), the collection of huge amount of spatio-temporal data is now possible. With the appearance of this datasets also appears the need of new techniques which allow the analysis and detection of useful patterns.

Applications for this kind of information are diverse and interesting, in particular if they come in the way of trajectory datasets [Jeung et al., 2011; Huang and Yuan, 2015]. Case of studies range from transportation system management [Di Lorenzo et al., 2016; Johansson and others, 2015] to Ecology [Johnston et al., 2015; La Sorte et al., 2016]. For instance, Turdukulov et al. [2014] explore the finding of complex motion patterns to discover similarities between tropical cyclone paths. Similarly, Amor et al. [2016] use eye trajectories to understand which strategies people use during a visual search. Also, Holland et al. [1999] track the behavior of tiger sharks in the coasts of Hawaii in order to understand their migration patterns.

Recently, there has been an increasing interest in exploiting more complex movement patterns in spatio-temporal datasets. Traditional range and nearest neighbor queries do not capture the collective behavior of moving objects. Moving cluster (Kalnis et al. [2005]), convoys (Jeung et al. [2008]) and flock patterns (Benkert et al. [2008]; Gudmundsson and van Kreveld [2006]) are new movement patterns which unveil how entities move together during a minimum time interval.

In particular, a moving flock pattern show how objects move close enough during a given period of time. A better understanding on how entities move in space is of special interest in areas such as sports (Iwase and Saito [2002]), surveillance and security (Makris

and Ellis [2002]; Piciarelli et al. [2005]), urban development (Huang et al. [2016]; Long and Thill [2015]) and socio-economic geography (Frank et al. [2000]).

Despite the fact that much more data become available, state-of-the-art techniques to mine complex movement patterns still depict low scalability and poor performance in big spatial data. The present work aims to find an initial solution to implement a parallel method to discover moving flock patterns in large spatio-temporal datasets. It is thought that new trends in distributed in-memory framework for spatial operations could help to speed up the detection of this kind of patterns.

The following section will state the related work in the area. Section 3 will explain the details of the implementation of the proposed solution while section 4 will present their experimental results. Finally, section 5 will discuss some conclusions and future work.

2 Related work

Recently increase use of location-aware devices (such as GPS, Smart-phones and RFID tags) has allowed the collection of a vast amount of data with a spatial component linked to them. Different studies have focused in analyzing and mining this kind of collections [Leung, 2010; Miller and Han, 2001]. In this area, trajectory datasets have emerged as an interesting field where diverse kind of patterns can be identified [Zheng and Zhou, 2011; Vieira and Tsotras, 2013]. For instance, authors have proposed techniques to discover motion spatial patterns such as moving clusters [Kalnis et al., 2005], convoys [Jeung et al., 2008] and flocks [Benkert et al., 2008; Gudmundsson and van Kreveld, 2006]. In particular, Vieira et al. [2009] proposed BFE (Basic Flock Evaluation), a novel algorithm to find moving flock patterns in polynomial time over large spatio-temporal datasets.

A flock pattern is defined as a group of entities which move together for a defined lapse of time [Benkert et al., 2008]. Applications to this kind of patterns are rich and diverse. For example, [Calderon, 2011] finds moving flock patterns in iceberg trajectories to understand their movement behavior and how they related to changes in ocean's currents.

The algorithm proposed by [Vieira et al., 2009] presents an initial strategy in order to detect flock patterns. In that, first they find disks with a predefined diameter where moving entities could be close enough at a given time interval. This is a costly operation due to the large number of points and intervals to be analyzed ($\mathcal{O}(2n^2)$ per time interval). The technique uses a grid-based index and a stencil (see figure 1) to speed up the process, but the complexity is still high.

Calderon [2011] and Turdukulov et al. [2014] use a frequent pattern mining approach to improve performance during the combination of disks between time intervals. Similarly, Tanaka et al. [2016] introduce the use of plane sweeping along with binary signatures and inverted indexes to speedup the same process. However, the above-mentioned methods still keep the same strategy as BFE to find the disks at each interval.

[Arimura et al., 2014] and [Geng et al., 2014] use depth-first algorithms to analyze




Figure 1: Grid-based index used in Vieira et al. [2009].

the time intervals of each trajectory to report maximal duration flocks. However, these techniques are not suitable to find patterns in an on-line fashion.

Given the high complexity of the task, it should not be surprising the use of parallelism to increase performance. Fort et al. [2014] use extremal and intersection sets to report maximal, longest and largest flocks on the GPU with the limitations of its memory model.

Indeed, despite the popularity of cluster computing frameworks (in particular those supporting spatial capabilities [Eldawy, 2014; Yu et al., 2016; Hughes et al., 2015; Xie et al., 2016]) there are not significant advances in this area. At the best of our knowledge, this work is the first to explore in-memory distributed systems towards the detection of moving flock patterns.

3 Parallelizing flock detection

Given that the finding of disks at each time interval is one of the most costly operations towards the detection of moving flock patterns, the main goal of this work is to implement a parallel method to detect that set of disks. In order to do that, we will use the spatial operations offered by Simba [Xie et al., 2016], a distributed in-memory spatial analytics engine based on Apache Spark. This section explains the details of the algorithm implemented in Simba and how some spatial predicates introduced by it can leverage the finding of disks.

3.1 Spatial operation on Simba

Simba (Spatial In-Memory Big data Analytics) extends the Spark SQL engine to provide rich spatial operations through both SQL and the DataFrame API. Besides, it introduces two-layer spatial indexing and cost-based optimizations to support efficient spatial queries. Simba is open source and public available at the project homepage¹.

¹<http://www.cs.utah.edu/~dongx/simba/>

```

SELECT
    *
FROM
    points p1
DISTANCE JOIN
    points p2
ON
    POINT(p2.x, p2.y) IN CIRCLERANGE(POINT(p1.x, p1.y),  $\varepsilon$ )
WHERE
    p1.id < p2.id

```

Figure 2: SQL statement on Simba to find points lying inside an ε distance.

In particular, `DISTANCE JOIN` and `CIRCLERANGE` operators were used in order to find groups of points lying close enough each other. The algorithm uses a user-defined distance (ε) to define the diameter of the disk. Figure 2 shows the SQL statement used to find pairs of points inside an ε .

4 Experiments

5 Conclusions and future work

References

- Tatiana A. Amor, Saulo D. S. Reis, Daniel Campos, Hans J. Herrmann, and José S. Andrade. Persistence in eye movement during visual search. *Scientific Reports*, 6: 20815, February 2016. ISSN 2045-2322. doi: 10.1038/srep20815. 00002.
- Hiroki Arimura, Takuya Takagi, Xiaoliang Geng, and Takeaki Uno. Finding All Maximal Duration Flock Patterns in High-dimensional Trajectories. 00004, 2014.
- Marc Benkert, Joachim Gudmundsson, Florian Hübner, and Thomas Wolle. Reporting flock patterns. *Computational Geometry*, 41(3):111–125, November 2008. ISSN 09257721. doi: 10.1016/j.comgeo.2007.10.003. 00148.
- Andres Calderon. Mining moving flock patterns in large spatio-temporal datasets using a frequent pattern mining approach. Master’s thesis, University of Twente, 2011. 00020.
- G. Di Lorenzo, M. Sbodio, F. Calabrese, M. Berlingerio, F. Pinelli, and R. Nair. Al-lAboard: Visual Exploration of Cellphone Mobility Data to Optimise Public Transport. *IEEE Transactions on Visualization and Computer Graphics*, 22(2):1036–1050, February 2016. ISSN 1077-2626. doi: 10.1109/TVCG.2015.2440259. 00004.

- Ahmed Eldawy. SpatialHadoop: Towards flexible and scalable spatial processing using mapreduce. pages 46–50. ACM Press, 2014. ISBN 978-1-4503-2924-8. doi: 10.1145/2602622.2602625. 00020.
- Marta Fort, J. Antoni Sellares, and Nacho Valladares. A parallel GPU-based approach for reporting flock patterns. *International Journal of Geographical Information Science*, 28(9):1877–1903, September 2014. ISSN 1365-8816, 1362-3087. doi: 10.1080/13658816.2014.902949. 00002.
- Andrew Frank, Jonathan Raper, and J. P. Cheylan, editors. *Life and Motion of Socio-Economic Units*. CRC Press, London ; New York, 1 edition edition, December 2000. ISBN 978-0-7484-0845-0. 00071.
- Xiaoliang Geng, Takuya Takagi, Hiroki Arimura, and Takeaki Uno. Enumeration of complete set of flock patterns in trajectories. pages 53–61. ACM Press, 2014. ISBN 978-1-4503-3139-5. doi: 10.1145/2676552.2676560. 00004.
- Joachim Gudmundsson and Marc van Kreveld. Computing Longest Duration Flocks in Trajectory Data. In *Proceedings of the 14th Annual ACM International Symposium on Advances in Geographic Information Systems*, GIS ’06, pages 35–42, New York, NY, USA, 2006. ACM. ISBN 1-59593-529-0. doi: 10.1145/1183471.1183479. 00210.
- K. N. Holland, B. M. Wetherbee, C. G. Lowe, and C. G. Meyer. Movements of tiger sharks (*Galeocerdo cuvier*) in coastal Hawaiian waters. *Marine Biology*, 134(4):665–673, 1999. 00165.
- Pengtao Huang and Bo Yuan. Mining Massive-Scale Spatiotemporal Trajectories in Parallel: A Survey. In *Trends and Applications in Knowledge Discovery and Data Mining*, volume 9441 of *Lecture Notes in Computer Science*. Springer International Publishing, Cham, 2015. ISBN 978-3-319-25659-7 978-3-319-25660-3. 00001.
- Xiaoke Huang, Ye Zhao, Chao Ma, Jing Yang, Xinyue Ye, and Chong Zhang. TrajGraph: A Graph-Based Visual Analytics Approach to Studying Urban Network Centralities Using Taxi Trajectory Data. *IEEE Transactions on Visualization and Computer Graphics*, 22(1):160–169, January 2016. ISSN 1077-2626. doi: 10.1109/TVCG.2015.2467771. 00012.
- James N. Hughes, Andrew Annex, Christopher N. Eichelberger, Anthony Fox, Andrew Hulbert, and Michael Ronquest. GeoMesa: A distributed architecture for spatio-temporal fusion. page 94730F, May 2015. doi: 10.1117/12.2177233. 00000.
- Sachiko Iwase and Hideo Saito. Tracking Soccer Player Using Multiple Views. In *MVA*, pages 102–105, 2002. 00030.
- Hoyoung Jeung, Man Lung Yiu, Xiaofang Zhou, Christian S. Jensen, and Heng Tao Shen. Discovery of Convoys in Trajectory Databases. *Proc. VLDB Endow.*, 1(1):1068–1080, August 2008. ISSN 2150-8097. doi: 10.14778/1453856.1453971. 00306.

- Hoyoung Jeung, Man Lung Yiu, and Christian S. Jensen. Trajectory pattern mining. In *Computing with Spatial Trajectories*, pages 143–177. Springer, 2011. 00038.
- Karl Henrik Johansson and others. An efficiency measure for road transportation networks with application to two case studies. In *2015 54th IEEE Conference on Decision and Control (CDC)*, pages 5149–5155. IEEE, 2015. 00002.
- Alison Johnston, Daniel Fink, Mark D. Reynolds, Wesley M. Hochachka, Brian L. Sullivan, Nicholas E. Bruns, Eric Hallstein, Matt S. Merrifield, Sandi Matsumoto, and Steve Kelling. Abundance models improve spatial and temporal prioritization of conservation resources. *Ecological Applications*, 25(7):1749–1756, 2015. 00007.
- Panos Kalnis, Nikos Mamoulis, and Spiridon Bakiras. On Discovering Moving Clusters in Spatio-temporal Data. In Claudia Bauzer Medeiros, Max J. Egenhofer, and Elisa Bertino, editors, *Advances in Spatial and Temporal Databases*, Lecture Notes in Computer Science, pages 364–381. Springer Berlin Heidelberg, August 2005. ISBN 978-3-540-28127-6 978-3-540-31904-7. doi: 10.1007/11535331_21. 00351.
- Frank A. La Sorte, Daniel Fink, Wesley M. Hochachka, and Steve Kelling. Convergence of broad-scale migration strategies in terrestrial birds. *Proceedings of the Royal Society B: Biological Sciences*, 283(1823):20152588, January 2016. ISSN 0962-8452, 1471-2954. doi: 10.1098/rspb.2015.2588. 00010.
- Yee Leung. *Knowledge Discovery in Spatial Data*. Springer Science & Business Media, March 2010. ISBN 978-3-642-02664-5. 00032.
- Ying Long and Jean-Claude Thill. Combining smart card data and household travel survey to analyze jobs–housing relationships in Beijing. *Computers, Environment and Urban Systems*, 53:19–35, September 2015. ISSN 0198-9715. doi: 10.1016/j.compenvurbsys.2015.02.005. 00026.
- Dimitrios Makris and Tim Ellis. Path detection in video surveillance. *Image and Vision Computing*, 20(12):895–903, October 2002. ISSN 0262-8856. doi: 10.1016/S0262-8856(02)00098-7. 00165.
- Harvey J. Miller and Jiawei Han. *Geographic Data Mining and Knowledge Discovery*. Taylor & Francis, Inc., Bristol, PA, USA, 2001. ISBN 0-415-23369-0. 00763.
- C. Piciarelli, G. L. Foresti, and L. Snidaro. Trajectory clustering and its applications for video surveillance. In *IEEE Conference on Advanced Video and Signal Based Surveillance, 2005.*, pages 40–45, September 2005. doi: 10.1109/AVSS.2005.1577240. 00092.
- Pedro Sena Tanaka, Marcos R. Vieira, and Daniel S. Kaster. An Improved Base Algorithm for Online Discovery of Flock Patterns in Trajectories. *Journal of Information and Data Management*, 7(1):52, 2016. 00000.

- Ulanbek Turdukulov, Andres Oswaldo Calderon Romero, Otto Huisman, and Vasilios Retsios. Visual mining of moving flock patterns in large spatio-temporal data sets using a frequent pattern approach. *International Journal of Geographical Information Science*, 28(10):2013–2029, October 2014. ISSN 1365-8816. doi: 10.1080/13658816.2014.889834. 00013.
- Marcos R. Vieira and Vassilis Tsotras. *Spatio-Temporal Databases: Complex Motion Pattern Queries*. Springer Science & Business Media, October 2013. ISBN 978-3-319-02408-0. 00005.
- Marcos R. Vieira, Petko Bakalov, and Vassilis J. Tsotras. On-line Discovery of Flock Patterns in Spatio-temporal Data. In *Proceedings of the 17th ACM SIGSPATIAL International Conference on Advances in Geographic Information Systems, GIS '09*, pages 286–295, New York, NY, USA, 2009. ACM. ISBN 978-1-60558-649-6. doi: 10.1145/1653771.1653812. 00107.
- Dong Xie, Feifei Li, Bin Yao, Gefei Li, Liang Zhou, and Minyi Guo. Simba: Efficient In-Memory Spatial Analytics. pages 1071–1085. ACM Press, 2016. ISBN 978-1-4503-3531-7. doi: 10.1145/2882903.2915237. 00006.
- J. Yu, J. Wu, and M. Sarwat. A demonstration of GeoSpark: A cluster computing framework for processing big spatial data. In *2016 IEEE 32nd International Conference on Data Engineering (ICDE)*, pages 1410–1413, May 2016. doi: 10.1109/ICDE.2016.7498357. 00002.
- Yu Zheng and Xiaofang Zhou. *Computing with Spatial Trajectories*. Springer Science & Business Media, October 2011. ISBN 978-1-4614-1629-6. 00297.