

Scalable Overlay Operations over DCEL Polygon Layers

Andres Oswaldo Calderon Romero

University of California, Riverside

November 2024

Introduction

- ▶ Spatial data structures, especially DCEL, are essential for various spatial applications.
- ▶ Doubly Connected Edge List (DCEL) helps manage topological information of edges, vertices, and faces.
- ▶ Overlay operations enable integration of different spatial data layers.
- ▶ This work addresses scalability challenges for overlay computations over DCEL layers.

Motivation and Problem Statement

- ▶ Large spatial datasets (e.g., US census tracts) make traditional DCEL overlay operations challenging.
- ▶ Need for scalable, distributed DCEL overlay solutions.
- ▶ Objectives:
 - ▶ Efficient partitioning and merging for scalable DCEL overlays.
 - ▶ Enable parallel overlay operations while maintaining data integrity.

Related Work

- ▶ Historical use of DCEL in various applications (e.g., computational geometry, 3D graphics).
- ▶ Existing sequential algorithms for overlay operations: LEDA, CGAL.
- ▶ Need for scalable, parallel approaches in spatial data processing.

DCEL Overview

- ▶ DCEL consists of vertices, edges (half-edges), and faces.
- ▶ Each half-edge has references to twin, next, and previous edges.
- ▶ Allows efficient topological and geometric queries.




Figure: DCEL Structure

Scalable Overlay Construction

- ▶ Partition Strategy: Quadtree-based partitioning to manage large datasets.
- ▶ Each cell in the quadtree can be processed independently.
- ▶ Local results merged to form global overlay.




Figure: Partitioning Strategy for Overlay Computation

Handling Orphan Cells and Holes

- ▶ Problem: Holes or faces spanning multiple cells require special handling.
- ▶ Solution: Label propagation using quadtree structure.
- ▶ Recursive search for label consistency across partitions.

Optimization Strategies

- ▶ Optimization for Faces Spanning Multiple Cells
 - ▶ Intermediate reduce phase to handle large number of faces.
 - ▶ Spatial proximity property to minimize central node workload.
- ▶ Optimization for Unbalanced Layers
 - ▶ Focused scanning of dense layers to improve performance.

Experimental Evaluation

- ▶ Datasets: MainUS, GADM, CCT
- ▶ Evaluation metrics: Runtime, scalability, efficiency.
- ▶ Comparison with baseline approaches like CGAL.

Results and Observations

- ▶ Partitioning improves overlay operation efficiency.
- ▶ Optimizations reduce computation time, especially in unbalanced datasets.
- ▶ Scalable solution performs significantly better on large datasets than sequential methods.

Conclusions

- ▶ Developed a scalable overlay computation for DCEL layers.
- ▶ Approach supports distributed, efficient DCEL operations.
- ▶ Future work: Further improvements in handling extremely dense data.