

Операционные системы

Анализ файловой структуры UNIX. Команды для работы с файлами и каталогами

Дургарян Аделина Ованесовна

31 мая 2025

Российский университет дружбы народов, Москва, Россия

Цели и задачи работы

Ознакомление с файловой системой Linux, её структурой, именами и содержанием каталогов. Приобретение практических навыков по применению команд для работы с файлами и каталогами, по управлению процессами, по проверке использования диска и обслуживанию файловой системы.

- 1 Выполнить приимеры
- 2 Выполнить дествия по работе с каталогами и файлами
- 3 Выполнить действия с правами доступа
- 4 Получить дополнительные сведения при помощи справки по командам.

Процесс выполнения лабораторной работы

```
aodurgaryan@aodurgaryan:~$ cd
aodurgaryan@aodurgaryan:~$ touch abc1
aodurgaryan@aodurgaryan:~$ cp abc1 april
aodurgaryan@aodurgaryan:~$ cp abc1 may
aodurgaryan@aodurgaryan:~$ mkdir monthly
aodurgaryan@aodurgaryan:~$ cp april may monthly/
aodurgaryan@aodurgaryan:~$ cp monthly/may monthly/june
aodurgaryan@aodurgaryan:~$ ls monthly/
april  june  may
aodurgaryan@aodurgaryan:~$ mkdir monthly.00
aodurgaryan@aodurgaryan:~$ cp -r monthly monthly.00/
aodurgaryan@aodurgaryan:~$ cp monthly.00/ /tmp
cp: не указан -r; пропускается каталог 'monthly.00/'
aodurgaryan@aodurgaryan:~$ cp -r monthly.00/ /tmp
aodurgaryan@aodurgaryan:~$
```

Рис. 1: Выполнение примеров

```
aodurgaryan@aodurgaryan:~$ cd
aodurgaryan@aodurgaryan:~$ mv april july
aodurgaryan@aodurgaryan:~$ mv july monthly.00/
aodurgaryan@aodurgaryan:~$ ls monthly.00/
july  monthly
aodurgaryan@aodurgaryan:~$ mv monthly.00/ monthly.01
aodurgaryan@aodurgaryan:~$ mkdir reports
aodurgaryan@aodurgaryan:~$ mv monthly.01/ reports/
aodurgaryan@aodurgaryan:~$ mv reports/monthly.01/ reports/monthly
aodurgaryan@aodurgaryan:~$
```

Рис. 2: Выполнение примеров

Выполнение примеров

```
aodurgaryan@aodurgaryan:~$ cd
aodurgaryan@aodurgaryan:~$ touch may
aodurgaryan@aodurgaryan:~$ ls -l may
-rw-r--r--. 1 aodurgaryan aodurgaryan 0 мая 31 11:29 may
aodurgaryan@aodurgaryan:~$ chmod u+x may
aodurgaryan@aodurgaryan:~$ ls -l may
-rwxr--r--. 1 aodurgaryan aodurgaryan 0 мая 31 11:29 may
aodurgaryan@aodurgaryan:~$ chmod u-x may
aodurgaryan@aodurgaryan:~$ ls -l may
-rw-r--r--. 1 aodurgaryan aodurgaryan 0 мая 31 11:29 may
aodurgaryan@aodurgaryan:~$ cd
aodurgaryan@aodurgaryan:~$ chmod g-r,o-r monthly/
aodurgaryan@aodurgaryan:~$ touch abc1
aodurgaryan@aodurgaryan:~$ chmod g+w abc1
aodurgaryan@aodurgaryan:~$
```

Рис. 3: Выполнение примеров

Создание директорий и копирование файлов

```
aodurgaryan@aodurgaryan:~$  
aodurgaryan@aodurgaryan:~$ cp /usr/include/linux/sysinfo.h ~  
aodurgaryan@aodurgaryan:~$ mv sysinfo.h equipment  
aodurgaryan@aodurgaryan:~$ mkdir ski.plases  
aodurgaryan@aodurgaryan:~$ mv equipment ski.plases/  
aodurgaryan@aodurgaryan:~$ mv ski.plases/equipment ski.plases/equiplist  
aodurgaryan@aodurgaryan:~$ touch abc1  
aodurgaryan@aodurgaryan:~$ cp abc1 ski.plases/equiplist2  
aodurgaryan@aodurgaryan:~$ cd ski.plases/  
aodurgaryan@aodurgaryan:~/ski.plases$ mkdir equipment  
aodurgaryan@aodurgaryan:~/ski.plases$ mv equiplist equipment/  
aodurgaryan@aodurgaryan:~/ski.plases$ mv equiplist2 equipment/  
aodurgaryan@aodurgaryan:~/ski.plases$ cd  
aodurgaryan@aodurgaryan:~$  
aodurgaryan@aodurgaryan:~$ mkdir newdir  
aodurgaryan@aodurgaryan:~$ mv newdir ski.plases/  
aodurgaryan@aodurgaryan:~$ mv ski.plases/newdir/ ski.plases/plans  
aodurgaryan@aodurgaryan:~$
```

Рис. 4: Работа с каталогами

Работа с командой chmod

```
aodurgaryan@aodurgaryan:~$ mkdir australia play
aodurgaryan@aodurgaryan:~$ touch my_os feathers
aodurgaryan@aodurgaryan:~$ chmod 744 australia/
aodurgaryan@aodurgaryan:~$ chmod 711 play/
aodurgaryan@aodurgaryan:~$ chmod 544 my_os
aodurgaryan@aodurgaryan:~$ chmod 664 feathers
aodurgaryan@aodurgaryan:~$ ls -l
итого 0
-rw-rw-r--. 1 aodurgaryan aodurgaryan  0 мая 31 11:31 abc1
drwxr--r--. 1 aodurgaryan aodurgaryan  0 мая 31 11:32 australia
-rw-rw-r--. 1 aodurgaryan aodurgaryan  0 мая 31 11:32 feathers
drwxr-xr-x. 1 aodurgaryan aodurgaryan 74 мая 31 10:46 git-extended
-rw-r--r--. 1 aodurgaryan aodurgaryan  0 мая 31 11:29 may
drwx--x--x. 1 aodurgaryan aodurgaryan 24 мая 31 11:24 monthly
-r-xr--r--. 1 aodurgaryan aodurgaryan  0 мая 31 11:32 my_os
drwx--x--x. 1 aodurgaryan aodurgaryan  0 мая 31 11:32 play
drwxr-xr-x. 1 aodurgaryan aodurgaryan 14 мая 31 11:28 reports
drwxr-xr-x. 1 aodurgaryan aodurgaryan 28 мая 31 11:32 ski.places
drwxr-xr-x. 1 aodurgaryan aodurgaryan 10 мая 31 10:23 work
drwxr-xr-x. 1 aodurgaryan aodurgaryan  0 мая 31 10:13 Видео
drwxr-xr-x. 1 aodurgaryan aodurgaryan  0 мая 31 10:13 Документы
drwxr-xr-x. 1 aodurgaryan aodurgaryan  0 мая 31 10:28 Загрузки
drwxr-xr-x. 1 aodurgaryan aodurgaryan  0 мая 31 10:13 Изображения
drwxr-xr-x. 1 aodurgaryan aodurgaryan  0 мая 31 10:13 Музыка
drwxr-xr-x. 1 aodurgaryan aodurgaryan  0 мая 31 10:13 Общедоступные
drwxr-xr-x. 1 aodurgaryan aodurgaryan  0 мая 31 10:13 'Рабочий стол'
drwxr-xr-x. 1 aodurgaryan aodurgaryan  0 мая 31 10:13 Шаблоны
aodurgaryan@aodurgaryan:~$
```




```
root:x:0:0:Super User:/root:/bin/bash
bin:x:1:1:bin:/bin:/usr/sbin/nologin
daemon:x:2:2:daemon:/sbin:/usr/sbin/nologin
adm:x:3:4:adm:/var/adm:/usr/sbin/nologin
lp:x:4:7:lp:/var/spool/lpd:/usr/sbin/nologin
sync:x:5:0:sync:/sbin:/bin/sync
shutdown:x:6:0:shutdown:/sbin:/sbin/shutdown
halt:x:7:0:halt:/sbin:/sbin/halt
mail:x:8:12:mail:/var/spool/mail:/usr/sbin/nologin
operator:x:11:0:operator:/root:/usr/sbin/nologin
games:x:12:100:games:/usr/games:/usr/sbin/nologin
ftp:x:14:50:FTP User:/var/ftp:/usr/sbin/nologin
nobody:x:65534:65534:Kernel Overflow User:/usr/sbin/nologin
dbus:x:81:81:System Message Bus:/usr/sbin/nologin
apache:x:48:48:Apache:/usr/share/httpd:/sbin/nologin
tss:x:59:59:Account used for TPM access:/usr/sbin/nologin
avahi:x:70:70:Avahi mDNS/DNS-SD Stack:/var/run/avahi-daemon:/sbin/nologin
geoclue:x:999:999>User for geoclue:/var/lib/geoclue:/sbin/nologin
usbmuxd:x:113:113:usbmuxd user:/sbin/nologin
systemd-oom:x:998:998:systemd Userspace OOM Killer:/usr/sbin/nologin
qemu:x:107:107:qemu user:/sbin/nologin
polkitd:x:114:114>User for polkitd:/sbin/nologin
rtkit:x:172:172:RealtimeKit:/sbin/nologin
chrony:x:997:994:chrony system user:/var/lib/chrony:/sbin/nologin
dnsmasq:x:996:993:Dnsmasq DHCP and DNS server:/var/lib/dnsmasq:/usr/sbin/nologin
gluster:x:995:992:GlusterFS daemons:/run/gluster:/sbin/nologin
rpc:x:32:32:Rpcbind Daemon:/var/lib/rpcbind:/sbin/nologin
pipewire:x:994:991:PipeWire System Daemon:/run/pipewire:/usr/sbin/nologin
unbound:x:993:990:Unbound DNS resolver:/var/lib/unbound:/sbin/nologin
```

Работа с файлами и правами доступа

```
aodurgaryan@aodurgaryan:~$  
aodurgaryan@aodurgaryan:~$ cp feathers file.old  
aodurgaryan@aodurgaryan:~$ mv file.old play/  
aodurgaryan@aodurgaryan:~$ mkdir fun  
aodurgaryan@aodurgaryan:~$ cp -R play/ fun/  
aodurgaryan@aodurgaryan:~$ mv fun/ play/games  
aodurgaryan@aodurgaryan:~$  
aodurgaryan@aodurgaryan:~$ chmod u-r feathers  
aodurgaryan@aodurgaryan:~$ cat feathers  
cat: feathers: Отказано в доступе  
aodurgaryan@aodurgaryan:~$ cp feathers feathers2  
cp: невозможно открыть 'feathers' для чтения: Отказано в доступе  
aodurgaryan@aodurgaryan:~$ chmod u+r feathers  
aodurgaryan@aodurgaryan:~$ chmod u-x play/  
aodurgaryan@aodurgaryan:~$ cd play/  
bash: cd: play/: Отказано в доступе  
aodurgaryan@aodurgaryan:~$ chmod +x play/  
aodurgaryan@aodurgaryan:~$
```

Рис. 7: Работа с файлами и правами доступа



```
aodurgaryan@aodurgaryan:~ — man mount

MOUNT(8)                                System Administration                                MOUNT(8)

NAME
    mount - mount a filesystem

SYNOPSIS
    mount [-h|-V]

    mount [-l] [-t fstype]

    mount -a [-ffnrsvw] [-t fstype] [-O optlist]

    mount [-fnrsvw] [-o options] device|mountpoint

    mount [-fnrsvw] [-t fstype] [-o options] device mountpoint

    mount --bind|--rbind|--move olddir newdir


    mount --make-[shared|slave|private|unbindable|rshared|rslave|rprivate|runbindable] mountpoint

DESCRIPTION
    All files accessible in a Unix system are arranged in one big tree, the file hierarchy, rooted at /.
    These files can be spread out over several devices. The mount command serves to attach the filesystem
    found on some device to the big file tree. Conversely, the umount(8) command will detach it again. The
    filesystem is used to control how data is stored on the device or provided in a virtual way by network
    or other services.

    The standard form of the mount command is:

        mount -t type device dir

    This tells the kernel to attach the filesystem found on device (which is of type type) at the directory
    Manual page mount(8) line 1 (press h for help or q to quit)
```



```
aodurgaryan@aodurgaryan:~ — man fsck
FSCK(8)                                     System Administration                                     FSCK(8)

NAME
    fsck - check and repair a Linux filesystem

SYNOPSIS
    fsck [-lsAVRTMNP] [-r [fd]] [-C [fd]] [-t fstype] [filesystem...] [--] [fs-specific-options]

DESCRIPTION
    fsck is used to check and optionally repair one or more Linux filesystems. filesystem can be a device
    name (e.g., /dev/hdc1, /dev/sdb2), a mount point (e.g., /, /usr, /home), or a filesystem label or UUID
    specifier (e.g., UUID=8868abf6-88c5-4a83-98b8-bfc24057f7bd or LABEL=root). Normally, the fsck program
    will try to handle filesystems on different physical disk drives in parallel to reduce the total amount
    of time needed to check all of them.

    If no filesystems are specified on the command line, and the -A option is not specified, fsck will
    default to checking filesystems in /etc/fstab serially. This is equivalent to the -As options.

    The exit status returned by fsck is the sum of the following conditions:

    0
        No errors


    1
        Filesystem errors corrected

    2
        System should be rebooted

    4
        Filesystem errors left uncorrected

Manual page fsck(8) line 1 (press h for help or q to quit)
```

Рис. 9: Команда fsck



```
aodurgaryan@aodurgaryan:~ — man mkfs
MKFS(8)                                     System Administration                                     MKFS(8)

NAME
    mkfs - build a Linux filesystem

SYNOPSIS
    mkfs [options] [-t type] [fs-options] device [size]

DESCRIPTION
    This mkfs frontend is deprecated in favour of filesystem specific mkfs.<type> utils.

    mkfs is used to build a Linux filesystem on a device, usually a hard disk partition. The device argument is either the device name (e.g., /dev/hda1, /dev/sdb2), or a regular file that shall contain the filesystem. The size argument is the number of blocks to be used for the filesystem.

    The exit status returned by mkfs is 0 on success and 1 on failure.

    In actuality, mkfs is simply a front-end for the various filesystem builders (mkfs,fs<type>) available under Linux. The filesystem-specific builder is searched for via your PATH environment setting only. Please see the filesystem-specific builder manual pages for further details.


OPTIONS
    -t, --type type
        Specify the type of filesystem to be built. If not specified, the default filesystem type (currently ext2) is used.

    fs-options
        Filesystem-specific options to be passed to the real filesystem builder.

    -V, --verbose
        Produce verbose output, including all filesystem-specific commands that are executed. Specifying this option more than once inhibits execution of any filesystem-specific commands. This is really

Manual page mkfs(8) line 1 (press h for help or q to quit)
```

Рис. 10: Команда mkfs



```
aodurgaryan@aodurgaryan:~ — man kill
KILL(1)                                User Commands                                KILL(1)

NAME
    kill - terminate a process

SYNOPSIS
    kill [-signal|-s signal|-p] [-q value] [-a] [--timeout milliseconds signal] [--] pid|name...

    kill -l [number] | -L

DESCRIPTION
    The command kill sends the specified signal to the specified processes or process groups.

    If no signal is specified, the TERM signal is sent. The default action for this signal is to terminate the process. This signal should be used in preference to the KILL signal (number 9), since a process may install a handler for the TERM signal in order to perform clean-up steps before terminating in an orderly fashion. If a process does not terminate after a TERM signal has been sent, then the KILL signal may be used; be aware that the latter signal cannot be caught, and so does not give the target process the opportunity to perform any clean-up before terminating.

    Most modern shells have a builtin kill command, with a usage rather similar to that of the command described here. The --all, --pid, and --queue options, and the possibility to specify processes by command name, are local extensions.

    If signal is 0, then no actual signal is sent, but error checking is still performed.

ARGUMENTS
    The list of processes to be signaled can be a mixture of names and PIDs.

    pid
        Each pid can be expressed in one of the following ways:
```

Manual page kill(1) line 1 (press h for help or q to quit)

Выводы по проделанной работе

В ходе данной работы мы ознакомились с файловой системой Linux, её структурой, именами и содержанием каталогов. Научились совершать базовые операции с файлами, управлять правами их доступа для пользователя и групп. Ознакомились с Анализом файловой системы. А также получили базовые навыки по проверке использования диска и обслуживанию файловой системы.