

Boyer–Moore string-search algorithm

Anders Søberg <andersob@ifi.uio.no>

Martin Mihle Nygaard <martimn@ifi.uio.no>

IN4120 2022 Science Fair



Boyer–Moore string-search [1]

Programming G. Manacher, S.L. Graham
Toolmakers Editors

A Fast String Searching Algorithm

Robert S. Boyer
Stanford Research Institute
J Strother Moore
Xerox Palo Alto Research Center

An algorithm is presented that searches for the location, y_i , of the first occurrence of a character string, "pat", in another string, "text". During the search operation, the characters of pat are matched starting with the last character of pat. The information gained by starting the match at the end of the pattern often allows the algorithm to proceed in large jumps through the text being searched. Thus the algorithm has the unusual property that, in most cases, not all of the first i characters of string are inspected. The number of characters actually inspected (on the average) decreases as a function of the length of pat. For a random English pattern of length 5, the algorithm will typically inspect 1/4 characters of string before finding a match at i . Furthermore, the algorithm has been implemented so that (on the average) fewer than $i + 1$ pointer machine instructions are executed. These conclusions are supported with empirical evidence and a theoretical analysis of the average behavior of the algorithm. The worst case behavior of the algorithm is linear in $i + 1$ pointer, assuming the availability of array space for tables linear in pointer plus the size of the alphabet.

Key Words and Phrases: bibliographic search, computational complexity, information retrieval, linear time heuristics, pattern matching, text editing
CR Categories: 3.74, 4.40, 5.28

Copyright © 1977, Association for Computing Machinery, Inc. General permission is granted to reproduce this work for personal or internal reference use, not for general distribution, for advertising or promotional purposes, for creating new collective works, or for resale. This work was partially supported by ONR Contract N0001-42-0-400-0001, U.S. Navy, and the Computer Research Laboratory, Xerox Palo Alto Research Center, Palo Alto, CA 94304, where this work was done. The authors address a Copyright Science Laboratory, 181 International, Menlo Park, CA 94025.

562

1. Introduction

Suppose that pat is a string of length p and we wish to find the position i of the leftmost character in the first occurrence of pat in some string string :

```
pat:      AT-TAT  
string: ... MUCH-FIDELITY-SACRE...AT-TAT-POPE...  
i:      0
```

The obvious search algorithm considers each character position of string and determines whether the successive pattern characters of string starting at that position match the successive pattern characters of pat. Knuth, Morris, and Pratt [4] have observed that this algorithm is quadratic. That is, in the worst case, the number of comparisons is on the order of $i \times p$ pointer.

Knuth, Morris, and Pratt have described a linear search algorithm which preprocesses pat in time linear in p pointer. In particular, their algorithm inspects each of the first $i \times p$ pointer - 1 characters of string precisely once.

We now present a search algorithm which is usually "simpler": It may not inspect each of the first $i \times p$ pointer - 1 characters of string. By "usually simpler" we mean that the expected value of the number of inspected characters is using is $i + 1$ pointer, where $i < 1$ and gets smaller as p increases. There are patterns and strings for which worse behavior is exhibited. However, Knuth, in [5], has shown that the algorithm is linear even in the worst case.

The actual number of characters inspected depends on statistical properties of the characters in pat and string. However, since the number of characters inspected on the average decreases as p increases, our algorithm actually speeds up on larger patterns.

Furthermore, the algorithm is suitable to another sense: It has been implemented so that on the average it requires the execution of fewer $i + 1$ pointer machine instructions per search.

The organization of this paper is as follows: In the next two sections we give an informal description of the algorithm and show an example of its use. We then define the algorithm precisely and discuss its efficient implementation. After this discussion we present the results of a thorough test of a particular machine code implementation of our algorithm. We compare these results to similar results for the Knuth, Morris, and Pratt algorithm and the simple search algorithm. Following this empirical evidence is a theoretical analysis which accurately predicts the performance material. Next we describe some situations in which it may not be advantageous to use our algorithm. We conclude with a discussion of the history of our algorithm.

The specific nature of the algorithm appears when initial authors of this paper were studying the performance of various string-searching algorithms on English text. This simple algorithm is presented as a $i \times p$ pointer and therefore applicable to most applications.

Communications
of the ACM

October 1977
Volume 28
Number 10

Proposition: Naïve string-search

Brute-force all alignments of a pattern P in text T .

Proposition: Naïve string-search

Brute-force all alignments of a pattern P in text T .

Example

$T = \text{"EKSEMPEL"}$ and $P = \text{"EMP"}$ gives
 $n - m + 1 = 6$ alignments to try (where
 n and m is the length of T and P)

Proposition: Naïve string-search

Brute-force all alignments of a pattern P in text T .

Example

$T = \text{"EKSEMPEL"}$ and $P = \text{"EMP"}$ gives
 $n - m + 1 = 6$ alignments to try (where
 n and m is the length of T and P)

E K S E M P E L

Proposition: Naïve string-search

Brute-force all alignments of a pattern P in text T .

Example

$T = \text{"EKSEMPEL"}$ and $P = \text{"EMP"}$ gives
 $n - m + 1 = 6$ alignments to try (where
 n and m is the length of T and P)

E	K	S	E	M	P	E	L
E	M	P	-	-	-	-	-

Proposition: Naïve string-search

Brute-force all alignments of a pattern P in text T .

Example

$T = \text{"EKSEMPEL"}$ and $P = \text{"EMP"}$ gives
 $n - m + 1 = 6$ alignments to try (where
 n and m is the length of T and P)

E	K	S	E	M	P	E	L
E	M	P	-	-	-	-	-
-	E	M	P	-	-	-	-

Proposition: Naïve string-search

Brute-force all alignments of a pattern P in text T .

Example

$T = \text{"EKSEMPEL"}$ and $P = \text{"EMP"}$ gives
 $n - m + 1 = 6$ alignments to try (where
 n and m is the length of T and P)

E	K	S	E	M	P	E	L
E	M	P	-	-	-	-	-
-	E	M	P	-	-	-	-
-	-	E	M	P	-	-	-

Proposition: Naïve string-search

Brute-force all alignments of a pattern P in text T .

Example

$T = \text{"EKSEMPEL"}$ and $P = \text{"EMP"}$ gives
 $n - m + 1 = 6$ alignments to try (where
 n and m is the length of T and P)

E	K	S	E	M	P	E	L
E	M	P	-	-	-	-	-
-	E	M	P	-	-	-	-
-	-	E	M	P	-	-	-
-	-	-	E	M	P	-	-

Proposition: Naïve string-search

Brute-force all alignments of a pattern P in text T .

Example

$T = \text{"EKSEMPEL"}$ and $P = \text{"EMP"}$ gives
 $n - m + 1 = 6$ alignments to try (where
 n and m is the length of T and P)

E	K	S	E	M	P	E	L
E	M	P	-	-	-	-	-
-	E	M	P	-	-	-	-
-	-	E	M	P	-	-	-
-	-	-	E	M	P	-	-
-	-	-	-	E	M	P	-

Proposition: Naïve string-search

Brute-force all alignments of a pattern P in text T .

Example

$T = \text{"EKSEMPEL"}$ and $P = \text{"EMP"}$ gives
 $n - m + 1 = 6$ alignments to try (where
 n and m is the length of T and P)

E	K	S	E	M	P	E	L
E	M	P	-	-	-	-	-
-	E	M	P	-	-	-	-
-	-	E	M	P	-	-	-
-	-	-	E	M	P	-	-
-	-	-	-	E	M	P	-
-	-	-	-	-	E	M	P

Improvement

Skip as many alignments as possible.

Improvement

Skip as many alignments as possible.

Idea

- ▶ Compare the **last aligned characters** in P to T , and shift along T based on result.

Improvement

Skip as many alignments as possible.

Idea

- ▶ Compare the **last aligned characters** in P to T , and shift along T based on result.
- ▶ Length of shift based on characters and suffixes of P .

Improvement

Skip as many alignments as possible.

Idea

- ▶ Compare the **last aligned characters** in P to T , and shift along T based on result.
- ▶ Length of shift based on characters and suffixes of P .
- ▶ Do some preprocessing of P .

Shift rules

The bad character rule (δ_1)

Shift rules

The bad character rule (δ_1)

If aligned character $\in P$:

- Shift P so that next occurrence of the character is aligned.

E	K	S	E	M	P	E	L
S	E	M	P	-	-	-	-
-	-	S	E	M	P	-	-

Shift rules

The bad character rule (δ_1)

If aligned character $\in P$:

- ▶ Shift P so that next occurrence of the character is aligned.

E	K	S	E	M	P	E	L
S	E	M	P	-	-	-	-
-	-	S	E	M	P	-	-

Else, aligned character $\notin P$:

- ▶ Shift P by it's own length, m .

E	K	S	E	M	P	E	L
E	M	P	-	-	-	-	-
-	-	-	E	M	P	-	-

Shift rules

The good suffix rule (δ_2)

Suppose for an alignment, S and P shares a suffix t .

- ▶ If a copy of t exists in P , shift to it. (Case 1)

Shift rules

The good suffix rule (δ_2)

Suppose for an alignment, S and P shares a suffix t .

- If a copy of t exists in P , shift to it. (Case 1)

Example

... FLÅKLYPA-GRAND-PRIX-SUFFIX-SUFFIX ...

Case 1: FIX-SUFFIX

Shift rules

The good suffix rule (delta_2)

Suppose for an alignment, S and P shares a suffix t .

- If a copy of t exists in P , shift to it. (Case 1)

Example

... FLÅKLYPA-GRAND-PRIX-SUFFIX-SUFFIX ...

Case 1:

FIX-SUFFIX

FIX-SUFFIX

Shift rules

The good suffix rule (δ_2)

Suppose for an alignment, S and P shares a suffix t .

- ▶ If a copy of t exists in P , shift to it. (Case 1)
- ▶ Else if, a prefix of P matches a suffix of t , shift to it. (Case 2)

Example

... FLÅKLYPA-GRAND-PRIX-SUF**FIX**-SUFFIX ...

Case 1: FIX-SUFFIX

Case 2: **FIX**-SUFFIX

Shift rules

The good suffix rule (δ_2)

Suppose for an alignment, S and P shares a suffix t .

- ▶ If a copy of t exists in P , shift to it. (Case 1)
- ▶ Else if, a prefix of P matches a suffix of t , shift to it. (Case 2)

Example

... FLÅKLYPA-GRAND-PRIX-SUFFIX-SUFFIX ...

Case 1: FIX-SUFFIX

Case 2: FIX-SUFFIX

FIX-SUFFIX

Shift rules

The good suffix rule (delta_2)

Suppose for an alignment, S and P shares a suffix t .

- ▶ If a copy of t exists in P , shift to it. (Case 1)
- ▶ Else if, a prefix of P matches a suffix of t , shift to it. (Case 2)
- ▶ Else, shift P past t .

Example

... FLÅKLYPA-GRAND-PRIX-SUFFIX-SUFFIX ...

Case 1: FIX-SUFFIX

Case 2: FIX-SUFFIX

 FIX-SUFFIX

Shift rules

The Galil rule [2]

- ▶ Proposed by Galil in 1979.
- ▶ Improvement by making the comparisons faster.
- ▶ Speeds up multi-matching, with *periodic* patterns.
- ▶ Improves worst cases significantly.

Shift rules

The Galil rule [2]

- ▶ Proposed by Galil in 1979.
- ▶ Improvement by making the comparisons faster.
- ▶ Speeds up multi-matching, with *periodic* patterns.
- ▶ Improves worst cases significantly.

Example

$T = \text{"KEBABABA"}$ and $P = \text{"BABA"}$, without and with Galil rule.

Shift rules

The Galil rule [2]

- ▶ Proposed by Galil in 1979.
- ▶ Improvement by making the comparisons faster.
- ▶ Speeds up multi-matching, with *periodic* patterns.
- ▶ Improves worst cases significantly.

Example

$T = \text{"KEBABABA"}$ and $P = \text{"BABA"}$, **without** and with Galil rule.

↓

K	E	B	A	B	A	B	A
B	A	B	A	-	-	-	-

Shift rules

The Galil rule [2]

- ▶ Proposed by Galil in 1979.
- ▶ Improvement by making the comparisons faster.
- ▶ Speeds up multi-matching, with *periodic* patterns.
- ▶ Improves worst cases significantly.

Example

$T = \text{"KEBABABA"}$ and $P = \text{"BABA"}$, **without** and with Galil rule.

		↓	↓				
K	E	B	A	B	A	B	A
B	A	B	A	-	-	-	-

Shift rules

The Galil rule [2]

- ▶ Proposed by Galil in 1979.
- ▶ Improvement by making the comparisons faster.
- ▶ Speeds up multi-matching, with *periodic* patterns.
- ▶ Improves worst cases significantly.

Example

$T = \text{"KEBABABA"}$ and $P = \text{"BABA"}$, **without** and with Galil rule.

	↓	↓	↓				
K	E	B	A	B	A	B	A
B	A	B	A	-	-	-	-

Shift rules

The Galil rule [2]

- ▶ Proposed by Galil in 1979.
- ▶ Improvement by making the comparisons faster.
- ▶ Speeds up multi-matching, with *periodic* patterns.
- ▶ Improves worst cases significantly.

Example

$T = \text{"KEBABABA"}$ and $P = \text{"BABA"}$, **without** and with Galil rule.

	↓	↓	↓		↓		
K	E	B	A	B	A	B	A
B	A	B	A	-	-	-	-
-	-	B	A	B	A	-	-

Shift rules

The Galil rule [2]

- ▶ Proposed by Galil in 1979.
- ▶ Improvement by making the comparisons faster.
- ▶ Speeds up multi-matching, with *periodic* patterns.
- ▶ Improves worst cases significantly.

Example

$T = \text{"KEBABABA"}$ and $P = \text{"BABA"}$, **without** and with Galil rule.

	↓	↓	↓	↓	↓		
K	E	B	A	B	A	B	A
B	A	B	A	-	-	-	-
-	-	B	A	B	A	-	-

Shift rules

The Galil rule [2]

- ▶ Proposed by Galil in 1979.
- ▶ Improvement by making the comparisons faster.
- ▶ Speeds up multi-matching, with *periodic* patterns.
- ▶ Improves worst cases significantly.

Example

$T = \text{"KEBABABA"}$ and $P = \text{"BABA"}$, **without** and with Galil rule.

↓

↓	↓	↓	↓	↓			
K	E	B	A	B	A	B	A
B	A	B	A	-	-	-	-
-	-	B	A	B	A	-	-

Shift rules

The Galil rule [2]

- ▶ Proposed by Galil in 1979.
- ▶ Improvement by making the comparisons faster.
- ▶ Speeds up multi-matching, with *periodic* patterns.
- ▶ Improves worst cases significantly.

Example

$T = \text{"KEBABABA"}$ and $P = \text{"BABA"}$, **without** and with Galil rule.

		↓	↓				
	↓	↓	↓	↓	↓		
K	E	B	A	B	A	B	A
B	A	B	A	-	-	-	-
-	-	B	A	B	A	-	-

Shift rules

The Galil rule [2]

- ▶ Proposed by Galil in 1979.
- ▶ Improvement by making the comparisons faster.
- ▶ Speeds up multi-matching, with *periodic* patterns.
- ▶ Improves worst cases significantly.

Example

$T = \text{"KEBABABA"}$ and $P = \text{"BABA"}$, **without** and with Galil rule.

		↓	↓				
	↓	↓	↓	↓	↓		↓
K	E	B	A	B	A	B	A
B	A	B	A	-	-	-	-
-	-	B	A	B	A	-	-
-	-	-	-	B	A	B	A

Shift rules

The Galil rule [2]

- ▶ Proposed by Galil in 1979.
- ▶ Improvement by making the comparisons faster.
- ▶ Speeds up multi-matching, with *periodic* patterns.
- ▶ Improves worst cases significantly.

Example

$T = \text{"KEBABABA"}$ and $P = \text{"BABA"}$, **without** and with Galil rule.

		↓	↓				
	↓	↓	↓	↓	↓	↓	↓
K	E	B	A	B	A	B	A
B	A	B	A	-	-	-	-
-	-	B	A	B	A	-	-
-	-	-	-	B	A	B	A

Shift rules

The Galil rule [2]

- ▶ Proposed by Galil in 1979.
- ▶ Improvement by making the comparisons faster.
- ▶ Speeds up multi-matching, with *periodic* patterns.
- ▶ Improves worst cases significantly.

Example

$T = \text{"KEBABABA"}$ and $P = \text{"BABA"}$, **without** and with Galil rule.

		↓	↓		↓		
	↓	↓	↓	↓	↓	↓	↓
K	E	B	A	B	A	B	A
B	A	B	A	-	-	-	-
-	-	B	A	B	A	-	-
-	-	-	-	B	A	B	A

Shift rules

The Galil rule [2]

- ▶ Proposed by Galil in 1979.
- ▶ Improvement by making the comparisons faster.
- ▶ Speeds up multi-matching, with *periodic* patterns.
- ▶ Improves worst cases significantly.

Example

$T = \text{"KEBABABA"}$ and $P = \text{"BABA"}$, **without** and with Galil rule.

		↓	↓	↓	↓		
	↓	↓	↓	↓	↓	↓	↓
K	E	B	A	B	A	B	A
B	A	B	A	-	-	-	-
-	-	B	A	B	A	-	-
-	-	-	-	B	A	B	A

11 comps.

Shift rules

The Galil rule [2]

- ▶ Proposed by Galil in 1979.
- ▶ Improvement by making the comparisons faster.
- ▶ Speeds up multi-matching, with *periodic* patterns.
- ▶ Improves worst cases significantly.

Example

$T = \text{"KEBABABA"}$ and $P = \text{"BABA"}$, without and **with** Galil rule.

↓ ↓ ↓ ↓
↓ ↓ ↓ ↓ ↓ ↓ ↓
K E B A B A B A
B A B A - - - -
- - B A B A - -
- - - - B A B A
11 comps.

↓
K E B A B A B A
B A B A - - - -

Shift rules

The Galil rule [2]

- ▶ Proposed by Galil in 1979.
- ▶ Improvement by making the comparisons faster.
- ▶ Speeds up multi-matching, with *periodic* patterns.
- ▶ Improves worst cases significantly.

Example

$T = \text{"KEBABABA"}$ and $P = \text{"BABA"}$, without and **with** Galil rule.

	↓	↓	↓	↓			
	↓	↓	↓	↓	↓	↓	↓
K	E	B	A	B	A	B	A
B	A	B	A	-	-	-	-
-	-	B	A	B	A	-	-
-	-	-	-	B	A	B	A

11 comps.

			↓	↓			
K	E	B	A	B	A	B	A
B	A	B	A	-	-	-	-

Shift rules

The Galil rule [2]

- ▶ Proposed by Galil in 1979.
- ▶ Improvement by making the comparisons faster.
- ▶ Speeds up multi-matching, with *periodic* patterns.
- ▶ Improves worst cases significantly.

Example

$T = \text{"KEBABABA"}$ and $P = \text{"BABA"}$, without and **with** Galil rule.

	↓	↓	↓	↓			
	↓	↓	↓	↓	↓	↓	↓
K	E	B	A	B	A	B	A
B	A	B	A	-	-	-	-
-	-	B	A	B	A	-	-
-	-	-	-	B	A	B	A

11 comps.

			↓	↓	↓		
K	E	B	A	B	A	B	A
B	A	B	A	-	-	-	-

Shift rules

The Galil rule [2]

- ▶ Proposed by Galil in 1979.
- ▶ Improvement by making the comparisons faster.
- ▶ Speeds up multi-matching, with *periodic* patterns.
- ▶ Improves worst cases significantly.

Example

$T = \text{"KEBABABA"}$ and $P = \text{"BABA"}$, without and **with** Galil rule.

	↓	↓	↓	↓			
	↓	↓	↓	↓	↓	↓	↓
K	E	B	A	B	A	B	A
B	A	B	A	-	-	-	-
-	-	B	A	B	A	-	-
-	-	-	-	B	A	B	A

11 comps.

			↓	↓	↓		↓
K	E	B	A	B	A	B	A
B	A	B	A	-	-	-	-
-	-	B	A	B	A	-	-

Shift rules

The Galil rule [2]

- ▶ Proposed by Galil in 1979.
- ▶ Improvement by making the comparisons faster.
- ▶ Speeds up multi-matching, with *periodic* patterns.
- ▶ Improves worst cases significantly.

Example

$T = \text{"KEBABABA"}$ and $P = \text{"BABA"}$, without and **with** Galil rule.

	↓	↓	↓	↓			
	↓	↓	↓	↓	↓	↓	↓
K	E	B	A	B	A	B	A
B	A	B	A	-	-	-	-
-	-	B	A	B	A	-	-
-	-	-	-	B	A	B	A

11 comps.

	↓	↓	↓	↓	↓		
K	E	B	A	B	A	B	A
B	A	B	A	-	-	-	-
-	-	B	A	B	A	-	-

Shift rules

The Galil rule [2]

- ▶ Proposed by Galil in 1979.
- ▶ Improvement by making the comparisons faster.
- ▶ Speeds up multi-matching, with *periodic* patterns.
- ▶ Improves worst cases significantly.

Example

$T = \text{"KEBABABA"}$ and $P = \text{"BABA"}$, without and **with** Galil rule.

		↓	↓	↓	↓		
	↓	↓	↓	↓	↓	↓	↓
K	E	B	A	B	A	B	A
B	A	B	A	-	-	-	-
-	-	B	A	B	A	-	-
-	-	-	-	B	A	B	A

11 comps.

				↓			
		↓	↓	↓	↓	↓	
K	E	B	A	B	A	B	A
B	A	B	A	-	-	-	-
-	-	B	A	B	A	-	-

Shift rules

The Galil rule [2]

- ▶ Proposed by Galil in 1979.
- ▶ Improvement by making the comparisons faster.
- ▶ Speeds up multi-matching, with *periodic* patterns.
- ▶ Improves worst cases significantly.

Example

$T = \text{"KEBABABA"}$ and $P = \text{"BABA"}$, without and **with** Galil rule.

	↓	↓	↓	↓			
	↓	↓	↓	↓	↓	↓	
K	E	B	A	B	A	B	A
B	A	B	A	-	-	-	-
-	-	B	A	B	A	-	-
-	-	-	-	B	A	B	A

11 comps.

		↓	↓				
		↓	↓	↓	↓	↓	
K	E	B	A	B	A	B	A
B	A	B	A	-	-	-	-
-	-	B	A	B	A	-	-

Shift rules

The Galil rule [2]

- ▶ Proposed by Galil in 1979.
- ▶ Improvement by making the comparisons faster.
- ▶ Speeds up multi-matching, with *periodic* patterns.
- ▶ Improves worst cases significantly.

Example

$T = \text{"KEBABABA"}$ and $P = \text{"BABA"}$, without and **with** Galil rule.

	↓	↓	↓	↓			
	↓	↓	↓	↓	↓	↓	↓
K	E	B	A	B	A	B	A
B	A	B	A	-	-	-	-
-	-	B	A	B	A	-	-
-	-	-	-	B	A	B	A

11 comps.

		↓	↓				
		↓	↓	↓	↓	↓	↓
K	E	B	A	B	A	B	A
B	A	B	A	-	-	-	-
-	-	B	A	B	A	-	-
-	-	-	-	B	A	B	A

Shift rules

The Galil rule [2]

- ▶ Proposed by Galil in 1979.
- ▶ Improvement by making the comparisons faster.
- ▶ Speeds up multi-matching, with *periodic* patterns.
- ▶ Improves worst cases significantly.

Example

$T = \text{"KEBABABA"}$ and $P = \text{"BABA"}$, without and **with** Galil rule.

		↓	↓	↓	↓		
	↓	↓	↓	↓	↓	↓	↓
K	E	B	A	B	A	B	A
B	A	B	A	-	-	-	-
-	-	B	A	B	A	-	-
-	-	-	-	B	A	B	A

11 comps.

		↓	↓				
	↓	↓	↓	↓	↓	↓	↓
K	E	B	A	B	A	B	A
B	A	B	A	-	-	-	-
-	-	B	A	B	A	-	-
-	-	-	-	B	A	B	A

9 comps.

Performance

- ▶ Best case performance is $O(n/m)$

Performance

- ▶ Best case performance is $O(n/m)$
 - ▶ When you can skip m elements at every step

Performance

- ▶ Best case performance is $O(n/m)$
 - ▶ When you can skip m elements at every step
- ▶ Worst case – two cases

Performance

- ▶ Best case performance is $O(n/m)$
 - ▶ When you can skip m elements at every step
- ▶ Worst case – two cases
 - ▶ If the pattern does not appear in the text, the worst case is $O(m + n)$

Performance

- ▶ Best case performance is $O(n/m)$
 - ▶ When you can skip m elements at every step
- ▶ Worst case – two cases
 - ▶ If the pattern does not appear in the text, the worst case is $O(m + n)$
 - ▶ Proven in “Fast Pattern Matching in Strings”

Performance

- ▶ Worst case for the original algorithm when the pattern does appear in the text is $O(mn)$.

Performance

- ▶ Worst case for the original algorithm when the pattern does appear in the text is $O(mn)$.
- ▶ This can be seen by considering the case where the pattern and text both contain the same letter repeatedly:

Performance

- ▶ Worst case for the original algorithm when the pattern does appear in the text is $O(mn)$.
- ▶ This can be seen by considering the case where the pattern and text both contain the same letter repeatedly:

A	A	A	A	A	A	A	A
A	A	A	-	-	-	-	-

Performance

- ▶ Worst case for the original algorithm when the pattern does appear in the text is $O(mn)$.
- ▶ This can be seen by considering the case where the pattern and text both contain the same letter repeatedly:

A	A	A	A	A	A	A	A
A	A	A	-	-	-	-	-

Performance

- ▶ Worst case for the original algorithm when the pattern does appear in the text is $O(mn)$.
- ▶ This can be seen by considering the case where the pattern and text both contain the same letter repeatedly:

A	A	A	A	A	A	A	A
A	A	A	-	-	-	-	-

Performance

- ▶ Worst case for the original algorithm when the pattern does appear in the text is $O(mn)$.
- ▶ This can be seen by considering the case where the pattern and text both contain the same letter repeatedly:

A	A	A	A	A	A	A	A
A	A	A	-	-	-	-	-

Performance

- ▶ Worst case for the original algorithm when the pattern does appear in the text is $O(mn)$.
- ▶ This can be seen by considering the case where the pattern and text both contain the same letter repeatedly:

A	A	A	A	A	A	A	A
A	A	A	-	-	-	-	-
-	A	A	A	-	-	-	-

Performance

- ▶ Worst case for the original algorithm when the pattern does appear in the text is $O(mn)$.
- ▶ This can be seen by considering the case where the pattern and text both contain the same letter repeatedly:

A	A	A	A	A	A	A	A
A	A	A	-	-	-	-	-
-	A	A	A	-	-	-	-
-	-	A	A	A	-	-	-

Performance

- ▶ Worst case for the original algorithm when the pattern does appear in the text is $O(mn)$.
- ▶ This can be seen by considering the case where the pattern and text both contain the same letter repeatedly:

A	A	A	A	A	A	A	A
A	A	A	-	-	-	-	-
-	A	A	A	-	-	-	-
-	-	A	A	A	-	-	-
-	-	-	A	A	A	-	-

Performance

- ▶ Worst case for the original algorithm when the pattern does appear in the text is $O(mn)$.
- ▶ This can be seen by considering the case where the pattern and text both contain the same letter repeatedly:

A	A	A	A	A	A	A	A
A	A	A	-	-	-	-	-
-	A	A	A	-	-	-	-
-	-	A	A	A	-	-	-
-	-	-	A	A	A	-	-
-	-	-	-	A	A	A	-

Performance

- ▶ Worst case for the original algorithm when the pattern does appear in the text is $O(mn)$.
- ▶ This can be seen by considering the case where the pattern and text both contain the same letter repeatedly:

A	A	A	A	A	A	A	A
A	A	A	-	-	-	-	-
-	A	A	A	-	-	-	-
-	-	A	A	A	-	-	-
-	-	-	A	A	A	-	-
-	-	-	-	A	A	A	-
-	-	-	-	-	A	A	A

Performance

- ▶ Worst case for the original algorithm when the pattern does appear in the text is $O(mn)$.
- ▶ This can be seen by considering the case where the pattern and text both contain the same letter repeatedly:
- ▶ With Galil rule, linear in general

A	A	A	A	A	A	A	A
A	A	A	-	-	-	-	-
-	A	A	A	-	-	-	-
-	-	A	A	A	-	-	-
-	-	-	A	A	A	-	-
-	-	-	-	A	A	A	-
-	-	-	-	-	A	A	A

Performance

- ▶ Preprocessing:
 - ▶ Varies depending on implementation.
 - ▶ Usually $O(m)$ or $O(km)$, where k is the size of the alphabet
 - ▶ Space complexity $O(k)$

EXTRA: Boyer–Moore–Horspool [3, 5]

A practical simplification: just use the ‘bad character rule’.

- ▶ Worst case is $O(nm)$, but average case is $O(n)$
- ▶ Trivial to implement.

EXTRA: Boyer–Moore–Horspool [3, 5]

A practical simplification: just use the ‘bad character rule’.

- ▶ Worst case is $O(nm)$, but average case is $O(n)$
- ▶ Trivial to implement.
 - ▶ See implementation

References

- [1] Robert S. Boyer and J. Strother Moore. “A Fast String Searching Algorithm”. In: *Commun. ACM* 20.10 (Oct. 1977), pp. 762–772. ISSN: 0001-0782. DOI: 10.1145/359842.359859. URL: <https://doi.org/10.1145/359842.359859>.
- [2] Zvi Galil. “On Improving the Worst Case Running Time of the Boyer-Moore String Matching Algorithm”. In: *Commun. ACM* 22.9 (Sept. 1979), pp. 505–508. ISSN: 0001-0782. DOI: 10.1145/359146.359148. URL: <https://doi.org/10.1145/359146.359148>.
- [3] R. Nigel Horspool. “Practical fast searching in strings”. In: *Software: Practice and Experience* 10.6 (1980), pp. 501–506. DOI: 10.1002/spe.4380100608. URL: <https://onlinelibrary.wiley.com/doi/abs/10.1002/spe.4380100608>.
- [4] Donald E. Knuth, James H. Morris Jr., and Vaughan R. Pratt. “Fast Pattern Matching in Strings”. In: *SIAM Journal on Computing* 6.2 (1977), pp. 323–350. DOI: 10.1137/0206024. URL: <https://doi.org/10.1137/0206024>.
- [5] Wikipedia. *Boyer–Moore–Horspool algorithm* — *Wikipedia, The Free Encyclopedia*. Nov. 7, 2022. URL: https://en.wikipedia.org/w/index.php?title=Boyer%E2%80%93Moore%E2%80%93Horspool_algorithm.