

## What is Quarkus?

Quarkus is a Kubernetes Native Java stack tailored for GraalVM & OpenJDK HotSpot, crafted from the best of breed Java libraries and standards. Also focused on developer experience, making things just work with little to no configuration and allowing to do live coding.

Cheat-sheet tested with **Quarkus 1.3.0.Final**.

## Getting Started

Quarkus comes with a Maven archetype to scaffold a very simple starting project.

```
mvn io.quarkus:quarkus-maven-plugin:1.3.0.Final:create \
  -DprojectId=org.acme \
  -DprojectArtifactId=getting-started \
  -DclassName="org.acme.quickstart.GreetingResource" \
  -Dpath="/hello"
```

To test a **candidate version** of Quarkus you need to run it differently:

```
mvn io.quarkus:quarkus-maven-plugin:1.4.0.CR1:create -DprojectGroupId=acme.co \
  -DprojectArtifactId=greeter -DclassName="acme.co.Greeting" -Dpath="/hello" \
  -DplatformArtifactId=quarkus-bom -DplatformVersion=1.4.0.CR1
```

This creates a simple JAX-RS resource called `GreetingResource`.

```
@Path("/hello")
public class GreetingResource {

    @GET
    @Produces(MediaType.TEXT_PLAIN)
    public String hello() {
        return "hello";
    }
}
```

## Gradle

There is no way to scaffold a project in Gradle but you only need to do:

```
plugins {
    id 'java'
    id 'io.quarkus' version '0.26.1'
}

repositories {
    mavenCentral()
}

dependencies {
    implementation enforcedPlatform('io.quarkus:quarkus-bom:0.26.1')
    implementation 'io.quarkus:quarkus-resteasy'
}
```

Or in Kotlin:

```
plugins {
    java
}

apply(plugin = "io.quarkus")

repositories {
    mavenCentral()
}

dependencies {
    implementation(enforcedPlatform("io.quarkus:quarkus-bom:0.26.1"))
    implementation("io.quarkus:quarkus-resteasy")
}
```

## Command mode

You can define the `main` CLI method to start Quarkus. There are two ways, implementing `io.quarkus.runtime.QuarkusApplication` interface or use the Java main method to launch Quarkus.

```
@io.quarkus.runtime.annotations.QuarkusMain
public class HelloWorldMain implements QuarkusApplication {
    @Override
    public int run(String... args) throws Exception {
        System.out.println("Hello World");
        return 10;
    }
}
```

`run` method called when Quarkus starts, and stops when it finishes.

As Java `main`:

```
@QuarkusMain
public class JavaMain {
    public static void main(String... args) {
        Quarkus.run(HelloWorldMain.class, args);
    }
}
```

## Extensions


Quarkus comes with extensions to integrate with some libraries such as JSON-B, Camel or MicroProfile spec. To list all available extensions just run:

```
./mvnw quarkus:list-extensions
```

 You can use `-DsearchPattern=panache` to filter out all extensions except the ones matching the expression.

And to register the extensions into build tool:

```
./mvnw quarkus:add-extension -Dextensions=""
```

 `extensions` property supports CSV format to register more than one extension at once.

## Application Lifecycle

You can be notified when the application starts/stops by observing `StartupEvent` and `ShutdownEvent` events.

```
@ApplicationScoped
public class ApplicationLifecycle {
    void onStart(@Observes StartupEvent event) {}
    void onStop(@Observes ShutdownEvent event) {}
}
```

Quarkus supports graceful shutdown. By default there is no timeout but can be set by using the `quarkus.shutdown.timeout` config property.

## Adding Configuration Parameters

To add configuration to your application, Quarkus relies on MicroProfile Config spec.

```
@ConfigProperty(name = "greetings.message")
String message;


@ConfigProperty(name = "greetings.message",
                defaultValue = "Hello")
String messageWithDefault;

@ConfigProperty(name = "greetings.message")
Optional<String> optionalMessage;
```

Properties can be set (in decreasing priority) as:

- System properties (-Dgreetings.message).
- Environment variables (GREETINGS\_MESSAGE).
- Environment file named .env placed in the current working directory (GREETING\_MESSAGE=).
- External config directory under the current working directory: config/application.properties.
- Resources src/main/resources/application.properties.

```
greetings.message = Hello World
```

 Array, List and Set are supported. The delimiter is comma (,) char and \ is the escape char.

### Configuration Profiles

Quarkus allow you to have multiple configuration in the same file (application.properties).

The syntax for this is \${profile}.config.key=value.

```
quarkus.http.port=9090
%dev.quarkus.http.port=8181
```

HTTP port will be 9090, unless the 'dev' profile is active.

Default profiles are:

- dev: Activated when in development mode (quarkus:dev).
- test: Activated when running tests.
- prod: The default profile when not running in development or test mode

You can create custom profile names by enabling the profile either setting quarkus.profile system property or QUARKUS\_PROFILE environment variable.


```
quarkus.http.port=9090
%staging.quarkus.http.port=9999
```

And enable it quarkus.profile=staging.

To get the active profile programmatically use io.quarkus.runtime.configuration.ProfileManager.getActiveProfile().

You can also set it in the build tool:

```
<groupId>org.apache.maven.plugins</groupId>
<artifactId>maven-surefire-plugin</artifactId>
<version>${surefire-plugin.version}</version>
<configuration>
  <systemPropertyVariables>
    <quarkus.test.profile>foo</quarkus.test.profile>
    <buildDirectory>${project.build.directory}</buildDirectory>
  </systemPropertyVariables>
</configuration>
```

 Same for maven-failsafe-plugin.

```
test {
    useJUnitPlatform()
    systemProperty "quarkus.test.profile", "foo"
}
```

Special properties are set in prod mode: quarkus.application.version and quarkus.application.name to get them available at runtime.

```
@ConfigProperty(name = "quarkus.application.name")
String applicationName;
```

### @ConfigProperties

As an alternative to injecting multiple related configuration values, you can also use the @io.quarkus.arc.config.ConfigProperties annotation to group properties.

```
@ConfigProperties(prefix = "greeting", namingStrategy=NamingStrategy.KEBAB_CASE)
public class GreetingConfiguration {
    private String message;
    // getter/setter
}
```

This class maps greeting.message property defined in application.properties.

You can inject this class by using CDI @Inject GreetingConfiguration greeting;.

Also you can use an interface approach:

```
@ConfigProperties(prefix = "greeting", namingStrategy=NamingStrategy.KEBAB_CASE)
public interface GreetingConfiguration {

    @ConfigProperty(name = "message")
    String message();
    String getSuffix();
}
```

If property does not follow getter/setter naming convention you need to use org.eclipse.microprofile.config.inject.ConfigProperty to set it.

Nested objects are also supported:


```
@ConfigProperties(prefix = "greeting", namingStrategy=NamingStrategy.KEBAB_CASE)
public class GreetingConfiguration {
    public String message;
    public HiddenConfig hidden;

    public static class HiddenConfig {
        public List<String> recipients;
    }
}
```

And an application.properties mapping previous class:

```
greeting.message = hello
greeting.hidden.recipients=Jane,John
```

Bean Validation is also supported so properties are validated at startup time, for example @Size(min = 20) public String message;.

 prefix attribute is not mandatory. If not provided, attribute is determined by class name (ie GreetingConfiguration is translated to greeting or GreetingExtraConfiguration to greeting-extra). The suffix of the class is always removed.

Naming strategy can be changed with property namingStrategy.KEBAB\_CASE (whatever.foo-bar) or VERBATIM (whatever.fooBar).

### YAML Config

YAML configuration is also supported. The configuration file is called application.yaml and you need to register a dependency to enable its support:

```
pom.xml

<dependency>
  <groupId>io.quarkus</groupId>
  <artifactId>quarkus-config-yaml</artifactId>
</dependency>
```

```
quarkus:
  datasource:
    url: jdbc:postgresql://localhost:5432/some-database
    driver: org.postgresql.Driver
```

Or with profiles:

```
"%dev":
  quarkus:
    datasource:
      url: jdbc:postgresql://localhost:5432/some-database
      driver: org.postgresql.Driver
```

In case of subkeys `~` is used to refer to the unprefixed part.

```
quarkus:
  http:
    cors:
      ~: true
      methods: GET,PUT,POST
```

Is equivalent to:

```
quarkus.http.cors=true
quarkus.http.cors.methods=GET,PUT,POST
```

Custom Loader

You can implement your own `ConfigSource` to load configuration from different places than the default ones provided by Quarkus. For example, database, custom XML, REST Endpoints, ...

You need to create a new class and implement `ConfigSource` interface:

```
package com.acme.config;

public class InMemoryConfig implements ConfigSource {

    private Map<String, String> prop = new HashMap<>();

    public InMemoryConfig() {
        // Init properties
    }

    @Override
    public int getOrdinal() {
        // The highest ordinal takes precedence
        return 900;
    }

    @Override
    public Map<String, String> getProperties() {
        return prop;
    }

    @Override
    public String getValue(String propertyName) {
        return prop.get(propertyName);
    }

    @Override
    public String getName() {
        return "MemoryConfigSource";
    }
}
```

Then you need to register the `ConfigSource` as Java service. Create a file with the following content:

```
/META-INF/services/org.eclipse.microprofile.config.spi.ConfigSource

com.acme.config.InMemoryConfig
```

Custom Converters

You can implement your own conversion types from String. Implement `org.eclipse.microprofile.config.spi.Converter` interface:

```
@Priority(DEFAULT_QUARKUS_CONVERTER_PRIORITY + 100)
public class CustomInstantConverter
    implements Converter<Instant> {

    @Override
    public Instant convert(String value) {
        if ("now".equals(value.trim())) {
            return Instant.now();
        }
        return Instant.parse(value);
    }
}
```

`@Priority` annotation is used to override the default `InstantConverter`.

Then you need to register the `Converter` as Java service. Create a file with the following content:

```
/META-INF/services/org.eclipse.microprofile.config.spi.Converter

com.acme.config.CustomInstantConverter
```

Undertow Properties

Possible parameters with prefix `quarkus.servlet:`

**context-path**  
The context path to serve all Servlet context from. (default: `/`)

**default-charset**  
The default charset to use for reading and writing requests. (default: `UTF-8`)

HTTPS

To configure HTTPS:

```
quarkus.http.ssl-port=8443
quarkus.http.ssl.certificate.key-store-file=keystore.jks
quarkus.http.ssl.certificate.key-store-file-type=jks
quarkus.http.ssl.certificate.key-store-password=changeit
quarkus.ssl.native=true
```

Possible parameters with prefix `quarkus.http:`

**ssl-port**  
The *HTTPS* port. (default: `8443`)

**ssl.certificate.file**  
The file path to a service certificate or certificate chain in *PEM* format. Relative to `src/main/resources`.

**ssl.certificate.key-file**  
The file path to the corresponding certificate private key in *PEM* format. Relative to `src/main/resources`.

**ssl.certificate.key-store-file**  
The key store contains the certificate information. Relative to `src/main/resources`.

**ssl.certificate.key-store-file-type**  
The key store type. It is automatically detected based on the file name or can be set manually. Supported values are: `JKS`, `JCEKS`, `P12`, `PKCS12` Or `PFX`.

**ssl.certificate.key-store-password**  
The password to open the key store file.

**ssl.certificate.trust-store-file** The trust store location which contains the certificate information of the certificates to trust. Relative to `src/main/resources`.

**ssl.certificate.trust-store-file-type**



The trust store type. It is automatically detected based on the file name or can be set manually.

`ssl.certificate.trust-store-password`

The password to open the trust store file.

`ssl.cipher-suites`

A list of strings of cipher suites to use. If not provided, a reasonable default is selected.

`ssl.protocols`

The list of protocols to explicitly enable. (default: `TLSv1.3` and `TLSv1.2`).

`ssl.client-auth`

Configures the engine to require/request client authentication. Possible values are: `NONE`, `REQUEST` and `REQUIRED`. (default: `NONE`).

`insecure-requests`

Disable the HTTP port and only support secure requests. Possible values: `ENABLED`, `DISABLED`, `REDIRECT`. (default: `enabled`).

## Injection

Quarkus is based on CDI 2.0 to implement injection of code. It is not fully supported and only a subset of the specification is implemented.

```
@ApplicationScoped
public class GreetingService {

    public String message(String message) {
        return message.toUpperCase();
    }
}
```

Scope annotation is mandatory to make the bean discoverable.

```
@Inject
GreetingService greetingService;
```



Quarkus is designed with Substrate VM in mind. For this reason, we encourage you to use *package-private* scope instead of *private*.

### Produces

You can also create a factory of an object by using `@javax.enterprise.inject.Produces` annotation.

```
@Produces
@ApplicationScoped
Message message() {
    Message m = new Message();
    m.setMsn("Hello");
    return m;
}

@Inject
Message msg;
```

### Qualifiers

You can use qualifiers to return different implementations of the same interface or to customize the configuration of the bean.

```
@Qualifier
@Retention(RUNTIME)
@Target({TYPE, METHOD, FIELD, PARAMETER})
public @interface Quote {
    @Nonbinding String value();
}

@Produces
@Quote("")
Message message(InjectionPoint msg) {
    Message m = new Message();
    m.setMsn(
        msg.getAnnotated()
            .getAnnotation(Quote.class)
            .value()
    );

    return m;
}

@Inject
@Quote("Aloha Beach")
Message message;
```



Quarkus breaks the CDI spec by allowing you to inject qualified beans without using `@Inject` annotation.

```
@Quote("Aloha Beach")
Message message;
```



Quarkus breaks the CDI spec by skipping the `@Produces` annotation completely if the producer method is annotated with a scope annotation, a stereotype or a qualifier.

```
@Quote("")
Message message(InjectionPoint msg) {
}

@Quote("Aloha Beach")
Message message;
```

### Alternatives

It is also possible to select alternatives for an application using `application.properties`.

```
quarkus.arc.selected-alternatives=org.acme.Foo,org.acme.*,Bar
```

### Beans by Quarkus Profile

Using `@io.quarkus.arc.profile.IfBuildProfile` and `@io.quarkus.arc.profile.UnlessBuildProfile` annotations, you can conditionally enable a bean.

```
@Dependent
public class TracerConfiguration {
    @Produces
    @IfBuildProfile("prod")
    public Tracer realTracer(Reporter reporter, Configuration configuration) {
        return new RealTracer(reporter, configuration);
    }

    @Produces
    @DefaultBean
    public Tracer noopTracer() {
        return new NoopTracer();
    }
}
```

## JSON Marshalling/Unmarshalling

To work with `JSON-B` you need to add a dependency:

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-resteasy-jsonb"
```

Any POJO is marshaled/unmarshalled automatically.

```
public class Sauce {
    private String name;
    private long scovilleHeatUnits;

    // getter/setters
}
```

JSON equivalent:

```
{
  "name": "Blair's Ultra Death",
  "scovilleHeatUnits": 1100000
}
```

In a `POST` endpoint example:

```
@POST
@Consumes(MediaType.APPLICATION_JSON)
public Response create(Sauce sauce) {
    // Create Sauce
    return Response.created(URI.create(sauce.getId()))
        .build();
}
```

To work with `Jackson` you need to add:

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-resteasy-jackson"
```

If you don't want to use the default `ObjectMapper` you can customize it by:

```
@ApplicationScoped
public class CustomObjectMapperConfig {
    @Singleton
    @Produces
    public ObjectMapper objectMapper() {
        ObjectMapper objectMapper = new ObjectMapper();
        // perform configuration
        return objectMapper;
    }
}
```

## XML Marshalling/Unmarshalling

To work with `JAX-B` you need to add a dependency:

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-resteasy-jaxb"
```

Then annotated POJOs are converted to XML.

```
@XmlRootElement
public class Message {
    // ...

    @GET
    @Produces(MediaType.APPLICATION_XML)
    public Message hello() {
        return message;
    }
}
```

## Validator

Quarkus uses `Hibernate Validator` to validate input/output of REST services and business services using Bean validation spec.

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-hibernate-validator"
```

Annotate POJO objects with validator annotations such as:

`@NotNull`, `@Digits`, `@NotBlank`, `@Min`, `@Max`, ...


```
public class Sauce {
    // ...

    @NotBlank(message = "Name may not be blank")
    private String name;
    @Min(0)
    private long scovilleHeatUnits;
    // ...

    // getter/setters
}
```

To validate an object use `@Valid` annotation:

```
public Response create(@Valid Sauce sauce) {}
```



If a validation error is triggered, a violation report is generated and serialized as JSON. If you want to manipulate the output, you need to catch in the code the `ConstraintViolationException` exception.

### Create Your Custom Constraints

First you need to create the custom annotation:

```
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR,
          PARAMETER, TYPE_USE })
@Retention(RUNTIME)
@Documented
@Constraint(validatedBy = { NotExpiredValidator.class})
public @interface NotExpired {

    String message() default "Sauce must not be expired";
    Class<?>[] groups() default { };
    Class<? extends Payload>[] payload() default { };
    // ...

}
```

You need to implement the validator logic in a class that implements `ConstraintValidator`.

```
public class NotExpiredValidator
    implements ConstraintValidator<NotExpired, LocalDate>
{
    // ...

    @Override
    public boolean isValid(LocalDate value,
                          ConstraintValidatorContext ctx) {
        if ( value == null ) return true;
        LocalDate today = LocalDate.now();
        return ChronoUnit.YEARS.between(today, value) > 0;
    }
}
```

And use it normally:

```
@NotExpired
@JsonbDateFormat(value = "yyyy-MM-dd")
private LocalDate expired;
```

### Manual Validation

You can call the validation process manually instead of relaying to `@Valid` by injecting `Validator` class.

```
@Inject
Validator validator;
```

And use it:

```
Set<ConstraintViolation<Sauce>> violations =
    validator.validate(sauce);
```

### Localization

You can configure the based locale for validation messages.

```
quarkus.default-locale=ca-ES
# Supported locales resolved by Accept-Language
quarkus.locales=en-US,es-ES,fr-FR, ca_ES
```

`ValidationMessages_ca_ES.properties`

```
pattern.message=No conforme al patro
```

```
@Pattern(regexp = "A.*", message = "{pattern.message}")
private String name;
```

## Logging

You can configure how Quarkus logs:

```
quarkus.log.console.enable=true
quarkus.log.console.level=DEBUG
quarkus.log.console.color=false
quarkus.log.category."com.lordofthejars".level=DEBUG
```

Prefix is `quarkus.log.`

`category."<category-name>".level`  
Minimum level category (default: `INFO`)

`level`  
Default minimum level (default: `INFO`)

`console.enabled`  
Console logging enabled (default: `true`)

<code>console.format</code>	Format pattern to use for logging. Default value: <code>%d{yyyy-MM-dd HH:mm:ss,SSS} %-5p [%c{3.}] (%t) %s%n</code>
<code>console.level</code>	Minimum log level (default: <code>INFO</code> )
<code>console.color</code>	Allow color rendering (default: <code>true</code> )
<code>file.enable</code>	File logging enabled (default: <code>false</code> )
<code>file.format</code>	Format pattern to use for logging. Default value: <code>%d{yyyy-MM-dd HH:mm:ss,SSS} %h %N[%i] %-5p [%c{3.}] (%t) %s%n</code>
<code>file.level</code>	Minimum log level (default: <code>ALL</code> )
<code>file.path</code>	The path to log file (default: <code>quarkus.log</code> )
<code>file.rotation.max-file-size</code>	The maximum file size of the log file
<code>file.rotation.max-backup-index</code>	The maximum number of backups to keep (default: <code>1</code> )
<code>file.rotation.file-suffix</code>	Rotating log file suffix.
<code>file.rotation.rotate-on-boot</code>	Indicates rotate logs at bootup (default: <code>true</code> )
<code>file.async</code>	Log asynchronously (default: <code>false</code> )
<code>file.async.queue-length</code>	The queue length to use before flushing writing (default: <code>512</code> )
<code>file.async.overflow</code>	Action when queue is full (default: <code>BLOCK</code> )
<code>syslog.enable</code>	syslog logging is enabled (default: <code>false</code> )
<code>syslog.format</code>	The format pattern to use for logging to syslog. Default value: <code>%d{yyyy-MM-dd HH:mm:ss,SSS} %h %N[%i] %-5p [%c{3.}] (%t) %s%n</code>
<code>syslog.level</code>	The minimum log level to write to syslog (default: <code>ALL</code> )
<code>syslog.endpoint</code>	The IP address and port of the syslog server (default: <code>localhost:514</code> )

<code>syslog.app-name</code>	The app name used when formatting the message in RFC5424 format (default: current process name)
<code>syslog.hostname</code>	The name of the host the messages are being sent from (default: current hostname)
<code>syslog.facility</code>	Priority of the message as defined by RFC-5424 and RFC-3164 (default: <code>USER_LEVEL</code> )
<code>syslog.syslog-type</code>	The syslog type of format message (default: <code>RFC5424</code> )
<code>syslog.protocol</code>	Protocol used (default: <code>TCP</code> )
<code>syslog.use-counting-framing</code>	Message prefixed with the size of the message (default <code>false</code> )
<code>syslog.truncate</code>	Message should be truncated (default: <code>true</code> )
<code>syslog.block-on-reconnect</code>	Block when attempting to reconnect (default: <code>true</code> )
<code>syslog.async</code>	Log asynchronously (default: <code>false</code> )
<code>syslog.async.queue-length</code>	The queue length to use before flushing writing (default: <code>512</code> )
<code>syslog.async.overflow</code>	Action when queue is full (default: <code>BLOCK</code> )
<code>handler.gelf.enabled</code>	Enable GELF logging handler (default: <code>false</code> )
<code>handler.gelf.host</code>	Hostname/IP of Logstash/Graylof. Prepend <code>tcp:</code> for using TCP protocol. (default: <code>udp:localhost</code> )
<code>handler.gelf.port</code>	The port. (default: <code>12201</code> )
<code>handler.gelf.version</code>	GELF version. (default: <code>1.1</code> )

<code>handler.gelf.extract-stack-trace</code>	Post Stack-Trace to StackTrace field. (default: <code>true</code> )
<code>handler.gelf.stack-trace-throwable-reference</code>	Gets the cause level to stack trace. <code>0</code> is fulls tack trace. (default: <code>0</code> )
<code>handler.gelf.filter-stack-trace</code>	Stack-Trace filtering. (default: <code>false</code> )
<code>handler.gelf.timestamp-pattern</code>	Java Date pattern. (default: <code>yyyy-MM-dd HH:mm:ss,SSS</code> )
<code>handler.gelf.level</code>	Log level <code>java.util.logging.Level</code> . (default: <code>ALL</code> )
<code>handler.gelf.facility</code>	Name of the facility. (default: <code>jboss-logmanage</code> )
<code>handler.gelf.additional-field.&lt;field&gt;.&lt;subfield&gt;</code>	Post additional fields. <code>quarkus.log.handler.gelf.additional-field.field1.type=String</code>
<h3>JSON output</h3> <p>You can configure the output to be in <i>JSON</i> format instead of plain text.</p> <pre>./mvnw quarkus:add-extension -Dextensions="quarkus-logging-json"</pre>	
<p>And the configuration values are prefix with <code>quarkus.log:</code></p>	
<code>json</code>	JSON logging is enabled (default: true).
<code>json.pretty-print</code>	JSON output is "pretty-printed" (default: false)
<code>json.date-format</code>	Specify the date format to use (default: the default format)
<code>json.record-delimiter</code>	Record delimiter to add (default: no delimiter)
<code>json.zone-id</code>	The time zone ID
<code>json.exception-output-type</code>	The exception output type: <code>detailed</code> , <code>formatted</code> , <code>detailed-and-formatted</code> (default: <code>detailed</code> )
<code>json.print-details</code>	Detailed caller information should be logged (default: false)

## Rest Client



Quarkus implements MicroProfile Rest Client spec:

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-rest-client"
```

To get content from <http://worldclockapi.com/api/json/cet/now> you need to create a service interface:

```
@Path("/api")
@RegisterRestClient
public interface WorldClockService {

    @GET @Path("/json/cet/now")
    @Produces(MediaType.APPLICATION_JSON)
    WorldClock getNow();

    @GET
    @Path("/json/{where}/now")
    @Produces(MediaType.APPLICATION_JSON)
    WorldClock getSauce(@BeanParam
        WorldClockOptions worldClockOptions);

}
```

```
public class WorldClockOptions {
    @HeaderParam("Authorization")
    String auth;

    @PathParam("where")
    String where;
}
```

And configure the hostname at `application.properties`:

```
org.acme.quickstart.WorldClockService/mp-rest/url=
http://worldclockapi.com
```

Injecting the client:

```
@RestClient
WorldClockService worldClockService;
```

If invocation happens within JAX-RS, you can propagate headers from incoming to outgoing by using next property.

```
org.eclipse.microprofile.rest.client.propagateHeaders=
Authorization,MyCustomHeader
```



You can still use the JAX-RS client without any problem

```
ClientBuilder.newClient().target(...)
```

## Adding headers

You can customize the headers passed by implementing `MicroProfile ClientHeadersFactory` annotation:

```
@RegisterForReflection
public class BaggageHeadersFactory
    implements ClientHeadersFactory {

    @Override
    public MultivaluedMap<String, String> update(
        MultivaluedMap<String, String> incomingHeaders,
        MultivaluedMap<String, String> outgoingHeaders) {}

}
```

And registering it in the client using `RegisterClientHeaders` annotation.

```
@RegisterClientHeaders(BaggageHeadersFactory.class)
@RegisterRestClient
public interface WorldClockService {}
```

Or statically set:

```
@GET
@ClientHeaderParam(name="X-Log-Level", value="ERROR")
Response getNow();
```

## Asynchronous

A method on client interface can return a `CompletionStage` class to be executed asynchronously.

```
@GET @Path("/json/cet/now")
@Produces(MediaType.APPLICATION_JSON)
CompletionStage<WorldClock> getNow();
```

## Reactive

Rest Client also integrates with reactive library named Mutiny. To start using it you need to add the `quarkus-resteasy-mutiny`.

After that, a method on a client interface can return a `io.smallrye.mutiny.Uni` instance.

```
@GET @Path("/json/cet/now")
@Produces(MediaType.APPLICATION_JSON)
Uni<WorldClock> getNow();
```

## Multipart

It is really easy to send multipart form-data with Rest Client.

```
<dependency>
  <groupId>org.jboss.resteasy</groupId>
  <artifactId>resteasy-multipart-provider</artifactId>
</dependency>
```

The model object:

```
import java.io.InputStream;

import javax.ws.rs.FormParam;
import javax.ws.rs.core.MediaType;

import
    org.jboss.resteasy.annotations.providers.multipart.Part
    Type;

public class MultipartBody {

    @FormParam("file")
    @PartType(MediaType.APPLICATION_OCTET_STREAM)
    private InputStream file;

    @FormParam("fileName")
    @PartType(MediaType.TEXT_PLAIN)
    private String name;

    // getter/setters
}
```

And the Rest client interface:

```
import
    org.jboss.resteasy.annotations.providers.multipart.Mult
    ipartForm;

@Path("/echo")
@RegisterRestClient
public interface MultipartService {

    @POST
    @Consumes(MediaType.MULTIPART_FORM_DATA)
    @Produces(MediaType.TEXT_PLAIN)
    String sendMultipartData(@MultipartForm
        MultipartBody data);

}
```

## SSL

You can configure Rest Client key stores.

```
org.acme.quickstart.WorldClockService/mp-rest/trustStore=
    classpath:/store.jks
org.acme.quickstart.WorldClockService/mp-rest/trustStorePas
sword=
    supersecret
```

Possible configuration properties:

`%s/mp-rest/trustStore`

Trust store location defined with `classpath:` or `file:` prefix.

`%s/mp-rest/trustStorePassword`

Trust store password.

`%s/mp-rest/trustStoreType`

Trust store type (default: `JKS`)

`%s/mp-rest/hostnameVerifier`

Custom hostname verifier class name.

`%s/mp-rest/keyStore`

Key store location defined with `classpath:` or `file:` prefix.

`%s/mp-rest/keyStorePassword`

Key store password.

`%s/mp-rest/keyStoreType`

Key store type (default: `JKS`)

### Timeout

You can define the timeout of the Rest Client:

```
org.acme.quickstart.WorldClockService/mp-rest/connectTimeout=
1000
org.acme.quickstart.WorldClockService/mp-rest/readTimeout=
2000
```

## Testing

Quarkus archetype adds test dependencies with JUnit 5 and Rest-Assured library to test REST endpoints.

```
@QuarkusTest
public class GreetingResourceTest {

    @Test
    public void testHelloEndpoint() {
        given()
            .when().get("/hello")
            .then()
                .statusCode(200)
                .body(is("hello"));
    }
}
```

Test port can be set in `quarkus.http.test-port` property.

You can also inject the URL where Quarkus is started:

```
@TestHTTPResource("index.html")
URL url;
```

### Quarkus Test Resource

You can execute some logic before the first test run (`start`) and execute some logic at the end of the test suite (`stop`).

You need to create a class implementing `QuarkusTestResourceLifecycleManager` interface and register it in the test via `@QuarkusTestResource` annotation.

```
public class MyCustomTestResource
    implements QuarkusTestResourceLifecycleManager {

    @Override
    public Map<String, String> start() {
        // return system properties that
        // should be set for the running test
        return Collections.emptyMap();
    }

    @Override
    public void stop() {
    }

    // optional
    @Override
    public void inject(Object testInstance) {
    }

    // optional
    @Override
    public int order() {
        return 0;
    }
}
```

! Returning new system properties implies running parallel tests in different JVMs.

And the usage:

```
@QuarkusTestResource(MyCustomTestResource.class)
public class MyTest {
}
```

### Mocking

If you need to provide an alternative implementation of a service (for testing purposes) you can do it by using CDI `@Alternative` annotation using it in the test service placed at `src/test/java`:

```
@Alternative
@Priority(1)
@ApplicationScoped
public class MockExternalService extends ExternalService {}
```

! This does not work when using native image testing.

A stereotype annotation `io.quarkus.test.Mock` is provided declaring `@Alternative`, `@Priority(1)` and `@Dependent`.

### Mockito

Instead of creating stubs, you can also create mocks of your services with `mockito`. Add the following dependency `io.quarkus:quarkus-junit5-mockito`:

```
@InjectMock
GreetingService greetingService;

@BeforeEach
public void setup() {
    Mockito.when(greetingService.greet()).thenReturn("Hi");
}

@Path("/hello")
public class ExampleResource {

    @Inject
    GreetingService greetingService;
}
```

Mock is automatically injected and only valid for the defined test class.

### Interceptors

Tests are actually full CDI beans, so you can apply CDI interceptors:

```
@QuarkusTest
@Stereotype
@Transactional
@Retention(RetentionPolicy.RUNTIME)
@Target(ElementType.TYPE)
public @interface TransactionalQuarkusTest {
}

@TransactionalQuarkusTest
public class TestStereotypeTestCase {}
```

**Test Coverage** Due the nature of Quarkus to calculate correctly the coverage information with JaCoCo, you might need offline instrumentation. I recommend reading [this document](#) to understand how JaCoCo and Quarkus works and how you can configure JaCoCo to get correct data.

### Native Testing

To test native executables annotate the test with `@NativeImageTest`.



## Persistence

Quarkus works with JPA(Hibernate) as persistence solution. But also provides an Active Record pattern implementation under Panache project.

To use database access you need to add Quarkus JDBC drivers instead of the original ones. At this time Apache Derby, H2, MariaDB, MySQL, MSSQL and PostgreSQL drivers are supported.

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-hibernate-orm-panache,
            io.quarkus:quarkus-jdbc-mariadb"
```

```
@Entity
public class Developer extends PanacheEntity {

    // id field is implicit

    public String name;
}
```

And configuration in src/main/resources/application.properties:

```
quarkus.datasource.jdbc.url=jdbc:mariadb://localhost:3306/mydb
quarkus.datasource.db-kind=mariadb
quarkus.datasource.username=developer
quarkus.datasource.password=developer
quarkus.hibernate-orm.database.generation=update
```

List of datasource parameters.

quarkus.datasource as prefix is skipped in the next table.

db-kind	Built-in datasource kinds so the JDBC driver is resolved automatically. Possible values: derby, h2, mariadb, mssql, mysql, postgresql.
username	Username to access.
password	Password to access.
driver	JDBC Driver class. It is not necessary to set if db-kind used.
jdbc.url	The datasource URL.
jdbc.min-size	The datasource pool minimum size. (default: 0)
jdbc.max-size	

The datasource pool maximum size. (default: 20)

jdbc.initial-size

The initial size of the pool.

jdbc.background-validation-interval

The interval at which we validate idle connections in the background. (default: 2M)

jdbc.acquisition-timeout

The timeout before cancelling the acquisition of a new connection. (default: 5)

jdbc.leak-detection-interval

The interval at which we check for connection leaks.

jdbc.idle-removal-interval

The interval at which we try to remove idle connections. (default: 5M)

jdbc.max-lifetime

The max lifetime of a connection.

jdbc.transaction-isolation-level

The transaction isolation level. Possible values: UNDEFINED, NONE, READ\_UNCOMMITTED, READ\_COMMITTED, REPEATABLE\_READ, SERIALIZABLE.

jdbc.detect-statement-leaks

Warn when a connection is returned to the pool without the application having closed all open statements. (default: true)

jdbc.new-connection-sql

Query executed when first using a connection.

jdbc.validation-query-sql

Query executed to validate a connection.

jdbc.enable-metrics

Enable datasource metrics collection when using quarkus-smallrye-metrics extension.

Hibernate configuration properties. Prefix quarkus.hibernate-orm is skipped.

dialect

Class name of the Hibernate ORM dialect.

dialect.storage-engine

The storage engine when the dialect supports multiple storage engines.

sql-load-script

Name of the file containing the SQL statements to execute when starts. no-file force Hibernate to skip SQL import. (default: import.sql)

batch-fetch-size

The size of the batches. (default: -1 disabled)

query.query-plan-cache-max-size

The maximum size of the query plan cache.

query.default-null-ordering

Default precedence of null values in ORDER BY. Possible values: none, first, last. (default: none)

database.generation

Database schema is generation. Possible values: none, create, drop-and-create, drop, update. (default: none)

database.generation.halt-on-error

Stop on the first error when applying the schema. (default: false)

database.default-catalog

Default catalog.

database.default-schema

Default Schema.

database.charset

Charset.

jdbc.timezone

Time Zone JDBC driver.

jdbc.statement-fetch-size

Number of rows fetched at a time.

jdbc.statement-batch-size

Number of updates sent at a time.

log.sql

Show SQL logs (default: false)

log.jdbc-warnings

statistics

Enable statiscs collection. (default: false)

physical-naming-strategy

Class name of the Hibernate PhysicalNamingStrategy implementation.

globally-quoted-identifiers

Should quote all identifiers. (default: false)

metrics-enabled

Metrics published with smallrye-metrics extension (default: false)

second-level-caching-enabled

Enable/Disable 2nd level cache. (default: true)

Database operations:

```
// Insert
Developer developer = new Developer();
developer.name = "Alex";
developer.persist();

// Find All
Developer.findAll().list();

// Find By Query
Developer.find("name", "Alex").firstResult();

// Delete
Developer developer = new Developer();
developer.id = 1;
developer.delete();

Person.deleteById(id);
// Delete By Query
long numberOfDeleted = Developer.delete("name", "Alex");
```

Remember to annotate methods with `@Transactional` annotation to make changes persisted in the database.

If queries start with the keyword `from` then they are treated as *HQL* query, if not then next short form is supported:

- `order by` which expands to `from EntityName order by ...`
- `<columnName> which expands to from EntityName where <columnName>=?`
- `<query>` which is expanded to `from EntityName where <query>`

Static Methods

**findById: Object**  
Returns object or null if not found. Overloaded version with `LockModeType` is provided.

**findByIdOptional: Optional<Object>**  
Returns object or `java.util.Optional`.

**find: String, [Object..., Map<String, Object>, Parameters]**  
Lists of entities meeting given query with parameters set.

**find: String, Sort, [Object..., Map<String, Object>, Parameters]**  
Lists of entities meeting given query with parameters set sorted by `Sort` attribute/s.

**findAll**  
Finds all entities.

**findAll: Sort**  
Finds all entities sorted by `Sort` attribute/s.

**stream: String, [Object..., Map<String, Object>, Parameters]**  
`java.util.stream.Stream` of entities meeting given query with parameters set.

**stream: String, Sort, [Object..., Map<String, Object>, Parameters]**

`java.util.stream.Stream` of entities meeting given query with parameters set sorted by `Sort` attribute/s.

**streamAll**  
`java.util.stream.Stream` of all entities.

**streamAll: Sort**  
`java.util.stream.Stream` of all entities sorted by `Sort` attribute/s.

**count**  
Number of entities.


**count: String, [Object..., Map<String, Object>, Parameters]**  
Number of entities meeting given query with parameters set.

**deleteAll**  
Number of deleted entities.

**delete: String, [Object..., Map<String, Object>, Parameters]**  
Number of deleted entities meeting given query with parameters set.

**deleteById: boolean, [Object]**  
Delete by id. Returns if deleted or not.

**persist: [Iterable, Steram, Object...]**  
In case of using streams, remember to close them or use a `try/catch` block: `try (Stream<Person> persons = Person.streamAll()) {`

 `find` methods defines a `withLock(LockModeType)` to define the lock type and `withHint(QueryHints.HINT_CACHEABLE, "true")` to define hints.

Named Queries

```
@Entity
@NamedQuery(name = "Person.getByName", query = "from Person where name = :name")
public class Person extends PanacheEntity {

    public static Person findByName(String name){
        return find("#Person.getByName", name).firstResult
    };
}
```

Pagination

```
PanacheQuery<Person> livingPersons = Person
    .find("status", Status.Alive);
livingPersons.page(Page.ofSize(25));

// get the first page
List<Person> firstPage = livingPersons.list();
// get the second page
List<Person> secondPage = livingPersons.nextPage().list();
```

Range

```
PanacheQuery<Person> livingPersons = Person
    .find("status", Status.Alive);
List<Person> secondRange = livingPersons.range(25, 49).list
();
```

You cannot mix pagination and range.

If entities are defined in external JAR, you need to enable in these projects the `Jandex` plugin in project.

```
<plugin>
  <groupId>org.jboss.jandex</groupId>
  <artifactId>jandex-maven-plugin</artifactId>
  <version>1.0.3</version>
  <executions>
    <execution>
      <id>make-index</id>
      <goals>
        <goal>jandex</goal>
      </goals>
    </execution>
  </executions>
  <dependencies>
    <dependency>
      <groupId>org.jboss</groupId>
      <artifactId>jandex</artifactId>
      <version>2.1.1.Final</version>
    </dependency>
  </dependencies>
</plugin>
```

DAO pattern

Also supports *DAO* pattern with `PanacheRepository<TYPE>`.

```
@ApplicationScoped
public class DeveloperRepository
    implements PanacheRepository<Person> {
    public Person findByName(String name){
        return find("name", name).firstResult();
    }
}
```

**EntityManager** You can inject `EntityManager` in your classes:

```
@Inject
EntityManager em;

em.persist(car);
```

Multiple datasources

You can register more than one datasource.

```
# default
quarkus.datasource.db-kind=h2
quarkus.datasource.jdbc.url=jdbc:h2:tcp://localhost/mem:default
....
# users datasource
quarkus.datasource.users.db-kind=h2
quarkus.datasource.users..jdbc.url=jdbc:h2:tcp://localhost/mem:users
```


Notice that after `datasource` you set the datasource name, in previous case `users`.

You can inject then `AgroalDataSource` with `io.quarkus.agroal.DataSource`.

```
@DataSource("users")
AgroalDataSource dataSource1;
```

Flushing

You can force flush operation by calling `.flush()` or `.persistAndFlush()` to make it in a single call.



This flush is less efficient and you still need to commit transaction.

Testing

There is a Quarkus Test Resource that starts and stops H2 server before and after test suite.

Register dependency `io.quarkus:quarkus-test-h2:test`.

And annotate the test:

```
@QuarkusTestResource(H2DatabaseTestResource.class)
public class FlywayTestResources {
}
```

Transactions

The easiest way to define your transaction boundaries is to use the `@Transactional` annotation.

Transactions are mandatory in case of none idempotent operations.

```
@Transactional
public void createDeveloper() {}
```

You can control the transaction scope:

- `@Transactional(REQUIRED)` (default): starts a transaction if none was started, stays with the existing one otherwise.
- `@Transactional(REQUIRES_NEW)`: starts a transaction if none was started; if an existing one was started, suspends it and starts a

new one for the boundary of that method.

- `@Transactional(MANDATORY)`: fails if no transaction was started ; works within the existing transaction otherwise.
- `@Transactional(SUPPORTS)`: if a transaction was started, joins it ; otherwise works with no transaction.
- `@Transactional(NOT_SUPPORTED)`: if a transaction was started, suspends it and works with no transaction for the boundary of the method; otherwise works with no transaction.
- `@Transactional(NEVER)`: if a transaction was started, raises an exception; otherwise works with no transaction.

You can configure the default transaction timeout using `quarkus.transaction-manager.default-transaction-timeout` configuration property. By default it is set to 60 seconds.

You can set a timeout property, in seconds, that applies to transactions created within the annotated method by using `@TransactionConfiguration` annotation.

```
@Transactional
@TransactionConfiguration(timeout=40)
public void createDeveloper() {}
```

If you want more control over transactions you can inject `UserTransaction` and use a programmatic way.

```
@Inject UserTransaction transaction

transaction.begin();
transaction.commit();
transaction.rollback();
```

Infinispan

Quarkus integrates with Infinispan:

```
./mvnw quarkus:add-extension
-Dextensions="infinispan-client"
```

Serialization uses a library called Protostream.

Annotation based

```
@ProtoFactory
public Author(String name, String surname) {
    this.name = name;
    this.surname = surname;
}

@ProtoField(number = 1)
public String getName() {
    return name;
}

@ProtoField(number = 2)
public String getSurname() {
    return surname;
}
```

Initializer to set configuration settings.

```
@AutoProtoSchemaBuilder(includeClasses =
    { Book.class, Author.class },
    schemaPackageName = "book_sample")
interface BookContextInitializer
    extends SerializationContextInitializer {
}
```

User written based

There are three ways to create your schema:

Protofile

Creates a `.proto` file in the `META-INF` directory.

```
package book_sample;

message Author {
    required string name = 1;
    required string surname = 2;
}
```

In case of having a Collection field you need to use the `repeated` key (ie `repeated Author authors = 4`).

In code

Setting `proto` schema directly in a produced bean.

```
@Produces
FileDescriptorSource bookProtoDefinition() {
    return FileDescriptorSource
        .fromString("library.proto",
            "package book_sample;\n" +
            "message Author {\n" +
            "    required string name = 1;\n" +
            "    required string surname = 2;\n" +
            "}");
}
```



Marshaller

Using `org.infinispan.protostream.MessageMarshaller` interface.

```
public class AuthorMarshaller
    implements MessageMarshaller<Author> {

    @Override
    public String getTypeName() {
        return "book_sample.Author";
    }

    @Override
    public Class<? extends Author> getJavaClass() {
        return Author.class;
    }

    @Override
    public void writeTo(ProtoStreamWriter writer,
        Author author) throws IOException {
        writer.writeString("name", author.getName());
        writer.writeString("surname", author.getSurname());
    }

    @Override
    public Author readFrom(ProtoStreamReader reader)
        throws IOException {
        String name = reader.readString("name");
        String surname = reader.readString("surname");
        return new Author(name, surname);
    }
}
```

And producing the marshaller:

```
@Produces
MessageMarshaller authorMarshaller() {
    return new AuthorMarshaller();
}
```

Infinispan Embedded

```
./mvnw quarkus:add-extension
-Dextensions="infinispan-embeddedy"
```

Configuration in `infinispan.xml`:

```
<local-cache name="quarkus-transaction">
  <transaction
    transaction-manager-lookup=
      "org.infinispan.transaction.lookup.JBossStandaloneJ
TAManagerLookup"/>
</local-cache>
```

Set configuration file location in `application.properties`:

```
quarkus.infinispan-embedded.xml-config=infinispan.xml
```

And you can inject the main entry point for the cache:

```
@Inject
org.infinispan.manager.EmbeddedCacheManager cacheManager;
```

Flyway

Quarkus integrates with Flyway to help you on database schema migrations.

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-flyway"
```

Then place migration files to the migrations folder (`classpath:db/migration`).

You can inject `org.flywaydb.core.Flyway` to programmatically execute the migration.

```
@Inject
Flyway flyway;

flyway.migrate();
```

Or can be automatically executed by setting `migrate-at-start` property to `true`.

```
quarkus.flyway.migrate-at-start=true
```

List of Flyway parameters.

`quarkus.flyway` as prefix is skipped in the next table.

<b>clean-at-start</b>	Execute Flyway clean command (default: <code>false</code> )
<b>migrate-at-start</b>	Flyway migration automatically (default: <code>false</code> )
<b>locations</b>	CSV locations to scan recursively for migrations. Supported prefixes <code>classpath</code> and <code>filesystem</code> (default: <code>classpath:db/migration</code> ).
<b>connect-retries</b>	The maximum number of retries when attempting to connect (default: 0)
<b>schemas</b>	CSV case-sensitive list of schemas managed (default: none)

<b>table</b>	The name of Flyway's schema history table (default: <code>flyway_schema_history</code> )
<b>sql-migration-prefix</b>	Prefix for versioned SQL migrations (default: <code>v</code> )
<b>repeatable-sql-migration-prefix::</b>	Prefix for repeatable SQL migrations (default: <code>R</code> )
<b>baseline-on-migrate</b>	Only migrations above <b>baseline-version</b> will then be applied
<b>baseline-version</b>	Version to tag an existing schema with when executing baseline (default: 1)
<b>baseline-description</b>	Description to tag an existing schema with when executing baseline (default: <code>Flyway Baseline</code> )
<b>validate-on-migrate</b>	Validate the applied migrations against the available ones (default: <code>true</code> )

Multiple Datasources

To use multiple datasource in Flyway you just need to add the datasource name just after the `flyway` property:

```
quarkus.datasource.users.jdbc.url=jdbc:h2:tcp://localhost/mem:users
quarkus.datasource.inventory.jdbc.url=jdbc:h2:tcp://localhost/mem:inventory
# ...

quarkus.flyway.users.schemas=USERS_TEST_SCHEMA
quarkus.flyway.inventory.schemas=INVENTORY_TEST_SCHEMA
# ...
```

Liquibase

Quarkus integrates with Liquibase to help you on database schema migrations.

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-liquibase"
```

Then place changelog files to the (`src/main/resources/db`) folder.

You can inject `org.quarkus.liquibase.LiquibaseFactory` to programmatically execute the migration.

```
@Inject
LiquibaseFactory liquibaseFactory;

try (Liquibase liquibase = liquibaseFactory.createLiquibase
()) {
    ...
}
```

Or can be automatically executed by setting `migrate-at-start` property to `true`.

```
quarkus.liquibase.migrate-at-start=true
```

List of Liquibase parameters.

`quarkus.liquibase` as prefix is skipped in the next table.

**change-log**

The change log file. `XML`, `YAML` , `JSON`, `SQL` formats supported. (default: `db/changeLog.xml`)

**migrate-at-start**

The migrate at start flag. (default: `false`)

**validate-on-migrate**

The validate on update flag. (default: `false`)

**clean-at-start**

The clean at start flag. (default: `false`)

**contexts**

The list of contexts.

**labels**

The list of labels.

**database-change-log-table-name**

The database change log lock table name. (default: `DATABASECHANGELOG`)

**database-change-log-lock-table-name**

The database change log lock table name. (default: `DATABASECHANGELOGLOCK`)

**default-catalog-name**

The default catalog name.

**default-schema-name**

The default schema name.

**liquibase-catalog-name**

The liquibase tables catalog name.

**liquibase-schema-name**

The liquibase tables schema name.

**liquibase-tablespace-name**

The liquibase tables tablespace name.

**Multiple Datasources**

To use multiple datasource in Liquibase you just need to add the datasource name just after the `liquibase` property:

```
quarkus.datasource.users.jdbc.url=jdbc:h2:tcp://localhost/mem:users
quarkus.datasource.inventory.jdbc.url=jdbc:h2:tcp://localhost/mem:inventory
# ...

quarkus.liquibase.users.schemas=USERS_TEST_SCHEMA
quarkus.liquibase.inventory.schemas=INVENTORY_TEST_SCHEMA
# ...
```

**Hibernate Search**

Quarkus integrates with Elasticsearch to provide a full-featured full-text search using Hibernate Search API.

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-hibernate-search-elasticsearch"
```

You need to annotate your model with Hibernate Search API to index it:

```
@Entity
@Indexed
public class Author extends PanacheEntity {

    @FullTextField(analyzer = "english")
    public String bio;

    @FullTextField(analyzer = "name")
    @KeywordField(name = "firstName_sort",
        sortable = Sortable.YES,
        normalizer = "sort")
    public String firstName;

    @OneToMany
    @IndexedEmbedded
    public List<Book> books;

}
```

! It is not mandatory to use Panache.

You need to define the analyzers and normalizers defined in annotations. You only need to implement `ElasticsearchAnalysisConfigurer` interface and configure it.

```
public class MyQuarkusAnalysisConfigurer
    implements ElasticsearchAnalysisConfigurer {

    @Override
    public void configure(
        ElasticsearchAnalysisDefinitionContainerContext ctx)
    {
        ctx.analyzer("english").custom()
            .withTokenizer("standard")
            .withTokenFilters("asciifolding",
                "lowercase", "porter_stem");

        ctx.normalizer("sort").custom()
            .withTokenFilters("asciifolding", "lowercase");
    }
}
```

Use Hibernate Search in REST service:

```
public class LibraryResource {

    @Inject
    EntityManager em;

    @Transactional
    public List<Author> searchAuthors(
        @QueryParam("pattern") String pattern) {
        return Search.getSession(em)
            .search(Author.class)
            .predicate(f ->
                pattern == null || pattern.isEmpty() ?
                    f.matchAll() :
                    f.simpleQueryString()
                        .onFields("firstName",
                            "lastName", "books.title")
                        .matching(pattern)
                )
            .sort(f -> f.byField("lastName_sort")
                .then().byField("firstName_sort"))
            .fetchHits();
    }
}
```

! When not using Hibernate ORM, index data using `Search.getSession(em).createIndexer().startAndWait()` at startup time.

Configure the extension in `application.properties`:

```
quarkus.hibernate-search-elasticsearch.version=7
quarkus.hibernate-search-elasticsearch.
    analysis-configurer=MyQuarkusAnalysisConfigurer
quarkus.hibernate-search-elasticsearch.
    automatic-indexing.synchronization-strategy=searchable
quarkus.hibernate-search-elasticsearch.
    index-defaults.lifecycle.strategy=drop-and-create
quarkus.hibernate-search-elasticsearch.
    index-defaults.lifecycle.required-status=yellow
```

List of Hibernate-Elasticsearch properties prefixed with `quarkus.hibernate-search.elasticsearch:`

**backends**  
Map of configuration of additional backends.

**version**  
Version of Elasticsearch

**analysis-configurer**  
Class or name of the neab used to configure.

**hosts**  
List of Elasticsearch servers hosts.

**username**  
Username for auth.

**password**  
Password for auth.

**connection-timeout**  
Duration of connection timeout.

**max-connections**  
Max number of connections to servers.

**max-connections-per-route**  
Max number of connections to server.

**indexes**  
Per-index specific configuration.

**discovery.enabled**  
Enables automatic discovery.

**discovery.refresh-interval**  
Refresh interval of node list.

**discovery.default-scheme**  
Scheme to be used for the new nodes.

**automatic-indexing.synchronization-strategy**  
Status for which you wait before considering the operation completed (`queued`, `committed` or `searchable`).

**automatic-indexing.enable-dirty-check**  
When enabled, re-indexing of is skipped if the changes are on properties that are not used when indexing.

**index-defaults.lifecycle.strategy**  
Index lifecycle (`none`, `validate`, `update`, `create`, `drop-and-create`, `drop-abd-create-drop`)

**index-defaults.lifecycle.required-status**  
Minimal cluster status (`green`, `yellow`, `red`)

**index-defaults.lifecycle.required-status-wait-timeout**

Waiting time before failing the bootstrap.

**index-defaults.refresh-after-write**  
Set if index should be refreshed after writes.

Possible annotations:

**@Indexed**  
Register entity as full text index

**@FullTextField**  
Full text search. Need to set an analyzer to split tokens.

**@KeywordField**  
The string is kept as one single token but can be normalized.

**IndexedEmbedded**  
Include the Book fields into the Author index.

**@ContainerExtraction**  
Sets how to extract a value from container, e.g from a `Map`.

**@DocumentId**  
Map an unusual entity identifier to a document identifier.

**@GenericField**  
Full text index for any supported type.

**@IdentifierBridgeRef**  
Reference to the identifier bridge to use for a `@DocumentId`.

**@IndexingDependency**  
How a dependency of the indexing process to a property should affect automatic reindexing.

**@ObjectPath**

**@ScaledNumberField**  
For `java.math.BigDecimal` or `java.math.BigInteger` that you need higher precision.

## Amazon DynamoDB

Quarkus integrates with Amazon DynamoDB:

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-amazon-dynamodb"
```

```
@Inject
DynamoDbClient dynamoDB;
```

To use asynchronous client with Mutiny:

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-amazon-dynamodb, resteasy-mutiny"
```

```
@Inject
DynamoDbAsyncClient dynamoDB;

Uni.createFrom().completionStage(() -> dynamoDB.scan(scanRequest()))....
```

To use it as a local DynamoDB instance:

```
quarkus.dynamodb.region=
    eu-central-1
quarkus.dynamodb.endpoint-override=
    http://localhost:8000
quarkus.dynamodb.credentials.type=STATIC
quarkus.dynamodb.credentials.static-provider
    .access-key-id=test-key
quarkus.dynamodb.credentials.static-provider
    .secret-access-key=test-secret
```

If you want to work with an AWS account, you'd need to set it with:

```
quarkus.dynamodb.region=<YOUR_REGION>
quarkus.dynamodb.credentials.type=DEFAULT
```

**DEFAULT** credentials provider chain:

- System properties `aws.accessKeyId`, `aws.secretKey`

- Env. Variables `AWS_ACCESS_KEY_ID`, `AWS_SECRET_ACCESS_KEY`

- Credentials profile `~/.aws/credentials`

- Credentials through the Amazon EC2 container service if the `AWS_CONTAINER_CREDENTIALS_RELATIVE_URI` set

- Credentials through Amazon EC2 metadata service.

Configuration parameters prefixed with `quarkus.dynamodb:`

Parameter	Default	Description
<code>enable-endpoint-discovery</code>	<code>false</code>	Endpoint discovery for a service API that supports endpoint discovery.
<code>endpoint-override</code>		Configure the endpoint with which the SDK should communicate.
<code>api-call-timeout</code>		Time to complete an execution.
<code>interceptors</code>		List of class interceptors



Configuration parameters prefixed with `quarkus.dynamodb.aws:`

Parameter	Default	Description
<code>region</code>		Region that hosts DynamoDB.
<code>credentials.type</code>	DEFAULT	Credentials that should be used DEFAULT, STATIC, SYSTEM_PROPERTY, ENV_VARIABLE, PROFILE, CONTAINER, INSTANCE_PROFILE, PROCESS, ANONYMOUS

Credentials specific parameters prefixed with `quarkus.dynamodb.aws.credentials:`

Parameter	Default	Description
DEFAULT		
<code>default-provider.async-credential-update-enabled</code>	false	Should fetch credentials async.
<code>default-provider.reuse-last-provider-enabled</code>	true	Should reuse the last successful credentials.
STATIC		
<code>static-provider.access-key-id</code>		AWS access key id.
<code>static-provider.secret-access-key</code>		AWS secret access key.
PROFILE		
<code>profile-provider.profile-name</code>	default	The name of the profile to use.

PROCESS

Parameter	Default	Description
<code>process-provider.command</code>		Command to execute to retrieve credentials.
<code>process-provider.process-output-limit</code>	1024	Max bytes to retrieve from process.
<code>process-provider.credential-refresh-threshold</code>	PT15S	The amount of time between credentials expire and credentials refreshed.
<code>process-provider.async-credential-update-enabled</code>	false	Should fetch credentials async.

In case of synchronous client, the next parameters can be configured prefixed by `quarkus.dynamodb.sync-client:`

Parameter	Default	Description
<code>connection-acquisition-timeout</code>	10S	Connection acquisition timeout.
<code>connection-max-idle-time</code>	60S	Max time to connection to be opened.
<code>connection-timeout</code>		Connection timeout.
<code>connection-time-to-live</code>	0	Max time connection to be open.
<code>socket-timeout</code>	30S	Time to wait for data.
<code>max-connections</code>	50	Max connections.
<code>expect-continue-enabled</code>	true	Client send an HTTP expect-continue handshake.
<code>use-idle-connection-reaper</code>	true	Connections in pool should be closed asynchronously.
<code>proxy.endpoint</code>		Endpoint of the proxy server.

Parameter	Default	Description
<code>proxy.enabled</code>	false	Enables HTTP proxy.
<code>proxy.username</code>		Proxy username.
<code>proxy.password</code>		Proxy password.
<code>proxy.ntlm-domain</code>		For NTLM, domain name.
<code>proxy.ntlm-workstation</code>		For NTLM, workstation name.
<code>proxy.preemptive-basic-authentication-enabled</code>		Authenticate preemptively.
<code>proxy.non-proxy-hosts</code>		List of non proxy hosts.
<code>tls-managers-provider.type</code>	system-property	TLS manager: none, system-property, file-store
<code>tls-managers-provider.file-store.path</code>		Path to key store.
<code>tls-managers-provider.file-store.type</code>		Key store type.
<code>tls-managers-provider.file-store.password</code>		Key store password.

In case of asynchronous client, the next parameters can be configured prefixed by `quarkus.dynamodb.async-client:`

Parameter	Default	Description
<code>connection-acquisition-timeout</code>	10S	Connection acquisition timeout.
<code>connection-max-idle-time</code>	60S	Max time to connection to be opened.
<code>connection-timeout</code>		Connection timeout.

Parameter	Default	Description
connection-time-to-live	0	Max time connection to be open.
max-concurrency	50	Max number of concurrent connections.
use-idle-connection-reaper	true	Connections in pool should be closed asynchronously.
read-timeout	30S	Read timeout.
write-timeout	30S	Write timeout.
proxy.endpoint		Endpoint of the proxy server.
proxy.enabled	false	Enables HTTP proxy.
proxy.non-proxy-hosts		List of non proxy hosts.
tls-managers-provider.type	system-property	TLS manager: none, system-property, file-store
tls-managers-provider.file-store.path		Path to key store.
tls-managers-provider.file-store.type		Key store type.
tls-managers-provider.file-store.password		Key store password.
ssl-provider		SSL Provider (jdk, openssl, openssl-refcnt).
protocol	HTTP_1_1	Sets the HTTP protocol.
max-http2-streams		Max number of concurrent streams.

Parameter	Default	Description
event-loop.override	false	Enable custom event loop conf.
event-loop.number-of-threads		Number of threads to use in event loop.
event-loop.thread-name-prefix	aws-java-sdk-NettyEventLoop	Prefix of thread names.

## Neo4j

Quarkus integrates with Neo4j:

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-neo4j"
```

```
@Inject
org.neo4j.driver.Driver driver;
```

Configuration properties:

quarkus.neo4j as prefix is skipped in the next table.

Prefix is quarkus.neo4j.

**uri**  
URI of Neo4j. (default: localhost:7687)

**authentication.username**  
Username. (default: neo4j)

**authentication.password**  
Password. (default: neo4j)

**authentication.disabled**  
Disable authentication. (default: false)

**pool.metrics-enabled**  
Enable metrics. (default: false)

**pool.log-leaked-sessions**  
Enable leaked sessions logging. (default: `false`)

**pool.max-connection-pool-size**  
Max amount of connections. (default: 100)

**pool.max-connection-lifetime**  
Pooled connections older will be closed and removed from the pool. (default: 1H)

**pool.connection-acquisition-timeout**  
Timout for connection adquisition. (default: 1M)

**pool.idle-time-before-connection-test**  
Pooled connections idled in the pool for longer than this timeout will be tested before they are used. (default: -1)

As Neo4j uses SSL communication by default, to create a native executable you need to compile with next options GraalVM options:

```
-H:EnableURLProtocols=http,https --enable-all-security-services -H:+JNI
```

And Quarkus Maven Plugin with next configuration:

```
<artifactId>quarkus-maven-plugin</artifactId>
<executions>
  <execution>
    <id>native-image</id>
    <goals>
      <goal>native-image</goal>
    </goals>
    <configuration>
      <enableHttpUrlHandler>true
    </enableHttpUrlHandler>
      <enableHttpsUrlHandler>true
    </enableHttpsUrlHandler>
      <enableAllSecurityServices>true
    </enableAllSecurityServices>
      <enableJni>true</enableJni>
    </configuration>
  </execution>
</executions>
```

Alternatively, and as a not recommended way in production, you can disable SSL and Quarkus will disable Bolt SSL as well. quarkus.ssl.native=false.

If you are using Neo4j 4.0, you can use fully reactive. Add the next extension: quarkus-resteasy-mutiny.

```
@GET
public Publisher<String> get() {
    return Multi.createFrom().resource(driver::rxSession,
        session -> session.readTransaction(tx -> {
            RxResult result = tx.run("MATCH (f:Fruit) RETURN f.name as name");
            return Multi.createFrom().publisher(result.records())
                .map(record -> record.get("name").asString());
        })
    ).withFinalizer(session -> {
        return Uni.createFrom().publisher(session.close());
    });
}
```

MongoDB Client

Quarkus integrates with MongoDB:

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-mongodb-client"
```

```
@Inject
com.mongodb.client.MongoClient client;

@Inject
io.quarkus.mongodb.reactive.ReactiveMongoClient client;
```

INFO: Reactive client uses exposes Mutiny API.

```
quarkus.mongodb.connection-string=mongodb://localhost:27018
quarkus.mongodb.write-concern.journal=false
```

Multi MongoDB support

You can configure multiple MongoDB clients using same approach as with DataSource. The syntax is quarkus.mongodb.<optional name>.<property>:

```
quarkus.mongodb.users.connection-string = mongodb://mongo2:27017/userdb
quarkus.mongodb.inventory.connection-string = mongodb://mongo3:27017/invdb
```

Inject the instance using @io.quarkus.mongodb.runtime.MongoClientName annotation:

```
@Inject
@MongoClientName("users")
MongoClient mongoClient1;
```

quarkus.mongodb as prefix is skipped in the next table.

Parameter	Type	Description
connection-string	String	MongoDB connection URI.
hosts	List<String>	Addresses passed as host:port.
application-name	String	Application name.
max-pool-size	Int	Maximum number of connections.
min-pool-size	Int	Minimum number of connections.
max-connection-idle-time	Duration	Idle time of a pooled connection.
max-connection-life-time	Duration	Life time of pooled connection.
wait-queue-timeout	Duration	Maximum wait time for new connection.
maintenance-frequency	Duration	Time period between runs of maintenance job.
maintenance-initial-delay	Duration	Time to wait before running the first maintenance job.
wait-queue-multiple	Int	Multiplied with max-pool-size gives max numer of threads waiting.
connection-timeout	Duration	
socket-timeout	Duration	
tls-insecure	boolean [false]	Insecure TLS.
tls	boolean [false]	Enable TLS

Parameter	Type	Description
replica-set-name	String	Implies hosts given are a seed list.
server-selection-timeout	Duration	Time to wait for server selection.
local-threshold	Duration	Minimum ping time to make a server eligible.
heartbeat-frequency	Duration	Frequency to determine the state of servers.
read-preference	primary, primaryPreferred, secondary, secondaryPreferred, nearest	Read preferences.
max-wait-queue-size	Int	Max number of concurrent operations allowed to wait.
write-concern.safe	boolean [true]	Ensures are writes are ack.
write-concern.journal	boolean [true]	Journal writing aspect.
write-concern.w	String	Value to all write commands.
write-concern.retry-writes	boolean [false]	Retry writes if network fails.
write-concern.w-timeout	Duration	Timeout to all write commands.
credentials.username	String	Username.
credentials.password	String	Password.
credentials.auth-mechanism	MONGO-CR, GSSAPI, PLAIN, MONGODB-X509	



Parameter	Type	Description
credentials.auth-source	String	Source of the authentication credentials.
credentials.auth-mechanism-properties	Map<String, String>	Authentication mechanism properties.

## MongoDB Panache

You can also use the Panache framework to write persistence part when using MongoDB.

```
./mvnw quarkus:add-extension
-Dextensions="mongodb-panache"
```


MongoDB configuration comes from MongoDB Client section.

```
@MongoEntity(collection="ThePerson")
public class Person extends PanacheMongoEntity {
    public String name;

    @BsonProperty("birth")
    public LocalDate birthDate;

    public Status status;
}
```

Possible annotations in fields: `@BsonId` (for custom ID), `@BsonProperty` and `@BsonIgnore`.

 `@MongoEntity` is optional.

### Multi-tenancy with MongoDB Panache

```
@MongoEntity(collection = "TheBook", clientName = "client2",
    database = "database2")
```

Methods provided are similar of the ones shown in Persistence section.

```
person.persist();
person.update();
person.delete();
```

```
List<Person> allPersons = Person.listAll();
person = Person.findById(personId);
List<Person> livingPersons = Person.list("status", Status.Alive);
List<Person> persons = Person.list(Sort.by("name").and("birth"));
```

```
long updated = Person.update("name", "Mortal").where("status", Status.Alive);
```

```
long countAll = Person.count();
```

```
Person.deleteById(id);
Person.delete("status", Status.Alive);
```

All `list` methods have equivalent `stream` versions.

### Pagination

You can also use pagination:

```
PanacheQuery<Person> livingPersons =
    Person.find("status", Status.Alive);
livingPersons.page(Page.ofSize(25));
```

```
// get the first page
List<Person> firstPage = livingPersons.list();
// get the second page
List<Person> secondPage = livingPersons.nextPage().list();
```

### Range

```
PanacheQuery<Person> livingPersons = Person
    .find("status", Status.Alive);
List<Person> secondRange = livingPersons.range(25, 49).list();
```

You cannot mix pagination and range.

### Queries

Native MongoDB queries are supported (if they start with `{` or `org.bson.Document` instance) as well as Panache Queries. Panache Queries equivalence in MongoDB:

- `firstname = ?1 and status = ?2 → {'firstname': ?1, 'status': ?2}`
- `amount > ?1 and firstname != ?2 → {'amount': {'$gt': ?1}, 'firstname': {'$ne': ?2}}`
- `lastname like ?1 → {'lastname': {'$regex': ?1}}`
- `lastname is not null → {'lastname': {'$exists': true}}`



PanacheQL refers to the Object parameter name but native queries refer to MongoDB field names.

### Projection

Projection can be done for both PanacheQL and native queries.

```
import io.quarkus.mongodb.panache.ProjectionFor;

@ProjectionFor(Person.class) (1)
public class PersonName {
    public String name;
}

PanacheQuery<PersonName> shortQuery = Person.find("status ", Status.Alive).project(PersonName.class);
```

### 1 Entity class.

### DAO pattern

```
@ApplicationScoped
public class PersonRepository
    implements PanacheMongoRepository<Person> {
}
```

### Jandex

If entities are defined in external JAR, you need to enable in these projects the `Jandex` plugin in project.

```
<plugin>
  <groupId>org.jboss.jandex</groupId>
  <artifactId>jandex-maven-plugin</artifactId>
  <version>1.0.3</version>
  <executions>
    <execution>
      <id>make-index</id>
      <goals>
        <goal>jandex</goal>
      </goals>
    </execution>
  </executions>
  <dependencies>
    <dependency>
      <groupId>org.jboss</groupId>
      <artifactId>jandex</artifactId>
      <version>2.1.1.Final</version>
    </dependency>
  </dependencies>
</plugin>
```

### Reactive Panache

MongoDB with Panache allows using reactive implementation too by using `ReactivePanacheMongoEntity` or `ReactivePanacheMongoEntityBase` or `ReactivePanacheMongoRepository` or `ReactivePanacheMongoRepositoryBase` depending on your style.

```
public class ReactivePerson extends ReactivePanacheMongoEntity {  
    public String name;  
}
```

```
CompletionStage<Void> csl = person.persist();  
CompletionStage<List<ReactivePerson>> allPersons = ReactivePerson.listAll();  
Publisher<ReactivePerson> allPersons = ReactivePerson.streamAll();
```

```
Uni<List<PersonName>> persons = ReactivePersonEntity.find("lastname", name).project(PersonName.class).list();
```

## Reactive Programming

Quarkus implements MicroProfile Reactive spec and uses RXJava2 to provide reactive programming model.

```
./mvnw quarkus:add-extension  
-Dextensions="quarkus-smallrye-reactive-streams-operators"
```

Asynchronous HTTP endpoint is implemented by returning Java CompletionStage. You can create this class either manually or using MicroProfile Reactive Streams spec:

```
@GET  
@Path("/reactive")  
@Produces(MediaType.TEXT_PLAIN)  
public CompletionStage<String> getHello() {  
    return ReactiveStreams.of("h", "e", "l", "l", "o")  
        .map(String::toUpperCase)  
        .toList()  
        .run()  
        .thenApply(list -> list.toString());  
}
```

Creating streams is also easy, you just need to return Publisher object.

```
@GET  
@Path("/stream")  
@Produces(MediaType.SERVER_SENT_EVENTS)  
public Publisher<String> publishers() {  
    return Flowable  
        .interval(500, TimeUnit.MILLISECONDS)  
        .map(s -> atomicInteger.getAndIncrement())  
        .map(i -> Integer.toString(i));  
}
```

### Mutiny and JAX-RS

Apart from the CompletionStage support, there is also support for Mutiny.

```
./mvnw quarkus:add-extension  
-Dextensions="quarkus-resteasy-mutiny"
```

```
@GET  
@Produces(MediaType.TEXT_PLAIN)  
public Uni<String> hello() {  
    return Uni.createFrom().item(() -> "hello");  
}  
  
@GET  
@Produces(MediaType.TEXT_PLAIN)  
public Multi<String> multi() {  
    return Multi.createFrom().items("hello", "world");  
}
```

### Mutiny

Quarkus integrates with Mutiny as reactive programming library:

```
./mvnw quarkus:add-extension  
-Dextensions="mutiny"
```

```
@ApplicationScoped  
public static class ReactiveHello {  
  
    public Uni<String> greeting() {  
        return Uni.createFrom().item(() -> "hello")  
            .emitOn(Infrastructure.getDefaultExecutor());  
    }  
  
    public Multi<String> stream() {  
        return Multi.createFrom().items("hello", "world")  
            .emitOn(Infrastructure.getDefaultExecutor());  
    }  
}
```

Converting from/to RxJava2 or Reactor APIs:

#### RxJava 2

```
<dependency>  
    <groupId>io.smallrye.reactive</groupId>  
    <artifactId>mutiny-rxjava</artifactId>  
</dependency>
```

From RxJava2:

```
Uni<Void> uniFromCompletable = Uni.createFrom()
    .converter(UniRxConverters.fromCompletable(), completable);
Uni<String> uniFromSingle = Uni.createFrom()
    .converter(UniRxConverters.fromSingle(), single);
Uni<String> uniFromObservable = Uni.createFrom()
    .converter(UniRxConverters.fromObservable(), observable);
Uni<String> uniFromFlowable = Uni.createFrom()
    .converter(UniRxConverters.fromFlowable(), flowable);
...

Multi<Void> multiFromCompletable = Multi.createFrom()
    .converter(MultiRxConverters.fromCompletable(), completable);
Multi<String> multiFromObservable = Multi.createFrom()
    .converter(MultiRxConverters.fromObservable(), observable);
Multi<String> multiFromFlowable = Multi.createFrom()
    .converter(MultiRxConverters.fromFlowable(), flowable);
...
```

To `RxJava2`:

```
Completable completable = uni.convert().with(UniRxConverters.toCompletable());
Single<Optional<String>> single = uni.convert().with(UniRxConverters.toSingle());
Observable<String> observable = uni.convert().with(UniRxConverters.toObservable());
Flowable<String> flowable = uni.convert().with(UniRxConverters.toFlowable());
...

Completable completable = multi.convert().with(MultiRxConverters.toCompletable());
Single<Optional<String>> single = multi.convert().with(MultiRxConverters.toSingle());
Observable<String> observable = multi.convert().with(MultiRxConverters.toObservable());
Flowable<String> flowable = multi.convert().with(MultiRxConverters.toFlowable());
...
```

Reactor API

```
<dependency>
  <groupId>io.smallrye.reactive</groupId>
  <artifactId>mutiny-reactor</artifactId>
</dependency>
```

From `Reactor`:

```
Uni<String> uniFromMono = Uni.createFrom().converter(UniReactorConverters.fromMono(), mono);
Uni<String> uniFromFlux = Uni.createFrom().converter(UniReactorConverters.fromFlux(), flux);
Multi<String> multiFromMono = Multi.createFrom().converter(MultiReactorConverters.fromMono(), mono);
Multi<String> multiFromFlux = Multi.createFrom().converter(MultiReactorConverters.fromFlux(), flux);
```

To `Reactor`:

```
Mono<String> mono = uni.convert().with(UniReactorConverters.toMono());
Flux<String> flux = uni.convert().with(UniReactorConverters.toFlux());

Mono<String> mono2 = multi.convert().with(MultiReactorConverters.toMono());
Flux<String> flux2 = multi.convert().with(MultiReactorConverters.toFlux());
```

CompletionStages or Publisher

```
CompletableFuture<String> future = Uni
    .createFrom().completionStage(CompletableFuture.supplyAsync(() -> "hello"));

CompletionStage<String> cs = Uni
    .createFrom().subscribeAsCompletionStage();
```

`Multi` implements `Publisher`.

Reactive Messaging

Quarkus relies on `MicroProfile Reactive Messaging spec` to implement reactive messaging streams.

```
mvn quarkus:add-extension
-Dextensions="io.quarkus:quarkus-smallrye-reactive-messaging"
```

You can just start using in-memory streams by using `@Incoming` to produce data and `@Outgoing` to consume data.

Produce every 5 seconds one piece of data.

```
@ApplicationScoped
public class ProducerData {

    @Outgoing("my-in-memory")
    public Flowable<Integer> generate() {
        return Flowable.interval(5, TimeUnit.SECONDS)
            .map(tick -> random.nextInt(100));
    }
}
```

or in `Mutiny`:

```
@ApplicationScoped
public class ProducerData {
    @Outgoing("my-in-memory")
    public Multi<Integer> generate() {
        return Multi.createFrom().ticks().every(Duration.ofSeconds(5))
            .onItem().apply(n -> random.nextInt(100));
    }
}
```

If you want to dispatch to all subscribers you can annotate the method with `@Broadcast`.

Consumes generated data from `my-in-memory` stream.

```
@ApplicationScoped
public class ConsumerData {
    @Incoming("my-in-memory")
    public void randomNumber(int randomNumber) {
        System.out.println("Received " + randomNumber);
    }
}
```

You can also inject an stream as a field:

```
@Inject
@Stream("my-in-memory") Publisher<Integer> randomNumbers;
```

```
@Inject @Stream("generated-price")
Emitter<String> emitter;
```

Patterns

*REST API* → *Message*

```
@Inject @Stream("in")
Emitter<String> emitter;

emitter.send(message);
```

*Message* → *Message*

```
@Incoming("in")
@Outgoing("out")
public String process(String in) {
}
```

*Message* → *SSE*



```
@Inject @Stream("out")
Publisher<String> result;

@GET
@Produces(SERVER_SENT_EVENTS)
public Publisher<String> stream() {
    return result;
}
```

Message → Business Logic

```
@ApplicationScoped
public class ReceiverMessages {
    @Incoming("prices")
    public void print(String price) {
    }
}
```

To indicate that the method should be executed on a worker pool you can use `@Blocking`:

```
@Outgoing("Y")
@Incoming("X")
@Blocking
```

To customize:

```
@Blocking(value="my-custom-pool", ordered = false)
```

```
smallrye.messaging.worker.my-custom-pool.max-concurrency=3
```

Possible implementations are:

In-Memory

If the stream is not configured then it is assumed to be an in-memory stream, if not then stream type is defined by `connector` field.

Kafka

To integrate with Kafka you need to add next extensions:

```
mvn quarkus:add-extension
-Dextensions="
    io.quarkus:quarkus-smallrye-reactive-messaging-kafka"
```

Then `@Outgoing`, `@Incoming` or `@Stream` can be used.

Kafka configuration schema: `mp.messaging.[outgoing|incoming].{stream-name}.<property>=<value>`.

The `connector` type is `smallrye-kafka`.

```
mp.messaging.outgoing.generated-price.connector=
    smallrye-kafka
mp.messaging.outgoing.generated-price.topic=
    prices
mp.messaging.outgoing.generated-price.bootstrap.servers=
    localhost:9092
mp.messaging.outgoing.generated-price.value.serializer=
    org.apache.kafka.common.serialization.IntegerSerializer

mp.messaging.incoming.prices.connector=
    smallrye-kafka
mp.messaging.incoming.prices.value.deserializer=
    org.apache.kafka.common.serialization.IntegerDeserializer
```

A complete list of supported properties are in Kafka site. For the producer and for consumer

JSON-B Serializer/Deserializer

You can use JSON-B to serialize/deserialize objects.

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-kafka-client"
```

To serialize you can use `io.quarkus.kafka.client.serialization.JsonbSerializer`.

To deserialize you need to extend and provide a type. `io.quarkus.kafka.client.serialization.JsonbDeserializer`

```
public class BeerDeserializer
    extends JsonbDeserializer<Beer> {

    public BeerDeserializer() {
        super(Beer.class);
    }

}
```

AMQP

To integrate with AMQP you need to add next extensions:

```
./mvnw quarkus:add-extension
-Dextensions="reactive-messaging-amqp"
```

Then `@Outgoing`, `@Incoming` or `@Stream` can be used.

AMQP configuration schema: `mp.messaging.[outgoing|incoming].{stream-name}.<property>=<value>`. Special properties `amqp-username` and `amqp-password` are used to configure AMQP broker credentials.

The connector type is `smallrye-amqp`.

```
amqp-username=quarkus
amqp-password=quarkus
# write
mp.messaging.outgoing.generated-price.connector=
    smallrye-amqp
mp.messaging.outgoing.generated-price.address=
    prices
mp.messaging.outgoing.generated-price.durable=
    true
# read
mp.messaging.incoming.prices.connector=
    smallrye-amqp
mp.messaging.incoming.prices.durable=
    true
```

A complete list of supported properties for AMQP.

MQTT

To integrate with MQTT you need to add next extensions:

```
./mvnw quarkus:add-extension
-Dextensions="vertx, smallrye-reactive-streams-operator
    smallrye-reactive-messaging"
```

And add `io.smallrye.reactive:smallrye-reactive-messaging-mqtt-1.0:0.0.10` dependency in your build tool.

Then `@Outgoing`, `@Incoming` or `@Stream` can be used.

MQTT configuration schema: `mp.messaging.[outgoing|incoming].{stream-name}.<property>=<value>`.

The connector type is `smallrye-mqtt`.

```
mp.messaging.outgoing.topic-price.type=
    smallrye-mqtt
mp.messaging.outgoing.topic-price.topic=
    prices
mp.messaging.outgoing.topic-price.host=
    localhost
mp.messaging.outgoing.topic-price.port=
    1883
mp.messaging.outgoing.topic-price.auto-generated-client-id=
    true

mp.messaging.incoming.prices.type=
    smallrye-mqtt
mp.messaging.incoming.prices.topic=
    prices
mp.messaging.incoming.prices.host=
    localhost
mp.messaging.incoming.prices.port=
    1883
mp.messaging.incoming.prices.auto-generated-client-id=
    true
```

Kafka Streams

Create streaming queries with the Kafka Streams API.

```
./mvnw quarkus:add-extension
-Dextensions="kafka-streams"
```

All we need to do for that is to declare a CDI producer method which returns the Kafka Streams `org.apache.kafka.streams.Topology`:

```
@ApplicationScoped
public class TopologyProducer {
    @Produces
    public Topology buildTopology() {
        org.apache.kafka.streams.StreamsBuilder.StreamsBuilder
            builder = new StreamsBuilder();
        // ...
        builder.stream()
            .join()
            // ...
            .toStream()
            .to();
        return builder.build();
    }
}
```

Previous example produces content to another stream. If you want to write interactive queries, you can use Kafka streams.

```
@Inject
KafkaStreams streams;

return streams
    .store("stream", QueryableStoreTypes.keyValueStore
());
```

The Kafka Streams extension is configured via the Quarkus configuration file `application.properties`.

```
quarkus.kafka-streams.bootstrap-servers=localhost:9092
quarkus.kafka-streams.application-id=temperature-aggregator
quarkus.kafka-streams.application-server=${hostname}:8080
quarkus.kafka-streams.topics=weather-stations,temperature-values

kafka-streams.cache.max.bytes.buffering=10240
kafka-streams.commit.interval.ms=1000
```

**IMPORTANT:** All the properties within the `kafka-streams` namespace are passed through as-is to the Kafka Streams engine. Changing their values requires a rebuild of the application.

## Reactive PostgreSQL Client

You can use Reactive PostgreSQL to execute queries to PostgreSQL database in a reactive way, instead of using JDBC way.

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-reactive-pg-client"
```

Database configuration is the same as shown in Persistence section, but URL is different as it is not a *jdbc*.

```
quarkus.datasource.db-kind=postgresql
quarkus.datasource.reactive.url=postgresql:///your_database
```

Then you can inject `io.vertx.mutiny.pgclient.PgPool` class.

```
@Inject
PgPool client;

Uni<List<Fruit>> fruits =
    client.preparedQuery("SELECT * FROM fruits")
        .onItem().apply(rowSet -> {
            JSONArray jsonArray = new JSONArray();
            for (Row row : rowSet) {
                jsonArray.add(from(row));
            }
            return jsonArray;
        })
```

## Reactive MySQL Client

You can use Reactive MySQL to execute queries to MySQL database in a reactive way, instead of using JDBC way.

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-reactive-mysql-client"
```

Database configuration is the same as shown in Persistence section, but URL is different as it is not a *jdbc*.

```
quarkus.datasource.db-kind=mysql
quarkus.datasource.reactive.url=mysql:///your_database
```

Then you can inject `io.vertx.mutiny.mysqlclient.MySQLPool` class.

## ActiveMQ Artemis

Quarkus uses Reactive Messaging to integrate with messaging systems, but in case you need deeper control when using Apache ActiveMQ Artemis there is also an extension:

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-artemis-core"
```

And then you can inject `org.apache.activemq.artemis.api.core.client.ServerLocator` instance.

```
@ApplicationScoped
public class ArtemisConsumerManager {

    @Inject
    ServerLocator serverLocator;

    private ClientSessionFactory connection;

    @PostConstruct
    public void init() throws Exception {
        connection = serverLocator.createSessionFactory();
    }
}
```

And configure `ServerLocator` in `application.properties`:

```
quarkus.artemis.url=tcp://localhost:61616
```

You can configure ActiveMQ Artemis in `application.properties` file by using next properties prefixed with `quarkus`:

`artemis.url`  
Connection URL.

`artemis.username`  
Username for authentication.

`artemis.password`  
Password for authentication.

### Artemis JMS

If you want to use JMS with Artemis, you can do it by using its extension:

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-artemis-jms"
```

And then you can inject `javax.jms.ConnectionFactory`:

```
@ApplicationScoped
public class ArtemisConsumerManager {

    @Inject
    ConnectionFactory connectionFactory;

    private Connection connection;

    @PostConstruct
    public void init() throws JMSException {
        connection = connectionFactory.createConnection();
        connection.start();
    }
}
```



Configuration options are the same as Artemis core.

## Vert.X Reactive Clients

Vert.X Reactive clients in Quarkus, the next clients are supported and you need to add the dependency to use them:

### Vert.X Mail Client

```
io.smallrye.reactive:smallrye-mutiny-vertx-mail-client
```

### Vert.X MongoDB Client

```
io.smallrye.reactive:smallrye-mutiny-vertx-mongo-client
```

### Vert.X Redis Client

```
io.smallrye.reactive:smallrye-mutiny-vertx-redis-client
```

### Vert.X Cassandra Client

```
io.smallrye.reactive:smallrye-mutiny-vertx-cassandra-client
```

### Vert.X Consul Client

```
io.smallrye.reactive:smallrye-mutiny-vertx-consul-client
```

### Vert.X Kafka Client

```
io.smallrye.reactive:smallrye-mutiny-vertx-kafka-client
```

### Vert.X AMQP Client

```
io.smallrye.reactive:smallrye-mutiny-vertx-amqp-client
```

### Vert.X RabbitMQ Client

```
io.smallrye.reactive:smallrye-mutiny-vertx-rabbitmq-client
```

Example of Vert.X Web Client:

```
@Inject
Vertx vertx;

private WebClient client;

@PostConstruct
void initialize() {
    this.client = WebClient.create(vertx, ...);
}
```

## RBAC

You can set RBAC using annotations or in `application.properties`.

### Annotations

You can define roles by using `javax.annotation.security.RolesAllowed` annotation.

```
@RolesAllowed("Subscriber")
```

You can use `io.quarkus.security.Authenticated` as a shortcut of `@RolesAllowed("*")`.

To alter RBAC behaviour there are two configuration properties:

```
quarkus.security.deny-unannotated=true
```

Configuration options:

**quarkus.jaxrs.deny-uncovered**

If true denies by default to all JAX-RS endpoints. (default: `false`)

**quarkus.security.deny-unannotated**

If true denies by default all CDI methods and JAX-RS endpoints. (default: `false`)

### File Configuration

Defining RBAC in `application.properties` instead of using annotations.

```
quarkus.http.auth.policy.role-policy1.roles-allowed=
    user,admin
quarkus.http.auth.permission.roles1.paths=
    /roles-secured*/,/other*/,/api/*
quarkus.http.auth.permission.roles1.policy=
    role-policy1
```

```
quarkus.http.auth.permission.permit1.paths=
    /public/*
quarkus.http.auth.permission.permit1.policy=
    permit
quarkus.http.auth.permission.permit1.methods=
    GET
```

```
quarkus.http.auth.permission.deny1.paths=
    /forbidden
quarkus.http.auth.permission.deny1.policy=
    deny
```

You need to provide permissions set by using the `roles-allowed` property or use the built-in ones `deny`, `permit` OR `authenticated`.

## JWT

Quarkus implements MicroProfile JWT RBAC spec.

```
mvn quarkus:add-extension
-Dextensions="io.quarkus:quarkus-smallrye-jwt"
```

Minimum JWT required claims: `typ`, `alg`, `kid`, `iss`, `sub`, `exp`, `iat`, `jti`, `upn`, `groups`.

You can inject token by using `JsonWebToken` or a claim individually by using `@Claim`.

```
@Inject
JsonWebToken jwt;

@Inject
@Claim(standard = Claims.preferred_username)
String name;

@Inject
@Claim("groups")
Set<String> groups;
```

Set of supported types: `String`, `Set<String>`, `Long`, `Boolean`, `javax.json.JsonValue`, `Optional`, `org.eclipse.microprofile.jwt.ClaimValue`.

And configuration in `src/main/resources/application.properties`:

```
mp.jwt.verify.publickey.location=
    META-INF/resources/publicKey.pem
mp.jwt.verify.issuer=
    https://quarkus.io/using-jwt-rbac
```

Configuration options:

**mp.jwt.verify.publickey**

Public Key text itself to be supplied as a string.

`mp.jwt.verify.publickey.location` Relative path or URL of a public key.

**mp.jwt.verify.issuer**

`iss` accepted as valid.

**smallrye.jwt.token.header**

Sets header such as `Cookie` is used to pass the token. (default: `Authorization`).

**smallrye.jwt.token.cookie**

Name of the cookie containing a token.



Comma-separated list containing an alternative single or multiple schemes. (default: `Bearer`).

`smallrye.jwt.require.named-principal`

A token must have a upn or preferred\_username or sub claim set if using `java.security.Principal.True` makes throw an exception if not set. (default: `false`).

`smallrye.jwt.path.sub`

Path to the claim with subject name.

`smallrye.jwt.claims.sub`

Default sub claim value.

`smallrye.jwt.path.groups`

Path to the claim containing the groups.

`smallrye.jwt.groups-separator`

Separator for splitting a string which may contain multiple group values. (default: ```).

`smallrye.jwt.claims.groups`

Default groups claim value.

`smallrye.jwt.jwks.refresh-interval`

JWK cache refresh interval in minutes. (default: `60`).

`smallrye.jwt.expiration.grace`

Expiration grace in seconds. (default: `60`).

`smallrye.jwt.verify.aud`

Comma separated list of the audiences that a token aud claim may contain.

`smallrye.jwt.verify.algorithm`

Signature algorithm. (defsult: `RS256`)

`smallrye.jwt.token.kid`

If set then the verification JWK key as well every JWT token must have a matching `kid` header.

`smallrye.jwt.time-to-live`

The maximum number of seconds that a JWT may be issued for use.

Supported public key formats:

- PKCS#8 PEM
- JWK
- JWKS
- JWK Base64 URL
- JWKS Base64 URL

To send a token to server-side you should use `Authorization` header: `curl -H "Authorization: Bearer eyJraWQiOi..."`.

To inject claim values, the bean must be `@RequestScoped` CDI scoped. If you need to inject claim values in scope with a lifetime greater than `@RequestScoped` then you need to use `javax.enterprise.inject.Instance` interface.

```
@Inject
@Claim(standard = Claims.iat)
private Instance<Long> providerIAT;
```

## RBAC

JWT `groups` claim is directly mapped to roles to be used in security annotations.

```
@RolesAllowed("Subscriber")
```

## Generate tokens

JWT generation API:

```
Jwt.claims()
    .issuer("https://server.com")
    .claim("customClaim", 3)
    .sign(createKey());

JwtSignatureBuilder jwtSignatureBuilder = Jwt.claims("/test
JsonToken.json").jws();
jwtSignatureBuilder
    .signatureKeyId("some-key-id")
    .signatureAlgorithm(SignatureAlgorithm.ES256)
    .header("custom-header", "custom-value");
    .sign(createKey());

Jwt.claims("/testJsonToken.json")
    .encrypt(createKey());

JwtEncryptionBuilder jwtEncryptionBuilder = Jwt.claims("/te
stJsonToken.json").jwe();
jwtEncryptionBuilder
    .keyEncryptionKeyId("some-key-id")
    .keyEncryptionAlgorithm(KeyEncryptionAlgorithm.ECDH_E
S_A256KW)
    .header("custom-header", "custom-value");
    .encrypt(createKey());

Jwt.claims("/testJsonToken.json")
    .innerSign(createKey());
    .encrypt(createKey());
```

## OpenId Connect

Quarkus can use OpenId Connect or OAuth 2.0 authorization servers such as Keycloak to protect resources using bearer token issued by Keycloak server.

```
mvn quarkus:add-extension
-Dextensions="using-openid-connect"
```

You can also protect resources with security annotations.

```
@GET
@RolesAllowed("admin")
```

Configure application to Keycloak service in `application.properties` file.

```
quarkus.oidc.realm=quarkus
quarkus.oidc.auth-server-url=http://localhost:8180/auth
quarkus.oidc.resource=backend-service
quarkus.oidc.bearer-only=true
quarkus.oidc.credentials.secret=secret
```

Configuration options with `quarkus.oidc` prefix:

`enabled`

The OIDC is enabled. (default: `true`)

`tenant-enabled`

If the tenant configuration is enabled. (default: `true`)

`application-type`

The application type. Possible values: `web_app`, `service`. (default: `service`)

`connection-delay`

The maximum amount of time the adapter will try connecting.

`auth-server-url`

The base URL of the OpenID Connect (OIDC) server.

`introspection-path`

Relative path of the RFC7662 introspection service.

`jwks-path`

Relative path of the OIDC service returning a JWK set.

`public-key`

Public key for the local JWT token verification

`client-id`

The client-id of the application.

`roles.role-claim-path`

Path to the claim containing an array of groups. (`realm/groups`)

`roles.role-claim-separator`

Separator for splitting a string which may contain multiple group values.


`token.issuer`

Issuer claim value.


`token.audience`

Audience claim value

<code>token.expiration-grace</code>	Expiration grace period in seconds.
<code>token.principal-claim</code>	Name of the claim which contains a principal name.
<code>credentials.secret</code>	The client secret
<code>authentication.redirect-path</code>	Relative path for calculating a <code>redirect_uri</code> query parameter.
<code>authentication.restore-path-after-redirect</code>	The original request URI used before the authentication will be restored after the user has been redirected back to the application. (default: <code>true</code> )
<code>authentication.scopes</code>	List of scopes.
<code>authentication.extra-params</code>	Additional properties which will be added as the query parameters .
<code>authentication.cookie-path</code>	Cookie path parameter.
<code>proxy.host</code>	The host (name or IP address) of the Proxy.
<code>proxy.port</code>	The port number of the Proxy. (default: <code>80</code> )
<code>proxy.username</code>	The username to authenticate.
<code>proxy.password</code>	The password to authenticate.



With `Keycloak` `OIDC` server `https://host:port/auth/realms/{realm}` where `{realm}` has to be replaced by the name of the Keycloak realm.



You can use `quarkus.http.cors` property to enable consuming form different domain.

### Multi-tenancy

Multi-tenancy is supported by adding a sub-category to `OIDC` configuration properties (ie `quarkus.oidc.{tenant_id}.property`).

```
quarkus.oidc.auth-server-url=http://localhost:8180/auth/realm/quarkus
quarkus.oidc.client-id=multi-tenant-client
quarkus.oidc.application-type=web-app

quarkus.oidc.tenant-b.auth-server-url=https://accounts.google.com
quarkus.oidc.tenant-b.application-type=web-app
quarkus.oidc.tenant-b.client-id=xxxx
quarkus.oidc.tenant-b.credentials.secret=yyyy
quarkus.oidc.tenant-b.token.issuer=https://accounts.google.com
quarkus.oidc.tenant-b.authentication.scopes=email,profile,openid
```

## OAuth2

Quarkus integrates with `OAuth2` to be used in case of opaque tokens (none `JWT`) and its validation against an introspection endpoint.

```
mvn quarkus:add-extension
-Dextensions="security-oauth2"
```

And configuration in `src/main/resources/application.properties`:

```
quarkus.oauth2.client-id=client_id
quarkus.oauth2.client-secret=secret
quarkus.oauth2.introspection-url=http://oauth-server/introspect
```

And you can map roles to be used in security annotations.

```
@RolesAllowed("Subscriber")
```

Configuration options:

`quarkus.oauth2.enabled`  
Determine if the `OAuth2` extension is enabled. (default: `true`)

`quarkus.oauth2.client-id`  
The `OAuth2` client id used to validate the token.

`quarkus.oauth2.client-secret`  
The `OAuth2` client secret used to validate the token.

`quarkus.oauth2.introspection-url`  
URL used to validate the token and gather the authentication claims.

`quarkus.oauth2.role-claim`  
The claim that is used in the endpoint response to load the roles ((default: `scope`)

## Authenticating via HTTP

`HTTP` basic auth is enabled by the `quarkus.http.auth.basic=true` property.

`HTTP` form auth is enabled by the `quarkus.http.auth.form.enabled=true` property.

Then you need to add `elytron-security-properties-file` or `elytron-security-jdbc`.

## Security with Properties File

You can also protect endpoints and store identities (user, roles) in the file system.

```
mvn quarkus:add-extension
-Dextensions="elytron-security-properties-file"
```

You need to configure the extension with users and roles files:

And configuration in `src/main/resources/application.properties`:

```
quarkus.security.users.file.enabled=true
quarkus.security.users.file.users=test-users.properties
quarkus.security.users.file.roles=test-roles.properties
quarkus.security.users.file.auth-mechanism=BASIC
quarkus.security.users.file.realm-name=MyRealm
quarkus.security.users.file.plain-text=true
```

Then `users.properties` and `roles.properties`:

```
scott=jb0ss
jdoe=p4ssw0rd
```

```
scott=Admin,admin,Tester,user
jdoe=NoRolesUser
```

**IMPORTANT:** If `plain-text` is set to `false` (or omitted) then passwords must be stored in the form MD5 (`username:`realm`:`password``).

Elytron File Properties configuration properties. Prefix `quarkus.security.users` is skipped.

<code>file.enabled</code>	The file realm is enabled. (default: <code>false</code> )
<code>file.auth-mechanism</code>	The authentication mechanism. ( default: <code>BASIC</code> )
<code>file.realm-name</code>	The authentication realm name. (default: <code>Quarkus</code> )
<code>file.plain-text</code>	If passwords are in plain or in MD5. (default: <code>false</code> )
<code>file.users</code>	Classpath resource of user/password. (default: <code>users.properties</code> )
<code>file.roles</code>	Classpath resource of user/role. (default: <code>roles.properties</code> )

Embedded Realm

You can embed user/password/role in the same application.properties:

```
quarkus.security.users.embedded.enabled=true
quarkus.security.users.embedded.plain-text=true
quarkus.security.users.embedded.users.scott=jb0ss
quarkus.security.users.embedded.roles.scott=admin,tester,user
quarkus.security.users.embedded.auth-mechanism=BASIC
```

**IMPORTANT:** If `plain-text` is set to `false` (or omitted) then passwords must be stored in the form MD5 (`username:`realm`:`password``).

Prefix `quarkus.security.users.embedded` is skipped.

<code>file.enabled</code>	The file realm is enabled. (default: <code>false</code> )
<code>file.auth-mechanism</code>	The authentication mechanism. (default: <code>BASIC</code> )
<code>file.realm-name</code>	The authentication realm name. (default: <code>Quarkus</code> )
<code>file.plain-text</code>	If passwords are in plain or in MD5. (default: <code>false</code> )
<code>file.users.*</code>	* is user and value is password.

<code>file.roles.*</code>	* is user and value is role.
---------------------------	------------------------------

Security with a JDBC Realm

You can also protect endpoints and store identities in a database.

```
mvn quarkus:add-extension
-Dextensions="elytron-security-jdbc"
```

You still need to add the database driver (ie `jdbc-h2`).

You need to configure JDBC and Elytron JDBC Realm:

```
quarkus.datasource.url=
quarkus.datasource.driver=org.h2.Driver
quarkus.datasource.username=sa
quarkus.datasource.password=sa

quarkus.security.jdbc.enabled=true
quarkus.security.jdbc.principal-query.sql=
    SELECT u.password, u.role FROM test_user u WHERE u.user
=?
quarkus.security.jdbc.principal-query
    .clear-password-mapper.enabled=true
quarkus.security.jdbc.principal-query
    .clear-password-mapper.password-index=1
quarkus.security.jdbc.principal-query
    .attribute-mappings.0.index=2
quarkus.security.jdbc.principal-query
    .attribute-mappings.0.to=groups
```

You need to set the index (1-based) of password and role.

Elytron JDBC Realm configuration properties. Prefix `quarkus.security.jdbc` is skipped.

<code>auth-mechanism</code>	The authentication mechanism. (default: <code>BASIC</code> )
<code>realm-name</code>	The authentication realm name. (default: <code>Quarkus</code> )
<code>enabled</code>	If the properties store is enabled. (default: <code>false</code> )
<code>principal-query.sql</code>	The sql query to find the password.
<code>principal-query.datasource</code>	The data source to use.
<code>principal-query.clear-password-mapper.enabled</code>	If the clear-password-mapper is enabled. (default: <code>false</code> )
<code>principal-query.clear-password-mapper.password-index</code>	The index of column containing clear password. (default: <code>1</code> )

<code>principal-query.bcrypt-password-mapper.enabled</code>	If the bcrypt-password-mapper is enabled. (default: <code>false</code> )
---	--

<code>principal-query.bcrypt-password-mapper.password-index</code>	The index of column containing password hash. (default: <code>0</code> )
--	--

<code>principal-query.bcrypt-password-mapper.hash-encoding</code>	A string referencing the password hash encoding ( <code>BASE64</code> or <code>HEX</code> ). (default: <code>BASE64</code> )
---	--

<code>principal-query.bcrypt-password-mapper.salt-index</code>	The index column containing the Bcrypt salt. (default: <code>0</code> )
--	---

<code>principal-query.bcrypt-password-mapper.salt-encoding</code>	A string referencing the salt encoding ( <code>BASE64</code> or <code>HEX</code> ). (default: <code>BASE64</code> )
---	---

<code>principal-query.bcrypt-password-mapper.iteration-count-index</code>	The index column containing the Bcrypt iteration count. (default: <code>0</code> )
---	--

For multiple datasources you can use the datasource name in the properties:


```
quarkus.datasource.url=
quarkus.security.jdbc.principal-query.sql=

quarkus.datasource.permissions.url=
quarkus.security.jdbc.principal-query.permissions.sql=
```

Security with JPA

You can also protect endpoints and store identities in a database using JPA.

```
mvn quarkus:add-extension
-Dextensions="security-jpa"
```



Also you might require `jdbc-postgresql`, `resteasy`, `hibernate-orm-panache`.



```
@io.quarkus.security.jpa.UserDefinition
@Table(name = "test_user")
@Entity
public class User extends PanacheEntity {
    @io.quarkus.security.Username
    public String name;

    @io.quarkus.security.Password
    public String pass;

    @ManyToMany
    @Roles
    public List<Role> roles = new ArrayList<>();

    public static void add(String username, String password) {
        User user = new User();
        user.username = username;
        user.password = BcryptUtil.bcryptHash(password);
        user.persist();
    }
}

@Entity
public class Role extends PanacheEntity {

    @ManyToMany(mappedBy = "roles")
    public List<ExternalRolesUserEntity> users;

    @io.quarkus.security.RolesValue
    public String role;
}
```

You need to configure JDBC:

```
quarkus.datasource.url=jdbc:postgresql:security_jpa
quarkus.datasource.driver=org.postgresql.Driver
quarkus.datasource.username=quarkus
quarkus.datasource.password=quarkus

quarkus.hibernate-orm.database.generation=drop-and-create
```

## Security with LDAP

You can also protect endpoints and store identities in a database using LDAP.

```
mvn quarkus:add-extension
-Dextensions="elytron-security-ldap"
```

```
quarkus.security.ldap.enabled=true
quarkus.security.ldap.dir-context.principal=uid=tool,ou=accounts,o=YourCompany,c=DE
quarkus.security.ldap.dir-context.url=ldaps://ldap.server.local
quarkus.security.ldap.dir-context.password=PASSWORD
quarkus.security.ldap.identity-mapping.rdn-identifier=uid
quarkus.security.ldap.identity-mapping.search-base-dn=ou=users,ou=tool,o=YourCompany,c=DE
quarkus.security.ldap.identity-mapping.attribute-mappings."0".from=cn
quarkus.security.ldap.identity-mapping.attribute-mappings."0".to=groups
quarkus.security.ldap.identity-mapping.attribute-mappings."0".filter=(member=uid={0})
quarkus.security.ldap.identity-mapping.attribute-mappings."0".filter-base-dn=ou=roles,ou=tool,o=YourCompany,c=DE
```

### Testing

There is a Quarkus Test Resource that starts and stops InMemory LDAP server before and after test suite. It is running in localhost with dc=quarkus,dc=io and binding credentials ("uid=admin,ou=system", "secret"). Imports *LDIF* from a file located at root of the classpath named quarkus-io.ldif.

Register dependency io.quarkus:quarkus-test-ldap:test.

And annotate the test:

```
@QuarkusTestResource(io.quarkus.test.ldap.LdapServerTestResource.class)
public class ElytronLdapExtensionTestResources {
}
```

Elytron LDAP Realm configuration properties. Prefix quarkus.security.ldap is skipped.

<b>enabled</b>	Enable the LDAP elytron module (default: false)
<b>realm-name</b>	The elytron realm name (default: Quarkus)
<b>direct-verification</b>	Provided credentials are verified against LDAP (default: true)
<b>dir-context.url</b>	The url of the LDAP server.
<b>dir-context.principal</b>	User (bindDn) which is used to connect to LDAP server.
<b>dir-context.password</b>	The password (bindCredential) which belongs to the principal.
<b>identity-mapping.rdn-identifier</b>	

The identifier (baseFilter) which correlates to the provided user (default: uid)

**identity-mapping.search-base-dn**  
The dn where we look for users.

**identity-mapping.attribute-mappings.<id>.from**  
The roleAttributeId from which is mapped

**identity-mapping.attribute-mappings.<id>.to**  
The identifier whom the attribute is mapped to (default: gropus)

**identity-mapping.attribute-mappings.<id>.filter**  
The filter (roleFilter)

## Vault

Quarkus integrates with Vault to manage secrets or protecting sensitive data.

```
mvn quarkus:add-extension
-Dextensions="vault"
```

And configuring Vault in application.properties:

```
# vault url
quarkus.vault.url=http://localhost:8200

quarkus.vault.authentication.userpass.username=bob
quarkus.vault.authentication.userpass.password=sinclair

# path within the kv secret engine
quarkus.vault.secret-config-kv-path=myapps/vault-quickstart/config
quarkus.vault.secret-config-kv-path.singer=multi/singer
```

```
vault kv put secret/myapps/vault-quickstart/config a-private-key=123456
```

```
vault kv put secret/multi/singer firstname=paul
```

```
@ConfigProperty(name = "a-private-key")
String privateKey;

@ConfigProperty(name = "singer.firstname")
String firstName;
```

You can access the KV engine programmatically:

```
@Inject
VaultKVSecretEngine kvSecretEngine;

kvSecretEngine.readSecret("myapps/vault-quickstart/" + vaultPath).toString();

Map<String, String> secrets;
kvSecretEngine.writeSecret("myapps/vault-quickstart/crud", secrets);

kvSecretEngine.deleteSecret("myapps/vault-quickstart/crud");
```

Fetching credentials DB

With the next `kv` vault `kv put secret/myapps/vault-quickstart/db password=connor`

```
quarkus.vault.credentials-provider.mydatabase.kv-path=
    myapps/vault-quickstart/db
quarkus.datasource.credentials-provider=
    mydatabase

quarkus.datasource.url=
    jdbc:postgresql://localhost:5432/mydatabase
quarkus.datasource.driver=
    org.postgresql.Driver
quarkus.datasource.username=
    sarah
```

No password is set as it is fetched from Vault.

INFO: `dynamic database credentials` through the `database-credentials-role` property.

Transit

```
@Inject
VaultTransitSecretEngine transit;

transit.encrypt("my_encryption", text);
transit.decrypt("my_encryption", text).asString();
transit.sign("my-sign-key", text);
```

Vault TOTP

TOTP `secret engine` is supported by using `io.quarkus.vault.VaultTOTPSecretEngine` class:

```
@Inject
VaultTOTPSecretEngine vaultTOTPSecretEngine;

CreateKeyParameters createKeyParameters = new CreateKeyParameters("Google", "test@gmail.com");
createKeyParameters.setPeriod("30m");

/** Generate Key (QR code) */
final Optional<KeyDefinition> myKey = vaultTOTPSecretEngine.createKey("my_key_2", createKeyParameters);

/** Generate key number to login */
final String keyCode = vaultTOTPSecretEngine.generateCode("my_key_2");

/** Login logic */
boolean valid = vaultTOTPSecretEngine.validateCode("my_key_2", keyCode);
```

Vault configuration properties. Prefix `quarkus.vault` is skipped.

<code>url</code>	Vault server URL
<code>authentication.client-token</code>	Vault token to access
<code>authentication.app-role.role-id</code>	Role Id for AppRole auth
<code>authentication.app-role.secret-id</code>	Secret Id for AppRole auth
<code>authentication.app-role.secret-id-wrapping-token</code>	Wrapping token containing a Secret Id. <code>secret-id</code> and <code>secret-id-wrapping-token</code> are exclusive.
<code>authentication.userpass.username</code>	Username for userpass auth
<code>authentication.userpass.password</code>	Password for userpass auth
<code>authentication.userpass.password-wrapping-token</code>	Wrapping token containing a password. <code>password</code> and <code>password-wrapping-token</code> are exclusive.
<code>authentication.kubernetes.role</code>	Kubernetes authentication role
<code>authentication.kubernetes.jwt-token-path</code>	Location of the file containing the Kubernetes JWT token
<code>renew-grace-period</code>	Renew grace period duration (default: <code>1H</code> )
<code>secret-config-cache-period</code>	

Vault config source cache period (default: `10M`)

<code>secret-config-kv-path</code>	Vault path in kv store. List of paths is supported in CSV
<code>log-confidentiality-level</code>	Used to hide confidential infos. <code>low</code> , <code>medium</code> , <code>high</code> (default: <code>medium</code> )
<code>kv-secret-engine-version</code>	Kv secret engine version (default: <code>1</code> )
<code>kv-secret-engine-mount-path</code>	Kv secret engine path (default: <code>secret</code> )
<code>tls.skip-verify</code>	Allows to bypass certificate validation on TLS communications (default: <code>false</code> )
<code>tls.ca-cert</code>	Certificate bundle used to validate TLS communications
<code>tls.use-kubernetes-ca-cert</code>	TLS will be active (default: <code>true</code> )
<code>connect-timeout</code>	Tiemout to establish a connection (default: <code>5s</code> )
<code>read-timeout</code>	Request timeout (default: <code>1s</code> )
<code>credentials-provider."credentials-provider".database-credentials-role</code>	Database credentials role
<code>credentials-provider."credentials-provider".kv-path</code>	A path in vault kv store, where we will find the kv-key
<code>credentials-provider."credentials-provider".kv-key</code>	Key name to search in vault path kv-path (default: <code>password</code> )

# JAX-RS

Quarkus uses JAX-RS to define REST-ful web APIs. Under the covers, Rest-EASY is working with Vert.X directly without using any Servlet.

It is **important** to know that if you want to use any feature that implies a `Servlet` (ie Servlet Filters) then you need to add the `quarkus-undertow` extension to switch back to the `Servlet` ecosystem but generally speaking, you don't need to add it as everything else is well-supported.

```
@Path("/book")
public class BookResource {

    @GET
    @Produces(MediaType.APPLICATION_JSON)
    public List<Book> getAllBooks() {}

    @POST
    @Produces(MediaType.APPLICATION_JSON)
    public Response createBook(Book book) {}

    @DELETE
    @Path("/{isbn}")
    @Produces(MediaType.APPLICATION_JSON)
    public Response deleteBook(
        @PathParam("isbn") String isbn) {}

    @GET
    @Produces(MediaType.APPLICATION_JSON)
    @Path("/search")
    public Response searchBook(
        @QueryParam("description") String description) {}
}
```

To get information from request:

- @PathParam**  
Gets content from request URI. (example: `/book/{id}`  
`@PathParam("id")`)
- @QueryParam**  
Gets query parameter. (example: `/book?desc=""`  
`@QueryParam("desc")`)
- @FormParam**  
Gets form parameter.
- @MatrixParam**  
Get URI matrix parameter. (example: `/book;author=mkyong;country=malaysia`)
- @CookieParam**  
Gets cookie param by name.
- @HeaderParam**  
Gets header parameter by name.

Valid HTTP method annotations provided by the spec are: `@GET`, `@POST`, `@PUT`, `@DELETE`, `@PATCH`, `@HEAD` and `@OPTIONS`.

You can create new annotations that bind to HTTP methods not defined by the spec.

```
@Target({ElementType.METHOD})
@Retention(RetentionPolicy.RUNTIME)
@HttpMethod("LOCK")
public @interface LOCK {

}

@LOCK
public void lockIt() {}
}
```

## Injecting

Using `@Context` annotation to inject JAX-RS and Servlet information.

```
@GET
public String getBase(@Context UriInfo uriInfo) {
    return uriInfo.getBaseUri();
}
```

Possible injectable objects: `SecurityContext`, `Request`, `Application`, `Configuration`, `Providers`, `ResourceContext`, `ServletConfig`, `ServletContext`, `HttpServletRequest`, `HttpServletResponse`, `HttpHeaders`, `UriInfo`, `SseEventSink` and `Sse`.

## HTTP Filters

HTTP request and response can be intercepted to manipulate the metadata (ie headers, parameters, media type, ...) or abort a request. You only need to implement the next `ContainerRequestFilter` and `ContainerResponseFilter` JAX-RS interfaces respectively.

```
@Provider
public class LoggingFilter
    implements ContainerRequestFilter {

    @Context
    UriInfo info;

    @Context
    HttpServletRequest request;

    @Override
    public void filter(ContainerRequestContext context) {
        final String method = context.getMethod();
        final String path = info.getPath();
        final String address = request.getRemoteAddr();
        System.out.println("Request %s %s from IP %s",
            method, path, address);
    }

}
```

## Exception Mapper

You can map exceptions to produce a custom output by implementing `ExceptionHandler` interface:

```
@Provider
public class ErrorMapper
    implements ExceptionMapper<Exception> {

    @Override
    public Response toResponse(Exception exception) {
        int code = 500;
        if (exception instanceof WebApplicationException) {
            code = ((WebApplicationException) exception)
                .getResponse().getStatus();
        }
        return Response.status(code)
            .entity(
                Json.createObjectBuilder()
                    .add("error", exception.getMessage())
                    .add("code", code)
                    .build()
            )
            .build();
    }
}
```

## Caching

Annotations to set Cache-Control headers:

```
@Produces(MediaType.APPLICATION_JSON)
@org.jboss.resteasy.annotations.cache.NoCache
public User me() {}

@Produces(MediaType.APPLICATION_JSON)
@org.jboss.resteasy.annotations.cache.Cache(
    maxAge = 2000,
    noStore = false
)
public User you() {}
```

# Vert.X Filters and Routes

## Programmatically

You can also register Vert.X Filters and Router programmatically inside a CDI bean:



```
import io.quarkus.vertx.http.runtime.filters.Filters;
import io.vertx.ext.web.Router;
import javax.enterprise.context.ApplicationScoped;
import javax.enterprise.event.Observes;

@ApplicationScoped
public class MyBean {

    public void filters(
        @Observes Filters filters) {
        filters
            .register(
                rc -> {
                    rc.response()
                        .putHeader("X-Filter", "filter 1");
                    rc.next();
                },
                10);
    }

    public void routes(
        @Observes Router router) {
        router
            .get("/")
            .handler(rc -> rc.response().end("OK"));
    }
}
```

Declarative

You can use `@Route` annotation to use reactive routes and `@RouteFilter` to sue reactive filters in a declarative way:

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-vertx-web"
```

```
@ApplicationScoped
public class MyDeclarativeRoutes {

    @Route(path = "/hello", methods = HttpMethod.GET)
    public void greetings(RoutingContext rc) {
        String name = rc.request().getParam("name");
        if (name == null) {
            name = "world";
        }
        rc.response().end("hello " + name);
    }

    @RouteFilter(20)
    void filter(RoutingContext rc) {
        rc.response().putHeader("X-Filter", "filter 2");
        rc.next();
    }

}
```

Vert.X Verticle

Vert.X Verticles are also supported:

```
@ApplicationScoped
public class VerticleDeployer {

    @Inject
    Vertx vertx;

    public void init(@Observes StartupEvent ev) {
        CountDownLatch latch = new CountDownLatch(1);
        vertx.deployVerticle(BareVerticle::new,
            new DeploymentOptions()
                .setConfig(
                    new JsonObject()
                        .put("id", "bare")
                )
            )
            .thenAccept(x -> latch.countDown());

        latch.countDown();
    }
}
```

Verticles can be:

bare

extending `io.vertx.core.AbstractVerticle`. mutiny: extending `io.smallrye.mutiny.vertx.core.AbstractVerticle`.

GZip Support

You can configure Quarkus to use GZip in the `application.properties` file using the next properties with `quarkus.resteasy` suffix:

`gzip.enabled`  
EnableGZip. (default: false)

`gzip.max-input`  
Configure the upper limit on deflated request body. (default: 10M)

CORS Filter

Quarkus comes with a CORS filter that can be enabled via configuration:

```
quarkus.http.cors=true
```

Prefix is `quarkus.http`.

`cors`  
Enable CORS. (default: false)

`cors.origins`  
CSV of origins allowed. (dedault: Any request valid.)

`cors.methods`  
CSV of methods valid. (default: Any method valid.)

`cors.headers`  
CSV of valid allowed headers. (default: Any requested header valid.)

`cors.exposed-headers`  
CSV of valid exposed headers.

Fault Tolerance

Quarkus uses MicroProfile Fault Tolerance spec:

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-smallrye-fault-tolerance"
```

MicroProfile Fault Tolerance spec uses CDI interceptor and it can be used in several elements such as CDI bean, JAX-RS resource or MicroProfile Rest Client.

To do automatic **retries** on a method:

```
@Path("/api")
@RegisterRestClient
public interface WorldClockService {

    @GET @Path("/json/cet/now")
    @Produces(MediaType.APPLICATION_JSON)
    @Retry(maxRetries = 2)
    WorldClock getNow();

}
```

You can set fallback code in case of an error by using `@Fallback` annotation:

```
@Retry(maxRetries = 1)
@Fallback(fallbackMethod = "fallbackMethod")
WorldClock getNow() {}

public WorldClock fallbackMethod() {
    return new WorldClock();
}
```

`fallbackMethod` must have the same parameters and return type as the annotated method.

You can also set logic into a class that implements `FallbackHandler` interface:

```
public class RecoverFallback
    implements FallbackHandler<WorldClock> {

    @Override
    public WorldClock handle(ExecutionContext context) {

    }

}
```

And set it in the annotation as value `@Fallback(RecoverFallback.class)`

In case you want to use **circuit breaker** pattern:

```
@CircuitBreaker(requestVolumeThreshold = 4,
                failureRatio=0.75,
                delay = 1000)
WorldClock getNow() {}
```

If 3 (4 x 0.75) failures occur among the rolling window of 4 consecutive invocations then the circuit is opened for 1000 ms and then be back to half open. If the invocation succeeds then the circuit is back to closed again.

You can use **bulkahead** pattern to limit the number of concurrent access to the same resource. If the operation is synchronous it uses a semaphore approach, if it is asynchronous a thread-pool one. When a request cannot be processed `BulkheadException` is thrown. It can be used together with any other fault tolerance annotation.

```
@Bulkhead(5)
@Retry(maxRetries = 4,
       delay = 1000,
       retryOn = BulkheadException.class)
WorldClock getNow() {}
```

Fault tolerance annotations:

Annotation	Properties
<code>@Timeout</code>	<code>unit</code>
<code>@Retry</code>	<code>maxRetries</code> , <code>delay</code> , <code>delayUnit</code> , <code>maxDuration</code> , <code>durationUnit</code> , <code>jitter</code> , <code>jitterDelayUnit</code> , <code>retryOn</code> , <code>abortOn</code>
<code>@Fallback</code>	<code>fallbackMethod</code>
<code>@Bulkhead</code>	<code>waitingTaskQueue</code> (only valid in asynchronous)
<code>@CircuitBreaker</code>	<code>failOn</code> , <code>delay</code> , <code>delayUnit</code> , <code>requestVolumeThreshold</code> , <code>failureRatio</code> , <code>successThreshold</code>
<code>@Asynchronous</code>	

You can override annotation parameters via configuration file using property `[classname/methodname/]annotation/parameter`:

```
org.acme.quickstart.WorldClock/getNow/Retry/maxDuration=30
# Class scope
org.acme.quickstart.WorldClock/Retry/maxDuration=3000
# Global
Retry/maxDuration=3000
```

You can also enable/disable policies using special parameter enabled.

```
org.acme.quickstart.WorldClock/getNow/Retry/enabled=false
# Disable everything except fallback
MP_Fault_Tolerance_NonFallback_Enabled=false
```



MicroProfile Fault Tolerance integrates with MicroProfile Metrics spec. You can disable it by setting `MP_Fault_Tolerance_Metrics_Enabled` to false.

## Observability

### Health Checks

Quarkus relies on MicroProfile Health spec to provide health checks.

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-smallrye-health"
```

By just adding this extension, an endpoint is registered to `/health` providing a default health check.

```
{
  "status": "UP",
  "checks": [
  ]
}
```

To create a custom health check you need to implement the `HealthCheck` interface and annotate either with `@Readiness` (ready to process requests) or `@Liveness` (is running) annotations.

```
@Readiness
public class DatabaseHealthCheck implements HealthCheck {
    @Override
    public HealthCheckResponse call() {
        HealthCheckResponseBuilder responseBuilder =
            HealthCheckResponse.named("Database conn");

        try {
            checkDatabaseConnection();
            responseBuilder.withData("connection", true);
            responseBuilder.up();
        } catch (IOException e) {
            // cannot access the database
            responseBuilder.down()
                .withData("error", e.getMessage());
        }
        return responseBuilder.build();
    }
}
```

Builds the next output:

```
{
  "status": "UP",
  "checks": [
    {
      "name": "Database conn",
      "status": "UP",
      "data": {
        "connection": true
      }
    }
  ]
}
```

Since health checks are CDI beans, you can do:

```
@ApplicationScoped
public class DatabaseHealthCheck {

    @Liveness
    HealthCheck check1() {
        return io.smallrye.health.HealthStatus
            .up("successful-live");
    }

    @Readiness
    HealthCheck check2() {
        return HealthStatus
            .state("successful-read", this::isReady)
    }

    private boolean isReady() {}
}
```

You can ping liveness or readiness health checks individually by querying `/health/live` or `/health/ready`.

Quarkus comes with some `HealthCheck` implementations for checking service status.

- **SocketHealthCheck:** checks if host is reachable using a socket.
- **UrlHealthCheck:** checks if host is reachable using a Http URL connection.
- **InetAddressHealthCheck:** checks if host is reachable using `InetAddress.isReachable` method.

```
@Liveness
HealthCheck check1() {
    return new UrlHealthCheck("https://www.google.com")
        .name("Google-Check");
}
```

If you want to override or set manually readiness/liveness probes, you can do it by setting health properties:

```
quarkus.smallrye-health.root-path=/hello
quarkus.smallrye-health.liveness-path=/customlive
quarkus.smallrye-health.readiness-path=/customready
```

Automatic readiness probes

Some default *readiness probes* are provided by default if any of the next features are added:

datasource

A probe to check database connection status.

kafka

A probe to check kafka connection status. In this case you need to enable manually by setting `quarkus.kafka.health.enabled` to `true`.

mongoDB

A probe to check MongoDB connection status.

neo4j

A probe to check Neo4J connection status.

artemis

A probe to check Artemis JMS connection status.

kafka-streams

Liveness (for stream state) and Readiness (topics created) probes.

vault

A probe to check Vault conection status.

You can disable the automatic generation by setting `<component>.health.enabled` to `false`.

```
quarkus.kafka-streams.health.enabled=false
quarkus.mongodb.health.enabled=false
quarkus.neo4j.health.enabled=false
```

In the case of Vault you can pass parameters to modify the call of the `status` endpoint in Vault.

```
quarkus.vault.health.enabled=true
quarkus.vault.health.stand-by-ok=true
quarkus.vault.health.performance-stand-by-ok=true
```

Health groups are supported to provide custom health checks groups:

```
@io.smallrye.health.HealthGroup("mygroup1")
public class SimpleHealthGroupCheck implements HealthCheck
{
}
```

You can ping group health checks by querying `/group/mygroup1`.

Group root path can be configured:

```
quarkus.smallrye-health.group-path=/customgroup
```

Metrics

Quarkus can utilize the MicroProfile Metrics spec to provide metrics support.

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-smallrye-metrics"
```

The metrics can be read with JSON or the OpenMetrics format. An endpoint is registered automatically at `/metrics` providing default metrics.

MicroProfile Metrics annotations:

- @Timed**  
Tracks the duration.
- @SimplyTimed**  
Tracks the duration without mean and distribution calculations.
- @Metered**  
Tracks the frequency of invocations.
- @Counted**  
Counts number of invocations.
- @Gauge**  
Samples the value of the annotated object.

**@ConcurrentGauge**  
Gauge to count parallel invocations.

**@Metric**  
Used to inject a metric. Valid types `Meter`, `Timer`, `Counter`, `Histogram`. `Gauge` only on producer methods/fields.

```
@GET
//...
@Timed(name = "checksTimer",
description = "A measure of how long it takes
                to perform a hello.",
unit = MetricUnits.MILLISECONDS)
public String hello() {}

@Counted(name = "countWelcome",
description = "How many welcome have been performed.")
public String hello() {}
```

**@Gauge** annotation returning a measure as a gauge.

```
@Gauge(name = "hottestSauce", unit = MetricUnits.NONE,
description = "Hottest Sauce so far.")
public Long hottestSauce() {}
```

Injecting a histogram using `@Metric`.

```
@Inject
@Metric(name = "histogram")
Histogram histogram;
```

You can configure Metrics:

```
quarkus.smallrye-metrics.path=/mymetrics
```

Prefix is `quarkus.smallrye-metrics`.

- path**  
The path to the metrics handler. (default: `/metrics`)
- extensions.enabled**  
Metrics are enabled or not. (default: `true`)
- micrometer.compatibility**  
Apply Micrometer compatibility mode. (default: `false`)

`quarkus.hibernate-orm.metrics.enabled` set to `true` exposes Hibernate metrics under `vendor` scope.

`quarkus.mongodb.metrics.enabled` set to `true` exposes MongoDB metrics under `vendor` scope.

You can apply metrics annotations via CDI stereotypes:



```
@Stereotype
@Retention(RetentionPolicy.RUNTIME)
@Target({ ElementType.TYPE, ElementType.METHOD, ElementType.FIELD })
@Timed(name = "checksTimer",
description = "A measure of how long it takes
                to perform a hello.",
unit = MetricUnits.MILLISECONDS)
public @interface TimedMilliseconds {
}
```

Tracing

Quarkus can utilize the MicroProfile OpenTracing spec.

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-smallrye-opentracing"
```

Requests sent to any endpoint are traced automatically.

This extension includes OpenTracing support and `Jaeger` tracer.

Jaeger tracer configuration:

```
quarkus.jaeger.service-name=myservice
quarkus.jaeger.sampler-type=const
quarkus.jaeger.sampler-param=1
quarkus.jaeger.endpoint=http://localhost:14268/api/traces
```

`@Traced` annotation can be set to disable tracing at class or method level.

`Tracer` class can be injected into the class.

```
@Inject
Tracer tracer;

tracer.activeSpan().setBaggageItem("key", "value");
```

You can disable `Jaeger` extension by using `quarkus.jaeger.enabled` property.

You can log the `traceId`, `spanId` and `sampled` in normal log:

```
quarkus.log.console.format=%d{HH:mm:ss} %-5p traceId=%X{traceId},
                                spanId=%X{spanId}, sampled
                                =%X{sampled} [%c{2.}] (%t) %s%n
```

Additional tracers

JDBC Tracer

Adds a span for each JDBC queries.

```
<dependency>
  <groupId>io.opentracing.contrib</groupId>
  <artifactId>opentracing-jdbc</artifactId>
</dependency>
```

Configure JDBC driver apart from tracing properties seen before:

```
# add ':tracing' to your database URL
quarkus.datasource.url=
    jdbc:tracing:postgresql://localhost:5432/mydatabase
quarkus.datasource.driver=
    io.opentracing.contrib.jdbc.TracingDriver
quarkus.hibernate-orm.dialect=
    org.hibernate.dialect.PostgreSQLDialect
```

AWS XRay

If you are building native images, and want to use AWS X-Ray Tracing with your lambda you will need to include `quarkus-amazon-lambda-xray` as a dependency in your pom.

Native Executable

You can build a native image by using GraalVM. The common use case is creating a Docker image so you can execute the next commands:

```
./mvnw package -Pnative -Dquarkus.native.container-build=true

docker build -f src/main/docker/Dockerfile.native
               -t quarkus/getting-started .

docker run -i --rm -p 8080:8080 quarkus/getting-started
```

You can use `quarkus.native.container-runtime` to select the container runtime to use. Now `docker` (default) and `podman` are the valid options.

```
./mvnw package -Pnative -Dquarkus.native.container-runtime=
podman
```

To configure native application, you can create a `config` directory at the same place as the native file and place an `application.properties` file inside. `config/application.properties`.

SSL

To create a native image with SSL you need to copy SunEC library and certificates:

Java 8:

```
FROM quay.io/quarkus/ubi-quarkus-native-image:{graalvm-version}-java8 as nativebuilder
RUN mkdir -p /tmp/ssl-lib/lib \
    && cp /opt/graalvm/jre/lib/security/cacerts /tmp/ssl-lib \
    && cp /opt/graalvm/jre/lib/amd64/libsunec.so /tmp/ssl-lib/lib/

FROM registry.access.redhat.com/ubi8/ubi-minimal
WORKDIR /work/
COPY --from=nativebuilder /tmp/ssl-lib/lib /work/
COPY target/*-runner /work/application
RUN chmod 775 /work /work/application
EXPOSE 8080
CMD ["/application", "-Dquarkus.http.host=0.0.0.0", "-Djava.library.path=/work/lib", "-Djavax.net.ssl.trustStore=/work/cacerts"]
```

Java 11:

```
FROM quay.io/quarkus/ubi-quarkus-native-image:{graalvm-version}-java11 as nativebuilder
RUN mkdir -p /tmp/ssl-libraries/lib \
    && cp /opt/graalvm/lib/security/cacerts /tmp/ssl-libraries \
    && cp /opt/graalvm/lib/libsunec.so /tmp/ssl-libraries/lib/

FROM registry.access.redhat.com/ubi8/ubi-minimal
WORKDIR /work/
COPY --from=nativebuilder /tmp/ssl-libraries /work/
COPY target/*-runner /work/application
RUN chmod 775 /work /work/application
EXPOSE 8080
CMD ["./application", "-Dquarkus.http.host=0.0.0.0", "-Djava.library.path=/work/lib", "-Djavax.net.ssl.trustStore=/work/cacerts"]
```

## Container Images Creation

You can leverage to Quarkus to generation and release of Docker containers. It provides several extensions to make it so.

```
mvn clean package
-Dquarkus.container-image.build=true
-Dquarkus.container-image.push=true
-Dquarkus.container-image.registry=quay.io
```

Prefix is `quarkus.container-image:`

### group

The group/repository of the image. (default: the `${user.name}`)

### name

The name of the image. (default: the application name)

### tag

The tag of the image. (default: the application version)

### registry

The registry to use for pushing. (default: `docker.io`)

### username

The registry username.

### password

The registry password.

### insecure

Flag to allow insecure registries. (default: `false`)

### build

Boolean to set if image should be built. (default: `false`)

### push

Boolean to set if image should be pushed. (default: `false`)

## Jib

```
./mvnw quarkus:add-extensions
-Dextensions="quarkus-container-image-jib"
```

Prefix is `quarkus.container-image-jib:`

### base-jvm-image

The base image to use for the jib build. (default: `fabric8/java-alpine-openjdk8-jre`)

### base-native-image

The base image to use for the native build. (default: `registry.access.redhat.com/ubi8/ubi-minimal`)

### jvm-arguments

The arguments to pass to java. (default: `-Dquarkus.http.host=0.0.0.0,-Djava.util.logging.manager=org.jboss.logmanager.LogManager`)

### native-arguments

The arguments to pass to the native application. (default: `-Dquarkus.http.host=0.0.0.0`)

### environment-variables

Map of environment variables.

## Docker

```
./mvnw quarkus:add-extensions
-Dextensions="quarkus-container-image-docker"
```

Prefix is `quarkus.container-image-s2i:`

### dockerfile-jvm-path

Path to the JVM Dockerfile. (default: `${project.root}/src/main/docker/Dockerfile.jvm`)

### dockerfile-native-path

Path to the native Dockerfile. (default: `${project.root}/src/main/docker/Dockerfile.native`)

## S2I

```
./mvnw quarkus:add-extensions
-Dextensions="quarkus-container-image-s2i"
```

Prefix is `quarkus.container-image-docker:`

### base-jvm-image

The base image to use for the s2i build. (default: `fabric8/java-alpine-openjdk8-jre`)

### base-native-image


The base image to use for the native build. (default: `registry.access.redhat.com/ubi8/ubi-minimal`)

## Kubernetes

Quarks can use Dekorater to generate Kubernetes resources.

```
./mvnw quarkus:add-extensions
-Dextensions="quarkus-kubernetes"
```

Running `./mvnw package` the Kubernetes resources are created at `target/kubernetes/` directory.



Container Images Creation integrates with Kubernetes extension, so no need of extra Kubernetes properties.

Generated resource is integrated with MicroProfile Health annotations.

Also, you can customize the generated resource by setting the new values in `application.properties`:

```
quarkus.kubernetes.replicas=3

quarkus.kubernetes.labelsfoo=bar

quarkus.kubernetes.readiness-probe.period-seconds=45

quarkus.kubernetes.mounts.github-token.path=/deployment/github
quarkus.kubernetes.mounts.github-token.read-only=true

quarkus.kubernetes.secret-volumes.github-token.volume-name=github-token
quarkus.kubernetes.secret-volumes.github-token.secret-name=greeting-security
quarkus.kubernetes.secret-volumes.github-token.default-mode=420

quarkus.kubernetes.config-map-volumes.github-token.config-map-name=my-secret

quarkus.kubernetes.expose=true
```

All possible values are explained at <https://quarkus.io/guides/kubernetes#configuration-options>.

## Labels and Annotations

The generated manifest use the Kubernetes recommended labels and annotations.

```
"labels" : {
  "app.kubernetes.io/part-of" : "todo-app",
  "app.kubernetes.io/name" : "todo-rest",
  "app.kubernetes.io/version" : "1.0-rc.1"
}

"annotations": {
  "app.quarkus.io/vcs-url" : "<some url>",
  "app.quarkus.io/commit-id" : "<some git SHA>",
}
```

You can override the labels by using the next properties:

```
quarkus.kubernetes.part-of=todo-app
quarkus.kubernetes.name=todo-rest
quarkus.kubernetes.version=1.0-rc.1
```

Or add new labels and/or annotations:

```
quarkus.kubernetes.labels.foo=bar
quarkus.kubernetes.annotations.foo=bar
```

### Kubernetes Deployment Targets

You can generate different resources setting the property `quarkus.kubernetes.deployment-target`.

Possible values are `kubernetes`, `openshift` and `knative`. The default value is `kubernetes`.

List of configuration options:

**kubernetes**  
<https://quarkus.io/guides/kubernetes#configuration-options>


**openshift**  
<https://quarkus.io/guides/kubernetes#openshift>

**Knative**  
<https://quarkus.io/guides/kubernetes#knative>

### Deployment

To deploy automatically the generated resources, you need to set `quarkus.container.deploy` flag to `true`.

```
mvn clean package -Dquarkus.kubernetes.deploy=true
```

 If you set this flag to `true`, the `build` and `push` flags from `container-image` are set to `true` too.

To deploy the application, the extension uses the `https://github.com/fabric8io/kubernetes-client`. All options described at `Kubernetes Client` are valid here.

### OpenShift

Instead of adding `Kubernetes` extension, set container image `s2i` and the `target` to `openshift` for working with `OpenShift`, an extension grouping all of the is created:

```
./mvnw quarkus:add-extension
-Dextensions="openshift"
```

### Kubernetes Configuration Extension

Integration between `MicroProfile Config spec` and `ConfigMaps/Secrets`:

```
./mvnw quarkus:add-extensions
-Dextensions="quarkus-kubernetes-config"
```

```
quarkus.kubernetes-config.enabled=true
quarkus.kubernetes-config.config-maps=cmap1,cmap2
quarkus.kubernetes-config.secrets=secret1
```

```
@ConfigProperty(name = "dummysecret")
String dummysecret;

@ConfigProperty(name = "secret.prop1")
String secretProp1;

@ConfigProperty(name = "some.prop1")
String someProp1;
```

If the config key is a `Quarkus configuration file application.properties/application.yaml`, the content is parsed and each key of the configuration file is used as config property.

List of `Kubernetes Config` parameters.

`quarkus.kubernetes-config` as prefix is skipped in the next table.

**enabled**  
The application will attempt to look up the configuration from the API server. (default: `false`)

**fail-on-missing-config**  
The application will not start if any of the configured config sources cannot be located. (default: `true`)

**config-maps**  
ConfigMaps to look for in the namespace that the `Kubernetes Client` has been configured for. Supports CSV.

**secrets**  
Secrets to look for in the namespace that the `Kubernetes Client` has been configured for. Supports CSV.

### Kubernetes Client

Quarkus integrates with `Fabric8 Kubernetes Client`.

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-kubernetes-client"
```

List of `Kubernetes client` parameters.

`quarkus.kubernetes-client` as prefix is skipped in the next table.

**trust-certs**

Trust self-signed certificates. (default: `false`)

**master-url**  
URL of `Kubernetes API` server.

**namespace**  
Default namespace.

**ca-cert-file**  
CA certificate data.

**client-cert-file**  
Client certificate file.

**client-cert-data**  
Client certificate data.

**client-key-data**  
Client key data.

**client-key-algorithm**  
Client key algorithm.

**client-key-passphrase**  
Client key passphrase.

**username**  
Username.

**password**  
Password.

**watch-reconnect-interval**  
Watch reconnect interval. (default: `PT1S`)

**watch-reconnect-limit**  
Maximum reconnect attempts. (default: `-1`)

**connection-timeout**  
Maximum amount of time to wait for a connection. (default: `PT10S`)

**request-timeout**  
Maximum amount of time to wait for a request. (default: `PT10S`)

**rolling-timeout**  
Maximum amount of time to wait for a rollout. (default: `PT15M`)

**http-proxy**  
HTTP proxy used to access the `Kubernetes`.

**https-proxy**  
HTTPS proxy used to access the `Kubernetes`.

**proxy-username**  
Proxy username.



**proxy-password**  
Proxy password.

**no-proxy**  
IP addresses or hosts to exclude from proxying

Or programmatically:

```
@Dependent
public class KubernetesClientProducer {

    @Produces
    public KubernetesClient kubernetesClient() {
        Config config = new ConfigBuilder()
            .withMasterUrl("https://mymaster.com")
            .build();
        return new DefaultKubernetesClient(config);
    }
}
```

And inject it on code:

```
@Inject
KubernetesClient client;

ServiceList myServices = client.services().list();

Service myservice = client.services()
    .inNamespace("default")
    .withName("myservice")
    .get();

CustomResourceDefinitionList crds = client
    .customResourceDefinitions()
    .list();

dummyCRD = new CustomResourceDefinitionBuilder()
    ...
    .build()
client.customResourceDefinitions()
    .create(dummyCRD);
```

## Testing

Quarkus provides a Kubernetes Mock test resource that starts a mock of Kubernetes API server and sets the proper environment variables needed by Kubernetes Client.

Register next dependency: `io.quarkus:quarkus-test-kubernetes-client:test`.

```
@QuarkusTestResource(KubernetesMockServerTestResource.class)
@QuarkusTest
public class KubernetesClientTest {

    @MockServer
    private KubernetesMockServer mockServer;

    @Test
    public void test() {
        final Pod pod1 = ...
        mockServer
            .expect()
            .get()
            .withPath("api/v1/namespaces/test/pods")
            .andReturn(200,
                new PodListBuilder()
                    .withNewMetadata()
                    .withResourceVersion("1")
                    .endMetadata()
                    .withItems(pod1, pod2)
                    .build())
            .always();
    }
}
```

## AWS Lambda

Quarkus integrates with Amazon Lambda.

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-amazon-lambda"
```

And then implement `com.amazonaws.services.lambda.runtime.RequestHandler` interface.

```
public class TestLambda
    implements RequestHandler<MyInput, MyOutput> {
    @Override
    public MyInput handleRequest(MyOutput input,
                                   Context context) {

    }
}
```

The `com.amazonaws.services.lambda.runtime.RequestStreamHandler` interface is also supported.

The interface `com.amazon.ask.SkillStreamHandler` is also supported.

You can set the handler name by using `quarkus.lambda.handler` property or by annotating the Lambda with the CDI `@Named` annotation.

## Test

You can write tests for Amazon lambdas:

```
<dependency>
  <groupId>io.quarkus</groupId>
  <artifactId>quarkus-test-amazon-lambda</artifactId>
  <scope>test</scope>
</dependency>
```

```
@Test
public void testLambda() {
    MyInput in = new MyInput();
    in.setGreeting("Hello");
    in.setName("Stu");
    MyOutput out = LambdaClient.invoke(MyOutput.class, in);
}
```

To scaffold a AWS Lambda run:

```
mvn archetype:generate \
  -DarchetypeGroupId=io.quarkus \
  -DarchetypeArtifactId=quarkus-amazon-lambda-archetype \
  -DarchetypeVersion={version}
```

## Azure Functions

Quarkus can make a microservice be deployable to the Azure Functions.

To scaffold a deployable microservice to the Azure Functions run:

```
mvn archetype:generate \
  -DarchetypeGroupId=io.quarkus \
  -DarchetypeArtifactId=quarkus-azure-functions-http-archetype \
  -DarchetypeVersion={version}
```

# Apache Camel

Apache Camel Quarkus has its own site:  
<https://github.com/apache/camel-quarkus>

## WebSockets

Quarkus can be used to handling web sockets.

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-undertow-websockets"
```

And web sockets classes can be used:

```
@ServerEndpoint("/chat/{username}")
@ApplicationScoped
public class ChatSocket {

    @OnOpen
    public void onOpen(Session session,
        @PathParam("username") String username) {}

    @OnClose
    public void onClose(..) {}

    @OnError
    public void onError(..., Throwable throwable) {}

    @OnMessage
    public void onMessage(...) {}

}
```

## OpenAPI

Quarkus can expose its API description as OpenAPI spec and test it using Swagger UI.

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-smallrye-openapi"
```

Then you only need to access to `/openapi` to get OpenAPI v3 spec of services.

You can update the OpenApi path by setting `quarkus.smallrye-openapi.path` property.

Also, in case of starting Quarkus application in `dev` or `test` mode, Swagger UI is accessible at `/swagger-ui`. If you want to use it in production mode you need to set `quarkus.swagger-ui.always-include` property to `true`.

You can update the Swagger UI path by setting `quarkus.swagger-ui.path` property.

```
quarkus.swagger-ui.path=/my-custom-path
```

You can customize the output by using Open API v3 annotations.

```
@Schema(name="Developers",
    description="POJO that represents a developer.")
public class Developer {
    @Schema(required = true, example = "Alex")
    private String name;
}

@POST
@Path("/developer")
@Operation(summary = "Create deeloper",
    description = "Only be done by admin.")
public Response createDeveloper(
    @RequestBody(description = "Developer object",
        required = true,
        content = @Content(schema =
            @Schema(implementation = Developer.class)))
        Developer developer)
```

All possible annotations can be seen at [org.eclipse.microprofile.openapi.annotations](https://org.eclipse.microprofile.openapi.annotations) package.

You can also serve OpenAPI Schema from static files instead of dynamically generated from annotation scanning.

You need to put OpenAPIdocumentation under `META-INF` directory (ie: `META-INF/openapi.yaml`).

A request to `/openapi` will serve the combined OpenAPI document from the static file and the generated from annotations. You can disable the scanning documents by adding the next configuration property: `mp.openapi.scan.disable=true`.

Other valid document paths are: `META-INF/openapi.yml`, `META-INF/openapi.json`, `WEB-INF/classes/META-INF/openapi.yml`, `WEB-INF/classes/META-INF/openapi.yaml`, `WEB-INF/classes/META-INF/openapi.json`.

## Mail Sender

You can send emails by using Quarkus Mailer extension:

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-mailer"
```

You can inject two possible classes `io.quarkus.mailer.Mailer` for synchronous API or `io.quarkus.mailer.reactive.ReactiveMailer` for asynchronous/reactive API.

```
@Inject
Mailer mailer;
```


And then you can use them to send an email:

```
mailer.send(
    Mail.withText("to@acme.org", "Subject", "Body")
);
```

## Reactive Mail client


```
@Inject
ReactiveMailer reactiveMailer;

CompletionStage<Response> stage =
    reactiveMailer.send(
        Mail.withText("to@acme.org", "Subject", "Body")
    )
    .subscribeAsCompletionStage()
    .thenApply(x -> Response.accepted().build());
```

 If you are using `quarkus-resteasy-mutiny`, you can return `io.smallrye.mutiny.Uni` type.

Mail class contains methods to add `cc`, `bcc`, `headers`, `bounce address`, `reply to`, `attachments`, `inline attachments` and `html body`.

```
mailer.send(Mail.withHtml("to@acme.org", "Subject", body)
    .addInlineAttachment("quarkus.png",
        new File("quarkus.png"),
        "image/png", "<my-image@quarkus.io>"));
```

 If you need deep control you can inject Vert.x mail client `@Inject MailClient client;`


You need to configure SMTP properties to be able to send an email:

```
quarkus.mailer.from=test@quarkus.io
quarkus.mailer.host=smtp.sendgrid.net
quarkus.mailer.port=465
quarkus.mailer.ssl=true
quarkus.mailer.username=....
quarkus.mailer.password=....
```

List of Mailer parameters. `quarkus.` as a prefix is skipped in the next table.

Parameter	Default	Description
<code>mailer.from</code>		Default address.
<code>mailer.mock</code>	false in <code>prod</code> , true in <code>dev</code> and <code>test</code> .	Emails not sent, just printed and stored in a <code>MockMailbox</code> .
<code>mailer.bounce-address</code>		Default address.
<code>mailer.host</code>	<i>mandatory</i>	SMTP host.
<code>mailer.port</code>	25	SMTP port.

Parameter	Default	Description
mailer.username		The username.
mailer.password		The password.
mailer.ssl	false	Enables SSL.
mailer.trust-all	false	Trust all certificates.
mailer.max-pool-size	10	Max connections .
mailer.own-host-name		Hostname for and
mailer.keep-alive	true	Connection pool enabled.
mailer.disable-esmtp	false	Disable ESMTP.
mailer.start-tls	OPTIONAL	TLS security mode. DISABLED, OPTIONAL, REQUIRED.
mailer.login	NONE	Login mode. NONE, OPTIONAL, REQUIRED.
mailer.auth-methods	All methods.	Space-separated list.
mailer.key-store		Path of the key store.
mailer.key-store-password		Key store password.



if you enable SSL for the mailer and you want to build a native executable, you will need to enable the SSL support

```
quarkus.ssl.native=true.
```

### Testing

If `quarkus.mailer.mock` is set to `true`, which is the default value in dev and test mode, you can inject `MockMailbox` to get the sent messages.

```
@Inject
MockMailbox mailbox;

@BeforeEach
void init() {
    mailbox.clear();
}

List<Mail> sent = mailbox
    .getMessagesSentTo("to@acme.org");
```

### Scheduled Tasks

You can schedule periodic tasks with Quarkus.

```
@ApplicationScoped
public class CounterBean {

    @Scheduled(every="10s", delayed="1s")
    void increment() {}

    @Scheduled(cron="0 15 10 * * ?")
    void morningTask() {}
}
```

`every` and `cron` parameters can be surrounded with `{}` and the value is used as config property to get the value.

```
@Scheduled(cron = "{morning.check.cron.expr}")
void morningTask() {}
```

And configure the property into `application.properties`:

```
morning.check.cron.expr=0 15 10 * * ?
```

By default Quarkus expresion is used, but you can change that by setting `quarkus.scheduler.cron-type` property.

```
quarkus.scheduler.cron-type=unix
```

`org.quartz.Scheduler` can be injected as any other bean and scehdule jobs programmatically.

```
@Inject
org.quartz.Scheduler quartz;

quartz.scheduleJob(job, trigger);
```

### Kogito

Quarkus integrates with Kogito, a next-generation business automation toolkit from Drools and jBPM projects for adding business automation capabilities.

To start using it you only need to add the next extension:

```
./mvnw quarkus:add-extension
-Dextensions="kogito"
```

### Apache Tika

Quarkus integrets with Apache Tika to detect and extract metadata/text from different file types:

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-tika"
```

```
@Inject
io.quarkus.tika.TikaParser parser;

@POST
@Path("/text")
@Consumes({ "text/plain", "application/pdf",
    "application/vnd.oasis.opendocument.text" })
@Produces(MediaType.TEXT_PLAIN)
public String extractText(InputStream stream) {
    return parser.parse(stream).getText();
}
```

You can configure Apache Tika in `application.properties` file by using next properties prefixed with `quarkus`:

Parameter	Default	Description
tika.tika-config-path	tika-config.xml	Path to the Tika configuration resource.
quarkus.tika.parsers		CSV of the abbreviated or full parser class to be loaded by the extension.
tika.append-embedded-content	true	The document may have other embedded documents. Set if autmatically append.

### JGit


Quarkus integrets with JGit to integrate with Git repositories:

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-jgit"
```

And then you can start using JGit:



```
try (Git git = Git.cloneRepository()
    .setDirectory(tmpDir)
    .setURI(url)
    .call()) {
    return tmpDir.toString();
}
```

 When running in native mode, make sure to configure SSL access correctly `quarkus.ssl.native=true` (Native and SSL).

## Web Resources

You can serve web resources with Quarkus. You need to place web resources at `src/main/resources/META-INF/resources` and then they are accessible (ie `http://localhost:8080/index.html`)

By default static resources as served under the root context. You can change this by using `quarkus.http.root-path` property.

## Transactional Memory

Quarkus integrates with the Software Transactional Memory (STM) implementation provided by the Narayana project.

```
./mvnw quarkus:add-extension
-Dextensions="narayana-stm"
```

Transactional objects must be interfaces and annotated with `org.jboss.stm.annotations.Transactional`.

```
@Transactional
@NestedTopLevel
public interface FlightService {
    int getNumberOfBookings();
    void makeBooking(String details);
}
```

The pessimistic strategy is the default one, you can change to optimistic by using `@Optimistic`.

Then you need to create the object inside `org.jboss.stm.Container`.

```
Container<FlightService> container = new Container<>();
FlightServiceImpl instance = new FlightServiceImpl();
FlightService flightServiceProxy = container.create(instance);
```

The implementation of the service sets the locking and what needs to be saved/restored:

```
import org.jboss.stm.annotations.ReadLock;
import org.jboss.stm.annotations.State;
import org.jboss.stm.annotations.WriteLock;
```

```
public class FlightServiceImpl
    implements FlightService {
    @State
    private int numberOfBookings;

    @ReadLock
    public int getNumberOfBookings() {
        return numberOfBookings;
    }

    @WriteLock
    public void makeBooking(String details) {
        numberOfBookings += 1;
    }
}
```

Any member is saved/restored automatically (`@State` is not mandatory). You can use `@NotState` to avoid behaviour.

### Transaction boundaries

#### Declarative

- `@NestedTopLevel`: Defines that the container will create a new top-level transaction for each method invocation.
- `@Nested`: Defines that the container will create a new top-level or nested transaction for each method invocation.

#### Programmatically

```
AtomicAction aa = new AtomicAction();

aa.begin();
{
    try {
        flightService.makeBooking("BA123 ...");
        taxiService.makeBooking("East Coast Taxis ...");

        aa.commit();
    } catch (Exception e) {
        aa.abort();
    }
}
```

## Quartz

Quarkus integrates with Quartz to schedule periodic clustered tasks.

```
./mvnw quarkus:add-extension
-Dextensions="quartz"
```


```
@ApplicationScoped
public class TaskBean {

    @Transactional
    @Scheduled(every = "10s")
    void schedule() {
        Task task = new Task();
        task.persist();
    }
}
```

To configure in clustered mode vida DataSource:

```
quarkus.datasource.url=jdbc:postgresql://localhost/quarkus_
test
quarkus.datasource.driver=org.postgresql.Driver
# ...

quarkus.quartz.clustered=true
quarkus.quartz.store-type=db
```

 You need to define the datasource used by clustered mode and also import the database tables following the Quartz schema.

## Qute

Qute is a templating engine designed specifically to meet the Quarkus needs. Templates should be placed by default at `src/main/resources/templates` and subdirectories.

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-resteasy-qute"
```

Templates can be defined in any format, in case of HTML:

```
item.html

{@org.acme.Item item}
<!DOCTYPE html>
<html>
<head>
<meta charset="UTF-8">
<title>{item.name}</title>
</head>
<body>
    <h1>{item.name ?: 'Unknown'}</h1>
    <div>Price: {item.price}</div>
    {#if item.price > 100}
    <div>Discounted Price: {item.discountedPrice}</div>
    {/if}
</body>
</html>
```

First line is not mandatory but helps on doing property checks at compilation time.

To render the template:

```
public class Item {
    public String name;
    public BigDecimal price;
}

@Inject
io.quarkus.qute.Template item;

@GET
@Path("/{id}")
@Produces(MediaType.TEXT_HTML)
public TemplateInstance get(@PathParam("id") Integer id) {
    return item.data("item", service.findItem(id));
}

@TemplateExtension
static BigDecimal discountedPrice(Item item) {
    return item.price.multiply(new BigDecimal("0.9"));
}
```

If `@ResourcePath` is not used in `Template` then the name of the field is used as file name. In this case the file should be `src/main/resources/templates/item.{{}}`. Extension of the file is not required to be set.

`discountedPrice` is not a field of the POJO but a method call. Method definition must be annotated with `@TemplateExtension` and be static method. First parameter is used to match the base object (`Item`). `@TemplateExtension` can be used at class level:

```
@TemplateExtension
public class MyExtensions {
    static BigDecimal discountedPrice(Item item) {
        return item.price.multiply(new BigDecimal("0.9"));
    }
}
```

Methods with multiple parameters are supported too:

```
{item.discountedPrice(2)}
```

```
static BigDecimal discountedPrice(Item item, int scale) {
    return item.price.multiply(scale);
}
```

`Qute for` syntax supports any instance of `Iterable`, `Map.EntrySet`, `Stream` OR `Integer`.

```
{#for i in total}
  {i}:
{/for}
```

The next map methods are supported:

```
{#for key in map.keySet}
{#for value in map.values}
{map.size}
{#if map.isEmpty}
{map['foo']}
```

The next list methods are supported:

```
{list[0]}
```

The next number methods are supported:

```
{#if counter.mod(5) == 0}
```

You can render programmatically the templates too:

```
// file located at src/main/resources/templates/reports/v1/
report_01.{{}}
@ResourcePath("reports/v1/report_01")
Template report;

String output = report
    .data("samples", service.get())
    .render();
```

Reactive and Async

```
CompletionStage<String> async = report.renderAsync();
Publisher<String> publisher = report.publisher();

Uni<String> content = io.smallrye.mutiny.Uni.createFrom()
    .completionStage(() -> report.r
enderAsync());
```

Qute Mail Integration

```
@Inject
MailTemplate hello;

CompletionStage<Void> c = hello.to("to@acme.org")
    .subject("Hello from Qute template")
    .data("name", "John")
    .send();
```

INFO: Template located at `src/main/resources/templates/hello.[html|txt]`.

Sentry

Quarkus integrates with Sentry for logging errors into an error monitoring system.

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-logging-sentry"
```

And the configuration to send all errors occuring in the package `org.example` to Sentrty with DSN `https://abcd@sentry.io/1234`:

```
quarkus.log.sentry=true
quarkus.log.sentry.dsn=https://abcd@sentry.io/1234
quarkus.log.sentry.level=ERROR
quarkus.log.sentry.in-app-packages=org.example
```

Full list of configuration properties having `quarkus.log` as prefix:

**sentry.enable**  
Enable the Sentry logging extension (default: false)

**sentry.dsn**  
Where to send events.

**sentry.level**  
Log level (default: `WARN`)

**sentry.in-app-packages**  
Configure which package prefixes your application uses.

JSch

Quarkus integrates with Jsch for SSH communication.

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-jsch"
```

```
JSch jsch = new JSch();
Session session = jsch.getSession(null, host, port);
session.setConfig("StrictHostKeyChecking", "no");
session.connect();
```

Cache

Quarkus can cache method calls by using as key the tuple (method + arguments).

```
./mvnw quarkus:add-extension
-Dextensions="cache"
```

```
@io.quarkus.cache.CacheResult(cacheName = "weather-cache")
public String getDailyForecast(LocalDate date, String city)
{}
```

`@CacheInvalidate` removes the element represented by the calculated cache key from cache `@CacheInvalidateAll` removes all

entries from the cache. `@CacheKey` to specifically set the arguments to be used as key instead of all.

```
@ApplicationScoped
public class CachedBean {

    @CacheResult(cacheName = "foo")
    public Object load(Object key) {}

    @CacheInvalidate(cacheName = "foo")
    public void invalidate(Object key) {}

    @CacheInvalidateAll(cacheName = "foo")
    public void invalidateAll() {}

}
```

This extension uses Caffeine as its underlying caching provider.

Each cache can be configured individually:

```
quarkus.cache.caffeine."foo".initial-capacity=10
quarkus.cache.caffeine."foo".maximum-size=20
quarkus.cache.caffeine."foo".expire-after-write
quarkus.cache.caffeine."bar".maximum-size=1000
```

Full list of configuration properties having `quarkus.cache.caffeine.[cache-name]` as prefix:

**initial-capacity**

Minimum total size for the internal data structures.

**maximum-size**

Maximum number of entries the cache may contain.

**expire-after-write**

Specifies that each entry should be automatically removed from the cache once a fixed duration has elapsed after the entry’s creation, or last write.

**expire-after-access**

Specifies that each entry should be automatically removed from the cache once a fixed duration has elapsed after the entry’s creation, or last write.



You can multiple cache annotations on a single method.

## Banner

Banner is printed by default. It is not an extension but placed in the core.

**quarkus.banner.path**

Path is relative to root of the classpath. (default: `default_banner.txt`)

**quarkus.banner.enabled**

Enables banner. (default : `true`)

## OptaPlanner

Quarkus integrates with OptaPlanner.

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-optaplanner, quarkus-optaplanner-jackson"
```

```
@PlanningSolution
public class TimeTable {
}

@Inject
private SolverManager<TimeTable, UUID> solverManager;

UUID problemId = UUID.randomUUID();
SolverJob<TimeTable, UUID> solverJob = solverManager.solve
(problemId, problem);
TimeTable solution = solverJob.getFinalBestSolution();
```

Possible configuration options prefixed with `quarkus.optaplanner:`

**solver-config-xml**

A classpath resource to read the solver configuration XML. Not mandatory.

**solver.environment-mode**

Enable runtime assertions to detect common bugs in your implementation during development. Possible values: `FAST_ASSERT`, `FULL_ASSERT`, `NON_INTRUSIVE_FULL_ASSERT`, `NON_REPRODUCIBLE`, `REPRODUCIBLE`. (default: `REPRODUCIBLE`)

**solver.move-thread-count**

Enable multithreaded solving for a single problem. Possible values: `MOVE_THREAD_COUNT_NONE`, `MOVE_THREAD_COUNT_AUTO`, a number or formula based on the available processors. (default: `MOVE_THREAD_COUNT_NONE`)

**solver.termination.spent-limit**

How long the solver can run. (ie `5s`)

**solver.termination.unimproved-spent-limit**

How long the solver can run without finding a new best solution after finding a new best solution. (ie `2h`)

**solver.termination.best-score-limit**

Terminates the solver when a specific or higher score has been reached. (ie `0hard/-1000soft`)

**solver-manager.parallel-solver-count**

The number of solvers that run in parallel. (default: `PARALLEL_SOLVER_COUNT_AUTO`)

## Context Propagation

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-smallrye-context-propagation"
```

If using `mutiny` extension together you already get context propagation for `ArC`, `RESTEasy` and transactions. With `CompletionStage` you need to:

```
@Inject ThreadContext threadContext;
@Inject ManagedExecutor managedExecutor;

threadContext.withContextCapture(..)
    .thenApplyAsync(r -> {}, managedExecutor);
```

If you are going to use security in a reactive environment you will likely need Smallrye Content Propagation to propagate the identity throughout the reactive callback.

## Amazon Alexa

You can use Amazon Alexa by adding the extension:

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-amazon-alexa"
```



# Spring DI

Quarkus provides a compatibility layer for Spring dependency injection.

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-spring-di"
```

Some examples of what you can do. Notice that annotations are the Spring original ones.

```
@Configuration
public class AppConfiguration {

    @Bean(name = "capitalizeFunction")
    public StringFunction capitalizer() {
        return String::toUpperCase;
    }
}
```

Or as a component:

```
@Component("noopFunction")
public class NoOpSingleStringFunction
    implements StringFunction {

}
```

Also as a service and injection properties from `application.properties`.

```
@Service
public class MessageProducer {

    @Value("${greeting.message}")
    String message;

}
```

And you can inject using `Autowired` or constructor in a component and in a JAX-RS resource too.

```
@Component
public class GreeterBean {

    private final MessageProducer messageProducer;

    @Autowired @Qualifier("noopFunction")
    StringFunction noopStringFunction;

    public GreeterBean(MessageProducer messageProducer) {
        this.messageProducer = messageProducer;
    }

}
```

# Spring Boot Configuration

Quarkus provides a compatibility layer for Spring Boot `ConfigurationProperties`.

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-spring-boot-properties"
```

```
@ConfigurationProperties("example")
public final class ClassProperties {

    private String value;
    private AnotherClass anotherClass;

    // getters/setters
}
```

```
example.value=class-value
example.anotherClass.value=true
```

# Spring Cloud Config Client

Quarkus integrates Spring Cloud Config Client and `MicroProfile Config` spec.

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-spring-cloud-config-client"
```

You need to configure the extension:

```
quarkus.sccccc.uri=http://localhost:8089
quarkus.sccccc.username=user
quarkus.sccccc.password=pass
quarkus.sccccc.enabled=true
```

```
@ConfigProperty(name = "greeting.message")
String greeting;
```

Prefix is `quarkus.sccccc`.

**uri**  
Base URI where the Spring Cloud Config Server is available. (default: `localhost:8888`)

**username**  
Username to be used if the Config Server has BASIC Auth enabled.

**password**  
Password to be used if the Config Server has BASIC Auth enabled.

**enabled**  
Enables read configuration from Spring Cloud Config Server. (default: `false`)

**fail-fast**  
True to not start application if cannot access to the server. (default: `false`)

**connection-timeout**  
The amount of time to wait when initially establishing a connection before giving up and timing out. (default: `10s`)

**read-timeout**  
The amount of time to wait for a read on a socket before an exception is thrown. (default: `60s`)

# Spring Web

Quarkus provides a compatibility layer for Spring Web.

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-spring-web"
```

Specifically supports the REST related features. Notice that infrastructure things like `BeanPostProcessor` will not be executed.

```
@RestController
@RequestMapping("/greeting")
public class GreetingController {


    private final GreetingBean greetingBean;

    public GreetingController(GreetingBean greetingBean) {
        this.greetingBean = greetingBean;
    }

    @GetMapping("/{name}")
    public Greeting hello(@PathVariable(name = "name")
        String name) {
        return new Greeting(greetingBean.greet(name));
    }

}
```

Supported annotations are: `RestController`, `RequestMapping`, `GetMapping`, `PostMapping`, `PutMapping`, `DeleteMapping`, `PatchMapping`, `RequestParam`, `RequestHeader`, `MatrixVariable`, `PathVariable`, `CookieValue`, `RequestBody`, `ResponseStatus`, `ExceptionHandler` and `RestControllerAdvice`.



If you scaffold the project with `spring-web` extension, then Spring Web annotations are sed in the generated project.

```
mvn io.quarkus:quarkus-maven-plugin:1.3.0.Final:create ... -Dextensions="spring-web".
```

The next return types are supported: `org.springframework.http.ResponseEntity` and `java.util.Map`.

The next parameter types are supported: An `Exception` argument

dependency).

## Spring Data JPA

While users are encouraged to use Hibernate ORM with Panache for Relational Database access, Quarkus provides a compatibility layer for Spring Data JPA repositories.

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-spring-data-jpa"
```

INFO: Of course you still need to add the JDBC driver, and configure it in `application.properties`.

```
public interface FruitRepository
    extends CrudRepository<Fruit, Long> {
    List<Fruit> findByColor(String color);
}
```

And then you can inject it either as shown in Spring DI or in Spring Web.

Interfaces supported:

- `org.springframework.data.repository.Repository`
- `org.springframework.data.repository.CrudRepository`
- `org.springframework.data.repository.PagingAndSortingRepository`
- `org.springframework.data.jpa.repository.JpaRepository`

INFO: Generated repositories are automatically annotated with `@Transactional`.

Repository fragments is also supported:

```
public interface PersonRepository
    extends JpaRepository<Person, Long>, PersonFragment {

    void makeNameUpperCase(Person person);
}
```

User defined queries:

```
@Query("select m from Movie m where m.rating = ?1")
Iterator<Movie> findByRating(String rating);

@Modifying
@Query("delete from Movie where rating = :rating")
void deleteByRating(@Param("rating") String rating);

@Query(value = "SELECT COUNT(*), publicationYear FROM Book
GROUP BY publicationYear")
List<BookCountByYear> findAllByPublicationYear2();

interface BookCountByYear {
    int getPublicationYear();

    Long getCount();
}
```

What is currently unsupported:

- Methods `org.springframework.data.repository.query.QueryByExampleExecutor` of
- QueryDSL support
- Customizing the base repository
- `java.util.concurrent.Future` as return type
- Native and named queries when using `@Query`

## Spring Security

Quarkus provides a compatibility layer for Spring Security.

```
./mvnw quarkus:add-extension
-Dextensions="spring-security"
```

You need to choose a security extension to define user, roles, ... such as `openid-connect`, `oauth2`, `properties-file` Or `security-jdbc` as seen at RBAC.

Then you can use Spring Security annotations to protect the methods:

```
@Secured("admin")
@GetMapping
public String hello() {
    return "hello";
}
```

Quarkus provides support for some of the most used features of Spring Security's `@PreAuthorize` annotation.

Some examples:

### hasRole

- `@PreAuthorize("hasRole('admin')")`

- `@PreAuthorize("hasRole(@roles.USER)")` where `roles` is a bean defined with `@Component` annotation and `USER` is a public field of the class.

### hasAnyRole

- `@PreAuthorize("hasAnyRole(@roles.USER, 'view')")`

### Permit and Deny All

- `@PreAuthorize("permitAll()")`

- `@PreAuthorize("denyAll()")`

### Anonymous and Authenticated

- `@PreAuthorize("isAnonymous()")`

- `@PreAuthorize("isAuthenticated()")`

### Expressions

- Checks if the current logged in user is the same as the username method parameter:

```
@PreAuthorize("#person.name == authentication.principal.username")
public void doSomethingElse(Person person){}
```

- Checks if calling a method if user can access:

```
@PreAuthorize("@personChecker.check(#person, authentication.principal.username)")
public void doSomething(Person person){}
```

```
@Component
public class PersonChecker {
    public boolean check(Person person, String username) {
        return person.getName().equals(username);
    }
}
```

- Combining expressions:

```
@PreAuthorize("hasAnyRole('user', 'admin') AND #user == principal.username")
public void allowedForUser(String user) {}
```

# Resources

- <https://quarkus.io/guides/>
- <https://www.youtube.com/user/lordofthejars>

# Authors :



**@alexsotob**  
Java Champion and Director of DevExp at Red Hat

1.3.0.Final

