

쿠버네티스, DevOps에서부터 Production 환경까지

at Open Infrastructure Community Day Korea 2020

최영락, 박인혜 / 마이크로소프트

최영락

Developer Product
Marketing Manager at
Microsoft

  @ianychoi



About Me...

Client 개발

Server 개발

오픈소스 개발

Cloud 관리 플랫폼 개발

Container 관리 플랫폼 개발

Cloud Infra Architecture

Application & DevOps Architecture

mail: cosmos0703@gmail.com




1. 쿠버네티스와 DevOps

DevOps와 함께 컨테이너 개발 속도 내기


CI/CD 통합을 통해 팀에서 반복되는 Kubernetes 개발 경험에 도움되는 Azure 클라우드 관련 사항

- Visual Studio Code: 네이티브 컨테이너 및 Kubernetes 개발 환경 지원
- Helm을 지원하는 프라이빗 컨테이너 레지스트리
- 의존성을 별도로 분리하지 않고 Kubernetes 앱 개발 및 테스트
- 몇 번의 클릭만으로 자동화된 작업을 CI/CD 파이프라인을 통해 코드 머지, 컨테이너화를 효율적으로 수행
- 미리 구성된 카나리 배포 전략 수행
- 심도 있는 빌드 및 배포 프로세스를 리뷰 및 통합테스트와 연계하여 가능




안전한 (Secure) DevOps

- 쿠버네티스 및 CI/CD와 함께 코드를 보다 빠르게 배포/전달
- 지속적인 모니터링을 통한 피드백 수용 과정을 가속화
- 지속적인 보안 & 심층 추적을 기반으로 한 **속도 (speed)**와 **보안에 대한 밸런싱**



데모 환경: GitHub Actions for Kubernetes on Azure



Update index.js for demo purpose
ianychoi-patch-1-1 e57333c

✓ Pull Request Workflow
on: pull_request

✓ build-image

✓ [container-scan] nodejs-hello-wo...

Container scan result

Scanned image nodejs-hello-world:13282d4bd2508f01e2ec1ea3d37b10e16950d37e .
Summary:

- No vulnerabilities were detected in the container image

For a better experience with managing allowedlist, install [Scanitizer](#) app.

DETAILS

Vulnerabilities -
None found.

Apply apps/v1 semantics on deployment.yml
master c0a83c6

✓ .github/workflows/ci.yaml
on: push

✓ build


✓ deploy

deploy
succeeded 33 minutes ago in 59s

- > ✓ Set up job
- > ✓ Run actions/checkout@master
- > ✓ Run azure/aks-set-context@v1
- > ✓ Run kubectl create namespace demo --dry-run -o json | kubectl apply -f -
- > ✓ Run azure/k8s-create-secret@v1
- > ✓ Run azure/k8s-deploy@v1
- > ✓ Post Run actions/checkout@master
- > ✓ Complete job

데모 설명: GitHub Actions for Kubernetes on Azure

1. 애저 구독에 안전하게 인증 & 로그인 수행
2. 대상 AKS 클러스터 지정
3. 민감한 정보를 안전하게 관리하기 위해 쿠버네티스 시크릿 (Secret) 오브젝트 생성
4. 쿠버네티스 클러스터에 연결 후 manifest 등을 배포



```
on: [push]

jobs:
  build:
    runs-on: ubuntu-latest
    steps:
      - uses: actions/checkout@master

      - uses: azure/container-actions/docker-login@master
        with:
          login-server: contoso.azurecr.io
          username: ${ secrets.REGISTRY_USERNAME }
          password: ${ secrets.REGISTRY_PASSWORD }

      - run: |
          docker build . -t contoso.azurecr.io/k8sdemo:${ github.sha }
          docker push contoso.azurecr.io/k8sdemo:${ github.sha }

      # Set the target AKS cluster.
      - uses: azure/k8s-actions/aks-set-context@master
        with:
          creds: '${ secrets.AZURE_CREDENTIALS }'
          cluster-name: contoso
          resource-group: contoso-rg

      - uses: azure/k8s-actions/k8s-create-secret@master
        with:
          container-registry-url: contoso.azurecr.io
          container-registry-username: ${ secrets.REGISTRY_USERNAME }
          container-registry-password: ${ secrets.REGISTRY_PASSWORD }
          secret-name: demo-k8s-secret

      - uses: azure/k8s-actions/k8s-deploy@master
        with:
          manifests: |
            manifests/deployment.yml
            manifests/service.yml
          images: |
            demo.azurecr.io/k8sdemo:${ github.sha }
          imagepullsecrets: |
            demo-k8s-secret
```


demo-25179

Kubernetes service



Connect

Delete

Refresh

Overview

- Activity log
- Access control (IAM)
- Tags
- Diagnose and solve problems
- Security

Kubernetes resources

- Namespaces (preview)
- Workloads (preview)
- Services and ingresses (preview)
- Storage (preview)
- Configuration (preview)

Settings

- Node pools
- Configuration

Essentials

[JSON View](#)

Properties

Capabilities

	Kubernetes services	
	Kubernetes version	1.18.10
	Azure AD integration	Not enabled
	Node pools	
	Node pools	1 node pool
	Kubernetes versions	1.18.10
	Node sizes	Standard_DS2_v2
	Virtual node pools	Not enabled


	Networking	
	API server address	demo-25179-devopssummitdemo-8ae5af-78129a6e.hcp.eastasia.azmk8s.io
	Network type (plugin)	Azure CNI
	Private cluster	Not enabled
	Pod CIDR	N/A
	Service CIDR	10.2.0.0/24
	DNS service IP	10.2.0.10
	Docker bridge CIDR	172.17.0.1/16
	HTTP application routing	Not enabled

	Integrations	
	Container insights	Not enabled



Microsoft & 커뮤니티 뉴스

정기적인 커뮤니티 & 마이크로소프트 소식 및
커뮤니티 이벤트, 워크샵에 대한 안내를 받으실
수 있습니다.



<https://aka.ms/devKR>

K8S Cluster를 프로덕션 환경에 부드럽게 랜딩 시키기

Sailing Smoothly on K8S

Microsoft App Dev CSA

Inhye Park





RENA
MONROVIA


Most common customer issues

Memory overload

IO overload

SNAT port exhaustion

Insufficient quota



Memory overload

- Memory overload
 - IO overload
 - SNAT port exhaustion
 - Insufficient quota

Symptoms

User's pods get evicted

User's pods get OOMKilled.

Kube-system pods get evicted.

Nodes get temporarily tainted for not scheduling.

Observations (1)

No limit is set

- name: JAVA_OPTS
value: "-**Xmx2g**"

Describe pod:

Status: Failed

Reason: **Evicted**

Message: The node had condition: [MemoryPressure]

....

Events:

default-scheduler 0/3 nodes are available: 3 node(s) had **taints** that the pod didn't tolerate.

Describe node:

Taints: node.kubernetes.io/**memory-pressure:NoSchedule**
status is now: **NodeHasInsufficientMemory**

Observations (2)

Limit is set too low.

- name: JAVA_OPTS

value: **"-Xmx1g"**

resources:

requests:

memory: "250Mi"

cpu: "250m"

limits:

memory: **"500Mi"**

cpu: "500m"

State: Waiting

Reason: CrashLoopBackOff

Last State: Terminated

Reason: **OOMKilled**

Exit Code: 137

Observations (3)

Critical system pods in kube-system namespace get evicted. Cluster goes into unstable or unusable state

kube-system	metrics-server-566bd9b4f7-gp9nt	1/1	Running	0	31m
kube-system	metrics-server-566bd9b4f7-zd8lm	0/1	Evicted	0	16h

Memory: Best practices

Set resource request and limit on every container.

Set ResourceQuota and/or LimitRange for namespaces.

Isolate system critical pods into their own dedicated node pool.

Put sufficient cores and memory in the pool.

All kube-system pods already have "CriticalAddonsOnly" toleration. Just taint the nodes.

IO overload

- Memory overload
- IO overload
- SNAT port exhaustion
- Insufficient quota

Symptoms

AKS Cluster nodes going NotReady

“TLS handshake timeout” when reaching the API server.

Critical daemonsets or pods such as kube-proxy, coreDNS start to fail.

Performance and stability issues when using istio or complex operator configurations.

Networking errors or high latency when reaching other Azure services.

Slow DNS queries.

PLEG (pod lifecycle event generator) errors on nodes.

“RPC context deadline exceeded” in kubelet/docker logs.

Slow PV attach/detach.

Observations (1)

Max IOPS is the lower of VM and the OS disk IOPS.

AKS OS disks are remote disks.

Small OS disk provides low IOPS and throughput.

VM Si...↑↓	Offering ↑↓	Family ↑↓	vCP...↑↓	RAM (...↑↓	Data disks ↑↓	Max IOPS ↑↓	Temporary stor...↑↓	Premium disk s...↑↓	Cost/month (es...↑↓
DS1_v2	Standard	General purpose	1	3.5	4	3200	7	Yes	\$42.41
DS2_v2	Standard	General purpose	2	7	8	6400	14	Yes	\$84.82
DS3_v2	Standard	General purpose	4	14	16	12800	28	Yes	\$170.38

Premium SSD sizes	P1*	P2*	P3*	P4	P6	P10
Disk size in GiB	4	8	16	32	64	128
IOPS per disk	120	120	120	120	240	500

Observations (2)

Usually triggered by:

Large number of containers or large container images running on the node.

Aggressive logging (e.g. 3rd party logging, monitoring, audit tools)

Using OS disk as data disk in workload.

Observations (3)

Disk queue depth is an indicator that the OS disk for you worker nodes is throttled.

Search (Cmd+)

New chart Refresh Share Feedback

Local Time : Last 12 hours (Automatic - 5 minutes)

Count OS Disk Queue Depth (Preview) and Count OS Disk Write Operations/Sec (Preview) for aks-nodepool1-75400638-vmss

Add metric Add filter Apply splitting Line chart Drill into Logs New alert rule Pin to dashboard

aks-nodepool1-75400638-v... OS Disk Queue Depth (... Co... x

SCOPE

aks-nodepool1-7540063...

METRIC NAMESPACE


Virtual Machine Host

METRIC

OS Disk Write Oper...

AGGREGATION

Count



IO: Best practices

Do not use OS disk for data, use Persistent Volume instead.

Use a sufficiently-sized OS disk.

Use Ephemeral OS Disk (once it is out).

Use knode to mount docker data-drive to ephemeral disk.

Audit I/O from 3rd party add-ons such as Splunk, logstash, filesystem scanners and container scanners.

Set alert for the OS disks

More fun details here: <https://aka.ms/aks/io-throttle-issue>

- Memory overload
- IO overload
- SNAT Port exhaustion
- Insufficient quota

SNAT Port Exhaustion

Symptoms

Intermittent DNS resolution failure.

Node appears NotReady due to unable to reach API server.

Pods get “i/o timeout” when reaching API server or other network addresses.

```
E0124 10:08:30.169432      1 reflector.go:134]
```

```
github.com/coredns/coredns/plugin/kubernetes/controller.go:317: Failed to list *v1.Endpoints: Get  
https://xxxx.hcp.eastus.azmk8s.io:443/api/v1/endpoints?limit=500&resourceVersion=0: dial tcp  
20.44.xx.xx:443: i/o timeout
```

SNAT port exhaustion: Solution

Increase frontend IP.

Increase per VM outbound ports.

[Monitor failed "SNAT connections"](#)

Debug using "Used SNAT Ports", split by "Backend IP Addresses"

Search (Cmd+)


- Overview
- Activity log
- Access control (IAM)
- Tags
- Diagnose and solve problems
- Settings
- Frontend IP configuration
- Backend pools
- Health probes
- Load balancing rules
- Inbound NAT rules
- Outbound rules
- Properties
- Locks
- Export template
- Monitoring
- Alerts
- Metrics

Support + troubleshooting

New support request

New chart Refresh Share Feedback

Local Time : Last 4 hours (Automatic - 1 minute)





kubernetes - Metrics

Load balancer

[Documentation](#)

- Overview
- Activity log
- Access control (IAM)
- Tags
- Diagnose and solve problems

Settings

- Frontend IP configuration
- Backend pools
- Health probes
- Load balancing rules
- Inbound NAT rules
- Outbound rules
- Properties
- Locks
- Export template


Monitoring

- Alerts
- Metrics

[+ New chart](#) [Refresh](#) [Share](#) [Feedback](#)

Local Time : Last 48 hours (Automatic - 15 minutes)

Sum Used SNAT Ports (Preview) for kubernetes by Backend IP Address

[Add metric](#) [Add filter](#) [Apply splitting](#) [Line chart](#) [Drill into Logs](#) [New alert rule](#) [Pin to dashboard](#)kubernetes, **Used SNAT Ports (Preview)** Sum [Backend IP Address](#)

Insufficient quota

- Memory overload
- IO overload
- SNAT Port exhaustion
- Insufficient quota

Symptoms

Cluster auto-scaling fails

Manual scaling fails

Upgrade fails

Observations

Cluster upgrade requires at least one more VM (with CPU, GPU, IP).

Using Azure CNI requires additional IPs from the subnet. For each additional node, $\text{maxPod} + 1$ IP addresses are needed.

Higher reliability can cost more, such as using blue/green deployment.

```
$ az aks scale -g qike_rg -n cni-cluster -c 10
```

Deployment failed. Correlation ID: 98d0c9a1-edb0-414b-9518-xxxxxxx. VMSSAgentPoolReconciler retry failed: Code="SubnetIsFull" Message="Subnet subnet_cni_2 with address prefix 10.0.1.0/24 does not have enough capacity for 155 IP addresses."

Quota: Best practices

Plan ahead.

Request quota in advance. Sometimes quota can be hard to grant when the inventory in the particular region is low.

Architect the service to run in multiple regions and easy to migrate.

