



Deep Learning for Visual Computing

CNNs for Classification, Backpropagation

Christopher Pramerdorfer
Computer Vision Lab, TU Wien

Topics

CNNs for classification

- ▶ General considerations
- ▶ Modern architectures

Computing $\nabla L(\theta)$ with backpropagation

CNNs for Classification

Three main layer types (previous lecture)

- ▶ Convolutional (conv), pooling (pool), fully-connected (fc)

Architectures always include two stages

- ▶ Frontend for feature extraction (conv and pool layers)
- ▶ Backend for classification (fc layers)

CNNs for Classification

General Considerations

Many hyperparameters

- ▶ Layer composition and individual layer properties
- ▶ In addition to learning rate, weight decay, momentum

Unable to test sufficient number of combinations

- ▶ Testing one combination can take days

Following considerations help with architecture design

CNNs for Classification

General Considerations – Input Layer

Input image size

- ▶ Affects runtime quadratically
- ▶ Does not affect number of conv layer weights

Minimum input size depends on task and dataset

- ▶ Sizes larger than 224 pixels are uncommon
- ▶ Start small and see if increasing size helps

CNNs for Classification

General Considerations – Input Layer

Input size should be divisible by 2 often

- ▶ Spatial resolution reduced by 2 multiple times
- ▶ Avoids issues with non-integral output resolution

Accomplished by scaling/cropping input images

CNNs for Classification

General Considerations – Output Layer

Last layer is always fc layer with T neurons (T classes)

- ▶ Want to predict vector $\mathbf{w} \in \mathbb{R}^T$ of class scores

CNNs thus always end with a linear classifier

CNNs for Classification

General Considerations – Input Size Reduction

Spatial resolution (width W and height H) reduced to < 10

- ▶ Using multiple pooling or conv layers with stride
- ▶ Common final sizes : 1×1 , 3×3 , 5×5 , 7×7

Motivation

- ▶ Reduce computational complexity
- ▶ Reduce dimensionality of final feature vector
- ▶ Increase final receptive field size
- ▶ Gain robustness to small translations in image

CNNs for Classification

General Considerations – Input Size Reduction

Reduction layers distributed evenly in network

Number of layers depends on input image size

Common reduction layers (both halve W and H)

- ▶ Max-pooling with stride 2 and extent 2×2 or 3×3
- ▶ Convolution with stride 2

CNNs for Classification

General Considerations – Network Depth

Recall that depth equals number of layers with parameters

- ▶ Mainly determined by number of conv layers

Suitable number depends on overall architecture and task


- ▶ Different tasks require different levels of abstraction
- ▶ Hundreds of layers possible (few parameters)

CNNs for Classification

General Considerations – Network Depth

At least 6 conv layers required in most cases

Diminishing returns in terms of depth vs. performance



CNNs for Classification

General Considerations – Conv Layers

Distributed evenly in network

- ▶ One or several conv layers \Rightarrow pooling layer \Rightarrow repeat

Always use stride 1 and zero-padding to preserve W and H

- ▶ Or stride 2 to replace pooling layers

Always use ReLU activation function

- ▶ Faster gradient descent convergence

CNNs for Classification

General Considerations – Conv Layers

Prefer more layers with $c = 3$ to fewer with $c > 3$

- ▶ Fewer parameters, more expressive features (non-linearities)

Example (consistent depth D , 7×7 receptive field)

- ▶ One layer with $c = 7$: $7 \cdot 7 \cdot D \cdot D = 49D^2$ weights
- ▶ Three layers with $c = 3$: $3 \cdot 3 \cdot D \cdot D \cdot 3 = 27D^2$ weights

CNNs for Classification

General Considerations – Conv Layers

Exception : Initial conv layer with $c = 7$ and stride 2

- ▶ Common with large input sizes (see below)
- ▶ To reduce computational and memory requirements

Number of feature maps D should increase with network depth

- ▶ Initial number of 64 is common
- ▶ Final number often 256 or 512

CNNs for Classification

Modern Architectures

New architectures usually designed for LSVRC

- ▶ Large dataset : 1000 classes, 1.4m samples
- ▶ Large color images : usually 224 by 224 pixels




Image from umich.edu

CNNs for Classification

Modern Architectures – VGGNet (VGG-16 for LSVRC)

Homogeneous architecture

- ▶ 3×3 convolutions, 2×2 max-pooling
- ▶ Depth usually doubled after pooling



CNNs for Classification

Modern Architectures – VGGNet

Good template for conventional frontends

Changes based on dataset properties

- ▶ Number of pooling layers
- ▶ Initial number of feature maps
- ▶ Number of conv layers per pooling layer

CNNs for Classification

Modern Architectures – VGGNet


Many parameters due to complex classifier stage

- ▶ MLP with two large hidden layers
- ▶ VGG-16 for LSVRC : about 140m parameters in total

CNNs for Classification

Modern Architectures – Inception

Architecture composed of **Inception modules**



CNNs for Classification

Modern Architectures – Inception

Extract features at four different scales

- ▶ Four columns in Inception module
- ▶ Resulting in $D^1 + D^2 + D^3 + D^4$ feature maps


$1 \times 1 \times D_l$ convolutions with $D_l \ll D_{l-1}$

- ▶ Perform depth dimensionality reduction
- ▶ Limit depth and increase efficiency

CNNs for Classification

Modern Architectures – Inception

Example architecture for LSVRC (GoogLeNet)



CNNs for Classification

Modern Architectures – Inception

Efficient architecture

- ▶ In terms of FLOPs and parameters (GoogLeNet : $\approx 7\text{m}$)

Aggressive input size reduction at beginning

- ▶ Initial conv layer with $c = 7$ and stride 2

Simple and efficient backend

- ▶ **Average pooling** with extent $W_{l-1} \times H_{l-1}$ (output : 1×1)
- ▶ Followed by linear classifier

CNNs for Classification

Modern Architectures – ResNet

Current state-of-the-art architecture

Frontend consisting of multiple **residual blocks**




Image adapted from [2]

CNNs for Classification

Modern Architectures – ResNet

Motivation

- ▶ Very deep networks are hard to optimize
- ▶ Larger training error despite increased capacity




Image adapted from [2]

CNNs for Classification

Modern Architectures – ResNet

Residual blocks facilitate training of very deep networks

- ▶ Learn additive residual function \mathcal{F} with respect to x
- ▶ Provides guidance (learn what to add/remove from x)




Image adapted from [2]

CNNs for Classification

Modern Architectures – ResNet

Residual blocks facilitate training of very deep networks

- ▶ Implemented using **shortcut (skip) connections**
- ▶ **Residual networks** currently reach depths up to 1000





Image adapted from [2]

CNNs for Classification

Modern Architectures – ResNet

ResNet-34 for LSVRC



CNNs for Classification

Modern Architectures – ResNet

Aggressive input size reduction at beginning

Input size reduction using strided convolutions

Same efficient backend as GoogLeNet

CNNs for Classification

Modern Architectures – Review

Same input size and number of input size reductions

Number of feature maps increases with network depth

- ▶ Same initial (64) and final (512) counts
- ▶ Good guideline (but should tune on validation set)

State-of-the-art networks

- ▶ Are deep (many conv layers) and have simple linear backend
- ▶ Attempt to learn features that achieve linear separability

CNNs for Classification

Architecture Selection

What works well on ImageNet works well in general

- ▶ Above architectures perform well on many datasets

Suggestions

- ▶ Use a deep ResNet for optimal performance
- ▶ Inception is good alternative if efficiency is relevant
- ▶ VGGNet (with simpler backend) is a decent baseline

Backpropagation

CNNs are trained just like linear models

- ▶ Loss function $L(\theta)$ (cross-entropy loss)
- ▶ Minibatch gradient descent

We already know everything except how to compute $\nabla L(\theta)$

- ▶ Can be done efficiently using backpropagation

Backpropagation

Recall that neural networks are computational graphs

- ▶ Function $f : \mathbf{x} \mapsto \mathbf{w}$ composed of other functions
- ▶ Loss function of neural networks is again graph

Backpropagation algorithm computes derivatives in such graphs

- ▶ Via recursive application of the chain rule

Backpropagation

Fundamental Neural Network Expressions

Neural networks decompose to graphs of few basic expressions

- ▶ $f^1(x_1, x_2) = x_1 x_2$
- ▶ $f^2(x_1, x_2) = x_1 + x_2$
- ▶ $f^3(x_1, x_2) = \max(x_1, x_2)$

Backpropagation

Fundamental Neural Network Expressions

The corresponding derivatives are

- ▶ $f_{x_1}^1(x_1, x_2) = x_2$ and $f_{x_2}^1(x_1, x_2) = x_1$
- ▶ $f_{x_1}^2(x_1, x_2) = 1$ and $f_{x_2}^2(x_1, x_2) = 1$
- ▶ $f_{x_1}^3(x_1, x_2) = 1$ if $x_1 \geq x_2$ else 0
- ▶ $f_{x_2}^3(x_1, x_2) = 1$ if $x_2 \geq x_1$ else 0

$f_{x_1}^1 = \partial f^1 / \partial x_1$ is partial derivative of f^1 with respect to x_1

Backpropagation

Derivatives in Graphs

Simple example : expression $e(a, b) = (a + b)(b + 1)$




Image from [colah.github.org](https://colah.github.io)

Backpropagation

Derivatives in Graphs

Evaluation (**forward pass**) with $a = 2$ and $b = 1$




Image from [colah.github.org](https://colah.github.io)

Backpropagation

Derivatives in Graphs

Every node can compute **local gradients** independently




Image from [colah.github.org](https://colah.github.io)

Backpropagation

Derivatives in Graphs

Can compute remaining gradients from local ones

- ▶ Using multivariate chain rule

To compute $f_{x_d}(\mathbf{x})$

- ▶ Multiply local gradients along every path from x_d to f
- ▶ Sum over all resulting values to obtain result

Backpropagation

Derivatives in Graphs

$$e_a(2,1) = c_a(2,1) \cdot e_c(2,1) = 1 \cdot 2 = 2$$

$$e_b(2,1) = \dots = 1 \cdot 2 + 1 \cdot 3 = 5$$




Image from [colah.github.org](https://colah.github.io)

Backpropagation

Derivatives of $L(\theta)$

Recall that $L(\theta)$ is average over S per-sample losses $l_s(\theta)$

- ▶ Compute gradient $\nabla l_s(\theta)$ for all $s \in \{1, \dots, S\}$
- ▶ Average gradients to obtain $L(\theta)$


Above algorithm allows us to compute $\nabla l_s(\theta)$

- ▶ Can decompose any network to fundamental expressions
- ▶ Can do same for l_s (some additional expressions like $\exp(x)$)
- ▶ Composition of both is again graph

Backpropagation

Derivatives of $L(\theta)$


Example : linear classifier with $D = 2$ and $T = 2$



Backpropagation

Derivatives of $L(\theta)$

“Attached” decomposed cross-entropy loss l_s



Backpropagation

Derivatives of $L(\theta)$

Can compute $\nabla l_s(\theta)$

- ▶ Perform forward pass
- ▶ Compute all local gradients
- ▶ Compute $\partial l_s / \partial \theta_k$ for all parameters θ_k as above

Works but too inefficient

- ▶ Number of paths grows exponentially with graph complexity

Backpropagation

Path Factorization

Three paths from X to Y , three paths from Y to Z

$$\partial Z / \partial X = \alpha\delta + \alpha\epsilon + \alpha\zeta + \beta\delta + \beta\epsilon + \beta\zeta + \gamma\delta + \gamma\epsilon + \gamma\zeta$$

- ▶ 9 paths from X to Z




Image from [colah.github.org](https://colah.github.io)

Backpropagation

Path Factorization

Much more efficient to factorize paths instead

- ▶ $\partial Z / \partial X = (\alpha + \beta + \gamma)(\delta + \epsilon + \zeta)$

Can use **reverse-mode differentiation** of Z to obtain factorization

- ▶ Computes derivative of Z with respect to every node
- ▶ Efficiently by touching every edge only once
- ▶ Called **backpropagation** in neural network community

Backpropagation

Algorithm

Start at output node e and move towards inputs

At every node n

- ▶ For every child c , compute local gradient $l_c = \partial c / \partial n$
- ▶ For every child c , compute $m_c = l_c \cdot \partial e / \partial c$ ($\partial e / \partial e = 1$)
- ▶ Compute $\partial e / \partial n$ as sum over all m_c

Backpropagation

Example 1




Image from [colah.github.org](https://colah.github.io)

Backpropagation

Example 2





Image from [colah.github.org](https://colah.github.io)

Backpropagation

Example 3


Forward pass using current parameters and training sample



Backpropagation

Example 3


Forward pass using current parameters and training sample



Backpropagation

Example 3


Backward pass step 1



Backpropagation

Example 3


Backward pass step 2



Backpropagation

Example 3


Backward pass step 3



Backpropagation

Example 3


Backward pass step 4



Backpropagation

Example 3


Backward pass step 5



Backpropagation

Example 3

Backward pass step 6 (and so on ...)



Backpropagation

Backpropagation allows training of large networks

- ▶ Efficiency increase by factor of million and more

In practice decomposition is not as fine (vectorization)

- ▶ E.g. backward pass through conv layer is again convolution

Bibliography

- [1] *Going deeper with convolutions*, CVPR, 2015.
- [2] *Deep residual learning for image recognition*, CVPR, 2016.