

Domain Services

Table of Contents

1. Domain Services.....	1
1.1. Other Guides	1
2. Introduction	2
2.1. Types of Domain Service	2
2.2. Public API vs Internal Services	3
2.3. Using the services.....	3
2.4. Overriding the services.....	4
2.5. Command and Events (1.13.0-SNAPSHOT)	5
3. Presentation Layer SPI	8
3.1. ContentMappingService	11
3.2. EmailNotificationService	12
3.3. ErrorReportingService	14
3.4. ExceptionRecognizer	17
3.5. GridSystemService	19
3.6. GridLoaderService	21
3.7. GridService	22
3.8. HintStore	23
3.9. LocaleProvider	25
3.10. RoutingService	26
3.11. TranslationService	27
3.12. TranslationsResolver	28
3.13. UrlEncodingService	29
3.14. UserProfileService	30
4. Presentation Layer internal SPI	32
4.1. ContentNegotiationService	32
4.2. RepresentationService	38
5. Application Layer API.....	41
5.1. AcceptHeaderService	43
5.2. ActionInvocationContext	45
5.3. BackgroundService2	47
5.4. CommandContext	53
5.5. InteractionContext (1.13.0-SNAPSHOT)	58
5.6. MessageService	58
5.7. SessionManagementService	60
5.8. TitleService	61
5.9. TransactionService	62
5.10. WrapperFactory	63
6. Application Layer SPI	67

6.1. BackgroundCommandService	68
6.2. CommandService	70
6.3. HomePageProviderService	72
7. Application Layer internal SPI	74
7.1. CommandDtoServiceInternal (1.13.0-SNAPSHOT)	74
7.2. InteractionDtoServiceInternal (1.13.0-SNAPSHOT)	75
8. Core/Domain API	76
8.1. ClockService	77
8.2. ConfigurationService	80
8.3. DomainObjectContainer	81
8.4. EventBusService	91
8.5. FactoryService	99
8.6. Scratchpad	100
8.7. UserService	102
9. Integration API	105
9.1. BookmarkService2	106
9.2. DeepLinkService	108
9.3. EmailService	109
9.4. GuiceBeanProvider	111
9.5. JaxbService	113
9.6. MementoService	114
9.7. XmlSnapshotService	117
10. Metadata API	122
10.1. ApplicationFeatureRepository	123
10.2. LayoutService	124
10.3. MetaModelService	126
10.4. ServiceRegistry	127
10.5. SwaggerService	128
11. Testing	130
11.1. FixtureScriptsDefault	130
11.2. SudoService	131
11.3. FixtureScriptsSpec'nProvider	133
12. Persistence Layer API	135
12.1. IsisJdoSupport	135
12.2. MetricsService (1.13.0-SNAPSHOT)	140
12.3. QueryResultsCache	140
12.4. RepositoryService	143
13. Persistence Layer SPI	150
13.1. AuditingService3	151
13.2. EventSerializer	153
13.3. PublisherService (1.13.0-SNAPSHOT)	156

13.4. PublishingService	158
13.5. UserRegistrationService.....	163
14. Persistence Layer internal SPI	166
14.1. AuditingServiceInternal (1.13.0-SNAPSHOT)	166
14.2. ChangedObjectsServiceInternal (1.13.0-SNAPSHOT)	166
14.3. PublishingServiceInternal (1.13.0-SNAPSHOT)	167
15. Bootstrapping SPI	168
15.1. ClassDiscoveryService	168

Chapter 1. Domain Services

This guide documents Apache Isis' domain services, both those that act as an API (implemented by the framework for your domain objects to call), and those domain services that act as an SPI (implemented by your domain application and which are called by the framework).

1.1. Other Guides

Apache Isis documentation is broken out into a number of user, reference and "supporting procedures" guides.

The user guides available are:

- [Fundamentals](#)
- [Wicket viewer](#)
- [Restful Objects viewer](#)
- [Security](#)
- [Testing](#)
- [Beyond the Basics](#)

The reference guides are:

- [Annotations](#)
- [Domain Services](#) (this guide)
- [Configuration Properties](#)
- [Classes, Methods and Schema](#)
- [Apache Isis Maven plugin](#)

The remaining guides are:

- [Developers' Guide](#) (how to set up a development environment for Apache Isis and contribute back to the project)
- [Committers' Guide](#) (release procedures and related practices)

Chapter 2. Introduction

2.1. Types of Domain Service

The domain services also group into various broad categories. Many support functionality of the various layers of the system (presentation layer, application layer, core domain, persistence layer); others exist to allow the domain objects to integrate with other bounded contexts, or provide various metadata (eg for development-time tooling). The diagram below shows these categories:



A small number of domain services can be considered both API and SPI; a good example is the [EmailService](#) that is of direct use for domain objects wishing to send out emails, but is also used by the framework to support the [user registration](#) functionality supported by the [Wicket viewer](#). The same is true of the [EventBusService](#); this can be used by domain objects to broadcast arbitrary events, but is also used by the framework to automatically emit events for `@Action#domainEvent()` etc.

For these hybrid services we have categorized the service as an "API" service. This chapter therefore contains only the strictly SPI services.

This rest of this guide is broken out into several chapters, one for each of the various types/categories of domain service.

2.2. Public API vs Internal Services

The vast majority of Apache Isis' domain services are defined in Apache Isis' applib (`o.a.i.core:isis-core-applib` module) as stable, public classes. Importantly, this also minimizes the coupling between your code and Apache Isis, allowing you to easily mock out these services in your unit tests.

The framework also defines a number of "internal" services. These are not part of the framework's formal API, in that they use classes that are outside of the applib. These are documented here, but should be thought of as part of the internal design of the framework, and are liable to change from release to release.

2.3. Using the services

Apache Isis includes an extensive number of domain services for your domain objects to use; simply define the service as an annotated field and Apache Isis will inject the service into your object.

For example:

```
public class Customer {  
  
    public void sendEmail( String subject, String body) {  
        List<String> cc = Collections.emptyList;  
        List<String> bcc = Collections.emptyList;  
        emailService.send(getEmailAddress(), cc, bcc, subject, body);  
    }  
    public boolean hideSendEmail() {  
        return !emailService.isConfigured();  
    }  
  
    @Inject  
    EmailService emailService;  
}
```

①

① Service automatically injected by the framework.

For objects that are already persisted, the service is automatically injected just after the object is rehydrated by JDO/DataNucleus.

For transient objects (instantiated programmatically), the `FactoryService`'s `instantiate()` method (or the deprecated `DomainObjectContainer`'s `newTransientInstance()` method) will automatically inject the services.

Alternatively the object can be instantiated simply using `new`, then services injected using `ServiceRegistry`'s `injectServicesInto(…)` method (or the deprecated `DomainObjectContainer`'s `injectServicesInto(…)` method).

2.4. Overriding the services

The framework provides default implementations for many of the domain services. This is convenient, but sometimes you will want to replace the default implementation with your own service implementation.

The trick is to use the `@DomainServiceLayout#menuOrder()` attribute, specifying a low number (typically "`1`").



For a small number of domain services, all implementations are used (following the chain-of-responsibility pattern), not just the first one. The services in question are: `ContentMappingService`, `GridSystemService`, and `RoutingService`.

For example, suppose you wanted to provide your own implementation of `LocaleProvider`. Here's how:

```
@DomainService(  
    nature = NatureOfService.DOMAIN  
)  
@DomainServiceLayout(  
    menuOrder = "1" ①  
)  
public class MyLocaleProvider implements LocaleProvider {  
    @Override  
    public Locale getLocale() {  
        return ...  
    }  
}
```

① takes precedence over the default implementation.

It's also quite common to want to decorate the existing implementation (ie have your own implementation delegate to the default); this is also possible and quite easy (if using `1.10.0` or later). The idea is to have the framework inject all implementations of the service, and then to delegate to the first one that isn't "this" one:

```

@DomainService(nature=NatureOfService.DOMAIN)
@DomainServiceLayout(
    menuOrder = "1"
①
)
public class MyLocaleProvider implements LocaleProvider {
    @Override
    public Locale getLocale() {
        return getDelegateLocaleProvider().getLocale();
②
    }
    private LocaleProvider getDelegateLocaleProvider() {
        return Iterables.tryFind(localeProviders, input -> input != this).orNull();
③
    }
    @Inject
    List<LocaleProvider> localeProviders;
④
}

```

- ① takes precedence over the default implementation when injected elsewhere.
- ② this implementation merely delegates to the default implementation
- ③ find the first implementation that isn't *this* implementation (else infinite loop!)
- ④ injects all implementations, including this implemenation

The above code could be improved by caching the delegateLocaleProvider once located (rather than searching each time).

2.5. Command and Events (1.13.0-SNAPSHOT)

A good number of the domain services manage the execution of action invocations/property edits, along with the state of domain objects that are modified as a result of these. These services capture information which can then be used for various purposes, most notably for auditing or for publishing events, or for deferring execution such that the execution be performed in the background at some later date.

The diagram below shows how these services fit together. The outline boxes are services while the coloured boxes represent data structures - defined in the applib and therefore accessible to domain applications - which hold various information about the executions.

To explain:

- the (request-scoped) **CommandContext** captures the user's intention to invoke an action or edit a property; this is held by the **Command** object.
- if a **CommandService** has been configured, then this will be used to create the **Command** object implementation, generally so that it can then also be persisted.

If the action or property is annotated to be invoked in the background (using `@Action#command…()` or `@Property#command…()`) then no further work is done. But, if the action/property is to be executed in the foreground, then the interaction continues.

- the (request-scoped) `InteractionContext` domain service acts as a factory for the `Interaction` object, which keeps track of the call-graph of executions (`Interaction.Execution`) of either action invocations or property edits. In the majority of cases there is likely to be just a single top-level node of this graph, but for applications that use the `WrapperFactory` extensively each successive call results in a new child execution.
- before and after each action invocation/property edit, a `domain event` is may be broadcast to all subscribers. Whether this occurs depends on whether the action/property has been annotated (using `@Action#domainEvent()` or `@Property#domainEvent()`).

(Note that susbcribers will also receive events for vetoing the action/property; this is not shown on the diagram).

- As each execution progresses, and objects that are modified are "enlisted" into the (internal) `ChangedObjectsServiceInternal` domain service. Metrics as to which objects are merely loaded into memory are also captured using the `MetricsService` (not shown on the diagram).
- At the end of each execution, details of that execution are published through the (internal) `PublisherServiceInternal` domain service. This is only done for actions/properties annotated appropriate (with `@Action#publishing()` or `@Property#publishing()`).

The internal service delegates in turn to any registered `PublishingService` (deprecated) and also to any registered `PublisherServices` (there may be more than one).

- At the end of all executions, details of all changed objects are published, again through the (internal) `PublisherServiceInternal` to any registered `PublishingService` or `PublisherService` implementations. Only domain objects specified to be published with `@DomainObject#publishing()` are published.
- Also at the end of all executions, details of all changed properties are passed to any registered `AuditingService` by way of the (internal) `AuditingServiceInternal` domain service.

Implementations of `CommandService` can use the `Command#getMemento()` method to obtain a XML equivalent of that `Command`, reified using the `cmd.xsd` schema. This can be converted back into a `CommandDto` using the `CommandDtoUtils` utility class (part of the applib).

Similarly, implementations of `PublisherService` can use the `InteractionDtoUtils` utility class to obtain a `InteractionDto` representing the interaction, either just for a single execution or for the entire call-graph. This can be converted into XML in a similar fashion.

Likewise, the `PublishedObjects` class passed to the `PublisherService` at the end of the interaction provides the `PublishedObjects#getDto()` method which returns a `ChangesDto` instance. This can be converted into XML using the `ChangesDtoUtils` utility class.

One final point: multiple `PublisherService` implementations are supported because different implementations may have different responsibilities. For example, the (non-ASF) `Isis addons' publishmq` module is responsible for publishing messages onto an ActiveMQ event bus, for inter-system communication. However, the SPI can also be used for profiling; each execution within the

call-graph contains metrics of the number of objects loaded or modified as a result of that execution, and thus could be used for application profiling. The framework provides a default [PublisherServiceLogging](#) implementation that logs this using SLF4J.

Chapter 3. Presentation Layer SPI

Domain service SPIs for the presentation layer influence how the Apache Isis viewers behave.

The table below summarizes the presentation layer SPIs defined by Apache Isis. It also lists their corresponding implementation, either a default implementation provided by Apache Isis itself, or provided by one of the in (non-ASF) [Isis Addons](#) modules.

Table 1. Presentation Layer SPI

SPI	Description	Implementation	Notes
<code>o.a.i.applib.services.conmap</code> <code>ContentMappingService</code>	(Attempt to) map the returned data into the representation required by the client's HTTP <code>Accept</code> header.		Replaces (and simplifies) the earlier <code>ContentMappingService</code> that defined an SPI using classes internal to the framework. + No default implementation.
<code>o.a.i.applib.services.userreg</code> <code>EmailNotificationService</code>	Notify a user during self-registration of users.	<code>EmailNotificationService-Default</code> <code>o.a.i.coreisis-core-runtime</code>	depends on: a configured <code>EmailService</code>
<code>o.a.i.applib.services.error</code> <code>ErrorReportingService</code>	Record details of an error occurring in the system (eg in an external incident recording system such as JIRA), and return a more friendly (jargon-free) message to display to the end user, with optional reference (eg <code>XXX-1234</code>).	(none)	

SPI	Description	Implementation	Notes
<code>o.a.i.applib.services.exceprecog.ExceptionRecognizer2</code>	Convert certain exceptions (eg foreign or unique key violation in the database) into a format that can be rendered to the end-user.	<code>ExceptionRecognizerCompositeForJdoObjectStore</code> <code>o.a.i.coreisis-core-applib</code>	Extensible using composite pattern if required
<code>o.a.i.applib.services.grid.GridSystemService</code>	Validates and normalizes the grid layout for a domain class (with respect to a particular grid system such as Bootstrap3), also providing a default grid (for those domain classes where there is no grid layout).	<code>GridSystemServiceBS3</code> <code>o.a.i.coreisis-core-metamodel</code>	
<code>o.a.i.applib.services.grid.GridLoaderService</code>	Responsible for loading a grid layout for a domain class, eg from a <code>layout.xml</code> file.	<code>GridLoaderServiceDefault</code> <code>o.a.i.coreisis-core-metamodel</code>	
<code>o.a.i.applib.services.grid.GridService</code>	A facade on top of both <code>GridLoaderService</code> and <code>GridSystemService</code> , thus being able to return normalized grids for any domain class.	<code>GridServiceDefault</code> <code>o.a.i.coreisis-core-metamodel</code>	
<code>o.a.i.applib.services_hint.HintStore</code>	Stores UI hints on a per-object basis. For example, the viewer remembers which tabs are selected, and for collections which view is selected (eg table or hidden), which page of a table to render, or whether "show all" (rows) is toggled.	<code>HintStoreUsingWicketSession</code> <code>o.a.i.viewerisis-viewer-wicket-impl</code>	
<code>o.a.i.applib.services_i18n.LocaleProvider</code>	Request-scoped service to return the locale of the current user, in support of i18n (ie so that the app's UI, messages and exceptions can be translated to the required locale by the <code>TranslationService</code> .	<code>LocaleProviderWicket</code> <code>o.a.i.viewerisis-viewer-wicket-impl</code>	

SPI	Description	Implementation	Notes
<code>o.a.i.applib.services.routing</code> <code>RoutingService</code>	Return an alternative object than that returned by an action.	<code>RoutingServiceDefault</code> <code>o.a.i.coreisis-core-applib</code>	The default implementation will return the home page (per <code>HomePageProviderService</code>) if a void or null is returned. Used by the Wicket viewer only.
<code>o.a.i.applib.services.i18n</code> <code>TranslationService</code>	Translate an app's UI, messages and exceptions for the current user (as per the locale provided by <code>LocalProvider</code> .	<code>TranslationServicePo</code> <code>o.a.i.coreisis-core-runtime</code>	related services: <code>TranslationServicePo</code> Menu depends on: <code>TranslationsResolver</code> , <code>LocaleProvider</code>
<code>o.a.i.applib.services.i18n</code> <code>TranslationsResolver</code>	Obtain translations for a particuar phrase and locale, in support of i18n (ie so that the app's UI, messages and exceptions can be translated to the required locale by the <code>TranslationService</code>	<code>TranslationsResolver</code> <code>Wicket</code> <code>o.a.i.viewerisis-viewer-wicket-impl</code>	
<code>o.a.i.applib.services.urlencoded</code> <code>UrlEncodingService</code>	Converts strings into a form safe for use within a URL. Used to convert view models mementos into usable URL form.	<code>UrlEncodingService</code> <code>UsingBaseEncoding</code> <code>o.a.i.applibisis-core-applib</code>	
<code>o.a.i.applib.services.userprof</code> <code>UserProfileService</code>	Obtain an alternative (usually enriched/customized) name for the current user, to render in the UI.		

Key:

- `o.a.i` is an abbreviation for `org.apache.isis`
- `o.ia.m` is an abbreviation for `org.isisaddons.module`

There are also a number of presentation layer SPIs that use internal classes. These can be found in the [next chapter](#).

3.1. ContentMappingService

The `ContentMappingService` supports the (default implementation of the) `ContentNegotiationService` allowing the `RestfulObjects viewer` to allow domain objects to be transformed into some other format as specified by the HTTP `Accept` header.

See `ContentNegotiationService` for further discussion.



Unlike most other domain services, the framework (that is, `ContentNegotiationService`) will check *all* available implementations of `ContentMappingService` to convert the domain object to the requested media type, rather than merely the first implementation found; in other words it uses the chain-of-responsibility pattern. Services are checked in the ordering defined by `@DomainServiceLayout#menuOrder()`. The mapped object used will be the first non-`null` result returned by an implementation.

3.1.1. SPI

The SPI defined by this service is:

```
public interface ContentMappingService {
    Object map(Object object,
               List<MediaType> acceptableMediaTypes); ①
}
```

- ① typically the input is a domain object (whose structure might change over time), and the output is a DTO (whose structure is guaranteed to be preserved over time)
- ② as per the caller's HTTP `Accept` header

In versions prior to `v1.12.0`, this interface resided in a different package, internal to the `Restful Objects` viewer, and defined a slightly different signature that used an internal enum:

```
public interface ContentMappingService {
    Object map(Object object,
               List<MediaType> acceptableMediaTypes,
               RepresentationType representationType); ①
}
```

- ① enum representing the requested representation; only ever take a value of `DOMAIN_OBJECT` or `ACTION_RESULT`.

3.1.2. Implementations

No default implementations are provided by Apache Isis framework itself.

However, the (non-ASF) [Isis addons' todoapp](#) includes a sample implementation to convert its `ToDoItem` entity into a (JAXB annotated) `ToDoItemDto`. The source code is:

```
@DomainService(nature = NatureOfService.DOMAIN)
public class ContentMappingServiceForToDoItem implements ContentMappingService {
    @Override
    public Object map(
        final Object object,
        final List<MediaType> acceptableMediaTypes) {
        if(object instanceof ToDoItem) {
            for (MediaType acceptableMediaType : acceptableMediaTypes) {
                final Map<String, String> parameters = acceptableMediaType
                    .getParameters();
                final String className = parameters.get("x-ro-domain-type");
                if(className.equals(ToDoItemV1_1.class.getName())) {
                    return newToDoItemV1_1((ToDoItem) object);
                }
            }
        }
        return null;
    }
    private ToDoItemV1_1 newToDoItemV1_1(final ToDoItem ToDoItem) {
        final ToDoItemV1_1 dto = new ToDoItemV1_1();
        dto.setToDoItem(ToDoItem);
        dto.setDescription(ToDoItem.getDescription());
        ...
        return dto;
    }
    ...
}
```

3.1.3. Related Services

This service is a companion to the default implementation of the `ContentNegotiationService`.

3.2. EmailNotificationService

The `EmailNotificationService` supports the `user registration` (self sign-up) features of the `Wicket viewer` whereby a user can sign-up to access an application by providing a valid email address.

The Wicket viewer will check whether an implementation of this service (and also the `UserRegistrationService`) is available, and if so will (unless configured not to) expose a sign-up page where the user enters their email address. A verification email is sent using this service; the email includes a link back to the running application. The user then completes the registration process (choosing a user name, password and so on) and the Wicket viewer creates an account for them

(using the aforementioned [UserRegistrationService](#)).

The role of this service in all of this is to format and send out emails for the initial registration, or for password resets.

The default implementation of this service uses the [EmailService](#), which must be configured in order for user registration to be enabled.

3.2.1. SPI

The SPI defined by this service is:

```
public interface EmailNotificationService extends Serializable {  
    @Programmatic  
    boolean send(EmailRegistrationEvent ev);          ①  
    @Programmatic  
    boolean send>PasswordResetEvent ev);            ②  
    @Programmatic  
    boolean isConfigured();                         ③  
}
```

① sends an email to verify an email address as part of the initial user registration

② sends an email to reset a password for an already-registered user

③ determines whether the implementation was configured and initialized correctly

If `isConfigured()` returns false then it is *not* valid to call `send(...)` (and doing so will result in an [IllegalStateException](#) being thrown).

3.2.2. Implementation

The framework provides a default implementation, [o.a.i.core.runtime.services.userreg.EmailNotificationServiceDefault](#) that constructs the emails to send.

Alternative Implementations

The text of these email templates is hard-coded as resources, in other words baked into the core jar files. If you need to use different text then you can of course always write and register your own implementation to be used instead of Isis' default.

If you have configured an alternative email service implementation, it should process the message body as HTML.

If you wish to write an alternative implementation of this service, note that (unlike most Apache Isis domain services) the implementation is also instantiated and injected by Google Guice. This is because [EmailNotificationService](#) is used as part of the [user registration](#) functionality and is used by Wicket pages that are accessed outside of the usual Apache Isis runtime.

This implies a couple of additional constraints:

- first, implementation class should also be annotated with `@com.google.inject.Singleton`
- second, there may not be any Apache Isis session running. (If necessary, one can be created on the fly using `IsisContext.doInSession(...)`)

To ensure that your alternative implementation takes the place of the default implementation, register it explicitly in `isis.properties`.

3.2.3. Registering the Service

Assuming that the `configuration-and-annotation` services installer is configured (implicit if using the `AppManifest` to bootstrap the app) then Apache Isis' default implementation of `EmailNotificationService` service is automatically registered and injected (it is annotated with `@DomainService`) so no further configuration is required.

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide).

3.2.4. Related Services

As noted elsewhere, the default implementation of this service uses `EmailService`. This service has no specific configuration properties but does require that the `EmailService` has been configured.

Conversely, this service is used by (Isis' default implementation of) `UserRegistrationService`.

3.3. ErrorReportingService

The `ErrorReportingService` service is an optional SPI that provides the ability to record any errors/exceptions that might occur in the application into an external incident recording system (such as JIRA). The service also allows a user-friendly (jargon-free) error message to be returned and rendered to the end-user, along with an optional incident reference (eg a JIRA issue `XXX-1234`).

3.3.1. SPI

The SPI defined by this service is:

```
public interface ErrorReportingService {
    Ticket reportError(ErrorDetails errorDetails);
}
```

where `ErrorDetails` provided to the service is:

```

public class ErrorDetails {
    public String getMainMessage() { ... }          ①
    public boolean isRecognized() { ... }           ②
    public boolean isAuthorizationCause() { ... }   ③
    public List<String> getStackTraceDetailList() { ④
}

```

- ① the main message to be displayed to the end-user. The service is responsible for translating this into the language of the end-user (it can use `LocaleProvider` if required).
- ② whether this message has already been recognized by an `ExceptionRecognizer` service. Generally this converts potentially non-recoverable (fatal) exceptions into recoverable exceptions (warnings) as well providing an alternative mechanism for generating user-friendly error messages.
- ③ whether the cause of the exception was due to a lack of privileges. In such cases the UI restricts the information shown to the end-user, to avoid leaking potentially sensitive information
- ④ the stack trace of the exception, including the trace of any exceptions in the causal chain. These technical details are hidden from the user and only shown for non-recoverable exceptions.

and `Ticket` (returned by the service) has the constructor:

```

public class Ticket implements Serializable {
    public Ticket(
        final String reference,               ①
        final String userMessage,             ②
        final String details) { ... }         ③
}

```

- ① is a unique identifier that the end-user can use to track any follow-up from this error. For example, an implementation might automatically log an issue in a bug tracking system such as JIRA, in which case the reference would probably be the JIRA issue number <tt>XXX-1234</tt>.
- ② a short, jargon-free message to display to the end-user.
- ③ is optional additional details to show. For example, these might include text on how to recover from the error, or workarounds, or just further details on contacting the help desk if the issue is severe and requires immediate attention.

3.3.2. Implementation

The (non-ASF) [Isis addons' kitchensink](#) app provides an example implementation:

```

@DomainService( nature = NatureOfService.DOMAIN )
public class KitchensinkErrorReportingService implements ErrorReportingService {
    private int ticketNumber = 1;
    @Override
    public Ticket reportError(final ErrorDetails errorDetails) {
        return new Ticket(
            nextTicketReference(),
            "The Kitchen sink app is sorry to report that: " + errorDetails
            .getMainMessage(),
            "These are additional details for the end-user to read.\n"
            + "This content should be able to span many lines.\n"
            + "More detail.\n"
            + "Some suggested work-arounds.\n"
            + "Details of how to contact help desk.\n"
            + "And so on");
    }
    String nextTicketReference() {
        return "" + ticketNumber++;
    }
}

```

which is rendered as:

Kitchensink

 The Kitchen sink app is sorry to report that: A non-recoverable exception has been thrown.

These are additional details for the end-user to read.

This content should be able to span many lines.

More detail.

Some suggested work-arounds.

Details of how to contact help desk.

And so on

Please quote reference: 1

Exception details

3.3.3. Registering the Services

There is no default implementation of this service. To register your own implementation (and assuming that an [AppManifest](#) is being used to [bootstrap the app](#)), then just ensure that the implementation is on the classpath and the module containing the implementation is returned in [AppManifest#getModules\(\)](#).

3.4. ExceptionRecognizer

The `ExceptionRecognizer` service provides the mechanism for both the domain programmer and also for components to be able to recognize and handle certain exceptions that may be thrown by the system. Rather than display an obscure error to the end-user, the application can instead display a user-friendly message.

For example, the JDO/DataNucleus Objectstore provides a set of recognizers to recognize and handle SQL constraint exceptions such as uniqueness violations. These can then be rendered back to the user as expected errors, rather than fatal stacktraces.

It is also possible to provide additional implementations, registered in `isis.properties`. Unlike other services, where any service registered in `isis.properties` replaces any default implementations, in the case of this service all implementations registered are "consulted" to see if they recognize an exception (the chain-of-responsibility pattern).

3.4.1. SPI

The SPI defined by this service is:

```
public interface ExceptionRecognizer2 ... {
    public enum Category { ... }                                ①
    ...
    public static class Recognition { ...
        private Category category;
        private String reason;
        ...
    }
    @Programmatic
    public Recognition recognize2(Throwable ex);               ③
    ...
    @Deprecated
    @Programmatic
    public String recognize(Throwable ex);                      ④
}
```

- ① an enumeration of varies categories of exceptions that are recognised
- ② represents the fact that an exception has been recognized as has been converted into a user-friendly message, and has been categorized
- ③ the main API, to attempt to recognize an exception
- ④ deprecated API which converted exceptions into strings (reasons), ie without any categorization.
This is no longer called.

The categories are:

```

public interface ExceptionRecognizer2 ... {
    public enum Category {
        CONSTRAINT_VIOLATION,           ①
        NOT_FOUND,                      ②
        CONCURRENCY,                   ③
        CLIENT_ERROR,                  ④
        SERVER_ERROR,                  ⑤
        OTHER                          ⑥
    }
    ...
}

```

- ① a violation of some declarative constraint (eg uniqueness or referential integrity) was detected.
- ② the object to be acted upon cannot be found (404)
- ③ a concurrency exception, in other words some other user has changed this object.
- ④ recognized, but for some other reason... 40x error
- ⑤ 50x error
- ⑥ recognized, but uncategorized (typically: a recognizer of the original [ExceptionRecognizer API](#)).

In essence, if an exception is recognized then it is also categorized. This lets the viewer act accordingly. For example, if an exception is raised from the loading of an individual object, then this is passed by the registered [ExceptionRecognizers](#). If any of these recognize the exception as representing a not-found exception, then an Apache Isis [ObjectNotFoundException](#) is raised. Both the viewers interprets this correctly (the [Wicket viewer](#) as a suitable error page, the [Restful Objects viewer](#) as a 404 status return code).

If the implementation recognizes the exception then it returns a user-friendly message to be rendered (by the viewer) back to the user; otherwise it returns `null`. There is no need for the implementation to check for exception causes; the causal chain is unwrapped by Apache Isis core and each exception in the chain will also be passed through to the recognizer (from most specific to least). The recognizer implementation can therefore be as fine-grained or as coarse-grained as it wishes.

3.4.2. Implementation

The framework provides two default implementations:

- `o.a.i.core.metamodel.services.container.DomainObjectContainerDefault` provided by Apache Isis core is itself an [ExceptionRecognizer](#), and will handle [ConcurrencyExceptions](#). It will also handle any application exceptions raised by the system (subclasses of `o.a.i.applib.RecoverableException`).
- `o.a.i.objectstore.jdo.applib.service.exceprecog.ExceptionRecognizerCompositeForJdoObjectStore` bundles up a number of more fine-grained implementations:
 - `ExceptionRecognizerForSQLIntegrityConstraintViolationUniqueOrIndexException`
 - `ExceptionRecognizerForJDOObjectNotFoundException`
 - `ExceptionRecognizerForJDODataStoreException`

If you want to recognize and handle additional exceptions (for example to capture error messages specific to the JDBC driver you might be using), then create a fine-grained implementation of `ExceptionRecognizer2` for the particular error message (there are some convenience implementations of the interface that you can subclass from if required) and register in `isis.properties`.

3.4.3. Registering the Services

Assuming that the `configuration-and-annotation` services installer is configured (implicit if using the `AppManifest` to bootstrap the app) then the default implementations provided by the framework (`DomainObjectContainerDefault` and `ExceptionRecognizerCompositeForJdoObjectStore`) will be registered.

In addition, you can register any further exception recognizers in `isis.properties`:

```
isis.services=..., \
    com.mycompany.myapp.MyExceptionRecognizer, \
    ...
```



Prior to 1.9.0, the `ExceptionRecognizerCompositeForJdoObjectStore` also required manual registration.

If the JDO exception recognizers are not required (rather unlikely), then they can be disabled en masse using the configuration property `isis.services.ExceptionRecognizerCompositeForJdoObjectStore.disable`.

3.5. GridSystemService

The `GridSystemService` encapsulates a single layout grid system which can be used to customize the layout of domain objects. In particular this means being able to return a "normalized" form (validating and associating domain object members into the various regions of the grid) and in providing a default grid if there is no other metadata available.

The framework provides a single such grid implementation, namely for `Bootstrap3`.



Unlike most other domain services, the framework will check *all* available implementations of `GridSystemService` to obtain available grid systems, rather than merely the first implementation found; in other words it uses the chain-of-responsibility pattern. Services are called in the order defined by `@DomainServiceLayout#menuOrder()`.

Note though that each concrete implementation must also provide corresponding Wicket viewer components capable of interpreting the grid layout.

3.5.1. SPI

The SPI defined by this service is:

```

public interface GridSystemService<G extends Grid> {
    Class<? extends Grid> gridImplementation();          ①
    String tns();                                       ②
    String schemaLocation();                            ③
    Grid defaultGrid(Class<?> domainClass);          ④
    void normalize(G grid, Class<?> domainClass);     ⑤
    void complete(G grid, Class<?> domainClass);       ⑥
    void minimal(G grid, Class<?> domainClass);        ⑦
}

```

- ① The concrete subclass of `Grid` supported by this implementation. As noted in the introduction, there can be multiple implementations of this service, but there can only be one implementation per concrete subclass. As is normal practice, the service with the lowest `@DomainServiceLayout#menuOrder()` takes precedence.
- ② the target namespace for this grid system. This is used when generating the XML. The Bootstrap3 grid system provided by the framework returns the value <http://isis.apache.org/applib/layout/grid/bootstrap3>.
- ③ the schema location for the XSD. The Bootstrap3 grid system provided by the framework returns the value <http://isis.apache.org/applib/layout/grid/bootstrap3/bootstrap3.xsd>.
- ④ a default grid, eg two columns in ratio 4:8. Used when no existing grid layout exists for a domain class.
- ⑤ Validates and normalizes a grid, modifying the grid so that all of the domain object's members (properties, collections, actions) are bound to regions of the grid. This is done using existing metadata, most notably that of the `@MemberOrder` annotation. Such a grid, if persisted as the layout XML file for the domain class, allows the `@MemberOrder` annotation to be removed from the source code of the domain class (but other annotations must be retained).
- ⑥ Takes a normalized grid and enriches it with additional metadata (taken from Apache Isis' internal metadata) that can be represented in the layout XML. Such a grid, if persisted as the layout XML file for the domain class, allows all layout annotations (`@ActionLayout`, `@PropertyLayout` and `@CollectionLayout`) to be removed from the source code of the domain class.
- ⑦ Takes a normalized grid and strips out removes all members, leaving only the grid structure. Such a grid, if persisted as the layout XML file for the domain class, requires that the `@MemberOrder` annotation is retained in the source code of said class in order to bind members to the regions of the grid.

3.5.2. Implementation

The framework provides `GridSystemServiceBS3`, an implementation that encodes the bootstrap3 grid system. (The framework also provides `Wicket viewer` components that are capable of interpreting and rendering this metadata).

3.5.3. Registering the Services

Assuming that the `configuration-and-annotation` services installer is configured (implicit if using the `AppManifest` to bootstrap the app), then the Bootstrap3 default implementation of

`GridSystemService` is automatically registered and injected, and no further configuration is required.

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide).

3.5.4. Related Services

This service is used by `GridService`.

3.6. GridLoaderService

The `GridLoaderService` provides the ability to load the XML layout (grid) for a domain class.

3.6.1. SPI

The SPI defined by this service is:

```
public interface GridLoaderService {  
    boolean supportsReloading();  
    void remove(Class<?> domainClass);  
    boolean existsFor(Class<?> domainClass);  
    Grid load(final Class<?> domainClass);  
}
```

- ① whether dynamic reloading of layouts is enabled. The default implementation enables reloading for prototyping, disables in production
- ② support metamodel invalidation/rebuilding of spec, eg as called by this [Object mixin](#) action.
- ③ whether any persisted layout metadata (eg a `.layout.xml` file) exists for this domain class.
- ④ returns a new instance of a `Grid` for the specified domain class, eg as loaded from a `layout.xml` file. If none exists, will return null (and the calling `GridService` will use `GridSystemService` to obtain a default grid for the domain class).

3.6.2. Implementation

The framework provides a default implementation of this service, namely `GridLoaderServiceDefault`. This implementation loads the grid from its serialized representation as a `.layout.xml` file, loaded from the classpath.

For example, the layout for a domain class `com.mycompany.myapp.Customer` would be loaded from `com/mycompany/myapp/Customer.layout.xml`.

3.6.3. Registering the Services

Assuming that the `configuration-and-annotation` services installer is configured (implicit if using the [AppManifest](#) to bootstrap the app), then the default implementation of `GridLoaderService` is automatically registered and injected, and no further configuration is required.

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide).

3.6.4. Related Services

This service is used by `GridService`.

3.7. GridService

The `GridService` provides the ability to load the XML layout (grid) for a domain class. To do this it delegates:

- to `GridLoaderService` to load a pre-existing layout for the domain class, if possible
- to `GridSystemService` to normalize the grid with respect to Apache Isis' internal metamodel, in other words to ensure that all of the domain objects' properties, collections and actions are associated with regions of the grid.

Once a grid has been loaded for a domain class, this is cached internally by Apache Isis' internal meta model (in the `GridFacet` facet). If running in prototype mode, any subsequent changes to the XML will be detected and the grid rebuilt. This allows for dynamic reloading of layouts, providing a far faster feedback (eg if tweaking the UI while working with end-users). Dynamic reloading is disabled in production mode.

3.7.1. SPI

The SPI defined by this service is:

```
public interface GridService {  
    boolean supportsReloading();  
    void remove(Class<?> domainClass);  
    boolean existsFor(Class<?> domainClass);  
    Grid load(final Class<?> domainClass);  
    Grid defaultGridFor(Class<?> domainClass);  
    Grid normalize(final Grid grid);  
    Grid complete(Grid grid);  
    Grid minimal(Grid grid);  
}
```

- ① whether dynamic reloading of layouts is enabled. The default implementation enables reloading for prototyping, disables in production
- ② support metamodel invalidation/rebuilding of spec, eg as called by this [Object mixin](#) action.
- ③ whether any persisted layout metadata (eg a `.layout.xml` file) exists for this domain class. Just delegates to corresponding method in `GridLoaderService`.
- ④ returns a new instance of a `Grid` for the specified domain class, eg as loaded from a `layout.xml` file. If none exists, will return null (and the calling `GridService` will use `GridSystemService` to obtain a default grid for the domain class).

- ⑤ returns a default grid, eg two columns in ratio 4:8. Used when no existing grid layout exists for a domain class.
- ⑥ validates and normalizes a grid, modifying the grid so that all of the domain object's members (properties, collections, actions) are bound to regions of the grid. This is done using existing metadata, most notably that of the `@MemberOrder` annotation. Such a grid, if persisted as the layout XML file for the domain class, allows the `@MemberOrder` annotation to be removed from the source code of the domain class (but other annotations must be retained).
- ⑦ Takes a normalized grid and enriches it with additional metadata (taken from Apache Isis' internal metadata) that can be represented in the layout XML. Such a grid, if persisted as the layout XML file for the domain class, allows all layout annotations (`@ActionLayout`, `@PropertyLayout` and `@CollectionLayout`) to be removed from the source code of the domain class.
- ⑧ Takes a normalized grid and strips out removes all members, leaving only the grid structure. Such a grid, if persisted as the layout XML file for the domain class, requires that the `@MemberOrder` annotation is retained in the source code of said class in order to bind members to the regions of the grid.

The first four methods just delegate to the corresponding methods in `GridSystemService`, while the last four delegate to the corresponding method in `GridSystemService`. The service inspects the `Grid`'s concrete class to determine which actual `GridSystemService` instance to delegate to.

3.7.2. Implementation

The framework provides a default implementation of this service, namely `GridServiceDefault`.

3.7.3. Registering the Services

Assuming that the `configuration-and-annotation` services installer is configured (implicit if using the `AppManifest` to bootstrap the app), then the default implementation of `GridLoaderService` is automatically registered and injected, and no further configuration is required.

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide). That said, there should be little reason to use a different implementation; if behaviour does need to be changed, it would also be possible to replace the implementation of either the `GridLoaderService` or the `GridSystemService`.

3.7.4. Related Services

This service calls `GridLoaderService` and `GridSystemService`.

This service is called by `LayoutService`, exposed in the UI through `LayoutServiceMenu` (to download the layout XML as a zip file for all domain objects) and the `downloadLayoutXml()` mixin (to download the layout XML for a single domain object).

3.8. HintStore

The `HintStore` service defines an SPI for the `Wicket viewer` to store UI hints on a per-object basis. For example, the viewer remembers which tabs are selected, and for collections which view is

selected (eg table or hidden), which page of a table to render, or whether "show all" (rows) is toggled.

The default implementation of this service uses the HTTP session. The service is an SPI because the amount of data stored could potentially be quite large (for large numbers of users who use the app all day). An SPI makes it easy to plug in an alternative implementation that is more sophisticated than the default (eg implementing MRU/LRU queue, or using a NoSQL database, or simply to disabling the functionality altogether).

3.8.1. SPI

The SPI of `HintStore` is:

```
public interface HintStore {  
    String get(final Bookmark bookmark, String hintKey);  
    void set(final Bookmark bookmark, String hintKey, String value);  
    void remove(final Bookmark bookmark, String hintKey);  
    void removeAll(Bookmark bookmark);  
    Set<String> findHintKeys(Bookmark bookmark);  
}
```

- ① obtain a hint (eg which tab to open) for a particular object. Object identity is represented by `Bookmark`, as per the `BookmarkService`, so that alternative implementations can easily serialize this state to a string.
- ② set the state of a hint. (The value of) all hints are represented as strings.
- ③ remove a single hint for an object;
- ④ remove all hints
- ⑤ obtain all known hints for an object

3.8.2. Implementation

The core framework provides a default implementation of this service (`org.apache.isis.viewer.wicket.viewer.services.HintStoreUsingWicketSession`).

3.8.3. Registering the Service

Assuming that the `configuration-and-annotation` services installer is configured (implicit if using the `AppManifest` to bootstrap the app) then Apache Isis' core implementation of `HintStore` service is automatically registered and injected (it is annotated with `@DomainService`) so no further configuration is required.

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide).

3.8.4. Related Services

The `Wicket viewer` exposes the "clear hints" mixin action that is for use by end-users of the

application to clear any UI hints that have accumulated for a domain object.

3.9. LocaleProvider

The `LocaleProvider` service is one of the services that work together to implement Apache Isis' support for i18n, being used by Isis' default implementation of `TranslationService`.

The role of the service itself is simply to return the `Locale` of the current user.



For the "big picture" and further details on Apache Isis' i18n support, see [here](#).

3.9.1. SPI

The SPI defined by this service is:

```
public interface LocaleProvider {  
    @Programmatic  
    Locale getLocale();  
}
```

This is notionally request-scoped, returning the `Locale` of the current user; *not* that of the server. (Note that the implementation is not required to actually be `@RequestScoped`, however).

3.9.2. Implementation

Isis' [Wicket viewer](#) provides an implementation of this service (`LocaleProviderWicket`) which leverages Apache Wicket APIs.



Currently there is no equivalent implementation for the [RestfulObjects viewer](#).

3.9.3. Registering the Services

Assuming that the `configuration-and-annotation` services installer is configured (implicit if using the `AppManifest` to bootstrap the app), *and* that the [Wicket viewer](#) is being used, then an implementation of `LocaleProvider` is automatically registered and injected (it is annotated with `@DomainService`) so no further configuration is required.

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide).

3.9.4. Related Services

This service works in conjunction with `TranslationService` and `TranslationsResolver` in order to provide i18n support.

3.10. RoutingService

The `RoutingService` provides the ability to return (and therefore render) an alternative object from an action invocation.

There are two primary use cases:

- if an action returns an aggregate leaf (that is, a child object which has an owning parent), then the parent object can be returned instead.

For example, an action returning `OrderItem` might instead render the owning `Order` object. It is the responsibility of the implementation to figure out what the "owning" object might be.

- if an action returns `null` or is `void`, then return some other "useful" object.

For example, return the home page (eg as defined by the `@HomePage` annotation).

Currently the routing service is used only by the [Wicket viewer](#); it is ignored by the [Restful Objects](#) viewer.



Unlike most other domain services, the framework will check *all* available implementations of `RoutingService` to return a route, rather than the first implementation found; in other words it uses the chain-of-responsibility pattern. Services are called in the order defined by `@DomainServiceLayout#menuOrder()`. The route used will be the result of the first implementation checked that declares that it can provide a route.

3.10.1. SPI

The SPI defined by this service is:

```
public interface RoutingService {  
    @Programmatic  
    boolean canRoute(Object original); ①  
    @Programmatic  
    Object route(Object original);      ②  
}
```

① whether this implementation recognizes and can "route" the object. The `route(...)` method is only called if this method returns `true`.

② the object to use; this may be the same as the original object, some other object, or (indeed) `null`.

3.10.2. Implementation

The framework provides a default implementation which will always return the original object provided, or the home page if a `null` or `void` was provided. It uses the `HomePageProviderService`.

There can be multiple implementations of `RoutingService` registered. These are checked in turn

(chain of responsibility pattern), ordered according to `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide). The route from the first service that returns `true` from its `canRoute(...)` method will be used.

3.10.3. Registering the Services

Assuming that the `configuration-and-annotation` services installer is configured (implicit if using the `AppManifest` to [bootstrap the app](#)) then Apache Isis' default implementation of `RoutingService` service is automatically registered and injected (it is annotated with `@DomainService`) so no further configuration is required.

3.10.4. Related Services

The default implementation of this service uses the `HomePageProviderService`.

3.11. TranslationService

The `TranslationService` is the cornerstone of Apache Isis' i18n support. Its role is to be able to provide translated versions of the various elements within the Apache Isis metamodel (service and object classes, properties, collections, actions, action parameters) and also to translate business rule (disable/valid) messages, and exceptions. These translations provide for both singular and plural forms.



For the "big picture" and further details on Apache Isis' i18n support, see [here](#).

3.11.1. SPI

The SPI defined by this service is:

```
public interface TranslationService {  
    @Programmatic  
    String translate(String context, String text);          ①  
    @Programmatic  
    String translate(String context,                      ②  
                    String singularText,  
                    String pluralText, int num);  
  
    enum Mode { READ, WRITE; }  
    @Programmatic  
    Mode getMode();                                     ③  
}
```

① translate the text, in the locale of the "current user".

② return a translation of either the singular or the plural text, dependent on the `num` parameter, in the locale of the "current user"

③ whether this implementation is operating in read or in write mode.

If in read mode, then the translations are expected to be present.

If in write mode, then the implementation is saving translation keys, and will always return the untranslated translation.

3.11.2. Implementation

The Apache Isis framework provides a default implementation (`TranslationServicePo`) that uses the GNU `.pot` and `.po` files for translations. It relies on the `LocaleProvider` service (to return the `Locale` of the current user) and also the `TranslationsResolver` service (to read existing translations).

The framework also provides a supporting `TranslationServicePoMenu` provides menu items under the "Prototyping" secondary menu for controlling this service and downloading `.pot` files for translation.

For more details on the implementation, see [i18n support](#).

3.11.3. Registering the Services

Assuming that the `configuration-and-annotation` services installer is configured (implicit if using the `AppManifest` to [bootstrap the app](#)) then Apache Isis' core implementation of `TranslationService` service (along with the supporting menu service) are automatically registered and injected (it is annotated with `@DomainService`) so no further configuration is required.

If the menu items are not required then these can be suppressed either using security or by implementing a [vetoing subscriber](#).

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide).

3.11.4. Related Menus

The `TranslationServicePoMenu` menu exposes the `TranslationServicePo` service's `toPot()` method so that all translations can be downloaded as a single file.

3.11.5. Related Services

This service works in conjunction with `LocaleProvider` and `TranslationsResolver` in order to provide i18n support.

3.12. TranslationsResolver

The `TranslationsResolver` service is one of the services that work together to implement Apache Isis' support for i18n, being used by Isis' default implementation of `TranslationService`.

The role of the service itself is locate and return translations.



For the "big picture" and further details on Apache Isis' i18n support, see [here](#).

3.12.1. SPI

The SPI defined by this service is:

```
public interface TranslationsResolver {  
    @Programmatic  
    List<String> readLines(final String file);  
}
```

3.12.2. Implementation

Isis' [Wicket viewer](#) provides an implementation of this service ([TranslationsResolverWicket](#)) which leverages Apache Wicket APIs. This searches for translation files in the standard [WEB-INF/](#) directory.



Currently there is no equivalent implementation for the [RestfulObjects viewer](#).

3.12.3. Registering the Service

Assuming that the `<code>configuration-and-annotation</code>` services installer is configured (implicit if using the `<code>AppManifest</code>` to [`bootstrap`](#) the app``), and that the [`Wicket viewer`](#) is being used, then an implementation of `<code>TranslationsResolver</code>` is automatically registered and injected (it is annotated with `<code>@DomainService</code>`) so no further configuration is required.

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide).

3.12.4. Related Services

This service works in conjunction with [LocaleProvider](#) and [TranslationService](#) in order to provide i18n support.

3.13. UrlEncodingService

The [UrlEncodingService](#) defines a consistent way to convert strings to/from a form safe for use within a URL. The service is used by the framework to map [view model](#) mementos (derived from the state of the view model itself) into a form that can be used as a view model. When the framework needs to recreate the view model (for example to invoke an action on it), this URL is converted back into a view model memento, from which the view model can then be hydrated.

Defining this functionality as an SPI has two use cases:

- first, (though some browsers support longer strings), there is a limit of 2083 characters for URLs. For view model mementos that correspond to large strings (as might occur when serializing a JAXB `@XmlElement`-annotated view model), the service provides a hook.

For example, each memento string could be mapped to a GUID held in some cluster-aware

cache.

- the service provides the ability, to encrypt the string in order to avoid leakage of potentially sensitive state within the URL.

The framework provides a default implementation of this service, [UrlEncodingServiceUsingBaseEncoding](#) (also in the applib) that uses base-64 encoding to [UTF-8](#) charset.

3.13.1. SPI

The SPI defined by the service is:

```
public interface UrlEncodingService {  
    @Programmatic  
    public String encode(final String str);      ①  
    @Programmatic  
    public String decode(String str);            ②  
}
```

① convert the string (eg view model memento) into a string safe for use within an URL

② unconvert the string from its URL form into its original form URL

3.13.2. Implementation

The framework provides a default implementation ([UrlEncodingServiceUsingBaseEncoding](#)) that simply converts the string using base-64 encoding and UTF-8 character set. As already noted, be aware that the maximum length of a URL should not exceed 2083 characters. For large view models, there's the possibility that this limit could be exceeded; in such cases register an alternative implementation of this service.

To use an alternative implementation, use [@DomainServiceLayout#menuOrder\(\)](#) (as explained in the [introduction](#) to this guide).

3.14. UserProfileService

The [UserProfileService](#) provides the ability for the domain application to return supplementary metadata about the current user. This information is used (by the [Wicket viewer](#)) to customize the appearance of the tertiary "Me" menu bar (top right). For example, rather than display the username, instead the user's first and last name could be displayed.

Another use case is to allow the user to switch context in some fashion or other. This might be to emulate a sort of "sudo"-like function, or perhaps to focus on some particular set of data.

3.14.1. SPI

The SPI defined by the service is:

```

public interface UserProfileService {
    @Programmatic
    String userProfileName();      ①
}

```

① is used (in the Wicket viewer) as the menu name of the tertiary "Me" menu bar.


If the method returns `null` or throws an exception then the framework will default to using the current user name.

In the future this API may be expanded; one obvious possibility is to return a profile photo or avatar URL.

3.14.2. Implementation

There is no default implementation of this service provided by the core Apache Isis framework.

An example implementation can be found in the (non-ASF) [Isis addons' todoapp](#):



The screenshot shows a web browser window for the 'ToDo App' application. The URL is `localhost:8080/wicket/wicket/page?3`. The top navigation bar includes links for 'Prototyping', 'Hi sven!', and 'Logout'. Below the header, there are two main sections: 'By Category' and 'By Date Range'. The 'By Category' section displays a table with columns for 'Category' (Professional, Domestic, Other), 'Not Yet Complete' tasks (e.g., OpenSource: 0, Consulting: 0, Education: 0, Marketing: 0), and 'Complete' tasks (e.g., OpenSource: 0, Consulting: 0, Education: 0, Marketing: 0). The 'By Date Range' section displays a table with columns for 'Date Range' (OverDue, Today, Tomorrow, ThisWeek, Later, Unknown) and 'Count' (all values are 0).



Currently this feature is not integrated with Apache Isis' authentication mechanisms; the information provided is purely metadata provided for presentation purposes only.

Chapter 4. Presentation Layer internal SPI

These domain services are internal to the framework, controlling various aspects of the presentation layer.



We do not guarantee that [semantic versioning](#) will be honoured for these SPIs.

The table below summarizes the presentation layer internal SPIs defined by Apache Isis. It also lists their corresponding implementation, either a default implementation provided by Apache Isis itself, or provided by one of the (non-ASF) [Isis Addons](#) modules.

Table 2. "Internal" SPI Services

SPI	Maven Module Impl'n (g: a:)	Implementation	Notes
<code>o.a.i.v.ro. rendering.service.conneg. ContentNegotiationService</code>	Encodes the algorithm that delegates to any registered <code>ContentMappingServices</code> .	<code>ContentNegotiation Service- XRoDomainType o.a.i.core isis-core-viewer- restfulobjects- rendering</code>	
<code>o.a.i.v.ro. rendering.service. RepresentationService</code>	Generates the representations, delegating to any registered <code>ContentNegotiationServices</code> .	<code>RepresentationServ ice- ForRestfulObjects o.a.i.core isis-core-viewer- restfulobjects- rendering</code>	

Key:

- `o.a.i.v.ro` is an abbreviation for `org.apache.isis.viewer.restfulobjects`

4.1. ContentNegotiationService

The `ContentNegotiationService` is a plug-in point for the `RestfulObjects viewer` so that it can generate representations according to HTTP `Accept` header of the request. This idea is discussed in section 34.1 of the [Restful Objects spec](#) v1.0.

The principal motivation is to allow more flexible representations to be generated for REST clients that (perhaps through their use of a certain Javascript library, say) expect, or at least works best with, a certain style of representation.

Another use case is to support "third party" REST clients over which you have no control. In this scenario you *must not* naively expose entities through the RO viewer, because over time those entities will inevitably evolve and change their structure. If the entities were exposed directly then those REST clients will break.

Instead you need to create some sort of stable facade over your domain entities, one which you will

preserve even if the domain entities change. There are three ways in which you can do this:

- first is to solve the problem at the domain layer by defining a regular Apache Isis [view model](#). This is then surfaced over the RO viewer.

If the underlying entities change, then care must be taken to ensure that structure of the view model nevertheless is unchanged.

- a second option is to solve the problem at the persistence layer, but defining a (SQL) view in the database and then [mapping this](#) to a (read-only) entity. Again this is surfaced by the RO viewer.

If the underlying tables change (as the result of a change in their corresponding domain entities) then once more the view must be refactored so that it still presents the same structure.

- our third option is to solve the problem at the presentation layer, using the [ContentNegotiationService](#) described in this section.


The [ContentNegotiationService](#) is responsible for inspecting the HTTP [Accept](#) header, and use this to select the correct representation to render.

The Apache Isis framework provides a default implementation of [ContentNegotiationService](#) which inspects the "x-ro-domaintype" component of the HTTP [Accept](#) header. If present, this implementation will delegate to the companion [ContentMappingService](#) service, if configured.

A typical implementation of [ContentMappingService](#) will convert the domain object into some sort of DTO (data transfer object) as specified by the "x-ro-domaintype". If this DTO is annotated with JAXB or Jackson mappings, then the RO viewer (courtesy of the underlying [RestEasy](#) framework) can serialize these directly

What all that means is that, if the underlying entities change, we are required to update the mappings in the [ContentMappingService](#) to map to the same DTOs.

This diagram illustrates the three options available:



4.1.1. SPI

The SPI defined by this service is:

```

public interface ContentNegotiationService {
    @Programmatic
    Response.ResponseBuilder buildResponse(                    ①
        RepresentationService.Context2 renderContext2,
        ObjectAdapter objectAdapter);
    @Programmatic
    Response.ResponseBuilder buildResponse(                    ②
        RepresentationService.Context2 renderContext2,
        ObjectAndProperty objectAndProperty);
    @Programmatic
    Response.ResponseBuilder buildResponse(                    ③
        RepresentationService.Context2 renderContext2,
        ObjectAndCollection objectAndCollection);
    @Programmatic
    Response.ResponseBuilder buildResponse(                    ④
        RepresentationService.Context2 renderContext2,
        ObjectAndAction objectAndAction);
    @Programmatic
    Response.ResponseBuilder buildResponse(                    ⑤
        RepresentationService.Context2 renderContext2,
        ObjectAndActionInvocation objectAndActionInvocation);
}

```

① representation of a single object, as per section 14.4 of the RO spec, v1.0

② representation of a single property of an object, as per section 16.4 of the RO spec v1.0

③ representation of a single collection of an object, as per section 17.5 of the RO spec v1.0

④ representation of a single action (prompt) of an object, as per section 18.2 of the RO spec v1.0

⑤ representation of the results of a single action invocation, as per section 19.5 of the RO spec v1.0

These methods provide:

- a `RepresentationService.Context2` which provides access to request-specific context (eg HTTP headers), session-specific context (eg authentication) and global context (eg configuration settings)
- an object representing the information to be rendered

eg `ObjectAdapter`, `ObjectAndProperty`, `ObjectAndCollection` etc

In all cases, returning `null` will result in the regular RO spec representation being returned.



This is an "internal" SPI, meaning that it uses types that are not part of the Isis applib. We do not guarantee that [semantic versioning](#) will be honoured for these APIs.

4.1.2. Implementation

`ContentNegotiationServiceAbstract` (in `o.a.i.v.ro.rendering.service.conneg`) provides a no-op

implementation of the SPI, along with supporting methods:

```
public abstract class ContentNegotiationServiceAbstract implements  
ContentNegotiationService {  
    ...  
    protected Object objectOf(final ObjectAdapter objectAdapter) { ... }  
    protected Object returnedObjectOf(ObjectAndActionInvocation  
objectAndActionInvocation) { ... }  
  
    protected Class<?> loadClass(String cls) { ... }  
  
    protected void ensureJaxbAnnotated(Class<?> domainType) { ... }  
    protected void ensureDomainObjectAssignable(  
        String xRoDomainType, Class<?> domainType, Object domainObject) { ... }  
}
```

As discussed in the introduction, the framework also provides a default implementation, `o.a.i.v.ro.rendering.service.conneg.ContentNegotiationServiceXRoDomainType`. This handles content negotiation for two of the possible representations, object representations and for action result representations:

- For object representations it will handle requests with HTTP `Accept` headers of the form:
 - `application/json;profile=urn:org.restfulobjects:repr-types/object;x-ro-domain-type=...`
 - `application/xml;profile=urn:org.restfulobjects:repr-types/object;x-ro-domain-type=...`
- for action result representations it will similarly handle requests with HTTP `Accept` headers of the form:
 - `application/json;profile=urn:org.restfulobjects:repr-types/action-result;x-ro-domain-type=...`
 - `application/xml;profile=urn:org.restfulobjects:repr-types/action-result;x-ro-domain-type=...`

The value of the `x-ro-domain-type` parameter corresponds to the DTO to be mapped into by the `ContentMappingService`.

If the DTO is annotated with JAXB, then also note that the runtime type must be annotated with the JAXB `javax.xml.bind.annotation.XmlRootElement` so that RestEasy is able to unambiguously serialize it.

4.1.3. Usage

You can find an example of all these services in the (non-ASF) [Isis addons' todoapp](#). This defines a `ToDoItemDto` class that is JAXB annotated (it is in fact generated from an XSD).

The example app also includes an implementation of `ContentMappingService` that maps `todoapp.dom.module.todoitem.ToDoItem` entities to `todoapp.dto.module.todoitem.ToDoItemDto` classes.

A REST client can therefore request a DTO representation of an entity by invoking

```
http://localhost:8080/restful/objects/TODO/0
```

with an **Accept** header of:

```
application/xml;profile=urn:org.restfulobjects:repr-types/object;x-ro-domain-type=todoapp.dto.module.todoitem.ToDoItemDto
```

will result in an XML serialization of that class:


The screenshot shows the Postman interface. The URL in the address bar is `http://localhost:8080/restful/objects/TODO/0`. The method is set to `GET`. In the `Headers` section, there is one entry: `Accept: application/xml;profile=urn:org.restfulobj`. The response status is `200 OK` with a time of `247 ms`. The response body is displayed in a code editor with line numbers, showing the XML serialization of a `ToDoItemDto` object. The XML content includes fields like `oid`, `description`, `category`, `subcategory`, and `cost`.

```
<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<ToDoItemDto
  xmlns="http://module.dto.todoapp/todoitem.xsd">
  <oid>
    <objectType>TODO</objectType>
    <objectIdentifier>0</objectIdentifier>
  </oid>
  <description>Buy bread</description>
  <category>DOMESTIC</category>
  <subcategory>SHOPPING</subcategory>
  <cost>1.75</cost>
</ToDoItemDto>
```

while similarly hitting the same URL with an **Accept** header of:

```
application/json;profile=urn:org.restfulobjects:repr-types/object;x-ro-domain-type=todoapp.dto.module.todoitem.ToDoItemDto
```

will result in the JSON serialization of that class:



4.1.4. Configuration

The default `ContentNegotiationServiceXRoDomainType` implementation provides a [configuration property](#) which controls whether a mapped domain object is pretty-printed (formatted, indented) or not:

```
isis.services.ContentNegotiationServiceXRoDomainType.prettyPrint=true
```

If the property is not set, then the default depends on the [deployment type](#); production mode will disable pretty printing, while prototyping mode will enable it.

4.1.5. Registering the Services

Assuming that the [configuration-and-annotation](#) services installer is configured (implicit if using the `AppManifest` to [bootstrap the app](#)) then Apache Isis' default implementation of `ContentNegotiationService` service is automatically registered and injected (it is annotated with `@DomainService`) so no further configuration is required.

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide).

4.1.6. Related Services

The default implementation of `ContentNegotiationService` delegates to `ContentMappingService` (if present) to convert domain entities into a stable form (eg DTO).

The `ContentNegotiationService` is itself called by the (default implementation of)

[RepresentationService](#).

4.2. RepresentationService

The [RepresentationService](#) is the main plug-in point for the [RestfulObjects viewer](#) to generate representations.

The default implementation generates representations according to the [Restful Objects spec v1.0](#). However, it also delegates to the [ContentNegotiationService](#) which provides a mechanism for altering representations according to the HTTP [Accept](#) header.

The principal motivation is to allow more flexible representations to be generated for REST clients that (perhaps through their use of a certain Javascript library, say) expect, or at least works best with, a certain style of representation.

In all there are three domain services that can influence the representations generated: this service, [ContentNegotiationService](#) and the [ContentMappingService](#). The diagram below shows how these collaborate:

The [RepresentationServiceForRestfulObjects](#) is the default implementation of this service; likewise [ContentNegotiationServiceXRoDomainType](#) is the default implementation of the [ContentNegotiationService](#). If you inspect the source code you'll see that the default implementation of this service's primary responsibility is to generate the default Restful Objects representations. Therefore, if you what you want to do is to generate a *different _representation then in many cases replacing either this service _or the ContentNegotiationService* will be equivalent (you'll notice that their SPIs are very similar).

4.2.1. SPI

The SPI defined by this service is:

```

public interface RepresentationService {
    @Programmatic
    Response objectRepresentation(
        Context rendererContext,                               ①
        ObjectAdapter objectAdapter);

    @Programmatic
    Response propertyDetails(
        Context rendererContext,                           ②
        ObjectAndProperty objectAndProperty,
        MemberReprMode memberReprMode);

    @Programmatic
    Response collectionDetails(                         ③
        Context rendererContext,
        ObjectAndCollection objectAndCollection,
        MemberReprMode memberReprMode);

    @Programmatic
    Response actionPrompt(                            ④
        Context rendererContext,
        ObjectAndAction objectAndAction);

    @Programmatic
    Response actionResult(                           ⑤
        Context rendererContext,
        ObjectAndActionInvocation objectAndActionInvocation,
        ActionResultReprRenderer.SelfLink selfLink);
}

public static interface Context extends RendererContext {
    ObjectAdapterLinkTo getAdapterLinkTo();
}
}

```

① representation of a single object, as per section 14.4 of the RO spec, v1.0

② representation of a single property of an object, as per section 16.4 of the RO spec v1.0

③ representation of a single collection of an object, as per section 17.5 of the RO spec v1.0

④ representation of a single action (prompt) of an object, as per section 18.2 of the RO spec v1.0

⑤ representation of the results of a single action invocation, as per section 19.5 of the RO spec v1.0

These methods provide:

- a **RendererContext** which provides access to request-specific context (eg HTTP headers), session-specific context (eg authentication) and global context (eg configuration settings)
- an object representing the information to be rendered

eg **ObjectAdapter**, **ObjectAndProperty**, **ObjectAndCollection** etc

- for members, whether the representation is in read/write mode

ie **MemberReprMode**



This is an "internal" SPI, meaning that it uses types that are not part of the Isis applib. We do not guarantee that [semantic versioning](#) will be honoured for these APIs.

4.2.2. Implementation

As discussed in the introduction, the framework provides a default implementation, `o.a.i.v.ro.rendering.service.RepresentationServiceForRestfulObjects`. This delegates to `ContentNegotiationService` to generate an alternative representation; but if none is provided then it falls back on generating the representations as defined in the [Restful Objects spec v1.0](#).

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide).

4.2.3. Registering the Services

Assuming that the `configuration-and-annotation` services installer is configured (implicit if using the `AppManifest` to bootstrap the app) then Apache Isis' default implementation of `RepresentationService` service is automatically registered and injected (it is annotated with `@DomainService`) so no further configuration is required.

4.2.4. Related Services

The default implementation delegates to `ContentNegotiationService`, whose default implementation may delegate in turn to `ContentMappingService` (if present).

Chapter 5. Application Layer API

Domain service APIs for the application layer allow the domain objects to control aspects of the application layer, such as sending info messages back to the end-user.

The table below summarizes the application layer APIs defined by Apache Isis. It also lists their corresponding implementation, either a default implementation provided by Apache Isis itself, or provided by one of the in (non-ASF) [Isis Addons](#) modules.

Table 3. Application Layer API

API	Description	Implementation	Notes
<code>o.a.i.applib.services.acceptheader</code> <code>AcceptHeaderService</code>	Request-scoped access to HTTP Accept headers.	<code>AcceptHeaderServiceDefault</code> <code>o.a.i.core.isis-viewer-restfulobjects-rendering</code>	Populated only when the domain objects are accessed using the Restful Objects viewer .
<code>o.a.i.applib.services.actinv</code> <code>ActionInvocationContext</code>	Request-scoped access to whether action is invoked on object and/or on collection of objects	<code>ActionInvocationContext</code> <code>o.a.i.core.isis-core-applib</code>	API is also concrete class
<code>o.a.i.applib.services.background</code> <code>BackgroundService</code>	Programmatic persistence of commands to be persisted (so can be executed by a background mechanism, eg scheduler)	<code>BackgroundServiceDefault</code> <code>o.a.i.core.isis-core-runtime</code>	depends on: Background Command-Service

API	Description	Implementation	Notes
<code>o.a.i.applib.services.command</code> <code>CommandContext</code>	Request-scoped access to capture the user's intention to invoke an action or to edit a property.	<code>CommandContext</code> <code>o.a.i.core</code> <code>isis-core-applib</code>	API is also a concrete class. depends on: <code>CommandService</code> for persistent <code>Command</code> , else in-memory impl. used. The <code>InteractionContext</code> manages the actual execution of the command.
<code>o.a.i.applib.services.iactn</code> <code>InteractionContext</code>	(1.13.0-SNAPSHOT) Request-scoped access to the current member execution (action invocation or property edit), represented as the <code>Interaction</code> context.	<code>InteractionContext</code> <code>o.a.i.core</code> <code>isis-core-applib</code>	API is also a concrete class.
<code>o.a.i.applib.services.message</code> <code>MessageService</code>	Methods to inform or warn the user, or to raise errors.	<code>FactoryService-Default</code> <code>o.a.i.core</code> <code>isis-core-metamodel</code>	Supercedes methods in <code>DomainObjectContainer</code> .
<code>o.a.i.applib.services.sessmgmt</code> <code>SessionManagementService</code>	Methods for batching long-running work (eg data migration) into multiple sessions.	<code>SessionManagementService-Default</code> <code>o.a.i.core</code> <code>isis-core-runtime</code>	
<code>o.a.i.applib.services.title</code> <code>TitleService</code>	Methods to programmatically obtain the title or icon of a domain object.	<code>TitleService-Default</code> <code>o.a.i.core</code> <code>isis-core-metamodel</code>	Supercedes methods in <code>DomainObjectContainer</code> .

API	Description	Implementation	Notes
<code>o.a.i.applib.services.xactn.TransactionService</code>	Methods for managing transactions.	<code>TransactionServiceDefault o.a.i.core.isis-core-metamodel</code>	Supercedes methods in <code>DomainObjectContainer</code> .
<code>o.a.i.applib.services.wrapper.WrapperFactory</code>	Interact with another domain object "as if" through the UI (enforcing business rules, firing domain events)	<code>WrapperFactoryDefault o.a.i.core.isis-core-wrapper</code>	

Key:

- `o.a.i` is an abbreviation for `org.apache.isis`
- `o.ia.m` is an abbreviation for `org.isisaddons.module`

5.1. AcceptHeaderService

The `AcceptHeaderService` domain service is a `@RequestScoped` service that simply exposes the HTTP `Accept` header to the domain. Its intended use is to support multiple versions of a REST API, where the responsibility for content negotiation (determining which version of the REST API is to be used) is managed by logic in the domain objects themselves.



As an alternative to performing content negotiation within the domain classes, the `ContentNegotiationService` and `ContentMappingService` SPI domain services allow the framework to perform the content negotiation responsibility.

5.1.1. API & Implementation

The API defined by the service is:

```

@DomainService(nature = NatureOfService.DOMAIN)
@RequestScoped
public interface AcceptHeaderService {
    @Programmatic
    List<MediaType> getAcceptableMediaTypes();
```

①

②

① is `@RequestScoped`, so this domain service instance is scoped to a particular request and is then destroyed

② returns the list of media types found in the HTTP `Accept` header.

The default implementation is provided by




Note that the service will only return a list when the request is initiated through the [Restful Objects viewer](#). Otherwise the service will return `null`.

5.1.2. Usage

The intended use of this service is where there are multiple concurrent versions of a REST API, for backward compatibility of existing clients. The [AcceptHeaderService](#) allows the responsibility for content negotiation (determining which version of the REST API is to be used) to be performed by logic in the domain objects themselves.

The diagram below illustrated this:



The REST request is submitted to a domain service with a `nature` of `VIEW_REST_ONLY` (`MyRestApi` in the diagram). This uses the [AcceptHeaderService](#) to obtain the values of the HTTP `Accept` header. Based on this it delegates to the appropriate underlying domain service (with a nature of `DOMAIN` so that they are not exposed in the REST API at all).



The service does not define any conventions as to the format of the media types. The option is to use the media type's type/subtype, eg `application/vnd.myrestapi-v1+json`; an alternative is to use a media type parameter as a hint, eg `application/json;x-my-rest-api-version=1` (where `x-my-rest-api-version` is the media type parameter).

The Restful Objects specification does this something similar with its own `x-ro-domain-type` media type parameter; this is used by the [ContentMappingService](#) to determine how to map domain objects to view models/DTOs.

5.1.3. Registering the Service

Assuming that the `configuration-and-annotation` services installer is configured (implicit if using the `AppManifest` to `bootstrap the app`) then Apache Isis' default implementation of `AcceptHeaderService` class is automatically registered (it is annotated with `@DomainService`) so no further configuration is required.

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide).

5.2. ActionInvocationContext

The `ActionInvocationContext` domain service is a `@RequestScoped` service intended to support the implementation of "bulk" actions annotated with `@Action#invokeOn()`. This allows the user to select multiple objects in a table and then invoke the same action against all of them.

When an action is invoked in this way, this service allows each object instance to "know where it is" in the collection; it acts a little like an iterator. In particular, an object can determine if it is the last object to be called, and so can perform special processing, eg to return a summary calculated result.

5.2.1. API & Implementation

The API defined by the service is:

```
@DomainService(nature = NatureOfService.DOMAIN)
@RequestScoped
public static class ActionInvocationContext {
    public InvokedOn getInvokedOn() { ... }          ①
    public List<Object> getDomainObjects() { ... }    ②
    public int getSize() { ... }
    public int getIndex() { ... }                     ③
    public boolean isFirst() { ... }
    public boolean isLast() { ... }
}
```

- ① is `@RequestScoped`, so this domain service instance is scoped to a particular request and is then destroyed
- ② an enum set to either `OBJECT` (if action has been invoked on a single object) or `COLLECTION` (if has been invoked on a collection).
- ③ returns the list of domain objects which are being acted upon
- ④ is the 0-based index to the object being acted upon.

5.2.2. Usage

For actions that are void or that return null, Apache Isis will return to the list once executed. But for bulk actions that are non-void, Apache Isis will render the returned object/value from the last object invoked (and simply discards the object/value of all actions except the last).

One idiom is for the domain objects to also use the `Scratchpad` service to share information, for example to aggregate values. The `ActionInvocationContext#isLast()` method can then be used to determine if all the information has been gathered, and then do something with it (eg derive variance across a range of values, render a graph etc).

More prosaically, the `ActionInvocationContext` can be used to ensure that the action behaves appropriately depending on how it has been invoked (on a single object and/or a collection) whether it is called in bulk mode or regular mode. Here's a snippet of code from the bulk action in the Isis addon example `todoapp` (not ASF):

```
public class ToDoItem ... {
    @Action(invokeOn=InvokeOn.OBJECTS_AND_COLLECTIONS)
    public ToDoItem completed() {
        setComplete(true);
        ...
        return actionInvocationContext.getInvokedOn() == InvokedOn.OBJECT
            ? this ①
            : null; ②
    }
    @Inject
    ActionInvocationContext actionInvocationContext;
}
```

① if invoked as a regular action, return this object;

② otherwise (if invoked on collection of objects), return null, so that the [Wicket viewer](#) will re-render the list of objects

5.2.3. Registering the Service

Assuming that the `configuration-and-annotation` services installer is configured (implicit if using the `AppManifest` to `bootstrap the app`) then Apache Isis' default implementation of `ActionInvocationContext` class is automatically registered (it is annotated with `@DomainService`) so no further configuration is required.

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide).

5.2.4. Unit testing support

The `ActionInvocationContext` class also has a couple of static factory methods intended to support unit testing:

```

@DomainService(nature = NatureOfService.DOMAIN)
@RequestScoped
public class ActionInvocationContext {
    public static ActionInvocationContext onObject(final Object domainObject) {
        return new ActionInvocationContext(InvokedOn.OBJECT, Collections.
singletonList(domainObject));
    }
    public static ActionInvocationContext onCollection(final Object... domainObjects)
{
        return onCollection(Arrays.asList(domainObjects));
    }
    public static ActionInvocationContext onCollection(final List<Object>
domainObjects) {
        return new ActionInvocationContext(InvokedOn.COLLECTION, domainObjects);
    }
    ...
}

```

5.3. BackgroundService2

The `BackgroundService2` domain service, and also the companion `BackgroundCommandService2` SPI service, enable commands to be persisted such that they may be invoked in the background. (The `BackgroundService2` and `BackgroundCommandService2` extensions to these services introduced in [1.13.0-SNAPSHOT](#)).

The `BackgroundService2` is responsible for capturing a memento representing the command in a typesafe way, and persisting it rather than executing it directly.

The default `BackgroundServiceDefault` implementation works by using a proxy wrapper around the target so that it can capture the action to invoke and its arguments. (As of [1.13.0-SNAPSHOT](#)), this is done using `CommandDtoServiceInternal` (in previous releases it used (a private copy of) `MementoService`).

The persistence delegates the persistence of the memento to an appropriate implementation of the companion `BackgroundCommandService2`. One such implementation of `BackgroundCommandService` is provided by (non-ASF) [Isis addons' command](#) module.

The persisting of commands is only half the story; there needs to be a separate process to read the commands and execute them. The `BackgroundCommandExecution` abstract class (discussed [below](#)) provides infrastructure to do this; the concrete implementation of this class depends on the configured `BackgroundCommandService` (in order to query for the persisted (background) `Commands`).

5.3.1. API & Implementation

The API is:

```

public interface BackgroundService2 {
    <T> T execute(final T object);                                ①
    <T> T executeMixin(Class<T> mixinClass, Object mixedIn);   ②
}

```

- ① returns a proxy around the domain object; any methods executed against this proxy will result in a command (to invoke the corresponding action) being persisted by `BackgroundCommandService2`
- ② (1.13.0-SNAPSHOT) returns a proxy around the mixin; any methods executed against this proxy will result in a command (to invoke the corresponding mixin action) being persisted by `BackgroundCommandService2`.

The default implementation is provided by core (`o.a.i.core.runtime.services.background.BackgroundServiceDefault`).

5.3.2. Usage

Using the service is very straight-forward; wrap the target domain object using `BackgroundService#execute(...)` and invoke the method on the object returned by that method.

For example:

```

public void submitCustomerInvoices() {
    for(Customer customer: customerRepository.findCustomersToInvoice()) {
        backgroundService.execute(customer).submitInvoice();
    }
    messageService.informUser("Calculating...");
}

```

This will create a bunch of background commands executing the `submitInvoice()` action for each of the customers returned from the customer repository.

The action method invoked must be part of the Apache Isis metamodel, which is to say it must be public, accept only scalar arguments, and must not be annotated with `@Programmatic` or `@Ignore`. However, it may be annotated with `@Action#hidden()` or `@ActionLayout#hidden()` and it will still be invoked.

In fact, when invoked by the background service, no business rules (hidden, disabled, validation) are enforced; the action method must take responsibility for performing appropriate validation and error checking.



If you want to check business rules, you can use `@WrapperFactory#wrapNoExecute(...)`.

5.3.3. End-user experience

For the end-user, executing an action that delegates work off to the `BackgroundService` raises the

problem of how does the user know the work is complete?

One option is for the background jobs to take responsibility to notify the user themselves. In the above example, this would be the `submitInvoice()` method called upon each customer. One could imagine more complex designs where only the final command executed notifies the user.

However, an alternative is to rely on the fact that the `BackgroundService` will automatically hint that the `Command` representing the original interaction (to `submitCustomerInvoices()` in the example above) should be persisted. This will be available if the related `CommandContext` and `CommandService` domain services are configured, and the `CommandService` supports persistent commands. Note that (non-ASF) `Isis addons' command` module does indeed provide such an implementation of `CommandService` (as well as of the required `BackgroundCommandService`).

Thus, the original action can run a query to obtain its corresponding `Command`, and return this to the user. The upshot is that the child `Commands` created by the `BackgroundService` will then be associated with `Command` for the original action.

We could if we wanted write the above example as follows:

```
public Command submitCustomerInvoices() {
    for(Customer customer: customerRepository.findCustomersToInvoice()) {
        backgroundService.execute(customer).submitInvoice();
    }
    return commandContext.getCommand();
}
@Inject
CommandContext commandContext;  ①
```

① the injected `CommandContext` domain service.

The user would be returned a domain object representing their action invocation.

5.3.4. Registering the Services

Assuming that the `configuration-and-annotation` services installer is configured (implicit if using the `AppManifest` to bootstrap the app) then Apache Isis' core implementation of `BackgroundService` is automatically registered (it is annotated with `@DomainService`) so no further configuration is required.

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide).

5.3.5. Related Services

This service is closely related to the `CommandContext` and also that service's supporting `CommandService` service.

The `CommandContext` service is responsible for providing a parent `Command` with which the background `Commands` can then be associated as children, while the `CommandService` is responsible for persisting those parent `Command`'s. The latter is analogous to the way in which the

'BackgroundCommandService' persists the child background `Command`'s.

The implementations of `CommandService` and `BackgroundCommandService` go together; typically both parent `Command`'s and child background `Command`'s will be persisted in the same way. The (non-ASF) `Isis addons`' `command` module provides implementations of both (see '`CommandService` and `BackgroundCommandService`).

The `CommandDtoServiceInternal` (1.13.0-SNAPSHOT) is used to obtain a memento of the command such that it can be persisted. (In earlier versions, `MementoService` was used for this purpose).

5.3.6. `BackgroundCommandExecution` abstract class

The `BackgroundCommandExecution` (in `isis-core`) is an abstract template class provided by `isis-core` that defines an abstract hook method to obtain background `Command`'s to be executed:

```
public abstract class BackgroundCommandExecution
    extends AbstractIsisSessionTemplate {
    ...
    protected abstract List<? extends Command> findBackgroundCommandsToExecute();
    ...
}
```

The developer is required to implement this hook method in a subclass.

5.3.7. Quartz Scheduler Configuration

The last part of the puzzle is to actually run the (appropriate implementation of) `BackgroundCommandExecution`. This could be run in a batch job overnight, or run continually by, say, the `Quartz` scheduler or by <http://camel.apache.org>[Apache Camel]. This section looks at configuring Quartz.

If using (non-ASF) `Isis addons`' `command` module, then note that this already provides a suitable concrete implementation, namely `org.isisaddons.module.command.dom.BackgroundCommandExecutionFromBackgroundCommandServiceJdo`. We therefore just need to schedule this to run as a Quartz job.

First, we need to define a Quartz job, for example:

```
import
org.isisaddons.module.command.dom.BackgroundCommandExecutionFromBackgroundCommandServiceJdo;
public class BackgroundCommandExecutionQuartzJob extends AbstractIsisQuartzJob {
    public BackgroundCommandExecutionQuartzJob() {
        super(new BackgroundCommandExecutionFromBackgroundCommandServiceJdo());
    }
}
```

where `AbstractIsisQuartzJob` is in turn the following boilerplate:

```

package domainapp.webapp.quartz;
import org.quartz.Job;
import org.quartz.JobExecutionContext;
import org.quartz.JobExecutionException;
...
public class AbstractIsisQuartzJob implements Job {
    public static enum ConcurrentInstancesPolicy {
        SINGLE_INSTANCE_ONLY,
        MULTIPLE_INSTANCES
    }

    private final AbstractIsisSessionTemplate isisRunnable;
    private final ConcurrentInstancesPolicy concurrentInstancesPolicy;
    private boolean executing;

    public AbstractIsisQuartzJob(AbstractIsisSessionTemplate isisRunnable) {
        this(isisRunnable, ConcurrentInstancesPolicy.SINGLE_INSTANCE_ONLY);
    }
    public AbstractIsisQuartzJob(
        AbstractIsisSessionTemplate isisRunnable,
        ConcurrentInstancesPolicy concurrentInstancesPolicy) {
        this.isisRunnable = isisRunnable;
        this.concurrentInstancesPolicy = concurrentInstancesPolicy;
    }

    public void execute(final JobExecutionContext context)
        throws JobExecutionException {
        final AuthenticationSession authSession = newAuthSession(context);
        try {
            if(concurrentInstancesPolicy == ConcurrentInstancesPolicy
.SINGLE_INSTANCE_ONLY &&
                executing) {
                return;
            }
            executing = true;

            isisRunnable.execute(authSession, context);
        } finally {
            executing = false;
        }
    }

    AuthenticationSession newAuthSession(JobExecutionContext context) {
        String user = getKey(context, SchedulerConstants.USER_KEY);
        String rolesStr = getKey(context, SchedulerConstants.ROLES_KEY);
        String[] roles = Iterables.toArray(
            Splitter.on(",").split(rolesStr), String.class);
        return new SimpleSession(user, roles);
    }
}

```

```

String getKey(JobExecutionContext context, String key) {
    return context.getMergedJobDataMap().getString(key);
}
}

```

This job can then be configured to run using Quartz' `quartz-config.xml` file:

```

<?xml version="1.0" encoding="UTF-8"?>
<job-scheduling-data
    xmlns="http://www.quartz-scheduler.org/xml/JobSchedulingData"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation="http://www.quartz-scheduler.org/xml/JobSchedulingData
    http://www.quartz-scheduler.org/xml/job_scheduling_data_1_8.xsd"
    version="1.8">
    <schedule>
        <job>
            <name>BackgroundCommandExecutionJob</name>
            <group>Isis</group>
            <description>
                Poll and execute any background actions persisted by the
                BackgroundActionServiceJdo domain service
            </description>
            <job-class>domainapp.webapp.quartz.BackgroundCommandExecutionQuartzJob</job-
            class>
            <job-data-map>
                <entry>
                    <key>webapp.scheduler.user</key>
                    <value>scheduler_user</value>
                </entry>
                <entry>
                    <key>webapp.scheduler.roles</key>
                    <value>admin_role</value>
                </entry>
            </job-data-map>
        </job>
        <trigger>
            <cron>
                <name>BackgroundCommandExecutionJobEveryTenSeconds</name>
                <job-name>BackgroundCommandExecutionJob</job-name>
                <job-group>Isis</job-group>
                <cron-expression>0/10 * * * * ?</cron-expression>
            </cron>
        </trigger>
    </schedule>
</job-scheduling-data>

```

The remaining two pieces of configuration are the `quartz.properties` file:

```

org.quartz.scheduler.instanceName = SchedulerQuartzConfigXml
org.quartz.threadPool.threadCount = 1
org.quartz.jobStore.class = org.quartz.simpl.RAMJobStore
org.quartz.plugin.jobInitializer.class
=org.quartz.plugins.xml.XMLSchedulingDataProcessorPlugin
org.quartz.plugin.jobInitializer.fileNames = webapp/scheduler/quartz-config.xml
org.quartz.plugin.jobInitializer.failOnFileNotFound = true

```

and the entry in `web.xml` for the Quartz servlet:

```

<servlet>
    <servlet-name>QuartzInitializer</servlet-name>
    <servlet-class>org.quartz.ee.servlet.QuartzInitializerServlet</servlet-class>
    <init-param>
        <param-name>config-file</param-name>
        <param-value>webapp/scheduler/quartz.properties</param-value>
    </init-param>
    <init-param>
        <param-name>shutdown-on-unload</param-name>
        <param-value>true</param-value>
    </init-param>
    <init-param>
        <param-name>start-scheduler-on-load</param-name>
        <param-value>true</param-value>
    </init-param>
    <load-on-startup>1</load-on-startup>
</servlet>

```

5.4. CommandContext

The `CommandContext` service is a `request-scoped` service that reifies the invocation of an action on a domain object into an object itself. This reified information is encapsulated within the `Command` object.

By default, the `Command` is held in-memory only; once the action invocation has completed, the `Command` object is gone. The optional supporting `CommandService` enables the implementation of `Command` to be pluggable. With an appropriate implementation (eg as provided by the (non-ASF) `Isis addons' command` module's `CommandService`) the `Command` may then be persisted.

Persistent `Commands` support several use cases:

- they enable profiling of the running application (which actions are invoked then most often, what is their response time)
- they act as a parent to any background commands that might be invoked through the `BackgroundService`
- if `AuditingService` is configured, they provide better audit information, since the `Command` (the 'cause' of an action) can be correlated to the audit records (the "effect" of the action) through the

unique `transactionId` GUID

- if `PublishingService` is configured, they provide better traceability as the `Command` is also correlated with any published events, again through the unique `transactionId` GUID

Assuming that the `CommandService` supports persistent `Command`'s, the associated `@Action#command()` annotation also allows action invocations to be performed in the background. In this case the act of invoking the action on an object instead returns the 'Command' to the user.

5.4.1. Screencast

The `screencast` provides a run-through of the command (profiling) service, auditing service, publishing service. It also shows how commands can be run in the background either explicitly by scheduling through the background service or implicitly by way of a framework annotation.



Note that this screencast shows an earlier version of the [Wicket viewer](#) UI (specifically, pre 1.8.0).

5.4.2. API & Implementation

The `CommandContext` request-scoped service defines the following very simple API:

```
@RequestScoped  
public class CommandContext {  
    @Programmatic  
    public Command getCommand() { ... }  
}
```

This class (`o.a.i.applib.services.CommandContext`) is also the default implementation. Under normal circumstances there shouldn't be any need to replace this implementation with another.

The `Command` type referenced above is in fact an interface, defined as:

```

public interface Command extends HasTransactionId {

    public abstract String getUser();                      ①
    public abstract Timestamp getTimestamp();             ②

    public abstract Bookmark getTarget();                 ③
    public abstract String getMemberIdentifier();         ④
    public abstract String getTargetClass();              ⑤
    public abstract String getTargetAction();             ⑥
    public String getArguments();                         ⑦
    public String getMemento();                          ⑧

    public ExecuteIn getExecuteIn();                     ⑨
    public Executor getExecutor();                       ⑩
    public Persistence getPersistence();                ⑪
    public boolean isPersistHint();                     ⑫

    public abstract Timestamp getStartedAt();           ⑬
    public abstract Timestamp getCompletedAt();          ⑭
    public Command getParent();                         ⑮

    public Bookmark getResult();                        ⑯
    public String getException();                      ⑰

    @Deprecated
    int next(final String sequenceAbbr);            ⑲
}

```

- ① `getUser()` - is the user that initiated the action.
- ② `getTimestamp()` - the date/time at which this action was created.
- ③ `getTarget()` - bookmark of the target object (entity or service) on which this action was performed
- ④ `getMemberIdentifier()` - holds a string representation of the invoked action
- ⑤ `getTargetClass()` - a human-friendly description of the class of the target object
- ⑥ `getTargetAction()` - a human-friendly name of the action invoked on the target object
- ⑦ `getArguments()` - a human-friendly description of the arguments with which the action was invoked
- ⑧ `getMemento()` - a formal (XML or similar) specification of the action to invoke/being invoked
- ⑨ `getExecuteIn()` - whether this command is executed in the foreground or background
- ⑩ `getExecutor()` - the (current) executor of this command, either user, or background service, or other (eg redirect after post).
- ⑪ `getPersistence()` - the policy controlling whether this command should ultimately be persisted (either "persisted", "if hinted", or "not persisted")
- ⑫ `isPersistHint()` - whether that the command should be persisted, if persistence policy is "if

hinted".

- ⑬ `getStartedAt()` - the date/time at which this action started (same as `timestamp` property for foreground commands)
- ⑭ `getCompletedAt()` - the date/time at which this action completed.
- ⑮ `getParent()` - for actions created through the `BackgroundService`, captures the parent action
- ⑯ `getResult()` - bookmark to object returned by action, if any
- ⑰ `getException()` - exception stack trace if action threw exception
- ⑱ (as of [1.13.0-SNAPSHOT](#)) no longer used by the framework; see instead `InteractionContext` and `Interaction#next()`.

5.4.3. Usage

The typical way to indicate that an action should be treated as a command is to annotate it with the `@Action#command()` annotation.

For example:

```
public class ToDoItem ... {  
    @Action(command=CommandReification.ENABLED)  
    public ToDoItem completed() { ... }  
}
```



As an alternative to annotating every action with `@Action#command()`, alternatively this can be configured as the default using `isis.services.command.actions` configuration property.

See `@Action#command()` and [runtime configuration](#) for further details.

The `@Action#command()` annotation can also be used to specify whether the command should be performed in the background, for example:

```
public class ToDoItem ... {  
    @Command(executeIn=ExecuteIn.BACKGROUND)  
    public ToDoItem scheduleImplicitly() {  
        completeSlowly(3000);  
        return this;  
    }  
}
```

When a background command is invoked, the user is returned the command object itself (to provide a handle to the command being invoked).

This requires that an implementation of `CommandService` that persists the commands (such as the (non-ASF) `Isis addons' command` module's `CommandService`) is configured. It also requires that a scheduler is configured to execute the background commands, see `BackgroundCommandService`).

5.4.4. Interacting with the services

Typically the domain objects have little need to interact with the `CommandContext` and `Command` directly; what is more useful is that these are persisted in support of the various use cases identified above.

One case however where a domain object might want to obtain the `Command` is to determine whether it has been invoked in the foreground, or in the background. It can do this using the `getExecutedIn()` method:

Although not often needed, this then allows the domain object to access the `Command` object through the `CommandContext` service. To expand th above example:

```
public class ToDoItem ... {
    @Action(
        command=CommandReification.ENABLED,
        commandExecuteIn=CommandExecuteIn.BACKGROUND
    )
    public ToDoItem completed() {
        ...
        Command currentCommand = commandContext.getCommand();
        ...
    }
    @Inject
    CommandContext commandContext;
}
```

If run in the background, it might then notify the user (eg by email) if all work is done.

This leads us onto a related point, distinguishing the current effective user vs the originating "real" user. When running in the foreground, the current user can be obtained from the `DomainObjectContainer`, using:

```
String user = container.getUser().getName();
```

If running in the background, however, then the current user will be the credentials of the background process, for example as run by a Quartz scheduler job.

The domain object can still obtain the original ("effective") user that caused the job to be created, using:

```
String user = commandContext.getCommand().getUser();
```

5.4.5. Registering the Services

Assuming that the `configuration-and-annotation` services installer is configured (implicit if using the `AppManifest` to bootstrap the app) then Apache Isis' core implementation of `CommandContext`

service is automatically registered and injected (it is annotated with `@DomainService`) so no further configuration is required.

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide).

5.4.6. Related Services

As discussed above, the supporting `CommandService` enables `Command` objects to be persisted. Other related services are the `BackgroundService` and `BackgroundCommandService`). For `BackgroundService` captures commands for execution in the background, while the `[BackgroundCommandService]` persists such commands for execution.

The implementations of `CommandService` and `BackgroundCommandService` are intended to go together, so that persistent parent ``Command``'s can be associated with their child background ``Command``'s.

5.5. InteractionContext (1.13.0-SNAPSHOT)



TODO

5.6. MessageService

The `MessageService` allows domain objects to raise information, warning or error messages. These messages can either be simple strings, or can be translated.



The methods in this service replace similar methods (now deprecated) in `DomainObjectContainer`.

5.6.1. API and Usage

The API of `MessageService` is:

```

public interface MessageService {

    void informUser(String message);
①     String informUser(TranslatableString message, Class<?> contextClass, String
contextMethod); ②

    void warnUser(String message);
③     String warnUser(TranslatableString message, Class<?> contextClass, String
contextMethod); ④

    void raiseError(String message);
⑤     String raiseError(TranslatableString message, Class<?> contextClass, String
contextMethod); ⑥

    ...
}

```

- ① display as a transient message to the user (not requiring acknowledgement). In the [Wicket viewer](#) this is implemented as a toast that automatically disappears after a period of time.
- ② ditto, but with translatable string, for [i18n support](#).
- ③ warn the user about a situation with the specified message. In the [Wicket viewer](#) this is implemented as a toast that must be closed by the end-user.
- ④ ditto, but with translatable string, for i18n support.
- ⑤ show the user an unexpected application error. In the [Wicket viewer](#) this is implemented as a toast (with a different colour) that must be closed by the end-user.
- ⑥ ditto, but with translatable string, for i18n support.

For example:

```

public Order addItem(Product product, @ParameterLayout(named="Quantity") int quantity)
{
    if(productRepository.stockLevel(product) == 0) {
        messageService.warnUser(
            product.getDescription() + " out of stock; order fulfillment may be
delayed");
    }
    ...
}

```

5.6.2. Implementation

The core framework provides a default implementation of this service ([o.a.i.core.runtime.services.message.MessageServiceDefault](#)).

5.6.3. Registering the Service

Assuming that the `configuration-and-annotation` services installer is configured (implicit if using the `AppManifest` to bootstrap the app) then Apache Isis' core implementation of `MessageService` service is automatically registered and injected (it is annotated with `@DomainService`) so no further configuration is required.

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide).

5.7. SessionManagementService

The `SessionManagementService` provides the ability to programmatically manage sessions. The primary use case is for fixture scripts or other routines that are invoked from the UI and which create or modify large amounts of data. A classic example is migrating data from one system to another.

5.7.1. API

The API of `SessionManagementService` is:

```
public interface SessionManagementService {  
    void nextSession();  
}
```

Normally, the framework will automatically start a session and then a transaction before each user interaction (action invocation or property modification), and will then commit that transaction and close the session after the interaction has completed. If the interaction throws an exception then the transaction is aborted.

The `nextSession()` method allows a domain object to commit the transaction, close the session, then open a new session and start a new transaction.



Any domain objects that were created in the "previous" session are no longer usable, and must not be rendered in the UI.

5.7.2. Implementation

The core framework provides a default implementation of this service (`o.a.i.core.runtime.services.xactn.SessionManagementServiceDefault`).

5.7.3. Registering the Service

Assuming that the `configuration-and-annotation` services installer is configured (implicit if using the `AppManifest` to bootstrap the app) then Apache Isis' core implementation of `SessionManagementService` service is automatically registered and injected (it is annotated with `@DomainService`) so no further configuration is required.

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide).

5.8. TitleService

The `TitleService` provides methods to programmatically obtain the title and icon of a domain object.



The methods in this service replace similar methods (now deprecated) in `DomainObjectContainer`.

5.8.1. API

The API of `TitleService` is:

```
public interface PresentationService {  
    String titleOf(Object domainObject);  
    String iconNameOf(Object domainObject);  
}
```

- ① return the title of the object, as rendered in the UI by the Apache Isis viewers.
- ② return the icon name of the object, as rendered in the UI by the Apache Isis viewers.

5.8.2. Usage

By way of example, here's some code based on a system for managing government benefits:

```
public class QualifiedAdult {  
  
    private Customer qualifying;  
  
    public String title() {  
        return "QA for " + titleService.titleOf(qualifying);  
    }  
  
    ...  
    @Inject  
    TitleService titleService;  
}
```

In this example, whatever the title of a `Customer`, it is reused within the title of that customer's `QualifiedAdult` object.

5.8.3. Implementation

The core framework provides a default implementation of this service (`o.a.i.core.metamodel.services.title.TitleServiceDefault`).

5.8.4. Registering the Service

Assuming that the [configuration-and-annotation](#) services installer is configured (implicit if using the [AppManifest](#) to [bootstrap the app](#)) then Apache Isis' core implementation of [TitleService](#) service is automatically registered and injected (it is annotated with [@DomainService](#)) so no further configuration is required.

To use an alternative implementation, use [@DomainServiceLayout#menuOrder\(\)](#) (as explained in the [introduction](#) to this guide).

5.9. TransactionService

The [TransactionService](#) provides a small number of methods to allow domain objects to influence user transactions.



The methods in this service replace similar methods (now deprecated) in [DomainObjectContainer](#).

5.9.1. API

The API of [TransactionService](#) is:

```
public interface TransactionService {  
    void flushTransaction();  
    void nextTransaction();  
}
```

Normally, the framework will automatically start a transaction before each user interaction (action invocation or property modification), and commit that transaction after the interaction has completed. If the interaction throws an exception then the transaction is aborted.

If the user interaction creates and persists an object (using [DomainObjectContainer](#)'s [persist\(\)](#) method), then the framework actually defers the call and only performs the persistence command at the end of the transaction, or immediately prior to the next query.

```
/**  
 *  
 *  
 * <p>  
 * Occasionally useful to ensure that newly persisted domain objects  
 * are flushed to the database prior to a subsequent repository query.  
 */
```

/** * Intended only for use by fixture scripts and integration tests; commits this transaction and starts a new one. */

5.9.2. Implementation

The core framework provides a default implementation of this service (`o.a.i.core.metamodel.services.xactn.TransactionServiceDefault`).

5.9.3. Registering the Service

Assuming that the `configuration-and-annotation` services installer is configured (implicit if using the `AppManifest` to [bootstrap the app](#)) then Apache Isis' core implementation of `TransactionService` service is automatically registered and injected (it is annotated with `@DomainService`) so no further configuration is required.

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide).

5.10. WrapperFactory

The `WrapperFactory` provides the ability to enforce business rules for programmatic interactions between domain objects. If there is a (lack-of-) trust boundary between the caller and callee—eg if they reside in different modules—then the wrapper factory is a useful mechanism to ensure that any business constraints defined by the callee are honoured.

For example, if the calling object attempts to modify an unmodifiable property on the target object, then an exception will be thrown. Said another way: interactions are performed "as if" they are through the viewer.



For a discussion of the use of the `WrapperFactory` within integration tests (the primary or at least original use case for this service) can be found [here](#)

This capability goes beyond enforcing the (imperative) constraints within the `hideXxx()`, `disableXxx()` and `validateXxx()` supporting methods; it also enforces (declarative) constraints such as those represented by annotations, eg `@MaxLength` or `@Regex`.

This capability is frequently used within [integration tests](#), but can also be used in production code. (There are analogies that can be drawn here with the way that JEE beans can interact through an EJB local interface).

5.10.1. API

The API provided by the service is:

```

public interface WrapperFactory {
    @Programmatic
    <T> T wrap(T domainObject);                                ①
    @Programmatic
    <T> T unwrap(T possibleWrappedDomainObject);               ②
    @Programmatic
    <T> boolean isWrapper(T possibleWrappedDomainObject);     ③

    public static enum ExecutionMode {                           ④
        EXECUTE(true,true),
        SKIP_RULES(false, true),                                ⑤
        NO_EXECUTE(true, false);                               ⑥
    }
    @Programmatic
    <T> T wrap(T domainObject, ExecutionMode mode);          ⑦
    @Programmatic
    <T> T wrapNoExecute(T domainObject);                      ⑧
    @Programmatic
    <T> T wrapSkipRules(T domainObject);                     ⑨
    ...
}

```

- ① wraps the underlying domain object. If it is already wrapped, returns the object back unchanged.
- ② Obtains the underlying domain object, if wrapped. If the object is not wrapped, returns back unchanged.
- ③ whether the supplied object has been wrapped.
- ④ enumerates how the wrapper interacts with the underlying domain object.
- ⑤ validate all business rules and then execute.
- ⑥ skip all business rules and then execute (including creating [commands](#) and firing pre- and post-execute [domain events](#)).
- ⑦ validate all business rules (including those from [domain events](#)) but do not execute.
- ⑧ convenience method to invoke `wrap(...)` with `ExecuteMode#NO_EXECUTE` (make this feature more discoverable)
- ⑨ convenience method to invoke `wrap(...)` with `ExecuteMode#SKIP_RULES` (make this feature more discoverable)

The service works by returning a "wrapper" around a supplied domain object (a [javassist proxy](#)), and it is this wrapper that ensures that the hide/disable/validate rules implied by the Apache Isis programming model are enforced. The wrapper can be interacted with as follows:

- a `get…()` method for properties or collections
- a `set…()` method for properties
- an `addTo…()` or `removeFrom…()` method for collections

any action

Calling any of the above methods may result in a (subclass of) `InteractionException` if the object disallows it. For example, if a property is annotated with `@Hidden` then a `HiddenException` will be thrown. Similarly if an action has a `validateXxx()` method and the supplied arguments are invalid then an `InvalidException` will be thrown.

In addition, the following methods may also be called:

- the `title()` and `toString()` methods
- any `default…()`, `choices…()` or `autoComplete…()` methods

An exception will be thrown if any other methods are thrown.

5.10.2. Usage

The caller will typically obtain the target object (eg from some repository) and then use the injected `WrapperFactory` to wrap it before interacting with it.

For example:

```
public class CustomerAgent {  
    @Action  
    public void refundOrder(final Order order) {  
        final Order wrappedOrder = wrapperFactory.wrap(order);  
        try {  
            wrappedOrder.refund();  
        } catch(InteractionException ex) {          ①  
            container.raiseError(ex.getMessage());  ②  
            return;  
        }  
    }  
    ...  
    @Inject  
    WrapperFactory wrapperFactory;  
    @Inject  
    DomainObjectContainer container;  
}
```

① if any constraints on the `Order's 'refund() action would be violated, then ...`

② ... these will be trapped and raised to the user as a warning.

It ought to be possible to implement an `ExceptionRecognizers` that would allow the above boilerplate to be removed. This recognizer service would recognize the `InteractionException` and convert to a suitable message.



At the time of writing Apache Isis does not provide an out-of-the-box implementation of such an `ExceptionRecognizer`; but it should be simple enough to write one...

5.10.3. Listener API

The `WrapperFactory` also provides a listener API to allow other services to listen in on interactions.

```
public interface WrapperFactory {  
    ...  
    @Programmatic  
    List<InteractionListener> getListeners(); ①  
    @Programmatic  
    public boolean addInteractionListener(InteractionListener listener); ②  
    @Programmatic  
    public boolean removeInteractionListener(InteractionListener listener); ③  
    @Programmatic  
    public void notifyListeners(InteractionEvent ev); ④  
}
```

- ① all `InteractionListener`s that have been registered.
- ② registers an `InteractionListener`, to be notified of interactions on all wrappers. The listener will be notified of interactions even on wrappers created before the listener was installed. (From an implementation perspective this is because the wrappers delegate back to the container to fire the events).
- ③ remove an `InteractionListener`, to no longer be notified of interactions on wrappers.
- ④ used by the framework itself

The original intent of this API was to enable test transcripts to be captured (in a BDD-like fashion) from integration tests. No such feature has yet been implemented however. Also, the capabilities have by and large been superceded by Apache Isis' support for domain events. We may therefore deprecate this API in the future.

5.10.4. Registering the Service

Assuming that the `configuration-and-annotation` services installer is configured (implicit if using the `AppManifest` to bootstrap the app) then Apache Isis' core implementation of `WrapperFactory` service is automatically registered and injected (it is annotated with `@DomainService`) so no further configuration is required.

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide).

Chapter 6. Application Layer SPI

Domain service SPIs influence how the framework handles application layer concerns, for example which home page to render to the end-user.

The table below summarizes the application layer SPIs defined by Apache Isis. It also lists their corresponding implementation, either a default implementation provided by Apache Isis itself, or provided by one of the in (non-ASF) [Isis Addons](#) modules.

Table 4. Application Layer SPI

API	Description	Implementation	Notes
<code>o.a.i.applib.services.background.BackgroundCommandService</code>	Persisted a memento of an action invocation such that it can be executed asynchronously ("in the background") eg by a scheduler.	<code>BackgroundCommandServiceJdo</code> <code>o.ia.m.command.isis-module-command</code>	related services: <code>BackgroundCommandServiceJdoContributions</code> , <code>BackgroundCommandServiceJdoRepository</code>
<code>o.a.i.applib.services.command.spi.CommandService</code>	Service to act as a factory and repository (create and save) of command instances, ie representations of an action invocation. Used for command/auditing and background services.	<code>CommandServiceJdo</code> <code>o.ia.m.command.isis-module-command</code>	related services: <code>CommandService`JdoContributions`</code> , <code>CommandService`JdoRepository`</code>
<code>o.a.i.applib.services.homepage.HomePageProviderService</code>	Returns the home page object, if any is defined.	<code>HomePageProviderServiceDefault</code> <code>o.a.i.core.isis-core-runtime</code>	Used by the default implementation of <code>RoutingService</code> .

Key:

- `o.a.i` is an abbreviation for `org.apache.isis`
- `o.ia.m` is an abbreviation for `org.isisaddons.module`

6.1. BackgroundCommandService

The `BackgroundCommandService` (SPI) service supports the `BackgroundService` (API) service, persisting action invocations as commands such that they can subsequently be invoked in the background.

The `BackgroundService` is responsible for capturing a memento representing the action invocation, and then hands off to the `BackgroundCommandService` `BackgroundCommandService` to actually persist it.

The persisting of commands is only half the story; there needs to be a separate process to read the commands and execute them. The abstract `BackgroundCommandExecution` provides a mechanism to execute such commands. This can be considered an API, albeit "internal" because the implementation relies on internals of the framework.

6.1.1. SPI

The SPI of the `BackgroundCommandService` is:

```
public interface BackgroundCommandService {
    void schedule(
        ActionInvocationMemento aim,           ①
        Command parentCommand,                 ②
        String targetClassName,
        String targetActionName,
        String targetArgs);
}
```

- ① is a wrapper around a `MementoService`'s `Memento`, capturing the details of the action invocation to be retained (eg persisted to a database) so that it can be executed at a later time
- ② reference to the parent `Command` requesting the action be performed as a background command. This allows information such as the initiating user to be obtained.

The API of `ActionInvocationMemento` in turn is:

```
public class ActionInvocationMemento {
    public String getActionId() { ... }
    public String getTargetClassName() { ... }
    public String getTargetActionName() { ... }
    public Bookmark getTarget() { ... }
    public int getNumArgs() { ... }
    public Class<?> getArgType(int num) throws ClassNotFoundException { ... }
    public <T> T getArg(int num, Class<T> type) { ... }

    public String asMementoString() { ... }      ①
}
```

- ① lets the `BackgroundCommandService` implementation convert the action invocation into a simple string.

6.1.2. "Internal" SPI

The `BackgroundCommandExecution` (in `isis-core`) is an abstract template class for `headless access`, that defines an abstract hook method to obtain background `Command`'s to be executed:

```
public abstract class BackgroundCommandExecution
    extends AbstractIsisSessionTemplate {
    ...
    protected abstract List<? extends Command> findBackgroundCommandsToExecute();
    ...
}
```

The developer is required to implement this hook method in a subclass.

6.1.3. Implementation

The (non-ASF) `Isis addons' command` module provides an implementation (`org.isisaddons.module.command.dom.BackgroundCommandServiceJdo`) that persists `Commands` using the JDO/DataNucleus object store. It further provides a number of supporting services:

- `org.isisaddons.module.command.dom.BackgroundCommandServiceJdoRepository` is a repository to search for persisted background `Commands`
- `org.isisaddons.module.command.dom.BackgroundCommandServiceJdoContributions` contributes actions for searching for persisted child and sibling `Commands`.

The module also provides a concrete subclass of `BackgroundCommandExecution` that knows how to query for persisted (background) `Command`'s such that they can be executed by a scheduler.



Details of setting up the Quartz scheduler to actually execute these persisted commands can be found on the `BackgroundService` page.

6.1.4. Usage

Background commands can be created either declaratively or imperatively.

The declarative approach involves annotating an action using `@Action#command()` with `@Action#commandExecuteIn=CommandExecuteIn.BACKGROUND`.

The imperative approach involves explicitly calling the `BackgroundService` from within domain object's action.

6.1.5. Registering the Services

The (non-ASF) `Isis addons' command` module provides an implementation of this service (`BackgroundCommandService`), and also provides a number of related domain services (`BackgroundCommandServiceJdo`, `BackgroundCommandJdoRepository` and `BackgroundCommandServiceJdoContributions`). This module also provides service implementations of the `CommandService`.

Assuming that an `AppManifest` is being used to bootstrap the app) then this can be activated by updating the `pom.xml` and updating the `AppManifest#getModules()` method.

If contributions are not required in the UI, these can be suppressed either using security or by implementing a `vetoing subscriber`.

6.1.6. Related Services

As discussed above, this service supports the `BackgroundService`, persisting `Command`'s such that they can be executed in the background.

There is also a tie-up with the `CommandContext` and its supporting `CommandService` domain service. The `CommandContext` service is responsible for providing a parent `Command` with which the background `Command`'s can then be associated as children, while the `CommandService` is responsible for persisting those parent `Command`'s (analogous to the way in which the `BackgroundCommandService` persists the child background `Command`'s). The `BackgroundCommandService` ensures that these background `Command`'s are associated with the parent "foreground" `Command`.

What that means is that the implementations of `CommandService` and `BackgroundCommandService` go together, hence both implemented in the (non-ASF) `Isis addons' command module`).

6.2. CommandService

The `CommandService` service supports the `CommandContext` service such that `Command` objects (that reify the invocation of an action/edit of a property on a domain object) can be persisted.

Persistent `Commands` support several use cases:

- they enable profiling of the running application (which actions are invoked then most often, what is their response time) ++

However, note that (as of 1.13.0-SNAPSHOT) much more powerful profiling capabilities are provided by `InteractionContext`; these can be logged using the `PublisherService`.

- they act as a parent to any background commands that might be invoked through the `BackgroundService`
- if `auditing` is configured, they provide better audit information, since the `Command` (the 'cause' of an action) can be correlated to the audit records (the "effect" of the action) by way of the `transactionId`
- if `publishing` is configured, they provide better traceability as the `Command` is also correlated with any published events, again through the unique `transactionId`
- the associated `@Action#command()` annotation attribute also allows action invocations to be performed in the background. In this case the act of invoking the action on an object instead returns the `Command` to the user.

6.2.1. Screencast

The `screencast` below provides a run-through of the command (profiling) service, auditing service, publishing service. It also shows how commands can be run in the background either explicitly by

scheduling through the background service or implicitly by way of a framework annotation.



Note that this screencast shows an earlier version of the [Wicket viewer](#) UI (specifically, pre 1.8.0).

6.2.2. SPI

The `CommandService` service defines the following very simple API:

```
public interface CommandService {  
    Command create();  
    @Deprecated  
    void startTransaction(Command command, UUID transactionId);  
    boolean persistIfPossible(Command command);  
    void complete(Command command);  
}
```

- ① Instantiate the appropriate instance of the `Command` (as defined by the `CommandContext` service). Its members will be populated automatically by the framework.
- ② (as of [1.13.0-SNAPSHOT](#)) is deprecated: the framework automatically populates the `Command`'s `timestamp`, `user` and `transactionId` fields, so there is no need for the service implementation to initialize any of these. In particular, the `Command` will already have been initialized with the provided `transactionId` argument.
- ③ Set the hint that the `Command` should be persisted if possible (when completed, see below).
- ④ "Complete" the command, typically meaning that the command should be persisted if its `Command#getPersistence()` flag and persistence hint (`Command#isPersistHint()`) indicate that it should be.

The framework will automatically have set the `completedAt` property of the `Command`.

6.2.3. Implementation

The (non-ASF) `Isis addons' command` module provides an implementation (`org.isisaddons.module.command.dom.CommandServiceJdo`) that persists `Commands` using the JDO/DataNucleus object store. It further provides a number of supporting services:

- `org.isisaddons.module.command.dom.CommandServiceJdoRepository` is a repository to search for persisted `Commands`
- `org.isisaddons.module.command.dom.CommandServiceJdoContributions` contributes actions for searching for persisted child and sibling `Commands`.

6.2.4. Usage

The typical way to indicate that an action should be reified into a `Command` is by annotating the action using `@Action#command()`.

6.2.5. Registering the Services

The (non-ASF) [Isis addons' command](#) module provides an implementation of this service ([CommandService](#)), and also provides a number of related domain services ([CommandJdoRepository](#) and [CommandServiceJdoContributions](#)). This module also provides service implementations of the [BackgroundCommandService](#).

Assuming that an [AppManifest](#) is being used to [bootstrap the app](#)) then this can be activated by updating the [pom.xml](#) and updating the [AppManifest#getModules\(\)](#) method.

If contributions are not required in the UI, these can be suppressed either using security or by implementing a [vetoing subscriber](#).

6.2.6. Related Services

As discussed above, this service supports the [CommandContext](#), providing the ability for [Command](#) objects to be persisted. This is closely related to the [BackgroundCommandService](#) that allows the [BackgroundService](#) to schedule commands for background/asynchronous execution.

The implementations of [CommandService](#) and [BackgroundCommandService](#) are intended to go together, so that persistent parent `Command`s can be associated with their child background `Command`s.

The services provided by this module combines very well with the [`<code>AuditingService</code>`](#). The [`<code>CommandService</code>`](#) captures the [`_cause`](#) of an interaction (an action was invoked, a property was edited), while the [`<code>AuditingService3</code>`](#) captures the [`effect`](#) of that interaction in terms of changed state.

You may also want to configure the [PublishingService](#).

All three of these services collaborate implicitly by way of the [HasTransactionId](#) interface.

6.3. HomePageProviderService

This service simply provides access to the home page object (if any) that is returned from the domain service action annotated with [@HomePage](#).

It is originally introduced to support the default implementation of [RoutingService](#), but was factored out to support alternative implementations of that service (and may be useful for other use cases).

6.3.1. API & Implementation

The API defined by [HomePageProviderService](#) is:

```
@DomainService(nature = NatureOfService.DOMAIN)
public interface HomePageProviderService {
    @Programmatic
    Object homepage();
}
```

The default implementation is provided by `o.a.i.core.runtime.services.homepage.HomePageProviderServiceDefault`.

6.3.2. Registering the Service

Assuming that the `configuration-and-annotation` services installer is configured (implicit if using the `AppManifest` to bootstrap the app) then Apache Isis' core implementation of `HomePageProviderService` is automatically registered (it is annotated with `@DomainService`) so no further configuration is required.

Chapter 7. Application Layer internal SPI

These domain services are internal to the framework, controlling various aspects of the application layer.



We do not guarantee that [semantic versioning](#) will be honoured for these SPIs.

The table below summarizes the application layer internal SPIs defined by Apache Isis. It also lists their corresponding implementation, either a default implementation provided by Apache Isis itself, or provided by one of the (non-ASF) [Isis Addons](#) modules.

Table 5. "Internal" SPI Services

SPI	Maven Module Impl'n (g: a:)	Implementation	Notes
<code>o.a.i.c.m.s</code> <code>m.s.command</code> <code>CommandDtoServiceInternal</code>	(1.13.0-SNAPSHOT) Creates memento of current action invocation, for use either as a reified command or for implementations of the <code>PublishingService</code> .	<code>CommandDtoServiceInternalServiceDefault</code> <code>o.a.i.c.r.s.command</code> <code>isis-core-runtime</code>	

Key:

- `o.a.i.c.m.s` is an abbreviation for `org.apache.isis.core.metamodel.services`
- `o.a.i.c.r.s` is an abbreviation for `org.apache.isis.core.runtime.services`

7.1. CommandDtoServiceInternal (1.13.0-SNAPSHOT)

The `CommandDtoServiceInternal` (1.13.0-SNAPSHOT) is responsible for creating an memento of the current action invocation or property edit, to store in the `Command` object (from `CommandContext`). This memento is a JAXB DTO being an instance of the "`cmd`" schema, so can be reified so that its execution can be deferred until later, as a [background command](#).

7.1.1. SPI & Implementation

The SPI of the service is:

```

public interface CommandMementoService {
    @Deprecated
    ActionInvocationMemento asActionInvocationMemento(①
        Method m,
        Object domainObject, Object[] args);
    CommandDto asCommandDto(②
        List<ObjectAdapter> targetAdapters,
        ObjectAction objectAction,
        ObjectAdapter[] argAdapters);
    CommandDto asCommandDto(③
        final List<ObjectAdapter> targetAdapters,
        final OneToOneAssociation association,
        final ObjectAdapter valueAdapterOrNull);
    void addActionArgs(④
        final ObjectAction objectAction,
        final ActionDto actionDto,
        final ObjectAdapter[] argAdapters);
    void addPropertyValue(⑤
        final OneToOneAssociation property,
        final PropertyDto propertyDto,
        final ObjectAdapter valueAdapter);
}

```

- ① Note that this method (more precisely, `ActionInvocationMemento`) does *not* support mixins.
- ② Returns a JAXB DTO being an instance of the "cmd" schema (hence convertible to XML) that represents the *intention* to invoke an action on a target object (or possibly many targets, for bulk actions). If an action, it can also be either mixin action or a contributed action.
- ③ Returns a JAXB DTO that represents the intention to edit (set or clear) a property on a target (or possibly many targets, for symmetry with actions).
- ④ add the arguments of an action to an `ActionDto`.
- ⑤ add the new value argument of a property to a `PropertyDto`.

The SPI is implemented by `o.a.i.c.r.s.command.CommandDtoServiceInternalServiceDefault`.

7.2. InteractionDtoServiceInternal (1.13.0-SNAPSHOT)



TODO

Chapter 8. Core/Domain API

The core/domain APIs provide general-purpose services to the domain objects, for example obtaining the current time or user, or instantiating domain objects.

The table below summarizes the core/domain APIs defined by Apache Isis. It also lists their corresponding implementation, either a default implementation provided by Apache Isis itself, or provided by one of the in (non-ASF) [Isis Addons](#) modules.

Table 6. Core/Domain Layer API

API	Description	Implementation	Notes
<code>o.a.i.applib.services.clock</code> <code>ClockService</code>	Access the current time (and for testing, allow the time to be changed)	<code>ClockService</code> <code>o.a.i.core</code> <code>isis-core-applib</code>	API is also a concrete class.
<code>o.a.i.applib.services.config</code> <code>ConfigurationService</code>	Access configuration properties (eg from <code>isis.properties</code> file)	<code>ConfigurationService</code> - Default <code>o.a.i.core</code> <code>isis-core-runtime</code>	The <code>ConfigurationService</code> Menu exposes the <code>allConfigurationProperties</code> action in the user interface. + Supercedes methods in <code>DomainObjectContainer</code> .
<code>o.a.i.applib</code> <code>DomainObjectContainer</code>	Miscellaneous functions, eg obtain title of object.	<code>DomainObjectContainer</code> - Default <code>o.a.i.core</code> <code>isis-core-metamodel</code>	
<code>o.a.i.applib.services.eventbus</code> <code>EventBusService</code>	Programmatically post events to the internal event bus. Also used by Apache Isis itself to broadcast domain events: * <code>Action#domainEvent()</code> * <code>Property#domainEvent()</code> * <code>Collection#domainEvent()</code>	<code>EventBusService</code> <code>Jdo</code> <code>o.a.i.core</code> <code>isis-core-runtime</code>	

API	Description	Implementation	Notes
<code>o.a.i.applib.services.factory</code> <code>FactoryService</code>	Methods to instantiate and initialize domain objects	<code>FactoryService-</code> <code>Default</code> <code>o.a.i.core</code> <code>isis-core-</code> <code>metamodel</code>	Supercedes methods in <code>DomainObjectContainer</code> .
<code>o.a.i.applib.services.scratchpad</code> <code>Scratchpad</code>	Request-scoped service for interchanging information between and aggregating over multiple method calls; in particular for use by "bulk" actions (invoking of an action for all elements of a collection)	<code>Scratchpad</code> <code>o.a.i.core</code> <code>isis-core-</code> <code>applib</code>	API is also a concrete class
<code>o.a.i.applib.services.xactn</code> <code>UserService</code>	Methods to access the currently-logged on user.	<code>UserServic</code> <code>e-</code> <code>Default</code> <code>o.a.i.core</code> <code>isis-core-</code> <code>metamodel</code>	Supercedes methods in <code>DomainObjectContainer</code> .

Key:

- `o.a.i` is an abbreviation for `org.apache.isis`
- `o.ia.m` is an abbreviation for `org.isisaddons.module`

There is also a number of deprecated domain services.

Table 7. Deprecated Domain Services

API	Description	Implementation	Notes
<code>o.a.i.applib.annotation</code> <code>Bulk.InteractionContext</code>	Request-scoped access to whether action is invoked on object and/or on collection of objects	<code>Bulk.InteractionContext</code> <code>o.a.i.core</code> <code>isis-core-applib</code>	Replaced by <code>ActionInvocationContext</code>

Key:

- `o.a.i` is an abbreviation for `org.apache.isis`

8.1. ClockService

Most applications deal with dates and times in one way or another. For example, if an `Order` is placed, then the `Customer` may have 30 days to pay the `Invoice`, otherwise a penalty may be levied.

However, such date/time related functionality can quickly complicate automated testing: "today+30" will be a different value every time the test is run.

Even disregarding testing, there may be a requirement to ensure that date/times are obtained from

an NNTP server (rather than the system PC). While instantiating a `java.util.Date` to current the current time is painless enough, we would not want complex technical logic for querying an NNTP server spread around domain logic code.

Therefore it's common to provide a domain service whose responsibility is to provide the current time. This service can be injected into any domain object (and can be mocked out for unit testing). Apache Isis provides such a facade through the `ClockService`.

8.1.1. API & Implementation

The API defined by `ClockService` is:

```
@DomainService(nature = NatureOfService.DOMAIN)
public class ClockService {
    @Programmatic
    public LocalDate now() { ... }
    @Programmatic
    public LocalDateTime nowAsLocalDateTime() { ... }
    @Programmatic
    public DateTime nowAsDateTime() { ... }
    @Programmatic
    public Timestamp nowAsJavaSqlTimestamp() { ... }
    @Programmatic
    public long nowAsMillis() { ... }
}
```

This class (`o.a.i.applib.services.clock.ClockService`) is also the default implementation. The time provided by this default implementation is based on the system clock.

8.1.2. Testing Support

The default `ClockService` implementation in fact simply delegates to another class defined in the API, namely the `o.a.i.applib.clock.Clock`, an abstract singleton class. It is not recommended that your code use the `Clock` directly, but you should understand how this all works:

- there are two subclasses implementations `Clock`, namely `SystemClock` and `FixtureClock`.
- the first implementation that is instantiated registers itself as the singleton.
- if running in `production` (server) mode, then (unless another implementation has beaten it to the punch) the framework will instantiate the `'SystemClock`. Once instantiated this cannot be replaced.
- if running in `rgcfg.pdf#rgcfg_deployment-types">prototype` mode, then the framework will instead instantiate `<code>FixtureClock</code>`. This `_can` be replaced if required.

The `FixtureClock` will behave as the system clock, unless its is explicitly set using `FixtureClock# setDate(...)` or `FixtureClock# setTime(...)` and so forth.

Alternative Implementations

Suppose you want (as discussed in the introduction to this service) to use a clock that delegates to NNTP. For most domain services this would amount to implementing the appropriate service and registering in `isis.properties` so that it is used in preference to any implementations provided by default by the framework.

In the case of the `ClockService`, though, this approach (unfortunately) will not work, because parts of Apache Isis (still) delegate to the `Clock` singleton rather than using the `ClockService` domain service.

The workaround, therefore, is to implement your functionality as a subclass of `Clock`. You can write a domain service that will ensure that your implementation is used ahead of any implementations provided by the framework.

For example:

```
@DomainService(nature=NatureOfService.DOMAIN)
public class NntpClockServiceInitializer {
    @Programmatic
    @PostConstruct
    public void postConstruct(Map<String, String> properties) {
        new NntpClock(properties);                                ①
    }
    private static class NntpClock extends Clock {
        NntpClock(Map<String, String> properties) { ... } ②
        protected long time() { ... }                         ③
        ... NNTP stuff here ...
    }
}
```

① enough to simply instantiate the `Clock`; it will register itself as singleton

② connect to NNTP service using configuration properties from `isis.properties`

③ call to NNTP service here

8.1.3. Registering the Service

Assuming that the `configuration-and-annotation` services installer is configured (implicit if using the `AppManifest` to `bootstrap the app`) then Apache Isis' core implementation of `ClockService` is automatically registered (it is annotated with `@DomainService`) so no further configuration is required.

If you want to use a different implementation of `Clock`, eg delegating to NNTP, then do *not* register directly, but instead subclass from `o.a.i.applib.clock.Clock` singleton (as described in the section above).

8.2. ConfigurationService

The **ConfigurationService** allows domain objects to read the configuration properties aggregated from the various [configuration files](#).



The methods in this service replace similar methods (now deprecated) in [DomainObjectContainer](#).

8.2.1. API and Usage

The API of **ConfigurationService** is:

```
public interface ConfigurationService {  
  
    String getProperty(String name); ①  
    String getProperty(String name, String defaultValue); ②  
    List<String> getPropertyNames(); ③  
    Set<ConfigurationProperty> allProperties(); ④  
  
}
```

- ① Return the configuration property with the specified name; else return null.
- ② Return the configuration property with the specified name; if it doesn't exist then return the specified default value.
- ③ Return the names of all the available properties.
- ④ Returns all properties, each as an instance of the [ConfigurationProperty](#) view model.

For example, here's a fictitious service that might wrap [Twitter4J](#). say:

```

@DomainService(nature=NatureOfService.DOMAIN)
public class TweetService {
    @Programmatic
    @PostConstruct
    public void init() {
        this.oauthConsumerKey = configurationService.getProperty
("tweetservice.oauth.consumerKey");
        this.oauthConsumerSecret = configurationService.getProperty
("tweetservice.oauth.consumerSecret");
        this.oauthAccessToken = configurationService.getProperty
("tweetservice.oauth.accessToken");
        this.oauthAccessTokenSecret = configurationService.getProperty
("tweetservice.oauth.accessTokenSecret");
    }
    ...
    @Inject
    ConfigurationService configurationService;
}

```



If you *do* have a domain service that needs to access properties, then note that an alternative is to define a `@PostConstruct` method and pass in a `Map<String, String>` of properties. The two techniques are almost identical; it's mostly a matter of taste.

8.2.2. Implementation

The core framework provides a default implementation of this service (`o.a.i.core.runtime.services.config.ConfigurationServiceDefault`).

8.2.3. Registering the Service

Assuming that the `configuration-and-annotation` services installer is configured (implicit if using the [AppManifest](#) to [bootstrap the app](#)) then Apache Isis' core implementation of `ConfigurationService` service is automatically registered and injected (it is annotated with `@DomainService`) so no further configuration is required.

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide).

8.2.4. Related services

The `ConfigurationServiceMenu` exposes the `allConfigurationProperties` action in the user interface.

8.3. DomainObjectContainer

The `DomainObjectContainer` service provides a set of general purpose functionality for domain objects to call. Principal amongst these are a generic APIs for querying objects and creating and

persisting objects. In addition, the service provides access to security context (the "current user"), allows information and warning messages to be raised, and various other miscellaneous functions.



(Almost all of) the methods in this service have been moved out into a number of more fine-grained services: `RepositoryService`, `MessageService`, `FactoryService`, `TitleService`, `ConfigurationService`, `UserService` and `ServiceRegistry`.

8.3.1. APIs

The sections below discuss the functions provided by the service, broken out into categories.

Object Creation API

The object creation APIs are used to instantiate new domain objects or view models.

```
public interface DomainObjectContainer {  
  
    <T> T newTransientInstance(final Class<T> ofType); ①  
    <T> T newViewModelInstance(final Class<T> ofType, final String memento); ②  
    <T> T mixin(); ③  
    ...  
}
```

- ① create a new non-persisted domain entity. Any services will be automatically injected into the service.
- ② create a new view model, with the specified memento (as per `ViewModel#viewModelMemento()`). In general it is easier to just annotate with `@ViewModel` and let Apache Isis manage the memento automatically.
- ③ programmatically instantiate a mixin, as annotated with `@Mixin` or `@DomainObject#nature()`.

For example:

```
Customer cust = container.newTransientInstance(Customer.class);  
cust.setFirstName("Freddie");  
cust.setLastName("Mercury");  
container.persist(cust);
```

As an alternative to using `newTransientInstance(...)` or `mixin(...)`, you could also simply `new()` up the object. Doing this will not inject any domain services, but they can be injected manually using `#injectServicesInto(...)`.



Calling `new(...)` also this circumvents Apache Isis' `created()` callback, and in addition any default values for properties (either explicitly set by `default…()` or defaulted implicitly according to Apache Isis' own conventions) will not be called either. If you don't intend to use these features, though, the net effect is code that has less coupling to Isis and is arguably easier to understand (has "less magic" happening).

Generic Repository API

The repository API acts as an abstraction over the JDO/DataNucleus objectstore. You can use it during prototyping to write naive queries (find all rows, then filter using the Guava `Predicate` API, or you can use it to call JDO `named queries` using JDOQL.

As an alternative, you could also use JDO `typesafe queries` through the `IsisJdoSupport` service.

```
public interface DomainObjectContainer {  
    public <T> List<T> allInstances(Class<T> ofType, long... range);  
    ①   <T> List<T> allMatches(Query<T> query);  
    ②   <T> List<T> allMatches(Class<T> ofType, Predicate<? super T> predicate, long...  
        range); ③   <T> List<T> allMatches(Class<T> ofType, String title, long... range);  
    ④   <T> List<T> allMatches(Class<T> ofType, T pattern, long... range);  
    ⑤   ...  
}
```

- ① all persisted instances of specified type. Mostly for prototyping, though can be useful to obtain all instances of domain entities if the number is known to be small. The optional varargs parameters are for paging control; more on this below.
- ② all persistence instances matching the specified `Query`. Query itself is an Isis abstraction on top of JDO/DataNucleus' Query API. **This is the primary API used for querying**
- ③ all persisted instances of specified type matching `Predicate`. Only really intended for prototyping because in effect constitutes a client-side WHERE clause
- ④ all persisted instances with the specified string as their title. Only very occasionally used
- ⑤ all persisted instances matching object (query-by-example). Only very occasionally used

There are various implementations of the `Query` API, but these either duplicate functionality of the other overloads of `allMatches(...)` or they are not supported by the JDO/DataNucleus object store. The only significant implementation of `Query` to be aware of is `QueryDefault`, which identifies a named query and a set of parameter/argument tuples.

For example, in the (non-ASF) [Isis addons' todoapp](#) the `ToDoItem` is annotated:

```

@javax.jdo.annotations.Queries( {
    @javax.jdo.annotations.Query(
        name = "findByAtPathAndComplete", language = "JDOQL",           ①
        value = "SELECT "
            + "FROM todoapp.dom.module.todoitem.ToDoItem "
            + "WHERE atIndex(:atPath) == 0 "                         ②
            + "    && complete == :complete"),                           ③
        ...
    })
public class ToDoItem ... {
    ...
}

```

- ① name of the query
- ② defines the `atPath` parameter
- ③ defines the `complete` parameter

This JDO query definitions are used in the `ToDoItemRepositoryImplUsingJdoql` service:

```

@DomainService(nature = NatureOfService.DOMAIN)
public class ToDoItemRepositoryImplUsingJdoql implements ToDoItemRepositoryImpl {
    @Programmatic
    public List<ToDoItem> findByAtPathAndCategory(final String atPath, final Category
category) {
        return container.allMatches(
            new QueryDefault<>(ToDoItem.class,
                "findByAtPathAndCategory",
                "atPath", atPath,
                "category", category));                                ①
    }
    ...
    @javax.inject.Inject
    DomainObjectContainer container;
}

```

- ① corresponds to the "findByAtPathAndCategory" JDO named query
- ② provide argument for the `atPath` parameter. The pattern is parameter, argument, parameter, argument, ... and so on.
- ③ provide argument for the `category` parameter. The pattern is parameter, argument, parameter, argument, ... and so on.

Other JDOQL named queries (not shown) follow the exact same pattern.

With respect to the other query APIs, the varargs parameters are optional, but allow for (client-side and managed) paging. The first parameter is the `start` (0-based, the second is the `count`.



It is also possible to query using DataNucleus' type-safe query API. For more details, see [IsisJdoSupport](#).

Object Persistence API

The persistence API is used to persist newly created objects (as per `#newTransientInstance(...)`, above and to delete (remove) objects that are persistent.

Note that there is no API for updating existing objects; the framework (or rather, JDO/DataNucleus) performs object dirty tracking and so any objects that are modified in the course of a request will be automatically updated).

```
public interface DomainObjectContainer {  
  
    boolean isPersistent(Object domainObject);          ①  
    boolean isViewModel(Object domainObject);            ②  
  
    void persist(Object domainObject);                  ③  
    void persistIfNotAlready(Object domainObject);      ④  
  
    void remove(Object persistentDomainObject);         ⑤  
    void removeIfNotAlready(Object domainObject);        ⑥  
  
    boolean flush();                                    ⑦  
    ...  
}
```

- ① test whether a particular domain object is persistent or not.
- ② test whether a particular domain object is a view model or not. Note that this includes any domain objects annotated with `@DomainObject#nature=Nature.EXTERNAL_ENTITY` or `@DomainObject#nature=Nature.INMEMORY_ENTITY`
- ③ persist a transient object. Note though that this will throw an exception if the object is already persistent; this can happen if JDO/DataNucleus's `persistence-by-reachability` is in effect. For this reason it is generally better to use `persistIfNotAlready(...)`. Also note that `persist(...)` has been deprecated. When moving to `RepositoryService#persist()` take into account that its behavior is identical to <4>, being a no-op if the object is persistent, instead of throwing an exception.
- ④ persist an object but only if known to not have been persistent. But if the object is persistent, is a no-op
- ⑤ remove (ie DELETE) a persistent object. For similar reasons to the persistence, it is generally better to use:
- ⑥ remove (ie DELETE) an object only if known to be persistent. But if the object has already been deleted, then is a no-op.
- ⑦ flushes all pending changes to the objectstore. Explained further below.

For example:

```

Customer cust = container.newTransientInstance(Customer.class);
cust.setFirstName("Freddie");
cust.setLastName("Mercury");
container.persistIfNotAlready(cust);

```

You should be aware that by default Apache Isis queues up calls to `#persist()` and `#remove()`. These are then executed either when the request completes (and the transaction commits), or if the queue is flushed. This can be done either implicitly by the framework, or as the result of a direct call to `#flush()`.

By default the framework itself will cause `#flush()` to be called whenever a query is executed by way of `#allMatches(Query)`, as documented [above](#). However, this behaviour can be disabled using the configuration property `isis.services.container.disableAutoFlush`.

Messages API

The `DomainObjectContainer` allows domain objects to raise information, warning or error messages. These messages can either be simple strings, or can be translated.

```

public interface DomainObjectContainer {

    void informUser(String message);

①     String informUser(TranslatableString message, Class<?> contextClass, String
contextMethod); ②

    void warnUser(String message);

③     String warnUser(TranslatableString message, Class<?> contextClass, String
contextMethod); ④

    void raiseError(String message);

⑤     String raiseError(TranslatableString message, Class<?> contextClass, String
contextMethod); ⑥

    ...
}

```

- ① display as a transient message to the user (not requiring acknowledgement). In the [Wicket viewer](#) this is implemented as a toast that automatically disappears after a period of time.
- ② ditto, but with translatable string, for [i18n support](#).
- ③ warn the user about a situation with the specified message. In the [Wicket viewer](#) this is implemented as a toast that must be closed by the end-user.
- ④ ditto, but with translatable string, for i18n support.
- ⑤ show the user an unexpected application error. In the [Wicket viewer](#) this is implemented as a toast (with a different colour) that must be closed by the end-user.

⑥ ditto, but with translatable string, for i18n support.

For example:

```
public Order addItem(Product product, @ParameterLayout(named="Quantity") int quantity)
{
    if(productRepository.stockLevel(product) == 0) {
        container.warnUser(
            product.getDescription() + " out of stock; order fulfillment may be
delayed");
    }
    ...
}
```

Security API

The security API allows the domain object to obtain the identity of the user interacting with said object.

```
public interface DomainObjectContainer {
    UserMemento getUser();
    ...
}
```

where in turn (the essence of) `UserMemento` is:

```
public final class UserMemento {
    public String getName() { ... }
    public boolean isCurrentUser(final String userName) { ... }

    public List<RoleMemento> getRoles() { ... }
    public boolean hasRole(final RoleMemento role) { ... }
    public boolean hasRole(final String roleName) { ... }
    ...
}
```

and `RoleMemento` is simpler still:

```
public final class RoleMemento {
    public String getName() { ... }
    public String getDescription() { ... }

    ...
}
```

The roles associated with the `UserMemento` will be based on the configured `security` (typically Shiro).

In addition, when using the [Wicket viewer](#) there will be an additional "org.apache.isis.viewer.wicket.roles.USER" role; this is used internally to restrict access to web pages without authenticating.

Presentation API

A responsibility of every domain object is to return a title. This can be done declaratively using the [@Title](#) annotation on property/ies, or it can be done imperatively by writing a [title\(\)](#) method.

It's quite common for titles to be built up of the titles of other objects. If using building up the title using [@Title](#) then Apache Isis will automatically use the title of the objects referenced by the annotated properties. We also need programmatic access to these titles if going the imperative route.

Similarly, it often makes sense if [raising messages](#) to use the title of an object in a message rather (than a some other property of the object), because this is how end-users will be used to identifying the object.

The API defined by [DomainObjectContainer](#) is simply:

```
public interface DomainObjectContainer {  
    String titleOf(Object domainObject);  
    String iconNameOf(Object domainObject);  
    ...  
}
```

① return the title of the object, as rendered in the UI by the Apache Isis viewers.

② return the icon name of the object, as rendered in the UI by the Apache Isis viewers.

By way of example, here's some code from the (non-ASF) [Isis addons' todoapp](#) showing the use of the API in an message:

```
public List<ToDoItem> delete() {  
    final String title = container.titleOf(this);  
    ...  
    container.removeIfNotAlready(this);  
    container.informUser(  
        TranslatableString.tr(  
            "Deleted {title}", "title", title),  
            this.getClass(), "delete");  
    ...  
}
```

① the title is obtained first, because we're not allowed to reference object after it's been deleted

② use the title in an i18n [TranslatableString](#)

Properties API

The properties API allows domain objects to read the configuration properties aggregated from the various [configuration files](#).

```
public interface DomainObjectContainer {  
    String getProperty(String name);  
    String getProperty(String name, String defaultValue);  
    List<String> getPropertyNames();  
}
```

- ① Return the configuration property with the specified name; else return null.
- ② Return the configuration property with the specified name; if it doesn't exist then return the specified default value.
- ③ Return the names of all the available properties.

For example, here's a fictitious service that might wrap [Twitter4J](#). say:

```
@DomainService(nature=NatureOfService.DOMAIN)  
public class TweetService {  
    @Programmatic  
    @PostConstruct  
    public void init() {  
        this.oauthConsumerKey = container.getProperty(  
"tweetservice.oauth.consumerKey");  
        this.oauthConsumerSecret = container.getProperty(  
("tweetservice.oauth.consumerSecret"));  
        this.oauthAccessToken = container.getProperty(  
"tweetservice.oauth.accessToken");  
        this.oauthAccessTokenSecret = container.getProperty(  
("tweetservice.oauth.accessTokenSecret"));  
    }  
    ...  
    @Inject  
    DomainObjectContainer container;  
}
```



If you *do* have a domain service that needs to access properties, then note that an alternative is to define a `@PostConstruct` method and pass in a `Map<String, String>` of properties. The two techniques are almost identical; it's mostly a matter of taste.

Services API

The services API allows your domain objects to programmatically inject services into arbitrary objects, as well as to look up services by type.

The methods are:

```

public interface DomainObjectContainer {
    <T> T injectServicesInto(final T domainObject);           ①
    <T> T lookupService(Class<T> service);                  ②
    <T> Iterable<T> lookupServices(Class<T> service);      ③
    ...
}

```

① injects services into domain object; used extensively internally by the framework (eg to inject to other services, or to entities, or integration test instances, or fixture scripts). Service injection is done automatically if objects are created using `#newTransientInstance()`, described [above](#)

② returns the first registered service that implements the specified class

③ returns an `Iterable` in order to iterate over all registered services that implement the specified class

The primary use case is to instantiate domain objects using a regular constructor ("new is the new new") rather than using the `#newTransientInstance()` API, and then using the `#injectServicesInto(...)` API to set up any dependencies.

For example:

```

Customer cust = container.injectServicesInto( new Customer());
cust.setFirstName("Freddie");
cust.setLastName("Mercury");
container.persist(cust);

```

Validation API

The intent of this API is to provide a mechanism where an object can programmatically check the state any class invariants. Specifically, this means the validating the current state of all properties, as well as any object-level validation defined by `validate()`.



These methods have been deprecated; this feature should be considered experimental and your mileage may vary.

The API provided is:

```

public interface DomainObjectContainer {
    boolean isValid(Object domainObject);
    String validate(Object domainObject);
    ...
}

```

8.3.2. Implementation

The core framework provides a default implementation of this service (`o.a.i.core.metamodel.services.container.DomainObjectContainerDefault`).

8.3.3. Registering the Service

Assuming that the `configuration-and-annotation` services installer is configured (implicit if using the `AppManifest` to bootstrap the app) then Apache Isis' core implementation of `DomainObjectContainer` service is automatically registered and injected (it is annotated with `@DomainService`) so no further configuration is required.

8.4. EventBusService

The `EventBusService` allows domain objects to emit events to subscribing domain services using an in-memory event bus.

The primary user of the service is the framework itself, which automatically emit events for `actions`, `properties` and `collections`. Multiple events are generated:

- when an object member is to be viewed, an event is fired; subscribers can veto (meaning that the member is hidden)
- when an object member is to be enabled, the same event instance is fired; subscribers can veto (meaning that the member is disabled, ie cannot be edited/invoked)
- when an object member is being validated, then a new event instance is fired; subscribers can veto (meaning that the candidate values/action arguments are rejected)
- when an object member is about to be changed, then the same event instance is fired; subscribers can perform pre-execution operations
- when an object member has been changed, then the same event instance is fired; subscribers can perform post-execution operations

If a subscriber throws an exception in the first three steps, then the interaction is vetoed. If a subscriber throws an exception in the last two steps, then the transaction is aborted. For more on this topic, see `@Action#domainEvent()`, `@Property#domainEvent()` and `@Collection#domainEvent()`.

It is also possible for domain objects to programmatically generate domain events. However the events are published, the primary use case is to decoupling interactions from one module/package/namespace and another.

Two implementations are available, using either Guava's `EventBus`, or alternatively using the AxonFramework's `SimpleEventBus`. It is also possible to plug in a custom implementation.

8.4.1. API & Implementation

The API defined by `EventBusService` is:

```

public abstract class EventBusService {
    @Programmatic
    public void post(Object event) { ... }          ①
    @Programmatic
    public void register(final Object domainService) { ... } ②
    @Programmatic
    public void unregister(final Object domainService) { ... } ③
}

```

- ① posts the event onto event bus
- ② allows domain services to register themselves. This should be done in their `@PostConstruct` initialization method (for both singleton and `@RequestScoped` domain services).
- ③ exists for symmetry, but need never be called (it is in fact deliberately a no-op).

Isis provides a default implementation of the service, `o.a.i.objectstore.jdo.datanucleus.service.eventbus.EventBusServiceJdo`.

8.4.2. Registering Subscribers

The `register()` method should be called in the `@PostConstruct` lifecycle method. It is valid and probably the least confusing to readers to also "unregister" in the `@PreDestroy` lifecycle method (though as noted [above](#), unregistering is actually a no-op).

For example:

```

@DomainService(nature=NatureOfService.DOMAIN) ①
@DomainServiceLayout( menuOrder="1")           ②
public class MySubscribingDomainService {
    @PostConstruct
    public void postConstruct() {
        eventBusService.register(this);          ③
    }
    @PreDestroy
    public void preDestroy() {
        eventBusService.unregister(this);         ④
    }
    ...
    @javax.inject.Inject
    EventBusService eventBusService;
}

```

- ① subscribers are typically not visible in the UI, so specify a `DOMAIN` nature
- ② It's important that subscribers register before any domain services that might emit events on the event bus service. For example, the (non-ASF) [Isis addons' security](#) module provides a domain service that automatically seeds certain domain entities; these will generate [lifecycle events](#) and so any subscribers must be registered before such seed services. The easiest way to do this is to use the `@DomainServiceLayout#menuOrder()` attribute.

③ register with the event bus service during `@PostConstruct` initialization

④ corresponding deregister when shutting down

This works for both singleton (application-scoped) and also `@RequestScoped` domain services.



The `AbstractSubscriber` class automatically performs this registration. As a convenience, it is also annotated with the `@DomainServiceLayout#menuOrder()` attribute.

8.4.3. Annotating Members

As discussed in the introduction, the framework will automatically emit domain events for all of the object members (actions, properties or collections) of an object whenever that object is rendered or (more generally) interacted with.

For example:

```
public class Customer {  
    @Action  
    public Customer placeOrder(Product product, @ParameterLayout(named="Quantity") int  
    qty) { ... }  
    ...  
}
```

will propagate an instance of the default `o.a.i.applib.services.eventbus.ActionDomainEvent.Default` class. If using the Guava event bus this can be subscribed to using:

```
@DomainService(nature=NatureOfService.DOMAIN)  
public class MySubscribingDomainService  
    @Programmatic  
    @com.google.common.eventbus.Subscribe  
    public void on(ActionDomainEvent ev) { ... }  
    ...  
}
```

or if using Axonframework, the subscriber uses a different annotation:

```
@DomainService(nature=NatureOfService.DOMAIN)  
public class MySubscribingDomainService  
    @Programmatic  
    @org.axonframework.eventhandling.annotation.EventHandler  
    public void on(ActionDomainEvent ev) { ... }  
    ...  
}
```

More commonly though you will probably want to emit domain events of a specific subtype. As a

slightly more interesting example, suppose in a library domain that a `LibraryMember` wants to leave the library. A letter should be sent out detailing any books that they still have out on loan:

In the `LibraryMember` class, we publish the event by way of an annotation:

```
public class LibraryMember {  
    @Action(domainEvent=LibraryMemberLeaveEvent.class) ①  
    public void leave() { ... }  
    ...  
}
```

① `LibraryMemberLeaveEvent` is a subclass of `o.a.i.applib.eventbus.ActionDomainEvent`. The topic of subclassing is discussed in more detail [below](#).

Meanwhile, in the `BookRepository` domain service, we subscribe to the event and act upon it. For example:

```
public class BookRepository {  
    @Programmatic  
    @com.google.common.eventbus.Subscribe  
    public void onLibraryMemberLeaving(LibraryMemberLeaveEvent e) {  
        LibraryMember lm = e.getLibraryMember();  
        List<Book> lentBooks = findBooksOnLoanFor(lm);  
        if(!lentBooks.isEmpty()) {  
            sendLetter(lm, lentBooks);  
        }  
    }  
    ...  
}
```

This design allows the `libraryMember` module to be decoupled from the `book` module.

8.4.4. Event hierarchy

By creating domain event subtypes we can be more semantically precise and in turn provides more flexibility for subscribers: they can choose whether to be broadly applicable (by subscribing to a superclass) or to be tightly focussed (by subscribing to a subclass).

We recommend that you define event classes at (up to) four scopes:

- at the top "global" scope is the Apache Isis-defined `o.a.i.applib.event.ActionDomainEvent`
- for the "module" scope, create a static class to represent the module itself, and creating nested classes within
- for each "class" scope, create a nested static event class in the domain object's class for all of the domain object's actions
- for each "action" scope, create a nested static event class for that action, inheriting from the "domain object" class.

To put all that into code; at the module level we can define:

```
package com.mycompany.modules.libmem;  
...  
public static class LibMemModule {  
    private LibMemModule() {}  
    public abstract static class ActionDomainEvent<S>  
        extends org.apache.isis.applib.event.ActionDomainEvent<S> {}  
    ...  
    public abstract static class PropertyDomainEvent<S,T>  
        extends org.apache.isis.applib.event.PropertyDomainEvent<S,T> {}  
    public abstract static class CollectionDomainEvent<S,E>  
        extends org.apache.isis.applib.event.CollectionDomainEvent<S,E> {}  
}
```

①

① similar events for properties and collections should also be defined

For the class-level we can define:

```
public static class LibraryMember {  
    public abstract static class ActionDomainEvent  
        extends LibMemModule.ActionDomainEvent<LibraryMember> {}  
    ...  
}
```

①

① similar events for properties and collections should also be defined

and finally at the action level we can define:

```
public class LibraryMember {  
    public static class LeaveEvent extends LibraryMember.ActionDomainEvent {}  
    @Action(domainEvent=LeaveEvent.class)  
    public void leave() { ... }  
    ...  
}
```

The subscriber can subscribe either to the general superclass (as before), or to any of the classes in the hierarchy.

Variation (for contributing services)

A slight variation on this is to not fix the generic parameter at the class level, ie:

```

public static class LibraryMember {
    public abstract static class ActionDomainEvent<S>
        extends LibMemModule.ActionDomainEvent<S> { }

    ...
}

```

and instead parameterize down at the action level:

```

public class LibraryMember {
    public static class LeaveEvent
        extends LibraryMember.ActionDomainEvent<LibraryMember> { } ①
    }
    @Action(domainEvent=LeaveEvent.class)
    public void leave() { ... }

    ...
}

```

This then allows for other classes - in particular domain services contributing members - to also inherit from the class-level domain events.

8.4.5. Programmatic posting

To programmatically post an event, simply call `#post()`.

The `LibraryMember` example described above could for example be rewritten into:

```

public class LibraryMember {
    ...

    public void leave() {
        ...
        eventBusService.post(new LibraryMember.LeaveEvent(...)); ①
    }
    ...
}

```

① `LibraryMember.LeaveEvent` could be *any* class, not just a subclass of `o.a.i.applib.event.ActionDomainEvent`.

In practice we suspect there will be few cases where the programmatic approach is required rather than the declarative approach afforded by `@Action#domainEvent()` et al.

8.4.6. Using `WrapperFactory`

An alternative way to cause events to be posted is through the `WrapperFactory`. This is useful when you wish to enforce a (lack-of-) trust boundary between the caller and the callee.

For example, suppose that `Customer#placeOrder(...)` emits a `PlaceOrderEvent`, which is subscribed to

by a `ReserveStockSubscriber`. This subscriber in turn calls `StockManagementService#reserveStock(...)`. Any business rules on `#reserveStock(...)` should be enforced.

In the `ReserveStockSubscriber`, we therefore use the `WrapperFactory`:

```
@DomainService(nature=NatureOfService.DOMAIN)
public class ReserveStockSubscriber {
    @Programmatic
    @Subscribe
    public void on(Customer.PlaceOrderEvent ev) {
        wrapperFactory.wrap(stockManagementService)
            .reserveStock(ev.getProduct(), ev.getQuantity());
    }
    ...
    @Inject
    StockManagementService stockManagementService;
    @Inject
    WrapperFactory wrapperFactory;
}
```

8.4.7. Implementation SPI

The implementation of `EventBusService` provided by Apache Isis will by default use Guava's `EventBus` as the underlying in-memory event bus. Alternatively the AxonFramework's `SimpleEventBus` can be used. Which is used is specified through configuration property (described below).

Guava vs Axon, which to use?



Guava actually queues up events; they are not guaranteed to be dispatched immediately. This generally is not problem, but can be for cases where the subscriber may in turn want to post its own events (using `WrapperFactory`).

The Axon `SimpleEventBus`-based implementation on the other hand is fully synchronous; events are dispatched as soon as they are posted. This works well in all scenarios (that we have tested).

It is also possible to use some other implementation.

```
public interface EventBusImplementation {
    void register(Object domainService);
    void unregister(Object domainService);
    void post(Object event);
}
```

As is probably obvious, the `EventBusService` just delegates down to these method calls when its own similarly named methods are called.

If you do provide your own implementation of this SPI, be aware that your subscribers will need to use whatever convention is required (eg different annotations) such that the events are correctly routed through to your subscribers.

8.4.8. Configuration

The implementation of `EventBusService` provided by Apache Isis will by default use Guava's `EventBus` as the underlying in-memory event bus. Alternatively the AxonFramework's `SimpleEventBus` can be used.

To specify which, add the configuration property `isis.services.eventbus.implementation`:

```
isis.services.eventbus.implementation=guava
```

or

```
isis.services.eventbus.implementation=axon
```

If you have written your own implementation of the `EventBusServiceImplementation` SPI, then specify instead its fully-qualified class name:

```
isis.services.eventbus.implementation=com.mycompany.isis.MyEventBusServiceImplementation
```

In addition, there is one further configuration property, whether to allow "late registration":

```
isis.services.eventbus.allowLateRegistration=false
```

Late registration refers to the idea that a domain service can register itself with the `EventBusService` after events have been posted. Since domain services are set up at boot time, this almost certainly constitutes a bug in the code and so by default late registration is *not* allowed. Setting the above property to `true` disables this check.

8.4.9. Registering the Services

Assuming that the `configuration-and-annotation` services installer is configured (implicit if using the `AppManifest` to `bootstrap the app`) then Apache Isis' core implementation of `EventBusService` service is automatically registered and injected (it is annotated with `@DomainService`) so no further configuration is required.

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide).

8.4.10. Related Services

The `EventBusService` is intended for fine-grained publish/subscribe for object-to-object interactions within an Apache Isis domain object model. The event propagation is strictly in-memory, and there are no restrictions on the object acting as the event (it need not be serializable, for example).

The `PublishingService` meanwhile is intended for coarse-grained publish/subscribe for system-to-system interactions, from Apache Isis to some other system. Here the only events published are those that action invocations (for actions annotated with `@Action#publishing()`) and of changed objects (for objects annotated with `@DomainObject#publishing()`).

8.5. FactoryService

The `FactoryService` collects together methods for instantiating domain objects.



The methods in this service replace similar methods (now deprecated) in `DomainObjectContainer`.

8.5.1. API

The API of `FactoryService` is:

```
public interface FactoryService {  
    <T> T instantiate(final Class<T> ofType);           ①  
    <T> T mixin();                                         ②  
}
```

① create a new non-persisted domain entity. Any services will be automatically injected into the service.

② programmatically instantiate a mixin, as annotated with `@Mixin` or `@DomainObject#nature()`.

The object is created in memory, but is not persisted. The benefits of using this method (instead of simply using the Java `new` keyword) are:

- any services will be injected into the object immediately (otherwise they will not be injected until the framework becomes aware of the object, typically when it is persisted through the `RepositoryService`)
- the default value for any properties (usually as specified by `defaultXxx()` supporting methods) will not be set and the `created()` callback will be called.

The corollary is: if your code never uses `defaultXxx()` or the `created()` callback, then you can just `new` up the object. The `ServiceRegistry` service can be used to inject services into the domain object.

8.5.2. Usage

For example:

```
Customer cust = factoryService.instantiate(Customer.class);
cust.setFirstName("Freddie");
cust.setLastName("Mercury");
repositoryService.persist(cust);
```

8.5.3. Implementation

The core framework provides a default implementation of this service ([o.a.i.core.metamodel.services.factory.FactoryServiceDefault](#)).

8.5.4. Registering the Service

Assuming that the [configuration-and-annotation](#) services installer is configured (implicit if using the [AppManifest](#) to [bootstrap the app](#)) then Apache Isis' core implementation of [FactoryService](#) service is automatically registered and injected (it is annotated with [@DomainService](#)) so no further configuration is required.

To use an alternative implementation, use [@DomainServiceLayout#menuOrder\(\)](#) (as explained in the [introduction](#) to this guide).

8.5.5. Related Services

The [RepositoryService](#) is often used in conjunction with the [FactoryService](#), to persist domain objects after they have been instantiated and populated.

An alternative to using the factory service is to simply instantiate the object ("new is the new new") and then use the [ServiceRegistry](#) service to inject other domain services into the instantiated object.

8.6. Scratchpad

The [Scratchpad](#) service is a [request-scoped](#) service to allow objects to exchange information even if they do not directly call each other.

8.6.1. API & Implementation

The API of [Scratchpad](#) service is:

```
@RequestScoped
public class Scratchpad {
    @Programmatic
    public Object get(Object key) { ... }
    @Programmatic
    public void put(Object key, Object value) { ... }
    @Programmatic
    public void clear() { ... }
}
```

This class (`o.a.i.applib.services.scratchpad.Scratchpad`) is also the implementation. And, as you can see, the service is just a request-scoped wrapper around a `java.util.Map`.

8.6.2. Usage

The most common use-case is for `bulk` actions that act upon multiple objects in a list. The (same) `Scratchpad` service is injected into each of these objects, and so they can use pass information.

For example, the Isis addons example `todoapp` (not ASF) demonstrates how the `Scratchpad` service can be used to calculate the total cost of the selected `ToDoItem`'s:

```
@Action(  
    semantics=SemanticsOf.SAFE,  
    invokeOn=InvokeOn.COLLECTION_ONLY  
)  
public BigDecimal totalCost() {  
    BigDecimal total = (BigDecimal) scratchpad.get("runningTotal");  
    if(getCost() != null) {  
        total = total != null ? total.add(getCost()) : getCost();  
        scratchpad.put("runningTotal", total);  
    }  
    return total.setScale(2);  
}  
@Inject  
Scratchpad scratchpad;
```

A more complex example could use a `view model` to enable bulk updates to a set of objects. The view model's job is to gather track of the items to be updated:

```
public class ToDoItemUpdateBulkUpdate extends AbstractViewModel {  
    private List<ToDoItem> _items = ...;  
    public ToDoItemBulkUpdate add(ToDoItem item) {  
        _items.add(item);  
        return this;  
    }  
    ...  
}
```

① not shown - the implementation of `ViewModel` for converting the list of `_items` into a string.

The bulk action in the objects simply adds the selected item to the view model:

```

@Action(
    invokeOn=InvokeOn.COLLECTIONS_ONLY
    semantics=SemanticsOf.SAFE
)
public ToDoItemBulkUpdate bulkUpdate() {
    return lookupBulkUpdateViewModel().add(this);
}
private ToDoItemBulkUpdate lookupBulkUpdateViewModel() {
    ToDoItemBulkUpdate bulkUpdate =
        (ToDoItemBulkUpdate) scratchpad.get("bulkUpdateViewModel");      ①
    if(bulkUpdate == null) {
        bulkUpdate = container.injectServicesInto(new ToDoItemBulkUpdate());
        scratchpad.put("bulkUpdateViewModel", bulkUpdate);            ②
    }
    return bulkUpdate;
}
@Inject
Scratchpad scratchpad;

```

① look for the `ToDoItemBulkUpdate` in the scratchpad...

② ... and add one if there isn't one (ie for the first object returned).

If using the [Wicket viewer](#), the `ToDoItemBulkUpdate` view model returned from the last action invoked will be displayed. Thereafter this view model can be used to perform a bulk update of the "enlisted" items.

8.6.3. Registering the Service

Assuming that the [configuration-and-annotation](#) services installer is configured (implicit if using the [AppManifest](#) to [bootstrap the app](#)) then Apache Isis' core implementation of `Scratchpad` service is automatically registered and injected (it is annotated with `@DomainService`) so no further configuration is required.

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide).

8.6.4. Related Services

The `ActionInteractionContext` service allows [bulk actions](#) to co-ordinate with each other.

The `QueryResultsCache` is useful for caching the results of expensive method calls.

8.7. UserService

The `UserService` allows the domain object to obtain the identity of the user interacting with said object.



The methods in this service replace similar methods (now deprecated) in [DomainObjectContainer](#).

8.7.1. API and Usage

The API of [UserService](#) is:

```
public interface UserService {  
    UserMemento getUser();  
}
```

where in turn (the essence of) [UserMemento](#) is:

```
public final class UserMemento {  
    public String getName() { ... }  
    public boolean isCurrentUser(final String userName) { ... }  
  
    public List<RoleMemento> getRoles() { ... }  
    public boolean hasRole(final RoleMemento role) { ... }  
    public boolean hasRole(final String roleName) { ... }  
    ...  
}
```

and [RoleMemento](#) is simpler still:

```
public final class RoleMemento {  
    public String getName() { ... }  
    public String getDescription() { ... }  
    ...  
}
```

The roles associated with the [UserMemento](#) will be based on the configured [security](#) (typically Shiro).

In addition, when using the [Wicket viewer](#) there will be an additional "org.apache.isis.viewer.wicket.roles.USER" role; this is used internally to restrict access to web pages without authenticating.

8.7.2. Implementation

The core framework provides a default implementation of this service ([o.a.i.core.runtime.services.user.UserServiceDefault](#)).

8.7.3. Registering the Service

Assuming that the [configuration-and-annotation](#) services installer is configured (implicit if using the [AppManifest](#) to [bootstrap the app](#)) then Apache Isis' core implementation of [UserService](#) service

is automatically registered and injected (it is annotated with `@DomainService`) so no further configuration is required.

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide).

Chapter 9. Integration API

The integration APIs provide functionality to the domain objects to integrate with other bounded contexts, for example sending an email or serializing an object out to XML.

The table below summarizes the integration APIs defined by Apache Isis. It also lists their corresponding implementation, either a default implementation provided by Apache Isis itself, or provided by one of the in (non-ASF) [Isis Addons](#) modules.

Table 8. Integration API

API	Description	Implementation	Notes
<code>o.a.i.applib.services.bookmark</code> <code>BookmarkService2</code>	Convert object reference to a serializable "bookmark", and vice versa.	<code>BookmarkServiceDefault</code> <code>o.a.i.core.isis-core-metamodel</code>	related services: <code>BookmarkHolder</code> - <code>ActionContributions</code> , <code>BookmarkHolder</code> - <code>Association</code> - <code>Contributions</code>
<code>o.a.i.applib.services.deeplink</code> <code>DeepLinkService</code>	Obtain a URL to a domain object (eg for use within an email or report)	<code>DeepLinkServiceWicket</code> <code>o.a.i.viewer.isis-viewer-wicket-impl</code>	Implementation only usable within Wicket viewer
<code>o.a.i.applib.services.email</code> <code>EmailService</code>	Send a HTML email, optionally with attachments.	<code>EmailServiceDefault</code> <code>o.a.i.core.isis-core-runtime</code>	
<code>o.a.i.applib.services.guice</code> <code>GuiceBeanProvider</code>	Access to internal framework services initialized using Guice DI.	<code>GuiceBeanProviderWicket</code> <code>o.a.i.core.isis-viewer-wicket-impl</code>	
<code>o.a.i.applib.services.jaxb</code> <code>JaxbService</code>	Marshal and unmarshal JAXB-annotated view models to/from XML.	<code>JaxbServiceDefault</code> <code>o.a.i.core.isis-core-schema</code>	

API	Description	Implementation	Notes
<code>o.a.i.applib.services.memento.MementoService</code>	Capture a serializable memento of a set of primitives or bookmarks . Primarily used internally, eg in support of commands/auditing.	<code>MementoServiceDefault</code> <code>o.a.i.coreisis-core-runtime</code>	
<code>o.a.i.applib.services.xmlsnapshot.XmlSnapshotService</code>	Generate an XML representation of an object and optionally a graph of related objects.	<code>XmlSnapshotServiceDefault</code> <code>o.a.i.coreisis-core-runtime</code>	

9.1. BookmarkService2

The `BookmarkService2` API provides the ability to obtain a serializable `o.a.i.applib.bookmarks.Bookmark` for any (persisted) domain object, and to lookup domain objects given a **Bookmark**. This can then in turn be converted to and from a string.

For example, a `Customer` object with:

- an object type of "custmgmt.Customer" (as per `DomainObject#objectType()` or equivalent), and
- an id=123

could correspond to a **Bookmark** with a string representation of `custmgmt.Customer|123`.

A **Bookmark** is little more than an API equivalent of Apache Isis' internal `Oid` (object identifier). Nevertheless, the ability to uniquely address *any* domain object within an Apache Isis system — to in effect provide a URN — is immensely useful.



For example, a **Bookmark** could be converted into a barcode, and then used for automated scanning of correspondence from a customer.

Bookmarks are used by several other domain services as a means of storing a reference to an arbitrary object (a polymorphic relationship). For example, the (non-ASF) **Isis addons'** auditing module's implementation of `AuditingService` uses bookmarks to capture the object that is being audited.



One downside of using **Bookmarks** is that there is no way for the JDO/DataNucleus objectstore to enforce any kind of referential integrity. However, the (non-ASF) **Isis addons'** poly module describes and supports a design pattern to address this requirement.

9.1.1. API & Implementation

The API defined by `BookmarkService2` is:

```

public interface BookmarkService2 {
    enum FieldResetPolicy {
        RESET,
        DONT_RESET
    }
    @Programmatic
    Object lookup(BookmarkHolder bookmarkHolder, FieldResetPolicy policy);
    @Programmatic
    Object lookup(Bookmark bookmark, FieldResetPolicy policy);
    @Programmatic
    <T> T lookup(Bookmark bookmark, FieldResetPolicy policy, Class<T> cls);      ②
    @Programmatic
    Bookmark bookmarkFor(Object domainObject);
    @Programmatic
    Bookmark bookmarkFor(Class<?> cls, String identifier);
}

```

① if the object has already been loaded from the database, then whether to reset its fields. The default it to `RESET`.

② same as `lookup(Bookmark bookmark)`, but downcasts to the specified type.

The core framework provides a default implementation of this API, namely `o.a.i.core.metamodel.services.bookmarks.BookmarkServiceDefault`

9.1.2. BookmarkHolder

The `BookmarkHolder` interface is intended to be implemented by domain objects that use a `Bookmark` to reference a (single) domain object; an example might be a class such as the audit entry, mentioned above. The interface is simply:

```

public interface BookmarkHolder {
    @Programmatic
    Bookmark bookmark();
}

```

There are two services that will contribute to this interface:

- `BookmarkHolderActionContributions` will provide a `lookup(...)` action
- `BookmarkHolderAssociationContributions` provides an `object` property.

Either of these can be suppressed, if required, using a vetoing subscriber. For example, to suppress the `object` property (so that only the `lookup(...)` action is ever shown for implementations of `BookmarkHolder`, define:

```

@DomainService(nature=NatureOfService.DOMAIN)
public class AlwaysHideBookmarkHolderAssociationsObjectProperty {
    @Subscribe
    public void on(BookmarkHolderAssociationContributions.ObjectDomainEvent ev) {
        ev.hide();
    }
}

```

A more sophisticated implementation could look inside the passed `ev` argument and selectively hide or not based on the contributee.

9.1.3. Usage by other services

Bookmarks are used by the (non-ASF) [Isis addons' command](#) module's implementation of `BackgroundCommandService`, which uses a bookmark to capture the target object on which an action will be invoked subsequently.

Bookmarks are also used by the (non-ASF) [Isis addons' publishing](#) module's implementation of `PublishingService`, and by the (non-ASF) [Isis addons' auditing](#) module's implementation of `AuditingService`.

9.1.4. Registering the Service

Assuming that the `configuration-and-annotation` services installer is configured (implicit if using the [AppManifest](#) to bootstrap the app) then Apache Isis' core implementation of `BookmarkService` is automatically registered (it is annotated with `@DomainService`) so no further configuration is required.

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide).

9.2. DeepLinkService

The `DeepLinkService` provides the ability to obtain a `java.net.URI` that links to a representation of any (persisted) domain entity or view model.

A typical use case is to generate a clickable link for rendering in an email, PDF, tweet or other communication.

9.2.1. API & Implementation

The API defined by `DeepLinkService` is:

```

public interface DeepLinkService {
    URI deepLinkFor(Object domainObject); ①
}

```

- ① Creates a URI that can be used to obtain a representation of the provided domain object in one of the Apache Isis viewers.

The [Wicket viewer](#) this provides an implementation for accessing the representation through this viewer. (For the [RestfulObjects viewer](#), a URL can be constructed according to the [Restful Objects spec](#) in conjunction with a [Bookmark](#) obtained via the [BookmarkService](#)).

9.2.2. Usage within the framework

The [EmailNotificationService](#) uses this service in order to generate emails as part of [user registration](#).

9.2.3. Implementations

The Wicket viewer core framework provides a default implementation of this API:

- `org.apache.isis.viewer.wicket.viewer.services.DeepLinkServiceWicket`

9.2.4. Registering the Services

Assuming that the `<code>configuration-and-annotation</code>` services installer is configured (implicit if using the `<code>AppManifest</code>` to [`bootstrap the app`](#), [`_and`](#) that the [`Wicket viewer`](#) is being used, then an implementation of `<code>DeepLinkService</code>` is automatically registered and injected (it is annotated with `<code>@DomainService</code>`) so no further configuration is required.

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide).

9.3. EmailService

The [EmailService](#) provides the ability to send HTML emails, with attachments, to one or more recipients.

Apache Isis provides a default implementation to send emails using an external SMTP provider. Note that this must be configured (using a number of configuration properties) before it can be used. The that sends email as an HTML message, using an external SMTP provider.

9.3.1. API & Implementation

The API for the service is:

```

public interface EmailService {
    @Programmatic
    boolean send(
        List<String> to, List<String> cc, List<String> bcc,           ①
        String subject,
        String body,                                         ②
        DataSource... attachments);                         ③
    @Programmatic
    boolean isConfigured();                            ④
}

```

- ① is the main API to send the email (and optional attachments). Will return `false` if failed to send
- ② pass either `null` or `Collections.emptyList()` if not required
- ③ should be HTML text
- ④ indicates whether the implementation was configured and initialized correctly. If this returns `false` then any attempt to call `send(...)` will fail.

As noted in the introduction, the core framework provides a default implementation ([EmailServiceDefault](#)) that sends email as an HTML message, using an external SMTP provider.

9.3.2. Configuration

To use this service the following properties must be configured:

- `isis.service.email.sender.address`
- `isis.service.email.sender.password`

and these properties may optionally be configured (each has a default to use gmail, documented [here](#)):

- `isis.service.email.sender.hostname`
- `isis.service.email.port`
- `isis.service.email.tls.enabled`

These configuration properties can be specified either in `isis.properties` or in an [external configuration file](#).

If prototyping (that is, running the app using `org.apache.isis.WebServer`), the configuration properties can also be specified as system properties. For example, if you create a test email account on gmail, you can configure the service using:

```

-Disis.service.email.sender.address=xxx@gmail.com
-Disis.service.email.sender.password=yyy

```

where "xxx" is the gmail user account and "yyy" is its password

9.3.3. Alternative Implementations

If you wish to write an alternative implementation, be aware that it should process the message body as HTML (as opposed to plain text or any other format).

Also, note that (unlike most Apache Isis domain services) the implementation is also instantiated and injected by Google Guice. This is because `EmailService` is used as part of the `user registration` functionality and is used by Wicket pages that are accessed outside of the usual Apache Isis runtime. This implies a couple of additional constraints:

- first, implementation class should also be annotated with `@com.google.inject.Singleton`
- second, there may not be any Apache Isis session running. (If necessary, one can be created on the fly using `IsisContext.doInSession(...)`)

To ensure that your alternative implementation takes the place of the default implementation, register it explicitly in `isis.properties`.

9.3.4. Registering the Services

Assuming that the `configuration-and-annotation` services installer is configured (implicit if using the `AppManifest` to `bootstrap the app`) then Apache Isis' core implementation of `EmailService` service is automatically registered and injected (it is annotated with `@DomainService`) so no further configuration is required.

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide).

9.3.5. Related Services

The email service is used by the `EmailNotificationService` which is, in turn, used by `UserRegistrationService`.

9.4. GuiceBeanProvider

The `GuiceBeanProvider` domain service acts as a bridge between Apache Isis' `Wicket viewer` internal bootstrapping using `Google Guice`.

This service operates at a very low-level, and you are unlikely to have a need for it. It is used internally by the framework, in the default implementation of the `DeepLinkService`.



Currently Apache Isis uses a combination of Guice (within the Wicket viewer only) and a home-grown dependency injection framework. In future versions we intended to refactor the framework to use CDI throughout. At that time this service is likely to become redundant because we will allow any of the internal components of Apache Isis to be injected into your domain object code.

9.4.1. API & Implementation

The API defined by this service is:

```
public interface GuiceBeanProvider {  
    @Programmatic  
    <T> T lookup(Class<T> beanType);  
    @Programmatic  
    <T> T lookup(Class<T> beanType, final Annotation qualifier);  
}
```

The [Wicket viewer](#) this provides an implementation of this service.

9.4.2. Usage

Using the [Wicket viewer](#) requires subclassing of [IsisWicketApplication](#). In the subclass it is commonplace to override [newIsisWicketModule\(\)](#), for example:

```
@Override  
protected Module newIsisWicketModule() {  
    final Module isisDefaults = super.newIsisWicketModule();  
    final Module overrides = new AbstractModule() {  
        @Override  
        protected void configure() {  
            bind(String.class).annotatedWith(Names.named("applicationName"))  
                .toInstance("ToDo App");  
            bind(String.class).annotatedWith(Names.named("applicationCss"))  
                .toInstance("css/application.css");  
            bind(String.class).annotatedWith(Names.named("applicationJs"))  
                .toInstance("scripts/application.js");  
            ...  
        }  
    };  
    return Modules.override(isisDefaults).with(overrides);  
}
```

This "module" is in fact a Guice module, and so the [GuiceBeanProvider](#) service can be used to lookup any of the components bound into it.

For example:

```

public class SomeDomainObject {
    private String lookupApplicationName() {
        return guiceBeanProvider.lookup(String.class, Names.named("applicationName"));
    }
    @Inject
    GuiceBeanProvider guiceBeanProvider;
}

```

should return "ToDo App".

9.4.3. Registering the Services

Assuming that the `configuration-and-annotation` services installer is configured (implicit if using the `AppManifest` to [bootstrap the app](#)), and that the [Wicket viewer](#) is being used, then an implementation of `GuiceBeanProvider` is automatically registered and injected (it is annotated with `@DomainService`) so no further configuration is required.

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide).

9.5. JaxbService

The `JaxbService` allows instances of JAXB-annotated classes to be marshalled to XML and unmarshalled from XML back into domain objects.

9.5.1. API & Implementation

The API defined by `JaxbService` is:

```

public interface JaxbService {
    @Programmatic
    <T> T fromXml(Class<T> domainClass, String xml);
    ①
    @Programmatic
    public String toXml(final Object domainObject);
    ②
    public enum IsisSchemas {
    ③
        INCLUDE, IGNORE
    }
    @Programmatic
    public Map<String, String> toXsd(final Object domainObject, final IsisSchemas
    isSchemas);} ④
}

```

① unmarshalls the XML into an instance of the class.

- ② marshalls the domain object into XML
- ③ whether to include or exclude the Isis schemas in the generated map of XSDs. Discussed further below.
- ④ generates a map of each of the schemas referenced; the key is the schema namespace, the value is the XML of the schema itself.

With respect to the `IsisSchemas` enum: a JAXB-annotated domain object will live in its own XSD namespace and may reference multiple other XSD schemas. In particular, many JAXB domain objects will reference the [common Isis schemas](#) (for example the `OidDto` class that represents a reference to a persistent entity). The enum indicates whether these schemas should be included or excluded from the map.

Isis provides a default implementation of the service, `o.a.i.schema.services.jaxb.JaxbServiceDefault`.

9.5.2. Usage within the framework

This service is provided as a convenience for applications, but is also used internally by the framework to `@XmlElement`-annotated [view models](#). The functionality to download XML and XSD schemas is also exposed in the UI through mixins to `Dto` interface.

9.5.3. Registering the Service

Assuming that the [configuration-and-annotation](#) services installer is configured (implicit if using the `AppManifest` to [bootstrap the app](#)) then Apache Isis' core implementation of `JaxbService` service is automatically registered and injected (it is annotated with `@DomainService`) so no further configuration is required.

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide).

9.6. MementoService

The `MementoService` was originally introduced to simplify the implementation of [ViewModels](#) which are required by the framework to return string representation of all of their backing state, moreover which is safe for use within a URL.

However, it can also be used to create a memento of arbitrary objects. (Prior to [1.13.0-SNAPSHOT](#) it is used internally by the core implementation of `'BackgroundService` to capture the state of action invocations so that they can be executed by a background process.



As of [1.13.0-SNAPSHOT](#) this service is deprecated.

9.6.1. API & Implementation

The API defined by `MementoService` is:

```

@Deprecated
public interface MementoService {
    @Deprecated
    public static interface Memento {
        public Memento set(String name, Object value);
        public <T> T get(String name, Class<T> cls);
        public String asString();
        public Set<String> keySet();
    }
    public Memento create();
    public Memento parse(final String str);
    public boolean canSet(Object input);
}

```

The core framework provides a default implementation of this API, namely `o.a.i.c.r.services.memento.MementoServiceDefault`. The string returned (from `Memento#asString()`) is a base-64 URL encoded representation of the underlying format (an XML string).



In fact, the `MementoServiceDefault` implementation does provide a mechanism to disable the URL encoding, but this is not part of the `MementoService` public API. Note also that the encoding method is not pluggable.

The types of objects that are supported by the `MementoService` are implementation-specific, but would typically include all the usual value types as well as Apache Isis' `Bookmark` class (to represent references to arbitrary entities). Nulls can also be set.

In the case of the default implementation provided by the core framework, the types supported are:

- `java.lang.String`
- `java.lang.Boolean, boolean`
- `java.lang.Byte, byte`
- `java.lang.Short, short`
- `java.lang.Integer, int`
- `java.lang.Long, long`
- `java.lang.Float, float`
- `java.lang.Double, double`
- `java.lang.Character, char`
- `java.math.BigDecimal`
- `java.math.BigInteger`
- `org.joda.time.LocalDate`
- `org.apache.isis.applib.services.bookmark.Bookmark`

If using another implementation, the `canSet(...)` method can be used to check if the candidate object's type is supported.

9.6.2. Usage

As noted in the introduction, a common use case for this service is in the implementation of the `ViewModel` interface.



Rather than implementing `ViewModel`, it's usually easier to annotate your view models with `@ViewModel` (or equivalently `@DomainObject#nature=EXTERNAL_ENTITY` or `@DomainObject#nature=INMEMORY_ENTITY`).

For example, suppose you were implementing a view model that represents an external entity in a SOAP web service. To access this service the view model needs to store (say) the hostname, port number and an id to the object.

Using an injected `MementoService` the view model can roundtrip to and from this string, thus implementing the `ViewModel` API:

```
public class ExternalEntity implements ViewModel {
    private String hostname;
    private int port;
    private String id;
    public String viewModelMemento() {           ①
        return mementoService.create()
            .set("hostname", hostname)
            .set("port", port)
            .set("id", id)
            .asString();
    }
    public void viewModelInit(String mementoStr) { ②
        Memento memento = mementoService.parse(mementoStr);
        hostname = memento.get("hostname", String.class);
        port = memento.get("port", int.class);
        id = memento.get("id", String.class);
        ...
    }
    @Inject
    MementoService mementoService;
}
```

① part of the `ViewModel` API

② part of the `ViewModel` API

9.6.3. Related Services

(Prior to `1.13.0-SNAPSHOT`), the memento service is used by the `CommandContext` service and also `BackgroundCommandService`. These both use a memento to capture a representation of an action invocation.

9.6.4. Registering the Service

Assuming that the `configuration-and-annotation` services installer is configured (implicit if using the `AppManifest` to `bootstrap the app`) then Apache Isis' core implementation of `MementoService` service is automatically registered and injected (it is annotated with `@DomainService`) so no further configuration is required.

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide).

9.7. XmlSnapshotService

The `XmlSnapshotService` provides the capability to generate XML snapshots (and if required corresponding XSD schemas) based on graphs of domain objects.

Typical use cases include creating mementos for business-focused auditing, such that a report could be generated as to which end-user performed a business action (perhaps for legal reasons). For one system that we know of, a digest of this snapshot of data is signed with the public encryption key so as to enforce non-repudiation.

Another use case is to grab raw data such that it could be merged into a report template or communication.

The service offers a basic API to create a snapshot of a single object, and a more flexible API that allows the size of the graph to be customized.

The core framework provides an implementation of this service (`o.a.i.core.runtime.services.xmlsnapshot.XmlSnapshotServiceDefault`).

9.7.1. Standard API

The (basic) API of `XmlSnapshotService` is:

```
public interface XmlSnapshotService {  
    public interface Snapshot {  
        Document getXmlDocument();  
        Document getXsdDocument();  
        String getXmlDocumentAsString();  
        String getXsdDocumentAsString();  
    }  
    @Programmatic  
    public XmlSnapshotService.Snapshot snapshotFor(Object domainObject);  
    ...  
}
```

The most straight-forward usage of this service is simply:

```
XmlSnapshot snapshot = xmlsnapshotService.snapshotFor(customer);
Element customerAsXml = snapshot.getXmlElement();
```

This will return an XML (document) element that contains the names and values of each of the customer's value properties, along with the titles of reference properties, and also the number of items in collections.

As well as obtaining the XML snapshot, it is also possible to obtain an XSD schema that the XML snapshot conforms to.

```
XmlSnapshot snapshot = ...;
Element customerAsXml = snapshot.getXmlElement();
Element customerXsd = snapshot.getXsdElement();
```

This can be useful for some tools. For example, [Altova Stylevision](#) can use the XML and XSD to transform into reports. Please note that this link does not imply endorsement (nor even a recommendation that this is a good design).

9.7.2. Builder API

The contents of the snapshot can be adjusted by including "paths" to other references or collections. To do this, the builder is used. The API for this is:

```
public interface XmlSnapshotService {
    ...
    public interface Builder {
        void includePath(final String path);
        void includePathAndAnnotation(String path, String annotation);
        XmlSnapshotService.Snapshot build();
    }
    @Programmatic
    public XmlSnapshotService.Builder builderFor(Object domainObject);
}
```

We start by obtaining a builder:

```
XmlSnapshot.Builder builder = xmlsnapshotService.builderFor(customer);
```

Suppose now that we want the snapshot to also include details of the customer's address, where **address** in this case is a reference property to an instance of the **Address** class. We can "walk-the-graph" by including these references within the builder.

```
builder.includePath("address");
```

We could then go further and include details of every order in the customer's `orders` collection, and details of every product of every order:

```
builder.includePath("orders/product");
```

When all paths are included, then the builder can build the snapshot:

```
XmlSnapshot snapshot = builder.build();
Element customerAsXml = snapshot.getXmlElement();
```

All of this can be strung together in a fluent API:

```
Element customerAsXml = xmlsnapshotService.builderFor(customer)
    .includePath("address")
    .includePath("orders/product")
    .build()
    .getXmlElement();
```

As you might imagine, the resultant XML document can get quite large very quickly with only a few "include"s.



If an XSD schema is being generated (using `snapshot.getXsdElement()`) then note that for the XSD to be correct, the object being snapshotted must have non-null values for the paths that are `include()'d. If this isn't done then the XSD will not be correct reflect for another snapshotted object that does have non-null values.

9.7.3. Automatic inclusions

If the domain object being snapshotted implements the `SnapshottableWithInclusions` interface, then this moves the responsibility for determining what is included within the snapshot from the caller to the snapshottable object itself:

```
public interface SnapshottableWithInclusions extends Snapshottable {
    List<String> snapshotInclusions();
}
```

If necessary, both approaches can be combined.



As an alternative to using `include()`, you might consider building a view model domain object which can reference only the relevant information required for the snapshot. For example, if only the 5 most recent Orders for a Customer were required, a `CustomerAndRecentOrders` view model could hold a collection of just those 5 Orders. Typically such view models would implement `SnapshottableWithInclusions`.

One reason for doing this is to provide a stable API between the domain model and whatever it is that might be consuming the XML. With a view model you can refactor the domain entities but still preserve a view model such that the XML is the same.

9.7.4. Convenience API

The `XmSnapshotService` also provides some API for simply manipulating XML:

```
public interface XmSnapshotService {  
    ...  
    @Programmatic  
    public Document asDocument(String xmlStr); ①  
    @Programmatic  
    public <T> T getChildElementValue(②  
        Element el, String tagname, Class<T> expectedCls);  
    @Programmatic  
    public Element getChildElement(③  
        Element el, String tagname);  
    @Programmatic  
    public String getChildTextValue(Element el); ④  
}
```

① is a convenience method to convert xml string back into a W3C Document

② is a convenience method to extract the value of an XML element, based on its type.

③ is a convenience method to walk XML document.

④ is a convenience method to obtain value of child text node.

9.7.5. Registering the Service

Assuming that the `configuration-and-annotation` services installer is configured (implicit if using the `AppManifest` to bootstrap the app) then Apache Isis' core implementation of `XmSnapshotService` service is automatically registered and injected (it is annotated with `@DomainService`) so no further configuration is required.

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide).

9.7.6. Related Services

The `BookmarkService` provides a mechanism for obtaining a string representations of a single domain object.

The `MementoService` also provides a mechanism for generating string representations of domain objects.

The `JaxbService` is a simple wrapper around standard JAXB functionality for generating both XMLs and XSDs from JAXB-annotated classes. Note that there is built-in support for JAXB classes (ie annotated with `@XmlElement`) to be used as view models.

Chapter 10. Metadata API

The metadata APIs provide access to the framework's internal metamodel. These are generally of use to support development-time activities, for example creating custom UIs through Swagger.

The table below summarizes the metadata APIs defined by Apache Isis. It also lists their corresponding implementation, either a default implementation provided by Apache Isis itself, or provided by one of the in (non-ASF) [Isis Addons](#) modules.

Table 9. Metadata API

API	Description	Implementation	Notes
<code>o.a.i.applib.services.appfeat</code> <code>ApplicationFeatureRepository</code>	Provides access to string representations of the features (package, class, class members) of the domain classes within the metamodel.	<code>ApplicationFeatureDefault</code> <code>o.a.i.core</code> <code>isis-core-metamodel</code>	(not visible in UI)
<code>o.a.i.applib.services.layout</code> <code>LayoutService</code>	Provides the ability to download dynamic layout XML files, in various styles.	<code>LayoutServiceDefault</code> <code>o.a.i.core</code> <code>isis-core-metamodel</code>	Functionality surfaced in the UI through related mixin and menu.
<code>o.a.i.applib.services.metamodel</code> <code>MetaModelService</code>	Access to certain information from the Apache Isis metamodel.	<code>MetaModelServiceDefault</code> <code>o.a.i.core</code> <code>isis-core-metamodel</code>	Functionality surfaced in the UI through related menu.
<code>o.a.i.applib.services.registry</code> <code>ServiceRegistry</code>	Methods to access and use other domain services.	<code>ServiceRegistry-Default</code> <code>o.a.i.core</code> <code>isis-core-metamodel</code>	Supercedes methods in <code>DomainObjectContainer</code> .

API	Description	Implementation	Notes
<code>o.a.i.applib.services.swagger</code> <code>SwaggerService</code>	Generates Swagger spec files to describe the public and/or private RESTful APIs exposed by the RestfulObjects viewer . These can then be used with the Swagger UI page to explore the REST API, or used to generate client-side stubs using the Swagger codegen tool, eg for use in a custom REST client app.	<code>SwaggerServiceDefault</code> <code>o.a.i.coreisis-core-metamodel</code>	A SwaggerServiceMenu domain service is also provided which enables the swagger spec to be downloaded. Apache Isis' Maven plugin also provides a swagger goal which allows the spec file(s) to be generated at build time (eg so that client-side stubs can then be generated in turn).

10.1. ApplicationFeatureRepository

The [ApplicationFeatureRepository](#) provides the access to string representations of the packages, classes and class members (collectively: "application features") of the domain classes within the Apache Isis' internal metamodel.



This functionality was originally implemented as part of (non-ASF) [Isis Addons](#) security module, where the string representations of the various features are used to represent permissions.

10.1.1. API & Implementation

The API defined by the service is:

```

public interface ApplicationFeatureRepository {
    List<String> packageNames();
    List<String> packageNamesContainingClasses(ApplicationMemberType memberType);
    List<String> classNamesContainedIn(String packageFqn, ApplicationMemberType memberType);
    List<String> classNamesRecursivelyContainedIn(String packageFqn);
    List<String> memberNamesOf(String packageFqn, String className,
ApplicationMemberType memberType);
}

```

where `ApplicationMemberType` in turn is:

```

public enum ApplicationMemberType {
    PROPERTY,
    COLLECTION,
    ACTION;
}

```

These methods are designed primarily to return lists of strings for use in drop-downs.

10.1.2. Registering the Service

Assuming that the `configuration-and-annotation` services installer is configured (implicit if using the `AppManifest` to bootstrap the app) then Apache Isis' core implementation of `ApplicationFeatureRepository` service is automatically registered and injected (it is annotated with `@DomainService`) so no further configuration is required.

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide).

10.2. LayoutService

The `LayoutService` provides the ability to obtain the XML layout for a single domain object or for all domain objects. This functionality is surfaced through the user interface through a related [mixin](#) and [menu](#) action.

10.2.1. API & Implementation

The API defined by `LayoutService` is:

```

public interface LayoutService {
    String toXml(Class<?> domainClass, Style style);           ①
    byte[] toZip(Style style);                                     ②
}

```

① Returns the serialized XML form of the layout (grid) for the specified domain class, in specified

style (discussed below).

- ② Returns (a byte array) of a zip of the serialized XML of the layouts (grids), for all domain entities and view models.

The `Style` enum is defined as:

```
enum Style {  
    CURRENT,  
    COMPLETE,  
    NORMALIZED,  
    MINIMAL  
}
```

The `CURRENT` style corresponds to the layout already loaded for the domain class, typically from an already persisted `layout.xml` file. The other three styles allow the developer to choose how much metadata is to be specified in the XML, and how much (if any) will be obtained elsewhere, typically from annotations in the metamodel (but also from `.layout.json` file if present). The table below summarises the choices:

Table 10. Table caption

Style	<code>@MemberGroupLayout</code>	<code>@MemberOrder</code>	<code>@ActionLayout</code> , <code>@PropertyLayout</code> , <code>@CollectionLayout</code>
<code>COMPLETE</code>	serialized as XML	serialized as XML	serialized as XML
<code>NORMALIZED</code>	serialized as XML	serialized as XML	not in the XML
<code>MINIMAL</code>	serialized as XML	not in the XML	not in the XML

As a developer, you therefore have a choice as to how you provide the metadata required for customised layouts:

- if you want all layout metadata to be read from the `.layout.xml` file, then download the "complete" version, and copy the file alongside the domain class. You can then remove all `@MemberGroupLayout`, `@MemberOrder`, `@ActionLayout`, `@PropertyLayout` and `@CollectionLayout` annotations from the source code of the domain class.
- if you want to use layout XML file to describe the grid (columns, tabs etc) and specify which object members are associated with those regions of the grid, then download the "normalized" version. You can then remove the `@MemberGroupLayout` and `@MemberOrder` annotations from the source code of the domain class, but retain the `@ActionLayout`, `@PropertyLayout` and `@CollectionLayout` annotations.
- if you want to use layout XML file ONLY to describe the grid, then download the "minimal" version. The grid regions will be empty in this version, and the framework will use the `@MemberOrder` annotation to bind object members to those regions. The only annotation that can be safely removed from the source code with this style is the `@MemberGroupLayout` annotation.

10.2.2. Related Mixins and Menus

The service's functionality is exposed in the UI through a mixin (per object) and a menu action (for all objects):

- the [Object mixin](#) provides the ability to download the XML layout for any domain object (entity or view model).
- the [LayoutServiceMenu](#) provides the ability to download all XML layouts as a single ZIP file (in any of the three styles).

The XML can then be copied into the codebase of the application, and annotations in the domain classes removed as desired.

10.2.3. Related Domain Services

The [GridService](#) is responsible for loading and normalizing layout XML for a domain class. It in turn uses the [GridLoaderService](#) and [GridSystemService](#) services.

10.3. MetaModelService

The [MetaModelService2](#) ([MetaModelService2](#) sub-interface introduced in [1.13.0-SNAPSHOT](#)) provides access to a number of aspects of Apache Isis' internal metamodel.

10.3.1. API

The API defined by the service is:

```
public interface MetaModelService2 {  
    Class<?> fromObjectType(final String objectType); ①  
    String toObjectType(final Class<?> domainType); ②  
    void rebuild(final Class<?> domainType); ③  
    List<DomainMember> export(); ④  
  
    enum Sort { ⑤  
        VIEW_MODEL, JDO_ENTITY, DOMAIN_SERVICE,  
        MIXIN, VALUE, COLLECTION;  
    }  
    Sort sortOf(final Class<?> domainType);  
    Sort sortOf(final Bookmark bookmark);  
}
```

① reverse lookup of a domain class' object type

② lookup of a domain class' object type

③ invalidate and rebuild the internal metadata (an [ObjectSpecification](#)) for the specified domain type.

④ returns a list of representations of each of member of each domain class.

⑤ ([1.13.0-SNAPSHOT](#)) what sort of object a domain type is (or bookmark represents)

10.3.2. Implementation

The framework provides a default implementation of this service ([org.apache.isis.core.metamodel.services.metamodel.MetaModelServiceDefault](#)).

10.3.3. Registering the Service

Assuming that the [configuration-and-annotation](#) services installer is configured (implicit if using the [AppManifest](#) to [bootstrap the app](#)) then Apache Isis' core implementation of [MetamodelService](#) service is automatically registered and injected (it is annotated with [@DomainService](#)) so no further configuration is required.

To use an alternative implementation, use [@DomainServiceLayout#menuOrder\(\)](#) (as explained in the [introduction](#) to this guide).

10.3.4. Related Services

The [MetaModelServiceMenu](#) provides a method to download all domain members as a CSV. Internally this calls [MetaModelService#export\(\)](#). Under the covers this uses the API provided by the [ApplicationFeatureRepository](#) domain service.

10.4. ServiceRegistry

The [ServiceRegistry](#) service collects together methods for accessing other domain services.



The methods in this service replace similar methods (now deprecated) in [DomainObjectContainer](#).

10.4.1. API

The API of [ServiceRegistry](#) is:

```
public interface ServiceRegistry {
    <T> T injectServicesInto(final T domainObject);          ①
    <T> T lookupService(Class<T> service);                  ②
    <T> Iterable<T> lookupServices(Class<T> service);      ③
}
```

- ① injects services into domain object; used extensively internally by the framework (eg to inject to other services, or to entities, or integration test instances, or fixture scripts).
- ② returns the first registered service that implements the specified class
- ③ returns an [Iterable](#) in order to iterate over all registered services that implement the specified class

Service injection is done automatically if objects are created using the [.adoc#_rgsvc_api_FactoryService\[FactoryService\]](#)

10.4.2. Usage

The primary use case is to instantiate domain objects using a regular constructor ("new is the new new"), and then using the `#injectServicesInto(…)` API to set up any dependencies.

For example:

```
Customer cust = serviceRegistry.injectServicesInto( new Customer());  
cust.setFirstName("Freddie");  
cust.setLastName("Mercury");  
repositoryService.persist(cust);
```

The alternative is to use the `FactoryService` API which performs both steps in a single factory method.

10.4.3. Implementation

The core framework provides a default implementation of this service (`o.a.i.core.runtime.services.registry.ServiceRegistryDefault`).

10.4.4. Registering the Service

Assuming that the `configuration-and-annotation` services installer is configured (implicit if using the `AppManifest` to bootstrap the app) then Apache Isis' core implementation of `ServiceRegistry` service is automatically registered and injected (it is annotated with `@DomainService`) so no further configuration is required.

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide).

10.5. SwaggerService

The `SwaggerService` generates `Swagger` spec files to describe the public and/or private RESTful APIs exposed by the `RestfulObjects` viewer.

These spec files can then be used with the `Swagger UI` page to explore the REST API, or used to generate client-side stubs using the `Swagger codegen` tool, eg for use in a custom REST client app.



Not all of the REST API exposed by the `Restful Objects viewer` is included in the `Swagger` spec files; the emphasis is those REST resources that are used to develop custom apps: domain objects, domain object collections and action invocations. When combined with Apache Isis' own `simplified representations`, these are pretty much all that is needed for this use case.

10.5.1. API & Implementation

The API defined by `SwaggerService` is:

```

public interface SwaggerService {
    enum Visibility {
        PUBLIC,                               ①
        PRIVATE,                                ②
        PRIVATE_WITH_PROTOTYPING;               ③
    }
    enum Format {                           ④
        JSON,
        YAML
    }
    String generateSwaggerSpec(final Visibility visibility, final Format format);
}

```

- ① Generate a Swagger spec for use by third-party clients, ie public use. This specification is restricted only to [view models](#) and to domain services with a [nature of VIEW_REST_ONLY](#).
- ② Generate a Swagger spec for use only by internally-managed clients, ie private internal use. This specification includes domain entities and all menu domain services (as well as any view models).
- ③ Generate a Swagger spec that is the same as private case (above), but also including any [prototype](#) actions.
- ④ Swagger specs can be written either in JSON or YAML format.

Isis provides a default implementation of the service, [o.a.i.core.metamodel.services.swagger.SwaggerServiceDefault](#).

10.5.2. Usage within the framework

This service is provided as a convenience for applications, it is not (currently) used by the framework itself.

10.5.3. Registering the Service

Assuming that the [configuration-and-annotation](#) services installer is configured (implicit if using the [AppManifest](#) to [bootstrap the app](#)) then Apache Isis' core implementation of [SwaggerService](#) service is automatically registered and injected (it is annotated with [@DomainService](#)) so no further configuration is required.

10.5.4. Related Services

A [SwaggerServiceMenu](#) domain service provides a prototype action that enables the swagger spec to be downloaded from the Wicket viewer's UI.

Apache Isis' [Maven plugin](#) also provides a [swagger goal](#) which allows the spec file(s) to be generated at build time. this then allows client-side stubs can then be generated in turn as part of a build pipeline.

Chapter 11. Testing

The testing APIs provide functionality to domain objects for use when testing or demoing an application.

The testing SPIs allow the framework to provide supporting functionality for use when testing or demoing an application.

The table below summarizes the testing APIs defined by Apache Isis. It also lists their corresponding implementation, either a default implementation provided by Apache Isis itself, or provided by one of the in (non-ASF) [Isis Addons](#) modules.

Table 11. Testing API

API	Description	Implementation	Notes
<code>o.a.i.applib.services.fixturespec</code> <code>FixtureScriptsDefault</code>	Fallback implementation of FixtureScripts , providing the ability to execute fixture scripts.	<code>FixtureScriptsDefault</code> <code>o.a.i.core</code> <code>isis-core-applib</code>	Interacts with FixtureScripts-SpecificationProvider .
<code>o.a.i.applib.services.fixturespec</code> <code>FixtureScripts-SpecificationProvider</code>	Provides settings for <code>FixtureScriptsDefault</code> fallback domain service for executing fixture scripts.		
<code>o.a.i.applib.services.sudo</code> <code>SudoService</code>	For use in testing while running fixture scripts , allows a block of code to run as a specified user account.	<code>SudoServiceDefault</code> <code>o.a.i.core</code> <code>isis-core-runtime</code>	API is also a concrete class

The table below summarizes the testing SPIs defined by Apache Isis. It also lists their corresponding implementation, either a default implementation provided by Apache Isis itself, or provided by one of the in (non-ASF) [Isis Addons](#) modules.

Table 12. Testing SPI

SPI	Description	Implementation	Notes

11.1. `FixtureScriptsDefault`

The `FixtureScriptsDefault` service provides the ability to execute [fixture scripts](#).

The service extends from the `FixtureScripts`, and is only instantiated by the framework if there no custom implementation of `FixtureScripts` has been otherwise provided; in other words it is a fallback.

If this service is instantiated (as a fallback) then it uses the `FixtureScriptsSpecificationProvider` to obtain a `FixtureScriptsSpecification`. This configures this service, telling it which package to search for `FixtureScript` classes, how to execute those classes, and hints that influence the UI.



We recommend using `FixtureScriptsSpecificationProvider` rather than subclassing `FixtureScripts`.

11.1.1. API & Implementation

The API for the service is:

```
public class FixtureScriptsDefault ... {  
    @Programmatic  
    public List<FixtureResult> runFixtureScript(  
        FixtureScript fixtureScript,  
        String parameters) { ... }  
}
```

- i. in other words the same as `FixtureScripts` superclass that it inherits from.

11.1.2. Configuration

As noted in the introduction, this service is only instantiated if there is no other implementation of `FixtureScripts` available on the classpath.

If an instance of `FixtureScriptsSpecificationProvider` is available on the classpath, then the service will be visible in the UI (assuming `prototype mode`). Otherwise the service will be available only to be injected and invoked programmatically.

11.1.3. Related Services

The service interacts with `FixtureScriptsSpecificationProvider`.

11.2. SudoService

The `SudoService` allows the current user reported by the `DomainObjectContainer` to be temporarily changed to some other user. This is useful both for `integration testing` (eg if testing a workflow system whereby objects are moved from one user to another) and while running `fixture scripts` (eg setting up objects that would normally require several users to have acted upon the objects).

11.2.1. API & Implementation

The API provided by the service is:

```

public interface SudoService {
    @Programmatic
    void sudo(String username, final Runnable runnable);
    @Programmatic
    <T> T sudo(String username, final Callable<T> callable);
    @Programmatic
    void sudo(String username, List<String> roles, final Runnable runnable);
    @Programmatic
    <T> T sudo(String username, List<String> roles, final Callable<T> callable);
}

```

which will run the provided block of code (a `Runnable` or a `Callable`) in a way such that calls to `DomainObjectContainer#getUser()` will return the specified user (and roles, if specified)

The core framework provides a default implementation of this service (`o.a.i.core.runtime.services.sudo.SudoServiceDefault`).

11.2.2. Usage

A good example can be found in the (non-ASF) [Isis addons' todoapp](#) which uses the `SudoService` in a fixture script to set up `ToDoItem` objects:

```

protected void execute(final ExecutionContext ec) {
    ...
    sudoService.sudo(getUsername(),
        new Runnable() {
            @Override
            public void run() {
                wrap(toDoItem).completed();
            }
        });
    ...
}

```

11.2.3. Registering the Service

Assuming that the `configuration-and-annotation` services installer is configured (implicit if using the `AppManifest` to [bootstrap the app](#)) then Apache Isis' core implementation of `SudoService` service is automatically registered and injected (it is annotated with `@DomainService`) so no further configuration is required.

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide).

11.3. FixtureScriptsSpec'nProvider

The `FixtureScriptsSpecificationProvider` configures the `FixtureScriptsDefault` domain service, providing the location to search for fixture scripts and other settings.

The service is only used if the `FixtureScriptsDefault` service is instantiated as a fallback by the framework. If the application provides its own subclass of `FixtureScripts` superclass, then this provider service is not used.



Of the two designs, we encourage you to implement this "provider" SPI rather than subclass `FixtureScripts`. The primary benefit (apart from decoupling responsibilities) is that it ensures that there is always an instance of `FixtureScripts` available for use.

11.3.1. SPI

The SPI defined by the service is:

```
public interface FixtureScriptsSpecificationProvider {  
    @Programmatic  
    FixtureScriptsSpecification getSpecification();  
}
```

where `FixtureScriptsSpecification` exposes these values:

```
public class FixtureScriptsSpecification {  
    public String getPackagePrefix() { ... }  
    public FixtureScripts.NonPersistedObjectsStrategy getNonPersistedObjectsStrategy()  
    { ... }  
    public FixtureScripts.MultipleExecutionStrategy getMultipleExecutionStrategy() {  
    ... }  
    public Class<? extends FixtureScript> getRunScriptDefaultScriptClass() { ... }  
    public DropDownPolicy getRunScriptDropDownPolicy() { ... }  
    public Class<? extends FixtureScript> getRecreateScriptClass() { ... }  
    ...  
}
```

The class is immutable but it has a builder (obtained using `FixtureScriptsSpecification.builder(...)`) for a fluent API.

11.3.2. Implementation

The `SimpleApp archetype` has a simple implementation of this service:

```
@DomainService(nature = NatureOfService.DOMAIN)
public class DomainAppFixturesProvider implements FixtureScriptsSpecificationProvider
{
    @Override
    public FixtureScriptsSpecification getSpecification() {
        return FixtureScriptsSpecification
            .builder(DomainAppFixturesProvider.class)
            .with(FixtureScripts.MultipleExecutionStrategy.EXECUTE)
            .withRunScriptDefault(RecreateSimpleObjects.class)
            .withRunScriptDropDown(FixtureScriptsSpecification.DropDownPolicy
.CHOICES)
            .withRecreate(RecreateSimpleObjects.class)
            .build();
    }
}
```

Chapter 12. Persistence Layer API

The persistence layer APIs provide domain objects with tools to manage the interactions with the persistence layer, for example adding on-the-fly caching to queries that are called many times within a loop.

The table below summarizes the persistence layer APIs defined by Apache Isis. It also lists their corresponding implementation, either a default implementation provided by Apache Isis itself, or provided by one of the in (non-ASF) [Isis Addons](#) modules.

Table 13. Persistence Layer API

API	Description	Implementation	Notes
<code>o.a.i.applib.services.jdosupport</code> <code>IsisJdoSupport</code>	Lower level access to the JDO Persistence API.	<code>IsisJdoSupportImpl</code> <code>o.a.i.core</code> <code>isis-core-runtime</code>	
<code>o.a.i.applib.services.metrics</code> <code>MetricsService</code>	Gathers and provides metrics on the numbers of objects used within a transaction.	<code>MetricsServiceDefault</code> <code>o.a.i.core</code> <code>isis-core-runtime</code>	
<code>o.a.i.applib.services.queryresultscache</code> <code>QueryResultsCache</code>	Request-scoped caching of the results of queries (or any data set generated by a given set of input arguments).	<code>QueryResultsCache</code> <code>o.a.i.core</code> <code>isis-core-applib</code>	API is also a concrete class
<code>o.a.i.applib.services.repository</code> <code>RepositoryService</code>	Methods to help implement repositories: query for existing objects, persist new or delete existing objects	<code>RepositoryService-Default</code> <code>o.a.i.core</code> <code>isis-core-metamodel</code>	Supercedes methods in <code>DomainObjectContainer</code> .

Key:

- `o.a.i` is an abbreviation for `org.apache.isis`
- `o.ia.m` is an abbreviation for `org.isisaddons.module`

12.1. `IsisJdoSupport`

The `IsisJdoSupport` service provides a number of general purpose methods for working with the JDO/DataNucleus objectstore. In general these act at a lower-level of abstraction than the APIs normally used (specifically, those of `DomainObjectContainer`), but nevertheless deal with some of the most common use cases. For service also provides access to the underlying JDO `PersistenceManager` for full control.

The following sections discuss the functionality provided by the service, broken out into categories.

12.1.1. Executing SQL

You can use the `IsisJdoSupportService` to perform arbitrary SQL SELECTs or UPDATES:

```
public interface IsisJdoSupport {  
    @Programmatic  
    List<Map<String, Object>> executeSql(String sql);  
    @Programmatic  
    Integer executeUpdate(String sql);  
    ...  
}
```

The `executeSql(...)` method allows arbitrary SQL **SELECT** queries to be submitted:

```
List<Map<String, Object>> results = isisJdoSupport.executeSql("select * from  
custMgmt.customers");
```

The result set is automatically converted into a list of maps, where the map key is the column name.

In a similar manner, the `executeUpdate(...)` allows arbitrary SQL **UPDATEs** to be performed.

```
int count = isisJdoSupport.executeUpdate("select count(*) from custMgmt.customers");
```

The returned value is the number of rows updated.



As an alternative, consider using DataNucleus' [type-safe JDO query API](#), discussed [below](#).

12.1.2. Type-safe JDOQL Queries

DataNucleus provides an [extension to JDO](#), so that JDOQL queries can be built up and executed using a set of type-safe classes.

The types in question for type safe queries are not the domain entities, but rather are companion "Q..." query classes. These classes are generated dynamically by an [annotation processor](#) as a side-effect of compilation, one "Q..." class for each of the `@PersistenceCapable` domain entity in your application. For example, a `ToDoItem` domain entity will give rise to a `QToDoItem` query class. These "Q..." classes mirror the structure of domain entity, but expose properties that allow predicates to be built up for querying instances, as well as other functions in support of order by, group by and other clauses.



Most IDEs (including IntelliJ and Eclipse) enable annotation processing by default, as does Maven. The DataNucleus' [documentation](#) offers some guidance on confirming that APT is enabled.

The `IsisJdoSupport` service offers two methods at different levels of abstraction:

```
public interface IsisJdoSupport {  
    @Programmatic  
    <T> List<T> executeQuery(final Class<T> cls, final BooleanExpression be);  
    @Programmatic  
    <T> TypesafeQuery<T> newTypesafeQuery(Class<T> cls);  
    ...  
}
```

The `executeQuery(...)` method supports the common case of obtaining a set of objects that meet some criteria, filtered using the provided `BooleanExpression`. To avoid memory leaks, the returned list is cloned and the underlying query closed.

For example, in the (non-ASF) `Isis addons' todoapp` there is an implementation of `ToDoItemRepository` using type-safe queries. The following JDOQL:

```
SELECT  
FROM todoapp.dom.module.todoitem.ToDoItem  
WHERE atPath.indexOf(:atPath) == 0  
  && complete == :complete")
```

can be expressed using type-safe queries as follows:

```
public List<ToDoItem> findByAtPathAndCategory(final String atPath, final Category category) {  
    final QToDoItem q = QToDoItem.candidate();  
    return isisJdoSupport.executeQuery(ToDoItem.class,  
        q.atPath.eq(atPath).and(  
            q.category.eq(category)));  
}
```



You can find the full example of the JDOQL equivalent in the `DomainObjectContainer`

The `newTypesafeQuery(...)` method is a lower-level API that allows a type safe query to be instantiated for most sophisticated querying, eg using group by or order by clauses. See the DataNucleus [documentation](#) for full details of using this.

One thing to be aware of is that after the query has been executed, it should be closed, using `query.closeAll()`. If calling `query.executeList()` we also recommend cloning the resultant list first. The following utility method does both of these tasks:

```

private static <T> List<T> executeListAndClose(final TypesafeQuery<T> query) {
    final List<T> elements = query.executeList();
    final List<T> list = Lists.newArrayList(elements);
    query.closeAll();
    return list;
}

```

12.1.3. Fixture support

When writing [integration tests](#) you'll usually need to tear down some/all mutable transactional data before each test. One way to do that is to use the `executeUpdate(...)` method described [above](#).

Alternatively, the `deleteAll(...)` method will let your test delete all instances of a class without resorting to SQL:

```

public interface IsisJdoSupport {
    @Programmatic
    void deleteAll(Class<?>... pcClasses);
    ...
}

```

For example:

```

public class TearDownAll extends FixtureScriptAbstract {
    @Override
    protected void execute(final ExecutionContext ec) {
        isisJdoSupport.deleteAll(Order.class);
        isisJdoSupport.deleteAll(CustomerAddress.class);
        isisJdoSupport.deleteAll(Customer.class);
    }
    @Inject
    IsisJdoSupport isisJdoSupport;
}

```



It can occasionally be the case that Apache Isis' internal adapter for the domain object is still in memory. JDO/DataNucleus seems to bump up the version of the object prior to its deletion, which under normal circumstances would cause Apache Isis to throw a concurrency exception. Therefore to prevent this from happening (ie to *force* the deletion of all instances), concurrency checking is temporarily disabled while this method is performed.

12.1.4. Reloading entities

An [\(intentional\) limitation](#) of JDO/DataNucleus is that persisting a child entity (in a 1:n bidirectional relationship) does not cause the parent's collection to be updated.

```

public interface IsisJdoSupport {
    @Programmatic
    <T> T refresh(T domainObject);
    @Programmatic
    void ensureLoaded(Collection<?> collectionOfDomainObjects);
    ...
}

```

The `refresh(T domainObject)` method can be used to reload the parent object (or indeed any object). Under the covers it uses the JDO `PersistenceManager#refresh(...)` API.

For example:

```

@DomainService(nature=NatureOfService.VIEW_CONTRIBUTIONS_ONLY)
public class OrderContributions {
    public Order newOrder(final Customer customer) {
        Order order = newTransientInstance(Order.class);
        order.setCustomer(customer);
        container.persist(customer);
        container.flush();          ①
        isisJdoSupport.refresh(customer); ②
        return order;
    }
    @Inject
    DomainObjectContainer container;
    @Inject
    IsisJdoSupport isisJdoSupport;
}

```

① flush to database, ensuring that the database row corresponding to the `Order` exists in its `order` table.

② reload the parent (`customer`) from the database, so that its collection of `Orders` is accurate.



The particular example that led to this method being added was a 1:m bidirectional relationship, analogous to `Customer 1<-→* Order`. Persisting the child `Order` object did not cause the parent `Customer`'s collection of orders to be updated. In fact, JDO does not make any such guarantee to do so. Options are therefore either to maintain the collection in code, or to refresh the parent.

The `ensureLoaded(...)` method allows a collection of domain objects to be loaded from the database in a single hit. This can be valuable as a performance optimization to avoid multiple roundtrips to the database. Under the covers it uses the `PersistenceManager#retrieveAll(...)` API.

12.1.5. JDO PersistenceManager

The functionality provided by `IsisJdoSupport` focus only on the most common use cases. If you require more flexibility than this, eg for dynamically constructed queries, then you can use the

service to access the underlying JDO `PersistenceManager` API:

```
public interface IsisJdoSupport {  
    @Programmatic  
    PersistenceManager getJdoPersistenceManager();  
    ...  
}
```

For example:

```
public List<Order> findOrders(...) {  
    javax.jdo.PersistenceManager pm = isisJdoSupport.getPersistenceManager();  
  
    // knock yourself out...  
  
    return someListOfOrders;  
}
```

12.1.6. Registering the Services

Assuming that the `configuration-and-annotation` services installer is configured (implicit if using the `AppManifest` to `bootstrap the app`) then Apache Isis' core implementation of `IsisJdoSupport` service is automatically registered and injected (it is annotated with `@DomainService`) so no further configuration is required.

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide).

12.2. MetricsService (1.13.0-SNAPSHOT)



TODO

12.3. QueryResultsCache

The purpose of the `QueryResultsCache` is to improve response times to the user, by providing a short-term (`request-scoped`) cache of the value of some (safe or idempotent) method call. This will typically be as the result of running a query, but could be any expensive operation.

Caching such values is useful for code that loops "naively" through a bunch of stuff, performing an expensive operation each time. If the data is such that the same expensive operation is made many times, then the query cache is a perfect fit.



This service was inspired by similar functionality that exists in relational databases, for example Sybase's `subquery results cache` and Oracle's `result_cache` hint.

12.3.1. API & Implementation

The API defined by `QueryResultsCache` is:

```
@RequestScoped
public class QueryResultsCache {
    public static class Key {
        public Key(Class<?> callingClass, String methodName, Object... keys) {...}
        public Class<?> getCallingClass() { ... }
        public String getMethodName() { ... }
        public Object[] getKeys() { ... }
    }
    public static class Value<T> {
        public Value(T result) { ... }
        private T result;
        public T getResult() {
            return result;
        }
    }
    @Programmatic
    public <T> T execute(
        final Callable<T> callable,
        final Class<?> callingClass, final String methodName, final Object... keys) {
    ...
    }
    @Programmatic
    public <T> T execute(final Callable<T> callable, final Key cacheKey) { ... }
    @Programmatic
    public <T> Value<T> get(
        final Class<?> callingClass, final String methodName, final Object... keys) {
    ...
    }
    @Programmatic
    public <T> Value<T> get(final Key cacheKey) { ... }
    @Programmatic
    public <T> void put(final Key cacheKey, final T result) { ... }
}
```

This class (`o.a.i.applib.services.queryresultscache.QueryResultsCache`) is also the implementation.

12.3.2. Usage

Suppose that there's a `TaxService` that calculates tax on `Taxable` items, with respect to some `TaxType`, and for a given `LocalDate`. To calculate tax it must run a database query and then perform some additional calculations.

Our original implementation is:

```

@DomainService
public class TaxService {
    public BigDecimal calculateTax(
        final Taxable t, final TaxType tt, final LocalDate d) {
        // query against DB using t, tt, d
        // further expensive calculations
    }
}

```

Suppose now that this service is called in a loop, for example iterating over a bunch of orders, where several of those orders are for the same taxable products, say. In this case the result of the calculation would always be the same for any given product.

We can therefore refactor the method to use the query cache as follows:

```

public class TaxService {
    public BigDecimal calculateTax(
        final Taxable t, final TaxType tt, final LocalDate d) {
        return queryResultsCache.execute(
            new Callable<BigDecimal>(){①
                public BigDecimal call() throws Exception {
                    // query against DB using t, tt, d
                    // further expensive calculations
                }
            },
②
            TaxService.class,
            "calculateTax",
            t, tt, d);
    }
}

```

① the `Callable` is the original code

② the remaining parameters in essence uniquely identify the method call.

This refactoring will be worthwhile provided that enough of the orders being processed reference the same taxable products. If however every order is for a different product, then no benefit will be gained from the refactoring.

12.3.3. Registering the Service

Assuming that the `configuration-and-annotation` services installer is configured (implicit if using the `AppManifest` to bootstrap the app) then Apache Isis' core implementation of `QueryResultsCache` service is automatically registered and injected (it is annotated with `@DomainService`) so no further configuration is required.

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the introduction to this guide).

12.3.4. Related Services

The `Scratchpad` service is also intended for actions that are called many times, allowing arbitrary information to be shared between them. Those methods could be called from some outer loop in domain code, or by the framework itself if the action invoked has the `@Action#invokeOn()` annotation attribute set to `OBJECT_AND_COLLECTION` or `COLLECTION_ONLY`.

12.4. RepositoryService

The `RepositoryService` collects together methods for creating, persisting and searching for entities from the underlying persistence store. It acts as an abstraction over the JDO/DataNucleus objectstore.

You can use it during prototyping to write naive queries (find all rows, then filter using the Guava `Predicate` API, or you can use it to call JDO `named queries` using JDOQL.

As an alternative, you could also use `JDO typesafe queries` through the `IsisJdoSupport` service.



The methods in this service replace similar methods (now deprecated) in `DomainObjectContainer`.

12.4.1. API

The API of `RepositoryService` is:

```

public interface RepositoryService {
    <T> T instantiate(final Class<T> ofType);
①

    boolean isPersistent(Object domainObject);
②

    void persist(Object domainObject);
③

    void persistAndFlush(Object domainObject);
④

    void remove(Object persistentDomainObject);
⑤

    void removeAndFlush(Object persistentDomainObject);
⑥

    <T> List<T> allInstances(Class<T> ofType, long... range);
⑦

    <T> List<T> allMatches(Query<T> query);
⑧

    <T> List<T> allMatches(Class<T> ofType, Predicate<? super T> predicate, long...
range); ⑨

    <T> T uniqueMatch(Query<T> query);
⑩

    <T> T uniqueMatch(final Class<T> ofType, final Predicate<T> predicate);
⑪

    <T> T firstMatch(Query<T> query);
⑫

    <T> T firstMatch(final Class<T> ofType, final Predicate<T> predicate);
⑬
}

```

- ①** create a new non-persisted domain entity. This is identical to `FactoryService`'s `instantiate(...)` method, but is provided in the `RepositoryService`'s API too because instantiating and persisting objects are often done together.
- ②** test whether a particular domain object is persistent or not
- ③** persist (ie save) an object to the persistent object store (or do nothing if it is already persistent).
- ④** **(1.13.0-SNAPSHOT)** persist (ie save) and flush; same as `persist()`, but also flushes changes to database and updates managed properties and collections (i.e., 1-1, 1-n, m-n relationships automatically maintained by the DataNucleus persistence mechanism).
- ⑤** remove (ie delete) an object from the persistent object store (or do nothing if it has already been deleted).
- ⑥** **(1.13.0-SNAPSHOT)** remove (delete) and flush; same as `remove()`, but also flushes changes to database and updates managed properties and collections (i.e., 1-1, 1-n, m-n relationships

automatically maintained by the DataNucleus persistence mechanism).

- ⑦ return all persisted instances of specified type. Mostly for prototyping, though can be useful to obtain all instances of domain entities if the number is known to be small. The optional varargs parameters are for paging control; more on this below.
- ⑧ all persistence instances matching the specified `Query`. Query itself is an Isis abstraction on top of JDO/DataNucleus' Query API. **This is the primary API used for querying**
- ⑨ As the previous, but with client-side filtering using a `Predicate`. Only really intended for prototyping.
- ⑩ Returns the first instance that matches the supplied query. If no instance is found then `null` will be returned, while if there is more than one instances a run-time exception will be thrown. Generally this method is preferred for looking up an object by its (primary or alternate) key.
- ⑪ As the previous, but with client-side filtering using a `Predicate`. Only really intended for prototyping.
- ⑫ Returns the first instance that matches the supplied query. If no instance is found then `null` will be returned. **No exception is thrown if more than one matches, so this is less strict than** `'uniqueMatch(...)`.
- ⑬ As the previous, but with client-side filtering using a `Predicate`. Only really intended for prototyping.

The `uniqueMatch(...)` methods are the recommended way of querying for (precisely) one instance. The `firstMatch(...)` methods are for less strict querying.

12.4.2. Usage

This section briefly discusses how application code can use (some of) these APIs.

Persist

```
Customer cust = repositoryService.instantiate(Customer.class);
cust.setFirstName("Freddie");
cust.setLastName("Mercury");
repositoryService.persist(cust);
```

You should be aware that by default Apache Isis queues up calls to `#persist()` and `#remove()`. These are then executed either when the request completes (and the transaction commits), or if the queue is flushed. This can be done either implicitly by the framework, or as the result of a direct call to `#flush()`.

By default the framework itself will cause `#flush()` to be called whenever a query is executed by way of `#allMatches(Query)`, as documented [above](#). However, this behaviour can be disabled using the configuration property `isis.services.container.disableAutoFlush`.

`persistAndFlush(...), removeAndFlush(...)`

In some cases, such as when using managed properties and collections for implementing 1-1, 1-n, or m-n relationships, the developer needs to invoke `flush()` to send the changes to the DataNucleus persistence mechanism. These managed properties and collections are then updated.

The `persistAndFlush(...)` and `removeAndFlush(...)` methods (introduced in 1.13.0-SNAPSHOT) save the developer from having to call the `flush(...)` method.

For example, the following code requires a flush to occur, so uses these methods:

```
public abstract class Warehouse extends SalesVIPEntity<Marketplace> {

    @Persistent(mappedBy = "marketplace", dependentElement = "true")
    @Getter @Setter
    private SortedSet<MarketplaceExcludedProduct> excludedProducts =
        new TreeSet<MarketplaceExcludedProduct>(); ①

    @Action(semantics = SemanticsOf.IDEMPOTENT)
    public MarketplaceExcludedProduct addExcludedProduct(final Product product) {
        MarketplaceExcludedProduct marketplaceExcludedProduct = this
            .findExcludedProduct(product);
        if (marketplaceExcludedProduct == null) {
            marketplaceExcludedProduct =
                this.factoryService.instantiate(MarketplaceExcludedProduct.class);
        }

        this.wrap(marketplaceExcludedProduct).setMarketplace(this);
        this.wrap(marketplaceExcludedProduct).setProduct(product);

        this.repositoryService.persistAndFlush(marketplaceExcludedProduct); ②
        return marketplaceExcludedProduct;
    }

    @Action(semantics = SemanticsOf.IDEMPOTENT)
    public void deleteFromExcludedProducts(final Product product) {
        final MarketplaceExcludedProduct marketplaceExcludedProduct =
            findExcludedProduct(product);
        if (marketplaceExcludedProduct != null) {
            this.repositoryService.removeAndFlush(marketplaceExcludedProduct);
        }
    }
    ... ③
}
```

① using lombok for brevity

② Needed for updating the managed properties and collections.

③ injected services and other methods omitted

On the “`addExcludedProduct()`” action, if the user didn’t flush, the following test would fail because

the managed collection would not containing the given product:

```
@Test
public void addExcludedProduct() {

    // given
    final AmazonMarketplace amazonMarketplace = this.wrapSkipRules(
        this.marketplaceRepository).findOrCreateAmazonMarketplace(
            AmazonMarketplaceLocation.FRANCE);

    final Product product = this.wrap(this.productRepository)
        .createProduct(UUID.randomUUID().toString(), UUID.randomUUID().toString());

    // when
    this.wrap(amazonMarketplace).addExcludedProduct(product);

    // then
    Assertions.assertThat(
        this.wrapSkipRules(amazonMarketplace).findAllProductsExcluded()
            .contains(product));
}

①
```

① this would fail.

Query and `xxxMatches(...)`

There are various implementations of the `Query` API, but these either duplicate functionality of the other overloads of `allMatches(...)` or they are not supported by the JDO/DataNucleus object store. The only significant implementation of `Query` to be aware of is `QueryDefault`, which identifies a named query and a set of parameter/argument tuples.

For example, in the (non-ASF) `Isis addons' todoapp` the `ToDoItem` is annotated:

```
@javax.jdo.annotations.Queries( {
    @javax.jdo.annotations.Query(
        name = "findByAtPathAndComplete", language = "JDOQL",
        value = "SELECT "
            + "FROM todoapp.dom.module.todoitem.ToDoItem "
            + "WHERE atIndex(:atPath) == 0 "
            + "    && complete == :complete"),
    ...
})
public class ToDoItem ... {
    ...
}
```

① name of the query

② defines the `atPath` parameter

③ defines the `complete` parameter

This JDO query definitions are used in the `ToDoItemRepositoryImplUsingJdoql` service:

```
@DomainService(nature = NatureOfService.DOMAIN)
public class ToDoItemRepositoryImplUsingJdoql implements ToDoItemRepositoryImpl {
    @Programmatic
    public List<ToDoItem> findByAtPathAndCategory(final String atPath, final Category
category) {
        return container.allMatches(
            new QueryDefault<>(ToDoItem.class,
                "findByAtPathAndCategory",
                "atPath", atPath,
                "category", category));
    }
    ...
    @javax.inject.Inject
    DomainObjectContainer container;
}
```

① corresponds to the "findByAtPathAndCategory" JDO named query

② provide argument for the `atPath` parameter. The pattern is parameter, argument, parameter, argument, ... and so on.

③ provide argument for the `category` parameter. The pattern is parameter, argument, parameter, argument, ... and so on.

Other JDOQL named queries (not shown) follow the exact same pattern.

With respect to the other query APIs, the varargs parameters are optional, but allow for (client-side and managed) paging. The first parameter is the `start` (0-based, the second is the `count`.



It is also possible to query using DataNucleus' type-safe query API. For more details, see [IsisJdoSupport](#).

12.4.3. Implementation

The core framework provides a default implementation of this service (`o.a.i.core.metamodel.services.repository.RepositoryServiceDefault`).

(Disabling) Auto-flush

Normally any queries are automatically preceded by flushing pending commands to persist or remove objects.

This key allows this behaviour to be disabled.

```

*
* <p>
*   Originally introduced as part of ISIS-1134 (fixing memory leaks in the
objectstore)
*   where it was found that the autoflush behaviour was causing a (now
unrepeatable)
*   data integrity error (see <a href="https://issues.apache.org/jira/browse/ISIS-
1134?focusedCommentId=14500638&page=com.atlassian.jira.plugin.system.issuetabpanels:co-
mment-tabpanel#comment-14500638">ISIS-1134 comment</a>, in the isis-module-security.
*   However, that this could be circumvented by removing the call to flush().
*   We don't want to break existing apps that might rely on this behaviour, on the
*   other hand we want to fix the memory leak. Adding this configuration property
*   seems the most prudent way forward.
* </p>
*/
public static final String KEY_DISABLE_AUTOFLUSH =
"isis.services.container.disableAutoFlush";

```

12.4.4. Registering the Service

Assuming that the [configuration-and-annotation](#) services installer is configured (implicit if using the [AppManifest](#) to [bootstrap the app](#)) then Apache Isis' core implementation of [RepositoryService](#) service is automatically registered and injected (it is annotated with [@DomainService](#)) so no further configuration is required.

To use an alternative implementation, use [@DomainServiceLayout#menuOrder\(\)](#) (as explained in the [introduction](#) to this guide).

12.4.5. Related Services

the [FactoryService](#) is often used in conjunction with the [RepositoryService](#), to instantiate domain objects before persisting.

Chapter 13. Persistence Layer SPI

The persistence layer SPIs influence how the framework persists domain objects, for example controlling how to create an audit log of changes to domain objects.

The table below summarizes the persistence layer SPIs defined by Apache Isis. It also lists their corresponding implementation, either a default implementation provided by Apache Isis itself, or provided by one of the in (non-ASF) [Isis Addons](#) modules.

Table 14. Persistence Layer SPI

SPI	Description	Implementation	Notes
<code>o.a.i.applib.services.audit</code> <code>AuditingService3</code>	Create an audit record for every changed property of every changed object within a transaction.	<code>AuditingService</code> <code>o.ia.m.audit</code> <code>isis-module-audit</code>	
<code>o.a.i.applib.services.publish</code> <code>EventSerializer</code>	(deprecated in 1.13.0-SNAPSHOT) Creates a representation of either an action invocation or a changed object being published through the PublishingService .	<code>RestfulObjects-SpecEventsSerializer</code> <code>o.ia.m.publishing</code> <code>isis-module-publishing</code>	
<code>o.a.i.applib.services.publish</code> <code>PublisherService</code>	(1.13.0-SNAPSHOT) Publish any action invocations/property edits and changed objects, typically for interchange with an external system in a different bounded context.	<code>PublisherServiceLogging</code> also <code>PublisherService-UsingActiveMq</code> <code>o.ia.m.publishmq</code> <code>isis-module-publishmq</code>	
<code>o.a.i.applib.services.publish</code> <code>PublishingService</code>	(deprecated in 1.13.0-SNAPSHOT) Publish any action invocations and changed objects, typically for interchange with an external system in a different bounded context.	<code>PublishingService</code> <code>o.ia.m.publishing</code> <code>isis-module-publishing</code>	

SPI	Description	Implementation	Notes
<code>o.a.i.applib.services.userreg.UserRegistrationService</code>	Create a new user account with the configured security mechanism.	<code>SecurityModule-AppUserRegistrationService</code> <code>o.ia.m.security.isis-module-security</code>	depends (implicitly) on: a configured <code>EmailService</code>

Key:

- `o.a.i` is an abbreviation for `org.apache.isis`
- `o.ia.m` is an abbreviation for `org.isisaddons.module`

Where an implementation is available (on the classpath) then it is always registered automatically (that is, they are all (with one exception) annotated with `@DomainService`.

13.1. AuditingService3

The `AuditingService3` auditing service provides a simple mechanism to capture changes to data. It is called for each property that has changed on any domain object, as a set of pre- and post-values.



In case you are wondering what happened to `AuditingService` and `AuditingService2`, these were earlier versions of the SPI that have since been deprecated and removed.

13.1.1. SPI

The SPI for the service is:

```
public interface AuditingService3 {

    @Programmatic
    public void audit(
        final UUID transactionId, String targetClassName, final Bookmark target,
        String memberIdentifier, final String propertyName,
        final String preValue, final String postValue,
        final String user, final java.sql.Timestamp timestamp);
}
```

The framework will call this for each and every domain object property that is modified within a transaction.

13.1.2. Implementation

The most full-featured available implementation is the (non-ASF) [Isis addons' Audit module](#). This creates an audit records for each changed property (ie every time that `AuditingService3#audit(...)` is called. The implementation is `org.isisaddons.module.audit.dom.AuditingService`.

The module also provides:

- `AuditingServiceMenu` service which provides actions to search for `AuditEntries`, underneath an 'Activity' menu on the secondary menu bar.
- `AuditingServiceRepository` service to search for persisted `AuditEntry`'s`. None of its actions are visible in the user interface (they are all '@Programmatic).
- `AuditingServiceContributions` which contributes collections to the `HasTransactionId` interface. This will therefore display all audit entries that occurred in a given transaction, in other words whenever a command, a published event or another audit entry is displayed.

If you just want to debug (writing to stderr), you can instead configure `o.a.i.applib.services.audit.AuditingService3$Stderr`

13.1.3. Usage

The typical way to indicate that an object should be audited is to annotate it with the `@DomainObject#auditing()` annotation.

13.1.4. Registering the Services

The (non-ASF) [Isis addons' audit](#) module provides an implementation of this service (`AuditingService`), and also provides a number of related domain services (`AuditingServiceMenu`, `AuditingServiceRepository` and `AuditingServiceContributions`).

Assuming that an `AppManifest` is being used to bootstrap the app) then this can be activated by updating the `pom.xml` and updating the `AppManifest#getModules()` method.

If menu items or contributions are not required in the UI, these can be suppressed either using security or by implementing a [vetoing subscriber](#).

13.1.5. Related Services

The auditing service works very well with the `<code>CommandService</code>`. The `CommandService` captures the `_cause` of an interaction (an action was invoked, a property was edited), while the `AuditingService3` captures the `effect` of that interaction in terms of changed state.

You may also want to configure the [PublishingService](#).

All three of these services collaborate implicitly by way of the `HasTransactionId` interface.

13.2. EventSerializer

The `EmailSerializer` service is a supporting service intended for use by (any implementation of) `PublishingService`. Its responsibility is to combine the `EventMetadata` and the `EventPayload` into some serialized form (such as JSON, XML or a string) that can then be published.



This service is deprecated, replaced with `PublisherService (1.13.0-SNAPSHOT)`.

See `PublishingService` for further discussion.

13.2.1. SPI

The SPI defined by this service is:

```
@Deprecated
public interface EventSerializer {
    Object serialize(
        EventMetadata metadata,          ①
        EventPayload payload);          ②
    }                                ③
```

- ① returns an object for maximum flexibility, which is then handed off to the `PublishingService`.
- ② standard metadata about the event, such as the user, the `transactionId`, date/time etc
- ③ for published actions, will generally be an `EventPayloadForActionInvocation` (or subclass thereof); for published objects, will generally be an `EventPayloadForObjectChanged` (or subclass thereof)

It's important to make sure that the publishing service implementation is able to handle the serialized form. Strings are a good lowest common denominator, but in some cases a type-safe equivalent, such as a w3c DOM `Document` or JSON node might be passed instead.

13.2.2. Implementation

The (non-ASF) `Isis addons'` `publishing` module provides an implementation (`org.isisaddons.module.publishing.dom.eventserializer.RestfulObjectsSpecEventSerializer`) that represents the event payload using the representation defined by the `Restful Objects spec` of (transient) objects, grafting on the metadata as additional JSON nodes.

For example, this is the JSON generated on an action invocation:

```

17:10:44,787 [FacetedMethodsBuilder 1209462641@qtp-130672250-0 INFO ] introspecting org.apache.
{
  "metadata" : {
    "guid" : "001edb96-0d93-4879-8b1d-bec7ad4dde9f",
    "user" : "sven",
    "timestamp" : 1360343444475
  },
  "payload" : {
    "title" : "ACTION:dom.todo.ToDoItem#completed()\n      target=TODO:L_0^2:sven:1360343444475\n",
    "members" : [ {
      "id" : "actionName",
      "memberType" : "property",
      "value" : "dom.todo.ToDoItem#completed()",
      "disabledReason" : "Always disabled"
    }, {
      "id" : "result",
      "memberType" : "property",
      "value" : {
        "rel" : "urn:org.restfulobjects:rels/object",
        "href" : "http://localhost:8080/restful/objects/TODO:L_0^2:sven:1360343444475",
        "method" : "GET",
        "type" : "application/json;profile=\"urn:org.restfulobjects:repr-types/domainobject\"",
        "title" : "Buy milk - Completed!"
      },
      "disabledReason" : "Always disabled"
    }, {
      "id" : "target",
      "memberType" : "property",
      "value" : {
        "rel" : "urn:org.restfulobjects:rels/object",
        "href" : "http://localhost:8080/restful/objects/TODO:L_0^2:sven:1360343444475",
        "method" : "GET",
        "type" : "application/json;profile=\"urn:org.restfulobjects:repr-types/domainobject\"",
        "title" : "Buy milk - Completed!"
      },
      "disabledReason" : "Always disabled"
    } ],
    "extensions" : {
      "isService" : false,
      "isPersistent" : false
    }
  }
}
17:11:10.041 [salonlv           1209462641@ato-130672250-0 DEBUG1   org.datanucleus.store.rdb

```

Figure 1. JSON representation of a published action invocation

while this is the object change JSON:

```

17:10:44,557 [FacetedMethodsBuilder 1209462641@qtp-130672250-0 INFO ] introspecting org.apache.
{
  "metadata" : {
    "guid" : "001edb96-0d93-4879-8b1d-bec7ad4dde9f",
    "user" : "sven",
    "timestamp" : 1360343444475
  },
  "payload" : {
    "title" : "CHANGED_OBJECT:dom.todo.ToDoItem@6f5dab79",
    "members" : [ {
      "id" : "changed",
      "memberType" : "property",
      "value" : {
        "rel" : "urn:org.restfulobjects:rels/object",
        "href" : "http://localhost:8080/restful/objects/TODO:L_0^2:sven:1360343444475",
        "method" : "GET",
        "type" : "application/json;profile=\"urn:org.restfulobjects:repr-types/domainobject\"",
        "title" : "Buy milk - Completed!"
      },
      "disabledReason" : "Always disabled"
    }, {
      "id" : "description",
      "memberType" : "property",
      "value" : "Buy milk",
      "disabledReason" : "Always disabled"
    } ],
    "extensions" : {
      "isService" : false,
      "isPersistent" : false
    }
  }
}
17:10:44.787 [FacetedMethodsBuilder 1209462641@qtn-130672250-0 INFO ] introspecting org.apache.

```

Figure 2. JSON representation of a published changed object

You could if you wish change the representation by registering your own implementation of this API in `isis.properties`:

13.2.3. Registering the Services

There is no default implementation of this service provided by the core Apache Isis framework.

The (non-ASF) `Isis addons' publishing` module provides an implementation of this service (`RestfulObjectsSpecEventSerializer`) that serializes action invocations and published objects into a format based on the Restful Objects specification. It also (as you might imagine) provides an implementation of the `PublishingService`.

Assuming that an `AppManifest` is being used to bootstrap the app) then this can be activated by updating the `pom.xml` and updating the `AppManifest#getModules()` method.

13.2.4. Related Services

This service is intended (though not mandated) to be used by implementations of `PublishingService`. The (non-ASF) `Isis addons' publishing` module does use it (though the (non-ASF) `Isis addons' publishmq` module does not).

13.3. PublisherService (1.13.0-SNAPSHOT)

The `PublisherService` API (1.13.0-SNAPSHOT) is intended for coarse-grained publish/subscribe for system-to-system interactions, from Apache Isis to some other system. Events that can be published are action invocations/property edits, and changed objects. A typical use case is to publish onto a pub/sub bus such as [ActiveMQ](#) with [Camel](#) to keep other systems up to date.

An alternative use is for profiling: for each execution (action invocation/property edit) the framework captures metrics of the number of objects loaded or dirtied as the result of that execution. If the `WrapperFactory` is used to call other objects then the metrics are captured for each sub-execution. The framework provides a default implementation, `PublisherServiceLogging`, that will log these execution graphs (in XML form, per the "[ixn](#)" schema) to an SLF4J logger.

Only actions/properties/domain objects annotated for publishing (using `@Action#publishing()`, `@Property#publishing()` or `@DomainObject#publishing()`) are published.

13.3.1. SPI

The SPI defined by the service is:

```
public interface PublisherService {  
    void publish(final Interaction.Execution<?, ?> execution); ①  
    void publish(final PublishedObjects publishedObjects); ②  
}
```

① to publish an individual action invocation or property edit, as captured within an `Interaction.Execution`.

② to publish a set of changed objects.

Each `Interaction.Execution` has an owning `Interaction`; this is the same object obtainable from `InteractionContext`. Implementations that publish member executions can use `Interaction.Execution#getDto()` method to return a DTO (as per the "[ixn](#)" schema) which can be converted into a serializable XML representation using the `InteractionDtoUtils` utility class. The XML can either serialize a single execution, or can be a "deep" serialization of an execution and all sub-executions.

The full API of `PublishedObjects` itself is:

```

public interface PublishedObjects extends HasTransactionId, HasUsername {
    UUID getTransactionId();          ①
    String getUsername();            ②
    Timestamp getCompletedAt();      ③
    ChangesDto getDto();            ④
    int getNumberLoaded();          ⑤
    int getNumberCreated();
    int getNumberUpdated();
    int getNumberDeleted();
    int getNumberPropertiesModified();
}

```

- ① inherited from `HasTransactionId`, correlates back to the unique identifier of the transaction in which these objects were changed.
- ② inherited from `HasUsername`, is the user that initiated the transaction causing these objects to change
- ③ the time that this set of objects was collated (just before the completion of the transaction completes)..
- ④ returns a DTO (as per the "["chg" schema](#)) which can be converted into a serializable XML representation can be obtained using the `ChangesDtoUtils` utility class.
- ⑤ metrics as to the number of objects loaded, created, updated or deleted and the number of object properties modified (in other words the "size" or "weight" of the transaction).

13.3.2. Implementation

The framework allows multiple implementations of this service to be registered; all will be called. The framework provides one implementation of its own, `PublisherServiceLogging` (in `o.a.i.applib.services.publish` package); this logs "deep" serializations to an SLF4J logger.

The (non-ASF) `Isis addons' publishmq` module also provides an implementation (`o.ia.m.publishmq.dom.servicespi.PublishingServiceUsingActiveMq`). This implementation publishes each member execution as an event on an `ActiveMQ` message queue. It also persists each execution as a `PublishedEvent` entity, allowing the event to be republished if necessary. The implementation also provides the ability to log additional `StatusMessage` entities, correlated on the `transactionId`, useful for diagnosing and monitoring the activity of subscribers of said message queues.

13.3.3. Usage

To indicate that an action invocation should be published, annotate it with the `@Action#publishing()` annotation.

To indicate that an property edit should be published, annotate it with the `@Property#publishing()` annotation.

To indicate that a changed object should be published is to annotate it with the `@DomainObject#publishing()` annotation.

13.3.4. Registering the Services

The (non-ASF) Isis addons' `publishmq` module provides an implementation of this service. Assuming that an `AppManifest` is being used to bootstrap the app) then this can be activated by updating the `pom.xml` and updating the `AppManifest#getModules()` method.

The module also provide services that contribute to the UI. If contributions are not required in the UI, these can be suppressed either using security or by implementing a `vetoing subscriber`.

13.3.5. Related Services

This service supports two main use cases:

- coarse-grained publish/subscribe for system-to-system interactions, from Apache Isis to some other system.



The `PublishingService` also supports this use case, but is deprecated: the `PublisherService` is intended as a replacement for `PublishingService`.

- profiling of interactions/transactions, eg to diagnose response/throughput issues.

To support these use cases several other services are involved:

- the `InteractionContext` is used to obtain the `Interaction` from which the member executions are published.
- the (internal) `ChangedObjectsServiceInternal` domain service is used to obtain the set of objects modified throughout the transaction
- the (internal) `PublisherServiceInternal` domain service filters these down to those changed objects that are also published (as per `@DomainObject#publishing()`) and delegates to the `PublisherService`.
- the `MetricsService` is used to obtain the objects that are loaded throughout the transaction; this info is used in order to instantiate the `PublishedObjects` object passed through to the `PublisherService`.

The `EventBusService` differs from the `PublisherService` in that it is intended for fine-grained publish/subscribe for object-to-object interactions within an Apache Isis domain object model. The event propagation is strictly in-memory, and there are no restrictions on the object acting as the event; it need not be serializable, for example. That said, it is possible to obtain a serialization of the action invocation/property edit causing the current event to be raised using `InteractionContext` domain service.

13.4. PublishingService

The `PublishingService` API is intended for coarse-grained publish/subscribe for system-to-system interactions, from Apache Isis to some other system. Here the only events published are those that action invocations and of changed objects. A typical use case is to publish onto a pub/sub bus such as `ActiveMQ` with `Camel` to keep other systems up to date.



This service is deprecated, replaced with [PublisherService \(1.13.0-SNAPSHOT\)](#).

13.4.1. SPI

The SPI defined by the service is:

```
@Deprecated
public interface PublishingService {
    public void publish(
        EventMetadata metadata,          ①
        EventPayload payload);          ②
    void setEventSerializer(EventSerializer eventSerializer); ③
}
```

- ① standard metadata about the event, such as the user, the `transactionId`, date/time etc
- ② for published actions, an `EventPayloadForActionInvocation` (or subclass thereof); for published objects, an `EventPayloadForObjectChanged` (or subclass thereof)
- ③ injects in the `EventSerializer` service. This is deprecated because not every implementation is required to use an `EventSerializer` so its inclusion within the SPI of `PublishingService` was in retrospect a mistake.

Typically implementations will use the injected `EventSerializer` to convert the metadata and payload into a form to be published:

```
public interface EventSerializer {
    public Object serialize(EventMetadata metadata, EventPayload payload);
}
```

The serialized form returned by `EventSerializer` must be in a form that the `PublishingService` implementation is able to handle. Strings are a good lowest common denominator, but (if custom implementations of both `EventSerializer` and `PublishingService` were in use) then it might also be some other type, for example an `org.w3c.dom.Document` or an `org.json.JSONObject` might be returned instead.

13.4.2. Implementation

The (non-ASF) `Isis addons' publishing` module provides an implementation (`org.isisaddons.module.publishing.dom.PublishingService`) that persists each event as a `PublishedEvent` entity. This holds the serialized form of the event metadata and payload as translated into a string by the injected `EventSerializer`. The module also provides its own implementation of `EventSerializer`, namely `RestfulObjectsSpecEventSerializer`, which represents the event payload using the representation defined by the `Restful Objects spec` of (transient) objects, grafting on the metadata as additional JSON nodes.

The `PublishedEvent` entity also has a `state` field taking the values either "QUEUED" or "PROCESSED". The intention here is that an event bus can poll this table to grab pending events and dispatch them

to downstream systems. When `PublishedEvents` are persisted initially they always take the value "QUEUED".

The framework provides no default implementations of this service.

13.4.3. Usage

To indicate that an action invocation should be published, annotate it with the `@Action#publishing()` annotation.

To indicate that a changed object should be published is to annotate it with the `@DomainObject#publishing()` annotation.

It is also possible to "fine-tune" the `EventPayload` using the `#publishingFactory()` attribute (for both annotations). By default the `EventPayload` that is serialized identifies the object(s) being interacted with or changed, and in the case of the action invocation provides details of the action arguments and result (if any) of that action. However, the payload does not (by default) include any information about the new state of these objects. It is therefore the responsibility of the subscriber to call back to Apache Isis to determine any information that has not been published.



The replacement `PublisherService` does *not* support the concept of "payload factories" (but is otherwise more flexible).

Although the representations (if using the Restful Object serializer and Restful Objects viewer) does include hrefs for the objects, this nevertheless requires an additional network call to obtain this information).

In some circumstances, then, it may make more sense to eagerly "push" information about the change to the subscriber by including that state within the payload.

To accomplish this, an implementation of a "PayloadFactory" must be specified in the annotation.

For actions, we implement the `PublishingPayloadFactoryForAction` (in `o.a.i.applib.annotation`):

```
@Deprecated
public interface PublishingPayloadFactoryForAction {
    public EventPayload payloadFor(
        Identifier actionIdentifier,
        Object target,
        List<Object> arguments,
        Object result);
}
```

The `EventPayloadForActionInvocation` abstract class (in the Isis applib) should be used as the base class for the object instance returned from `payLoadFor(…)`.

For objects, the interface to implement is `PublishingPayloadFactoryForObject`:

```

@Deprecated
public interface PublishingPayloadFactoryForObject {
    public EventPayload payloadFor(
        Object changedObject,
        PublishingChangeKind publishingChangeKind); ①
}

```

① an enum taking the values `CREATE`, `UPDATE`, `DELETE`

Similarly, the `EventPayloadForObjectChanged` abstract class should be used as the base class for the object returned from `payloadFor(...)`.

For example, the following will eagerly include a `ToDoItem`'s `'description'` property whenever it is changed:

```

@DomainObject(publishingPayloadFactory=ToDoItemPayloadFactory.class)
public class ToDoItem {
    ...
}

```

where `ToDoItemPayloadFactory` is defined as:

```

public class ToDoItemChangedPayloadFactory implements
PublishingPayloadFactoryForObject {
    public static class ToDoItemPayload
        extends EventPayloadForObjectChanged<ToDoItem> {
            public ToDoItemPayload(ToDoItem changed) { super(changed); }
            public String getDescription() { return getChanged().getDescription(); }
        }
    @Override
    public EventPayload payloadFor(Object changedObject, PublishingChangeKind kind) {
        return new ToDoItemPayload((ToDoItem) changedObject);
    }
}

```

13.4.4. Registering the Services

There is no default implementation of this service provided by the core Apache Isis framework.

The (non-ASF) Isis addons' `publishing` module provides an implementation of this service. Assuming that an `AppManifest` is being used to bootstrap the app) then this can be activated by updating the `pom.xml` and updating the `AppManifest#getModules()` method.

The module also provides services that contribute to the UI. If contributions are not required in the UI, these can be suppressed either using security or by implementing a `vetoing subscriber`.

13.4.5. Related Services

The `PublishingService` is intended for coarse-grained publish/subscribe for system-to-system interactions, from Apache Isis to some other system. Here the only events published are those that action invocations (for actions annotated with `@Action#publishing()`) and of changed objects (for objects annotated with `@DomainObject#publishing()`).


The `PublisherService` is intended as a replacement for this service. The use case for `PublisherService` is the same: coarse-grained publishing of events for system-to-system interactions. It is in most respects more flexible though: events are published both for action invocations (annotated with `@Action#publishing()`) and also for property edits (annotated with `@Property#publishing()`). It also publishes changed objects (for objects annotated with `@DomainObject#publishing()`). However, rather than publishing one event for every changed objects, it publishes a single event that identifies all objects created, updated or deleted.

Another significant difference between `PublishingService` and `PublisherService` is in the content of the events themselves. While the former uses the `MementoService` to create an ad-hoc serialization of the action being invoked, the latter uses the `DTOs/XML schemas` as a formal specification of the nature of the interaction (action invocation, property edit or changed objects).

The `EventBusService` meanwhile differs from both `PublishingService` and `PublisherService` in that it is intended for fine-grained publish/subscribe for object-to-object interactions within an Apache Isis domain object model. The event propagation is strictly in-memory, and there are no restrictions on the object acting as the event; it need not be serializable, for example. (That said, it is possible to obtain a serialization of the action invocation/property edit causing the current event to be raised using `InteractionContext` domain service).

13.4.6. Design Notes

The following class diagram shows how the above components fit together:



This yuml.me diagram was generated at yuml.me.

13.5. UserRegistrationService

The `UserRegistrationService` provides the ability for users to sign-up to access an application by providing a valid email address, and also provides the capability for users to reset their password if forgotten.

For user sign-up, the `Wicket viewer` will check whether an implementation of this service (and also the `<code>EmailNotificationService</code>`) is available, and if so will render a sign-up page where the user enters their email address. A verification email is sent (using the aforementioned `<code>EmailNotificationService</code>`) which includes a link back to the running application; this allows the user then to complete their registration process (choose user name, password and so on). When the user has provided the additional details, the Wicket viewer calls `_this` service in order to create an account for them, and then logs the user on.

For the password reset feature, the Wicket viewer will render a password reset page, and use the `EmailNotificationService` to send a "password forgotten" email. This service provides the ability to reset a password based on the user's email address.

It is of course possible for domain objects to use this service; it will be injected into domain object or other domain services in the usual way. That said, we expect that such use cases will be comparatively rare; the primary use case is for the Wicket viewer's sign-up page.



For further details on the user registration feature (as supported by the Wicket viewer), see [here](#).

13.5.1. SPI

The SPI defined by the service is:

```
public interface UserRegistrationService {  
    @Programmatic  
    boolean usernameExists(String username); ①  
    @Programmatic  
    boolean emailExists(String emailAddress); ②  
    @Programmatic  
    void registerUser(String username, String password, String emailAddress); ③  
    @Programmatic  
    boolean updatePasswordByEmail(String emailAddress, String password); ④  
}
```

- ① checks if there is already a user with the specified username
- ② checks if there is already a user with the specified email address
- ③ creates the user, with specified password and email address. The username and email address must both be unique (not being used by an existing user)
- ④ allows the user to reset their password

13.5.2. Implementation

The core Apache Isis framework itself defines only an API; there is no default implementation. Rather, the implementation will depend on the security mechanism being used.

That said, if you have configured your app to use the [Isis addons security module](#), then note that the security module does provide an abstract implementation ([SecurityModuleAppUserRegistrationServiceAbstract](#)) of the [UserRegistrationService](#). You will need to extend that service and provide implementation for the two abstract methods: [getInitialRole\(\)](#) and [getAdditionalInitialRoles\(\)](#).

This is needed so that the self-registered users are assigned automatically to your application role(s) and be able to use the application. Without any role such user will be able only to see/use the logout link of the application.

13.5.3. Registering the Services

There is no default implementation of this service provided by the core Apache Isis framework.

If using the (non-ASF) [Isis addons' security](#) module for authentication and authorization, then note that it provides an adapter class, [SecurityModuleAppUserRegistrationServiceAbstract](#), that provides most of the implementation. You are still required to implement a subclass and register.

For example:

```
@DomainService(nature=NatureOfService.DOMAIN)
public class AppUserRegistrationService extends
SecurityModuleAppUserRegistrationServiceAbstract {
    protected ApplicationRole getInitialRole() {
        return findRole("regular-user");
    }
    protected Set<ApplicationRole> getAdditionalInitialRoles() {
        return Collections.singleton(findRole("self-registered-user"));
    }
    private ApplicationRole findRole(final String roleName) {
        return applicationRoles.findRoleByName(roleName);
    }
    @Inject
    private ApplicationRoles applicationRoles;
}
```

13.5.4. Related Services

The most common use case is to allow users to sign-up through Apache Isis' Wicket viewer. Because the process requires email to be sent, the following services must be configured:

- [EmailService](#)
- [EmailNotificationService](#)
- [UserRegistrationService](#) (this service)

The [EmailService](#) in particular requires additional [configuration properties](#) to specify the external SMTP service.

Chapter 14. Persistence Layer internal SPI

These domain services are internal to the framework, controlling various aspects of the persistence layer.



We do not guarantee that [semantic versioning](#) will be honoured for these SPIs.

The table below summarizes the persistence layer internal SPIs defined by Apache Isis. It also lists their corresponding implementation, either a default implementation provided by Apache Isis itself, or provided by one of the (non-ASF) [Isis Addons](#) modules.

Table 15. "Internal" SPI Services

SPI	Maven Module Impl'n (g: a:)	Implementation	Notes
<code>o.a.i.c.r.auditing.AuditingServiceInternal</code>	(1.13.0-SNAPSHOT) Co-ordinates between <code>ChangedObjectsServiceInternal</code> and <code>AuditingService</code> .	concrete class.	
<code>o.a.i.c.r.changes.ChangedObjectsServiceInternal</code>	(1.13.0-SNAPSHOT) Request-scoped service holding objects enlisted into current transaction.	concrete class.	
<code>o.a.i.c.m.s.publishing.PublishingServiceInternal</code>	(1.13.0-SNAPSHOT) Co-ordinates between <code>ChangedObjectsServiceInternal</code> and <code>MetricsService</code> and the SPI services, <code>PublisherService</code> and (deprecated) <code>PublishingService</code> .	<code>PublishingServiceInternalDefault</code> <code>o.a.i.c.r.publishing</code> <code>isis-core-runtime</code>	

Key:

- `o.a.i.c.m.s` is an abbreviation for `org.apache.isis.core.metamodel.services`
- `o.a.i.c.r.s` is an abbreviation for `org.apache.isis.core.runtime.services`

14.1. `AuditingServiceInternal` (1.13.0-SNAPSHOT)



TODO

14.2. `ChangedObjectsServiceInternal` (1.13.0-SNAPSHOT)



TODO

14.3. PublishingServiceInternal (1.13.0-SNAPSHOT)



TODO

Chapter 15. Bootstrapping SPI

Bootstrapping SPIs influence how the framework locates the components that make up the running application.

The table below summarizes the bootstrapping SPI defined by Apache Isis. It also lists their corresponding implementation, either a default implementation provided by Apache Isis itself, or provided by one of the in (non-ASF) [Isis Addons](#) modules.

Table 16. Bootstrapping SPI

SPI	Description	Implementation	Notes
<code>o.a.i.applib.services.classDiscovery</code> <code>ClassDiscoveryService</code>	Mechanism to locate (from the classpath) classes with a specific annotation (eg <code>@DomainService</code>) Subtypes of a given type (eg <code>FixtureScript</code>).	<code>ClassDiscoveryService</code> <code>UsingReflections</code> <code>o.a.i.core.isis-core-applib</code>	requires <code>org.reflections:reflections</code> as Maven dependency

15.1. ClassDiscoveryService

The `ClassDiscovery` service is used to automatically discover subclasses of any given type on the classpath. The primary use case is to support "convention-over-configuration" designs that work with a minimum of configuration.

This service is used by the `FixtureScripts` service to automatically locate any `FixtureScript` implementations.

15.1.1. SPI

The SPI defined by the service is:

```
public interface ClassDiscoveryService2 {  
    @Programmatic  
    <T> Set<Class<? extends T>> findSubTypesOfClasses(Class<T> type, String  
packagePrefix);  
    @Deprecated  
    @Programmatic  
    <T> Set<Class<? extends T>> findSubTypesOfClasses(Class<T> type);      ①  
}
```

① no longer used

15.1.2. Implementation

Isis provides an implementation of this service, namely



This implementation is also used to discover domain services annotated with `@DomainService`. Currently this logic uses the implementation directly, so is not pluggable. However, the entire `ServicesInstaller`

15.1.3. Usage

The usage will vary depending upon the conventions of the design. As of 1.9.0, the usage of the service has been centralized such that the packages to be scanned are located from the `AppManifest`'s `#getModules()` method.

For example, the `SimpleApp archetype`'s app manifest includes:

```
public class DomainAppAppManifest implements AppManifest {  
    @Override  
    public List<Class<?>> getModules() {  
        return Arrays.asList(  
            DomainAppDomainModule.class, // domain (entities and repositories)  
            DomainAppFixtureModule.class, // fixtures  
            DomainApp AppModule.class // home page service etc  
        );  
    }  
    ...  
}
```

where the three module classes in effect define three different package prefixes to search under (for domain services, fixture scripts and persistent entities).

Other usages of the `ClassDiscoveryService` are likely to work in a similar way, requiring some sort of scope to be specified.

15.1.4. Registering the Services

Assuming that the `configuration-and-annotation` services installer is configured (implicit if using the `AppManifest` to bootstrap the app) then Apache Isis' core implementation of `ClassDiscoveryService2` service is automatically registered and injected (it is annotated with `@DomainService`) so no further configuration is required.

To use an alternative implementation, use `@DomainServiceLayout#menuOrder()` (as explained in the [introduction](#) to this guide).