Appendix D - Example UNIX shell script

Script is owned by the user tomcat runs as and uses setuid so that the script can be run by someone other than root. An alternative would be for the script to be run as root.

```
-r-sr-x---   1 tomcatd  staff         573 Nov 15 06:59 check_tomcat.sh
```

Here are the crontab entries for running this script every 10 minutes:

```
# Check Tomcat every 10 minutes for load problems
0,10,20,30,40,50 * * * * $HOME/check_tomcat.sh
```

Here is the script:

```
#!/bin/sh

# Script for detecting major tomcat problems

# Get the current date
date=`/usr/bin/date "+%Y-%m-%d"`
# Format the name of todays catalina connector log file
logfile="/usr/local/tomcat4/logs/catalina_log.$date.txt"

# If the log file doesn't exist we have nothing to check
if [ ! -r $logfile ]; then
  exit
fi

# Check the last 50 lines in the log for a line indicating that a new
# Tomcat Processor was started
num=`/usr/local/bin/tail -50 $logfile | \
  /usr/local/bin/egrep "Starting background thread" | \
  /usr/local/bin/wc -l`

if [ $num -ge 5 ]; then
  # Signal the JVM to do a Thread Stacktrace Dump
  /usr/bin/pkill -QUIT java
  # Send email to administrator that Tomcat is having problems
  /usr/bin/mailx -r admin\@your.host -s "Tomcat load problems" admin\@your.host
fi
```