

# Access Controllers

by Andreas Hartmann

## Table of contents

|  |   |
|--|---|
| 1 Introduction.....                                  | 2 |
| 2 Defining the Role in lenya.roles.....              | 2 |
| 3 Declaring an AccessController in cocoon.xconf..... | 2 |
| 4 Default Access Controller.....                     | 2 |
| 5 Bypassable Access Controller.....                  | 2 |

## 1. Introduction

An *AccessController* has the responsibility to authenticate clients and to authorize requests.

## 2. Defining the Role in lenya.roles

```
<role name="org.apache.lenya.ac.AccessController"
  shorthand="access-controller"
  default-class="org.apache.lenya.ac.impl.BypassableAccessController"/>
```

## 3. Declaring an AccessController in cocoon.xconf

Each *AccessController* component needs a type that is attached to the `role` attribute, separated with a slash (/). This allows you to choose an *AccessController* in your publication in combination with the Publication [AccessControllerResolver](#) (`accesscontrollerresolvers.html`) . The following example shows the declaration of an *AccessController* with the type *bypassable*:

```
<component logger="lenya.ac.accesscontroller.bypassable"
  class="org.apache.lenya.ac.impl.BypassableAccessController"
  role="org.apache.lenya.ac.AccessController/bypassable">
  ...
</component>
```

## 4. Default Access Controller

The *DefaultAccessController* combines an [Authenticator](#) (`authenticators.html`) , a set of [Authorizers](#) (`authorizers.html`) , an [AccreditableManager](#) (`accreditablemanagers.html`) and a [PolicyManager](#) (`policymanagers.html`) to perform these tasks.

```
<component logger="lenya.ac.accesscontroller.default"
  class="org.apache.lenya.ac.impl.DefaultAccessController"
  role="org.apache.lenya.ac.AccessController/default"/>
```

## 5. Bypassable Access Controller

The *BypassableAccessController* is a *DefaultAccessController* that can be bypassed for certain URL patterns. For URLs that match those patterns (regular expressions), access is granted for free.

The *BypassableAccessController* allows the definition of a regular expression for the public URL patterns:

```
<component logger="lenya.ac.accesscontroller.bypassable"
  class="org.apache.lenya.ac.impl.BypassableAccessController"
  role="org.apache.lenya.ac.AccessController/bypassable">
  <public>.*[.]css|.*[.]jpg|.*[.]gif</public>
</component>
```