

Policies and Policy Managers

by Andreas Hartmann

1. Policies

A Policy assigns Roles to Accreditables.

There is a common policy definition XML schema which is handled by the PolicyBuilder. It can be used together with the FilePolicyManager and the SitemapPolicyManager.

Here is an example of a policy definition:

```
<policy xmlns="http://apache.org/cocoon/lenya/ac/1.0">

  <user id="lenya">
    <role id="editor"/>
    <role id="reviewer"/>
  </group>

  <group id="reviewer">
    <role id="reviewer"/>
  </group>

  <ip-range id="localhost">
    <role id="editor"/>
  </ip-range>

  <world>
    <role id="visitor"/>
  </world>

</policy>
```

2. Policy Managers

A *PolicyManager* is used to resolve the policy for a certain URL. Lenya ships with the following *PolicyManagers*:

3. Inheriting Policy Manager

This is an abstract base class. It merges the policies of all steps in the URL. For each URL, a *url policy* and a *subtree policy* can be defined. The *InheritingPolicyManager* adds the credentials of

- the subtree policies for all parent directories of the requested page,
- the subtree policy of the requested page, and
- the url policy of the requested page.

For instance, if the URL is `/lenya/news/index.html`, the following policies are merged:

- subtree policy of `/`
- subtree policy of `/lenya`
- subtree policy of `/lenya/news`
- subtree policy of `/lenya/news/index.html`
- url policy of `/lenya/news/index.html`

4. File Policy Manager

The *FilePolicyManager* is an *InheritingPolicyManager*. The policies are defined by policy files that are arranged as a directory tree that reflects the URI space, e.g.:

```
/subtree-policy.acml
/lenya/subtree-policy.acml
/lenya/news/index.html/subtree-policy.acml
/lenya/news/index.html/url-policy.acml
```

If a certain policy file does not exist (like /lenya/news in the above example), an empty policy is used instead.

The *FilePolicyManager* needs a directory parameter which contains a URL pointing to the policies directory:

```
<policy-manager type="file">
  <parameter name="directory"
    value="context:///lenya/pubs/mypub/config/ac/policies"/>
</policy-manager>
```

5. Document Policy Manager Wrapper

This *InheritingPolicyManager* subclass is used together with another *InheritingPolicyManager*. It is able to apply a single policy to all versions of a document (languages, print version, ...). E. g., if you define

- /foo/bar/subtree-policy.xml

and you use the *DefaultDocumentBuilder*, this policy is applied to the URLs

- /foo/bar.html
- /foo/bar_de.html
- /foo/bar_en.print.html
- ...

To configure the *DefaultDocumentBuilder*, just put the declaration of the wrapped *PolicyManager* inside the *DefaultDocumentBuilder* declaration:

```
<policy-manager type="document">
  <policy-manager type="file">
    <parameter name="directory"
      value="context:///lenya/pubs/mypub/config/ac/policies"/>
  </policy-manager>
</policy-manager>
```

6. Sitemap Policy Manager

The *SitemapPolicyManager* uses the policy sitemap to resolve the policy for a certain URL. For this purpose it sends a request of the form

```
cocoon://{publication-id}/policies{url}.acml
```

Example:
cocoon://mypub/policies/authoring/foo/bar_de.html.acml

which is processed by global-sitemap.xmap and forwarded to lenya/pubs/{publication-id}/policies-sitemap.xmap. The request is supposed to return a valid policy XML document.

The configuration of the *SitemapPolicyManager* is very simple:

```
<policy-manager type="sitemap"/>
```