Lucene

0.1Documentation

by Michael Wechner

1. Generic Search

URL:

/lenya/\$PUB_ID/search-\$AREA/lucene

Indices and Excerpts:

src/webapp/lenya/pubs/\$PUB_ID/work/search/index/\$AREA/index
src/webapp/lenya/pubs/\$PUB_ID/work/search/htdocs_dump/\$AREA

Configuration:

src/webapp/global-sitemap.xmap

2. Customizing/Overwriting Generic Search Interface

XSLT:

src/webapp/lenya/pubs/\$PUB_ID/lenya/xslt/search/search-and-results.xsl

URL:

/lenya/\$PUB_ID/search-\$AREA/lucene

3. Crawling a website

Crawl a website by running

ant -f src/webapp/lenya/bin/crawl_and_index.xml crawl -Dcrawler.xconf=/home/username/src/cocoon-lenya/

whereas the crawler.xconf has the following elements

```
<uri-list src="work/search/lucene/uris.txt"/>
  <htdocs-dump-dir src="work/search/lucene/htdocs_dump/cocoon.apache.org"/>
  <!-- <robots src="robots.txt" domain="cocoon.apache.org"/> -->
  </crawler>
```

where the element robots is optional.

In case you don't have access to the server and want to disallow certain URLs from being crawled, then you can also define a "robots.txt" on the crawler side, e.g.

```
# cocoon.apache.org
User-agent: *
Disallow: /there_seems_to_be_a_bug_within_websphinx_Robot_Exclusion.html
#Disallow:
User-agent: lenya
Disallow: /do/not/crawl/this/page.html
```

4. Creating an index from the command line

ant -f src/webapp/lenya/bin/crawl_and_index.xml -Dlucene.xconf=/home/username/src/cocoon-lenya/src/web

whereas the lucene.xconf has the following elements

```
<lucene>
 <update-index type="new"/>
 <update-index type="incremental"/>
 <index-dir src="../../work/search/lucene/index/index"/>
   <htdocs-dump-dir src="../../work/search/lucene/htdocs_dump"/>
   <indexer class="org.apache.lenya.lucene.index.DefaultIndexer"/>
<!--
   <indexer class="org.apache.lenya.lucene.index.ConfigurableIndexer">
     <configuration src="cmfs-luceneDoc.xconf"/>
     <extensions src="xml"/>
   </indexer>
-->
<!--
   <indexer class="org.apache.lenya.lucene.index.ConfigurableIndexer">
     <configuration src="cmfs-luceneDoc.xconf"/>
      <filter class="foo.bar.FileFilter"/>
   </indexer>
</lucene>
```

5. Extract text from a PDF document

ant -f src/webapp/lenya/bin/crawl_and_index.xml -Dhtdocs.dump.dir=/home/username/src/cocoon-lenya/src/

Also see the targets pdfbox and pdfadobe.