

Usecases

Version 0.2

by Christian Egli, Felix Maeder, Andreas Hartmann

Description of the usecase concept and the existing usecases.

1. Introduction

Usecases are sequences of pages that are orthogonal to the website, i.e. they can be executed without leaving the current URI. They are mainly used to execute CMS functions, e.g., to publish a page. Usecases are specified by

- a **name** and
- a set of **steps**.

A usecase is executed using the request parameters `lenya.usecase` and `lenya.step`.

2. Matching Usecases

To match a usecase in a sitemap, the `WildcardRequestParameterMatcher` is used on the `lenya.usecase` and `lenya.step` request parameters. The predefined matchers have the types `usecase` and `step`. A simple example of a usecase pipeline would be:

```
<map:match type="usecase" pattern="publish">

  <!-- confirmation screen -->
  <map:match type="step" pattern="showscreen">
    <map:generate type="serverpages"
      src="content/publishing/publish-screen-usecase.xsp"/>
    <map:transform src="xslt/publishing/screen.xsl"/>
    <map:serialize/>
  </map:match>

  <!-- call publish task -->
  <map:match type="step" pattern="publish">
    <map:act type="task">
      <map:parameter name="publication-id" value="{.../.../1}"/>
    </map:act>
  </map:match>
</map:match>
```

```

    <map:parameter name="task-id" value="{request-param:task-id}"/>
    <map:redirect-to uri="{request:requestURI}" session="true"/>
  </map:act>
</map:match>

</map:match>

```

3. The Usecase Sitemap

The main usecase sitemap supports a set of generic usecases. It is located at `lenya/usecase.xmap`. To implement your publication-specific usecases or to override a generic usecase, just add a `usecase.xmap` sitemap to your publication directory. The Lenya usecase sitemap looks for it and mounts it before the generic usecases are matched.

4. Overview of use cases

The following use cases are known:

Use case	lenya.usecase=	lenya.step=	Comment
Add Child	add-child	showscreen	Confirm to add a child document to the current node in the site tree.
		add-child	
Add Sibling	add-sibling	showscreen	Confirm to add a sibling document to the current node in the site tree.
Reject Approval	approval-reject	showscreen	Confirm to reject a document from approval.
		approval-reject	
Submit for Approval	approval-submit	showscreen	Confirm to submit a document to approval.
		approval-submit	
Archive	archive	showscreen	Confirm to archive a document.
		archive	
		add-sibling	

Usecases

Checkin	checkin	showscreen	Confirm the checkin of this document
		checkin	
Checkout	checkout	showscreen	Confirm the checkout of this document
		checkout	
Copy	copy	showscreen	Confirm to copy a document. (The document is held in a clipboard until it is pasted again)
		copy	
Create	create	showscreen	Show a form allowing to specify the parameters for creation of a document
		create	Create the document
Cut	cut	showscreen	Confirm to cut a document. (The document is held in a clipboard until it is pasted again)
		cut	
Deactivate	deactivate	showscreen	Confirm to deactivate a document.
		deactivate	
Delete	delete	showscreen	Confirm to delete a document.
		delete	
Logout	logout	showscreen	Confirm the logout
Move Down	move-down	showscreen	Confirm to move a document downwards in the site tree.
		move-down	

Move Up	move-up	showscreen	Confirm to move a document upwards in the site tree.
		move-up	
Paste	paste	showscreen	Confirm to paste a document. (The document which is held in a clipboard until is pasted)
		paste	
Publish	publish	showscreen	Confirm the publication of this document
		publish	Publish this document
Asset upload	aset	showscreen	Show a form allowing to specify the parameters for uploading of an asset
		upload	Upload the asset
		insert	Insert an already uploaded asset
		upload-and-insert	Upload and insert an asset
		remove	Remove a previously uploaded asset
Rename	rename	showscreen	Confirm to rename a document.
		rename	
Rollback	rollback	showscreen	Show a list of all versions of this document
		view	View a particular version of this document
		rollback	Roll back to a particular version of

Usecases

			this document
Schedule	schedule	showscreen	Show a list of all task scheduled for this document
		add	Add a new task
		modify	Modify an existing task
		delete	Delete an existing task
Edit			
User Admin	user-admin	showscreen	Show an overview page listing all users
	user-add	showscreen	Show a form for adding users
		add	Add a user
	user-modify	showscreen	Show a form for modifying users
		modify	Modify a user
	user-delete	showscreen	Confirm the deletion of a user
		delete	Delete a user
View Logs	view-logs	overview	Show the logfile list for this publication
		log	Show a single logfile

FIXME (ce):

Can the authenticate process done in a similar way?

5. Use cases

5.1. Resource upload

lenya.usecase=upload

lenya.step=	additional parameters	sample value
-------------	-----------------------	--------------

showscreen	xpath	/NewsML/body.content/block[1]/*[1]
	insertBefore [optional]	true
upload	documentid	
	xpath	
	insertBefore [optional]	
	uploadFile	
	identifier [optional]	
	All Dublin core identifiers are also accepted	

5.2. Create

lenya.usecase=create

lenya.step=	additional parameters	sample value
showscreen	parentid	/dossiers/2003
	doctype	Dossier
create	parentid	
	childid	
	doctype	

5.3. Rollback

lenya.usecase=rollback

lenya.step=	additional parameters	sample value
showscreen		
view	version	

5.4. View Logs

lenya.usecase=view-logs

lenya.step=	additional parameters	sample value
overview		

Usecases

log	logfile	2003-05-13-18-34-00-314.xml
-----	---------	-----------------------------

FIXME (ce):

Add remaining use cases

© 200 wyona.org