

# Application Configuration

This file is located in **WEB-INF** for a war and **META-INF** for an ear.

## @Asynchronous configuration

Default pool size for **@Asynchronous** is 5. It can be very small for some applications highly relying on asynchronism or reactive patterns. Therefore it is possible to customize it adding these entries in **application.properties**:

Name	Default	Description
AsynchronousPool.Size	5	Core size of the pool
AsynchronousPool.CorePoolSize	5	Core size of the pool (inherit its default from .Size alias)
AsynchronousPool.MaximumPoolSize	5	Maximum size of the pool
AsynchronousPool.QueueSize	5	Maximum size of the pool
AsynchronousPool.KeepAliveTime	1 minute	Thread keep alive duration
AsynchronousPool.AllowCoreThreadTimeout	true	Should thread timeout
AsynchronousPool.QueueType	LINKED (or SYNCHRONOUS if size == 0)	The type of queue of the pool in ARRAY, LINKED, PRIORITY or SYNCHRONOUS (same behavior as java implementations of the same name)
AsynchronousPool.ShutdownWaitDuration	1 minute	How many time to wait for the pool to shutdown when undeploying the application
AsynchronousPool.RejectedExecutionHandlerClass	-	A fully qualified name of a <b>java.util.concurrent.RejectedExecutionHandler</b>

## TimerService and @Scheduled

**timerStore.class** allows to switch from the in memory (**org.apache.openejb.core.timer.MemoryTimerStore**) timer storage for quartz tasks to a custom implementation (using a database or anything for instance). Constructor can take a **TransactionManager** or nothing.

All quartz properties prefixed with **org.apache.openejb.quartz.** (instead of **org.quartz.**) are passthrough to quartz.

## CDI

The boolean **openejb.cdi.skip-resource-validation** allows to not validate resources ie **@EJB** and **@Resource** usages in CDI beans.

All properties understood by OpenWebBeans will also be passthrough to OpenWebBeans from this location, see [OWB config](#) for more details.

## @WebServiceRef

Name	Description
cxf.jaxws.client.wsFeatures	Allows to set WSFeature on the client injection. Values is a list (comma separated) of resource id in resources.xml or fully qualified names.

## @Stateless

Name	Description
AccessTimeout or Timeout	container timeout
CloseTimeout	container timeout
BackgroundStartup	Don't create instances in parallel if minimum count is > 0, default to false

## resources.xml

`resources.xml` is a `tomee.xml` using application classloader.

As `tomee.xml` it supports filtering so you can use environment variables and system properties, for instance to use a MySQL database on OpenShift you can do:

```
<?xml version="1.0" encoding="UTF-8"?>
<resources>
  <Resource id="MySQL" aliases="myAppDataSourceName" type="DataSource">
    JdbcDriver = com.mysql.jdbc.Driver
    JdbcUrl =
jdbc:mysql://${OPENSIFT_MYSQL_DB_HOST}:${OPENSIFT_MYSQL_DB_PORT}/rmannibucau?tcpKeep
Alive=true
    UserName = ${OPENSIFT_MYSQL_DB_USERNAME}
    Password = ${OPENSIFT_MYSQL_DB_PASSWORD}
    ValidationQuery = SELECT 1
    ValidationInterval = 30000
    NumTestsPerEvictionRun = 5
    TimeBetweenEvictionRuns = 30 seconds
    TestWhileIdle = true
    MaxActive = 200
  </Resource>
</resources>
```

`resources.xml` supports `Resource`, `Service` and `Container`.

## resources.xml mechanism

resources.xml resources are still available globally like any tomee.xml resource.

The actual resource is bound in an application subtree called with the application name and a resource facade is bound in the global naming tree to be able to route the requests depending the application.

Typically if your application is named myapp and your resource id is myresource then instead of being registered as myresource, it will get registered as myapp/myresource.

If you get any ambiguity in resource name matching try to fully qualified your resource prefixing it with the application name.