

# Trafodion Messages Guide

Version 1.3.0, January 2016

# Table of Contents

1. About This Document .....	2
1.1. Intended Audience .....	2
1.2. New and Changed Information .....	2
1.3. Notation Conventions .....	2
1.4. Publishing History .....	5
1.5. Comments Encouraged .....	5
2. Introduction .....	6
2.1. Message Handling .....	6
2.2. Viewing Trafodion Database Messages .....	6
2.3. SQLSTATE and SQLCODE .....	7
2.4. Getting Help .....	8
3. Data Definition Language (DDL) Messages (1000 through 1999) .....	9
3.1. SQL 1002 .....	9
3.2. SQL 1003 .....	9
3.3. SQL 1004 .....	10
3.4. SQL 1005 .....	10
3.5. SQL 1006 .....	11
3.6. SQL 1008 .....	11
3.7. SQL 1009 .....	12
3.8. SQL 1010 .....	12
3.9. SQL 1012 .....	13
3.10. SQL 1013 .....	13
3.11. SQL 1014 .....	14
3.12. SQL 1015 .....	14
3.13. SQL 1016 .....	15
3.14. SQL 1017 .....	15
3.15. SQL 1020 .....	16
3.16. SQL 1021 .....	16
3.17. SQL 1022 .....	17
3.18. SQL 1023 .....	17
3.19. SQL 1024 .....	18
3.20. SQL 1025 .....	18
3.21. SQL 1026 .....	19
3.22. SQL 1027 .....	19
3.23. SQL 1028 .....	20
3.24. SQL 1029 .....	20
3.25. SQL 1030 .....	21
3.26. SQL 1031 .....	21
3.27. SQL 1035 .....	22
3.28. SQL 1036 .....	22
3.29. SQL 1037 .....	23

3.30. SQL 1038	23
3.31. SQL 1039	24
3.32. SQL 1040	24
3.33. SQL 1041	25
3.34. SQL 1042	25
3.35. SQL 1043	26
3.36. SQL 1044	26
3.37. SQL 1045	27
3.38. SQL 1046	27
3.39. SQL 1047	28
3.40. SQL 1048	28
3.41. SQL 1049	29
3.42. SQL 1050	29
3.43. SQL 1051	30
3.44. SQL 1053	30
3.45. SQL 1057	31
3.46. SQL 1058	31
3.47. SQL 1059	32
3.48. SQL 1061	32
3.49. SQL 1062	33
3.50. SQL 1063	33
3.51. SQL 1064	34
3.52. SQL 1065	34
3.53. SQL 1066	35
3.54. SQL 1069	35
3.55. SQL 1070	36
3.56. SQL 1071	36
3.57. SQL 1072	37
3.58. SQL 1073	37
3.59. SQL 1075	38
3.60. SQL 1078	38
3.61. SQL 1079	39
3.62. SQL 1080	39
3.63. SQL 1081	40
3.64. SQL 1082	40
3.65. SQL 1083	41
3.66. SQL 1084	41
3.67. SQL 1085	42
3.68. SQL 1086	42
3.69. SQL 1087	43
3.70. SQL 1088	43
3.71. SQL 1089	44
3.72. SQL 1090	44
3.73. SQL 1094	45

3.74. SQL 1095	45
3.75. SQL 1098	46
3.76. SQL 1099	46
3.77. SQL 1104	47
3.78. SQL 1105	47
3.79. SQL 1106	48
3.80. SQL 1108	48
3.81. SQL 1109	49
3.82. SQL 1112	49
3.83. SQL 1114	50
3.84. SQL 1115	50
3.85. SQL 1116	51
3.86. SQL 1117	51
3.87. SQL 1118	52
3.88. SQL 1119	52
3.89. SQL 1120	53
3.90. SQL 1121	53
3.91. SQL 1122	54
3.92. SQL 1123	54
3.93. SQL 1124	55
3.94. SQL 1127	55
3.95. SQL 1130	56
3.96. SQL 1132	56
3.97. SQL 1133	57
3.98. SQL 1134	57
3.99. SQL 1135	58
3.100. SQL 1136	58
3.101. SQL 1139	59
3.102. SQL 1140	59
3.103. SQL 1141	60
3.104. SQL 1142	60
3.105. SQL 1143	61
3.106. SQL 1144	61
3.107. SQL 1145	62
3.108. SQL 1146	62
3.109. SQL 1147	63
3.110. SQL 1148	63
3.111. SQL 1150	64
3.112. SQL 1151	65
3.113. SQL 1154	66
3.114. SQL 1155	66
3.115. SQL 1156	67
3.116. SQL 1157	67
3.117. SQL 1158	68

3.118. SQL 1159	68
3.119. SQL 1160	69
3.120. SQL 1161	69
3.121. SQL 1180	70
3.122. SQL 1181	70
3.123. SQL 1182	71
3.124. SQL 1183	71
3.125. SQL 1184	72
3.126. SQL 1185	72
3.127. SQL 1186	73
3.128. SQL 1187	73
3.129. SQL 1188	74
3.130. SQL 1224	74
3.131. SQL 1225	75
3.132. SQL 1226	75
3.133. SQL 1231	76
3.134. SQL 1232	76
3.135. SQL 1233	77
3.136. SQL 1235	77
3.137. SQL 1236	78
3.138. SQL 1238	78
3.139. SQL 1239	79
3.140. SQL 1240	79
3.141. SQL 1241	80
3.142. SQL 1242	80
3.143. SQL 1243	81
3.144. SQL 1245	81
3.145. SQL 1246	82
3.146. SQL 1248	82
3.147. SQL 1250	83
3.148. SQL 1251	83
3.149. SQL 1252	84
3.150. SQL 1254	84
3.151. SQL 1262	85
3.152. SQL 1263	85
3.153. SQL 1264	86
3.154. SQL 1265	86
3.155. SQL 1266	87
3.156. SQL 1267	87
3.157. SQL 1268	88
3.158. SQL 1270	88
3.159. SQL 1271	89
3.160. SQL 1273	89
3.161. SQL 1274	90

3.162. SQL 1275 .....	90
3.163. SQL 1277 .....	91
3.164. SQL 1278 .....	91
3.165. SQL 1301 .....	92
3.166. SQL 1302 .....	92
3.167. SQL 1305 .....	93
3.168. SQL 1307 .....	93
3.169. SQL 1309 .....	94
3.170. SQL 1310 .....	94
4. Trafodion Compiler Messages (2000 through 2999) .....	95
4.1. SQL 2004 .....	95
4.2. SQL 2009 .....	95
4.3. SQL 2011 .....	96
4.4. SQL 2012 .....	96
4.5. SQL 2013 .....	97
4.6. SQL 2014 .....	97
4.7. SQL 2020 .....	98
4.8. SQL 2029 .....	98
4.9. SQL 2030 .....	99
4.10. SQL 2033 .....	99
4.11. SQL 2034 .....	100
4.12. SQL 2035 .....	100
4.13. SQL 2038 .....	101
4.14. SQL 2050 .....	101
4.15. SQL 2051 .....	102
4.16. SQL 2053 .....	102
4.17. SQL 2054 .....	103
4.18. SQL 2055 .....	103
4.19. SQL 2056 .....	104
4.20. SQL 2057 .....	104
4.21. SQL 2058 .....	105
4.22. SQL 2059 .....	105
4.23. SQL 2060 .....	106
4.24. SQL 2061 .....	106
4.25. SQL 2062 .....	107
4.26. SQL 2063 .....	107
4.27. SQL 2064 .....	108
4.28. SQL 2065 .....	108
4.29. SQL 2066 .....	109
4.30. SQL 2067 .....	109
4.31. SQL 2068 .....	110
4.32. SQL 2069 .....	110
4.33. SQL 2070 .....	111
4.34. SQL 2071 .....	111

4.35. SQL 2072	112
4.36. SQL 2073	112
4.37. SQL 2074	113
4.38. SQL 2075	113
4.39. SQL 2076	114
4.40. SQL 2080	114
4.41. SQL 2081	115
4.42. SQL 2082	115
4.43. SQL 2083	116
4.44. SQL 2084	116
4.45. SQL 2085	117
4.46. SQL 2086	117
4.47. SQL 2090	118
4.48. SQL 2091	118
4.49. SQL 2092	119
4.50. SQL 2093	119
4.51. SQL 2094	120
4.52. SQL 2095	120
4.53. SQL 2096	121
4.54. SQL 2097	121
4.55. SQL 2098	122
4.56. SQL 2099	122
4.57. SQL 2100	123
4.58. SQL 2102	123
4.59. SQL 2103	124
4.60. SQL 2104	124
4.61. SQL 2105	125
4.62. SQL 2106	125
4.63. SQL 2107	126
4.64. SQL 2108	126
4.65. SQL 2200	127
4.66. SQL 2201	127
4.67. SQL 2202	128
4.68. SQL 2203	128
4.69. SQL 2204	129
4.70. SQL 2205	129
4.71. SQL 2206	130
4.72. SQL 2207	130
4.73. SQL 2208	131
4.74. SQL 2209	131
4.75. SQL 2210	132
4.76. SQL 2211	132
4.77. SQL 2212	133
4.78. SQL 2213	133

4.79. SQL 2214	134
4.80. SQL 2215	134
4.81. SQL 2220	135
4.82. SQL 2221	135
4.83. SQL 2222	136
4.84. SQL 2223	136
4.85. SQL 2233	137
4.86. SQL 2900	137
5. Parser and Compilation Messages (3000 through 3999)	138
5.1. SQL 3001	138
5.2. SQL 3002	138
5.3. SQL 3003	139
5.4. SQL 3004	139
5.5. SQL 3005	140
5.6. SQL 3006	140
5.7. SQL 3007	141
5.8. SQL 3008	141
5.9. SQL 3009	142
5.10. SQL 3010	142
5.11. SQL 3011	143
5.12. SQL 3012	143
5.13. SQL 3013	144
5.14. SQL 3014	144
5.15. SQL 3015	145
5.16. SQL 3016	145
5.17. SQL 3017	146
5.18. SQL 3018	146
5.19. SQL 3019	147
5.20. SQL 3020	147
5.21. SQL 3021	148
5.22. SQL 3022	148
5.23. SQL 3023	149
5.24. SQL 3024	149
5.25. SQL 3025	150
5.26. SQL 3026	150
5.27. SQL 3027	151
5.28. SQL 3028	151
5.29. SQL 3029	152
5.30. SQL 3030	152
5.31. SQL 3031	153
5.32. SQL 3032	153
5.33. SQL 3033	154
5.34. SQL 3034	154
5.35. SQL 3035	155

5.36. SQL 3036	155
5.37. SQL 3037	156
5.38. SQL 3038	156
5.39. SQL 3039	157
5.40. SQL 3040	157
5.41. SQL 3041	158
5.42. SQL 3042	158
5.43. SQL 3043	159
5.44. SQL 3044	159
5.45. SQL 3045	160
5.46. SQL 3046	160
5.47. SQL 3047	161
5.48. SQL 3048	161
5.49. SQL 3049	162
5.50. SQL 3050	162
5.51. SQL 3051	163
5.52. SQL 3052	163
5.53. SQL 3053	164
5.54. SQL 3054	164
5.55. SQL 3055	165
5.56. SQL 3056	165
5.57. SQL 3057	166
5.58. SQL 3058	166
5.59. SQL 3059	167
5.60. SQL 3060	167
5.61. SQL 3061	168
5.62. SQL 3062	168
5.63. SQL 3063	169
5.64. SQL 3064	169
5.65. SQL 3065	170
5.66. SQL 3067	170
5.67. SQL 3068	171
5.68. SQL 3070	171
5.69. SQL 3071	172
5.70. SQL 3072	172
5.71. SQL 3073	173
5.72. SQL 3074	173
5.73. SQL 3075	174
5.74. SQL 3076	174
5.75. SQL 3077	175
5.76. SQL 3078	175
5.77. SQL 3079	176
5.78. SQL 3080	176
5.79. SQL 3081	177

5.80. SQL 3082	177
5.81. SQL 3083	178
5.82. SQL 3084	178
5.83. SQL 3085	179
5.84. SQL 3086	179
5.85. SQL 3087	180
5.86. SQL 3088	180
5.87. SQL 3089	181
5.88. SQL 3090	181
5.89. SQL 3091	182
5.90. SQL 3092	182
5.91. SQL 3093	183
5.92. SQL 3094	183
5.93. SQL 3095	184
5.94. SQL 3096	184
5.95. SQL 3097	185
5.96. SQL 3098	185
5.97. SQL 3099	186
5.98. SQL 3100	186
5.99. SQL 3101	187
5.100. SQL 3102	187
5.101. SQL 3103	188
5.102. SQL 3104	188
5.103. SQL 3105	189
5.104. SQL 3106	189
5.105. SQL 3107	190
5.106. SQL 3108	190
5.107. SQL 3109	191
5.108. SQL 3110	191
5.109. SQL 3111	192
5.110. SQL 3112	192
5.111. SQL 3113	193
5.112. SQL 3114	193
5.113. SQL 3115	194
5.114. SQL 3116	194
5.115. SQL 3117	195
5.116. SQL 3118	195
5.117. SQL 3119	196
5.118. SQL 3120	196
5.119. SQL 3122	197
5.120. SQL 3123	197
5.121. SQL 3127	198
5.122. SQL 3128	198
5.123. SQL 3129	199

5.124. SQL 3130	199
5.125. SQL 3131	200
5.126. SQL 3132	200
5.127. SQL 3133	201
5.128. SQL 3134	201
5.129. SQL 3135	202
5.130. SQL 3136	202
5.131. SQL 3137	203
5.132. SQL 3138	203
5.133. SQL 3139	204
5.134. SQL 3140	204
5.135. SQL 3141	205
5.136. SQL 3142	205
5.137. SQL 3143	206
5.138. SQL 3145	206
5.139. SQL 3147	207
5.140. SQL 3148	207
5.141. SQL 3149	208
5.142. SQL 3150	208
5.143. SQL 3151	209
5.144. SQL 3153	209
5.145. SQL 3155	210
5.146. SQL 3157	210
5.147. SQL 3158	211
5.148. SQL 3159	211
5.149. SQL 3160	212
5.150. SQL 3161	212
5.151. SQL 3162	213
5.152. SQL 3163	213
5.153. SQL 3164	214
5.154. SQL 3165	214
5.155. SQL 3166	215
5.156. SQL 3167	215
5.157. SQL 3168	216
5.158. SQL 3169	216
5.159. SQL 3171	217
5.160. SQL 3172	217
5.161. SQL 3173	218
5.162. SQL 3174	218
5.163. SQL 3175	219
5.164. SQL 3176	219
5.165. SQL 3177	220
5.166. SQL 3178	220
5.167. SQL 3179	221

5.168. SQL 3180	221
5.169. SQL 3181	222
5.170. SQL 3182	222
5.171. SQL 3183	223
5.172. SQL 3184	223
5.173. SQL 3185	224
5.174. SQL 3186	224
5.175. SQL 3187	225
5.176. SQL 3188	225
5.177. SQL 3189	226
5.178. SQL 3192	226
5.179. SQL 3193	227
5.180. SQL 3195	227
5.181. SQL 3196	228
5.182. SQL 3197	228
5.183. SQL 3199	229
5.184. SQL 3201	229
5.185. SQL 3202	230
5.186. SQL 3203	230
5.187. SQL 3204	231
5.188. SQL 3205	231
5.189. SQL 3206	232
5.190. SQL 3207	232
5.191. SQL 3208	233
5.192. SQL 3209	233
5.193. SQL 3210	234
5.194. SQL 3211	234
5.195. SQL 3212	235
5.196. SQL 3213	235
5.197. SQL 3214	236
5.198. SQL 3215	236
5.199. SQL 3216	237
5.200. SQL 3217	237
5.201. SQL 3218	238
5.202. SQL 3220	238
5.203. SQL 3225	239
5.204. SQL 3226	239
5.205. SQL 3228	240
5.206. SQL 3229	240
5.207. SQL 3230	241
5.208. SQL 3400	241
5.209. SQL 3401	242
5.210. SQL 3402	242
5.211. SQL 3403	243

5.212. SQL 3404 .....	243
5.213. SQL 3405 .....	244
5.214. SQL 3406 .....	244
5.215. SQL 3411 .....	245
5.216. SQL 3412 .....	245
5.217. SQL 3413 .....	246
5.218. SQL 3414 .....	246
6. Optimizer Messages (6000 through 6999) .....	247
6.1. SQL 6001 .....	247
6.2. SQL 6002 .....	247
6.3. SQL 6003 .....	248
6.4. SQL 6007 .....	248
6.5. SQL 6008 .....	249
7. Generator Messages (7000 through 7999) .....	250
7.1. SQL 7001 .....	250
7.2. SQL 7003 .....	250
8. Executor Messages (8000 through 8999) .....	251
8.1. SQL 8006 .....	251
8.2. SQL 8007 .....	251
8.3. SQL 8012 .....	252
8.4. SQL 8016 .....	252
8.5. SQL 8017 .....	253
8.6. SQL 8101 .....	253
8.7. SQL 8102 .....	254
8.8. SQL 8103 .....	254
8.9. SQL 8104 .....	255
8.10. SQL 8105 .....	255
8.11. SQL 8302 .....	256
8.12. SQL 8553 .....	256
8.13. SQL 8573 .....	257
8.14. SQL 8576 .....	257
8.15. SQL 8577 .....	258
8.16. SQL 8578 .....	258
8.17. SQL 8579 .....	259
8.18. SQL 8604 .....	259
8.19. SQL 8605 .....	260
8.20. SQL 8606 .....	260
8.21. SQL 8607 .....	261
8.22. SQL 8608 .....	261
8.23. SQL 8609 .....	262
8.24. SQL 8610 .....	262
8.25. SQL 8612 .....	263
8.26. SQL 8613 .....	263
8.27. SQL 8808 .....	264

8.28. SQL 8809 . . . . .	264
8.29. SQL 8819 . . . . .	265
8.30. SQL 8820 . . . . .	265
8.31. SQL 8821 . . . . .	266
8.32. SQL 8824 . . . . .	266
8.33. SQL 8826 . . . . .	267
8.34. SQL 8827 . . . . .	267
8.35. SQL 8832 . . . . .	268
8.36. SQL 8833 . . . . .	268
8.37. SQL 8834 . . . . .	269
8.38. SQL 8836 . . . . .	269
8.39. SQL 8837 . . . . .	270
8.40. SQL 8840 . . . . .	270
8.41. SQL 8841 . . . . .	271
8.42. SQL 8842 . . . . .	271
8.43. SQL 8846 . . . . .	272
8.44. SQL 8850 . . . . .	272
8.45. SQL 8860 . . . . .	273
8.46. SQL 8861 . . . . .	273
8.47. SQL 8862 . . . . .	274
8.48. SQL 8863 . . . . .	274
8.49. SQL 8864 . . . . .	275
8.50. SQL 8865 . . . . .	275
8.51. SQL 8866 . . . . .	276
8.52. SQL 8867 . . . . .	276
8.53. SQL 8882 . . . . .	277
8.54. SQL 8888 . . . . .	277
8.55. SQL 8890 . . . . .	278
8.56. SQL 8901 . . . . .	278
8.57. SQL 8904 . . . . .	279
9. Sort Messages (9200 through 10049) . . . . .	280
9.1. SQL 9200 . . . . .	280
9.2. SQL 9201 . . . . .	280
9.3. SQL 9202 . . . . .	281
9.4. SQL 9203 . . . . .	281
9.5. SQL 9204 . . . . .	282
9.6. SQL 9205 . . . . .	282
9.7. SQL 9206 . . . . .	283
9.8. SQL 9207 . . . . .	283
9.9. SQL 9208 . . . . .	284
9.10. SQL 9209 . . . . .	284
9.11. SQL 9210 . . . . .	285
9.12. SQL 9212 . . . . .	285
9.13. SQL 9213 . . . . .	286

9.14. SQL 9214	286
9.15. SQL 10007	287
9.16. SQL 10011	287
9.17. SQL 10013	288
9.18. SQL 10014	288
9.19. SQL 10015	289
9.20. SQL 10016	289
9.21. SQL 10017	290
9.22. SQL 10018	290
9.23. SQL 10019	291
9.24. SQL 10020	291
9.25. SQL 10021	292
9.26. SQL 10022	292
9.27. SQL 10023	293
9.28. SQL 10024	293
9.29. SQL 10027	294
9.30. SQL 10028	294
9.31. SQL 10029	295
9.32. SQL 10047	295
9.33. SQL 10048	296
10. UDR Server and Language Manager Messages (11000 through 11399)	297
10.1. SQL 11108	297
10.2. SQL 11201	297
10.3. SQL 11202	298
10.4. SQL 11221	298
10.5. SQL 11222	299
11. SQLSTATE	300
11.1. SQLSTATE and SQLCODE Considerations	300
11.2. SQLSTATE Values	300
12. File-System Errors	357

## License Statement

Licensed to the Apache Software Foundation (ASF) under one or more contributor license agreements. See the NOTICE file distributed with this work for additional information regarding copyright ownership. The ASF licenses this file to you under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at

<http://www.apache.org/licenses/LICENSE-2.0>

Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

<b>Version</b>	<b>Date</b>
1.3.0	January, 2016

# Chapter 1. About This Document

Trafodion is a relational database management system based on ANSI SQL. It uses the industry standard Structured Query Language (SQL) to define and manipulate data. This manual describes messages produced by the Trafodion SQL engine and its associated components.

## 1.1. Intended Audience

This manual was written for Trafodion database administrators and programmers who use the Trafodion database software conversational or programmatic interface.

## 1.2. New and Changed Information

This is a new manual.

## 1.3. Notation Conventions

This list summarizes the notation conventions for syntax presentation in this manual.

- UPPERCASE LETTERS

Uppercase letters indicate keywords and reserved words. Type these items exactly as shown. Items not enclosed in brackets are required.

```
SELECT
```

- lowercase letters

Lowercase letters, regardless of font, indicate variable items that you supply. Items not enclosed in brackets are required.

```
file-name
```

- [ ] Brackets

Brackets enclose optional syntax items.

```
DATETIME [start-field TO] end-field
```

A group of items enclosed in brackets is a list from which you can choose one item or none.

The items in the list can be arranged either vertically, with aligned brackets on each side of the list, or horizontally, enclosed in a pair of brackets and separated by vertical lines.

For example:

```
DROP SCHEMA schema [ CASCADE ]
DROP SCHEMA schema [ CASCADE | RESTRICT ]
```

- { } Braces

Braces enclose required syntax items.

```
FROM { grantee [, grantee ] ... }
```

A group of items enclosed in braces is a list from which you are required to choose one item.

The items in the list can be arranged either vertically, with aligned braces on each side of the list, or horizontally, enclosed in a pair of braces and separated by vertical lines.

For example:

```
INTERVAL { start-field TO end-field }
{ single-field }
INTERVAL { start-field TO end-field | single-field }
```

- | Vertical Line

A vertical line separates alternatives in a horizontal list that is enclosed in brackets or braces.

```
{expression | NULL}
```

- ... Ellipsis

An ellipsis immediately following a pair of brackets or braces indicates that you can repeat the enclosed sequence of syntax items any number of times.

```
ATTRIBUTE[S] attribute [, attribute] ...
{, sql-expression } ...
```

An ellipsis immediately following a single syntax item indicates that you can repeat that syntax item any number of times.

For example:

```
expression-n ...
```

- Punctuation

Parentheses, commas, semicolons, and other symbols not previously described must be typed as shown.

```
DAY (datetime-expression)
@script-file
```

Quotation marks around a symbol such as a bracket or brace indicate the symbol is a required character that you must type as shown.

For example:

```
"{ " module-name [, module-name] ... " }"
```

- Item Spacing

Spaces shown between items are required unless one of the items is a punctuation symbol such as a parenthesis or a comma.

```
DAY (datetime-expression) DAY(datetime-expression)
```

If there is no space between two items, spaces are not permitted. In this example, no spaces are permitted between the period and any other items:

```
myfile.sh
```

- Line Spacing

If the syntax of a command is too long to fit on a single line, each continuation line is indented three spaces and is separated from the preceding line by a blank line.

This spacing distinguishes items in a continuation line from items in a vertical list of selections.

```
match-value [NOT] LIKE _pattern  
[ESCAPE esc-char-expression]
```

## 1.4. Publishing History

Product Version	Publication Date
Trafodion Release 1.3.0	To be announced.

## 1.5. Comments Encouraged

The Trafodion community encourages your comments concerning this document. We are committed to providing documentation that meets your needs. Send any errors found, suggestions for improvement, or compliments to:

[issues@trafodion.incubator.apache.org](mailto:issues@trafodion.incubator.apache.org)

Include the document title and any comment, error found, or suggestion for improvement you have concerning this document.

## Chapter 2. Introduction

### 2.1. Message Handling

Trafodion reports exception condition messages at a Trafodion Database Connectivity Service conversational interface (DCS) window and in the Trafodion Command Interface (TrafCI).

Most Trafodion exception condition messages describe error conditions for which recovery action is required. Some messages are warnings that provide information for which no action is required.

Error messages that appear in response to SQL commands are logged to the DCS application's log file if you have used the LOG command to request them.

The format of a Trafodion error is "\* ERROR" followed by the error number in brackets, and the descriptive text. Use the error number shown to find information about a particular error in this manual. For example, information for Trafodion error 1125 can be found under "SQL 1125."

Messages are listed in this manual in numeric order, broken down by the component that produced them.

### 2.2. Viewing Trafodion Database Messages

The message key is a sequential SQL message number that is returned automatically by Trafodion when an exception condition occurs. For example, the following message might be displayed within your application development tool while you prepare an embedded SQL program:

```
*** ERROR[1000] A syntax error occurred.
```

This message number is the SQLCODE value (without the sign). In this manual, you will find the following message information for ERROR[1000]:

### SQL 1000

1000 A syntax error occurred.

**Cause:** You specified a statement with incorrect syntax.

**Effect:** The Trafodion statement fails.

**Recovery:** Correct the syntax and resubmit.

## 2.3. SQLSTATE and SQLCODE

SQLSTATE and SQLCODE status codes are returned to indicate either that an SQL statement completed successfully or that an exception condition was raised during execution of an SQL statement.

The ANSI SQL SQLSTATE variable is a five-character string with a two-character class code followed by a three-character subclass code. An SQLSTATE value of 00000 indicates successful completion.

Trafodion extends the ANSI SQL SQLSTATE values to include other situations not described by the ANSI values. If an ANSI SQL SQLSTATE value exists for an error condition, the Trafodion database software returns that value. Otherwise, Trafodion returns an SQLSTATE value that is defined by the Trafodion database software.

Trafodion also returns a numeric SQLCODE value after SQL statement execution. SQLCODE values with negative numbers signify errors.

SQLCODE values with positive numbers other than 0 (successful completion) or 100 (no data was found) signify warning messages. Trafodion identifies all messages by their unsigned SQLCODE value and their calculated SQLSTATE value. The SQLCODE is used to calculate the SQLSTATE value for all Trafodion messages other than those for which an ANSI SQL SQLSTATE value exists.

The SQLCODE parameter is a deprecated feature that is supported to maintain compatibility with earlier versions of the American standard.

*SQLSTATE Values* identifies the equivalent SQLSTATE and SQLCODE values for Trafodion warning and error messages.

## 2.4. Getting Help

Some messages have no recovery and you will be instructed to contact the  
[mailt:user@trafodion.incubator.apache.org](mailto:user@trafodion.incubator.apache.org)[Trafodion user mailing list].

## Chapter 3. Data Definition Language (DDL) Messages (1000 through 1999)

### 3.1. SQL 1002

```
Catalog <catalog> does not exist or has not been registered on node <node>.
```

Where <catalog> is the ANSI name of the target catalog.

Where <node> is the node where the process executes.

**Cause:** The catalog is not visible on the local node, either because it does not exist or because it exists elsewhere on the network but has not been registered on the local node.

**Effect:** The operation fails.

**Recovery:** Enter a valid catalog name (or register the catalog on the node indicated) and resubmit.

### 3.2. SQL 1003

```
Schema <schema> does not exist.
```

Where <schema> is the ANSI name of the affected schema.

**Cause:** In a replication context: a REPLICATION SCHEMA operation specified a schema that does not exist.

**Effect:** The operation fails.

**Recovery:** Check that a schema named <schema> does exist and resubmit.

### 3.3. SQL 1004

Table, view, or stored procedure <object-name> does not exist or object type is invalid for the current operation.

Where <object-name> is the name of a Trafodion database object.

**Cause:** You attempted an operation on an object that does not exist.

**Effect:** The operation fails.

**Recovery:** Check that an object named <object-name> does exist. If you did not fully qualify the name, check that the defaults generate the correct fully qualified name and resubmit.

### 3.4. SQL 1005

Constraint <constraint-name> does not exist.

Where <constraint-name> is the name of a column constraint or table constraint.

**Cause:** The ALTER TABLE statement you attempted requires the existence of a constraint named <constraint-name>.

**Effect:** The operation fails.

**Recovery:** Check that a constraint named <constraint-name> exists for the table specified. You can use the SHOWDDL command to find the names of the constraints that exist on a table.

## 3.5. SQL 1006

```
Index <index-name> does not exist.
```

Where <index-name> is a Trafodion database object name.

**Cause:** The operation you attempted requires the existence of an index named <index-name>.

**Effect:** The operation fails.

**Recovery:** Check that an index named <index-name> does exist. If you did not fully qualify the name, check that the defaults generate the correct qualified name.

## 3.6. SQL 1008

```
User name <user-name> does not exist.
```

Where <user-name> is a Trafodion platform user name.

**Cause:** The user name specified in a GRANT or REVOKE statement, or the authorization ID in a CREATE SCHEMA statement, does not represent a valid Trafodion platform user.

**Effect:** The operation fails.

**Recovery:** Correct the user name and resubmit.

## 3.7. SQL 1009

Column <column-name> does not exist in the specified table.

Where <column-name> is an SQL identifier.

**Cause:** The table that is referenced does not have a column with this name.

**Effect:** The operation fails.

**Recovery:** Replace either the name of the table or the name of the column (whichever is incorrect) and resubmit.

## 3.8. SQL 1010

The statement just specified is currently not supported.

**Cause:** The statement that you specified is not available for use.

**Effect:** The operation fails.

**Recovery:** Do not attempt to use this Trafodion database statement.

## 3.9. SQL 1012

No privileges were granted. You lack grant option on the specified privileges.

**Cause:** You attempted to grant privileges for which you do not have grant options.

**Effect:** No privileges are granted.

**Recovery:** You must have grant options for privileges to grant them.

## 3.10. SQL 1013

Not all privileges were granted. You lack grant option on some of the specified privileges.

**Cause:** You attempted to grant privileges, but you do not have grant options for at least one of them.

**Effect:** The Trafodion database granted some privileges, but not all that you attempted to grant.

**Recovery:** You must have grant options for privileges to grant them.

## 3.11. SQL 1014

Privileges were not revoked. Dependent privilege descriptors still exist.

**Cause:** You attempted to revoke a privilege for a user who has granted privileges to another user. Privileges must be revoked in reverse order from how they were granted. If you perform a grant to another user who then performs a grant to a third user, you cannot revoke privileges to the second user until that user revokes their privileges to the third user.

**Effect:** The Trafodion database did not revoke the privileges.

**Recovery:** Make sure that the dependent privileges from the user whose privileges you want to revoke are revoked first.

## 3.12. SQL 1015

Some of the specified privileges could not be revoked.

**Cause:** You attempted to revoke a privilege that does not exist or that was granted by another user.

**Effect:** The Trafodion database did not revoke the privileges.

**Recovery:** The user who granted the privileges must revoke them.

## 3.13. SQL 1016

Redundant references to column <column-name> were specified in the constraint or trigger definition.

Where <column-name> is an SQL identifier.

**Cause:** You created a constraint with multiple references to <column-name>.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 3.14. SQL 1017

You are not authorized to perform this operation.

**Cause:** You attempted a replication operation without proper authorization.

**Effect:** The operation fails.

**Recovery:** In a replication context: Only the catalog owner and the local super ID can perform a replication operation for a catalog and for multiple schemas in a single catalog. Additionally, the schema owner can perform a replication operation for a single schema.

## 3.15. SQL 1020

Privilege settings on metadata tables cannot be changed.

**Cause:** You attempted to change privilege settings on a metadata table. They cannot be changed.

**Effect:** Trafodion does not change the settings.

**Recovery:** None.

## 3.16. SQL 1021

SQL is already initialized on system <node-name>.

Where <node-name> is the name of the system on which the INITIALIZE SQL statement was executed.

**Cause:** The Trafodion database has already been initialized on this node.

**Effect:** No operation is performed.

**Recovery:** None needed if SQL is operating normally.

## 3.17. SQL 1022

```
Schema <schema-name> already exists.
```

Where <schema-name> is the name of a Trafodion database schema.

**Cause:** You attempted to create a schema in a catalog that already contains a schema with that name.

**Effect:** The operation fails.

**Recovery:** If you did not use a fully qualified name, check that the default generates the correct catalog name. Retry the request, specifying a schema that does not already exist.

## 3.18. SQL 1023

```
Only services ID can name an authorization ID other than the current user name.
```

**Cause:** You attempted to create a schema with the authorization ID of another user. Only the services ID can do this.

**Effect:** The operation fails.

**Recovery:** Use the services ID to create a schema with another owner.

## 3.19. SQL 1024

```
File system error <error-number> occurred on <text-string-1> <text-string-2>.
```

Where <error-number> is an error originating from the file system.

Where <text-string-1> is the file name.

Where <text-string-2> is (optionally) additional details about the error.

**Cause:** Look up this error number in the file system manual to determine the cause.

**Effect:** The operation fails.

**Recovery:** For information about file system errors, see [File-System Errors](#).

## 3.20. SQL 1025

```
Request failed. One or more dependent objects exist.
```

**Cause:** This error can occur when you drop a constraint, index, or table. These objects cannot be dropped if they have dependent objects and the drop-behavior is RESTRICT.

**Effect:** Trafodion does not perform the operation.

**Recovery:** For DROP statements that support the CASCADE drop-behavior, you can reissue the statement specifying CASCADE. For other DROP statements, you must first drop each of the dependent objects, then drop the object.

## 3.21. SQL 1026

Only the schema owner or services ID can drop a schema.

**Cause:** An attempt was made to drop a schema by someone other than its owner or the services ID.

**Effect:** No SQL objects are dropped.

**Recovery:** The owner of the schema (or services ID) needs to issue the DROP SCHEMA statement.

## 3.22. SQL 1027

The definition schema <definition-schema-name> is dropped when its catalog is dropped.

Where <definition-schema-name> is the name of the definition schema specified.

**Cause:** You attempted to drop the schema containing the metadata tables for the catalog.

**Effect:** No SQL objects are dropped.

**Recovery:** Use DROP SCHEMA statements to drop all the user-created schemas in the catalog. Then use the DROP CATALOG statement to drop the catalog. The schema <definition-schema-name> is dropped when you drop its catalog.

## 3.23. SQL 1028

The schema must be empty. It contains at least one object <object-name>.

Where <object-name> is the name of a Trafodion database object existing in the schema.

**Cause:** You attempted to drop a schema that contains one or more objects.

**Effect:** The schema is not dropped.

**Recovery:** Either drop all the objects in <schema-name> and resubmit the statement, or resubmit the drop statement using the CASCADE option.

## 3.24. SQL 1029

Object <object-name> could not be created.

Where <object-name> is the name supplied in a CREATE statement.

**Cause:** This error can result from various CREATE statements. See the accompanying error messages to determine the cause.

**Effect:** The object is not created.

**Recovery:** Apply the recovery of the accompanying error messages.

## 3.25. SQL 1030

```
File label <file-name> could not be accessed. File system error <error>.
```

Where <file-name> is the name of a Trafodion database file.

Where <error> is a file system error number.

**Cause:** See the accompanying error message for the cause.

**Effect:** The operation fails.

**Recovery:** For information about file system errors, see [File-System Errors](#).

## 3.26. SQL 1031

```
Object <object-name> could not be dropped.
```

Where <object-name> is the SQL object.

**Cause:** See the accompanying error message for the cause.

**Effect:** Trafodion does not drop the object.

**Recovery:** Apply the recovery of the accompanying error message.

## 3.27. SQL 1035

```
Catalog <catalog-name> already exists.
```

Where <catalog-name> is the name of a Trafodion database catalog.

**Cause:** You attempted to create a catalog using the name of an already existing catalog.

**Effect:** The operation fails.

**Recovery:** None if this is the desired catalog. Otherwise, correct the catalog name and resubmit.

## 3.28. SQL 1036

```
Only super ID can execute DROP SQL.
```

**Cause:** An attempt was made to drop SQL by a user who is not the super ID.

**Effect:** The operation fails.

**Recovery:** The super ID needs to issue the DROP SCHEMA statement.

## 3.29. SQL 1037

Trafodion is not installed on system <node>.

Where <node> is the name of the node referenced by the operation.

**Cause:** In a replication or distribution context: An operation attempted to create a catalog reference or a partition on a node where the Trafodion database has not been installed.

**Effect:** The operation fails.

**Recovery:** Either reissue the statement specifying a different node, or install the Trafodion database on <node> and resubmit.

## 3.30. SQL 1038

Not all user catalogs have been dropped from the system.

**Cause:** You attempted to drop SQL while one or more user-created catalogs existed.

**Effect:** The operation fails.

**Recovery:** You must drop all user-created catalogs before dropping SQL.

## 3.31. SQL 1039

The DROP SQL statement could not be executed.

**Cause:** See the accompanying error message for the cause.

**Effect:** Trafodion does not drop SQL.

**Recovery:** Apply the recovery of the accompanying error message.

## 3.32. SQL 1040

The use of ALTER on metadata tables is not permitted.

**Cause:** An ALTER TABLE statement was issued naming a table that is part of the Trafodion database metadata. Such tables cannot be altered.

**Effect:** The operation fails.

**Recovery:** None.

## 3.33. SQL 1041

The primary key has already been defined.

**Cause:** You attempted to add a primary key to a table that already has a primary key.

**Effect:** The operation fails.

**Recovery:** None.

## 3.34. SQL 1042

All PRIMARY KEY or UNIQUE constraint columns must be NOT NULL.

**Cause:** You did not specify NOT NULL on one or more columns that are included in a UNIQUE or PRIMARY KEY constraint.

**Effect:** The operation fails.

**Recovery:** Reissue the statement with NOT NULL specified for all columns that are in the PRIMARY KEY and UNIQUE constraints.

## 3.35. SQL 1043

```
Constraint <constraint-name> already exists.
```

Where <constraint-name> is the name of a column constraint or table constraint.

**Cause:** You assigned the same constraint name to two constraints on the same table. Constraint names must be unique among all the constraints for a table.

**Effect:** The operation fails.

**Recovery:** Make all the constraint names for the table unique. Use SHOWDDL to see the names of existing constraints.

## 3.36. SQL 1044

```
Constraint <constraint-name> could not be created because the referenced columns in the  
referenced table are not part of a unique constraint.
```

Where <constraint-name> is the name of a column constraint or table constraint.

**Cause:** The columns that <constraint-name> references in the referenced table are not part of a unique constraint.

**Effect:** The operation fails.

**Recovery:** Check that <constraint-name> references a unique or primary constraint in the referenced table.

## 3.37. SQL 1045

The unique constraint cannot be used because it is deferrable.

**Cause:** The referential constraint is referencing the unique constraint that is declared as deferrable. This is an internal error.

**Effect:** The operation fails.

**Recovery:** Check that the referential constraint references a unique constraint that is not declared deferrable. Contact the Trafodion User Distribution List

## 3.38. SQL 1046

Referenced and referencing column lists do not match for constraint <constraint-name>.

Where <constraint-name> is the name of a column constraint or table constraint.

**Cause:** The list of referencing columns in <constraint-name> does not match the list of unique key columns that it is referencing.

**Effect:** The operation fails.

**Recovery:** Check that the <constraint-name> list of referencing columns matches the list of referenced columns.

## 3.39. SQL 1047

Request failed. Dependent view <view-name> exists.

Where <view-name> is the name of the view on the object being dropped.

**Cause:** An object that has a dependent view cannot be dropped unless you use the CASCADE option on the DROP statement.

**Effect:** The operation fails.

**Recovery:** To drop the object and all its dependent objects, you can either drop each of the dependent objects using individual DROP statements before dropping the object itself, or use the CASCADE clause on the DROP statement for the object.

## 3.40. SQL 1048

The statement currently supports only RESTRICT drop behavior.

**Cause:** Drop behavior CASCADE was specified on a DROP statement that supports only RESTRICT drop behavior.

**Effect:** The operation fails.

**Recovery:** Reissue the DROP statement, specifying RESTRICT or omitting the drop behavior (which will default to RESTRICT).

## 3.41. SQL 1049

Constraint cannot be dropped because it was specified to be NOT DROPPABLE.

**Cause:** You attempted to drop a constraint that is NOT DROPPABLE.

**Effect:** The operation fails.

**Recovery:** None.

## 3.42. SQL 1050

Constraint cannot be dropped because it is used as a referenced object for a foreign key.

**Cause:** You attempted to drop a unique or primary constraint, with dependent referential constraints, using the RESTRICT option, which does not remove such constraints.

**Effect:** The drop command fails.

**Recovery:** If you want to drop the dependent referential constraints, use the CASCADE option for the DROP CONSTRAINT command.

## 3.43. SQL 1051

You do not have the required privilege(s) on <object-name>.

Where <object-name> is the name of the object for which you have insufficient privileges.

**Cause:** You have insufficient privileges to create a view or a trigger.

**Effect:** The operation fails.

**Recovery:** See the [Trafodion SQL Reference Manual](#) for the required security needed to create a view or trigger.

## 3.44. SQL 1053

Unique index <index-name> could not be created because the specified column(s) contain duplicate data.

Where <index-name> is the name specified for the index to create.

**Cause:** The rows already existing in the table violate the uniqueness constraint specified in the CREATE INDEX statement.

**Effect:** The index is not created.

**Recovery:** Either change the list of columns for the unique index, or change the rows in the table to remove duplicates. Then reissue the statement.

## 3.45. SQL 1057

```
Trafodion objects cannot be created on <volume-name>: File system error <error-number>.
```

Where <volume-name> is the name of a volume.

Where <error-number> is the file system error number.

**Cause:** An attempt to create a file on volume <volume-name> resulted in file system error <error-number>.

**Effect:** The operation fails.

**Recovery:** For information about file system errors, see [File-System Errors](#).

## 3.46. SQL 1058

```
Lock <lock-name> already exists.
```

Where <lock-name> is the name of the DDL lock.

**Cause:** The statement required creation of a lock with a unique lock name, which was not generated.

**Effect:** The operation fails.

**Recovery:** Specify a unique lock name and resubmit.

## 3.47. SQL 1059

Request failed. Dependent constraint <constraint-name> exists.

Where <constraint-name> is the name of a column constraint or table constraint.

**Cause:** You attempted to drop a table that has a referential constraint or a check constraint that refers to another table.

**Effect:** Trafodion does not drop the table.

**Recovery:** Either drop all constraints that refer to other tables and then drop the table, or reissue the DROP TABLE statement, specifying the CASCADE option.

## 3.48. SQL 1061

Dropping metadata catalog <catalog-name> is not allowed.

Where <catalog-name> is the name of a Trafodion database catalog.

**Cause:** You attempted to drop a catalog that is part of the Trafodion database metadata.

**Effect:** The operation fails.

**Recovery:** None.

## 3.49. SQL 1062

```
Dropping metadata schema <schema-name> is not allowed.
```

Where <schema-name> is the name of a Trafodion database metadata schema.

**Cause:** You attempted to drop a schema that is part of the Trafodion database metadata.

**Effect:** The operation fails.

**Recovery:** None.

## 3.50. SQL 1063

```
Dropping metadata index <index-name> is not allowed.
```

Where <index-name> is the name of a Trafodion database index.

**Cause:** An attempt was made to drop an index that is part of the Trafodion database metadata.

**Effect:** The operation fails.

**Recovery:** None.

## 3.51. SQL 1064

```
Dropping metadata view <table-name> is not allowed.
```

Where <table-name> is the name of a Trafodion database table.

**Cause:** An attempt was made to drop a view that is a metadata object. Metadata views and their creation are not currently supported, so this error should not be encountered.

**Effect:** The operation fails.

**Recovery:** None.

## 3.52. SQL 1065

```
Creating constraint <constraint-name> in metadata schema is not allowed.
```

Where <constraint-name> is the name of the constraint.

**Cause:** You attempted to create a constraint on a metadata table, which is not allowed.

**Effect:** The operation fails.

**Recovery:** None.

## 3.53. SQL 1066

Creating index <index-name> in metadata schema is not allowed.

Where <index-name> is the name specified for the index.

**Cause:** You attempted to create an index on a metadata table, which is not allowed.

**Effect:** The operation fails.

**Recovery:** None.

## 3.54. SQL 1069

Schema <schema-name> could not be dropped.

Where <schema-name> is the name of a Trafodion database schema.

**Cause:** See the accompanying error message for the cause of the problem.

**Effect:** The operation fails.

**Recovery:** Apply the recovery action from the accompanying error message.

## 3.55. SQL 1070

```
Object <object-name> could not be created. File error: <error-number>.
```

Where <object-name> is the name of the Trafodion database object.

Where <error-number> is the file system error number.

**Cause:** An attempt to create object <object-name> resulted in file system error <error-number>.

**Effect:** The operation fails.

**Recovery:** For information about file system errors, see [File-System Errors](#).

## 3.56. SQL 1071

```
Object <ANSI-name> could not be accessed.
```

Where <ANSI-name> is the name of the Trafodion database object.

**Cause:** The statement issued required access to the Trafodion platform file underlying object <ANSI-name>.

**Effect:** The operation fails.

**Recovery:** Apply the recovery action from the accompanying error message.

## 3.57. SQL 1072

Unique constraint <constraint-name-1> is disabled, so foreign key constraint <constraint-name-2> could not be created.

Where <constraint-name-1> is the name of the disabled constraint.

Where <constraint-name-2> is the name of the foreign key constraint.

**Cause:** You created a referential constraint that references a unique constraint that has been disabled. This is an internal error.

**Effect:** The operation fails.

**Recovery:** Create the referential constraint that references a unique constraint that has not been disabled.

## 3.58. SQL 1073

Only services ID can execute INITIALIZE SQL.

**Cause:** You attempted to initialize the Trafodion database, but you are not the services ID. Only the services ID can perform this function.

**Effect:** The operation fails.

**Recovery:** Log on as the services ID before executing this command.

## 3.59. SQL 1075

The catalog must be empty. It contains at least one schema <schema-name>.

Where <schema-name> is the name of a schema in the specified catalog.

**Cause:** An attempt was made to drop a catalog that is not empty.

**Effect:** The catalog is not dropped. None of its schemas are dropped.

**Recovery:** Drop all schemas in the catalog and resubmit.

**Recovery:** None. Contact the Trafodion User Distribution List

## 3.60. SQL 1078

The format of the specified location name <location-name> is not valid.

Where <location-name> is a name specified in a LOCATION clause.

**Cause:** An invalid name was supplied in a LOCATION clause.

**Effect:** The operation fails.

**Recovery:** See the [Trafodion SQL Reference Manual](#) for limitations on names allowed in the LOCATION clause. Correct the name and resubmit.

## 3.61. SQL 1079

Trafodion was not able to prepare the statement.

**Cause:** See the accompanying error message for the cause.

**Effect:** The operation fails.

**Recovery:** Apply the recovery of the accompanying error message.

## 3.62. SQL 1080

The create request has duplicate references to column <column-name>.

Where <column-name> is the name of a column of a table.

**Cause:** You attempted to create a table that has two columns with the same name. If you name a column "SYSKEY," duplication can result from the implicit creation by the Trafodion database software of a column named SYSKEY to ensure uniqueness for the clustering key.

**Effect:** The operation fails.

**Recovery:** Remove duplicate column names and resubmit.

## 3.63. SQL 1081

```
Loading of index <index-name> failed unexpectedly.
```

Where <index-name> is the name of the index being populated.

**Cause:** Population of the index failed, either because another concurrent operation was being performed on the base table or because data could not be loaded into the index by the Call-level interface (CLI).

**Effect:** The operation fails.

**Recovery:** Determine the cause of the CLI failure and resubmit.

## 3.64. SQL 1082

```
Validation for constraint <constraint-name> failed unexpectedly.
```

Where <constraint-name> is the name of a column or table constraint.

**Cause:** The constraint validation failed, either because a concurrent operation was being performed on the table or on the referenced table (for a referential integrity constraint), or data in the table violates the constraint.

**Effect:** The constraint operation fails.

**Recovery:** If a concurrent operation is in progress, wait until it has finished and try the operation again. If data in the table violates the constraint, remove that data and resubmit.

## 3.65. SQL 1083

```
Validation for constraint <constraint-name> failed; incompatible data exists in table.
```

Where <constraint-name> is the name of a column or table constraint.

**Cause:** Data in the table violates the check constraint.

**Effect:** The constraint operation fails.

**Recovery:** Remove data that violates the constraint from the table and resubmit.

## 3.66. SQL 1084

```
An invalid default value was specified for column <column-name>.
```

Where <column-name> is the specified column.

**Cause:** An invalid default value was specified in the column definition for <column-name>.

**Effect:** Creation of the table or addition of the column fails.

**Recovery:** Specify a valid default value for the column and resubmit.

## 3.67. SQL 1085

The calculated key length is greater than 255 bytes.

**Cause:** The length of the primary key, which is calculated by the number of primary key columns and their data types, exceeds the maximum length.

**Effect:** The operation fails.

**Recovery:** Make sure the key length is less than 255 bytes and resubmit.

## 3.68. SQL 1086

Lock <lock-name> does not exist.

Where <lock-name> is the name of the specified lock.

**Cause:** Lock <lock-name> was specified, but does not exist.

**Effect:** The operation fails.

**Recovery:** Create a lock <lock-name> or specify a valid lock name and resubmit.

## 3.69. SQL 1087

DDL lock cannot be granted, invalid operation has been specified.

**Cause:** An invalid utility operation requested a DDL lock.

**Effect:** The lock request fails.

**Recovery:** Specify a valid utility operation, or check to see if invalid utilities are being run, and resubmit.

## 3.70. SQL 1088

The system generated column SYSKEY must be specified last or not specified at all in the STORE BY column list.

**Cause:** If the system-generated column SKSKEY is specified in the STORE BY list of columns, it must be specified last.

**Effect:** The operation fails.

**Recovery:** Correct the STORE BY clause and resubmit.

## 3.71. SQL 1089

The system generated column SYSKEY must be specified last or not specified at all in the index column list.

**Cause:** The system-generated SYSKEY column was not the last column in a CREATE INDEX statement.

**Effect:** The operation fails.

**Recovery:** Change the column list to place SYSKEY at the end of the list and resubmit the statement.

## 3.72. SQL 1090

Self-referencing constraints are currently not supported.

**Cause:** You attempted to create a self-referencing constraint. A referential constraint is self-referencing if the foreign key is referencing the primary key of the same table.

**Effect:** The operation fails.

**Recovery:** Remove the self-reference and resubmit.

## 3.73. SQL 1094

Object <object-name> could not be dropped because it is not of type <object-type>.

Where <object-name> is the ANSI name of the object stated in the DROP command.

Where <object-type> is the type of object that was stated in the DROP command.

**Cause:** A DROP TABLE specified an object that is not a base table, or a DROP VIEW specified an object that is not a view, or a DROP PROCEDURE specified an object that is not a procedure.

**Effect:** The operation fails.

**Recovery:** Reissue the DROP statement with the correct combination of specified object type and actual object type.

## 3.74. SQL 1095

The PARTITION BY column <column-name> should also be part of the clustering/storage key.

Where <column-name> is the name of a column of the specified table.

**Cause:** This error is reported if a column specified in the partitioning key of the **PARTITION BY (<partitioning-columns | )** clause of a CREATE TABLE or CREATE INDEX statement is not also a member of the clustering key.

**Effect:** The table or index is not created.

**Recovery:** Either remove the offending column from the partitioning key specification (and possibly replace it with a column that is a member of the clustering key) or add the offending column to the clustering key by using the STORE BY clause or by adding it to the primary key.

## 3.75. SQL 1098

```
Duplicate partition key (<key>)specified for object <object-name>.
```

Where <key> is a partition key.

Where <object-name> is the name of the table being created or changed.

**Cause:** You attempted to create or change a table so that more than one partition has the same first key.

**Effect:** The operation fails.

**Recovery:** Change the statement so that it does not define two partitions to have the same first key, and resubmit.

## 3.76. SQL 1099

```
Column <column-number> is unnamed. You must specify an AS clause for that column expression, or name all the columns by specifying a view column list.
```

Where <column-number> is the specified column.

**Cause:** You attempted to create a view by using a query expression in which <column-number> was unnamed.

**Effect:** The operation fails.

**Recovery:** Correct the statement to supply an AS clause for each unnamed column and resubmit.

## 3.77. SQL 1104

```
Default value string is too long for column <column-name>.
```

Where <column-name> is the name of a character-type column for which a default value is specified.

**Cause:** The specified default value for <column-name> is longer than the maximum of 239 characters.

**Effect:** The operation fails.

**Recovery:** Correct the error and resubmit.

## 3.78. SQL 1105

```
CREATE TABLE LIKE statement cannot contain both HORIZONTAL PARTITIONS and STORE BY clauses.
```

**Cause:** A CREATE TABLE . . . LIKE statement specifies both the WITH PARTITIONS and STORE BY clause, which is not allowed.

**Effect:** The operation fails.

**Recovery:** Correct the error and resubmit.

## 3.79. SQL 1106

The specified partition <partition-location> of object <table-name> does not exist.

Where <partition-location> is the location of the specified partition.

Where <table-name> is the name of the table.

**Cause:** The location name <partition-location> specified in the partition operation does not exist.

**Effect:** The partition operation fails.

**Recovery:** Specify a valid partition location name and resubmit.

## 3.80. SQL 1108

The number of columns specified in the view column list, <view-col-num>, does not match the degree of the query expression, <query-col-num>.

Where <view-col-num> is the number of columns in the view column list.

Where <query-col-num> is the number of columns resulting from the query expression used to define the view.

**Cause:** The number of columns in the query do not equal the number of columns specified for the view.

**Effect:** The operation fails.

**Recovery:** Specify a query statement that has a degree that matches the number of columns in the view column list, and resubmit.

## 3.81. SQL 1109

The WITH CHECK OPTION clause appears in the definition of view <view-name>, but the view is not updatable.

Where <view-name> is the name of the view being created.

**Cause:** You used WITH CHECK OPTION in the definition of a view that is not updatable.

**Effect:** The operation fails.

**Recovery:** Either make the view updatable or omit the WITH CHECK OPTION and resubmit.

## 3.82. SQL 1112

An index column list cannot consist only of the system-generated column SYSKEY.

**Cause:** The column list specified in a CREATE INDEX statement consisted only of the system-generated column SYSKEY.

**Effect:** The operation fails.

**Recovery:** Change the column list to include additional columns and reissue the statement.

## 3.83. SQL 1114

```
Metadata tables for catalog <catalog-name> could not be created on <location-info>.
```

Where <catalog-name> is the name of a Trafodion database catalog.

Where <location-info> is the location where the tables could not be created.

**Cause:** This error can result from various CREATE statements issued to create the metadata. See the accompanying error messages to determine the cause.

**Effect:** One or more objects are not created.

**Recovery:** See the accompanying error messages for recovery action.

## 3.84. SQL 1115

```
Label <file-name> could not be created for <ANSI-name> (file error <error>).
```

Where <file-name> is the name of the file for the label creation that failed.

Where <ANSI-name> is the name of the table.

Where <error> is the error number returned.

**Cause:** A file system error occurred on the attempt to create the label.

**Effect:** The table is not created.

**Recovery:** Correct the file system error and reissue the CREATE statement. For information about file system errors, see [File-System Errors](#).

## 3.85. SQL 1116

The current partitioning scheme requires a user-specified clustering key on object <table-name>.

Where <table-name> is the name of the table.

**Cause:** The partitioning scheme requires a user-specified clustering key.

**Effect:** The operation fails.

**Recovery:** Specify a clustering key, either through a PRIMARY KEY, STORE BY, or PARTITION BY clause.

## 3.86. SQL 1117

Dropping the only partition of an object is not allowed. At least two partitions must exist to perform the drop.

**Cause:** You attempted to drop the only partition of the object.

**Effect:** The operation fails.

**Recovery:** None.

## 3.87. SQL 1118

Creating object <table-name> is not allowed in metadata schema.

Where <table-name> is the name of the object.

**Cause:** You attempted to create an object in the metadata schema.

**Effect:** The operation fails.

**Recovery:** Specify a different schema and resubmit.

## 3.88. SQL 1119

Dropping metadata object <table-name> is not allowed.

Where <table-name> is the name of a Trafodion database metadata table.

**Cause:** You attempted to use the DROP TABLE statement to drop a table that is part of the Trafodion database metadata.

**Effect:** The table is not dropped.

**Recovery:** Metadata tables can be dropped only by using the DROP SQL statement or the MXTOOL GOAWAY utility.

Both methods will irrevocably destroy the database.

## 3.89. SQL 1120

Use of float datatype in a partitioning key is not allowed.

**Cause:** You attempted an operation on a partitionable table that has float datatype in the partitioning key.

**Effect:** The operation fails.

**Recovery:** Enable the default ALLOW\_FLOAT\_DATATYPES\_IN\_PARTITIONING\_KEY via a control query default statement and retry the operation.

## 3.90. SQL 1121

Partitions cannot be added or dropped on table <table-name>. These partition operations are not allowed on tables whose clustering key consists only of the SYSKEY.

Where <table-name> is the name of the table.

**Cause:** You attempted to do an invalid ADD, DROP, or MODIFY of a partition.

**Effect:** The operation fails.

**Recovery:** None.

## 3.91. SQL 1122

The number of specified partition key values (<partitionkey-value-list>) for object <object-name> exceeds the number of user defined key columns, <key-col-number>.

Where <partition-key-value-list> is a list of the partition key values.

Where <object-name> is the name of the object.

Where <key-col-number> is the number of columns in the user-defined key.

**Cause:** The number of specified partition key values (<partition-key-valuelist>) for object <object-name> exceeds the number of user-defined key columns, <key-col-number>.

**Effect:** The operation fails.

**Recovery:** Fix the statement and resubmit.

## 3.92. SQL 1123

Not all of the partition key values (<key>) for object <object-name> could be processed. Please verify that the correct key value data types were specified.

Where <key> is a list of the partition key values.

Where <object-name> is the name of the object.

**Cause:** You attempted to access a table using a first key value that contains an element that is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 3.93. SQL 1124

Use of a float datatype in a partitioning key has been enabled by the default ALLOW\_FLOAT\_DATATYPES\_IN\_PARTITIONING\_KEY. This could give some incorrect results and the users should be aware of it.

**Cause:** You attempted an operation on a partitionable table that has float datatype in the partitioning key.

**Effect:** The operation completes without errors, but the results might not be correct. The float data value might not be evaluated consistently to the same value each time.

**Recovery:** Do not use float data types in the partitioning key of a partitionable table.

## 3.94. SQL 1127

The specified table <table-name> is not a base table. Please verify that the correct table was specified.

Where <table-name> is the name of the table.

**Cause:** You attempted to perform an operation that can be performed only on a base table, and the specified object is not a base table.

**Effect:** The operation fails.

**Recovery:** Specify a valid base table and resubmit.

## 3.95. SQL 1130

The column requires a default value.

**Cause:** You attempted to create a column that requires a default value, without specifying a default value.

**Effect:** The operation fails.

**Recovery:** Specify a valid default value for the column and resubmit.

## 3.96. SQL 1132

An added column cannot have both DEFAULT NULL and NOT NULL.

**Cause:** You attempted to add a column that is both DEFAULT NULL and NOT NULL.

**Effect:** The operation fails.

**Recovery:** Determine whether the column should be DEFAULT NULL or NOT NULL and resubmit.

## 3.97. SQL 1133

Only super ID can perform this operation.

**Cause:** You attempted to perform an operation that can be performed only by the super ID.

**Effect:** The operation fails.

**Recovery:** Log on as the super ID and then resubmit.

## 3.98. SQL 1134

A concurrent utility or DDL is being performed on object <object-name>, its parent, or one of its dependencies. That operation must complete before the requested operation can run.

Where <object-name> is the name of the object.

**Cause:** You attempted to execute a utility or alter the DDL of an object while a concurrent utility or DDL operation was being performed on the object, its parent, or its dependencies.

**Effect:** The operation fails.

**Recovery:** Wait until the concurrent operation has finished and then resubmit.

## 3.99. SQL 1135

Clustering key column <column-name> must be assigned a NOT NULL NOT DROPPABLE constraint.

Where <column-name> is the name of the column in the clustering key.

**Cause:** You attempted to make a column that is not NOT NULL NOT DROPPABLE a part of the clustering key of a table.

**Effect:** The operation fails.

**Recovery:** Specify that the <column-name> is NOT NULL NOT DROPPABLE and resubmit.

## 3.100. SQL 1136

For an added column, the PRIMARY KEY clause cannot specify NOT DROPPABLE.

**Cause:** You used the ALTER TABLE statement to add a column specifying a primary key that is not droppable. A primary key added through ALTER TABLE must be droppable.

**Effect:** The operation fails.

**Recovery:** Change the ALTER TABLE statement to specify DROPPABLE for the primary key.

## 3.101. SQL 1139

System-generated column <column-name> of base table <table-name> cannot appear in the search condition of a check constraint definition.

Where <column-name> is the name of a column of <table-name>.

Where <table-name> is the name of the affected table.

**Cause:** You attempted to create a check constraint that references a system-generated column. The column named SYSKEY is often system-generated.

**Effect:** The operation fails.

**Recovery:** Modify the statement so that no check constraints reference any system-generated column and resubmit.

## 3.102. SQL 1140

Row-length <actual-row-length> exceeds the maximum allowed row-length of <maximum-row-length> for table <table-name>.

Where <actual-row-length> is the length of a row of the table.

Where <maximum-row-length> is the largest row size allowed.

Where <table-name> is the name of the table.

**Cause:** On a CREATE or ALTER TABLE statement, the size of the row exceeds the maximum allowed row size.

**Effect:** The operation fails.

**Recovery:** See the [Trafodion SQL Reference Manual](#) for row size limit calculations. Change the column definitions and reissue the statement.

## 3.103. SQL 1141

```
Label <file-name> for object could not be accessed. File system error <error-number>.
```

Where <file-name> is the Trafodion platform file name of a partition of object.

Where <error-number> is a Trafodion platform file system error.

**Cause:** An ALTER TABLE or ALTER INDEX operation encountered a file system error.

**Effect:** The operation fails.

**Recovery:** For information about file system errors, see [File-System Errors](#).

## 3.104. SQL 1142

```
Because it is not audited, this table cannot have a column added that is declared NOT NULL, or has a CHECK, UNIQUE, PRIMARY KEY, or FOREIGN KEY constraint.
```

**Cause:** Internal error.

**Effect:** The Trafodion database is unable to perform the requested operation.

**Recovery:** None. Contact the Trafodion User Distribution List

## 3.105. SQL 1143

Validation for constraint <constraint-name> failed; incompatible data exists in referencing base table <referencing-table-name> and referenced base table <referenced-table-name>. To display the data violating the constraint, please use the following DML statement: <statement-text>.

Where <constraint-name> is the name of a column constraint or table constraint.

Where <referencing-table-name> is the table on which the constraint is being added.

Where <referenced-table-name> is the table specified in the FOREIGN KEY clause.

Where <statement-text> is a query.

**Cause:** You attempted to add a referential integrity constraint that is violated by rows already in the table.

**Effect:** The operation fails.

**Recovery:** Run the query <statement-text> to see the rows that violate the referential constraint. Either change those rows or change the referential constraint definition and resubmit.

## 3.106. SQL 1144

A quoted string was expected in first key clause for column <column-name> on table <table-name>, but the value detected is (<first-key-string>).

Where <column-name> is the column in <table-name>.

Where <table-name> is the name of the table.

Where <first-key-string> is the erroneous value used in the FIRST KEY clause for <column-name>.

**Cause:** In a CREATE TABLE statement, a value specified as first key is not a quoted string, but the type of the column for which this value is specified is one of the character data types.

**Effect:** The operation fails.

**Recovery:** Correct the value <first-key-string> to be a type that is compatible with the type of column <column-name> and resubmit.

## 3.107. SQL 1145

The catalog name <catalog-name> is reserved for Trafodion metadata.

Where <catalog-name> is the name of a Trafodion database catalog.

**Cause:** Trafodion reserves certain catalog names for its own use.

**Effect:** The operation fails.

**Recovery:** See the [Trafodion SQL Reference Manual](#) for reserved names. Change <catalog-name> to a name that is not reserved and resubmit.

## 3.108. SQL 1146

Object <object-name> could not be altered because it is not a <object-type>.

Where <object-name> is the name of the object being requested.

Where <object-type> is the type of object required for the DDL statement issued.

**Cause:** The type of the object specified in the command is inconsistent with the DDL command being used. For example, this occurs if DROP TABLE is used, and the object you specify is an INDEX.

**Effect:** The operation fails.

**Recovery:** Check that the correct object name was specified and execute a statement that is consistent with that type of object.

## 3.109. SQL 1147

System-generated column <column-name> of base table <table-name> cannot appear in a unique or primary key constraint.

Where <column-name> is the SYSKEY column.

Where <table-name> is the name of the table.

**Cause:** You tried to create a unique or primary key constraint on the SYSKEY column.

**Effect:** The operation fails.

**Recovery:** Do not use the SYSKEY as part of the unique or primary key.

## 3.110. SQL 1148

System-generated column <column-name> of base table <table-name> cannot appear in a referential integrity constraint definition.

Where <column-name> is the SYSKEY column.

Where <table-name> is the name of the table.

**Cause:** You tried to create a referential constraint on a table column that is the SYSKEY, which is not supported.

**Effect:** The operation fails.

**Recovery:** Do not use the SYSKEY as part of the referenced key.

## 3.111. SQL 1150

Table <table-name> was not created as Partition Overlay Support could not generate volume names for the partitions to reside on.

Where <table-name> is the name of the table.

**Cause:** When the Partition Overlay Support feature is enabled without setting volume names (through CQD POS\_LOCATIONS) for table partitions to reside on, location names are generated automatically. However, the Trafodion database software could not generate the location names automatically and, because the CQD POS\_RAISE\_ERROR is set, the table is not created.

**Effect:** The operation fails.

**Recovery:** To correct the error, choose a recovery method:

- Verify that the disk volumes are available on the current node and retry the request.
- Specify the volume names where the partitions need to be created for the given CREATE TABLE statement through CONTROL QUERY DEFAULT POS\_LOCATIONS, and then retry the request.
- Do not set the CQD POS\_RAISE\_ERROR, in which case, a simple table without partitions is created when the volume names cannot be generated.

## 3.112. SQL 1151

POS (Partition Overlay Support) was not applied as volume names could not be generated for the partitions. So a simple table <table-name> was created without partitions.

Where <table-name> is the name of the table.

**Cause:** When the Partition Overlay Support feature is enabled without setting volume names (through CQD POS\_LOCATIONS) for table partitions to reside on, location names are generated automatically. However, the Trafodion database software could not generate the location names automatically, and because the CQD POS\_RAISE\_ERROR is not set, the given table is created as a simple table without partitions as it would be if the Partition Overlay Support feature was not enabled.

**Effect:** The POS feature was not applied. A simple table without partitions was created.

**Recovery:** None if a non-partitioned table is requested. To request a partitioned table, delete the table, verify that disk volumes are available, and resubmit. You can also specify the volume names where the partitions need to be created for the given CREATE TABLE through CONTROL QUERY DEFAULT POS\_LOCATIONS, and then retry the request.

## 3.113. SQL 1154

Cannot create object <object-name> as the table size is too big to fit on the system.

**Cause:** Trafodion could not create the object because the requested table size is bigger than the total amount of disk space available on the system.

**Effect:** The SQL operation fails.

**Recovery:** Check that the table size requested is big enough to fit on the system and retry the statement.

## 3.114. SQL 1155

Operation cannot be performed because <object-name> is not a synonym.

**Cause:** You specified an alter or drop of synonym on an object <object-name>, which is not a synonym.

**Effect:** The operation fails.

**Recovery:** Correct the syntax so that the correct <object-name> is used.

## 3.115. SQL 1156

Synonym <name> does not exist or object type is invalid for the current operation.

**Cause:** You specified a create or alter of synonym <name> on an object that is not a table or view.

**Effect:** The operation fails.

**Recovery:** Correct the syntax so that the correct <name> is used.

## 3.116. SQL 1157

Synonym object <name> is the same as previous mapping.

**Cause:** You specified an alter of synonym on an object <name>, which is the same as its previous mapping.

**Effect:** The operation succeeds with a warning.

**Recovery:** None.

## 3.117. SQL 1158

```
Synonym <name> already exists.
```

**Cause:** You specified a create of synonym <name> on an object, but a synonym of that name already exists.

**Effect:** The operation fails.

**Recovery:** Correct the syntax so that the correct <name> is used.

## 3.118. SQL 1159

```
The specified object <name> is not a table or a view. Please verify that the correct  
object was specified.
```

**Cause:** You specified an alter or drop of synonym <name>, but a synonym of that name already exists.

**Effect:** The operation fails.

**Recovery:** Correct the syntax so that the correct <name> is used.

## 3.119. SQL 1160

A mismatch between the NOT DROPPABLE PRIMARY KEY constraint and the STORE BY clause was detected. When both clauses are specified, the STORE BY key column list must be the same as, or a prefix of , the PRIMARY KEY column list. This mismatch is caused by differences between the columns themselves, the order of columns, or the ASC/DESC attribute.

**Cause:** You attempted to create a table that contains both a NOT DROPPABLE PRIMARY KEY constraint and a STORE BY clause. The syntax specified is not correct. The STORE BY column list must be the same as, or a prefix of, the NOT DROPPABLE PRIMARY KEY column list.

**Effect:** The operation fails.

**Recovery:** If you want the STORE BY column list that specifies the clustering key to be different than the PRIMARY KEY, specify a DROPPABLE PRIMARY KEY. If you want the PRIMARY KEY to be the same as the STORE BY key, do not specify a STORE BY clause. Correct the syntax and resubmit.

## 3.120. SQL 1161

System generated column SYSKEY cannot be specified as part of the PARTITION BY clause.

**Cause:** Trafodion could not create the object because system-generated column SYSKEY is not allowed as part of the PARTITION BY clause.

**Effect:** The DDL operation fails.

**Recovery:** Remove the system added column SYSKEY from the PARTITION BY clause and retry the DDL statement.

## 3.121. SQL 1180

The required subvolume name for locations in schema <schema-name> is <directory-name>.

Where <schema-name> is the schema in which the object is being created.

Where <directory-name> is the designated subvolume name for that schema.

**Cause:** One or more LOCATION clauses in the CREATE or MODIFY statement contained a Trafodion platform location whose subvolume did not match the designated subvolume for the schema in which the object was being created.

**Effect:** The object was not created.

**Recovery:** Either correct the invalid LOCATION clauses or remove them and allow the system to generate the Trafodion platform locations.

## 3.122. SQL 1181

Label <file-name> could not be dropped. (file error <error>).

Where <file-name> is the name of the table, index, view, or routine being dropped.

Where <error> is the returned file system error number.

**Cause:** The object you attempted to drop resulted in file system error <error>.

**Effect:** The DDL DROP operation fails.

**Recovery:** See previous messages in this Trafodion database software operation to determine the necessary corrective actions. Also, use the file system error <error-number> to analyze the cause. For information about file system errors, see [File-System Errors](#). Fix the error and resubmit.

## 3.123. SQL 1182

```
Error <error> was returned by the file system on resource fork <file-name>.
```

Where <error> is the error returned.

Where <file-name> is the name of the file.

**Cause:** File system error.

**Effect:** The operation fails.

**Recovery:** For information about file system errors, see [File-System Errors](#).

## 3.124. SQL 1183

```
Error <error> was returned by the file system on metadata table <ANSI-name> (file name <file-name>).
```

Where <error> is the error returned.

Where <ANSI-name> is the metadata table.

Where <file-name> is the name of the file.

**Cause:** File system error.

**Effect:** The operation fails.

**Recovery:** For information about file system errors, see [File-System Errors](#).

## 3.125. SQL 1184

You do not have the required privilege(s) on <column-name>.

Where <column-name> is the name of a column specified in the references part of a referential integrity constraint.

**Cause:** You attempted to establish a referential integrity constraint on a column for which the executing user ID has no REFERENCES privileges.

**Effect:** The operation fails.

**Recovery:** Establish correct column privileges and resubmit.

## 3.126. SQL 1185

The location name is either invalid or missing.

**Cause:** A partition location is either invalid or missing.

**Effect:** The operation fails.

**Recovery:** Specify the correct location for all partitions involved in the affected command.

## 3.127. SQL 1186

Column <column-name> is of type <column-data-type> which is not compatible with the default value's type, <value-datatype>.

Where <column-name> is the name of the column that has an error.

Where <column-data-type> is the data type of <column-name>

Where <value-data-type> is the value specified as the default value for the column.

**Cause:** The value specified as the default for the column is incompatible with the type of the column.

**Effect:** The operation fails.

**Recovery:** Change either the column data type or the value for the default to be compatible types and resubmit.

## 3.128. SQL 1187

The schema name <schema-name> is reserved for Trafodion metadata.

Where <schema-name> is the name of a Trafodion database schema.

**Cause:** Trafodion reserves certain schema names for its own use.

**Effect:** The operation fails.

**Recovery:** See the [Trafodion SQL Reference Manual](#) for reserved schema names. Choose a name that is not reserved and reissue the CREATE statement.

## 3.129. SQL 1188

```
Referential integrity constraint <constraint-name> for table <table-name> could not be created due to circular dependency: <dependency-information>.
```

Where <constraint-name> is the name of a column constraint or table constraint. Where <table-name> is the name of the table specified in the operation.

Where <dependency-information> is a list of unique constraints that cause the circular dependency.

**Cause:** You tried to define a referential constraint that is creating a circular dependency, where one of the columns of the table is referencing a column that belongs to the same table, either directly or indirectly.

**Effect:** The operation fails.

**Recovery:** None. You cannot define a referential constraint that creates a circular dependency.

## 3.130. SQL 1224

```
An invalid data type was specified for routine parameter <parameter-name>.
```

Where <parameter-name> is the name of the parameter.

**Cause:** You specified a data type for this routine parameter that is not supported.

**Effect:** Trafodion is unable to complete the operation.

**Recovery:** Specify a different data type.

## 3.131. SQL 1225

Mixing EXECUTE with other privileges is not allowed.

**Cause:** EXECUTE and another privilege were specified in the same GRANT or REVOKE statement, which is not allowed.

**Effect:** The operation fails.

**Recovery:** Use separate GRANT or REVOKE statements for EXECUTE and other privileges.

## 3.132. SQL 1226

No valid combination of privileges was specified.

**Cause:** The GRANT or REVOKE statement did not specify a valid combination of privileges.

**Effect:** The operation fails.

**Recovery:** Specify a valid combination of privileges in the GRANT or REVOKE statement.

## 3.133. SQL 1231

```
User-defined routine <procedure-name> could not be created.
```

Where <procedure-name> is the stored procedure's ANSI name.

**Cause:** The stored procedure could not be created.

**Effect:** The CREATE PROCEDURE statement fails.

**Recovery:** Fix the error conditions identified in messages preceding this message and reissue the CREATE PROCEDURE statement.

## 3.134. SQL 1232

```
A file error occurred when saving dropped table DDL for table <table-name> to <path-name>.
```

Where <table-name> is the table being dropped whose DDL was to be saved.

Where <path-name> is the pathname of the file to which the DDL was to be saved.

**Cause:** A file system error occurred when you attempted to save a table DDL. Possible reasons are:

- The directory /usr/tandem/sqlmx/ddl did not exist or could not be created.
- The system did not have write access to /usr/tandem/sqlmx/ddl.
- Insufficient file space was available.

**Effect:** The table is not dropped.

**Recovery:** Either correct the file system problem and drop the table or perform a SHOWDDL on the existing table, capture the output, set SET SAVE\_DROPPED\_TABLE\_DDL to "OFF," and drop the table. For information about file system errors, see [File-System Errors](#).

## 3.135. SQL 1233

Creating schema in Trafodion system catalog <catalog-name> is prohibited.

Where <catalog-name> is the name of the Trafodion database catalog.

**Cause:** You attempted to create a schema in the system catalog.

**Effect:** The operation fails.

**Recovery:** Choose a different catalog name and reissue the CREATE statement.

## 3.136. SQL 1235

An invalid combination of EXTENT sizes and MAXEXTENTS was specified

for table or index <table-name>.

**Cause:** A CREATE or ALTER statement specified an invalid combination of EXTENT sizes and MAXEXTENTS.

**Effect:** The operation fails.

**Recovery:** Correct the error and retry the operation.

## 3.137. SQL 1236

The schema name specified for SQL object <object-name> is not valid. The schema name must be the same as the schema being created.

Where <object-name> is the name of the SQL object.

**Cause:** You specified a schema name for an object that is different from the name of the schema being created.

**Effect:** The operation fails.

**Recovery:** Specify a schema name for the object that matches the name of the schema being created.

## 3.138. SQL 1238

The character set for TRIGGER text must be ISO88591.

**Cause:** You specified a literal with a character set other than ISO88591 in the text of a create trigger statement.

**Effect:** The operation fails.

**Recovery:** Specify only ISO88591 literals in the command.

## 3.139. SQL 1239

The character set for string literals in VIEW text must be ISO88591.

**Cause:** You specified a literal with a character set other than ISO88591 in the text of a create view statement.

**Effect:** The operation fails.

**Recovery:** Specify only ISO88591 literals in the command.

## 3.140. SQL 1240

The character set for a PARTITION KEY column must be ISO88591.

**Cause:** You specified a literal with a character set other than ISO88591 as a partition key.

**Effect:** The operation fails.

**Recovery:** Specify only ISO88591 literals as partition keys.

## 3.141. SQL 1241

The character set for HEADING must be ISO88591.

**Cause:** You specified a literal with a character set other than ISO88591 in a HEADING clause.

**Effect:** The operation fails.

**Recovery:** Specify only ISO88591 literals in HEADING clauses.

## 3.142. SQL 1242

The character set for string literals in CONSTRAINT must be ISO88591.

**Cause:** You specified a literal with a character set other than

ISO88591 in the text of a constraint.

**Effect:** The operation fails.

**Recovery:** Specify only ISO88591 literals in constraints.

## 3.143. SQL 1243

The hexadecimal form of string literals is not allowed in this context.

**Cause:** You specified a hexadecimal literal in the text of the statement, which is not allowed.

**Effect:** The operation fails.

**Recovery:** Do not specify hexadecimals in this type of command.

## 3.144. SQL 1245

The supplied partition key value (<key-value>) for column <column-name> of object <object-name> is not valid.

Where <key-value> is the specified first key value.

Where <column-name> is the column of <object-name> that corresponds to the invalid key value.

Where <object-name> is the name of the affected object.

**Cause:** A utility command specified an invalid key value.

**Effect:** The operation fails.

**Recovery:** Specify valid key values and resubmit.

## 3.145. SQL 1246

The supplied partition key value (<key-value>) is inconsistent

with the data type of column <column-name> of object <object-name>.

Where <key-value> is the specified first key value.

Where <column-name> is the column of <object-name> that corresponds to the invalid key value.

Where <object-name> is the name of the affected object.

**Cause:** A utility command specified a key value that is inconsistent with the data type of the column that corresponds to the key value.

**Effect:** The operation fails.

**Recovery:** Specify valid key values and resubmit.

## 3.146. SQL 1248

Partition name <partition-name> has already been used. Each partition in an object should have a unique name.

Where <partition-name> is the name specified for a partition.

**Cause:** Partition names are required to be unique within the set of partitions of an object.

**Effect:** The CREATE statement fails.

**Recovery:** Choose a name that is not the same as any other partition name in this object and reissue the CREATE statement.

## 3.147. SQL 1250

DROP cannot be performed on object <object-name> because a utility operation (<operation-type>) associated with DDL\_LOCK <lock-name> is currently running.

Where <object-name> is the ANSI name of the object named in the DROP command.

Where <operation-type> is the type of utility operation.

Where <lock-name> is the ANSI name of the DDL lock object that is associated with the utility operation.

**Cause:** You attempted to drop an object that a utility command is using.

**Effect:** The operation fails.

**Recovery:** Wait until the utility operation has finished, and then retry the DROP operation.

## 3.148. SQL 1251

The extra insignificant digits of default value <value> are truncated to match the scale of the data type of column <column-name>.

Where <value> is the default value that was specified for <column-name>.

Where <column-name> is the name of the column in the table.

**Cause:** A CREATE TABLE or ALTER TABLE . . . ADD COLUMN specified a default value with a scale greater than the scale of the column.

**Effect:** The scale of the default value is set to that of the column; extra digits to the right are discarded.

**Recovery:** None. This is a warning message only.

## 3.149. SQL 1252

The existing index <index-name> to be used by a unique or primary constraint has not been populated. Please populate the index and then try to add the constraint again.

Where <index-name> is the name of an existing unpopulated index.

**Cause:** An existing index that is not populated has been chosen for a unique or primary constraint, which is not allowed.

**Effect:** The operation fails.

**Recovery:** Populate the index and resubmit.

## 3.150. SQL 1254

Duplicate unique constraints are not allowed with same set of columns.

**Cause:** You attempted to specify both the unique and primary key constraints or multiple unique constraints on the same set of columns, which is not allowed.

**Effect:** The operation fails.

**Recovery:** Change your query so that both unique and primary constraints or multiple unique constraints are not specified on the same set of columns.

## 3.151. SQL 1262

The command cannot be executed because <operation> is in progress for <schema>.

Where <operation> is a schema-level operation.

Where <schema> is the ANSI name of the affected schema.

**Cause:** You attempted a DDL or utility operation on a database object while <operation> was in progress for that object's <schema>.

**Effect:** The DDL or utility operation fails.

**Recovery:** Wait until the operation has finished, and then retry the DDL or utility operation.

## 3.152. SQL 1263

Table, view, and stored procedure names that start with <text> are reserved for Trafodion metadata.

Where <text> is the disallowed name that was specified.

**Cause:** You specified a Trafodion database reserved object name.

**Effect:** The object is not created.

**Recovery:** See the *Trafodion SQL Reference Manual* for the list of reserved object names. Choose a name that is not reserved and reissue the CREATE statement.

## 3.153. SQL 1264

Duplicate privileges are not allowed in a GRANT or REVOKE statement.

**Cause:** You specified duplicate privileges in a GRANT or REVOKE statement.

**Effect:** The operation fails.

**Recovery:** Reissue the GRANT or REVOKE statement, specifying a single privilege or a list of distinct privileges.

## 3.154. SQL 1265

Duplicate grantees not allowed in a GRANT or REVOKE statement.

**Cause:** You specified duplicate grantees in a GRANT or REVOKE statement.

**Effect:** The operation fails.

**Recovery:** Reissue the GRANT or REVOKE statement specifying a single grantee or a list of distinct grantees.

## 3.155. SQL 1266

Only EXECUTE privilege is supported for a procedure or routine.

**Cause:** You specified an unsupported privilege on a procedure or routine in a GRANT statement.

**Effect:** The operation fails.

**Recovery:** Reissue the GRANT statement specifying the valid privilege for the procedure or routine.

## 3.156. SQL 1267

EXECUTE privilege is incompatible with this object type.

**Cause:** You specified a privilege that is not supported for the object type in a GRANT statement.

**Effect:** The operation fails.

**Recovery:** Reissue the GRANT statement specifying the valid privilege for the object type.

## 3.157. SQL 1268

Duplicate columns are not allowed in a GRANT or REVOKE statement.

**Cause:** You specified duplicate column names with the update or references privilege in a GRANT or REVOKE statement.

**Effect:** The operation fails.

**Recovery:** Correct the GRANT or REVOKE statement by specifying a single column name or a list of distinct column names.

## 3.158. SQL 1270

ALLOCATE or DEALLOCATE failed for object <sql-object-name> due to file error <file-system-error-number> on <file-name>.

Where <sql-object-name> is the ANSI name of the affected SQL database object.

Where <file-system-error-number> is a Trafodion platform file system error code.

**Cause:** A CREATE or ALTER operation encountered a file system error <error-number> during processing of the ALLOCATE or DEALLOCATE attribute.

**Effect:** The operation fails.

**Recovery:** For information about file system errors, see <file-system-errors,File-System Errors>.

## 3.159. SQL 1271

```
ALLOCATE failed for object <object-name> because extents to be allocated <number> is greater than the MAXEXTENTS for a partition of the object.
```

Where <object-name> is the ANSI name of the affected database object.

Where <number> is the specified number of extents.

**Cause:** A CREATE or ALTER operation specified an ALLOCATE attribute value that was greater than the MAXEXTENTS value for the affected database object, which is not allowed.

**Effect:** The operation fails.

**Recovery:** If possible, alter the MAXEXTENTS attribute value to be greater than the

desired number of extents to be allocated. The current maximum value for MAXEXTENTS is 768.

## 3.160. SQL 1273

```
The specified MAXEXTENTS value must be greater than the number of extents allocated.
```

**Cause:** The value that you specified to change MAXEXTENTS is less than or equal to the allocated extents.

**Effect:** The operation fails.

**Recovery:** Use a MAXEXTENTS value greater than the allocated extents.

## 3.161. SQL 1274

The specified or default MAXEXTENTS value is not sufficient. The MAXEXTENTS value has been automatically set to the new value of <value> for the file <file-name>.

**Cause:** You specified an insufficient MAXEXTENTS value while creating an index.

**Effect:** The SQL operation completed with a warning.

**Recovery:** This is a warning only.

## 3.162. SQL 1275

Constraint <constraint-1> cannot be dropped because it is needed by unique constraint <constraint-2>.

Where <constraint-1> is the constraint you are trying to drop.

Where <constraint-2> is the UNIQUE constraint.

**Cause:** You attempted to drop a constraint that is needed by a UNIQUE constraint, which is not allowed because it would leave a UNIQUE constraint on a column, but without a NOT NULL constraint for that column.

**Effect:** The operation fails.

**Recovery:** To drop the constraint, you must remove the UNIQUE constraint or add an additional NOT NULL constraint to the columns that contain UNIQUE constraints and only one NOT NULL constraint for that column.

## 3.163. SQL 1277

```
Unrecognized partitioning scheme for object <object-name>.
```

<object-name> is the name of the SQL object (table or index).

**Cause:** The Trafodion database does not recognize the partitioning scheme stored in the metadata for the named object.

**Effect:** The named object is considered corrupt and is inaccessible.

**Recovery:** None. Contact the Trafodion User Distribution List Consider running the VERIFY operation on the named object to check for inconsistencies in the metadata with respect to the partitioning scheme.

## 3.164. SQL 1278

```
The command cannot be executed because <operation> is in progress for all schemas in catalog <catalog>.
```

<operation> is a schema level operation, currently UPGRADE or DOWNGRADE, that uses the ALL SCHEMAS IN CATALOG flavor. <catalog> is a catalog name that is affected by <operation>.

**Cause:** An attempt was made to execute a DDL or utility operation that affected <catalog>, or a schema in that catalog.

**Effect:** The operation fails.

**Recovery:** Wait until <operation> is finished, then retry the failed DDL or utility operation.

## 3.165. SQL 1301

NO ACTION referential action for <referential-triggered-action> clause is not yet supported as specified by ANSI SQL-99 standard. To alter the behavior, set an appropriate value for the REF\_CONSTRAINT\_NO\_ACTION\_LIKE\_RESTRICT default.

Where <referential-triggered-action> can either be ON DELETE or ON UPDATE.

**Cause:** NO ACTION referential action is specified in the referential integrity definition, and the CONTROL QUERY DEFAULT value for REF\_CONSTRAINT\_NO\_ACTION\_LIKE\_RESTRICT is 'OFF.'

**Effect:** The NO ACTION referential action cannot be defined.

**Recovery:** To alter the behavior of NO ACTION referential action, set the appropriate value for the REF\_CONSTRAINT\_NO\_ACTION\_LIKE\_RESTRICT default.

## 3.166. SQL 1302

NO ACTION referential action for <referential-triggered-action> clause behaves like RESTRICT referential action. To alter the behavior, set the appropriate value for the REF\_CONSTRAINT\_NO\_ACTION\_LIKE\_RESTRICT default.

Where <referential-triggered-action> can either be ON DELETE or ON UPDATE.

**Cause:** NO ACTION referential action is specified in the referential definition and the CONTROL QUERY DEFAULT value for REF\_CONSTRAINT\_NO\_ACTION\_LIKE\_RESTRICT is 'SYSTEM.'

**Effect:** The NO ACTION referential action has RESTRICT referential action semantics. It is recorded as NO ACTION in the metadata table.

**Recovery:** To alter the behavior of the NO ACTION referential action, set the appropriate value for the REF\_CONSTRAINT\_NO\_ACTION\_LIKE\_RESTRICT default.

## 3.167. SQL 1305

The specified schema location <directory> is already in use by schema <schema>.

Where <directory> is the Trafodion platform subvolume name specified in the LOCATION clause of the CREATE SCHEMA command.

Where <schema> is the ANSI name of an existing schema that already uses <directory> as a schema subvolume.

**Cause:** In a CREATE SCHEMA command, you specified <directory> in the LOCATION clause; however, this subvolume is already being used as schema subvolume by <schema>.

**Effect:** The statement fails unless it includes the optional REUSE clause to allow reuse of the same schema subvolume name. If the REUSE clause is used, this is a warning message and the schema is created successfully. The warning can be issued repeatedly for a single CREATE SCHEMA command if multiple schemas already exist with <directory> as the schema subvolume.

**Recovery:** Only schemas that are RDF replicated to another node should have the same subvolume names as their corresponding schemas on the other node. To create these, use the optional REUSE clause in the CREATE SCHEMA statement. All other schemas should have unique subvolume names. Schemas that are, or will be, related as RDF primary and backup schemas must have identical schema names and subvolumes on the primary and backup nodes.

## 3.168. SQL 1307

The schema location <directory> is reserved for Trafodion metadata.

Where <directory> is the Trafodion platform subvolume name specified in the LOCATION clause of the CREATE SCHEMA command.

**Cause:** In a CREATE SCHEMA command, you specified subvolume in the LOCATION clause, however subvolume names with the format ZSD<digit><anything> are reserved for Trafodion database software metadata schemas.

**Effect:** The operation fails.

**Recovery:** Specify a subvolume name using the format ZSD<letter><anything> in the LOCATION clause, and resubmit.

## 3.169. SQL 1309

Object type for <object-name> is not valid for the current operation.

Where <object-name> is the name of the object.

**Cause:** You specified an object for an SQL operation that does not support its object type.

**Effect:** The operation fails.

**Recovery:** Specify an object of valid object type and retry the operation.

## 3.170. SQL 1310

The CREATE SCHEMA statement does not support the creation of triggers.

**Cause:** You specified creation of triggers in the CREATE SCHEMA statement.

**Effect:** The operation fails.

**Recovery:** Remove the creation of triggers from the CREATE SCHEMA statement and resubmit. Create triggers in separate statements.

## Chapter 4. Trafodion Compiler Messages (2000 through 2999)

This section includes process creation errors, IPC errors, static compilation errors, and miscellaneous errors from the optimizer.

### 4.1. SQL 2004

```
Internal error: error from MXCMP; cannot work on this query.
```

**Cause:** Trafodion received an internal error from the Trafodion compiler.

**Effect:** The operation fails.

**Recovery:** None. Report the entire message to [the Trafodion User mailing list](#).

### 4.2. SQL 2009

```
The user transaction must be rolled back (or committed, if that makes sense in the application) before MXCMP can be restarted and proceed.
```

**Cause:** An outstanding transaction must be resolved before the Trafodion compiler can be restarted.

**Effect:** The operation fails.

**Recovery:** None.

## 4.3. SQL 2011

```
Server process could not be created - error <number> while resolving program file name  
<name>.
```

Where error <number> is the error number.

Where <name> is the name of the program file.

**Cause:** Trafodion was unable to create a server process because of the process control procedure error <number> it received while resolving the program file name.

**Effect:** The operation fails.

**Recovery:** Use the process control procedure error to diagnose and correct the problem.

## 4.4. SQL 2012

```
Server process <name> could not be created - error <number> <number-1>, TPCError =  
<number-2>, error detail = <text>.
```

Where <name> is the name of the server process.

Where <number-1> is the error number.

Where <number-2> is the TPCError.

Where <text> is the error message text.

**Cause:** Trafodion was unable to create server process <name> because of the process control procedure error <number> it received. More information appears in detail <text>.

**Effect:** The operation fails.

**Recovery:** Use the process control procedure error to diagnose and correct the problem.

## 4.5. SQL 2013

```
Server process <name> could not be created - error <number> on program file.
```

Where <name> is the name of the server process.

Where <number> is the error number.

**Cause:** Trafodion was unable to create server process <name> because of the process control procedure error <number> it received on the program file.

**Effect:** The operation fails.

**Recovery:** Use the process control procedure error to diagnose and correct the problem.

## 4.6. SQL 2014

```
Server process <name> could not be created - error <number> on swap file.
```

Where <name> is the server process name.

Where <number> is the error number.

**Cause:** Trafodion was unable to create server process <name> because of the process control procedure error <number> it received on the swap file.

**Effect:** Trafodion does not create the server process.

**Recovery:** Use the process control procedure error to diagnose and correct the problem.

## 4.7. SQL 2020

Server process <name> could not be created - unlicensed privileged program.

Where <name> is the server process name.

**Cause:** Trafodion was unable to create server process <name> because it is an unlicensed privileged program. The server process was configured incorrectly at installation.

**Effect:** The operation fails.

**Recovery:** The server process must be a licensed privileged program. Check your configuration.

## 4.8. SQL 2029

The new min value is greater than the current max value <number>.

Where <number> is the current maximal value.

**Cause:** The new minimal value is greater than the current maximal value.

**Effect:** The new minimal value is not set.

**Recovery:** Specify a new minimal value that is less than the current maximal value or specify a new maximal value that is greater than the new minimal value.

## 4.9. SQL 2030

```
The new max value is less than the current min value <number>.
```

Where <number> is the current minimal value.

**Cause:** The new maximal value is smaller than the current minimal value.

**Effect:** The new maximal value is not set.

**Recovery:** Specify a new maximal value that is greater than the current minimal value.

## 4.10. SQL 2033

```
<process-id>: Error <number> while communicating with process <name>.
```

Where <process-id> identifies the process.

Where <number> is the error number.

Where <name> is the name of the server process.

**Cause:** The Trafodion database <process-id> received process control procedure error <number> while communicating with the server process <name>.

**Effect:** Trafodion is not able to communicate with the process.

**Recovery:** Use the process control procedure error to diagnose and correct the problem.

## 4.11. SQL 2034

```
<process-id>: Error <number> while communicating with server process <name>.
```

Where `<process-id>` identifies the process.

Where `<number>` is the error number.

Where `<name>` is the name of the server process.

**Cause:** The Trafodion database `<process-id>` received process control procedure error `<number>` while communicating with server process `<name>`.

**Effect:** Trafodion process is not able to communicate with the server process.

**Recovery:** Use the process control procedure error to diagnose and correct the problem.

## 4.12. SQL 2035

```
<process-id>: Open of process <name> failed - error = <number>.
```

Where `<process-id>` identifies the process.

Where `<name>` is the name of the server process.

Where `<number>` is the error number.

**Cause:** The Trafodion database `<process-id>` was unable to open server process `<name>` because of the operating system error `<number>` it received.

**Effect:** The operation fails.

**Recovery:** Use the operating system error to diagnose and correct the problem.

## 4.13. SQL 2038

```
Character set <name> is not supported for SQLCI attribute TERMINAL_CHARSET.
```

Where <name> is the name of the character set.

**Cause:** You specified a non-ISO88591 character set name.

**Effect:** The operation fails.

**Recovery:** Specify an ISO88591 character set name.

## 4.14. SQL 2050

```
<attribute> is not the name of any DEFAULTS table attribute.
```

Where <attribute> is the attribute name you specified.

**Cause:** If the SQLSTATE is 42000, this is an error. You attempted to set a CONTROL QUERY DEFAULT setting, but the <attribute> name you specified is not valid. If the SQLSTATE is 01000, this is a warning. In an earlier Trafodion database session, you inserted a row into a DEFAULTS table whose <attribute> column value is invalid.

**Effect:** If this is an error, the operation fails. If this is a warning, this is an informational message.

**Recovery:** Correct the attribute name and resubmit.

## 4.15. SQL 2051

```
Either <control-option-name> or value '<value>' is not valid.
```

**Cause:** You specified an invalid <control-option name> or a valid option with an invalid <value>.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 4.16. SQL 2053

```
Optimizer pass two assertion failure (<failure-text>) in file <filename> at line <line-num>.
```

**Cause:** This is an informational message that is a result of the two-pass mechanism of the optimizer. The optimizer created a simple plan, and then while refining that plan, an internal error occurred, so the simple plan was not improved. The simple plan is still valid and will work.

**Effect:** Your query will use the original, simple plan.

**Recovery:** Informational message only; no corrective action is needed. This message will be accompanied by an assertion failure message and, possibly, CONTROL QUERY SHAPE information. However, report the entire message, and the preceding assertion failure message, to [the Trafodion User mailing list](#).

This additional information will also be helpful: the DDL for the tables involved, the query that produced this warning, and any CONTROL QUERY SHAPE and CONTROL QUERY DEFAULT settings in effect when the error occurred.

## 4.17. SQL 2054

HIST\_NO\_STATS\_ROWCOUNT should always be greater than or equal to CQD HIST\_NO\_STATS\_UEC. Present value of HIST\_NO\_STATS\_UEC is '<value>'.

**Cause:** You attempted to set the CQD HIST\_NO\_STATS\_ROWCOUNT value as less than the current value of CQD HIST\_NO\_STATS\_UEC.

**Effect:** The current value of the HIST\_NO\_STATS\_ROWCOUNT is retained.

**Recovery:** Set the value of CQD HIST\_NO\_STATS\_ROWCOUNT greater than or equal to the value of HIST\_NO\_STATS\_UEC. If you want to use a smaller value, reduce the value of CQD HIST\_NO\_STATS\_UEC first. Note that any change in either of the two values can have an effect on the plan quality.

## 4.18. SQL 2055

The specified value '<value>' for DEFAULTS attribute <name> is not valid.

**Cause:** You specified an invalid value for the DEFAULTS attribute listed in the message.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 4.19. SQL 2056

The value must be a number in the range <value>.

**Cause:** You specified a value outside of the allowed range <value>.

**Effect:** The operation fails.

**Recovery:** Enter a valid value and resubmit.

## 4.20. SQL 2057

The value must be a multiple of <value>.

**Cause:** You specified an invalid value for an attribute. It must be a multiple of <value>.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 4.21. SQL 2058

```
DEFAULTS attribute <name> is of type <data-type> but is being converted to <data-type>.
```

Where <name> is the DEFAULTS attribute name.

Where <data-type> is the attribute name value.

**Cause:** You specified a DEFAULTS attribute name value of <data-type>, which is not supported. The item is being converted to <data-type>, which is supported.

**Effect:** Because of the conversion, the actual value used might be truncated or rounded.

**Recovery:** Specify the value using the expected type, if appropriate.

## 4.22. SQL 2059

```
Errors or warnings occurred while reading values from DEFAULTS table <name>.
```

Where <name> is the name of the table.

**Cause:** You received an error on the DEFAULTS table <name>. A previous error message has appeared with specific information.

**Effect:** The operation fails.

**Recovery:** None.

## 4.23. SQL 2060

Procedure <name> has already been defined in this module. The previous definition is being retained and this latest one ignored.

Where <name> is the procedure name.

**Cause:** You defined procedure <name> twice in this module.

**Effect:** Trafodion uses the first definition.

**Recovery:** This is an informational message only; no corrective action is needed.

## 4.24. SQL 2061

Static cursor <name> has already been defined in this module. The previous definition, as a static cursor, is being retained and this latest one ignored.

Where <name> is the cursor name.

**Cause:** You defined the static cursor <name> twice in this module.

**Effect:** Trafodion uses the first static cursor definition.

**Recovery:** This is an informational message only; no corrective action is needed.

## 4.25. SQL 2062

Static cursor <name> has already been defined in this module. The previous definition, as a dynamic cursor, is being retained and this latest one ignored.

Where <name> is the cursor name.

**Cause:** You defined the static cursor <name> twice in this module.

**Effect:** Trafodion uses the first dynamic cursor definition.

**Recovery:** This is an informational message only; no corrective action is needed.

## 4.26. SQL 2063

Dynamic cursor <name> has already been defined in this module. The previous definition, as a static cursor, is being retained and this latest one ignored.

Where <name> is the cursor name.

**Cause:** You defined the dynamic cursor <name> twice in this module.

**Effect:** Trafodion uses the first static cursor definition.

**Recovery:** This is an informational message only; no corrective action is needed.

## 4.27. SQL 2064

Dynamic cursor <name> has already been defined in this module. The previous definition, as a dynamic cursor, is being retained and this latest one ignored.

Where <name> is the cursor name.

**Cause:** You defined the dynamic cursor <name> twice in this module.

**Effect:** Trafodion uses the first dynamic cursor definition.

**Recovery:** This is an informational message only; no corrective action is needed.

## 4.28. SQL 2065

Statement <name> was not found in module <name>.

Where <name> is the statement name.

Where <name> is the module name.

**Cause:** Trafodion could not find statement <name> in module <name>.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 4.29. SQL 2066

```
Cursor <name> was not found in module <name>.
```

Where `<name>` is the cursor name.

Where `<name>` is the module name.

**Cause:** Trafodion could not find cursor `<name>` in module `<name>`.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 4.30. SQL 2067

```
Descriptor <name> has already been defined in this module. The previous definition is  
being retained and this latest one ignored.
```

Where `<name>` is the descriptor name.

**Cause:** You defined the descriptor `<name>` twice in this module.

**Effect:** Trafodion uses the first definition.

**Recovery:** Informational message only; no corrective action is needed.

## 4.31. SQL 2068

A procedure body must be a SELECT, INSERT, UPDATE, DELETE, DECLARE CATALOG, DECLARE SCHEMA, or a static DECLARE CURSOR.

**Cause:** You specified a procedure whose body is invalid. It must be a SELECT, INSERT, UPDATE, DELETE, DECLARE CATALOG, DECLARE SCHEMA, or static DECLARE CURSOR.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 4.32. SQL 2069

A static cursor declaration may appear only in the body of a procedure.

**Cause:** You specified a static cursor declaration that is outside the body of a procedure. It should appear only in the body of a procedure.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 4.33. SQL 2070

Statement is not valid in this context.

**Cause:** In a module definition file, you specified a query statement such as SELECT, INSERT, UPDATE, DELETE, or a DDL statement. These statements must be embedded in procedures.

**Effect:** Trafodion is unable to compile the module.

**Recovery:** Correct the syntax and resubmit.

## 4.34. SQL 2071

The name <name> has already been declared or defined in this module. The previous definition, as a <definition-type>, is being retained and this latest one ignored.

Where <name> is the name of the module.

Where <definition-type> is the previous definition

**Cause:** You defined <name> twice in this module in which it was defined as a type *definition type*.

**Effect:** Trafodion uses the previous definition.

**Recovery:** Specify a new name for the item and resubmit, if necessary.

## 4.35. SQL 2072

A simple value specification that is a literal is not yet supported.

**Cause:** You specified a simple value as a literal, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 4.36. SQL 2073

Only super ID user can compile system module <name>.

Where <name> is the name of the module.

**Cause:** You attempted to compile a system module that can be compiled only by the super ID.

**Effect:** The operation fails and is unable to compile the entire module correctly.

**Recovery:** None. Use a different name for your module and recompile.

## 4.37. SQL 2074

The name <name> is reserved for future system modules.

Where <name> is the name of the module.

**Cause:** You attempted to use a name that is reserved for future system modules.

**Effect:** The operation fails and is unable to compile the entire module correctly.

**Recovery:** None. Use a different name for your module and recompile.

## 4.38. SQL 2075

The -a <application-name> option is not allowed for system module

compilation

**Cause:** You specified mxcmp -a <application-name> system-module-definition-file, which is not supported.

**Effect:** The operation fails.

**Recovery:** Delete the -a <application-name> and retry the mxcmp systemmodule-definition-file command.

## 4.39. SQL 2076

```
HIST_NO_STATS_UEC should always be less than or equal to CQD HIST_NO_STATS_ROWCOUNT.  
Present value of HIST_NO_STATS_ROWCOUNT is 'value'.
```

**Cause:** You attempted to set the CQD HIST\_NO\_STATS\_UEC value as greater than the current value of CQD HIST\_NO\_STATS\_ROWCOUNT.

**Effect:** The current value of the HIST\_NO\_STATS\_UEC is retained.

**Recovery:** Set the value of CQD HIST\_NO\_STATS\_UEC less than or equal to the value of HIST\_NO\_STATS\_ROWCOUNT. If you want to use a larger value, increase the value of CQD HIST\_NO\_STATS\_ROWCOUNT first. Note that any change in either of the two values can have an effect on the plan quality.

## 4.40. SQL 2080

```
Error <number> while reading file: <value> bytes were read from <text> when <value>  
were expected in module <name>.
```

**Cause:** Trafodion received error <number> while reading module <name>. <value> shows the number of bytes read from <text>. The module file is unusable. Either it has been corrupted or overwritten.

**Effect:** The operation fails.

**Recovery:** Recompile the module definition file, using the Trafodion compiler, to create a valid module file.

## 4.41. SQL 2081

```
Error <number> while opening file <name> for read.
```

Where <number> is the error number.

Where <name> is the name of the file.

**Cause:** Trafodion received error <number> while opening file <name> for read.

**Effect:** Trafodion does not open the file.

**Recovery:** Use the error number to diagnose and correct the problem.

## 4.42. SQL 2082

```
Error <number> while opening file <name> for write.
```

Where <number> is the error number.

Where <name> is the name of the file.

**Cause:** Trafodion received error <number> while opening file <name> for write.

**Effect:** Trafodion does not open the file.

**Recovery:** Use the error number to diagnose and correct the problem.

## 4.43. SQL 2083

```
Error <number> while naming or locating file <name>.
```

Where <number> is the error number.

Where <name> is the name of the file.

**Cause:** Trafodion received error <number> while naming or locating file <name>.

**Effect:** Trafodion does not name or locate the file.

**Recovery:** Use the error to diagnose and correct the problem.

## 4.44. SQL 2084

```
Error <number> while writing <value> bytes to file <name>.
```

**Cause:** Trafodion database software received error <number> while writing to file <name>. <value> shows the number of bytes being written.

**Effect:** Trafodion does not open the file.

**Recovery:** Use the error to diagnose and correct the problem.

## 4.45. SQL 2085

```
Error <number> was returned when closing file <name>.
```

Where <number> is the error number.

Where <name> is the name of the file.

**Cause:** Trafodion received error <number> when closing file <name>.

**Effect:** Trafodion does not close the file.

**Recovery:** Use the error number to diagnose and correct the problem.

## 4.46. SQL 2086

```
The file <name> could not be purged. This file contains the results of a failed compilation and should be purged.
```

Where <name> is the name of the file.

**Cause:** A compilation failed, and for some reason Trafodion database software was not able to purge the module file.

**Effect:** The module file is not valid and should not be used.

**Recovery:** Purge the file from the Trafodion platform.

## 4.47. SQL 2090

The command line argument for module name, <name-1>, is being ignored in favor of module name <name-2> in file <name-3>.

Where <name-1>, <name-2>, and <name-3> are module file names.

**Cause:** Trafodion ignored the command line argument for module <name-1>. Instead, it used the second module <name-2> in file <name-3>.

**Effect:** None.

**Recovery:** None.

## 4.48. SQL 2091

The required module statement was not found in file <name>.

Where <name> is the name of the file.

**Cause:** Trafodion could not find the required module statement in file <name>.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 4.49. SQL 2092

A module statement has already appeared in this file. The previous definition, <name>, is being retained and this latest one ignored.

Where <name> is the name of the file.

**Cause:** You included more than one module statement. <name> will be used.

**Effect:** Trafodion ignores the second module statement.

**Recovery:** Informational message only; no corrective action is needed.

## 4.50. SQL 2093

A module timestamp statement was not found in file <name>.

Where <name> is the name of the file.

**Cause:** Trafodion did not find a module timestamp statement in the module definition file <name>.

**Effect:** Trafodion uses a default timestamp value of all zeros.

**Recovery:** Supply a timestamp and resubmit.

## 4.51. SQL 2094

A module timestamp statement has already appeared in this module. The previous timestamp is being retained and this latest one ignored.

**Cause:** You specified a timestamp statement twice in this module.

**Effect:** Trafodion uses the first timestamp.

**Recovery:** Informational message only; no corrective action is needed.

## 4.52. SQL 2095

Module file <name-1>, expected to contain module <name-2>, instead contains <name-3>.

Where <name-1>, <name-2>, and <name-3> are module file names.

**Cause:** Trafodion expected to find the first module <name-1>, but instead found the second module <name-2>, in file <name-3>.

**Effect:** Only the second module is compiled.

**Recovery:** None.

## 4.53. SQL 2096

A source file statement has already appeared in this module. The previous source file is being retained and this latest one ignored.

**Cause:** The Trafodion compiler was invoked on a module definition file that contains more than one SOURCE\_FILE statement. A module definition can have only one SOURCE\_FILE statement that specifies that module's SQL source file.

**Effect:** The operation fails.

**Recovery:** Edit the module definition file so that it contains no more than one SOURCE\_FILE statement, and rerun the Trafodion compiler on the module definition.

## 4.54. SQL 2097

Source file name is over 1024 characters long.

**Cause:** The Trafodion compiler was invoked on a module definition file that contains a SOURCE\_FILE statement whose *source path name* has over 1024 characters.

**Effect:** The operation fails.

**Recovery:** Edit the module definition file so that its SOURCE\_FILE statement's *source path name* is no more than 1024 characters long. Rerun the Trafodion compiler on the module definition file.

## 4.55. SQL 2098

The <compilation-type> compilation completed with <value> warnings.

**Cause:** <compilation-type> completed with the number of warnings given as <value>.

**Effect:** None.

**Recovery:** Informational message only; no corrective action is needed.

## 4.56. SQL 2099

The <compilation-type> compilation failed with <value> errors and <value> warnings.

**Cause:** <compilation-type> failed with the number of errors and warnings given as <value>.

**Effect:** Any statement with an error is not compiled.

**Recovery:** If this is a warning, this is an informational message. Otherwise, correct the syntax and resubmit.

## 4.57. SQL 2100

Break was received. The compilation has been aborted.

**Cause:** Trafodion received a break and aborted the compilation.

**Effect:** Trafodion does not continue compilation.

**Recovery:** Informational message only; no corrective action is needed.

## 4.58. SQL 2102

This query could not be compiled with 'MINIMUM' optimization level. Suggestion: Retry with 'MEDIUM' optimization level.

**Cause:** Trafodion was unable to compile this query using the MINIMUM optimization level.

**Effect:** Trafodion is unable to process this query.

**Recovery:** Resubmit the query with MEDIUM optimization level. Precede the statement with: CONTROL QUERY DEFAULT OPTIMIZATION-LEVEL 'MEDIUM';

## 4.59. SQL 2103

This query could not be compiled for one/both of the following reasons: a) Use of 'MINIMUM' optimization level, or b) incompatible Control Query Shape specifications.

**Cause:** Trafodion was unable to compile this query, either because it was not able to use the MINIMUM optimization level or because you used an incompatible CONTROL QUERY SHAPE specification.

**Effect:** Trafodion is unable to process this query.

**Recovery:** If applicable, resubmit the query with MINIMUM optimization level. Precede the statement with:

CONTROL QUERY DEFAULT OPTIMIZATION-LEVEL 'MEDIUM'; Correct the CONTROL QUERY SHAPE specification and resubmit.

## 4.60. SQL 2104

This query could not be compiled for one of two reasons: a) incompatible Control Query Shape (CQS) specifications, or b) 'MEDIUM' optimization level is not sufficient to satisfy the CQS in effect. Suggestion: a) inspect the CQS in effect; or b) raise the optimization level to 'MAXIMUM'. Note that for this query, 'MAXIMUM' optimization level may result in a long compile time.

**Cause:** Trafodion was unable to compile this query, either because it was not able to use the MEDIUM optimization level or because you used an incompatible CONTROL QUERY SHAPE specification.

**Effect:** Trafodion is unable to process this query.

**Recovery:** If applicable, use the MAXIMUM optimization level, correct the CONTROL QUERY SHAPE specification, and resubmit.

## 4.61. SQL 2105

This query could not be compiled because of incompatible Control Query Shape (CQS) specifications. Inspect the CQS in effect.

**Cause:** Trafodion was unable to compile this query because you used an incompatible CONTROL QUERY SHAPE specification.

**Effect:** Trafodion is unable to process this query.

**Recovery:** Correct the CONTROL QUERY SHAPE specification and resubmit.

## 4.62. SQL 2106

This statement could not be compiled since it is too long. Break up large statements into smaller pieces.

**Cause:** Trafodion was unable to compile this query because it is too long.

**Effect:** Trafodion is unable to process this query.

**Recovery:** Try breaking the statement into smaller pieces.

## 4.63. SQL 2107

This statement could not be compiled. Suggestion: Address the issue(s) raised in the reported warning(s).

**Cause:** Trafodion was unable to compile the query.

**Effect:** The operation fails.

**Recovery:** Use the warning messages returned by the compiler to diagnose and correct the problem.

## 4.64. SQL 2108

Statement was compiled as if query plan caching were off.

**Cause:** Trafodion attempted to compile this query with query caching on but failed. It then successfully compiled this query with caching turned off.

**Effect:** Trafodion compiled the query as if query plan caching was turned off even though caching is currently on. The prepared query can be executed as usual.

**Recovery:** This is an informational message. To prevent this warning, turn off query caching before query preparation.

## 4.65. SQL 2200

```
DEFAULTS attribute <attribute> is read-only.
```

Where <attribute> is the DEFAULTS attribute.

**Cause:** You attempted to change the DEFAULTS <attribute>, which is read-only.

**Effect:** The operation fails.

**Recovery:** None.

## 4.66. SQL 2201

```
SQL compilation return code is <mxcmp-non-zero-exit-code>.
```

**Cause:** You invoked mxCompileUserModule on an application file that has an embedded module definition. An SQL compilation of an embedded module definition resulted in a Trafodion compiler nonzero exit code, indicating a warning or error.

**Effect:** The operation fails.

**Recovery:** Review the Trafodion compiler warning or error message. Trace the diagnostic back to the module source file and correct the offending source statement. Retry preprocessing, translating, compiling, and SQL compiling the application file.

## 4.67. SQL 2202

```
<application-file> is not an application (ELF or SQL) file.
```

**Cause:** You invoked mxCompileUserModule on an application file that is not a Trafodion platform ELF object file.

**Effect:** The operation fails.

**Recovery:** Verify that the name <application-file> is an ELF object file. Verify that the name of <application-file> is spelled correctly, and retry the command.

## 4.68. SQL 2203

```
Application file <application-pathname> cannot be opened.
```

**Cause:** You invoked mxCompileUserModule (or mxcmp -a <application-pathname> mdf) on an application that does not exist or is inaccessible to the user.

**Effect:** The operation fails.

**Recovery:** Verify that <application-pathname> exists and is readable by the user. Verify that <application-pathname> is spelled correctly, and retry the command.

## 4.69. SQL 2204

```
SQL compilation of <module-name> failed.
```

Where <module-name> is the name of the module.

**Cause:** You invoked mxCompileUserModule on an application file that has embedded module definition(s). The SQL compilation of the named embedded module definition produced a Trafodion compiler warning or error.

**Effect:** The operation fails.

**Recovery:** Review the Trafodion compiler warning or error. Trace the diagnostic back to the source file of the named module. Correct offending source statements. Retry preprocessing, translating, compiling, and SQL compiling the application file.

## 4.70. SQL 2205

```
A temporary filename could not be created.
```

**Cause:** You invoked mxCompileUserModule on an application file that has many embedded module definitions. The tool cannot create another temporary file name to hold the contents of an embedded module definition. The tool used tmpnam() to create a string that is not the name of an existing file which tmpnam() could not do.

**Effect:** The operation fails.

**Recovery:** Clean up TMPDIR (the directory where temporary files are created) by deleting unused temporary files. Retry the command.

## 4.71. SQL 2206

```
Temporary file <temp-filename> could not be created.
```

Where <temp-filename> is the name of the temporary file.

**Cause:** You invoked mxCompileUserModule on an application file that has many embedded module definitions. The tool cannot create another temporary file to hold the contents of an embedded module definition.

**Effect:** The operation fails.

**Recovery:** Verify that you have write access to TMPDIR (the directory where temporary files are created) and that TMPDIR has free space. Delete unused temporary files from TMPDIR and retry the command.

## 4.72. SQL 2207

```
-<option> is an unknown command line option.
```

Where -<option> is the command-line option.

**Cause:** You invoked mxCompileUserModule with an unrecognized command-line option.

**Effect:** The operation fails.

**Recovery:** Review the allowable command-line options by invoking

mxCompileUserModule. Verify that the desired command-line options are spelled correctly and retry the command.

## 4.73. SQL 2208

```
mxCompileUserModule requires an <application-filename>.
```

**Cause:** You invoked mxCompileUserModule without supplying an application file.

**Effect:** The operation fails.

**Recovery:** Invoke mxCompileUserModule on an application file, such as a Trafodion platform ELF object file.

## 4.74. SQL 2209

```
<string> is not a valid delimited identifier.
```

**Cause:** You invoked mxCompileUserModule using a command-line option allowing a delimited identifier, but the delimited identifier has an invalid character, such as the @ sign.

**Effect:** The operation fails.

**Recovery:** Remove invalid characters, such as the @ sign, from the delimited identifier and retry the command.

## 4.75. SQL 2210

Delimited identifier has no ending quote.

**Cause:** You invoked mxCompileUserModule using a command-line option allowing a delimited identifier, but the delimited identifier has no closing quote.

**Effect:** The operation fails.

**Recovery:** Make sure that the delimited identifier has a closing quote and retry the command.

## 4.76. SQL 2211

Lexical error: unknown symbol <character>.

**Cause:** You invoked mxCompileUserModule on an application file, possibly intending to SQL compile only a subset of its embedded module definitions, but you specified an unknown character in the module name list.

**Effect:** The operation fails.

**Recovery:** Review the module name list syntax. Verify that the module names are specified correctly and retry the command.

## 4.77. SQL 2212

```
A syntax error was encountered: expecting <string-1> instead of <string-2>.
```

**Cause:** You invoked mxCompileUserModule on an application file, intending to SQL compile only a subset of its embedded module definitions, but you specified an unexpected string in the module name list.

**Effect:** The operation fails.

**Recovery:** Review the module name list syntax, especially where *string1* is expected. Verify that the list of module names are specified correctly and retry the command.

## 4.78. SQL 2213

```
A syntax error was encountered: expecting an identifier instead of <string>.
```

**Cause:** You invoked mxCompileUserModule on an application file, possibly intending to SQL compile only a subset of its embedded module definitions, but you specified an unexpected string in the module name list.

**Effect:** The operation fails.

**Recovery:** Review the module name list syntax, especially where an identifier is expected. Verify that the list of module names are specified correctly and retry the command.

## 4.79. SQL 2214

```
Internal error in mxCompileUserModule in file <filename> at line <linenumber>: <error-message>.
```

**Cause:** You invoked mxCompileUserModule on an application file to SQL compile its embedded module definitions. An internal error occurred during the operation.

**Effect:** The operation fails.

**Recovery:** None. Contact the Trafodion User Distribution List

## 4.80. SQL 2215

```
<identifier> is not a valid regular identifier.
```

**Cause:** You invoked mxCompileUserModule on an application file, possibly intending to SQL compile only a subset of its embedded module definitions, but you specified an invalid regular identifier in the module name list.

**Effect:** The operation fails.

**Recovery:** Review the module name list syntax, especially where an identifier is expected. Verify that the list of module names is specified correctly. Verify that regular identifiers used are not SQL reserved words and retry the command.

## 4.81. SQL 2220

```
<mxcmp-path> (MXCMP environment variable) does not exist or is not executable.
```

Where <mxcmp-path> is the Trafodion compiler environment variable.

**Cause:** You set your Trafodion compiler environment variable to point to your own Trafodion compiler and invoked mxCompileUserModule on an application file to SQL compile its module definitions. Your Trafodion compiler is not executable.

**Effect:** The operation fails.

**Recovery:** Verify that your Trafodion compiler exists and is executable and retry the command.

## 4.82. SQL 2221

```
SQL compiler invocation failed with return code <error-code>.
```

Where <error-code> is the error message code.

**Cause:** You invoked mxCompileUserModule on an application file to SQL compile its module definitions. This command invoked the Trafodion compiler, which returned *error code*, indicating an abnormal termination.

**Effect:** The operation fails.

**Recovery:** If the system is heavily loaded, retry the command later. If the problem persists under normal system load, report it as an internal error and Contact the [Trafodion User Distribution mailing list](#).

## 4.83. SQL 2222

```
SQL module <module-name> was not found in <application-filename>.
```

Where <module-name> is the requested module name.

Where <application-filename> is the requested application file.

**Cause:** You invoked mxCompileUserModule on an application file with a list of module names to SQL compile. This list includes the named module, which cannot be found in the application file.

**Effect:** The operation fails.

**Recovery:** Verify the spelling of the module name and retry the command.

## 4.84. SQL 2223

```
Application file <filename> does not exist or is not readable.
```

Where <filename> is the name of the application file.

**Cause:** You invoked mxCompileUserModule on the named application file, which does not exist or is not readable.

**Effect:** The operation fails.

**Recovery:** Verify the spelling of the application file name and retry the command.

## 4.85. SQL 2233

Query involves remote node <nodename> that is currently down. Compiler encountered a file system error <error-num>. It may produce a plan that is suboptimal or of incompatible version.

Where <nodename> is the name of the node such as node01.host.com on which the failure occurred.

Where <error-num> is the file system error number.

**Cause:** The <nodename> you specified is not available.

**Effect:** The compiler tried to produce a plan without using that node. This might result in a suboptimal plan.

**Recovery:** For information about file system errors, see [File-System Errors](#).

## 4.86. SQL 2900

Error in file <filename> at line <number>.

Where <number> is the line number.

**Cause:** An error occurred in file name at line <number>.

**Effect:** Compilation failed because of a syntax error.

**Recovery:** This is a general error that is issued before a more specific error. Use the error that follows this one to diagnose and correct the problem.

# Chapter 5. Parser and Compilation Messages (3000 through 3999)

## 5.1. SQL 3001

```
Syntax error at or before <SQL-text>.
```

**Cause:** There is a syntax error near the text <SQL-text>.

**Effect:** The operation fails.

**Recovery:** See the errors that accompany this message for more information. Correct the syntax and resubmit.

## 5.2. SQL 3002

```
<column-name> is not a valid column reference; it has more than 4 name parts.
```

**Cause:** You specified an invalid column reference, which must have four or fewer parts.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.3. SQL 3003

Length or precision must be greater than zero.

**Cause:** You defined length or precision as zero. You must enter a value greater than zero.

**Effect:** The operation fails.

**Recovery:** Enter a value greater than zero and resubmit.

## 5.4. SQL 3004

A delimited identifier must contain at least one non-blank character.

**Cause:** You defined a delimited identifier as blanks. You must enter at least one non-blank character.

**Effect:** The operation fails.

**Recovery:** Enter at least one non-blank character and resubmit.

## 5.5. SQL 3005

A DECLARE CURSOR statement cannot dynamically get its cursor name from a host variable while also statically declaring a cursor specification. A dynamic cursor requires the name of a previously prepared statement or a host variable containing such a name; a static cursor requires a fixed, static name.

**Cause:** You attempted to use a DECLARE CURSOR statement without declaring a cursor name or using the name of a previously prepared statement.

**Effect:** The operation fails.

**Recovery:** Declare a cursor name, or use the name of a previously prepared statement, and resubmit.

## 5.6. SQL 3006

In a dynamic cursor declaration, both the cursor and the statement must be named in the same way: both must be literals or both must be string host variable expressions.

**Cause:** You attempted to declare a dynamic cursor in a way that does not match the statement. Both must be literals or both must be string host variable expressions.

**Effect:** The operation fails.

**Recovery:** Declare the cursor in a way that matches the statement and resubmit.

## 5.7. SQL 3007

In an ALLOCATE CURSOR statement, both the cursor and the statement must be named using string host variables.

**Cause:** You specified an ALLOCATE CURSOR statement with invalid syntax. Both the cursor and the statement must be named using string host variables.

**Effect:** The operation fails.

**Recovery:** Name the cursor and statement with string host variables and resubmit.

## 5.8. SQL 3008

Precision of <type> UNSIGNED data type, <value>, cannot exceed 9.

**Cause:** You specified a CREATE TABLE statement with a precision value greater than nine for the PRECISION field, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.9. SQL 3009

DROP ASSERTION statement is not yet supported.

**Cause:** You attempted to perform a DROP ASSERTION statement, which is not supported.

**Effect:** The operation fails.

**Recovery:** None.

## 5.10. SQL 3010

Character set <name> is not yet supported.

Where <name> is the name of the character set.

**Cause:** You specified character set <name> that is not supported for use in a Trafodion object, such as a table or module.

Examples include creating a KANJI or KSC5601 column in a Trafodion table.

**Effect:** The operation fails.

**Recovery:** Specify a valid character set and resubmit.

## 5.11. SQL 3011

```
<name> is not a valid qualified name; it has more than 3 name parts.
```

Where <name> is the name specified in the operation.

**Cause:** You specified an invalid name <name>, which must have three or fewer parts. <catalog.schema.table> is valid. <catalog.schema.table.name> is invalid.

**Effect:** The operation fails.

**Recovery:** Correct the name and resubmit.

## 5.12. SQL 3012

```
COUNT is the only aggregate function that accepts (*) as an operand.
```

**Cause:** You submitted an AVG or other aggregate function that does not allow (\*) as an operand. Only COUNT allows you to use (\\*).

**Effect:** The operation fails.

**Recovery:** Remove the (\*) operand and resubmit.

## 5.13. SQL 3013

Subtraction is the only operation allowed in the parenthesized expression preceding an interval qualifier.

**Cause:** You specified an expression with invalid syntax. Only subtraction is supported in the parenthesized expression that precedes an interval qualifier.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.14. SQL 3014

Precision of numeric, <value>, cannot exceed 18.

**Cause:** You defined a numeric item, <value>, with precision greater than 18, which is not supported.

**Effect:** The operation fails.

**Recovery:** Redefine the item with a precision value of 18 or less.

## 5.15. SQL 3015

```
Scale <value> cannot exceed precision <value>.
```

**Cause:** You defined a scale value with greater precision than Trafodion allows.

**Effect:** The operation fails.

**Recovery:** Redefine the scale with a precision value less than or equal to the allowable value.

## 5.16. SQL 3016

```
Precision of decimal, <value>, cannot exceed 18.
```

**Cause:** You gave a decimal item, <value>, with precision greater than 18, which is not supported.

**Effect:** The operation fails.

**Recovery:** Redefine the item with a precision value of 18 or less.

## 5.17. SQL 3017

```
An unsigned integer was expected, not <value>.
```

**Cause:** You specified an unexpected value, <value>. Trafodion requires an unsigned integer.

**Effect:** The operation fails.

**Recovery:** Replace the value with an unsigned integer and resubmit.

## 5.18. SQL 3018

```
An unsigned smallint was expected, not <value>.
```

**Cause:** You specified an unexpected value, <value>. Trafodion requires an unsigned smallint.

**Effect:** The operation fails.

**Recovery:** Replace the value with an unsigned smallint and resubmit.

## 5.19. SQL 3019

An unsigned number was expected within the parentheses, not <value>.

**Cause:** You specified an unexpected value, <value>. Trafodion requires an unsigned number.

**Effect:** The operation fails.

**Recovery:** Replace the value with an unsigned number and resubmit.

## 5.20. SQL 3020

An unsigned number was expected as the first operand within parentheses, not <value>.

**Cause:** You specified an unexpected value, <value>. Trafodion requires an unsigned number.

**Effect:** The operation fails.

**Recovery:** Replace the value with an unsigned number and resubmit.

## 5.21. SQL 3021

An unsigned number was expected as the second operand within parentheses, not <value>.

**Cause:** You specified an unexpected value, <value>. Trafodion requires an unsigned number.

**Effect:** The operation fails.

**Recovery:** Replace the value with an unsigned number and resubmit.

## 5.22. SQL 3022

The <name> operator is not yet supported.

**Cause:** You attempted to use an operator that is not supported.

**Effect:** The operation fails.

**Recovery:** None.

## 5.23. SQL 3023

The COLLATE clause in a sort specification is not yet supported.

**Cause:** You attempted to perform a COLLATE clause in a sort specification, which is not supported.

**Effect:** Trafodion ignores the COLLATE clause.

**Recovery:** Remove the COLLATE clause and resubmit.

## 5.24. SQL 3024

The MATCH PARTIAL clause is not yet supported.

**Cause:** You attempted to use a MATCH PARTIAL clause, which is not supported.

**Effect:** The operation fails.

**Recovery:** Remove the MATCH PARTIAL clause and resubmit.

## 5.25. SQL 3025

The format of the subvolume name part in the specified location name <name> is not valid. The subvolume name part must be eight characters long and begin with the letters ZSD.

**Cause:** You used an invalid location <name> for a subvolume that must be eight characters long and begin with the letters <ZSD>.

**Effect:** The operation fails.

**Recovery:** Correct the name and resubmit.

## 5.26. SQL 3026

A comma must be used to separate file attributes.

**Cause:** You made a syntax error in a list of file attributes, which must be separated by commas.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.27. SQL 3027

```
<name> is not a valid simple name; it has more than one name part.
```

**Cause:** You specified an invalid name <name>, which must have only one name part.

**Effect:** Trafodion could not prepare the statement.

**Recovery:** Correct the name and resubmit.

## 5.28. SQL 3028

```
Specifying a privilege column list in the INSERT clause is not yet supported.
```

**Cause:** You attempted to specify a privilege column list in an INSERT clause, which is not supported.

**Effect:** The operation fails.

**Recovery:** Remove the privilege column list and resubmit.

## 5.29. SQL 3029

```
<option> is not yet supported in referential integrity constraint definition.
```

**Cause:** You attempted to specify an <option> that is not supported in a referential integrity constraint definition.

**Effect:** The operation fails.

**Recovery:** Remove the option and resubmit.

## 5.30. SQL 3030

```
The PARALLEL EXECUTION clause is not yet supported.
```

**Cause:** You used the PARALLEL EXECUTION clause, which is not supported.

**Effect:** The operation fails.

**Recovery:** Remove the PARALLEL EXECUTION clause and resubmit.

## 5.31. SQL 3031

CASCADE drop behavior is not yet supported.

**Cause:** You attempted to drop an object with the CASCADE option, which is not supported.

**Effect:** The operation fails.

**Recovery:** Drop the item without CASCADE.

## 5.32. SQL 3032

The COLUMN clause in the ALTER TABLE statement is not yet supported.

**Cause:** You used the COLUMN clause in the ALTER TABLE statement, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.33. SQL 3033

The MOVE clause in the ALTER TABLE statement is not yet supported.

**Cause:** You used the MOVE clause in the ALTER TABLE statement, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.34. SQL 3034

The PARTITION clause in the ALTER TABLE statement is not yet supported.

**Cause:** You used the PARTITION clause in the ALTER TABLE statement, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.35. SQL 3035

The RENAME clause in the ALTER TABLE statement is not yet supported.

**Cause:** You used the RENAME clause in the ALTER TABLE statement, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.36. SQL 3036

The SET CONSTRAINT clause in the ALTER TABLE statement is not yet supported.

**Cause:** You used the SET CONSTRAINT clause in the ALTER TABLE statement, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.37. SQL 3037

Precision of type <data-type> cannot exceed 18.

**Cause:** You specified a CREATE TABLE statement with a precision value greater than 18 for <data-type>, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.38. SQL 3038

PIC X types cannot have leading signs, or any signs at all.

**Cause:** You specified a PIC X type with a sign, which is not supported.

**Effect:** The operation fails.

**Recovery:** Remove the sign, or redefine the type, and resubmit.

## 5.39. SQL 3039

PIC X types do not have any COMP representation.

**Cause:** You specified a PIC X type with COMP, which is not supported.

**Effect:** The operation fails.

**Recovery:** Remove the COMP, or redefine the type, and resubmit.

## 5.40. SQL 3040

Precision zero is not valid. Add a '9' to the PICTURE clause.

**Cause:** You specified an item with precision zero. You must add the number nine to the PICTURE clause.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.41. SQL 3041

UNSIGNED is not valid for a numeric or decimal type with a scale greater than 9.

**Cause:** You specified UNSIGNED for a numeric or decimal type that has a scale greater than nine, which is not supported.

**Effect:** The operation fails.

**Recovery:** Change the specification to SIGNED and resubmit.

## 5.42. SQL 3042

UPSHIFT for a numeric type is not valid.

**Cause:** You specified UPSHIFT for a numeric type, which is not supported.

**Effect:** The operation fails.

**Recovery:** Change the specification and resubmit.

## 5.43. SQL 3043

Precision greater than 18 for a COMP numeric type is not valid.

**Cause:** You specified a precision value greater than 18 for a COMP numeric type, which is not supported.

**Effect:** The operation fails.

**Recovery:** Change the precision to a value of 18 or less and resubmit.

## 5.44. SQL 3044

The interval <value> is not valid.

**Cause:** You specified an invalid interval <value>.

**Effect:** The operation fails.

**Recovery:** Correct the interval value to a valid one and resubmit.

## 5.45. SQL 3045

The date <value> is not valid.

**Cause:** You specified an invalid date <value>.

**Effect:** The operation fails.

**Recovery:** Change the date value and resubmit.

## 5.46. SQL 3046

The time <value> is not valid.

**Cause:** You specified an invalid time <value>.

**Effect:** The operation fails.

**Recovery:** Correct the time value and resubmit.

## 5.47. SQL 3047

The timestamp <value> is not valid.

**Cause:** You specified an invalid timestamp <value>.

**Effect:** The operation fails.

**Recovery:** Correct the timestamp value to a valid one and resubmit.

## 5.48. SQL 3048

Dynamic parameters, such as <name>, are not allowed in a static compilation.

**Cause:** You attempted to use parameters in a static compilation, which is not supported.

**Effect:** The operation fails.

**Recovery:** Remove the parameters and resubmit.

## 5.49. SQL 3049

Host variables, such as <name>, are not allowed in a dynamic compilation.

**Cause:** You attempted to use host variables in dynamic compilation, which is not supported.

**Effect:** The operation fails.

**Recovery:** Remove the host variables and resubmit.

## 5.50. SQL 3050

The constraint must have the same catalog and schema as the specified table.

**Cause:** You specified a constraint whose catalog and schema do not match the specified table.

**Effect:** The operation fails.

**Recovery:** Correct the syntax so that the constraint and table have the same catalog and schema.

## 5.51. SQL 3051

Duplicate HEADING clauses were specified in column definition <name>.

**Cause:** You defined column <name> with more than one HEADING clause.

**Effect:** The operation fails.

**Recovery:** Define the column with only one HEADING clause and resubmit.

## 5.52. SQL 3052

Duplicate NOT NULL clauses were specified in column definition <name>.

**Cause:** You defined column <name> with more than one NOT NULL clause.

**Effect:** The operation fails.

**Recovery:** Define the column with only one NOT NULL clause and resubmit.

## 5.53. SQL 3053

Duplicate PRIMARY KEY clauses were specified in column definition <name>.

**Cause:** You defined column <name> with more than one PRIMARY KEY clause.

**Effect:** The operation fails.

**Recovery:** Define the column with only one PRIMARY KEY clause and resubmit.

## 5.54. SQL 3054

The NOT DROPPABLE clause is allowed only in PRIMARY KEY and NOT NULL constraint definitions.

**Cause:** You specified a constraint with an invalid NOT DROPPABLE clause, which can appear only in PRIMARY KEY and NOT NULL constraint definitions.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.55. SQL 3055

Duplicate DELETE rules were specified.

**Cause:** You defined duplicate DELETE rules.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.56. SQL 3056

Duplicate UPDATE rules were specified.

**Cause:** You defined duplicate UPDATE rules.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.57. SQL 3057

The ALLOCATE value must be between 1 and <number>.

**Cause:** You provided an invalid size value in the ALLOCATE clause.

**Effect:** The operation fails.

**Recovery:** See the *Trafodion SQL Reference Manual* for correct size values, and resubmit.

## 5.58. SQL 3058

The BLOCKSIZE value must be 4096.

**Cause:** You defined a BLOCKSIZE with an invalid value. It must be 4096.

**Effect:** The operation fails.

**Recovery:** Correct the BLOCKSIZE value and resubmit.

## 5.59. SQL 3059

The specified size value (in the MAXSIZE clause or EXTENT size clause) is not valid.

**Cause:** You provided an invalid size value in the MAXSIZE clause.

**Effect:** The operation fails.

**Recovery:** See the *Trafodion SQL Reference Manual* for correct size values, and resubmit.

## 5.60. SQL 3060

The specified percentage value in the DSLACK clause is not valid.

**Cause:** You provided an invalid percentage value in the DSLACK clause.

**Effect:** The operation fails.

**Recovery:** See the *Trafodion SQL Reference Manual* for correct percentage values, and resubmit.

## 5.61. SQL 3061

The format of the specified location name <name> is not valid.

**Cause:** You provided a location <name> with an invalid format.

**Effect:** The operation fails.

**Recovery:** See the *Trafodion SQL Reference Manual* for correct name format, and resubmit.

## 5.62. SQL 3062

Duplicate EXTENT/MAXEXTENTS clauses were specified in the PARTITION clause.

**Cause:** You specified duplicate EXTENT/MAXEXTENTS clauses in the PARTITION clause.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.63. SQL 3063

Duplicate DSLACK clauses were specified in the PARTITION clause.

**Cause:** You specified duplicate DSLACK clauses in the PARTITION clause.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.64. SQL 3064

Duplicate ISLACK clauses were specified in the PARTITION clause.

**Cause:** You specified duplicate ISLACK clauses in the PARTITION clause.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.65. SQL 3065

The primary key constraint cannot be droppable when the STORE BY PRIMARY KEY clause appears in a table definition.

**Cause:** You defined a primary key as droppable in a table that includes STORE BY PRIMARY KEY in its definition, which is not supported.

**Effect:** Trafodion is unable to process this definition.

**Recovery:** Change the definition of the primary key constraint so that it is NOT DROPPABLE.

## 5.66. SQL 3067

ALTER TABLE ADD CONSTRAINT allows only DROPPABLE constraints.

**Cause:** You specified an ALTER TABLE ADD CONSTRAINT statement with NOT DROPPABLE constraints. Only DROPPABLE constraints are allowed.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.67. SQL 3068

The ALLOCATE and DEALLOCATE clauses cannot coexist in the same ALTER INDEX statement.

**Cause:** You specified an ALTER INDEX statement with both an ALLOCATE and a DEALLOCATE clause, which is not supported.

**Effect:** Trafodion ignores the ALTER INDEX statement.

**Recovery:** Correct the ALTER INDEX statement to include either ALLOCATE or DEALLOCATE.

## 5.68. SQL 3070

The [NO]AUDIT clause is not supported.

**Cause:** You specified the [NO]AUDIT clause, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.69. SQL 3071

Duplicate [NO]AUDITCOMPRESS clauses were specified.

**Cause:** You specified duplicate [NO]AUDITCOMPRESS clauses.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.70. SQL 3072

The BLOCKSIZE clause is not allowed in the ALTER INDEX . . . ATTRIBUTE(S) statement.

**Cause:** You specified an ALTER INDEX. . .ATTRIBUTE(S) statement that includes a BLOCKSIZE clause, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.71. SQL 3073

The [NO]BUFFERED clause is not supported.

**Cause:** You specified a [NO]BUFFERED clause, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.72. SQL 3074

The SEPARATE BY clause is not supported.

**Cause:** You specified the SEPARATE BY clause, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.73. SQL 3075

The [NO]COMPRESS clause is not allowed in the ALTER INDEX . . . ATTRIBUTE(S) statement.

**Cause:** You specified an ALTER INDEX . . . ATTRIBUTE(S) statement that includes a [NO]COMPRESS clause, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.74. SQL 3076

Duplicate DEALLOCATE clauses were specified.

**Cause:** You specified duplicate DEALLOCATE clauses.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.75. SQL 3077

The [NO]ICOMPRESS clause is not allowed in the ALTER INDEX . . . ATTRIBUTE(S) statement.

**Cause:** You specified an ALTER INDEX . . . ATTRIBUTE(S) statement that includes the [NO]ICOMPRESS clause, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.76. SQL 3078

The LOCKLENGTH clause is not allowed in the ALTER INDEX . . . ATTRIBUTE(S) statement.

**Cause:** You specified an ALTER INDEX . . . ATTRIBUTE(S) statement that includes the LOCKLENGTH clause, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.77. SQL 3079

Duplicate EXTENT/MAXEXTENTS clauses were specified.

**Cause:** You specified duplicate EXTENT/MAXEXTENT clauses.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.78. SQL 3080

The [NO]SERIALWRITES clause is not supported.

**Cause:** You specified the [NO]SERIALWRITES clause, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.79. SQL 3081

Duplicate ALLOCATE clauses were specified.

**Cause:** You specified duplicate ALLOCATE clauses.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.80. SQL 3082

Duplicate [NO]AUDIT clauses were specified.

**Cause:** You specified duplicate [NO]AUDIT clauses.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.81. SQL 3083

Duplicate [NO]AUDITCOMPRESS clauses were specified.

**Cause:** You specified duplicate [NO]AUDITCOMPRESS clauses.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.82. SQL 3084

The BLOCKSIZE clause is not allowed in the ALTER TABLE . . . ATTRIBUTE(S) statement.

**Cause:** You specified an ALTER TABLE . . . ATTRIBUTE(S) statement that includes the BLOCKSIZE clause, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.83. SQL 3085

Duplicate [NO]BUFFERED clauses were specified.

**Cause:** You specified duplicate [NO]BUFFERED clauses.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.84. SQL 3086

Duplicate [NO]CLEARONPURGE clauses were specified.

**Cause:** You specified duplicate [NO]CLEARONPURGE clauses.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.85. SQL 3087

The [NO]COMPRESS clause is not allowed in the ALTER TABLE . . .

ATTRIBUTE(S) statement.

**Cause:** You specified an ALTER TABLE. . .ATTRIBUTE(S) statement that includes the [NO]COMPRESS clause, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.86. SQL 3088

The ALLOCATE AND DEALLOCATE cannot coexist in the same ALTER TABLE statement.

**Cause:** You specified an ALTER TABLE statement with both ALLOCATE and DEALLOCATE clauses, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the ALTER TABLE statement to include either ALLOCATE or DEALLOCATE.

## 5.87. SQL 3089

The [NO]ICOMPRESS clause is not allowed in the ALTER TABLE . . . ATTRIBUTE(S) statement.

**Cause:** You specified an ALTER TABLE . . . ATTRIBUTE(S) statement that includes the [NO]ICOMPRESS clause, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.88. SQL 3090

Duplicate LOCKLENGTH clauses were specified.

**Cause:** You specified a statement with duplicate LOCKLENGTH clauses.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.89. SQL 3091

The [NO]AUDIT clause is not allowed in the CREATE INDEX statements.

**Cause:** You specified a CREATE INDEX statement with the [NO]AUDIT clause, which is not supported.

**Effect:** Trafodion ignores the CREATE INDEX statement.

**Recovery:** Correct the syntax and resubmit.

## 5.90. SQL 3092

Duplicate BLOCKSIZE clauses were specified.

**Cause:** You specified a statement with duplicate BLOCKSIZE clauses.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.91. SQL 3093

Duplicate DCOMPRESS clauses were specified.

**Cause:** You specified a statement with duplicate DCOMPRESS clauses.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.92. SQL 3094

The DEALLOCATE clause is not allowed in the CREATE INDEX statements.

**Cause:** You specified a CREATE INDEX statement that includes the DEALLOCATE clause, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.93. SQL 3095

Duplicate [NO]ICOMPRESS clauses were specified.

**Cause:** You specified a statement with duplicate [NO]ICOMPRESS clauses.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.94. SQL 3096

Duplicate [NO]SERIALWRITES clauses were specified.

**Cause:** You specified a statement with duplicate [NO]SERIALWRITES clauses.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.95. SQL 3097

The DEALLOCATE clause is not allowed in the CREATE TABLE statements.

**Cause:** You specified a CREATE TABLE statement that includes the DEALLOCATE clause, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.96. SQL 3098

Duplicate LOCATION clauses were specified.

**Cause:** You specified a statement with duplicate LOCATION clauses.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.97. SQL 3099

Duplicate FILE ATTRIBUTE(S) clauses were specified.

**Cause:** You specified a statement with duplicate FILE ATTRIBUTE(S) clauses.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.98. SQL 3100

Duplicate DSLACK clauses were specified.

**Cause:** You specified a statement with duplicate DSLACK clauses.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.99. SQL 3101

Duplicate ISLACK clauses were specified.

**Cause:** You specified a statement with duplicate ISLACK clauses.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.100. SQL 3102

Duplicate PARALLEL EXECUTION clauses were specified.

**Cause:** You specified a statement with duplicate PARALLEL EXECUTION clauses.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.101. SQL 3103

Duplicate PARTITION clauses were specified.

**Cause:** You specified a statement with duplicate PARTITION clauses.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.102. SQL 3104

Only the ADD option is allowed in a PARTITION clause in a CREATE TABLE statement.

**Cause:** You specified a CREATE TABLE statement with incorrect syntax. Only the ADD option is supported in a PARTITION clause.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.103. SQL 3105

Only range, hash, hash2 and system partitioning are currently supported.

**Cause:** You attempted to specify an invalid partitioning method. Currently only range, hash, hash2, and system partitioning are supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.104. SQL 3106

Duplicate PRIMARY KEY clauses were specified.

**Cause:** You specified a statement with duplicate PRIMARY KEY clauses.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.105. SQL 3107

Duplicate LIKE clauses were specified.

**Cause:** You specified a statement with duplicate LIKE clauses.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.106. SQL 3108

The LIKE clause and STORE BY clause cannot coexist in the same statement.

**Cause:** You specified a statement with both LIKE and STORE BY clauses, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the statement to include one of these clauses.

## 5.107. SQL 3109

Duplicate STORE BY clauses were specified.

**Cause:** You specified a statement with duplicate STORE BY clauses.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.108. SQL 3110

The LIKE clause and ATTRIBUTE(S) clause cannot coexist in the same statement.

**Cause:** You specified a statement with both LIKE and ATTRIBUTE(S) clauses, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the statement to include one of these clauses.

## 5.109. SQL 3111

The LIKE clause and LOCATION clause cannot coexist in the same statement.

**Cause:** You specified a statement with both LIKE and LOCATION clauses, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the statement to include one of these clauses.

## 5.110. SQL 3112

The LIKE clause and PARTITION clause cannot coexist in the same statement.

**Cause:** You specified a statement with both LIKE and PARTITION clauses, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the statement to include one of these clauses.

## 5.111. SQL 3113

```
Error in CONTROL statement: <number>
```

Where <number> is the error number.

**Cause:** There is an error <number> in the CONTROL statement you specified.

**Effect:** The operation fails.

**Recovery:** Correct the CONTROL statement and resubmit.

## 5.112. SQL 3114

```
Transaction access mode READ WRITE is incompatible with isolation level READ  
UNCOMMITTED.
```

**Cause:** You specified a statement with both READ WRITE and READ UNCOMMITTED clauses, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the statement to include one of these clauses.

## 5.113. SQL 3115

Duplicate ISOLATION LEVEL clauses were specified.

**Cause:** You specified a statement with duplicate ISOLATION LEVEL clauses.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.114. SQL 3116

Duplicate transaction access mode clauses were specified.

**Cause:** You specified a statement with duplicate access mode clauses.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.115. SQL 3117

Duplicate DIAGNOSTICS SIZE clauses were specified.

**Cause:** You specified a statement with duplicate DIAGNOSTICS SIZE clauses.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.116. SQL 3118

Specified identifier is too long.

**Cause:** You specified an identifier that is too long.

**Effect:** The operation fails.

**Recovery:** Shorten the identifier and resubmit.

## 5.117. SQL 3119

The WITH LOCAL CHECK OPTION clause is not supported.

**Cause:** You attempted to create a constraint with the WITH LOCAL CHECK OPTION clause, which is not supported.

**Effect:** The operation fails.

**Recovery:** Eliminate the WITH LOCAL CHECK OPTION clause and resubmit.

## 5.118. SQL 3120

The CREATE ASSERTION statement is not yet supported.

**Cause:** You specified the CREATE ASSERTION statement, which is not supported.

**Effect:** The operation fails.

Correct the syntax and resubmit.

## 5.119. SQL 3122

The system specified in the location clause <name> is not accessible.

Where <name> is the system name.

**Cause:** You specified an invalid <name>.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.120. SQL 3123

The format of the file name part in the specified location name <name> is not valid.  
The file name part must be eight characters long and end with the digits 00.

Where <name> is the name of the file.

**Cause:** You specified an invalid file <name>. The file name must be eight characters long and end with the digits 00 (zero).

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.121. SQL 3127

An invalid character was found in identifier <name>.

**Cause:** You specified an identifier that includes an invalid character.

**Effect:** The operation fails.

**Recovery:** Correct the syntax of the identifier and resubmit.

## 5.122. SQL 3128

<object-name> is a reserved word. It must be delimited by double-quotes to be used as an identifier.

Where <object-name> is the identifier.

**Cause:** You used an identifier that is a reserved word. You must put it between double quotes ("") to use it as an identifier.

**Effect:** The operation fails.

Enclose the identifier in double quotes or select another name that is not a reserved word.

## 5.123. SQL 3129

Function <name> accepts exactly one operand.

Where <name> is the name of the function.

**Cause:** You specified two operands for an aggregate function that accepts exactly one operand. Only VARIANCE and STDDEV support two operands.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.124. SQL 3130

The UNSIGNED option is not supported for LARGEINT type.

**Cause:** You attempted to define a LARGEINT data item with the UNSIGNED option, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.125. SQL 3131

The statement just entered is currently not supported.

**Cause:** You specified a statement that is not supported by Trafodion.

**Effect:** The operation fails.

**Recovery:** None.

## 5.126. SQL 3132

The HEADING for column <name> exceeds the maximum size of 128 characters.

Where <name> is the name of the column.

**Cause:** You specified a heading for column <name> that exceeds the maximum size of 128 characters.

**Effect:** The operation fails.

Correct the syntax and resubmit.

## 5.127. SQL 3133

PERFORM is valid only in COBOL programs.

**Cause:** You specified a PERFORM statement, which is supported only in COBOL programs.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.128. SQL 3134

The precision of time or timestamp, <value>, cannot exceed 6.

**Cause:** You specified a time or timestamp precision value that exceeds six, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.129. SQL 3135

The precision of float, <value>, cannot exceed 54.

**Cause:** You specified a value for float precision that exceeds 54, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.130. SQL 3136

Only LEFT, RIGHT, and FULL OUTER JOIN are valid in {oj . . .}

**Cause:** You attempted to perform an invalid outer join. Only LEFT, RIGHT, and FULL OUTER JOIN are supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.131. SQL 3137

UNION JOIN is not yet supported.

**Cause:** You attempted to perform a UNION JOIN, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.132. SQL 3138

A key-sequenced table with range partitioning requires a FIRST KEY clause.

**Cause:** You attempted to create a key-sequenced table with range partitioning without a FIRST KEY clause.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.133. SQL 3139

A range partitioned index requires a FIRST KEY clause.

**Cause:** You attempted to create a range-partitioned index without a required FIRST KEY clause.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.134. SQL 3140

The isolation level cannot be READ UNCOMMITTED for an INSERT,

UPDATE, DELETE, or DDL statement.

**Cause:** You attempted to perform an INSERT, UPDATE, DELETE, or DDL statement with a READ UNCOMMITTED isolation level, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.135. SQL 3141

The transaction access mode cannot be READ ONLY for an INSERT, UPDATE, DELETE, or DDL statement.

**Cause:** You attempted to perform an INSERT, UPDATE, DELETE, or DDL statement with a transaction access mode of READ ONLY, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.136. SQL 3142

INTO clause host variables not allowed in a static cursor.

**Cause:** You attempted to create a static cursor with INTO clause host variables, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.137. SQL 3143

BROWSE or READ UNCOMMITTED access is not allowed on a table value constructor.

**Cause:** You attempted to create a table value constructor with BROWSE or READ UNCOMMITTED access, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.138. SQL 3145

Positioned UPDATE or DELETE is allowed only in embedded SQL.

**Cause:** You attempted to perform a positioned UPDATE or DELETE, which is supported only in embedded Trafodion.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.139. SQL 3147

In an IN predicate whose right operand is a value list, the left operand must be scalar (degree of one).

**Cause:** You specified an IN predicate whose right operand is a value list but whose left operand is not scalar, which is required.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.140. SQL 3148

Environment variable <value> is being ignored because this version of the code is Release, not Debug. Actual query results will likely not match expected results.

Where <value> is the environment variable value specified.

**Cause:** Trafodion is ignoring the environment variable you specified. Query results might not match expected results.

**Effect:** None.

**Recovery:** Informational message only; no corrective action is needed.

## 5.141. SQL 3149

Duplicate WITH CONSTRAINTS phrases were specified in LIKE clause in CREATE TABLE statement.

**Cause:** The WITH CONSTRAINTS phrase appears multiple times within the LIKE clause of the CREATE TABLE statement, which is not supported.

**Effect:** The operation fails.

**Recovery:** Remove the duplicate WITH CONSTRAINTS phrases.

## 5.142. SQL 3150

Duplicate WITH HEADING phrases were specified in LIKE clause in CREATE TABLE statement.

**Cause:** The WITH HEADINGS phrase appears multiple times within the LIKE clause of the CREATE TABLE statement, which is not supported.

**Effect:** The operation fails.

**Recovery:** Remove the duplicate WITH HEADINGS phrases.

## 5.143. SQL 3151

Duplicate WITH HORIZONTAL PARTITIONS phrases were specified in LIKE clause in CREATE TABLE statement.

**Cause:** The WITH HORIZONTAL PARTITIONS phrase appears multiple times within the LIKE clause of the CREATE TABLE statement, which is not supported.

**Effect:** The operation fails.

**Recovery:** Remove the duplicate WITH HORIZONTAL PARTITIONS phrases.

## 5.144. SQL 3153

The FIRST KEY clause is not allowed with hash or hash2 partitioning.

**Cause:** You attempted to use the FIRST KEY clause with hash or hash2 partitioning, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.145. SQL 3155

The POPULATE and NO POPULATE clauses cannot coexist in the same CREATE INDEX statement.

**Cause:** You specified a CREATE INDEX statement using both the POPULATE or NO POPULATE clauses, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.146. SQL 3157

A catalog name is required.

**Cause:** You attempted to create a catalog without specifying a catalog name.

**Effect:** The operation fails.

**Recovery:** Specify a catalog name and resubmit.

## 5.147. SQL 3158

The DATETIME value <value> is not valid.

**Cause:** You specified an invalid DATETIME literal. Either the DATETIME qualifier has an invalid combination of start and end fields or the DATETIME literal string is invalid.

**Effect:** The operation fails.

**Recovery:** Specify a valid DATETIME literal and resubmit.

## 5.148. SQL 3159

If you intended <name> to be a character set specifier for a character string literal, you must remove the spaces in front of the single quote delimiter.

Where <name> is the character set specifier.

**Cause:** You apparently specified <name> as a character set specifier (for example, KANJI), but you placed a space in front of the single quote delimiter, which is not supported. For example, KANJI 'xyz' causes this error. KANJI'XYZ' does not.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.149. SQL 3160

```
<host-variable> was declared more than once in the procedure parameter list.
```

**Cause:** You declared <host-variable> more than once in the procedure parameter list.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.150. SQL 3161

```
<procedure-parameter> was not declared in the procedure parameter list.
```

**Cause:** You did not declare <procedure-parameter> in the parameter list, which is required.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.151. SQL 3162

```
Procedure parameter <name> was not used.
```

Where <name> is the name of the procedure parameter.

**Cause:** Trafodion did not use procedure parameter <name>.

**Effect:** None.

**Recovery:** Informational message only; no corrective action is needed.

## 5.152. SQL 3163

```
Host variable <name> appears more than once in the INTO list. Execution results will be undefined.
```

Where <name> is the host variable.

**Cause:** You specified an INSERT statement whose INTO list includes host variable <name> more than once.

**Effect:** Execution results are undefined.

**Recovery:** This is an informational message only. No corrective action is needed, but you might want to rewrite your query.

## 5.153. SQL 3164

There is a data type mismatch between output host variable and selected value.

**Cause:** A data type mismatch occurred between the output host variable and the selected value in the statement you specified.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.154. SQL 3165

The precision or exponent value specified in <value> was less than the minimum allowed or greater than the maximum allowed.

**Cause:** You specified a statement in which you exceed the min or max precision or the exponent <value>.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.155. SQL 3166

The value specified in the float or double <value> was less than the minimum allowed or greater than the maximum allowed.

**Cause:** You specified a statement in which you exceed the min or max precision for float or double <value>.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.156. SQL 3167

Duplicate [ NOT ] DROPPABLE clauses were specified.

**Cause:** You specified a statement with more than one [NOT] DROPPABLE clause.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.157. SQL 3168

```
The FOR . . . ACCESS clause is not allowed in a CREATE VIEW statement.
```

**Cause:** You specified a CREATE VIEW statement with the FOR . . . ACCESS clause, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.158. SQL 3169

```
<name> is not a known collation.
```

**Cause:** You attempted to use a collation that is not a known collation.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.159. SQL 3171

Transaction statements are not allowed in compound statements.

**Cause:** You specified a compound statement that contains transaction statements, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.160. SQL 3172

EXIT is not allowed in a compound statement.

**Cause:** You specified a compound statement that contains an EXIT command.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.161. SQL 3173

UPDATE STATISTICS is not allowed in a compound statement.

**Cause:** You specified a compound statement that contains an UPDATE STATISTICS command.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.162. SQL 3174

DDL statements are not allowed in compound statements.

**Cause:** You specified a compound statement that contains DDL statements.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.163. SQL 3175

Dynamic SQL statements are not allowed in compound statements.

**Cause:** You specified a compound statement that contains dynamic Trafodion statements.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.164. SQL 3176

Subqueries are not allowed in the IF Condition.

**Cause:** You specified an IF statement that contains a subquery.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.165. SQL 3177

Character set <name> requires an even number of characters in the length declaration of the data type.

Where <name> is the name of the character set.

**Cause:** You specified a character set with an odd number of characters in the length declaration of the data type.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.166. SQL 3178

One or more of the following external (host-language) data types incorrectly appears within the SQL query or operation: <name>.

**Cause:** You specified a Trafodion query or attempted to perform an operation with an incorrect data type.

The operation fails.

Correct the syntax and resubmit.

## 5.167. SQL 3179

```
Collation <name-1> is not defined on the character set <name-2>.
```

Where <name-1> is the name of the collation.

Where <name-2> is the character set name.

**Cause:** You attempted to used a collation name that is not defined on the character set. A valid collation name is required.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.168. SQL 3180

```
STREAM statements are not allowed in compound statements.
```

**Cause:** You specified a compound statement that contains a STREAM statement, which is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.169. SQL 3181

Specified name is not a valid three part ANSI name.

**Cause:** You specified an invalid logical name.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.170. SQL 3182

Extra semicolon(;) in a compound statement.

**Cause:** You specified an extra semicolon in a compound statement.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.171. SQL 3183

```
Duplicate <clause-name> clauses were specified.
```

Where `<clause-name>` is the clause specified.

**Cause:** You specified a CREATE PROCEDURE containing multiple occurrences of the `<clause-name>` clause.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.172. SQL 3184

```
An invalid SQLSTATE value <string-1> was found. Message: <string-2>
```

Where `<string-1>` is the illegal SQLSTATE value.

**Cause:** You attempted to use an illegal SQLSTATE value. A valid SQLSTATE value is a single quoted string value that begins with an "S" or an "s" followed by a four-digit integer.

**Effect:** The operation fails.

**Recovery:** Specify a valid SQLSTATE value and resubmit.

## 5.173. SQL 3185

```
SIGNAL parameter 3 must be of type string.
```

**Cause:** You attempted a SIGNAL statement with a third parameter that is not a quoted string.

**Effect:** The operation fails.

**Recovery:** Specify a parameter that is a quoted string and resubmit.

## 5.174. SQL 3186

```
<string>: Dynamic parameters and host variables are currently not allowed in DDL.
```

Where <string> is the dynamic parameter or host variable that was specified.

**Cause:** Trafodion does not support the use of dynamic parameters or host variables in DDL statements. The operation fails.

**Recovery:** Remove occurrences of dynamic parameters or host variables and resubmit.

## 5.175. SQL 3187

Specifying a specific stream with SET STREAM TIMEOUT is not allowed.

**Cause:** You attempted to use a SET STREAM TIMEOUT statement, which is not supported.

**Effect:** The operation fails.

**Recovery:** None.

## 5.176. SQL 3188

A NOT DROPPABLE primary key constraint must be defined when STORE BY primary key is specified.

**Cause:** You specified a STORE BY primary key but did not define a NOT DROPPABLE primary key.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.177. SQL 3189

Setting a lock timeout is not allowed on a view.

**Cause:** You attempted to set a lock timeout on a view, which is not supported.

**Effect:** The operation fails.

**Recovery:** None.

## 5.178. SQL 3192

Union operands <table-1> and <table-2> have different access/lock modes.

**Cause:** Trafodion attempted to compile a UNION query that has an access/lock mode that can be applied to both branches of the access/lock mode or only to the second branch of the UNION.

**Effect:** The access/lock mode is applied only to the second branch of the UNION.

**Recovery:** Specify that the access/lock mode apply to both branches and resubmit.

## 5.179. SQL 3193

```
SIGNAL SQLSTATE= <string>, message: <string-1>.
```

Where <string> is the SIGNAL SQLSTATE value.

Where <string-1> is the SIGNAL text message.

**Cause:** You attempted a SIGNAL statement. SIGNAL statements are commonly used as an action for a trigger in a compound statement or in a user application.

**Effect:** The operation fails.

**Recovery:** None.

## 5.180. SQL 3195

```
Table creation with data type <dtype> is not supported.
```

Where <dtype> is a data type specified for a column.

**Cause:** The data type specified for a column in a CREATE TABLE statement is not supported.

**Effect:** The operation fails.

**Recovery:** Correct the data and resubmit.

## 5.181. SQL 3196

Only one access clause for may be specified for a single table SELECT.

**Cause:** You specified two or more table-level access options for the same table reference.

**Effect:** The offending SQL statement is rejected with an error.

**Recovery:** Remove all but one of the table-level access options for each table reference.

## 5.182. SQL 3197

Only one lock clause may be specified for a single table SELECT.

**Cause:** You specified two or more table-level lock options for the same table reference. The offending SQL statement is rejected with an error.

**Recovery:** Remove all but one of the table-level access options for each table reference.

## 5.183. SQL 3199

Column <col-name> is incorrectly specified. Keywords ASCENDING and DESCENDING are not allowed in the partitioning key list.

Where <col-name> is the name of the column.

**Cause:** You cannot specify ordering for columns of a partitioning key clause.

**Effect:** The operation fails.

**Recovery:** Remove any of the following keywords from the columns specified in the PARTITION clause: ASCENDING, ASC, DESCENDING, DESC, and resubmit.

## 5.184. SQL 3201

EXTERNAL PATH clause is required.

**Cause:** In the CREATE PROCEDURE statement, you omitted the mandatory EXTERNAL PATH clause.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.185. SQL 3202

PARAMETER STYLE clause is required.

**Cause:** In the CREATE PROCEDURE statement, you omitted the mandatory PARAMETER STYLE clause.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.186. SQL 3203

LANGUAGE clause is required.

**Cause:** In the CREATE PROCEDURE statement, you omitted this mandatory LANGUAGE clause.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.187. SQL 3204

```
EXTERNAL NAME clause is badly formed.
```

**Cause:** In the CREATE PROCEDURE statement, the EXTERNAL NAME clause you specified does not conform to the required syntax.

**Effect:** Trafodion is unable to create the procedure.

**Recovery:** Correct the syntax and resubmit.

## 5.188. SQL 3205

```
EXTERNAL NAME clause is required.
```

**Cause:** In the CREATE PROCEDURE statement, you omitted the mandatory EXTERNAL NAME clause.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 5.189. SQL 3206

The name for an object of this type must be fully qualified, or set NAMETYPE ANSI.

**Cause:** In the CREATE PROCEDURE statement, you specified a partially qualified name when NAMETYPE was not set to ANSI.

**Effect:** The operation fails.

**Recovery:** Set NAMETYPE ANSI or fully qualify the name.

## 5.190. SQL 3207

Value for DYNAMIC RESULT SETS must be zero.

**Cause:** In the CREATE PROCEDURE statement, you specified the optional DYNAMIC RESULT SETS clause with nonzero value.

**Effect:** The operation fails.

**Recovery:** Remove the clause or use the value zero, and then resubmit.

## 5.191. SQL 3208

UNSIGNED numeric is not allowed for routine parameter.

**Cause:** In the CREATE PROCEDURE statement, one of the parameters you specified is an unsigned numeric.

**Effect:** The operation fails.

**Recovery:** Change the parameter specification to SIGNED.

## 5.192. SQL 3209

Maximum length of LONGWVARCHAR is <value>.

**Cause:** You attempted a CREATE TABLE table name (columnname longwvarchar(N)) where N >current MAX\_LONG\_WVARCHAR\_DEFAULT\_SIZE setting.

**Effect:** The operation fails.

**Recovery:** Decrease the CREATE TABLE statement's longwvarchar column width N or increase the current MAX\_LONG\_WVARCHAR\_DEFAULT\_SIZE setting and resubmit.

## 5.193. SQL 3210

Minimum length of LONGWVARCHAR is <value>.

**Cause:** You attempted a CREATE TABLE table name (columnname longvarchar(N)) where N < current MIN\_LONG\_WVARCHAR\_DEFAULT\_SIZE setting.

**Effect:** The operation fails.

**Recovery:** Increase the CREATE TABLE statement's longvarchar column width N or decrease the current MIN\_LONG\_WVARCHAR\_DEFAULT\_SIZE setting and resubmit.

## 5.194. SQL 3211

Maximum length of LONG VARBINARY is <value>.

**Cause:** You attempted a CREATE TABLE table name (columnname long varbinary(N)) where N > current MAX\_LONG\_VARCHAR\_DEFAULT\_SIZE setting.

**Effect:** The operation fails.

**Recovery:** Decrease the CREATE TABLE statement's long varbinary column width N or increase the current MAX\_LONG\_VARCHAR\_DEFAULT\_SIZE setting and resubmit.

## 5.195. SQL 3212

Minimum length of LONG VARBINARY is <value>.

**Cause:** You attempted a CREATE TABLE table name (columnname long varbinary(N)) where N < current MIN\_LONG\_VARCHAR\_DEFAULT\_SIZE setting.

**Effect:** The operation fails.

**Recovery:** Increase the CREATE TABLE statement's long varbinary column width N or decrease the current MIN\_LONG\_VARCHAR\_DEFAULT\_SIZE setting and resubmit.

## 5.196. SQL 3213

Maximum length of LONG VARCHAR is <value>.

**Cause:** You attempted a CREATE TABLE table name (columnname long varchar(N)) where N > current MAX\_LONG\_VARCHAR\_DEFAULT\_SIZE setting.

**Effect:** The operation fails.

**Recovery:** Decrease the CREATE TABLE statement's long varchar column width N or increase the current MAX\_LONG\_VARCHAR\_DEFAULT\_SIZE setting and resubmit.

## 5.197. SQL 3214

Minimum length of LONG VARCHAR is <value>.

**Cause:** You attempted a CREATE TABLE table name (columnname long varchar(N) where N < current MIN\_LONG\_VARCHAR\_DEFAULT\_SIZE setting.

**Effect:** The operation fails.

**Recovery:** Decrease the CREATE TABLE statement's long varchar column width N or increase the current MIN\_LONG\_VARCHAR\_DEFAULT\_SIZE setting and resubmit.

## 5.198. SQL 3215

Computed LONG VARCHAR length len1 is below minimum len2.

**Cause:** You attempted a CREATE TABLE table name (c1 longvarchar, c2 long varchar,.. .cn long varchar) and the computed long varchar columns' width is below the current MIN\_LONG\_VARCHAR\_DEFAULT\_SIZE setting.

**Effect:** The operation fails.

**Recovery:** Decrease the number of long varchar columns in the CREATE TABLE statement or increase the current MIN\_LONG\_VARCHAR\_DEFAULT\_SIZE setting and resubmit.

## 5.199. SQL 3216

Computed LONG WVARCHAR length <value-1> is below minimum <value-2>.

**Cause:** You attempted a CREATE TABLE table name (c1 longvarchar, c2 longvarchar, . . . cn longvarchar) and the computed width for each of the longvarchar columns falls below the current MIN\_LONG\_WVARCHAR\_DEFAULT\_SIZE setting.

**Effect:** The operation fails.

**Recovery:** Reduce the number of longvarchar columns in the CREATE TABLE statement or increase the current MIN\_LONG\_WVARCHAR\_DEFAULT\_SIZE setting and resubmit.

## 5.200. SQL 3217

Character set <name> is not allowed in the <function-name> function.

**Cause:** You specified KANJI or KSC5601 character expressions to function LOWER, LCASE, UPPER, UPSHIFT, or UCASE.

**Effect:** The operation fails.

**Recovery:** Do not use KANJI or KSC5601 character expressions in these functions.

## 5.201. SQL 3218

A table reference cannot contain DELETE or UPDATE in a CREATE VIE statement.

**Cause:** A create view statement was issued with a delete or update operation as a table reference.

**Effect:** The statement does not compile.

**Recovery:** Do not use delete or update in a CREATE view statement.

## 5.202. SQL 3220

SHOWDDL failed for object <object-name> because an SQL/MP display option was used on a Trafodion object.

Where <object-name> specifies the ANSI name of a table, view, or ALIAS.

**Cause:** SHOWDDL was given the display option with a Trafodion table given as an argument.

**Effect:** SHOWDDL does not display output.

**Recovery:** Reissue the command without the display option or specify an object.

## 5.203. SQL 3225

```
SHOWLABEL failed for object <object-name>. The object does not exist in the given namespace <name-space>, the object is not accessible, or the object type is not supported. SHOWLABEL supports only Trafodion tables, views and indexes.
```

Where <object-name> is the specified name of an object.

Where <name-space> is either the TABLE or INDEX namespace. The default namespace for SHOWLABEL is TABLE.

**Cause:** SHOWLABEL was unable to find the object in the *namespace* namespace, the object is not accessible, or the object is unsupported. The table namespace is used as the default.

**Effect:** SHOWLABEL does not display output.

**Recovery:** Reissue the command with an object name and corresponding namespace of a valid, supported, and accessible object.

## 5.204. SQL 3226

```
SHOWLABEL failed for physical location name <location-name>. Object does not exist or object type is not supported. SHOWLABEL supports only Trafodion tables, views, and indexes.
```

Where <location-name> specifies the physical location name of a Trafodion object.

**Cause:** SHOWLABEL was given an invalid physical location as an argument.

**Effect:** SHOWLABEL does not display output.

**Recovery:** Reissue the command with a valid location name.

## 5.205. SQL 3228

```
SHOWLABEL failed for physical location name <location-name>. SHOWLABEL supports only  
the data forks of Trafodion tables, views, and indexes.
```

Where <location-name> specifies the physical location name of a Trafodion object.

**Cause:** SHOWLABEL supports only the physical names of data forks of Trafodion objects (physical location names that end in "00"). SHOWLABEL does not support resource forks.

**Effect:** SHOWLABEL does not display output.

**Recovery:** Reissue the command with a valid location name.

## 5.206. SQL 3229

```
SHOWLABEL failed for object <name>. SHOWLABEL does not support synonyms.
```

**Cause:** The requested operation is not allowed on synonyms.

**Effect:** The operation fails.

**Recovery:** Try the command using the reference object name.

## 5.207. SQL 3230

The synonym must be defined in the same catalog as the specified table or view.

**Cause:** You specified a synonym that has a different catalog than the object.

**Effect:** The operation fails.

**Recovery:** Correct the syntax so that the synonym and the object have the same catalog and schema values.

## 5.208. SQL 3400

Invalid code point value for character set <name>.

**Cause:** There is an undefined character in the character set.

**Effect:** The operation fails.

**Recovery:** Remove the invalid character and resubmit.

## 5.209. SQL 3401

Hexadecimal representation of string literals associated with character set <name> is not supported.

**Cause:** You used a hexadecimal format to represent a character string that is not supported by Trafodion.

**Effect:** The operation fails.

**Recovery:** Do not use a hexadecimal format for the character set you specified.

## 5.210. SQL 3402

The format of the <value> hexadecimal string literal is not valid.

**Cause:** You either used illegal hexadecimal digits, supplied an odd number of hexadecimal digits, or misplaced space separators.

**Effect:** The operation fails.

**Recovery:** Specify the string in the correct hexadecimal format and resubmit.

## 5.211. SQL 3403

Function <name-1> does not take an operand with character set <name-2>.

**Cause:** You specified a character operand with a character set that the function does not support.

**Effect:** The operation fails.

**Recovery:** Do not use the character operand with that character set in the function.

## 5.212. SQL 3404

Character set <name>, to which SQL\_TEXT is aliased, is not allowed for a SQL module.

**Cause:** You specified SQL\_TEXT as the module character name set. SQL\_TEXT is synonymous with UCS2, which is not supported.

**Effect:** The operation fails.

**Recovery:** Replace SQL\_TEXT with ISO88591 and resubmit.

## 5.213. SQL 3405

A logical partition name cannot be specified in the LOCATION clause of the CREATE statement of this object.

**Cause:** You cannot specify the logical partition name in the LOCATION clause of the create statement of catalog, procedure, view and materialized view object types.

**Effect:** The operation fails.

**Recovery:** Remove the logical partition name syntax from the LOCATION clause and resubmit.

## 5.214. SQL 3406

A DDL statement could not be translated into a statement consisting of single-byte characters for processing.

**Cause:** The DDL statement coded in unicode contains non-ISO88591 characters. Trafodion does not support arbitrary unicode characters.

**Effect:** The operation fails.

**Recovery:** Remove non-ISO88591 characters and resubmit.

## 5.215. SQL 3411

Expressions are not allowed as IDENTITY column values. Specify DEFAULT or supply a largeint value.

**Cause:** Tried to specify an expression in place of a constant largeint value or DEFAULT.

**Effect:** The operation failed.

**Recovery:** Specify DEFAULT or supply a largeint value.

## 5.216. SQL 3412

IDENTITY column <column-name> must be the primary key or must have a unique index on it.

**Cause:** Tried to INSERT a system generated value for the IDENTITY column, which does not have a unique index on it.

**Effect:** The operation failed.

**Recovery:** Create a unique index on the IDENTITY column. Note that the unique index must only be on the IDENTITY column.

## 5.217. SQL 3413

The NOT NULL constraint on IDENTITY column <column-name> must be NOT DROPPABLE.

**Cause:** Specified DROPPABLE attribute on the NOT NULL constraint on the IDENTITY column.

**Effect:** The operation failed.

**Recovery:** Specify NOT DROPPABLE attribute on the NOT NULL constraint on the IDENTITY column.

## 5.218. SQL 3414

For an IDENTITY column <column-name>, the tuple list cannot have mixed user specified and DEFAULT values. Specify values for all or specify DEFAULT for all.

**Cause:** Provided mixed user specified and DEFAULT values in a tuple list for the IDENTITY column.

**Effect:** The operation failed.

**Recovery:** Specify values for all the tuples in the list or specify DEFAULT for all the tuples in the list.

## Chapter 6. Optimizer Messages (6000 through 6999)

### 6.1. SQL 6001

DISTINCT aggregates can be computed for only one column per table expression.

**Cause:** You attempted to compute DISTINCT aggregates for more than one column.

**Effect:** DISTINCT aggregates can be computed only for one column per table expression.

**Recovery:** Correct syntax and resubmit.

### 6.2. SQL 6002

The metadata table HISTOGRAMS or HISTOGRAM\_INTERVALS contains invalid values. If you have manually modified the metadata table, then you should undo your changes using the CLEAR option in UPDATE STATISTICS.

**Cause:** You have manually modified the metadata table, and now it contains invalid values.

**Effect:** Trafodion is unable to complete compilation.

**Recovery:** Undo your changes using the CLEAR option in UPDATE STATISTICS.

## 6.3. SQL 6003

The metadata table HISTOGRAMS or HISTOGRAM\_INTERVALS contains invalid boundary value <value> for column <name>. If you have manually modified the metadata table, then you should undo your changes using the CLEAR option in UPDATE STATISTICS.

**Cause:** You have manually modified the metadata table, and now it contains an invalid boundary value.

**Effect:** The Trafodion database uses default histograms to compile the query. This is a warning message.

**Recovery:** Undo your changes using the CLEAR option in UPDATE STATISTICS.

## 6.4. SQL 6007

Multi-column statistics for columns <names> from table <name> were not available; as a result, the access path chosen might not be the best possible.

**Cause:** Statistics are not available for the multicolumn join you are performing.

This message appears when the user has not updated statistics for column <names> and when the row count in table <name> is more than the value of the defaults table constant HIST\_ROWCOUNT\_REQUIRING\_STATS. If you want to suppress this message, set that value to a very large number, and you will see this message only for tables with more rows than that, and for which there are no updated statistics.

**Effect:** None. This is a warning message.

**Recovery:** None.

## 6.5. SQL 6008

Statistics for column <name> were not available. As a result, the access path chosen might not be the best possible.

**Cause:** Statistics are not available for the statement you specified.

This message appears when the user has not updated statistics for column <name> and when the ROWCOUNT in the table is more than the value of the defaults table constant HIST\_ROWCOUNT\_REQUIRING\_STATS. If you want to suppress this message, set that value to a very large number, and you will see this message only for tables with more rows than that, and for which there are no updated statistics.

**Effect:** None. This is a warning message.

**Recovery:** None.

## Chapter 7. Generator Messages (7000 through 7999)

### 7.1. SQL 7001

Default value <value> is not valid for column <name>.

**Cause:** You attempted to create a table with an invalid default <value> for column <name>.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

### 7.2. SQL 7003

A plan using cluster sampling could not be produced for this query.

**Cause:** You can use cluster sampling in a query only on a base table result set and only if there is no WHERE clause in the SELECT statement. This query does not satisfy these conditions.

**Effect:** Trafodion is unable to compile the query.

**Recovery:** Rewrite the query (for example, using nested queries) so that cluster sampling is performed on a base table with no WHERE-clause predicate.

## Chapter 8. Executor Messages (8000 through 8999)

### 8.1. SQL 8006

The stream timed out, but the cursor is still open.

**Cause:** A cursor is still open although its stream timed out.

**Effect:** The operation fails.

**Recovery:** Close the cursor before trying to open it.

### 8.2. SQL 8007

The operation has been canceled.

**Cause:** You pressed the break key.

**Effect:** The operation stops.

**Recovery:** None.

## 8.3. SQL 8012

Encoding of CONTROL QUERY DEFAULTs: <encoding>.

**Cause:** Trafodion displays an internal CONTROL QUERY DEFAULT encoding.

**Effect:** None.

**Recovery:** This is an informational message only; no corrective action is needed.

## 8.4. SQL 8016

An attempt was made to access <name> which has a system version that is incompatible with the version of the accessing software.

**Cause:** You attempted to access a system version that is incompatible with the version of the accessing software.

**Effect:** The operation fails.

**Recovery:** The system you are trying to access must be on a system version that is compatible with your accessing software. Upgrade that system.

## 8.5. SQL 8017

Explain information is not available for this query.

**Cause:** The explain default has been turned off for this query.

**Effect:** Trafodion is not able to display explain information.

**Recovery:** Turn the explain default on for this query.

## 8.6. SQL 8101

The operation is prevented by check constraint <name-1> on table <name-2>.

Where constraint <name-1> is the name of the constraint.

Where table <name-2> is the name of the table.

**Cause:** You attempted to perform an operation on table <name-1> that is prevented by check constraint <name-2>.

**Effect:** The operation fails.

**Recovery:** Change the data you are attempting to enter to be consistent with the constraint.

## 8.7. SQL 8102

The operation is prevented by a unique constraint.

**Cause:** You attempted to perform an operation that is prevented by a unique constraint.

**Effect:** Trafodion could not perform the operation.

**Recovery:** Make the data you enter unique to be consistent with the constraint.

## 8.8. SQL 8103

The operation is prevented by referential integrity constraint <name-1> on table <name-2>.

Where <name-1> is the name of the constraint.

Where <name-2> is the name of the table.

**Cause:** You attempted to perform an operation on table <name-1> that is prevented by referential integrity constraint <name-2>.

**Effect:** The operation fails.

**Recovery:** Change the data you are attempting to enter to be consistent with the constraint. The data must exist in another table. For example, if you are trying to enter a department number for an employee, the department number must exist in a department number table.

## 8.9. SQL 8104

The operation is prevented by the check on view <name-1> cascaded from the check option on <name-2>.

Where view <name-1> is the name of the view.

Where <name-2> is the name of the table.

**Cause:** You attempted to perform an operation on table <name-1>. The operation has been prevented by the check on view <name-2>, cascaded from the check option on the table.

**Effect:** The operation fails.

**Recovery:** Change the view properties, if appropriate.

## 8.10. SQL 8105

The operation is prevented by the check option on view <name>.

Where <name> is the name of the view.

**Cause:** You attempted to perform an operation on table name that is prevented by the check option on view <name>.

**Effect:** The operation fails.

**Recovery:** Insert into the base table rather than this view.

## 8.11. SQL 8302

```
All partitions of <type> <object> are unavailable.
```

Where *<type>* is the type of the affected object, such as table.

Where *<object>* is the fully qualified ANSI name of the affected object.

**Cause:** Late name resolution could not resolve the ANSI name to an available partition.

**Effect:** The operation fails.

**Recovery:** Determine why none of the partitions were available, then correct the error and resubmit.

## 8.12. SQL 8553

```
Stream overflow; subscription rate has fallen too far behind publishing rate.
```

**Cause:** The table used by the streaming cursor has overflowed.

**Effect:** The cursor or statement is closed.

**Recovery:** Reopen the statement or cursor and resume subscribing.

## 8.13. SQL 8573

8573 The user does not have <level> privilege on table or view <name>.

Where <level> is the user privilege level.

Where <name> is the name of the object.

**Cause:** You attempted to perform an operation on object <name>, for which you do not have a sufficient privilege <level>.

**Effect:** The operation fails.

**Recovery:** None. Have the system administrator change your privilege level, if appropriate.

## 8.14. SQL 8576

Statement was recompiled.

**Cause:** Trafodion recompiled the statement.

**Effect:** The operation fails.

**Recovery:** Recompile the program.

## 8.15. SQL 8577

```
Table, index or view <name> was not found.
```

Where <name> is the name of the object.

**Cause:** Trafodion could not find the object <name>.

**Effect:** The operation fails.

**Recovery:** Verify the location of the object and resubmit.

## 8.16. SQL 8578

```
Similarity check passed.
```

**Cause:** The similarity check passed.

**Effect:** None.

**Recovery:** Informational message only; no corrective action is needed.

## 8.17. SQL 8579

```
Similarity check failed: <name>
```

**Cause:** The similarity check failed.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 8.18. SQL 8604

```
Transaction subsystem <name> returned error <number> while starting a transaction.
```

Where <name> is the subsystem name.

Where <number> is the error number.

**Cause:** Transaction subsystem <name> has returned error <number> while starting a transaction.

**Effect:** The operation fails.

**Recovery:** Contact the [Trafodion User Distribution mailing list](#).

## 8.19. SQL 8605

Committing a transaction which has not started.

**Cause:** You attempted to commit a transaction that has not been started.

**Effect:** The operation fails.

**Recovery:** Correct the syntax so that the transaction is started before it is committed, and resubmit.

## 8.20. SQL 8606

Transaction subsystem <name> returned error <number> on a commit transaction.

Where <name> is the name of the subsystem.

Where <number> is the error number.

**Cause:** Transaction subsystem <name> has returned error <number> while committing a transaction.

**Effect:** The operation fails.

**Recovery:** Contact the [Trafodion User Distribution mailing list](#).

## 8.21. SQL 8607

```
Rolling back a transaction that has not started.
```

**Cause:** You attempted to roll back a transaction that has not started.

**Effect:** The operation fails.

**Recovery:** Correct the syntax so that the sequence of events is correct, and resubmit.

## 8.22. SQL 8608

```
Transaction subsystem <name> returned error <number> on rollback transaction.
```

Where <name> is the name of the subsystem.

Where <number> is the error number.

**Cause:** Transaction subsystem <name> has returned error <number> while rolling back a transaction.

**Effect:** The operation fails.

**Recovery:** Contact the [Trafodion User Distribution mailing list](#).

## 8.23. SQL 8609

```
Waited rollback performed without starting a transaction.
```

**Cause:** You attempted to perform a waited rollback on a transaction that has not started.

**Effect:** The operation fails.

**Recovery:** Correct the syntax so that the sequence of events is correct, and resubmit.

## 8.24. SQL 8610

```
Transaction subsystem <name> reported error <number> on a waited rollback transaction.
```

Where <name> is the name of the subsystem.

Where <number> is the error number.

**Cause:** Transaction subsystem <name> has returned error <number> while performing a waited rollback transaction.

**Effect:** The operation fails.

**Recovery:** Contact the [Trafodion User Distribution mailing list](#).

## 8.25. SQL 8612

Transaction mode cannot be set if the transaction is already running.

**Cause:** You attempted to set the transaction mode, but the transaction is already running.

**Effect:** The operation fails.

**Recovery:** Abort and restart the transaction if you must change its mode.

## 8.26. SQL 8613

SQL cannot commit or rollback a transaction that was started by application.

**Cause:** An application started a transaction outside of Trafodion that Trafodion could not commit or rollback.

**Effect:** The operation fails.

**Recovery:** The application that started the transaction must perform a commit or rollback. Trafodion must start any transactions it will later commit or rollback.

## 8.27. SQL 8808

```
Module file <name> contains corrupted or invalid data.
```

Where <name> is the name of the file.

**Cause:** Trafodion has detected corrupted or invalid data in the module file <name>.

**Effect:** Trafodion could not execute the file.

**Recovery:** Recompile the .mdf file, using the Trafodion compiler, to create a valid module file.

## 8.28. SQL 8809

```
Open of the module file <name> failed with error <number>.
```

Where <name> is the name of the file.

Where <number> is the error number returned.

**Cause:** Trafodion was unable to open module file <name>.

**Effect:** The operation fails.

**Recovery:** Check the location of the module file and retry the operation.

## 8.29. SQL 8819

Begin transaction failed while preparing the statement.

**Cause:** This is an internal error.

**Effect:** The operation fails.

**Recovery:** None. Contact the [Trafodion User Distribution mailing list](#).

## 8.30. SQL 8820

Transaction commit failed while closing the statement.

**Cause:** This is an internal error.

**Effect:** The operation fails.

**Recovery:** None. Contact the [Trafodion User Distribution mailing list](#).

## 8.31. SQL 8821

Rollback transaction failed during the process of fetching the statement.

**Cause:** This is an internal error.

**Effect:** The operation fails.

**Recovery:** None. Contact the Trafodion User Distribution mailing list.

## 8.32. SQL 8824

The input <module-id> does not have a module name.

**Cause:** A module name was not passed into the module ID structure that was passed in.

**Effect:** The operation fails.

**Recovery:** Make sure a module name is passed into the module ID structure.

## 8.33. SQL 8826

The module could not be added.

**Cause:** This is an internal error.

**Effect:** The operation fails.

**Recovery:** None. Contact the Trafodion User Distribution mailing list.

## 8.34. SQL 8827

The request <name> could not be sent.

Where <name> is the name of the request.

**Cause:** Trafodion was unable to send request <name>.

**Effect:** The operation fails.

**Recovery:** Use the errors that accompany this one to diagnose and correct the problem.

## 8.35. SQL 8832

Transaction has not been started.

**Cause:** A transaction has not been started.

**Effect:** The operation fails.

**Recovery:** Verify that the transaction has been started or start it if it has not been.

## 8.36. SQL 8833

The input parameter is an invalid SQL transaction command.

**Cause:** This is an internal error.

**Effect:** The operation fails.

**Recovery:** None. Contact the [Trafodion User Distribution mailing list](#).

## 8.37. SQL 8834

The SQL installation directory could not be found. Operating system error <number>.

Where <number> is the error number.

**Cause:** Trafodion was unable to find the Trafodion installation directory and received an operating system error <number>.

**Effect:** The operation fails.

**Recovery:** Locate the Trafodion installation directory, correct your syntax, and resubmit.

## 8.38. SQL 8836

Application specified an invalid update column for cursor.

**Cause:** There is an error in the program that this code is embedded in. The build might not have completed correctly.

**Effect:** The operation fails.

**Recovery:** Verify that the build was successful and resubmit.

## 8.39. SQL 8837

The user id passed in is invalid.

**Cause:** The value of the user ID passed in is not valid.

**Effect:** The operation fails.

**Recovery:** Make sure that the user ID of the form group id | name, user id | user name, and that the password is valid and exists on the current system.

## 8.40. SQL 8840

Object name provided to CLI is not valid.

**Cause:** The object named provided to CLI is invalid

**Effect:** The operation fails.

**Recovery:** Correct the object name and resubmit.

## 8.41. SQL 8841

User application committed or aborted a transaction started by SQL. This transaction needs to be committed or aborted by calling SQL COMMIT or ROLLBACK WORK.

**Cause:** Trafodion started a transaction that was committed or aborted by an embedded program, rather than by Trafodion.

**Effect:** The operation fails.

**Recovery:** Commit or abort the transaction by calling SQL COMMIT or ROLLBACKWORK.

## 8.42. SQL 8842

The cursor, <name>, referenced by this statement is not found or is not updatable.

Where <name> is the name of the cursor.

**Cause:** There is an error in the program that this code is embedded in. The build might not have completed successfully.

**Effect:** The operation fails.

**Recovery:** Verify that the build was successful and resubmit.

## 8.43. SQL 8846

An empty SQL statement was passed in.

**Cause:** The SQL source statement passed to the compiler to do the prepare was empty.

**Effect:** The operation fails.

**Recovery:** You must pass in a valid SQL source statement.

## 8.44. SQL 8850

The table specified in this cursor update or delete statement is different than the table specified in the declare cursor statement.

**Cause:** The table specified in the update or DELETE statement is not the same as the one specified in the declare cursor statement, as is required.

**Effect:** The operation fails.

**Recovery:** Correct the syntax and resubmit.

## 8.45. SQL 8860

```
Module file <name> has an obsolete module header.
```

Where <name> is the file name.

**Cause:** The module file <name> has an obsolete module header.

**Effect:** The operation fails.

**Recovery:** Rebuild the module file and resubmit.

## 8.46. SQL 8861

```
Module file <name> has an obsolete descriptor location table header.
```

Where <name> is the file name.

**Cause:** The module file <name> has an obsolete table header.

**Effect:** The operation fails.

**Recovery:** Rebuild the module file and resubmit.

## 8.47. SQL 8862

```
Module file <name> has an obsolete descriptor location table entry.
```

Where <name> is the file name.

**Cause:** The module file <name> has an obsolete descriptor location table entry.

**Effect:** The operation fails.

**Recovery:** Rebuild the module file and resubmit.

## 8.48. SQL 8863

```
Module file <name> has an obsolete descriptor header.
```

Where <name> is the file name.

**Cause:** The module file <name> has an obsolete descriptor header.

**Effect:** The operation fails.

**Recovery:** Rebuild the module file and resubmit.

## 8.49. SQL 8864

```
Module file <name> has an obsolete descriptor entry.
```

Where <name> is the file name.

**Cause:** The module file <name> has an obsolete descriptor entry.

**Effect:** The operation fails.

**Recovery:** Rebuild the module file and resubmit.

## 8.50. SQL 8865

```
Module file <name> has an obsolete procedure location table header.
```

Where <name> is the file name.

**Cause:** The module file <name> has an obsolete procedure location table header.

**Effect:** The operation fails.

**Recovery:** Rebuild the module file and resubmit.

## 8.51. SQL 8866

```
Module file <name> has an obsolete procedure location table entry.
```

Where <name> is the file name.

**Cause:** The module file <name> has an obsolete procedure location table entry.

**Effect:** The operation fails.

**Recovery:** Rebuild the module file and resubmit.

## 8.52. SQL 8867

```
An error while reading from file <name>.
```

Where <name> is the file name.

**Cause:** Trafodion encountered an error while reading the module file <name>.

**Effect:** The operation fails.

**Recovery:** Rebuild the module file and resubmit.

## 8.53. SQL 8882

Containing SQL is not permitted.

**Cause:** A stored procedure registered with the NO SQL attribute attempted to access Trafodion.

**Effect:** The corresponding SQL request is rejected.

**Recovery:** Either change the definition of the stored procedure to allow SQL access, or determine why the stored procedure contains Trafodion statements that might be called while the stored procedure is executing.

## 8.54. SQL 8888

The underlying insert, update, or delete operation of cursor <cursor-name> is still in progress. Since the cursor is being closed before the operation is complete, all affected rows will be rolled back.

<cursor-name> is the cursor being closed.

**Cause:** A cursor with an underlying insert, delete, or update operation was closed before the operation was complete.

**Effect:** The cursor was closed but all rows affected by opening this cursor have been rolled back.

**Recovery:** OPEN the cursor again and FETCH all rows until SQLCODE = 100 is returned.

## 8.55. SQL 8890

The SQL compiler failed to initialize properly. Query results may differ from what is expected, due to different compiler defaults.

**Cause:** The Trafodion compiler failed to correctly initialize.

**Effect:** Query results might be affected.

**Recovery:** Stop the Trafodion and restart it.

## 8.56. SQL 8901

The MXUDR server for this statement is no longer running. The statement will be assigned a new MXUDR server if it is executed again.

**Cause:** During execution of a Trafodion statement, an attempt was made to contact a nonexistent Trafodion UDR server.

**Effect:** The operation fails.

**Recovery:** Retry the Trafodion statement.

## 8.57. SQL 8904

Trafodion did not receive a reply from MXUDR, possibly caused by internal errors while executing user-defined routines.

**Cause:** During execution of a Trafodion statement, the Trafodion did not receive an expected reply from the Trafodion UDR server.

**Effect:** The operation fails.

**Recovery:** Verify that the Trafodion UDR server is running. If not, the Trafodion statement will acquire a new Trafodion UDR server when it is next executed.

## Chapter 9. Sort Messages (9200 through 10049)

### 9.1. SQL 9200

```
UPDATE STATISTICS encountered an error from statement <name>.
```

**Cause:** UPDATE STATISTICS encountered an error from the Trafodion statement <name>.

**Effect:** The operation fails.

**Recovery:** Other error messages will appear with this one, depending on what statement caused the error. Use them to diagnose and correct the problem.

### 9.2. SQL 9201

```
Unable to DROP object <name>.
```

**Cause:** UPDATE STATISTICS encountered an error during a DROP of the object <name>.

**Effect:** Trafodion is unable to continue processing.

**Recovery:** Resubmit the statement. If this does not correct the problem, stop and restart Trafodion. If this does not correct the problem, contact the [Trafodion User distribution list](#).

## 9.3. SQL 9202

UPDATE STATISTICS has located previously generated histograms that are not being regenerated. This may affect the plans that will be generated. Missing column lists are <column-list>.

**Cause:** UPDATE STATISTICS has located previously generated histograms that are not being regenerated.

**Effect:** Processing continues without interruption.

**Recovery:** Remove or replace previously generated histograms by performing either one of these two recovery actions:

- Re-execute the same UPDATE STATISTICS command, but also include the <column-list> from the message.
- Perform UPDATE STATISTICS FOR the table. Then re-execute UPDATE STATISTICS with the column lists in which you are interested.

## 9.4. SQL 9203

Column names must be unique when specified in column list: (<name>).

**Cause:** You specified a non unique column name in the specified column list.

**Effect:** Trafodion is unable to continue processing.

**Recovery:** Correct the syntax and resubmit.

## 9.5. SQL 9204

```
Invalid option <option> specified. Value must be <range>.
```

**Cause:** You specified an invalid option for UPDATE STATISTICS. The value <range> specifies the valid range for this option.

**Effect:** Trafodion is unable to continue processing.

**Recovery:** Correct the syntax and resubmit.

## 9.6. SQL 9205

```
UPDATE STATISTICS is not supported for object <name>.
```

**Cause:** You attempted to run UPDATE STATISTICS against an object that is not supported.

**Effect:** Trafodion is unable to continue processing.

**Recovery:** Correct the syntax and resubmit.

## 9.7. SQL 9206

You are not authorized to read/write object <name>. Verify that you have the necessary access privileges.

**Cause:** Trafodion could not perform an UPDATE STATISTICS statement because you are not authorized to perform this operation against this table. You must either own the object <name> or be the super ID.

**Effect:** Trafodion is unable to continue processing.

**Recovery:** Resubmit after checking the table location and access privileges.

## 9.8. SQL 9207

The specified SAMPLE option generated an empty sample set. Modify the SAMPLE option and resubmit.

**Cause:** The SAMPLE option you specified generated an empty sample set.

**Effect:** Trafodion is unable to continue processing.

**Recovery:** Modify the SAMPLE option and resubmit.

## 9.9. SQL 9208

Column definitions could not be accessed.

**Cause:** An UPDATE STATISTICS statement was unable to access column definitions.

**Effect:** The operation fails.

**Recovery:** Resubmit the statement. If this does not correct the problem, stop and restart the Trafodion database software. If this does not correct the problem, report the entire message to [the Trafodion User mailing list](#).

## 9.10. SQL 9209

Column <name> does not exist in object <name>.

**Cause:** You tried to access column <name>, which does not exist in object <name>.

**Effect:** The operation fails.

**Recovery:** Check the column <name> and resubmit.

## 9.11. SQL 9210

One of the column data types is not supported by UPDATE STATISTICS. You must exclude this column from the column list in UPDATE STATISTICS.

**Cause:** You attempted to perform UPDATE STATISTICS on a column whose data type does not support this operation.

**Effect:** The operation fails.

**Recovery:** Exclude this column from the column list and resubmit.

## 9.12. SQL 9212

Cardinality statistics will be more accurate if you use the SET ROWCOUNT option in the SAMPLE clause.

**Cause:** The SET ROWCOUNT option was not used in the SAMPLE clause.

**Effect:** Processing continues without interruption.

**Recovery:** Provide SET ROWCOUNT option and resubmit for more accurate statistics.

## 9.13. SQL 9213

If you intend to update histogram statistics for columns, you must specify a column list in the statement.

**Cause:** You attempted to perform UPDATE STATISTICS and did not specify a column list.

**Effect:** Processing continues without interruption.

**Recovery:** Correct your syntax to specify the column list and resubmit.

## 9.14. SQL 9214

Object <name> could not be created.

**Cause:** UPDATE STATISTICS encountered an error during a CREATE of the object <name>.

**Effect:** Trafodion is unable to continue processing.

**Recovery:** Resubmit the statement. If this does not correct the problem, stop and restart the Trafodion database software. If this does not correct the problem, report the entire message to [the Trafodion User mailing list](#).

## 9.15. SQL 10007

```
Sort failed while writing to a scratch file with error <system-error>.
```

**Cause:** An I/O error occurred during a scratch file I/O operation.

**Effect:** The operation fails.

**Recovery:** Contact the [Trafodion User distribution list](#).

## 9.16. SQL 10011

```
Sort failed while reading a scratch file with error <system-error>.
```

Where <system-error> is the error returned.

**Cause:** An I/O error occurred during a scratch file I/O operation.

**Effect:** The operation fails.

**Recovery:** Contact the [Trafodion User distribution list](#).

## 9.17. SQL 10013

Sort could not find any appropriate disks for overflow.

**Cause:** The available disks on the system are not suitable for scratch usage.

**Effect:** The operation fails.

**Recovery:** Make sure there are appropriate disks with enough space for scratch file use. Disks such as optical disks, phantom disks, and virtual disks are not considered suitable. See the [Trafodion SQL Reference Manual](#) for more information on how to influence the placement of scratch files.

## 9.18. SQL 10014

Sort ran out of memory while allocating an internal data structure.

**Cause:** An internal data structure could not be allocated because of an out of memory condition.

**Effect:** The operation fails.

**Recovery:** None. This is an internal error. Contact the [Trafodion User distribution list](#).

## 9.19. SQL 10015

```
Sort failed while calling PROCESSHANDLE_GETMINE_ with error <number>.
```

**Cause:** An error occurred while calling a system level call.

**Effect:** The operation fails.

**Recovery:** Contact the [Trafodion User distribution list](#).

## 9.20. SQL 10016

```
Sort failed while calling PROCESSHANDLE_DECOMPOSE_ with error <number>.
```

**Cause:** An error occurred while calling a system level call.

**Effect:** The operation fails.

**Recovery:** Contact the [Trafodion User distribution list](#).

## 9.21. SQL 10017

```
Sort failed while calling DEVICE_GETINFOBYLDEV_ with error <number>.
```

**Cause:** An error occurred while calling a system level call.

**Effect:** The operation fails.

**Recovery:** Contact the [Trafodion User distribution list](#).

## 9.22. SQL 10018

```
Sort failed while calling FILENAME_FILESTART_ with error <number>.
```

**Cause:** An error occurred while calling a system level call.

**Effect:** The operation fails.

**Recovery:** Contact the [Trafodion User distribution list](#).

## 9.23. SQL 10019

```
Sort failed while calling FILENAME_FILENOEXT_ with error <number>.
```

**Cause:** An error occurred while calling a system level call.

**Effect:** The operation fails.

**Recovery:** Contact the [Trafodion User distribution list](#).

## 9.24. SQL 10020

```
Sort failed while calling FILENAME_FINDFINISH_ with error <number>.
```

**Cause:** An error occurred while calling a system level call.

**Effect:** The operation fails.

**Recovery:** Contact the [Trafodion User distribution list](#).

## 9.25. SQL 10021

```
Sort failed while calling FILE_GETINFOLISTBYNAME_ with error <number>.
```

**Cause:** An error occurred while calling a system level call.

**Effect:** The operation fails.

**Recovery:** Contact the [Trafodion User distribution list](#).

## 9.26. SQL 10022

```
Sort failed while calling FILE_CREATE with error <number>.
```

**Cause:** An error occurred while calling a system level call.

**Effect:** The operation fails.

**Recovery:** Contact the [Trafodion User distribution list](#).

## 9.27. SQL 10023

```
Sort failed while calling FILE_OPEN_ with error <number>.
```

**Cause:** An error occurred while calling a system level call.

**Effect:** The operation fails.

**Recovery:** Contact the [Trafodion User distribution list](#).

## 9.28. SQL 10024

```
Sort failed while calling SETMODE_ with error <number>.
```

**Cause:** An error occurred while calling a system level call.

**Effect:** The operation fails.

**Recovery:** Contact the [Trafodion User distribution list](#).

## 9.29. SQL 10027

```
Sort failed while calling FILE_GETINFOLIST with error <number>.
```

**Cause:** An error occurred while calling a system level call.

**Effect:** The operation fails.

**Recovery:** Contact the [Trafodion User distribution list](#).

## 9.30. SQL 10028

```
Sort failed while calling POSITION with error <number>.
```

**Cause:** An error occurred while calling a system level call.

**Effect:** The operation fails.

**Recovery:** Contact the [Trafodion User distribution list](#).

## 9.31. SQL 10029

```
Sort failed while calling FILE_GETINFO_ with error <number>.
```

**Cause:** An error occurred while calling a system level call.

**Effect:** The operation fails.

**Recovery:** Contact the [Trafodion User distribution list](#).

## 9.32. SQL 10047

```
Sort Error: Wrong length read.
```

**Cause:** The length of the data returned was not what was expected.

**Effect:** The operation fails.

**Recovery:** None. This is an internal error. Contact the [Trafodion User distribution list](#).

## 9.33. SQL 10048

IO to a scratch file failed because the free space threshold was reached on all available disks.

**Cause:** The threshold, specified by the default SCRATCH\_FREESPACE\_THRESHOLD\_PERCENT was reached on all available disks.

**Effect:** The operation fails.

**Recovery:** Reduce the threshold percentage and retry the query or specify a particular disk with adequate free space specifically for scratch use.

# Chapter 10. UDR Server and Language Manager Messages (11000 through 11399)

## 10.1. SQL 11108

```
MXUDR: Unable to allocate memory for object <object-name>.
```

Where <object-name> is the name of the object.

**Cause:** The Trafodion UDR server was not able to obtain enough memory to allocate the named object.

**Effect:** The request message is rejected, and the Trafodion statement fails.

**Recovery:** Stop and start the client process to restart a new Trafodion UDR server, and retry the stored procedure call.

## 10.2. SQL 11201

```
Language Manager initialization failed. Details: Error occurred while loading Java class <class-name>.
```

Where <class-name> is the name of the Java class.

**Cause:** Initialization of the language manager failed because a required Java class could not be loaded or because a required Java method was not found.

**Effect:** The operation fails.

**Recovery:** Check the installation of the Trafodion platform for Java product and the Trafodion language manager. Verify the existence of the specified class. Stop and restart the session, and retry the Trafodion statement.

## 10.3. SQL 11202

Language Manager initialization failed. Details: Unable to initialize the Java virtual machine.

**Cause:** Initialization of the language manager failed during creation of the Java Virtual Machine.

**Effect:** The operation fails.

**Recovery:** Check the installation of the Trafodion platform for Java product. Stop and restart the session, and retry the Trafodion statement.

## 10.4. SQL 11221

Language Manager is out of memory <string>.

**Cause:** The language manager could not acquire enough memory to complete its work on the Trafodion statement.

**Effect:** The operation fails.

**Recovery:** Stop and restart the session and retry the Trafodion statement.

## 10.5. SQL 11222

The operation failed because the Java Virtual Machine ran out of memory.

**Cause:** The Java Virtual Machine, hosted by a Trafodion UDR server, did not have enough memory to execute a Java method. This error condition will be accompanied by another condition that shows when the Java Virtual Machine encountered the error.

**Effect:** The operation fails.

**Recovery:** Stop and restart the session and retry the Trafodion statement.

# Chapter 11. SQLSTATE

Trafodion returns SQLSTATE values that are defined in the ISO/ANSI SQL standard and implementation-defined SQLSTATE values. See Subclause 22, "Status Codes" in the ISO/ANSI SQL92 Standard "Database Language SQL."

## 11.1. SQLSTATE and SQLCODE Considerations

- Using SQLSTATE causes performance overhead because of the representation of SQLSTATE as five characters. The overhead is most noticeable with short SQL statements and in error situations.
- Mapping SQLSTATE values to SQLCODE values can result in ambiguous SQLCODE values:
  - SQLCODE values will often not map to a unique SQLSTATE value. For example, see the many SQLCODE values mapped to SQLSTATE 42000 in the table below.
  - To deal with the problem of ambiguous SQLCODE values, we recommends retrieving the error message text or the SQLCODE value in addition to the SQLSTATE.
- SQLSTATE values for some Trafodion error and warning messages might be subject to change:
  - In the future, Trafodion might return different SQLSTATE values for error conditions than it does now.
  - In the future, the Trafodion error handling might use a different error path, and therefore return a slightly different SQLCODE and implementation defined SQLSTATE value for an error.

## 11.2. SQLSTATE Values

The table below is a list of returned SQLSTATE values ordered by SQLSTATE. SQLSTATE values are provided for both warning messages (positive SQLCODE numbers) and error messages (negative SQLCODE numbers).

SQLSTATE	SQLCODE	Error Text
00000	0	Successful completion
01001	8106	The last row fetched by this cursor was updated or deleted between the FETCH and UPDATE/DELETE...WHERE CURRENT... of statements.
01004	8402	A string overflow occurred during the evaluation of a character expression.
01006	1015	Some of the specified privileges could not be revoked.
01007	1012	No privileges were granted. You lack grant option on the specified privileges.
01007	1013	Not all privileges were granted. You lack grant option on some of the specified privileges.
01500	1000	A syntax error occurred.
01501	1001	An internal error occurred in module <name> on line <num>. DETAILS(<details>).
01502	1002	Catalog <catalog> does not exist, or has not been registered on node <node>
01503	1003	Schema <schema> does not exist.

SQLSTATE	SQLCODE	Error Text
01504	1004	Table, view, or stored procedure <object-name> does not exist or object type is invalid for the current operation.
01505	1005	Constraint <constraint-name> does not exist.
01506	1006	Index <index-name> does not exist.
01508	1008	User name <user-name> does not exist.
01509	1009	Column <column-name> does not exist in the specified table.
0150A	1010	The statement just specified is currently not supported.
0150E	1014	Privileges were not revoked. Dependent privilege descriptors still exist.
0150G	1016	Redundant references to column <column-name> were specified in the constraint or trigger definition.
0150H	1017	You are not authorized to perform this operation.
0150J	1019	No valid primary partition for <table-name> could be found.
0150K	1020	Privilege settings on metadata tables cannot be changed.
0150L	1021	SQL is already initialized on system <node-name>.
0150M	1022	Schema <schema-name> already exists.
0150N	1023	Only the super ID can name an authorization ID other than the current user name.
0150O	1024	File system error <error-number> occurred on module <text-string-1>. <text-string-2>.
0150P	1025	Request failed. One or more dependent objects exist.
0150Q	1026	Only the schema owner or super ID user can drop a schema.
0150R	1027	The definition <schema-name> is dropped when its catalog is dropped.
0150S	1028	The schema must be empty. It contains at least one object <object-name>.
0150T	1029	Object <object-name> could not be created.
0150U	1030	File label <name> could not be accessed. File System error <error>.
0150V	1031	Object <object-name> could not be dropped.
0150Y	1034	Trafodion was not able to initialize.
0150Z	1035	Catalog <catalog-name> already exists
01510	1036	Only super ID can execute DROP SQL.
01511	1037	Trafodion is not installed on system <node>.
01512	1038	Not all catalogs have been dropped from the system.
01513	1039	The drop SQL statement could not be executed.
01514	1040	The use of ALTER on metadata tables is not permitted.
01515	1041	The primary key has already been defined.
01516	1042	All PRIMARY KEY or UNIQUE constraint columns must be NOT NULL.
01517	1043	Constraint <constraint-name> already exists.
01518	1044	Constraint <constraint-name> could not be created because the referenced columns in the referenced table are not part of a unique constraint.
01519	1045	The unique constraint cannot be used because it is deferrable.
0151A	1046	Referenced and referencing column lists do not match for constraint <name>.
0151B	1047	Request failed. Dependent view <view-name> exists.
0151C	1048	Currently only supporting restrict drop behavior.
0151D	1049	Attempting to drop a NOT DROPPABLE constraint.
0151E	1050	Cannot drop constraint used as a referenced object for a foreign key.
0151F	1051	Insufficient privilege on <table-name>.

SQLSTATE	SQLCODE	Error Text
0151G	1052	Trying to drop a constraint that does not belong to requested table.
0151H	1053	Unique index <table-name> could not be created because the column(s) specified contain duplicate data.
0151I	1054	Index <table-name> already exists.
0151J	1055	Table, view, or stored procedure <table-name> already exists.
0151L	1057	The DAM volume specified (<name>) is not available or is not audit protected.
0151M	1058	Lock <table-name> already exists.
0151N	1059	Request failed. Dependent constraint <name> exists.
0151P	1061	Cannot drop metadata catalog <name>.
0151Q	1062	Cannot drop metadata schema <name>.
0151R	1063	Cannot drop metadata index <table-name>.
0151S	1064	Cannot drop metadata view <table-name>.
0151T	1065	Cannot create constraint <name> in metadata schema.
0151U	1066	Cannot create index <table-name> in metadata schema.
0151X	1069	Unable to drop schema <name>.
0151Y	1070	Unable to create object <table-name> (file error <num>).
0151Z	1071	Unable to access object <table-name> (file error <num>).
01520	1072	Unique constraint <name> is disabled; cannot create foreign key constraint <name>.
01521	1073	Only the super ID user can execute INITIALIZE SQL.
01523	1075	Catalog <name> contains at least one schema. The catalog must be empty.
01525	1077	Metadata table <name> does not contain information for view <name>.
01526	1078	The format of the specified location name <name> is invalid.
01527	1079	Unable to prepare the statement.
01528	1080	Duplicate references to column <name> in the create request.
01529	1081	Loading of index <table-name> failed unexpectedly.
0152A	1082	Validation for constraint <name> failed unexpectedly.
0152B	1083	Validation for constraint <name> failed; incompatible data exists in table.
0152C	1084	Invalid default value for column <name>.
0152D	1085	The calculated key length is greater than 255 bytes.
0152E	1086	Lock <table-name> does not exist.
0152F	1087	Lock cannot be granted, conflicting operation is in progress.
0152G	1088	Cannot instantiate object <table-name>, conflicting lock exists.
0152I	1090	Self-referencing constraints are currently not supported.
0152M	1094	Unable to drop object <table-name> because it is not a <name>.
0152N	1095	The partition by column <name> should also be part of the clustering/storage key.
0152Q	1098	Duplicate partition key (<name>) specified for object <name>.
0152R	1099	Column <num> is unnamed. You must specify an AS clause for that column expression, or name all the columns by specifying a view column list.
0152S	1100	Unable to select <table.schema.name>
0152T	1101	Unable to update <table.schema.name>
0152U	1102	Unable to insert rows into <table.schema.name>
0152V	1103	Unable to delete rows from <table.schema.name>
0152W	1104	Default value string too long for column <name>.

SQLSTATE	SQLCODE	Error Text
0152X	1105	CREATE TABLE LIKE statement cannot contain both HORIZONTAL PARTITIONS and STORE BY clauses.
0152Y	1106	The specified partition <name> of object <name> does not exist.
01530	1108	The number of columns specified in the view column list, <num>, does not match the degree of the query expression, <num>.
01531	1109	The WITH CHECK OPTION clause appears in the definition of view <table-name>, but the view is not updateable.
01533	1111	Error starting transaction. Table name <name>
01536	1114	Unable to create catalog <name> metadata tables on <name>.
01537	1115	Unable to create label for <name> (file error <num>) <text>.
01538	1116	The current partitioning scheme requires a user-specified primary key on object <name>.
01539	1117	Cannot drop the only partition of the table. There must be at least two partitions available to perform the drop.
0153A	1118	Cannot create object <name> in metadata schema.
0153B	1119	Cannot drop metadata object <name>.
0153C	1120	Attempting to change the audit flags for a table in an unsupported way.
0153D	1121	Attempting to perform a partition add, move, or drop on table <name>. Partition operations are not allowed on tables with vertical partitions, entry sequenced operations, and SYSKEY only partitioned tables.
0153E	1122	The number of specified partition key values (<name>) for object <name> exceeds the number of key columns used, <num>.
0153F	1123	Unable to process the partition key values (<name>) for object <name>. Please verify that the correct key value data types were specified.
0153G	1124	Schema <name> is an unknown version.
0153H	1125	API request version number mismatch.
0153I	1126	Referential integrity is not yet supported. Constraint <name> will not be enforced.
0153J	1127	The specified table <name> is not a base table. Please verify that the correct table was specified.
0153K	1128	Invalid API request. Details: <text>.
0153M	1130	The column requires a default value.
0153O	1132	An added column cannot have both DEFAULT NULL and NOT NULL.
0153P	1133	Only the super ID can perform this operation.
0153Q	1134	Concurrent DDL operations are being performed on the given object. The current operation cannot be performed.
0153R	1135	Clustering key column <name> must be assigned a NOT NULL NOT DROPPABLE constraint.
0153S	1136	For an added column, the PRIMARY KEY clause cannot be NOT DROPPABLE.
0153T	1137	Invalid index status. Details: <text>.
0153U	1138	Invalid input parameter(s). Object name and status are required.
0153V	1139	System-generated column <name> of base table <name> cannot appear in the search condition of a check constraint definition.
0153W	1140	Row-length <num> exceeds the maximum allowed row-length of <num> for table <name>.
0153X	1141	Could not obtain an up-and-audited DAM volume. Please check your system configuration.
0153Y	1142	Attempting to add a column with a NULL, UNIQUE, CHECK, PRIMARY KEY, or FOREIGN KEY constraint defined. This is not supported for a non-audited table.

SQLSTATE	SQLCODE	Error Text
0153Z	1143	Validation for constraint <name> failed; incompatible data exists in referencing base table <name> and referenced base table <name>. To display the data violating the constraint, please use the following DML statement: <text>
01540	1144	Expected a quoted string in first key clause for column <name> on table <name>, value detected is (<num>).
01541	1145	The catalog name <name> is reserved for the Trafodion metadata.
01542	1146	Unable to alter object <name> because it is not a <name>.
01543	1147	System-generated column <name> of base table <name> cannot appear in a unique or primary key constraint definition.
01544	1148	System-generated column <name> of base table <name> cannot appear in a referential integrity constraint definition.
01551	1181	Unable to drop object <name> (file error <num>).
01552	1182	Cannot instantiate constraint <name>, conflicting lock exists.
01553	1183	Cannot instantiate module <name>, conflicting lock exists.
01554	1184	Insufficient privilege on <name>.
01555	1185	The location name is either invalid or missing.
01556	1186	Column <name> is of type <type>, incompatible with the default value's type, <type>.
01557	1187	The schema name <name> is reserved for the Trafodion metadata.
01558	1188	Unable to create referential integrity constraint <name> for table <name> due to circular dependency: <name>.
01566	1222	Invalid file type <name>.
01568	1224	Invalid data type for routine param <name>.
01569	1225	Error on access to PROCS table. Trafodion error <integer>.
0156A	1226	Error on access to PARAMS table. Trafodion error <integer>.
0156F	1231	Unable to create user-defined routine <string>.
01600	2000	Error messages for compiler main, IPC, and DEFAULTS table; assertions for optimizer.
01601	2001	Error or warning <num> occurred while opening or reading from DEFAULTS table <name>. Using <name> values.
01602	2002	Internal error: cannot create Trafodion compiler server.
01603	2003	Internal error: cannot establish connection with MXCMP server.
01604	2004	Internal error: error from MXCMP; cannot work on this query.
01605	2005	Internal error: from compilation, no errors in diagnostics yet for statement: <name>
01606	2006	Internal error: assertion failure (<name>) in file <name> at line <num>.
01608	2008	Internal error: out of virtual memory.
01609	2009	The user transaction must be rolled back (or committed, if that makes sense in the application) before MXCMP can be restarted and proceed.
0160A	2010	Internal IPC error.
0160B	2011	Unable to create server process. error <num> while resolving program file name <name>.
0160C	2012	Unable to create server process <name>. error <num>, TPC error = <num>, error detail = <num>. (See procedure PROCESS_LAUNCH_ for details).
0160D	2013	Unable to create server process <name>. error <num> on program file.
0160E	2014	Unable to create server process <name>. error <num> on swap file.
0160F	2015	Unable to create server process <name>. CPU is unavailable ( error <num>).
0160G	2016	Server process <name> was started but had undefined externals.
0160H	2017	Unable to create server process <name>. No more processes (PCBs) available.

SQLSTATE	SQLCODE	Error Text
0160I	2018	Unable to create server process <name>. Library conflict.
0160J	2019	Unable to create server process <name>. Unable to allocate virtual memory.
0160K	2020	Unable to create server process <name>. Unlicensed privileged program.
0160L	2021	System error <num> in <name> from <name>.
0160M	2022	System error <num> in <name> from <name>, detail <num>.
0160N	2023	Unable to create server process <name>. <name>.
0160P	2025	Unable to create server process <name>. CPU is unavailable; <text>.
0160R	2027	Error <num> while sending a startup message to process <name>.
0160S	2028	Unable to create OSS server process <name>. Insufficient resources.
0160T	2029	Unable to create OSS server process <name>. OSS is not running.
0160X	2033	<text>: error <num> while communicating with process <name>.
0160Y	2034	<text>: error <num> while communicating with server process <name>.
0160Z	2035	<text>: Unable to open process <name> (err no = <num>).
01611	2037	<receiving-process>: A message from process <sending-process> was incorrectly formatted and could not be processed.
0161E	2050	<name> is not the name of any DEFAULTS table attribute.
0161F	2051	Invalid <name> option <name> or value '<num>'.
0161G	2052	Optimizer internal counters: <name> <name> <name> <name>.
0161H	2053	ASSERTION FAILURE CAUGHT BY OPTIMIZER! Attempting to recover and produce a plan.
0161J	2055	Invalid value '<num>' for DEFAULTS attribute <name>.
0161K	2056	The value must be a number in the range <num>.
0161L	2057	The value must be a multiple of <num>.
0161M	2058	DEFAULTS attribute <name> is of type <type> but is being converted to <type>.
0161N	2059	Warnings while reading values from DEFAULTS table <name>.
0161O	2060	Procedure <name> has already been defined in this module. The previous definition is being retained and this latest one ignored.
0161P	2061	Static cursor <name> has already been defined in this module. The previous definition, as a static cursor, is being retained and this latest one ignored.
0161Q	2062	Static cursor <name> has already been defined in this module. The previous definition, as a dynamic cursor, is being retained and this latest one ignored.
0161R	2063	Dynamic cursor <name> has already been defined in this module. The previous definition, as a static cursor, is being retained and this latest one ignored.
0161S	2064	Dynamic cursor <name> has already been defined in this module. The previous definition, as a dynamic cursor, is being retained and this latest one ignored.
0161T	2065	Statement <name> was not found in module <name>.
0161U	2066	Cursor <name> was not found in module <name>.
0161V	2067	Descriptor <name> has already been defined in this module. The previous definition is being retained and this latest one ignored.
0161W	2068	A procedure body must be a SELECT, INSERT, UPDATE, DELETE, DECLARE CATALOG, DECLARE SCHEMA, or a static DECLARE CURSOR.
0161X	2069	A static cursor declaration might appear only in the body of a procedure.
0161Y	2070	Invalid statement type in this context.
0161Z	2071	The name <name> has already been declared or defined in this module. The previous definition, as a <name>, is being retained and this latest one ignored.

SQLSTATE	SQLCODE	Error Text
01620	2072	A simple value specification that is a literal is not yet supported.
01621	2073	Only the super ID user can compile system module <name>.
01622	2074	The name <name> is reserved for future system modules.
01628	2080	Error <num> while reading file: <num> bytes were read from <name> when <num> were expected in module <name>.
01629	2081	Error <num> while opening file <name> for read.
0162A	2082	Error <num> while opening file <name> for write.
0162B	2083	Error <num> while naming or locating file <name>.
0162C	2084	Error <num> while writing <num> bytes to file <name>.
0162D	2085	Error <num> while closing file <name>.
0162E	2086	Unable to purge the file <name>. This file contains the results of a failed compilation and should be purged.
0162I	2090	The command line argument for module name, <name>, is being ignored in favor of module name <name> in file <name>.
0162J	2091	The required module statement was not found in file <name>.
0162K	2092	A module statement has already appeared in this file. The previous definition, <name>, is being retained and this latest one ignored.
0162L	2093	A module timestamp statement was not found in file <name>.
0162M	2094	A module timestamp statement has already appeared in this module. The previous timestamp is being retained and this latest one ignored.
0162N	2095	Module file <name>, expected to contain module <name>, instead contains <name>.
0162Q	2098	The <name> compilation completed with <num> warnings.
0162R	2099	The <name> compilation failed with <num> errors and <num> warnings.
0162S	2100	Break was received. The compilation has been aborted.
0162T	2101	Compilation failure due to internal error.
0162U	2102	Unable to compile this query with 'MINIMUM' optimization level. Suggestion: Retry with 'MEDIUM' optimization level.
0162V	2103	Unable to compile this query for one/both of the following reasons: a) Use of 'MINIMUM' optimization level, or b) Incompatible Control Query Shape specifications.
0162W	2104	Unable to compile this query for one of two reasons: a) Incompatible Control Query Shape (CQS) specifications, or b) 'MEDIUM' optimization level is not sufficient to satisfy the CQS in effect.  Suggestion: a) Inspect the CQS in effect; or b) Raise the optimization level to 'MAXIMUM'. Note that for this query, 'MAXIMUM' optimization level might result in a long compile time.
0162X	2105	Unable to compile this query because of incompatible Control Query Shape (CQS) specifications. Suggestion: Inspect the CQS in effect.
0162Y	2106	Unable to compile this statement since it is too long. Suggestion: Break up large statements into smaller pieces.
0162Z	2107	Unable to compile this statement. Suggestion: Address the issue(s) raised in the reported warning(s).
01630	2108	Statement was compiled as if query plan caching were off.
0165K	2200	DEFAULTS attribute <name> is read-only.
016P0	2900	in file <name> at line <num>:
01700	3000	An internal error occurred in module <name> on line <number>. DETAILS (<detailed-text>).
01701	3001	Syntax error at or before <SQL-text>.

SQLSTATE	SQLCODE	Error Text
01702	3002	<name> is not a valid column reference; it has more than 4 name parts.
01703	3003	Length or precision must be greater than zero.
01704	3004	A delimited identifier must contain at least one non-blank character.
01705	3005	A DECLARE CURSOR statement cannot dynamically get its cursor name from a host variable while also statically declaring a cursor specification. A dynamic cursor requires the name of a previously prepared statement, or a host variable containing such a name; a static cursor requires a fixed, static name.
01706	3006	In a dynamic cursor declaration both the cursor and the statement must be named in the same way: both must be literals or both must be string host variable expressions.
01707	3007	In an ALLOCATE CURSOR statement both the cursor and the statement must be named using string host variables.
01708	3008	Precision of <type> UNSIGNED data type, <value>, cannot exceed 9.
01709	3009	DROP ASSERTION statement is not yet supported.
0170A	3010	Character set <name> is not yet supported.
0170B	3011	<name> is not a valid qualified name; it has more than 3 name parts.
0170C	3012	COUNT is the only aggregate function that accepts (*) as an operand.
0170D	3013	Subtraction is the only operation allowed in the parenthesized expression preceding an interval qualifier.
0170E	3014	Precision of numeric, <value>, cannot exceed 18.
0170F	3015	Scale <value> cannot exceed precision <value>.
0170G	3016	Precision of decimal, <value>, cannot exceed 18.
0170H	3017	Expected an unsigned integer, not <value>.
0170I	3018	Expected an unsigned smallint, not <value>.
0170J	3019	Expected an unsigned number within the parentheses, not <value>.
0170K	3020	Expected an unsigned number as the first operand within the parentheses, not <value>.
0170L	3021	Expected an unsigned number as the second operand within the parentheses, not <value>.
0170M	3022	The <name> operator is not yet supported.
0170N	3023	The COLLATE clause in a sort specification is not yet supported.
0170O	3024	The MATCH PARTIAL clause is not yet supported.
0170P	3025	The format of the subvolume name part in the specified location name <name> is invalid. The subvolume name part must be eight characters long and begin with the letters ZSD.
0170Q	3026	A comma must be used to separate file attributes.
0170R	3027	<name> is not a valid simple name; it has more than one name part.
0170S	3028	Specifying a privilege column list in the INSERT clause is not yet supported.
0170T	3029	<name> is not yet supported in referential integrity constraint definition.
0170U	3030	The PARALLEL EXECUTION clause is not yet supported.
0170V	3031	CASCADE drop behavior is not yet supported.
0170W	3032	The COLUMN clause in the ALTER TABLE statement is not yet supported.
0170X	3033	The MOVE clause in the ALTER TABLE statement is not yet supported.
0170Y	3034	The PARTITION clause in the ALTER TABLE statement is not yet supported.
0170Z	3035	The RENAME clause in the ALTER TABLE statement is not yet supported.
01710	3036	The SET CONSTRAINT clause in the ALTER TABLE statement is not yet supported.
01711	3037	Precision of type <data-type> cannot exceed 18.

SQLSTATE	SQLCODE	Error Text
01712	3038	PIC X types cannot have leading signs, or any signs at all.
01713	3039	PIC X types do not have any COMP representation.
01714	3040	Precision zero is invalid. Add a '9' to the PICTURE clause.
01715	3041	UNSIGNED is invalid for a numeric or decimal type with a scale greater than 9.
01716	3042	UPSHIFT for a numeric type is invalid.
01717	3043	Precision greater than 18 for a COMP numeric type is invalid.
01718	3044	Invalid interval <value>.
01719	3045	Invalid date <value>.
0171A	3046	Invalid time <value>.
0171B	3047	Invalid timestamp <timestamp>.
0171C	3048	Dynamic parameters, such as <name>, are not allowed in a static compilation.
0171D	3049	Host variables, such as <name>, are not allowed in a dynamic compilation.
0171E	3050	The constraint must have the same catalog and schema as the specified table.
0171F	3051	Duplicate HEADING clauses in column definition <name>.
0171G	3052	Duplicate NOT NULL clauses in column definition <name>.
0171H	3053	Duplicate PRIMARY KEY clauses in column definition <name>.
0171I	3054	The NOT DROPPABLE clause is allowed only in PRIMARY KEY and NOT NULL constraint definitions.
0171J	3055	Duplicate DELETE rules specified.
0171K	3056	Duplicate UPDATE rules specified.
0171L	3057	Invalid size value in the ALLOCATE clause.
0171M	3058	The BLOCKSIZE value must be 4096.
0171N	3059	Invalid size value in the MAXSIZE clause.
0171O	3060	Invalid percentage value in the DSLACK clause.
0171P	3061	The format of the specified location name <name> is invalid.
0171Q	3062	Duplicate MAXSIZE clauses in the PARTITION clause.
0171R	3063	Duplicate DSLACK clauses in the PARTITION clause.
0171S	3064	Duplicate ISLACK clauses in the PARTITION clause.
0171T	3065	The primary key constraint cannot be droppable when the STORE BY PRIMARY KEY clause appears in a table definition.
0171V	3067	ALTER TABLE ADD CONSTRAINT allows only DROPPABLE constraints.
0171W	3068	The ALLOCATE and DEALLOCATE clauses cannot coexist in the same ALTER INDEX statement.
0171Y	3070	The [NO]AUDIT clause is not supported.
0171Z	3071	Duplicate [NO]AUDITCOMPRESS clauses.
01720	3072	The BLOCKSIZE clause is not allowed in the ALTER INDEX . . . ATTRIBUTE(S) statement.
01721	3073	Duplicate [NO]BUFFERED clauses.
01722	3074	Duplicate [NO]CLEARONPURGE clauses.
01723	3075	The [NO]COMPRESS clause is not allowed in the ALTER INDEX . . . ATTRIBUTE(S) statement.
01724	3076	Duplicate DEALLOCATE clauses.
01725	3077	The [NO]ICOMPRESS clause is not allowed in the ALTER INDEX . . . ATTRIBUTE(S) statement.

SQLSTATE	SQLCODE	Error Text
01726	3078	The LOCKLENGTH clause is not allowed in the ALTER INDEX . . . ATTRIBUTE(S) statement.
01727	3079	Duplicate MAXSIZE clauses.
01728	3080	The [NO]SERIALWRITES clause is not supported.
01729	3081	Duplicate ALLOCATE clauses.
0172A	3082	Duplicate [NO]AUDIT clauses.
0172B	3083	Duplicate [NO]AUDITCOMPRESS clauses.
0172C	3084	The BLOCKSIZE clause is not allowed in the ALTER TABLE . . . ATTRIBUTE(S) statement.
0172D	3085	Duplicate [NO]BUFFERED clauses.
0172E	3086	Duplicate [NO]CLEARONPURGE clauses.
0172F	3087	The [NO]COMPRESS clause is not allowed in the ALTER TABLE . . . ATTRIBUTE(S) statement.
0172G	3088	The ALLOCATE AND DEALLOCATE cannot coexist in the same ALTER TABLE statement.
0172H	3089	The [NO]ICOMPRESS clause is not allowed in the ALTER TABLE . . . ATTRIBUTE(S) statement.
0172I	3090	Duplicate LOCKLENGTH clauses.
0172J	3091	The [NO]AUDIT clause is not allowed in the CREATE INDEX statements.
0172K	3092	Duplicate BLOCKSIZE clauses.
0172L	3093	Duplicate DCOMPRESS clauses.
0172M	3094	The DEALLOCATE clause is not allowed in the CREATE INDEX statements.
0172N	3095	Duplicate [NO]ICOMPRESS clauses.
0172O	3096	Duplicate [NO]SERIALWRITES clauses.
0172P	3097	The DEALLOCATE clause is not allowed in the CREATE TABLE statements.
0172Q	3098	Duplicate LOCATION clauses.
0172R	3099	Duplicate FILE ATTRIBUTE(S) clauses.
0172S	3100	Duplicate DSLACK clauses.
0172T	3101	Duplicate ISLACK clauses.
0172U	3102	Duplicate PARALLEL EXECUTION clauses.
0172V	3103	Duplicate PARTITION clauses.
0172W	3104	Only the ADD option is allowed in a PARTITION clause in a CREATE TABLE statement.
0172X	3105	Currently only range, hash and system partitioning are supported.
0172Y	3106	Duplicate PRIMARY KEY clauses.
0172Z	3107	Duplicate LIKE clauses.
01730	3108	The LIKE clause and STORE BY clause cannot coexist in the same statement.
01731	3109	Duplicate STORE BY clauses.
01732	3110	The LIKE clause and ATTRIBUTE(S) clause cannot coexist in the same statement.
01733	3111	The LIKE clause and LOCATION clause cannot coexist in the same statement.
01734	3112	The LIKE clause and PARTITION clause cannot coexist in the same statement.
01735	3113	Error in CONTROL statement: <error>
01736	3114	Transaction access mode READ WRITE is incompatible with isolation level READ UNCOMMITTED.
01737	3115	Duplicate ISOLATION LEVEL clause specified.
01738	3116	Duplicate transaction access mode clause specified.

SQLSTATE	SQLCODE	Error Text
01739	3117	Duplicate DIAGNOSTICS SIZE specified.
0173A	3118	Identifier too long.
0173B	3119	The WITH LOCAL CHECK OPTION clause is not supported.
0173C	3120	The CREATE ASSERTION statement is not yet supported.
0173D	3121	Partitioned entry-sequenced tables are not yet supported.
0173E	3122	The format of the system name part in the specified location name <name> is invalid.
0173F	3123	The format of the file name part in the specified location name <name> is invalid. The file name part must be eight characters long and end with the digits 00.
0173J	3127	Invalid character in identifier <name>.
0173K	3128	<object-name> is a reserved word. It must be delimited by double-quotes to be used as an identifier.
0173L	3129	Function <name> accepts exactly one operand.
0173M	3130	UNSIGNED option is not supported for LARGEINT type.
0173N	3131	The statement just specified is currently not supported.
0173O	3132	The HEADING for column <name> exceeds the maximum size of 128 characters.
0173P	3133	PERFORM is valid only in COBOL programs.
0173Q	3134	Precision of time or timeStamp, <value>, cannot exceed 6.
0173R	3135	Precision of float, <value>, cannot exceed 54.
0173S	3136	Only LEFT, RIGHT, and FULL OUTER JOIN are valid in {oj . . .}
0173T	3137	UNION JOIN is not yet supported.
0173U	3138	A key-sequenced table with range partitioning requires a FIRST KEY clause.
0173V	3139	A range-partitioned index requires a FIRST KEY clause.
0173W	3140	The isolation level cannot be READ UNCOMMITTED for an INSERT, UPDATE, DELETE, or DDL statement.
0173X	3141	The transaction access mode cannot be READ ONLY for an INSERT, UPDATE, DELETE, or DDL statement.
0173Y	3142	INTO clause host variables are not allowed in a static cursor.
0173Z	3143	BROWSE or READ UNCOMMITTED access is not allowed on a table value constructor.
01741	3145	Positioned UPDATE or DELETE is allowed only in embedded SQL.
01743	3147	In an IN predicate whose right operand is a value list, the left operand must be scalar (degree of one).
01744	3148	Environment variable <name> is being ignored because this version of the code is Release, not Debug. Actual query results will likely not match expected results.
01745	3149	Duplicate WITH CONSTRAINTS phrases in LIKE clause in CREATE TABLE statement.
01746	3150	Duplicate WITH HEADING phrases in LIKE clause in CREATE TABLE statement.
01747	3151	Duplicate WITH HORIZONTAL PARTITIONS phrases in LIKE clause in CREATE TABLE statement.
01749	3153	The FIRST KEY clause is not allowed with hash partitioning.
0174B	3155	The POPULATE and NO POPULATE clauses cannot coexist in the same CREATE INDEX statement.
0174D	3157	Catalog name is required.
0174E	3158	Invalid DATETIME <name>.
0174F	3159	If you intended <name> to be a character set specifier for a character string literal, you must remove the spaces in front of the single quote delimiter.
0174G	3160	<name> was declared more than once in the procedure parameter list.

SQLSTATE	SQLCODE	Error Text
0174H	3161	<name> was not declared in the procedure parameter list.
0174I	3162	Procedure parameter <name> was not used.
0174J	3163	Host variable <name> appears more than once in the INTO list. Execution results will be undefined.
0174K	3164	Data type mismatch between output host variable and selected value.
0174L	3165	Min or max precision or exponent value exceeded, <num>.
0174M	3166	Min or max value for float or double value exceeded, <num>.
0174N	3167	Duplicate [ NOT ] DROPPABLE clauses.
0174O	3168	The FOR . . . ACCESS clause is not allowed in a CREATE VIEW statement.
0174P	3169	<name> is not a known collation.
0174R	3171	Transaction statements are not allowed in compound statements.
0174S	3172	EXIT is not allowed in a compound statement.
0174T	3173	UPDATE STATISTICS is not allowed in a compound statement.
0174U	3174	DDL statements are not allowed in compound statements.
0174V	3175	Dynamic SQL statements are not allowed in compound statements.
0174W	3176	Subqueries are not allowed in the IF Condition.
0174X	3177	Character set <name> requires an even number of characters in the length declaration of the data type.
0174Y	3178	One or more of the following external (host-language) data types incorrectly appears within the SQL query or operation: <name>.
0174Z	3179	Collation <name> is not defined on the character set <name>.
01750	3180	STREAM statements are not allowed in compound statements.
01751	3181	Invalid logical name, a three part logical name is required.
01752	3182	Extra semicolon(;) in a compound statement.
01757	3187	Not supported: SET STREAM TIMEOUT per a specific stream.
01759	3189	Cannot set lock timeout on a view.
0175L	3201	EXTERNAL PATH clause is required.
0175M	3202	PARAMETER STYLE clause is required.
0175N	3203	LANGUAGE clause is required.
0175O	3204	EXTERNAL NAME clause is badly formed.
0175P	3205	EXTERNAL NAME clause is required.
0175Q	3206	The name for an object of this type must be fully qualified, or set NAMETYPE ANSI.
0175R	3207	Value for DYNAMIC RESULT SETS must be zero.
0175S	3208	UNSIGNED numeric is not allowed for routine parameter.
01800	4000	Internal error in the query binder.
01801	4001	Column <name> is not found. Tables in scope: <name>. Default schema: <name>.
01802	4002	Column <name> is not found. Table <name> not exposed. Tables in scope: <name>. Default schema: <name>.
01803	4003	Column <name> is not a column in table <name>, or, after a NATURAL JOIN or JOIN USING, is no longer allowed to be specified with a table correlation name.
01804	4004	Column name <name> is ambiguous. Tables in scope: <name>. Default schema: <name>.
01805	4005	Column reference <name> must be a grouping column or be specified within an aggregate.
01806	4006	Within an aggregate, all column references must come from the same scope.

SQLSTATE	SQLCODE	Error Text
01807	4007	The select list index <num> is out of range. It must be between 1 and the number of select expressions, which in this case is <num>.
01808	4008	A subquery is not allowed inside an aggregate function.
01809	4009	An aggregate is not allowed inside an aggregate function.
0180A	4010	There are no columns with the correlation name <name>.
0180B	4011	Ambiguous star column reference <name>.
0180C	4012	Column reference <name> must be a grouping column or be specified within an aggregate. On this grouped table a star reference is not allowed.
0180D	4013	Column <name> is a system column and cannot be updated or inserted into.
0180E	4014	The operands of an INTERSECT must be of equal degree.
0180F	4015	Aggregate functions placed incorrectly: <name>.
0180G	4016	The number of derived columns (<num>) must equal the degree of the derived table (<num>).
0180H	4017	Derived column name <name> was specified more than once.
0180I	4018	Rows cannot be deleted from an entry-sequenced table.
0180J	4019	The select list of a subquery in a select list must be scalar (degree of one).
0180K	4020	Arithmetic operations on row value constructors are not allowed.
0180L	4021	The select list contains a nongrouping non-aggregated column, <name>.
0180M	4022	Target column <name> was specified more than once.
0180N	4023	The degree of each row value constructor (<num>) must equal the degree of the target table column list (<num>).
0180O	4024	Column <name> has no default value, so must be explicitly specified in the insert column list.
0180P	4025	Error while preparing constraint <name> on table <name>.
0180Q	4026	Reading from and inserting into, or updating in, or deleting from the same table, <name>, is not currently supported.
0180R	4027	Table <name> is not insertable.
0180S	4028	Table <name> is not updateable.
0180U	4030	Column <name> is an invalid combination of datetime fields (<num>, <num>, <num>).
0180V	4031	Column <name> is an unknown data type, <num>.
0180W	4032	Column <name> is an unknown class, <num>. It is neither a system column nor a user column.
0180X	4033	Column <name> is a primary or clustering key column and cannot be updated.
0180Y	4034	The operation (<name> <name> <name>) <name> is not allowed.
0180Z	4035	Type <name> cannot be cast to type <type>.
01810	4036	The source field of the EXTRACT function must be of DateTime or Interval type.
01811	4037	Field <name> cannot be extracted from a source of type <type>.
01812	4038	The operand of an AVG or SUM function must be numeric or interval.
01813	4039	Column <name> is of type <type>, incompatible with the value's type, <type>.
01814	4040	The operands of a BETWEEN predicate must be of equal degree.
01815	4041	Type <name> cannot be compared with type <name>.
01816	4042	The operands of a comparison predicate must be of equal degree.
01817	4043	The operand of function <name> must be character.
01818	4044	Collation <name> does not support the <name> predicate or function.

SQLSTATE	SQLCODE	Error Text
01819	4045	The operand of function <name> must be numeric.
0181A	4046	The operands of function <name> must be exact numeric.
0181B	4047	The operands of function <name> must have a scale of 0.
0181C	4048	The third operand of a ternary comparison operator must be of type BOOLEAN, not <name>.
0181D	4049	A CASE expression cannot have a result data type of both <type> and <type>.
0181E	4050	The operands of the <name> predicate must be comparable character data types (that is, of the same character set and collation).
0181F	4051	The first operand of function <name> must be character.
0181G	4052	The second operand of function <name> must be numeric.
0181H	4053	The third operand of function <name> must be numeric.
0181J	4055	The select lists or tuples must have comparable data types. <type> and <type> are not comparable.
0181K	4056	Exposed name <name> appears more than once.
0181L	4057	Correlation name <name> conflicts with qualified identifier of table <name>.
0181N	4059	The first operand of function <name> must be numeric.
0181O	4060	Reading from and inserting into, or updating in, or deleting from the same table, <name>, is not currently supported. <name> is contained by view(s) <name>.
0181P	4061	Rows cannot be inserted into, or updated in, an individual table partition.
0181Q	4062	The preceding error actually occurred in function <name>.
0181R	4063	The operands of function <name> must be comparable character data types (that is, of the same character set and collation).
0181S	4064	The operands of function <name> must be compatible character data types (that is, of the same character set).
0181U	4066	The operands of a UNION must be of equal degree.
0181V	4067	The operands of function <name> must be character data types.
0181W	4068	The operand of function <name> must contain an even number of characters.
0181X	4069	Column <name> uses an unsupported collation, <name>.
0181Y	4070	The operand of function <name> must be exact numeric.
0181Z	4071	The first operand of function <name> must be a datetime.
01820	4072	The operand of function <name> must be a datetime containing a <name>.
01821	4073	The COLLATE clause might appear only after an expression of character data type, not <name>.
01822	4074	CONTROL QUERY successful.
01823	4075	Division by zero in constant expression <name>.
01824	4076	Overflow in constant expression <name>.
01825	4077	Function <name> accepts only one or two operands.
01826	4078	Function <name> does not accept a weight operand.
01827	4079	The operands of function <name> must be numeric.
0182A	4082	Table <name> does not exist or is inaccessible.
0182C	4084	SQL object <name> is corrupt.
0182D	4085	File organization <type> of object <name> is not supported.
0182E	4086	Environment variable or define <name> does not exist.
0182F	4087	Prototype value '<name>' is not a valid qualified name.

SQLSTATE	SQLCODE	Error Text
0182G	4088	The number of values in each TRANSPOSE item of a TRANSPOSE set must be equal.
0182H	4089	Check constraint <name> contains a subquery, which is not yet supported.
0182L	4093	The number of output dynamic parameters (<num>) must equal the number of selected values (<num>).
0182M	4094	The number of output host variables (<num>) must equal the number of selected values (<num>).
0182N	4095	A DEFAULT whose value is NULL is not allowed in <name>.
0182O	4096	A DEFAULT specification is currently allowed only when simply contained in the VALUES list of an INSERT.
0182P	4097	A NULL operand is not allowed in function <name>.
0182Q	4098	A NULL operand is not allowed in operation <name>.
0182R	4099	A NULL operand is not allowed in predicate <name>.
0182S	4100	A NULL value is not allowed in a select list unless it is CAST to some data type.
0182T	4101	If <name> is intended to be a further table reference in the FROM clause, the preceding join search condition must be enclosed in parentheses.
0182U	4102	The FIRST/ANY n syntax cannot be used with in an outermost SELECT statement.
0182W	4104	If a character literal was intended, you must use the single quote delimiter instead of the double: <name> instead of <name>.
0182X	4105	Unknown translation.
0182Y	4106	The character set for the operand of function <name> must be <name>.
0182Z	4107	Column <name> has no default value, so DEFAULT cannot be specified.
01830	4108	Inside a ROWS SINCE, another sequence function contained an invalid reference to the THIS function.
01831	4109	Sequence functions placed incorrectly: <name>.
01832	4110	The query contains sequence functions but no SEQUENCE BY clause: <name>.
01833	4111	The query contains a SEQUENCE BY clause but no sequence functions.
01834	4112	Absolute and relative sampling cannot occur in the same BALANCE expression.
01835	4113	The sample size for <name> Sampling must be <num>.
01836	4114	An absolute sample size must have a scale of zero.
01837	4115	The sample size must be less than or equal to the sample period.
01838	4116	The second operand of function <name> is invalid.
01839	4117	The cursor query expression might be nonupdateable.
0183A	4118	The cursor query expression is not updateable.
0183C	4120	In a query with a GROUP BY, DISTINCT, or aggregate function, each column in the ORDER BY clause must be one of the columns explicitly SELECTed by the query. Column in error: <name>.
0183D	4121	In a query with a GROUP BY, DISTINCT, or aggregate function, each column in the ORDER BY clause must be one of the columns explicitly SELECTed by the query. Column in error: <name>. Table in scope: <name>.
0183E	4122	NULL cannot be assigned to NOT NULL column <name>.
0183F	4123	NULL cannot be cast to a NOT NULL data type.
0183G	4124	More than one table will be locked: <name>.
0183H	4125	The select list of a subquery in a row value constructor, if the subquery is one of several expressions rather than the only expression in the constructor, must be scalar (degree of one).
0183I	4126	The row value constructors in a VALUES clause must be of equal degree.

SQLSTATE	SQLCODE	Error Text
0183J	4127	Type <type> cannot be assigned to type <type>.
0183K	4128	Cannot retrieve default volume and subvolume information from =_DEFAULTS define, DEFINEINFO error <num>.
0183Q	4134	The operation (<name>) is not allowed. Try UNION ALL instead.
01846	4150	Primary key of table expression <name> must be used for join with embedded <name> expression. Tables in scope: <name>.
01847	4151	Stream access supported only on updateable views <name>.
01848	4152	Table <name> cannot be both read and updated.
01849	4153	Statement might not compile due to an order requirement on stream expression.
0184A	4154	Statement might not compile due to an order requirement on embedded <name> expression.
0184D	4157	Inner relation of left join cannot be stream expression. Tables in scope: <name>.
0184E	4158	Join of stream expressions not supported. Tables in scope: <name>.
0184F	4159	Intersection of stream expressions not supported. Tables in scope: <name>.
0184G	4160	Intersection between embedded <name> expression and embedded <name> expression not supported. Tables in scope: <name>, <name>.
0184H	4161	Union between embedded <name> expression and embedded <name> expression not supported. Tables in scope: <name>, <name>.
0184I	4162	Groupby not supported for stream expression. Tables in scope: <name>.
0184J	4163	Groupby not supported for embedded <name> expression. Tables in scope: <name>.
0184K	4164	Outer relation of right join cannot be embedded <name> expression. Tables in scope: <name>.
0184L	4165	Outer relation of right join cannot be stream expression. Tables in scope: <name>.
0184M	4166	ORDER BY clause not supported in UNION of two streams. Tables in scope: <name>, <name>.
0184N	4167	Embedded <name> statements not supported in subqueries.
0184O	4168	Stream expressions not supported in subqueries.
0184P	4169	Embedded DELETE statements not allowed when using DECLARE . . . FOR UPDATE clause.
0184Q	4170	Stream expressions not supported for insert statements.
0184R	4171	Embedded <name> statements not supported in INSERT statements.
0184T	4173	Stream expression not supported for top level UPDATE statements.
0184U	4174	JOIN_ORDER_BY_USER prevented compiler from reordering query tree.
0184V	4175	Join between embedded <name> expression and embedded <name> expression not supported. Tables in scope: <name>.
0184W	4176	Join between stream expression and embedded <name> expression not supported. Tables in scope: <name>.
0184X	4177	Update of <name> column <name> not permitted on rollback.
0184Y	4178	Update of variable length column <name> not permitted on rollback.
0184Z	4179	SEQUENCE BY not supported for stream expressions.
01850	4180	Stream expression not supported for top level DELETE statement.
0185K	4200	Stream expressions not supported for compound statements.
0185L	4201	Embedded <type> expression not supported for compound statements.
0185M	4202	SEQUENCE BY not supported for embedded <type> expressions.

SQLSTATE	SQLCODE	Error Text
0185N	4203	INSERT/UPDATE/DELETE operation on nonaudited table <name> requires index maintenance which might cause the index(es) to become corrupt.
0185O	4204	Stream access supported only for key-sequenced tables. Table: <name>.
0185P	4205	Embedded <type> supported only for key-sequenced tables. Table: <name>.
0185Q	4206	Embedded <type> supported only for updateable views. View: <name>.
0185R	4207	Index <name> and other indexes covering a subset of columns do not cover all output values of stream.
0185S	4208	Index <name> and other indexes covering a subset of columns do not cover all columns referenced in where clause of stream.
0185T	4209	Update of nullable column <name> not permitted on rollback.
0185U	4210	Embedded UPDATE/DELETE statements are not supported within an IF statement.
0185W	4212	<table-name> cannot be used to satisfy order requirement on the stream because it is partitioned.
0185X	4213	Use of rowsets in a predicate with embedded UPDATE/DELETE not supported.
0185Y	4214	The SET ON ROLLBACK clause is not allowed on a non-audited table. Table: <name>.
0185Z	4215	Stream access is not allowed on a nonaudited table. Table: <name>.
01860	4216	The FIRST/ANY n syntax cannot be used with an embedded update or embedded DELETE statement.
01861	4217	<text>
0188C	4300	Invalid usage of procedure <procedure-name> - A UDR was invoked within a trigger.
0188E	4302	Procedure <procedure-name> expects <value-1> parameters but was called with <value-2> parameters.
0188F	4303	The supplied type for parameter value of routine <routine-name> was <type-name-1> which is not compatible with the expected type <type-name-2>.
0188G	4304	Host variable or dynamic parameter <parameter-name> is used in more than one OUT or INOUT parameter for routine routine-name. Results might be unpredictable.
0188H	4305	Parameter <value> for used defined routine <routine-name> is an OUT or INOUT parameter and must be a host variable or a dynamic parameter.
0188I	4306	A CALL statement is not allowed within a compound statement.
0188J	4307	Rowset parameters are not allowed in a CALL statement.
0188K	4308	Internal error: unsupported SQL data type <value> specified for a CALL statement parameter.
01900	5000	Internal error in the query normalizer.
01I00	6000	Internal error in the query optimizer.
01I01	6001	DISTINCT aggregates can be computed only for one column per table expression.
01I02	6002	The metadata table HISTOGRAMS or HISTOGRAM_INTERVALS contains invalid values. If you have manually modified the metadata table, then you should undo your changes using the CLEAR option in UPDATE STATISTICS.
01I07	6007	Multi-column statistics for columns <name> from table <name> were not available; as a result, the access path chosen might not be the best possible.
01I08	6008	Statistics for column <name> were not available; as a result, the access path chosen might not be the best possible.
01J00	7000	Internal error in the code generator in file <name> at line <num>: <text>.
01J01	7001	Invalid default value <name> for column <name>.
01J03	7003	A plan using cluster sampling could not be produced for this query.
01K01	8001	Internal executor error.

SQLSTATE	SQLCODE	Error Text
01K02	8002	The current nowaited operation is not complete.
01K03	8003	The descriptor is locked by another nowaited operation.
01K04	8004	Trying to open a statement or cursor that is not in the closed state.
01K05	8005	Trying to fetch from a cursor that is not in the open state.
01K06	8006	The stream timed out, but the cursor is still open.
01K07	8007	The operation has been canceled.
01K08	8008	Catalog name <name> is invalid.
01K09	8009	Schema name <name> is invalid.
01K0A	8010	Default catalog name: <name>. Default schema name: <name>.
01K0B	8011	SELECT statement inside compound (BEGIN . . . END) statement returns more than one row.
01K0C	8012	Encoding of CONTROL QUERY DEFAULTs: <name>.
01K0D	8013	Trying to update or delete from a cursor that is not in the fetched state.
01K0E	8014	A SELECT statement within a compound statement did not return any row.
01K0F	8015	Aborting transaction because a compound statement performed an update operation followed by a SELECT statement that did not return any row.
01K0G	8016	An attempt was made to access <name> which has a system version that is incompatible with the version of the accessing software.
01K0H	8017	Explain information is not available for this query.
01K2S	8100	Define <name> does not exist
01K2T	8101	The operation is prevented by check constraint <name> on table <name>.
01K2U	8102	The operation is prevented by a unique constraint.
01K2V	8103	The operation is prevented by referential integrity constraint <name> on table <name>.
01K2W	8104	The operation is prevented by the check on view <name> cascaded from the check option on <name>.
01K2X	8105	The operation is prevented by the check option on view <name>.
01K3W	8140	The statement was canceled, to test cancel processing. File <name> at line <num>.
01K3X	8141	An error was artificially injected, to test error handling. File <name> at line <num>.
01K8C	8300	Late name resolution failed.
01K8D	8301	Late name resolution failed. File system error <num> on file <name>.
01K8E	8302	Late name resolution failed. SQLCODE error <num> from <name>.
01KB7	8403	The length argument of function SUBSTRING cannot be less than zero or greater than source string length.
01KB8	8404	The trim character argument of function TRIM must be one character in length.
01KB9	8405	The operand of function CONVERTTIMESTAMP is out of range.
01KBB	8407	The operand of function JULIANTIMESTAMP is out of range.
01KBD	8409	The escape character argument of a LIKE predicate must be one character in length.
01KBE	8410	An escape character in a LIKE pattern must be followed by another escape character, an underscore, or a percent character.
01KBF	8411	A numeric overflow occurred during an arithmetic computation or data conversion.
01KBG	8412	An input character host variable is missing its null terminator.
01KBH	8413	The string argument contains characters that cannot be converted.
01KBI	8414	The attempted conversion is not supported on this platform.
01KBJ	8415	The provided DATE, TIME, or TIMESTAMP is not valid and cannot be converted.

SQLSTATE	SQLCODE	Error Text
01KBK	8416	A datetime expression evaluated to an invalid datetime value.
01KBL	8417	An error occurred during the evaluation of a USER function.
01KBM	8418	The USER function is not supported on this platform.
01KBN	8419	An arithmetic expression attempted a division by zero.
01KBO	8420	Missing indicator parameter for a NULL value.
01KBP	8421	NULL cannot be assigned to a NOT NULL column.
01KBQ	8422	The provided INTERVAL is not valid and cannot be converted.
01KBR	8423	The provided field number is not valid.
01KBS	8424	Function <name> is not yet supported.
01KBT	8425	NULL cannot be assigned to a DEFAULT NULL NOT NULL column.
01KBV	8427	<text>
01KBW	8428	The argument to function <name> is not valid.
01KBX	8429	The preceding error actually occurred in function <name>.
01KFA	8550	Error <num> was returned by the Data Access Manager.
01KFB	8551	Error <num> was returned by the Distribution Service on <name>.
01KFC	8552	Error <num> was returned by the Distribution Service while fetching the version of the system <name>.
01KFD	8553	Stream overflow; subscription rate has fallen too far behind publishing rate.
01KFU	8570	Insufficient memory to build query.
01KFW	8571	Insufficient memory to execute query.
01KFW	8572	The statement has incurred a fatal error and must be deallocated.
01KFX	8573	The user does not have <name> privilege on table or view <name>.
01KFY	8574	An OPEN was blown away on table <name>.
01KFZ	8575	Timestamp mismatch on table <name>.
01KG0	8576	Statement was recompiled.
01KG1	8577	Table, index, or view <name> not found.
01KG2	8578	Similarity check passed.
01KG3	8579	Similarity check failed: <name>
01KGP	8601	Error returned from file system while locking/unlocking.
01KGQ	8602	The file system reported error <num> on a lock/unlock operation.
01KGR	8603	Trying to begin a transaction that has already been started.
01KGS	8604	Transaction subsystem <name> returned error <num> while starting a transaction.
01KGT	8605	Committing a transaction which has not started.
01KGU	8606	Transaction subsystem <name> returned error <num> on a commit transaction.
01KGV	8607	Rolling back a transaction that has not started.
01KGW	8608	Transaction subsystem <name> returned error <num> on rollback transaction.
01KGX	8609	Waited rollback performed without starting a transaction.
01KGY	8610	Transaction subsystem <name> reported error <num> on a waited rollback transaction.
01KH0	8612	Transaction mode cannot be set if the transaction is already running.
01KH1	8613	SQL cannot commit or rollback a transaction that was started by application.
01KH2	8614	SQL cannot begin a transaction when multiple contexts exist.
01KJG	8700	An assertion failure or out-of-memory condition occurred during parallel execution.
01KJQ	8710	Error <num> returned by Measure when attempting to update SQL counters.

SQLSTATE	SQLCODE	Error Text
01KM9	8801	Trying to allocate a descriptor that already exists in the current context.
01KMA	8802	Trying to allocate a statement that already exists in the current context.
01KMB	8803	The input descriptor provided does not exist in the current context.
01KMC	8804	The input statement provided does not exist in the current context.
01KMD	8805	Trying to <action> a descriptor that is not allocated with AllocDesc() call.
01KME	8806	Trying to <action> a statement that is not allocated with AllocStmt() call.
01KMF	8807	Trying to allocate more than <num> entries for a descriptor.
01KMG	8808	Module file <name> contains corrupted or invalid data.
01KMH	8809	Unable to open the module file <name>.
01KMJ	8811	Trying to close a statement that is either not in the open state or has not reached EOF.
01KMK	8812	Trying to execute a statement that is not in the closed state.
01KML	8813	Trying to fetch from a statement that is in the closed state.
01KMM	8814	The transaction mode at run time (<num>) differs from that specified at compile time (<num>).
01KMN	8815	Error while building the TCB tree when executing the statement.
01KMO	8816	Error while executing the TCB tree.
01KMP	8817	Error while fetching from the TCB tree.
01KMQ	8818	Error from root_tdb describe.
01KMR	8819	Begin transaction failed while preparing the statement.
01KMS	8820	Transaction commit failed while closing the statement.
01KMT	8821	Rollback transaction failed during the process of fetching the statement.
01KMU	8822	Unable to prepare the statement.
01KMV	8823	Internal error: IO requests are waiting for <name> message in the IpcMessageStream.
01KMW	8824	The input <module-id> does not have a module name.
01KMX	8825	Module is already added into the current context.
01KMY	8826	Unable to add the module.
01KMZ	8827	Unable to send the request <name>.
01KN0	8828	Out of memory while creating the <name>.
01KN1	8829	Trying to set descriptor item for an entry that is either invalid or greater than the maximum entry count for that descriptor.
01KN2	8830	There is no current context.
01KN3	8831	Either no current context or the module to which the statement belongs is not added to the current context.
01KN4	8832	Transaction has not been started.
01KN5	8833	The input parameter is an invalid SQL transaction command.
01KN6	8834	Unable to find Trafodion installation directory. Operating system error <num>.
01KN7	8835	Invalid SQL descriptor information requested.
01KN8	8836	Invalid update column for cursor.
01KN9	8837	Invalid user id.
01KNA	8838	Unable to receive reply from MXCMP, possibly caused by internal errors when compiling SQL statements, processing DDL statements, or executing the built in stored procedures.
01KNB	8839	Transaction was aborted.
01KNC	8840	Object name provided to CLI is invalid.

SQLSTATE	SQLCODE	Error Text
01KND	8841	User application committed or aborted a transaction started by SQL. This transaction needs to be committed or aborted by calling SQL COMMIT or ROLLBACK WORK.
01KNE	8842	The cursor, <name>, referenced by this statement is not found or is not updateable.
01KNF	8843	Trying to retrieve an item, <num>, that is out of range.
01KNG	8844	A transaction started by SQL that was committed or aborted by user application from outside of SQL, has now been cleaned up.
01KNH	8845	Internal error: root_tcb is null.
01KNI	8846	Empty SQL statement.
01KNK	8848	Cancel on DDL statements or stored procedures is not supported.
01KNM	8850	The table specified in this cursor update or DELETE statement is different than the table specified in the declare cursor statement.
01KNN	8851	CLI Parameter bound check error.
01KNO	8852	Holdable cursors are supported only for streaming cursors and embedded UPDATE/DELETE cursors.
01KNP	8853	Invalid attribute definition.
01KNQ	8854	Invalid attribute value.
01KNR	8855	Statement attribute cannot be set now.
01KNS	8856	Invalid attribute value. INPUT_ARRAY_MAXSIZE must be positive.
01KNU	8858	The value:<num> passed in through input a host variable/parameter is an invalid SQL identifier
01KNV	8859	There are pending insert, delete, or update operations.
01KNW	8860	Module file <name> has obsolete module header.
01KNX	8861	Module file <name> has obsolete descriptor location table header.
01KNY	8862	Module file <name> has obsolete descriptor location table entry.
01KNZ	8863	Module file <name> has obsolete descriptor header.
01KO0	8864	Module file <name> has obsolete descriptor entry.
01KO1	8865	Module file <name> has obsolete procedure location table header.
01KO2	8866	Module file <name> has obsolete procedure location table entry.
01KO3	8867	Error while reading from file <name>.
01KO4	8868	Unable to create context when current transaction is implicitly started by SQL.
01KO5	8869	The specified file number is not a QFO, or the file number is not internally associated with a QFO object (CLI internal error).
01KO6	8870	The current statement is not associated with any QFO.
01KO7	8871	Nowait tag is not specified in the <statement-id>.
01KO8	8872	Unable to execute a new operation while there is another nowaited operation pending.
01KO9	8873	The current statement is already associated with a QFO.
01KOG	8880	Cannot remove the current context.
01KOH	8881	The specified CLI context handle is not found
01KOI	8882	Containing SQL not permitted.
01KOJ	8883	The current context has violation checking functions disabled. Use SQL_EXEC_SetUdrAttributes_Internal() to enable it.
01KOK	8884	Prohibited SQL statement attempted.
01KOQ	8890	The SQL compiler failed to initialize properly. Query results might differ from what is expected, due to different compiler defaults.

SQLSTATE	SQLCODE	Error Text
01K0R	8891	Non-ASCII character host variable type for <name> field.
01K0T	8893	The statement argument count does not match the descriptor entry count.
01K0U	8894	Argument <argument-name> of CLI function <function-name> is reserved for future use and must be set to <string> when calling the function.
01K0X	8897	RPC exception in CLI request from non-trusted shadow client to trusted shadow server.
01K0Y	8898	Internal error in CLI.
01KP1	8901	The MXUDR server for this statement is no longer running. The statement will be assigned a new MXUDR server if it is executed again.
01KP2	8902	Internal error: MXUDR returned an invalid UDR handle.
01KP3	8903	An attempt was made by the Trafodion to kill the MXUDR server for this statement <process-name>. PROCESS_STOP_ returned <value>.
01KP4	8904	Unable to receive reply from MXUDR, possibly caused by internal errors while executing user-defined routines.
01KP6	8906	An invalid or corrupt MXUDR reply could not be processed, possibly due to memory corruption in MXUDR while executing friendly user-defined routines or an internal error in Trafodion.
01L5K	9200	UPDATE STATISTICS encountered an error from statement <name>.
01L5L	9201	Unable to DROP object <name>.
01L5M	9202	UPDATE STATISTICS has located previously generate histogram that are not being regenerated. This might affect the plans that will be generated. Missing column lists are <column-list>.
01L5N	9203	Column names must be unique when specified in column list: (<name>).
01L5O	9204	Invalid option <option> specified. Value must be <range>.
01L5P	9205	UPDATE STATISTICS for object <name> is not supported.
01L5Q	9206	You are not authorized to read/write object <name>. Verify that you have the necessary access privileges.
01L5R	9207	You are not allowed to generate histogram statistics on an ISO88591 CHARACTER SET column which contains a null terminator character. You need to exclude this column from the column group list in UPDATE STATISTICS.
01L5S	9208	Unable to access column definitions.
01L5T	9209	Column name <name> does not exist in the table.
01L5U	9210	One of the column data types is not supported by UPDATE STATISTICS. You need to exclude this column from the column group list in UPDATE STATISTICS.
01L5W	9212	Cardinality statistics will be more accurate if you use SET ROWCOUNT option in the SAMPLE clause.
01L5X	9213	If you intend to update histogram statistics for columns, you must specify a column group list in the statement.
01L5Y	9214	Unable to CREATE object <name>.
01L5Z	9215	UPDATE STATISTICS encountered an internal error (<location>).
01M01	10001	Sort Error: No error text is defined for this error
01M03	10003	Sort Error: Warning: Scratch File EOF
01M04	10004	Sort Error: Merge is disallowed for Sort
01M05	10005	Sort Error: Unexpected error value. Check error
01M06	10006	Sort Error: Previous IO failed
01M07	10007	Sort Error: Error writing to Scratch File
01M08	10008	Sort Error: Invalid sort algorithm selected

SQLSTATE	SQLCODE	Error Text
01M0A	10010	Sort Error: Run number is invalid
01M0B	10011	Sort Error: Error reading Scratch File
01M0C	10012	Sort Error: Scratch Block number is invalid
01M0D	10013	Sort Error: No fixed disks to sort on
01M0E	10014	Sort Error: No memory to allocate scratch space
01M0F	10015	Sort Error: PROCESSHANDLE_GETMINE_ failed
01M0G	10016	Sort Error: PROCESSHANDLE_DECOMPOSE_ failed
01M0H	10017	Sort Error: DEVICE_GETINFOBYLDEV_ failed
01M0I	10018	Sort Error: FILENAME_FINDSTART_ failed
01M0J	10019	Sort Error: FILENAME_FINDNEXT_ failed
01M0K	10020	Sort Error: FILENAME_FINDFINISH_ failed
01M0L	10021	Sort Error: FILE_GETINFOLISTBYNAME_ failed
01M0M	10022	Sort Error: FILE_CREATE failed
01M0N	10023	Sort Error: FILE_OPEN_ failed
01M0O	10024	Sort Error: SetMode failed
01M0O	10024	Sort Error: SetMode failed
01M0Q	10026	Sort Error: AWAITIOX failed
01M0R	10027	Sort Error: FILE_GETINFOLIST failed
01M0S	10028	Sort Error: POSITION failed
01M0T	10029	Sort Error: FILE_GETINFO_ failed
01M18	10044	Sort Error: IO did not complete
01M1B	10047	Sort Error: Wrong length read
01N2T	11101	MXUDR: Unknown message type: <value>.
01N2V	11103	MXUDR: Invalid routine handle: <string>.
01N2W	11104	MXUDR: CLI Error: <error-text>.
01N2X	11105	MXUDR: Invalid Language Manager param mode. Parameter <parameter-value>.
01N30	11108	MXUDR: Unable to allocate memory for object <object-name>.
01N32	11110	MXUDR: Unexpected error during message processing: <string>.
01N33	11111	MXUDR: Internal error: <value>.
01N35	11113	MXUDR: Internal error: An unexpected UNLOAD request arrived for UDR handle <string>.
01N5L	11201	Language Manager initialization failed. Details: Error occurred while loading Java System Class <class-name>.
01N5M	11202	Language Manager initialization failed. Details: Unable to initialize JVM.
01N5N	11203	The Language Manager failed to create its class loader, possibly due to corrupt LmClassLoader.class file.
01N5P	11205	Java class <class-file-name> was not found in external path <path-name>.
01N5Q	11206	Java class <class-file-name> failed to initialize.
01N5R	11207	Java method <method-name> was not found in Java class <class-file-name>.
01N5S	11208	Specified signature is invalid. Reason: The list of parameter types must be enclosed in parentheses.
01N5T	11209	Specified signature is invalid. Reason: the number of parameters <value> must match the number of parameters in Java method.
01N5U	11210	Specified signature is invalid. Reason: Missing [ ] for OUT/INOUT parameter at position <value>.

SQLSTATE	SQLCODE	Error Text
01N5V	11211	Specified signature is invalid. Reason: Unknown parameter type used at position <value>.
01N5W	11212	Specified signature is invalid. Reason: Java signature size is more than supported.
01N5X	11213	Specified signature is invalid. Reason: A return type must not be specified.
01N5Z	11215	Java execution: Invalid null input value at parameter position <value>.
01N60	11216	Java execution: Data overflow occurred while retrieving data at parameter position <parameter-number>.
01N61	11217	Java execution: Data overflow occurred while retrieving data at parameter position <parameter-number>. Value is truncated.
01N62	11218	A Java method completed with an uncaught Java exception. Details: <string>.
01N63	11219	A Java method completed with an uncaught java.sql.SQLException. Details: <string>.
01N64	11220	A Java method completed with an uncaught java.sql.SQLException with invalid SQLSTATE. The uncaught exception had an SQLCODE of <SQLCODE-value> and SQLSTATE of <SQLSTATE-value>. Details: <string>.
01N65	11221	Language Manager is out of memory <string>.
01N66	11222	The operation failed because the Java Virtual Machine ran out of memory.
01N67	11223	Language Manager encountered internal error <detail-text>.
01N68	11224	JVM raised an exception. Details: <detail-text>.
01N69	11225	Specified signature is invalid. Reason: The Java signature for a Java main method must be (java.lang.<string>[ ]).
01N6A	11226	All SQL parameters associated with a Java main method must have a parameter mode of IN.
01N6B	11227	All SQL parameters associated with a Java main method must be an SQL character type.
01N6C	11228	Floating point conversion error <string>.
01P01	13001	Internal Error. Unable to translate SQL statement.
01P02	13002	Syntax error near line <num>.
01P03	13003	This feature is unsupported.
01P04	13004	No error.
01P05	13005	General programming error in file <name> at line <num>.
01P06	13006	Switch has bad value, <num>, for its expression at line <num> in file <name>.
01P07	13007	Missing output file argument after the -c option.
01P08	13008	Missing module definition file argument after the -m option.
01P09	13009	Missing listing file argument after the -l option.
01P0A	13010	Missing timestamp argument after the -t option.
01P0B	13011	<name> is an unknown command line option.
01P0C	13012	<name> is an invalid or undefined command line argument.
01P0D	13013	Help for SQLC and SQLCO is available by typing SQLC or SQLCO on the command line.
01P0E	13014	Unable to open the output source file <name>.
01P0F	13015	Unable to open the module definition file <name>.
01P0G	13016	Descriptor name <name> conflicts with SQLC default name <name>.
01P0H	13017	Descriptor <name> is multiply defined.
01P0I	13018	Descriptor name <name> is invalid.
01P0J	13019	Statement name <name> uses <name>, a reserved name SQLC generates.
01P0K	13020	Statement name <name> is multiply defined.
01P0L	13021	<name> is already defined.

SQLSTATE	SQLCODE	Error Text
01P0M	13022	Cursor <name> is already defined.
01P0N	13023	<name> is already defined as a dynamic cursor.
01P0O	13024	Cursor <name> was not declared.
01P0P	13025	Warning(s) near line <num>.
01P0Q	13026	The EXEC SQL MODULE statement must precede any cursor definitions or executable SQL statements.
01P0R	13027	Only one EXEC SQL MODULE statement is allowed.
01P0S	13028	Cannot open static cursor <name> because <name> is out of scope at time of open.
01P0T	13029	<line-number-detail-text>
01P0U	13030	<line-number-detail-text>
01P0V	13031	Expecting a single host variable of type string.
01P0W	13032	Not expecting input host variables for static cursor <name>.
01P0X	13033	Host variable <name> is in different scope than when cursor <name> was declared.
01P0Y	13034	Character set <name> is not yet supported.
01P0Z	13035	Invalid line number <num> for line pragma; ignoring the rest.
01P10	13036	C/C++ syntax error in switch/for/while condition near line <num>.
01P11	13037	Function header syntax error near line <num>.
01P12	13038	Array size <num> expected to be an unsigned integer near line <num>.
01P13	13039	Function definition is not allowed within an SQL declare section near line <num>.
01P14	13040	Expecting ")" near line <num>.
01P15	13041	Typedef encountered near line <num>, and typedefs are not supported.
01P16	13042	Unnamed declaration near line <num>.
01P17	13043	Expecting <name> near line <num>.
01P18	13044	Type specification <type> is not a recognized type near line <num>.
01P19	13045	Unexpected class declaration near line <num> ignored.
01P1A	13046	Expecting "}" to end member declaration near line <num>.
01P1B	13047	Undefined tag <name> near line <num>.
01P1C	13048	Tag <name> redefined near line <num>.
01P1D	13049	Input file not good near line <num>.
01P1E	13050	Cursor <name> not closed.
01P1F	13051	Cursor <name> not opened.
01P1G	13052	Cursor <name> not fetched.
01P1H	13053	Cursor <name> not opened or closed.
01P1I	13054	Cursor <name> not fetched or closed.
01P1J	13055	Cursor <name> not opened or fetched.
01P1K	13056	Cursor <name> not used.
01P1L	13057	End-of-file processing generated unexpected cursor status of <num> for cursor <name>.
01P1M	13058	Unable to open SQL CLI header file <name>.
01P1O	13060	Unable to open the listing file <name>.
01P1P	13061	Invalid NUMERIC precision specified near line <num>.
01P1Q	13062	Unsigned long long type not allowed near line <num>.
01P1R	13063	Identifier <name> not defined near line <num>.
01P1S	13064	Identifier <name> is not a member of struct <name> near line <num>.

SQLSTATE	SQLCODE	Error Text
01P1T	13065	End of file was found after <name> when <name> was expected, near line <num>.
01P1U	13066	Identifier <name> was expected to be a structure type near line <num>.
01P1V	13067	Unable to open source file <name>.
01P1W	13068	C/C++ syntax error near line <num>.
01P1X	13069	Missing module specification string argument after -g option.
01P1Y	13070	Module Group Specification String <MVSS-string> is not a Regular Identifier, or is longer than 31 characters.
01P1Z	13071	Module Tableset Specification String <MTSS-string> is not a Regular Identifier, or is longer than 31 characters.
01P20	13072	Module Version Specification String <MVSS-string> is not a Regular Identifier, or is longer than 31 characters.
01P21	13073	Module name <module-name> is not a valid OSS file name, or is longer than 128 characters.
01P22	13074	One or more of the first three parts of the externally qualified module name <module-name> is longer than 128 characters.
01P23	13075	Externally qualified module name <module-name> is not a Regular Identifier, or is longer than 248 characters.
01P24	13076	Catalog name <catalog-name> is not a valid OSS file name, or is longer than 128 characters.
01P25	13077	Schema name <schema-name> is not a valid OSS file name, or is longer than 128 characters.
01PDW	13500	SQLCO errors
01PDX	13501	Invalid command option <name>.
01PDY	13502	Source file name must be specified.
01PDZ	13503	Missing filename for command option <name>.
01PE0	13504	Missing timestamp command option.
01PE1	13505	Source input file <name> cannot be opened.
01PE2	13506	COBOL output source file <name> cannot be opened.
01PE3	13507	Error while parsing source: <text>.
01PE4	13508	Expecting <name>, found <name>.
01PE5	13509	Expecting <name> after <name>, found <name>.
01PE6	13510	The SQL declare section might not contain COPY or REPLACE.
01PE7	13511	End of input file while processing EXEC SQL.
01PE8	13512	Input file error while processing EXEC SQL.
01PE9	13513	The BIT data type is not implemented in the Trafodion software.
01PEA	13514	The CHARACTER SET attribute is not implemented in Trafodion.
01PEB	13515	Picture <name> is not valid for a host variable.
01PEC	13516	Unexpected end of input file encountered after line <num>.
01PED	13517	Line <num> is too long to process and has been truncated.
01PEE	13518	Line <num> cannot be interpreted as a COBOL line type.
01PEF	13519	Line <num> contains an unterminated character literal.
01PEG	13520	Line <num> does not correctly continue a character literal.
01PEH	13521	Line <num>: DISPLAY host variables must be SIGN LEADING SEPARATE.
01PEI	13522	DECLARE SECTION cannot be nested.

SQLSTATE	SQLCODE	Error Text
01PEJ	13523	END DECLARE SECTION without a matching BEGIN DECLARE SECTION.
01PEK	13524	DECLARE SECTION encountered in unexpected program section.
01PEL	13525	Variable <name> might not be allocated correctly for a host variable.
01PEM	13526	Line <num>, <name>: <name> clause is not valid for a host variable.
01PEN	13527	The first declaration in an SQL DECLARE SECTION must have level 01 or 77.
01PEO	13528	Line <num>: Variable <num> is not alphabetic and cannot have a CHARACTER SET clause.
01PEP	13529	Missing END DECLARE SECTION detected at line <num>.
01PM8	13800	Line <num>: <name> is not a valid character set name.
01R00	15000	SQLCI error messages.
01R01	15001	Syntax error at or before: <string>.
01R02	15002	Internal parser error: <name.name>
01R03	15003	Incomplete statement in input: <name>
01R04	15004	Error <num> on change directory attempt to <action>.
01R05	15005	Unmatched quote in input (unterminated string): <name>
01R06	15006	Error <num> while reading from file.
01R07	15007	Error <num> while opening file <name>.
01R08	15008	The specified statement does not exist in the history buffer.
01R09	15009	The requested help topic is too long.
01R0A	15010	The help file could not be opened.
01R0B	15011	No help is available for the requested topic.
01R0C	15012	File read error on the help file.
01R0D	15013	This command is not supported by the SQLCI OLE server.
01R0E	15014	Section <name> not found in file <name>.
01R0F	15015	PARAM <name> (value <num>) cannot be converted to type <type>.
01R0G	15016	PARAM <name> not found.
01R0H	15017	Statement <name> not found.
01R0I	15018	Break was received. The last statement might be lost.
01R0J	15019	<num> values were supplied in the USING list while the statement contains <num> unnamed parameters.
01R0K	15020	The USING list must contain at least one parameter value.
01R0L	15021	The USING list cannot contain more than <num> parameter values.
01R0N	15023	The USING list value <name> exceeds the SQLCI limit of <num> characters.
01R0O	15024	The USING list quoted literal <name> must be followed by either a comma or a semicolon.
01R0P	15025	Cursor operations are not supported by SQLCI.
01R0Q	15026	Break rejected.
01R0S	15028	Break error.
01R0U	15030	The specified define already exists. Use alter or delete and add.
01R0V	15031	The specified define does not exist.
01R0W	15032	An error occurred while adding, altering or deleting this define.
01R0X	15033	Break was received.
01R0Y	15034	Invalid LOG file name.
01R0Z	15035	Permission denied to access this file

SQLSTATE	SQLCODE	Error Text
01R10	15036	Invalid Filecode OR Invalid Function Argument
01RRR	15999	SQLCI internal error.
01S00	19000	Internal error in internal stored procedure processing.
01S01	19001	Error in field description of internal stored procedure.
01S02	19002	No such internal stored procedure: <name> defined.
01S03	19003	Internal stored procedure failed without any error information returned.
01S0K	19020	Stored procedure <name> expects <num> input parameters.
01S0L	19021	Stored procedure <name> returns with error: <name>.
01T00	20000	SQL Utilities error messages.
01T31	20109	<text>
01U01	30001	A rowset must be composed of host variable arrays.
01U02	30002	The given rowset size (<num>) must be smaller or equal to the smallest dimension (<num>) of the arrays composing the rowset.
01U03	30003	Rowset size must be an integer host variable or constant.
01U04	30004	The dimension of the arrays composing the rowset must be greater than zero. A value of <num> was given.
01U05	30005	The dimensions of the arrays composing the rowset are different. The smallest dimension is assumed.
01U06	30006	Rowset and one-dimensional variable are in output list.
01U07	30007	Incompatible assignment from type <type> to type <type>
01U08	30008	Internal error. Rowset index is out of range.
01U09	30009	Internal error. Trying to add more elements than maximum rowset size.
01U0A	30010	Internal error. Rowset is corrupted.
01U0B	30011	More than one INTO statement in the same query is not supported.
01U0C	30012	Rowset index <name> must be specified last in the derived column list of <name>.
01U0D	30013	Hostvar used to set input size of rowset has zero or negative value.
01U0E	30014	Hostvar used to set input size of rowset is not of type short, int, or long.
01U0K	30020	Embedded UPDATE/DELETE cannot be used with SELECT . . . INTO and rowset.
01Y00	16000	Error message file not found.
01Y01	16001	No message found for error or warning <sqlcode>.
02000	100	The "no data" completion condition (SQLCODE = +100).
01Z01	25001	Program <executable>, executing on <node>, has encountered a version error.
01Z2S	25100	Remote node <node> runs an incompatible version of Trafodion. The Trafodion version (version) of <node> is <version-1>, the local node does not support versions older than <version-2>.
01Z2T	25101	Remote node <node> runs an incompatible version of Trafodion. The Trafodion version (version) of <node> is <version-1>, the local node supports only version <version-2>.
01Z2U	25102	Remote node <node> runs a version of Trafodion which cannot interoperate with other versions. The Trafodion version (version) of <node> is <version-1>.
01Z8C	25300	Module <module> has module version <version-1>; node <node> does not support module versions lower than <version-2>.
01Z8D	25301	Module <module> has module version <version-1>; the local node does not support module versions higher than <version-2>.
01Z8I	25306	A required system module has module version <version-1>; node <node> does not support query plans from modules with module version lower than <version-2>.

SQLSTATE	SQLCODE	Error Text
01Z8J	25307	The query plan can be executed only by a node with Trafodion version (version) <version-1>, the version of <node> is <version-1>.
01Z8K	25308	The query plan has plan version <version-1>, the local Trafodion version (version) can execute only query plans with plan version <version-1>.
01Z8L	25309	Module <module> can be executed only by a node with Trafodion version (version) version1, the version of <node> is <version-1>.
01Z8M	25310	Module <module> has module version <version-1>, the local Trafodion version (version) can execute only modules with module version <version-1>.
01Z8N	25311	System module <module> has a wrong module version. The expected module version is <version-1>. the actual module version is <version-2>.
02000	100	The "no data" completion condition (SQLCODE=+100).
07001	-15015	PARAM <name> (value <num>) cannot be converted to type <type>.
07001	-15016	PARAM <name> not found.
07001	-15019	<num> values were supplied in the USING list while the statement contains <num> unnamed parameters.
07008	-8807	Trying to allocate more than <num> entries for a descriptor.
07008	-8893	The statement argument count does not match the descriptor entry count.
07009	-8829	Trying to set descriptor item for an entry that is either invalid or greater than the maximum entry count for that descriptor.
07009	-8843	Trying to retrieve an item, <num>, that is out of range.
0A000	-1010	The statement just specified is currently not supported.
0A000	-1048	Currently only supporting restrict drop behavior.
0A000	-1074	SQL system metadata not supported by this catalog manager version.
0A000	-1090	Self-referencing constraints are currently not supported.
0A000	-1091	The constraint, index, or file option is not supported on a vertically partitioned table.
0A000	-1120	Attempting to change the audit flags for a table in an unsupported way.
0A000	-1121	Attempting to perform a partition add, move, or drop on table <name>. Partition operations are not allowed on tables with vertical partitions, entry sequenced operations, and SYSKEYonly partitioned tables.
0A000	-1126	Referential integrity is not yet supported. Constraint <name> will not be enforced.
0A000	-1142	Attempting to add a column with a NULL, UNIQUE, CHECK, PRIMARY KEY, or FOREIGN KEY constraint defined. This is not supported for a nonaudited table.
0A000	-13003	This feature is unsupported.
0A000	-13034	Character set <name> is not yet supported.
0A000	-13041	Typedef encountered near line <num>, and typedefs are not supported.
0A000	-15013	This command is not supported by the SQLCI OLE server.
0A000	-15025	Cursor operations are not supported by SQLCI.
0A000	-2072	A simple value specification that is a literal is not yet supported.
0A000	-3009	DROP ASSERTION statement is not yet supported.
0A000	-3010	Character set <name> is not yet supported.
0A000	-3022	The <name> operator is not yet supported.
0A000	-3023	The COLLATE clause in a sort specification is not yet supported.
0A000	-3024	The MATCH PARTIAL clause is not yet supported.
0A000	-3028	Specifying a privilege column list in the INSERT clause is not yet supported.
0A000	-3029	<name> is not yet supported in referential integrity constraint definition.

SQLSTATE	SQLCODE	Error Text
0A000	-3030	The PARALLEL EXECUTION clause is not yet supported.
0A000	-3031	CASCADE drop behavior is not yet supported.
0A000	-3032	The COLUMN clause in the ALTER TABLE statement is not yet supported.
0A000	-3033	The MOVE clause in the ALTER TABLE statement is not yet supported.
0A000	-3034	The PARTITION clause in the ALTER TABLE statement is not yet supported.
0A000	-3035	The RENAME clause in the ALTER TABLE statement is not yet supported.
0A000	-3036	The SET CONSTRAINT clause in the ALTER TABLE statement is not yet supported.
0A000	-3070	The [NO]AUDIT clause is not supported.
0A000	-3080	The [NO]SERIALWRITES clause is not supported.
0A000	-3105	Currently only range, hash and system partitioning are supported.
0A000	-3119	The WITH LOCAL CHECK OPTION clause is not supported.
0A000	-3120	The CREATE ASSERTION statement is not yet supported.
0A000	-3121	Partitioned entry-sequenced tables are not yet supported.
0A000	-3130	UNSIGNED option is not supported for LARGEINT type.
0A000	-3131	The statement just specified is currently not supported.
0A000	-3137	UNION JOIN is not yet supported.
0A000	-3169	<name> is not a known collation.
0A000	-4026	Reading from and inserting into, or updating in, or deleting from the same table, <name>, is not currently supported.
0A000	-4060	Reading from and inserting into, or updating in, or deleting from the same table, <name>, is not currently supported. <name> is contained by view(s) <name>.
0A000	-4069	Column <name> uses an unsupported collation, <name>.
0A000	-4085	File organization <name> of object <name> is not supported.
0A000	-4089	Check constraint <name> contains a subquery, which is not yet supported.
0A000	-4096	A DEFAULT specification is currently allowed only when simply contained in the VALUES list of an INSERT.
0A000	-4103	Reading from and inserting into the same table <name> is not currently supported. View <name> contains <name>.
0A000	-6001	DISTINCT aggregates can be computed only for one column per table expression.
0A000	-8414	The attempted conversion is not supported on this platform.
0A000	-8418	The USER function is not supported on this platform.
0A000	-8424	Function <name> is not yet supported.
0A000	-8848	Cancel on DDL statements or stored procedures is not supported.
22001	-8402	A string overflow occurred during the evaluation of a character expression.
22002	-8420	Missing indicator parameter for a NULL value.
22003	-8411	A numeric overflow occurred during an arithmetic computation or data conversion.
22007	-3045	Invalid date '<date>'.
22007	-3046	Invalid time '<time>'.
22007	-3047	Invalid timestamp '<timestamp>'.
22007	-3158	Invalid DATETIME <datetime>.
22007	-8413	The string argument contains characters that cannot be converted.
22007	-8415	The provided DATE, TIME, or TIMESTAMP is not valid and cannot be converted.
22007	-8422	The provided INTERVAL is not valid and cannot be converted.

SQLSTATE	SQLCODE	Error Text
22008	-8405	The operand of function CONVERTTIMESTAMP is out of range.
22008	-8407	The operand of function JULIANTIMESTAMP is out of range.
22008	-8416	A datetime expression evaluated to an invalid datetime value.
22008	-8403	The length argument of function SUBSTRING cannot be less than zero or greater than source string length.
22008	-4075	Division by zero in constant expression <name>.
22012	-8419	An arithmetic expression attempted a division by zero.
22015	-3044	Invalid interval <num>.
22019	-8409	The escape character argument of a LIKE predicate must be one character in length.
22019	-8412	An input character host variable is missing its null terminator.
22019	-8410	An escape character in a LIKE pattern must be followed by another escape character, an underscore, or a percent character.
22027	-8404	The trim character argument of function TRIM must be one character in length.
23000	-8101	The operation is prevented by check constraint <name> on table <name>.
23000	-8102	The operation is prevented by a unique constraint.
23000	-8103	The operation is prevented by referential integrity constraint <name> on table <name>.
23000	-8421	NULL cannot be assigned to a NOT NULL column.
24000	-8004	Trying to open a statement or cursor that is not in the closed state.
24000	-8005	Trying to fetch from a cursor that is not in the open state.
24000	-8013	Trying to update or delete from a cursor that is not in the fetched state.
24000	-8811	Trying to close a statement that is either not in the open state or has not reached EOF.
24000	-8812	Trying to execute a statement that is not in the closed state.
24000	-8813	Trying to fetch from a statement that is in the closed state.
24000	-8850	The table specified in this cursor update or DELETE statement is different than the table specified in the declare cursor statement.
25000	-1111	Error starting transaction. <i>table name.schema.name</i>
25000	-1112	Error committing transaction. <i>table name.schema.name</i>
25000	-3114	Transaction access mode READ WRITE is incompatible with isolation level READ UNCOMMITTED.
25000	-3140	The isolation level cannot be READ UNCOMMITTED for an INSERT, UPDATE, DELETE, or DDL statement.
25000	-3141	The transaction access mode cannot be READ ONLY for an INSERT, UPDATE, DELETE, or DDL statement.
25000	-8603	Trying to begin a transaction that has already been started.
25000	-8604	Transaction subsystem <name> returned error <num> while starting a transaction.
25000	-8605	Committing a transaction which has not started.
25000	-8606	Transaction subsystem <name> returned error <num> on a commit transaction.
25000	-8612	Transaction mode cannot be set if the transaction is already running.
25000	-8613	SQL cannot commit or rollback a transaction that was started by application.
25000	-8614	SQL cannot begin a transaction when multiple contexts exist.
25000	-8814	The transaction mode at run time (<num>) differs from that specified at compile time (<num>).
25000	-8819	Begin transaction failed while preparing the statement.
25000	-8820	Transaction commit failed while closing the statement.

SQLSTATE	SQLCODE	Error Text
25000	-8832	Transaction has not been started.
25000	-8833	The input parameter is an invalid SQL transaction command.
25000	-8841	User application committed or aborted a transaction started by SQL. This transaction needs to be committed or aborted by calling SQL COMMIT or ROLLBACK WORK.
25000	-8844	A transaction started by SQL that was committed or aborted by user application from outside of SQL, has now been cleaned up.
26000	-15017	Statement <name> not found.
26000	-2065	Statement <name> was not found in module <name>.
26000	-8802	Trying to allocate a statement that already exists in the current context.
26000	-8804	The input statement provided does not exist in the current context.
26000	-8806	Trying to <action> a statement that is not allocated with AllocStmt() call.
2B000	-1014	Privileges were not revoked. Dependent privilege descriptors still exist.
33000	-8801	Trying to allocate a descriptor that already exists in the current context.
33000	-8803	The input descriptor provided does not exist in the current context.
33000	-8805	Trying to <action> a descriptor that is not allocated with AllocDesc() call.
34000	-2066	Cursor <name> was not found in module <name>.
38000	-11218	A Java method completed with an uncaught Java exception. Details: <string>.
39001	-11220	A Java method completed with an uncaught java.sql.SQLException with invalid SQLSTATE. The uncaught exception had an SQLCODE of <SQLCODE-value> and SQLSTATE of <SQLSTATE-value>. Details: <string>.
3D000	-8008	Catalog name <name> is invalid.
3F000	-8009	Schema name <name> is invalid.
40000	-1113	Error rolling back transaction. <table name.schema.name>
40000	-2007	Internal error: need to rollback transaction.
40000	-2009	The user transaction must be rolled back (or committed, if that makes sense in the application) before MXCMP can be restarted and proceed.
40000	-8015	Aborting transaction because a compound statement performed an update operation followed by a SELECT statement that did not return any row.
40000	-8607	Rolling back a transaction that has not started.
40000	-8609	Waited rollback performed without starting a transaction.
40000	-8821	Rollback transaction failed during the process of fetching the statement.
40000	-8839	Transaction was aborted.
40003	-8608	Transaction subsystem <name> returned error <num> on rollback transaction.
40003	-8610	Transaction subsystem <name> reported error <num> on a waited rollback transaction.
42000	-1000	A syntax error occurred.
42000	-3201	EXTERNAL PATH clause is required.
42000	-3202	PARAMETER STYLE clause is required.
42000	-3203	LANGUAGE clause is required.
42000	-3204	EXTERNAL NAME clause is badly formed.
42000	-3205	EXTERNAL NAME clause is required.
42000	-3206	The name for an object of this type must be fully qualified, or set NAMETYPE ANSI.
42000	-3207	Value for DYNAMIC RESULT SETS must be zero.
42000	-3208	UNSIGNED numeric is not allowed for routine parameter.

SQLSTATE	SQLCODE	Error Text
42000	-1123	Unable to process the partition key values (<num>) for object <name>. Please verify that the correct key value data types were specified.
42000	-1136	For an added column, the PRIMARY KEY clause cannot be NOT DROPPABLE.
42000	-1186	Column <name> is of type <type>, incompatible with the default value's type, <type>.
42000	-13002	Syntax error near line <num>.
42000	-13025	Warning(s) near line <num>.
42000	-13036	C/C++ syntax error in switch/for/while condition near line <num>.
42000	-13037	Function header syntax error near line <num>.
42000	-13068	C/C++ syntax error near line <num>.
42000	-15001	Syntax error at or before: <string>.
42000	-15002	Internal parser error: <name.name>
42000	-15003	Incomplete statement in input: <name>
42000	-15005	Unmatched quote in input (unterminated string): <name>
42000	-15020	The USING list must contain at least one parameter value.
42000	-15021	The USING list cannot contain more than <num> parameter values.
42000	-15022	A USING list unquoted literal is the empty string.
42000	-15023	The USING list value <num> exceeds the SQLCI limit of <num> characters.
42000	-15024	The USING list quoted literal <name> must be followed by either a comma or a semicolon.
42000	-2050	<name> is not the name of any DEFAULTS table attribute.
42000	-2051	Invalid <name> option <name> or value '<num>'.
42000	-2055	Invalid value '<num>' for DEFAULTS attribute <name>.
42000	-2056	The value must be a number in the range <num>.
42000	-2057	The value must be a multiple of <num>.
42000	-2058	DEFAULTS attribute <name> is of type <type> but is being converted to <type>.
42000	-2060	Procedure <name> has already been defined in this module. The previous definition is being retained and this latest one ignored.
42000	-2061	Static cursor <name> has already been defined in this module. The previous definition, as a static cursor, is being retained and this latest one ignored.
42000	-2062	Static cursor <name> has already been defined in this module. The previous definition, as a dynamic cursor, is being retained and this latest one ignored.
42000	-2063	Dynamic cursor <name> has already been defined in this module. The previous definition, as a static cursor, is being retained and this latest one ignored.
42000	-2064	Dynamic cursor <name> has already been defined in this module. The previous definition, as a dynamic cursor, is being retained and this latest one ignored.
42000	-2067	Descriptor <name> has already been defined in this module. The previous definition is being retained and this latest one ignored.
42000	-2068	A procedure body must be a SELECT, INSERT, UPDATE, DELETE, DECLARE CATALOG, DECLARE SCHEMA, or a static DECLARE CURSOR.
42000	-2069	A static cursor declaration might appear only in the body of a procedure.
42000	-2070	Invalid statement type in this context.
42000	-2071	The name <name> has already been declared or defined in this module. The previous definition, as a <type>, is being retained and this latest one ignored.
42000	-2091	The required module statement was not found in file <name>.
42000	-2092	A module statement has already appeared in this file. The previous definition, <name>, is being retained and this latest one ignored.

SQLSTATE	SQLCODE	Error Text
42000	-2093	A module timestamp statement was not found in file <name>.
42000	-2094	A module timestamp statement has already appeared in this module. The previous timestamp is being retained and this latest one ignored.
42000	-2093	A module timestamp statement was not found in file <name>.
42000	-2094	A module timestamp statement has already appeared in this module. The previous timestamp is being retained and this latest one ignored.
42000	-2200	DEFAULTS attribute <name> is read-only.
42000	-30001	A rowset must be composed of host variable arrays.
42000	-30002	The given rowset size (<num>) must be smaller or equal to the smallest dimension (<num>) of the arrays composing the rowset.
42000	-30003	Rowset size must be an integer host variable or constant.
42000	-30004	The dimension of the arrays composing the rowset must be greater than zero. A value of <num> was given.
42000	-30005	The dimensions of the arrays composing the rowset are different. The smallest dimension is assumed.
42000	-30006	Rowset and one-dimensional variable are in output list.
42000	-30007	Incompatible assignment from type <type> to type <type>
42000	-3001	Syntax error at or before <SQL-text>.
42000	-3002	<name> is not a valid column reference; it has more than 4 name parts.
42000	-3003	Length or precision must be greater than zero.
42000	-3004	A delimited identifier must contain at least one non-blank character.
42000	-3005	A DECLARE CURSOR statement cannot dynamically get its cursor name from a host variable while also statically declaring a cursor specification. A dynamic cursor requires the name of a previously prepared statement, or a host variable containing such a name; a static cursor requires a fixed, static name.
42000	-3006	In a dynamic cursor declaration both the cursor and the statement must be named in the same way: both must be literals or both must be string host variable expressions.
42000	-3007	In an ALLOCATE CURSOR statement both the cursor and the statement must be named using string host variables.
42000	-3008	Precision of <name> UNSIGNED data type, <value>, cannot exceed 9.
42000	-3011	<name> is not a valid qualified name; it has more than 3 name parts.
42000	-3012	COUNT is the only aggregate function that accepts (*) as an operand.
42000	-3013	Subtraction is the only operation allowed in the parenthesized expression preceding an interval qualifier.
42000	-3014	Precision of numeric, <value>, cannot exceed 18.
42000	-3015	Scale <value> cannot exceed precision <value>.
42000	-3016	Precision of decimal, <value>, cannot exceed 18.
42000	-3017	Expected an unsigned integer, not <value>.
42000	-3018	Expected an unsigned smallint, not <value>.
42000	-3019	Expected an unsigned number within the parentheses, not <value>.
42000	-3020	Expected an unsigned number as the first operand within the parentheses, not <value>.
42000	-3021	Expected an unsigned number as the second operand within the parentheses, not <value>.
42000	-3025	The format of the subvolume name part in the specified location name <name> is invalid. The subvolume name part must be eight characters long and begin with the letters ZSD.
42000	-3026	A comma must be used to separate file attributes.

SQLSTATE	SQLCODE	Error Text
42000	-3027	<name> is not a valid simple name; it has more than one name part.
42000	-3037	Precision of type <data-type> cannot exceed 18.
42000	-3038	PIC X types cannot have leading signs, or any signs at all.
42000	-3039	PIC X types do not have any COMP representation.
42000	-3040	Precision zero is invalid. Add a '9' to the PICTURE clause.
42000	-3041	UNSIGNED is invalid for a numeric or decimal type with a scale greater than 9.
42000	-3042	UPSHIFT for a numeric type is invalid.
42000	-3043	Precision greater than 18 for a COMP numeric type is invalid.
42000	-3048	Dynamic parameters, such as <name>, are not allowed in a static compilation.
42000	-3049	Host variables, such as <name>, are not allowed in a dynamic compilation.
42000	-3050	The constraint must have the same catalog and schema as the specified table.
42000	-3051	Duplicate HEADING clauses in column definition <name>.
42000	-3052	Duplicate NOT NULL clauses in column definition <name>.
42000	-3053	Duplicate PRIMARY KEY clauses in column definition <name>.
42000	-3054	The NOT DROPPABLE clause is allowed only in PRIMARY KEY and NOT NULL constraint definitions.
42000	-3055	Duplicate DELETE rules specified.
42000	-3056	Duplicate UPDATE rules specified.
42000	-3057	Invalid size value in the ALLOCATE clause.
42000	-3058	The BLOCKSIZE value must be 4096.
42000	-3059	Invalid size value in the MAXSIZE clause.
42000	-3060	Invalid percentage value in the DSLACK clause.
42000	-3061	The format of the specified location name <name> is invalid.
42000	-3062	Duplicate MAXSIZE clauses in the PARTITION clause.
42000	-3063	Duplicate DSLACK clauses in the PARTITION clause.
42000	-3064	Duplicate ISLACK clauses in the PARTITION clause.
42000	-3065	The primary key constraint cannot be droppable when the STORE BY PRIMARY KEY clause appears in a table definition.
42000	-3067	ALTER TABLE ADD CONSTRAINT allows only DROPPABLE constraints.
42000	-3068	The ALLOCATE and DEALLOCATE clauses cannot coexist in the same ALTER INDEX statement.
42000	-3071	Duplicate [NO]AUDITCOMPRESS clauses.
42000	-3072	The BLOCKSIZE clause is not allowed in the ALTER INDEX . . . ATTRIBUTE(S) statement.
42000	-3073	Duplicate [NO]BUFFERED clauses.
42000	-3074	Duplicate [NO]CLEARONPURGE clauses.
42000	-3075	The [NO]COMPRESS clause is not allowed in the ALTER INDEX . . . ATTRIBUTE(S) statement.
42000	-3076	Duplicate DEALLOCATE clauses.
42000	-3077	The [NO]ICOMPRESS clause is not allowed in the ALTER INDEX . . . ATTRIBUTE(S) statement.
42000	-3078	The LOCKLENGTH clause is not allowed in the ALTER INDEX . . . ATTRIBUTE(S) statement.
42000	-3079	Duplicate MAXSIZE clauses.
42000	-3081	Duplicate ALLOCATE clauses.

SQLSTATE	SQLCODE	Error Text
42000	-3082	Duplicate [NO]AUDIT clauses.
42000	-3083	Duplicate [NO]AUDITCOMPRESS clauses.
42000	-3084	The BLOCKSIZE clause is not allowed in the ALTER TABLE . . . ATTRIBUTE(S) statement.
42000	-3085	Duplicate [NO]BUFFERED clauses.
42000	-3086	Duplicate [NO]CLEARONPURGE clauses.
42000	-3087	The [NO]COMPRESS clause is not allowed in the ALTER TABLE . . . ATTRIBUTE(S) statement.
42000	-3088	The ALLOCATE AND DEALLOCATE cannot coexist in the same ALTER TABLE statement.
42000	-3089	The [NO]ICOMPRESS clause is not allowed in the ALTER TABLE . . . ATTRIBUTE(S) statement.
42000	-3090	Duplicate LOCKLENGTH clauses.
42000	-3091	The [NO]AUDIT clause is not allowed in the CREATE INDEX statements.
42000	-3092	Duplicate BLOCKSIZE clauses.
42000	-3093	Duplicate DCOMPRESS clauses.
42000	-3094	The DEALLOCATE clause is not allowed in the CREATE INDEX statements.
42000	-3095	Duplicate [NO]ICOMPRESS clauses.
42000	-3096	Duplicate [NO]SERIALWRITES clauses.
42000	-3097	The DEALLOCATE clause is not allowed in the CREATE TABLE statements.
42000	-3098	Duplicate LOCATION clauses.
42000	-3099	Duplicate FILE ATTRIBUTE(S) clauses.
42000	-3100	Duplicate DSLACK clauses.
42000	-3101	Duplicate ISLACK clauses.
42000	-3102	Duplicate PARALLEL EXECUTION clauses.
42000	-3103	Duplicate PARTITION clauses.
42000	-3104	Only the ADD option is allowed in a PARTITION clause in a CREATE TABLE statement.
42000	-3106	Duplicate PRIMARY KEY clauses.
42000	-3107	Duplicate LIKE clauses.
42000	-3108	The LIKE clause and STORE BY clause cannot coexist in the same statement.
42000	-3109	Duplicate STORE BY clauses.
42000	-3110	The LIKE clause and ATTRIBUTE(S) clause cannot coexist in the same statement.
42000	-3111	The LIKE clause and LOCATION clause cannot coexist in the same statement.
42000	-3112	The LIKE clause and PARTITION clause cannot coexist in the same statement.
42000	-3113	Error in CONTROL statement: <name>
42000	-3115	Duplicate ISOLATION LEVEL clause specified.
42000	-3116	Duplicate transaction access mode clause specified.
42000	-3117	Duplicate DIAGNOSTICS SIZE specified.
42000	-3118	Identifier too long.
42000	-3122	The format of the system name part in the specified location name <name> is invalid.
42000	-3123	The format of the file name part in the specified location name <name> is invalid. The file name part must be eight characters long and end with the digits 00.
42000	-3127	Invalid character in identifier <name>.
42000	-3128	<name> is a reserved word. It must be delimited by double- quotes to be used as an identifier.

SQLSTATE	SQLCODE	Error Text
42000	-3129	Function <name> accepts exactly one operand.
42000	-3132	The HEADING for column <name> exceeds the maximum size of 128 characters.
42000	-3133	PERFORM is valid only in COBOL programs.
42000	-3134	Precision of time or timeStamp, <num>, cannot exceed 6.
42000	-3135	Precision of float, <value>, cannot exceed 54.
42000	-3136	Only LEFT, RIGHT, and FULL OUTER JOIN are valid in \{oj . . .}
42000	-3138	A key-sequenced table with range partitioning requires a FIRST KEY clause.
42000	-3139	A range-partitioned index requires a FIRST KEY clause.
42000	-3142	INTO clause host variables are not allowed in a static cursor.
42000	-3143	BROWSE or READ UNCOMMITTED access is not allowed on a table value constructor.
42000	-3145	Positioned UPDATE or DELETE is allowed only in embedded SQL.
42000	-3147	In an IN predicate whose right operand is a value list, the left operand must be scalar (degree of one).
42000	-3149	Duplicate WITH CONSTRAINTS phrases in LIKE clause in CREATE TABLE statement.
42000	-3150	Duplicate WITH HEADING phrases in LIKE clause in CREATE TABLE statement.
42000	-3151	Duplicate WITH HORIZONTAL PARTITIONS phrases in LIKE clause in CREATE TABLE statement.
42000	-3153	The FIRST KEY clause is not allowed with hash partitioning.
42000	-3155	The POPULATE and NO POPULATE clauses cannot coexist in the same CREATE INDEX statement.
42000	-3157	Catalog name is required.
42000	-3159	If you intended <name> to be a character set specifier for a character string literal, you must remove the spaces in front of the single quote delimiter.
42000	-3160	<name> was declared more than once in the procedure parameter list.
42000	-3161	<name> was not declared in the procedure parameter list.
42000	-3164	Data type mismatch between output host variable and selected value.
42000	-3165	Min or max precision or exponent value exceeded, <num>.
42000	-3166	Min or max value for float or double value exceeded, <num>. 42000 -3167 Duplicate [ NOT ] DROPPABLE clauses.
42000	-3168	The FOR . . . ACCESS clause is not allowed in a CREATE VIEW statement.
42000	-3171	Transaction statements are not allowed in compound statements.
42000	-3172	EXIT is not allowed in a compound statement.
42000	-3173	UPDATE STATISTICS is not allowed in a compound statement.
42000	-3174	DDL statements are not allowed in compound statements.
42000	-3175	Dynamic SQL statements are not allowed in compound statements.
42000	-3176	Subqueries are not allowed in the IF Condition.
42000	-3177	Character set <name> requires an even number of characters in the length declaration of the data type.
42000	-3178	One or more of the following external (host-language) data types incorrectly appears within the SQL query or operation: <type>.
42000	-3179	Collation <name> is not defined on the character set <name>.
42000	-3180	STREAM statements are not allowed in compound statements.
42000	-3181	Invalid logical name, a three part logical name is required.
42000	-3187	Not supported: SET STREAM TIMEOUT per a specific stream.

SQLSTATE	SQLCODE	Error Text
42000	-3189	cannot set lock timeout on a view.
42000	-4001	Column <name> is not found. Tables in scope: <name>. Default schema: <name>.
42000	-4002	Column <name> is not found. Table <name> not exposed. Tables in scope: <name>. Default schema: <name>.
42000	-4003	Column name is not a column in table <name>, or, after a NATURAL JOIN or JOIN USING, is no longer allowed to be specified with a table correlation name.
42000	-4004	Column name <name> is ambiguous. Tables in scope: <name>. Default schema: <name>.
42000	-4005	Column reference <name> must be a grouping column or be specified within an aggregate.
42000	-4006	Within an aggregate, all column references must come from the same scope.
42000	-4007	The select list index <num> is out of range. It must be between 1 and the number of select expressions, which in this case is <num>.
42000	-4008	A subquery is not allowed inside an aggregate function.
42000	-4009	An aggregate is not allowed inside an aggregate function.
42000	-4010	There are no columns with the correlation name <name>.
42000	-4011	Ambiguous star column reference <name>.
42000	-4012	Column reference <name> must be a grouping column or be specified within an aggregate. On this grouped table a star reference is not allowed.
42000	-4013	Column <name> is a system column and cannot be updated or inserted into.
42000	-4014	The operands of an INTERSECT must be of equal degree.
42000	-4010	There are no columns with the correlation name <name>.
42000	-4011	Ambiguous star column reference <name>.
42000	-4012	Column reference <name> must be a grouping column or be specified within an aggregate. On this grouped table a star reference is not allowed.
42000	-4013	Column <name> is a system column and cannot be updated or inserted into.
42000	-4014	The operands of an INTERSECT must be of equal degree.
42000	-4015	Aggregate functions placed incorrectly: <name>.
42000	-4016	The number of derived columns (<num>) must equal the degree of the derived table (<num>).
42000	-4017	Derived column name <name> was specified more than once.
42000	-4018	Rows cannot be deleted from an entry-sequenced table.
42000	-4019	The select list of a subquery in a select list must be scalar (degree of one).
42000	-4020	Arithmetic operations on row value constructors are not allowed.
42000	-4021	The select list contains a nongrouping non-aggregated column, <name>.
42000	-4022	Target column <name> was specified more than once.
42000	-4023	The degree of each row value constructor (<num>) must equal the degree of the target table column list (<num>).
42000	-4024	Column <name> has no default value, so must be explicitly specified in the insert column list.
42000	-4025	Error while preparing constraint <name> on table <name>.
42000	-4027	Table <name> is not insertable.
42000	-4028	Table <name> is not updateable.
42000	-4030	Column <name> is an invalid combination of datetime fields (<num>, <num>, <num>).
42000	-4031	Column <name> is an unknown data type, <num>.

SQLSTATE	SQLCODE	Error Text
42000	-4032	Column <name> is an unknown class, <num>. It is neither a system column nor a user column.
42000	-4033	Column <name> is a primary or clustering key column and cannot be updated.
42000	-4034	The operation (<name> <name> <name>) <name> is not allowed.
42000	-4035	Type <type> cannot be cast to type <type>.
42000	-4036	The source field of the EXTRACT function must be of DateTime or Interval type.
42000	-4037	Field <name> cannot be extracted from a source of type <type>.
42000	-4038	The operand of an AVG or SUM function must be numeric or interval.
42000	-4039	Column <name> is of type <type>, incompatible with the value's type, <type>.
42000	-4040	The operands of a BETWEEN predicate must be of equal degree.
42000	-4041	Type <type> cannot be compared with type <type>.
42000	-4042	The operands of a comparison predicate must be of equal degree.
42000	-4043	The operand of function <name> must be character.
42000	-4044	Collation <name> does not support the <name> predicate or function.
42000	-4045	The operand of function <name> must be numeric.
42000	-4046	The operands of function <name> must be exact numeric.
42000	-4047	The operands of function <name> must have a scale of 0.
42000	-4048	The third operand of a ternary comparison operator must be of type BOOLEAN, not <name>.
42000	-4049	A CASE expression cannot have a result data type of both <type> and <type>.
42000	-4050	The operands of the <name> predicate must be comparable character data types (that is, of the same character set and collation).
42000	-4051	The first operand of function <name> must be character.
42000	-4052	The second operand of function <name> must be numeric.
42000	-4053	The third operand of function <name> must be numeric.
42000	-4055	The select lists or tuples must have comparable data types. <type> and <type> are not comparable.
42000	-4056	Exposed name <name> appears more than once.
42000	-4057	Correlation name <name> conflicts with qualified identifier of table <name>.
42000	-4059	The first operand of function <name> must be numeric.
42000	-4061	Rows cannot be inserted into, or updated in, an individual table partition.
42000	-4062	The preceding error actually occurred in function <name>.
42000	-4063	The operands of function <name> must be comparable character data types (that is, of the same character set and collation).
42000	-4064	The operands of function <name> must be compatible character data types (that is, of the same character set).
42000	-4066	The operands of a UNION must be of equal degree.
42000	-4067	The operands of function <name> must be character data types.
42000	-4068	The operand of function <name> must contain an even number of characters.
42000	-4070	The operand of function <name> must be exact numeric.
42000	-4071	The first operand of function <name> must be a datetime.
42000	-4072	The operand of function <name> must be a datetime containing a <name>.
42000	-4073	The COLLATE clause might appear only after an expression of character data type, not <type>.

SQLSTATE	SQLCODE	Error Text
42000	-4076	Overflow in constant expression <name>.
42000	-4077	Function <name> accepts only one or two operands.
42000	-4078	Function <name> does not accept a weight operand.
42000	-4079	The operands of function <name> must be numeric.
42000	-4082	Table <name> does not exist or is inaccessible.
42000	-4084	SQL object <table-name> is corrupt.
42000	-4086	Environment variable or define <name> does not exist.
42000	-4087	Prototype value '<name>' is not a valid qualified name.
42000	-4088	The number of values in each TRANSPOSE item of a TRANSPOSE set must be equal.
42000	-4093	The number of output dynamic parameters (<num>) must equal the number of selected values (<num>).
42000	-4094	The number of output host variables (<num>) must equal the number of selected values (<num>).
42000	-4095	A DEFAULT whose value is NULL is not allowed in <name>.
42000	-4097	A NULL operand is not allowed in function <name>.
42000	-4098	A NULL operand is not allowed in operation <name>.
42000	-4099	A NULL operand is not allowed in predicate <name>.
42000	-4100	A NULL value is not allowed in a select list unless it is CAST to some data type.
42000	-4101	If <name> is intended to be a further table reference in the FROM clause, the preceding join search condition must be enclosed in parentheses.
42000	-4104	If a character literal was intended, you must use the single quote delimiter instead of the double: <name> instead of <name>.
42000	-4105	Unknown translation.
42000	-4106	The character set for the operand of function <name> must be <name>.
42000	-4107	Column <name> has no default value, so DEFAULT cannot be specified.
42000	-4108	Inside a ROWS SINCE, another sequence function contained an invalid reference to the THIS function.
42000	-4109	Sequence functions placed incorrectly: <name>.
42000	-4110	The query contains sequence functions but no SEQUENCE BY clause: <name>.
42000	-4111	The query contains a SEQUENCE BY clause but no sequence functions.
42000	-4112	Absolute and relative sampling cannot occur in the same BALANCE expression.
42000	-4113	The sample size for <name> Sampling must be <num>.
42000	-4114	An absolute sample size must have a scale of zero.
42000	-4115	The sample size must be less than or equal to the sample period.
42000	-4116	The second operand of function <name> is invalid.
42000	-4117	The cursor query expression might be nonupdatable.
42000	-4118	The cursor query expression is not updateable.
42000	-4120	In a query with a GROUP BY, DISTINCT, or aggregate function, each column in the ORDER BY clause must be one of the columns explicitly SELECTed by the query. Column in error: <name>.
42000	-4121	In a query with a GROUP BY, DISTINCT, or aggregate function, each column in the ORDER BY clause must be one of the columns explicitly SELECTed by the query. Column in error: <name>. Table in scope: <name>.
42000	-4122	NULL cannot be assigned to NOT NULL column <name>.
42000	-4123	NULL cannot be cast to a NOT NULL data type.

SQLSTATE	SQLCODE	Error Text
42000	-4125	The select list of a subquery in a row value constructor, if the subquery is one of several expressions rather than the only expression in the constructor, must be scalar (degree of one).
42000	-4126	The row value constructors in a VALUES clause must be of equal degree.
42000	-4127	Type <type> cannot be assigned to type <type>.
42000	-4128	Cannot retrieve default volume and subvolume information from =_DEFAULTS define, DEFINEINFO error <num>.
42000	-4134	The operation (<name>) is not allowed. Try UNION ALL instead.
42000	-7003	A plan using cluster sampling could not be produced for this query.
42000	-8573	The user does not have <name> privilege on table or view <name>.
44000	-8104	The operation is prevented by the check on view <name> cascaded from the check option on <table-name>.
44000	-8105	The operation is prevented by the check option on view <name>.
46007	-11208	Specified signature is invalid. Reason: The list of parameter types must be enclosed in parentheses.
46007	-11209	Specified signature is invalid. Reason: the number of parameters <value> must match the number of parameters in Java method.
46007	-11210	Specified signature is invalid. Reason: Missing [ ] for OUT/INOUT parameter at position <value>.
46007	-11211	Specified signature is invalid. Reason: Unknown parameter type used at position <value>.
46007	-11212	Specified signature is invalid. Reason: Java signature size is more than supported.
46007	-11213	Specified signature is invalid. Reason: A return type must not be specified.
46101	-11215	Java execution: Invalid null input value at parameter position <value>.
46103	-11205	Java class <class-file-name> was not found in external path <path-name>.
HY011	-8855	Statement attribute cannot be set now.
HY011	-8857	Statement attribute cannot be set now. INPUT_ARRAY_MAXSIZE must be set before compiling the statement.
HY024	-8854	Invalid attribute value.
HY024	-8856	Invalid attribute value. INPUT_ARRAY_MAXSIZE must be positive.
HY092	-8853	Invalid attribute definition.
X0101	-1001	An internal error occurred in module <name> on line <num>. DETAILS(<text>).
X0102	-1002	Catalog <name> does not exist.
X0103	-1003	Schema <name> does not exist.
X0104	-1004	Table, view, or stored procedure <name> does not exist.
X0105	-1005	Constraint <name> does not exist.
X0106	-1006	Index <name> does not exist.
X0108	-1008	User name <name> does not exist.
X0109	-1009	Column <name> does not exist in the specified table.
X010G	-1016	Redundant references to column <name> in the constraint.
X010H	-1017	You are not authorized to perform this operation.
X010J	-1019	Cannot find a valid primary partition for <name>.
X010K	-1020	Privilege settings on metadata tables cannot be changed.
X010L	-1021	SQL is already initialized on system <name>.
X010M	-1022	Schema <name> already exists.

SQLSTATE	SQLCODE	Error Text
X010N	-1023	Only the super ID user can name an authorization ID other than the current user name.
X010O	-1024	Distribution Service/Data Access Manager error <num> occurred in module <name> on line <num>. DETAILS(<text>).
X010P	-1025	Request failed. One or more dependent objects exist.
X010Q	-1026	Only the schema owner or the super ID user can drop a schema.
X010R	-1027	The definition schema <name> is dropped when its catalog is dropped.
X010S	-1028	Schema <name> contains at least one object. The schema must be empty.
X010T	-1029	Unable to create object <name>.
X010U	-1030	Unable to access object <name> (file error <num>).
X010V	-1031	Unable to drop object <name>.
X010Y	-1034	Unable to initialize SQL.
X010Z	-1035	Catalog <name> already exists.
X0110	-1036	Only the super ID can execute DROP SQL.
X0111	-1037	SQL is not installed on system <name>.
X0112	-1038	All catalogs have not been dropped from the system.
X0113	-1039	Unable to drop SQL.
X0114	-1040	Cannot alter metadata table.
X0115	-1041	The primary key has already been defined.
X0116	-1042	All PRIMARY KEY or UNIQUE constraint columns must be NOT NULL.
X0118	-1044	Unable to create constraint <name>. The referenced table does not contain a unique constraint.
X0119	-1045	The unique constraint cannot be used because it is deferrable.
X011A	-1046	Referenced and referencing column lists do not match for constraint <name>.
X011B	-1047	Unable to drop view <name> due to view being used by other objects.
X011D	-1049	Attempting to drop a NOT DROPPABLE constraint.
X011E	-1050	Cannot drop constraint used as a referenced object for a foreign key.
X011F	-1051	Insufficient privilege on <name>.
X011G	-1052	Trying to drop a constraint that does not belong to requested table.
X011H	-1053	Unique index <name> could not be created because the column(s) specified contain duplicate data.
X011I	-1054	Index <name> already exists.
X011J	-1055	Table, view, or stored procedure <name> already exists.
X011L	-1057	The DAM volume specified (<name>) is not available or is not audit protected.
X011M	-1058	Lock <name> already exists.
X011N	-1059	Request failed. Dependent constraint <name> exists.
X011P	-1061	Cannot drop metadata catalog <name>.
X011Q	-1062	Cannot drop metadata schema <name>.
X011R	-1063	Cannot drop metadata index <name>.
X011S	-1064	Cannot drop metadata view <name>.
X011T	-1065	Cannot create constraint <name> in metadata schema.
X011U	-1066	Cannot create index <name> in metadata schema.
X011X	-1069	Unable to drop schema <name>.
X011Y	-1070	Unable to create object <name> (file error <num>).

SQLSTATE	SQLCODE	Error Text
X011Z	-1071	Unable to access object <name> (file error <num>).
X0120	-1072	Unique constraint <name> is disabled; cannot create foreign key constraint <name>.
X0121	-1073	Only the super ID user can execute INITIALIZE SQL.
X0123	-1075	Catalog <name> contains at least one schema. The catalog must be empty.
X0125	-1077	Metadata table <name> does not contain information for view <name>.
X0126	-1078	The format of the specified location name <name> is invalid.
X0127	-1079	Unable to prepare the statement.
X0128	-1080	Duplicate references to column <name> in the create request.
X0129	-1081	Loading of index <name> failed unexpectedly.
X012A	-1082	Validation for constraint <name> failed unexpectedly.
X012B	-1083	Validation for constraint <name> failed; incompatible data exists in table.
X012C	-1084	Invalid default value for column <name>.
X012D	-1085	The calculated key length is greater than 255 bytes.
X012E	-1086	Lock <name> does not exist.
X012F	-1087	Lock cannot be granted, conflicting operation is in progress.
X012G	-1088	Cannot instantiate object <name>, conflicting lock exists.
X012M	-1094	Unable to drop object <name> because it is not a <name>.
X012N	-1095	The partition by column <name> should also be part of the clustering/storage key.
X012Q	-1098	Duplicate partition key (<name>) specified for object <name>.
X012R	-1099	Column <num> is unnamed. You must specify an AS clause for that column expression, or name all the columns by specifying a view column list.
X012S	-1100	Unable to select <name.schema.name>.
X012T	-1101	Unable to update <name.schema.name>.
X012U	-1102	Unable to insert rows into <name.schema.name>.
X012V	-1103	Unable to delete rows from <name.schema.name>.
X012W	-1104	Default value string too long for column <name>.
X012X	-1105 a	CREATE TABLE LIKE statement cannot contain both HORIZONTAL PARTITIONS and STORE BY clauses.
X012Y	-1106	The specified partition <name> of object <name> does not exist.
X0130	-1108	The number of columns specified in the view column list, <num>, does not match the degree of the query expression, <num>.
X0131	-1109	The WITH CHECK OPTION clause appears in the definition of view name, but the view is not updateable.
X0136	-1114	Unable to create catalog <name> metadata tables on <name>.
X0137	-1115	Unable to create label for <name> (file error <num>) <name>.
X0138	-1116	The current partitioning scheme requires a user-specified primary key on object <name>.
X0139	-1117	Cannot drop the only partition of the table. There must be at least two partitions available to perform the drop.
X013A	-1118	Cannot create object <name> in metadata schema.
X013B	-1119	Cannot drop metadata object <name>.
X013E	-1122	The number of specified partition key values (<num>) for object <name> exceeds the number of key columns used, <num>.
X013G	-1124	Schema <name> is an unknown version.
X013H	-1125	API request version number mismatch.

SQLSTATE	SQLCODE	Error Text
X013J	-1127	The specified table <name> is not a base table. Please verify that the correct table was specified.
X013K	-1128	Invalid API request. Details: <text>.
X013M	-1130	The column requires a default value.
X013O	-1132	An added column cannot have both DEFAULT NULL and NOT NULL.
X013P	-1133	Only the super ID can perform this operation.
X013Q	-1134	Concurrent DDL operations are being performed on the given object. The current operation cannot be performed.
X013R	-1135	Clustering key column <name> must be assigned a NOT NULL NOT DROPPABLE constraint.
X013T	-1137	Invalid index status. Details: <text>.
X013U	-1138	Invalid input parameter(s). Object name and status are required.
X013V	-1139	System-generated column <name> of base table <name> cannot appear in the search condition of a check constraint definition.
X013W	-1140	Row-length <num> exceeds the maximum allowed row-length of <num> for table <name>.
X013X	-1141	Could not obtain an up-and-audited DAM volume. Please check your system configuration.
X013Z	-1143	Validation for constraint <name> failed; incompatible data exists in referencing base table <name> and referenced base table <name>. To display the data violating the constraint, please use the following DML statement: <name>
X0140	-1144	Expected a quoted string in first key clause for column <name> on table <name>, value detected is (<name>).
X0141	-1145	The catalog name <name> is reserved for Trafodion metadata.
X0142	-1146	Unable to alter object <name> because it is not a <name>.
X0143	-1147	System-generated column <name> of base table <name> cannot appear in a unique or primary key constraint definition.
X0144	-1148	System-generated column <name> of base table <name> cannot appear in a referential integrity constraint definition.
X0151	-1181	Unable to drop object <name> (file error <num>).
X0152	-1182	Cannot instantiate constraint <name>, conflicting lock exists.
X0153	-1183	Cannot instantiate module <name>, conflicting lock exists.
X0154	-1184	Insufficient privilege on <name>.
X0155	-1185	The location name is either invalid or missing.
X0157	-1187	The schema name <name> is reserved for Trafodion metadata.
X0158	-1188	Unable to create referential integrity constraint <name> for table <name> due to circular dependency: <name>.
X0166	-1222	Invalid file type <type>.
X0168	-1224	Invalid data type for routine param <name>.
X0169	-1225	Error on access to PROCS table. Trafodion error <integer>.
X016A	-1226	Error on access to PARAMS table. Trafodion error <integer>.
X016F	-1231	Unable to create user-defined routine <routine-name>.
X0200	-2000	Error messages for compiler main, IPC, and DEFAULTS table; assertions for optimizer.
X0201	-2001	Error or warning <num> occurred while opening or reading from DEFAULTS table <name>. Using <name> values.
X0202	-2002	Internal error: cannot create MXCMP server.
X0203	-2003	Internal error: cannot establish connection with MXCMP server.

SQLSTATE	SQLCODE	Error Text
X0204	-2004	Internal error: error from MXCMP; cannot work on this query.
X0205	-2005	Internal error: from compilation, no errors in diagnostics yet for statement: <name>
X0206	-2006	Internal error: assertion failure (<name>) in file <name> at line <num>.
X0208	-2008	Internal error: out of virtual memory.
X020A	-2010	Internal IPC error.
X020B	-2011	Unable to create server process. Error <num> while resolving program file name <name>.
X020C	-2012	Unable to create server process <name>. Error <num>, TPC Error = <num>, error detail = <text>. (See procedure PROCESS_LAUNCH_ for details).
X020D	-2013	Unable to create server process <name>. error <num> on program file.
X020E	-2014	Unable to create server process <name>. error <num> on swap file.
X020F	-2015	Unable to create server process <name>. CPU is unavailable ( error <num>).
X020G	-2016	Server process <name> was started but had undefined externals.
X020H	-2017	Unable to create server process <name>. No more processes (PCBs) available.
X020I	-2018	Unable to create server process <name>. Library conflict.
X020J	-2019	Unable to create server process <name>. Unable to allocate virtual memory.
X020K	-2020	Unable to create server process <name>. Unlicensed privileged program.
X020L	-2021	System error <num> in <name> from <name>.
X020M	-2022	System error <num> in <name> from <name>, detail <text>.
X020N	-2023	Unable to create server process <name>. <name>.
X020P	-2025	Unable to create server process <name>. CPU is unavailable; <name>.
X020R	-2027	error <num> while sending a startup message to process <name>.
X020S	-2028	Unable to create OSS server process <name>. Insufficient resources.
X020T	-2029	Unable to create OSS server process <name>. OSS is not running.
X020U	-2030	Unable to create server process <name> via inetd (err no = <num>).
X020X	-2033	<text>: error <num> while communicating with process <name>.
X020Y	-2034	<text>: error <num> while communicating with server process <name>.
X020Z	-2035	<text>: Unable to open process <name> (err no = <num>).
X0211	-2037	<receiving-process>: A message from process <sending-process> was incorrectly formatted and could not be processed.
X021G	-2052	Optimizer internal counters: <name> <name> <name> <name>.
X021H	-2053	ASSERTION FAILURE CAUGHT BY OPTIMIZER! Attempting to recover and produce a plan.
X021N	-2059	Warnings while reading values from DEFAULTS table <name>.
X0221	-2073	Only the super ID user can compile system module <name>.
X0222	-2074	The name <name> is reserved for future system modules.
X0228	-2080	Error <num> while reading file: <num> bytes were read from <name> when <num> were expected in module <name>.
X0229	-2081	Error <num> while opening file <name> for read.
X022A	-2082	Error <num> while opening file <name> for write.
X022B	-2083	Error <num> while naming or locating file <name>.
X022C	-2084	Error <num> while writing <num> bytes to file <name>.
X022D	-2085	Error <num> while closing file <name>.
X022E	-2086	Unable to purge the file <name>. This file contains the results of a failed compilation and should be purged.

SQLSTATE	SQLCODE	Error Text
X022I	-2090	The command line argument for module name, <name>, is being ignored in favor of module name <name> in file <name>.
X022N	-2095	Module file <name>, expected to contain module <name>, instead contains <name>.
X022Q	-2098	The <name> compilation completed with <num> warnings.
X022R	-2099	The <name> compilation failed with <num> errors and <num> warnings.
X022S	-2100	Break was received. The compilation has been aborted.
X022T	-2101	Compilation failure due to internal error.
X022U	-2102	Unable to compile this query with 'MINIMUM' optimization level. Suggestion: Retry with 'MEDIUM' optimization level.
X022V	-2103	Unable to compile this query for one/both of the following reasons: a) Use of 'MINIMUM' optimization level, or b) Incompatible Control Query Shape specifications.
X022W	-2104	Unable to compile this query for one of two reasons: a) Incompatible Control Query Shape (CQS) specifications, or b) 'MEDIUM' optimization level is not sufficient to satisfy the CQS in effect. Suggestion: a) Inspect the CQS in effect; or b) Raise the optimization level to 'MAXIMUM'. Note that for this query, 'MAXIMUM' optimization level might result in a long compile time.
X022X	-2105	Unable to compile this query because of incompatible Control Query Shape (CQS) specifications. Suggestion: Inspect the CQS in effect.
X022Y	-2106	Unable to compile this statement since it is too long. Suggestion: Break up large statements into smaller pieces.
X022Z	-2107	Unable to compile this statement. Suggestion: Address the issue(s) raised in the reported warning(s).
X0230	-2108	Statement was compiled as if query plan caching were off.
X02P0	-2900	in file <name> at line <num>:
X0300	-3000	An internal error occurred in module <name> on line <num>. DETAILS(<text>).
X0344	-3148	Environment variable <name> is being ignored because this version of the code is Release, not Debug. Actual query results will likely not match expected results.
X034I	-3162	Procedure parameter <name> was not used.
X034J	-3163	Host variable <name> appears more than once in the INTO list. Execution results will be undefined.
X0352	-3182	Extra semicolon(;) in a compound statement.
X0400	-4000	Internal error in the query binder.
X0422	-4074	CONTROL QUERY successful.
X042U	-4102	The FIRST/ANY n syntax cannot be used with in an outermost SELECT statement.
X043G	-4124	More than one table will be locked: <name>.
X0446	-4150	Primary key of table expression <name> must be used for join with embedded <name> expression. Tables in scope: <name>.
X0447	-4151	Stream access supported only on updateable views <name>.
X0448	-4152	Table <name> cannot be both read and updated.
X0449	-4153	Statement might not compile due to an order requirement on stream expression.
X044A	-4154	Statement might not compile due to an order requirement on embedded <name> expression.
X044B	-4155	Secondary indexes don't support order requirement. Table: <name>.
X044D	-4157	Inner relation of left join cannot be stream expression. Tables in scope: <name>.
X044E	-4158	Join of stream expressions not supported. Tables in scope: <name>.
X044F	-4159	Intersection of stream expressions not supported. Tables in scope: <name>.

SQLSTATE	SQLCODE	Error Text
X044G	-4160	Intersection between embedded <name> expression and embedded <name> expression not supported. Tables in scope: <name>, <name>.
X044H	-4161	Union between embedded <name> expression and embedded <name> expression not supported. Tables in scope: <name>, <name>.
X044I	-4162	Groupby not supported for stream expression. Tables in scope: <name>.
X044J	-4163	Groupby not supported for embedded <name> expression. Tables in scope: <name>.
X044K	-4164	Outer relation of right join cannot be embedded <name> expression. Tables in scope: <name>.
X044L	-4165	Outer relation of right join cannot be stream expression. Tables in scope: <name>.
X044M	-4166	ORDER BY clause not supported in UNION of two streams. Tables in scope: <name>, <name>.
X044N	-4167	Embedded <name> statements not supported in subqueries.
X044O	-4168	Stream expressions not supported in subqueries.
X044P	-4169	Embedded DELETE statements not allowed when using DECLARE . . . FOR UPDATE clause.
X044Q	-4170	Stream expressions not supported for insert statements.
X044R	-4171	Embedded <name> statements not supported in INSERT statements.
X044T	-4173	Stream expression not supported for top level UPDATE statements.
X044U	-4174	JOIN_ORDER_BY_USER prevented compiler from reordering query tree.
X044V	-4175	Join between embedded <name> expression and embedded <name> expression not supported. Tables in scope: <name>.
X044W	-4176	Join between stream expression and embedded <name> expression not supported. Tables in scope: <name>.
X044X	-4177	Update of <name> column <name> not permitted on rollback.
X044Y	-4178	Update of variable length column <name> not permitted on rollback.
X044Z	-4179	SEQUENCE BY not supported for stream expressions.
X0450	-4180	Stream expression not supported for top level DELETE statement.
X0451	-4181	Join with embedded <name> expression is not supported.
X0452	-4182	Selection predicate on any but the innermost correlation name of an embedded <name> expression is not supported.
X045K	-4200	Stream expressions not supported for compound statements.
X045L	-4201	Embedded <name> expression not supported for compound statements.
X045M	-4202	SEQUENCE BY not supported for embedded <name> expressions.
X045N	-4203	INSERT/UPDATE/DELETE operation on nonaudited table <name> requires index maintenance which might cause the index(es) to become corrupt.
X045O	-4204	Stream access supported only for key-sequenced tables. Table: <name>.
X045P	-4205	Embedded <name> supported only for key-sequenced tables. Table: <name>.
X045Q	-4206	Embedded <name> supported only for updateable views. View: <name>.
X045R	-4207	Index <name> and other indexes covering a subset of columns do not cover all output values of stream.
X045S	-4208	Index <name> and other indexes covering a subset of columns do not cover all columns referenced in where clause of stream.
X045T	-4209	Update of nullable column <name> not permitted on rollback.
X045U	-4210	Embedded UPDATE/DELETE statements are not supported within an IF statement.
X045W	-4212	<table-name> cannot be used to satisfy order requirement on the stream because it is partitioned.

SQLSTATE	SQLCODE	Error Text
X045X	-4213	Use of rowsets in a predicate with embedded UPDATE/DELETE not supported.
X045Y	-4214	The SET ON ROLLBACK clause is not allowed on a nonaudited table. Table: <name>.
X045Z	-4215	Stream access is not allowed on a nonaudited table. Table: <name>.
X0460	-4216	The FIRST/ANY n syntax cannot be used with an embedded update or embedded DELETE statement.
X0461	-4217	
X048C	-4300	Invalid usage of procedure <procedure-name> - A UDR was invoked within a trigger.
X048E	-4302	Procedure <procedure-name> expects <value-1> parameters but was called with <value-2> parameters.
X048F	-4303	The supplied type for parameter value of routine <routine-name> was <type-name-1> which is not compatible with the expected type <type-name-2>.
X048G	-4304	Host variable or dynamic parameter <parameter-name> is used in more than one OUT or INOUT parameter for routine routine-name. Results might be unpredictable.
X048H	-4305	Parameter <value> for used defined routine <routine-name> is an OUT or INOUT parameter and must be a host variable or a dynamic parameter.
X048I	-4306	A CALL statement is not allowed within a compound statement.
X048J	-4307	Rowset parameters are not allowed in a CALL statement.
X048K	-4308	Internal error: unsupported SQL data type <value> specified for a CALL statement parameter.
X0500	-5000	Internal error in the query normalizer.
X0600	-6000	Internal error in the query optimizer.
X0602	-6002	The metadata table HISTOGRAMS or HISTOGRAM_INTERVALS contains invalid values. If you have manually modified the metadata table, then you should undo your changes using the CLEAR option in UPDATE STATISTICS.
X0607	-6007	Multi-column statistics for columns <name> from table <name> were not available; as a result, the access path chosen might not be the best possible.
X0608	-6008	Statistics for column <name> were not available; as a result, the access path chosen might not be the best possible.
X0700	-7000	Internal error in the code generator in file <name> at line <num>: <text>.
X0701	-7001	Invalid default value <name> for column <name>.
X0801	-8001	Internal executor error.
X0802	-8002	The current nowaited operation is not complete.
X0803	-8003	The descriptor is locked by another nowaited operation.
X0806	-8006	The stream timed out, but the cursor is still open.
X0807	-8007	The operation has been canceled.
X080A	-8010	Default catalog name: <name>. Default schema name: <name>.
X080B	-8011	SELECT statement inside compound (BEGIN . . . END) statement returns more than one row.
X080C	-8012	Encoding of CONTROL QUERY DEFAULTs: <name>.
X080E	-8014	A SELECT statement within compound statement did not return any row.
X080G	-8016	An attempt was made to access <name> which has a system version that is incompatible with the version of the accessing software.
X080H	-8017	Explain information is not available for this query.
X080J	-8883	
X08P1	-8901	The MXUDR server for this statement is no longer running. The statement will be assigned a new MXUDR server if it is executed again.

SQLSTATE	SQLCODE	Error Text
X08P2	-8902	Internal error: MXUDR returned an invalid UDR handle.
X08P3	-8903	An attempt was made by Trafodion to kill the MXUDR server for this statement <process-name>. PROCESS_STOP_ returned <value>.
X08P4	-8904	Unable to receive reply from MXUDR, possibly caused by internal errors while executing user-defined routines.
X08P6	-8906	An invalid or corrupt MXUDR reply could not be processed, possibly due to memory corruption in MXUDR while executing friendly user-defined routines or an internal error in Trafodion.
X082S	-8100	Define <name> does not exist
X08O4	-8868	Unable to create context when current transaction is implicitly started by SQL.
X08O5	-8869	The specified file number is not a QFO, or the file number is not internally associated with a QFO object (CLI internal error).
X08O6	-8870	The current statement is not associated with any QFO.
X08O7	-8871	Nowait tag is not specified in the <statement-id>.
X08O8	-8872	Unable to execute a new operation while there is another nowaited operation pending.
X08O9	-8873	The current statement is already associated with a QFO.
X08OG	-8880	Cannot remove the current context.
X08OH	-8881	The specified CLI context handle is not found
X08OI	-8882	Containing SQL not permitted.
X08OJ	-8883	The current context has violation checking functions disabled. Use SQL_EXEC_SetUdrAttributes_Internal() to enable it.
X08OU	-8894	Argument <argument-name> of CLI function <function-name> is reserved for future use and must be set to <string> when calling the function.
X083W	-8140	Prohibited SQL statement attempted.
X083X	-8141	An error was artificially injected, to test error handling. File <name> at line <num>.
X088C	-8300	Late name resolution failed.
X088D	-8301	Late name resolution failed. File system error <num> on file <name>.
X088E	-8302	Late name resolution failed. SQLCODE error <num> from <name>.
X08BL	-8417	An error occurred during the evaluation of a USER function.
X08BR	-8423	The provided field number is not valid.
X08BT	-8425	NULL cannot be assigned to a DEFAULT NULL NOT NULL column.
X08BV	-8427	<text>
X08BW	-8428	The argument to function <name> is not valid.
X08BX	-8429	The preceding error actually occurred in function <name>.
X08FA	-8550	Error <num> was returned by the Data Access Manager.
X08FB	-8551	Error <num> was returned by the Distribution Service on <name>.
X08FC	-8552	Error <num> was returned by the Distribution Service while fetching the version of the system <name>.
X08FD	-8553	Stream overflow; subscription rate has fallen too far behind publishing rate.
X08FU	-8570	Insufficient memory to build query.
X08FV	-8571	Insufficient memory to execute query.
X08FW	-8572	The statement has incurred a fatal error and must be deallocated.
X08FY	-8574	An OPEN was blown away on table <name>.
X08FZ	-8575	Timestamp mismatch on table <name>.

SQLSTATE	SQLCODE	Error Text
X08G0	-8576	Statement was recompiled.
X08G1	-8577	Table, index, or view <name> not found.
X08G2	-8578	Similarity check passed.
X08G3	-8579	Similarity check failed: <name>
X08GP	-8601	Error returned from file system while locking/unlocking.
X08GQ	-8602	The file system reported error <num> on a lock/unlock operation.
X08JG	-8700	An assertion failure or out-of-memory condition occurred during parallel execution.
X08JQ	-8710	Error <num> returned by Measure when attempting to update SQL counters.
X08MG	-8808	Module file <name> contains corrupted or invalid data.
X08MH	-8809	Unable to open the module file <name>.
X08MN	-8815	Error while building the TCB tree when executing the statement.
X08MO	-8816	Error while executing the TCB tree.
X08MP	-8817	Error while fetching from the TCB tree.
X08MQ	-8818	Error from root_tdb describe.
X08MU	-8822	Unable to prepare the statement.
X08MV	-8823	Internal error: IO requests are waiting for <name> message in the IpcMessageStream.
X08MW	-8824	The input <module-id> does not have a module name.
X08MX	-8825	Module is already added into the current context.
X08MY	-8826	Unable to add the module.
X08MZ	-8827	Unable to send the request <name>.
X08N0	-8828	Out of memory while creating the <name>.
X08N2	-8830	There is no current context.
X08N3	-8831	Either no current context or the module to which the statement belongs is not added to the current context.
X08N6	-8834	Unable to find the installation directory. Operating system error <num>.
X08N7	-8835	Invalid SQL descriptor information requested.
X08N8	-8836	Invalid update column for cursor.
X08N9	-8837	Invalid user id.
X08NA	-8838	Unable to receive reply from MXCMP, possibly caused by internal errors when compiling SQL statements, processing DDL statements, or executing the built in stored procedures.
X08NC	-8840	Object name provided to CLI is invalid.
X08NE	-8842	The cursor, <name>, referenced by this statement is not found or is not updateable.
X08NH	-8845	Internal error: root_tcb is null.
X08NI	-8846	Empty SQL statement.
X08NN	-8851	CLI Parameter bound check error.
X08NO	-8852	Holdable cursors are supported only for streaming cursors and embedded UPDATE/DELETE cursors.
X08NU	-8858	The value: (<num>) passed in through input a host variable/parameter is an invalid SQL identifier
X08NV	-8859	There are pending insert, delete, or update operations.
X08NW	-8860	Module file <name> has obsolete module header.
X08NX	-8861	Module file <name> has obsolete descriptor location table header.
X08NY	-8862	Module file <name> has obsolete descriptor location table entry.

SQLSTATE	SQLCODE	Error Text
X08NZ	-8863	Module file <name> has obsolete descriptor header.
X08O0	-8864	Module file <name> has obsolete descriptor entry.
X08O1	-8865	Module file <name> has obsolete procedure location table header.
X08O2	-8866	Module file <name> has obsolete procedure location table entry.
X08O3	-8867	Error while reading from file <name>.
X08OQ	-8890	The SQL compiler failed to initialize properly. Query results might differ from what is expected, due to different compiler defaults.
X08OR	-8891	Non-ASCII character host variable type for <name> field.
X08OX	-8897	RPC exception in CLI request from non-trusted shadow client to trusted shadow server.
X08OY	-8898	Internal error in CLI.
X095K	-9200	UPDATE STATISTICS encountered an error from <name>.
X095L	-9201	Unable to DROP object <name>.
X095M	-9202	UPDATE STATISTICS has located previously generate histogram that are not being regenerated. This might affect the plans that will be generated. Missing column lists are <column-list>.
X095N	-9203	Column names must be unique when specified in column list: (<name>).
X095O	-9204	The range of interval count is from 1 to 200.
X095P	-9205	UPDATE STATISTICS for object <name> is not supported.
X095Q	-9206	You are not authorized to read/write object <name>. Verify that you have the necessary access privileges.
X095R	-9207	You are not allowed to generate histogram statistics on an ISO88591 CHARACTER SET column which contains a null terminator character. You need to exclude this column from the column group list in UPDATE STATISTICS.
X095S	-9208	Unable to access column definitions.
X095T	-9209	Column name <name> does not exist in the table.
X095U	-9210	One of the column data types is not supported by UPDATE STATISTICS. You need to exclude this column from the column group list in UPDATE STATISTICS.
X095W	-9212	Cardinality statistics will be more accurate if you use SET ROWCOUNT option in the SAMPLE clause.
X095X	-9213	If you intend to update histogram statistics for columns, you must specify a column group list in the statement.
X095Y	-9214	Unable to create object <name>.
X095Z	-9215	UPDATE STATISTICS encountered an internal error (<location>).
X0A01	-10001	Sort Error: No error text is defined for this error.
X0A03	-10003	Sort Error: Warning: Scratch File EOF
X0A04	-10004	Sort Error: Merge is disallowed for Sort
X0A05	-10005	Sort Error: Unexpected error value. Check error
X0A06	-10006	Sort Error: Previous IO failed
X0A07	-10007	Sort Error: Error writing to Scratch File
X0A08	-10008	Sort Error: Invalid sort algorithm selected
X0A0A	-10010	Sort Error: Run number is invalid
X0A0B	-10011	Sort Error: Error reading Scratch File
X0A0C	-10012	Sort Error: Scratch Block number is invalid
X0A0D	-10013	Sort Error: No fixed disks to sort on
X0A0E	-10014	Sort Error: No memory to allocate scratch space

SQLSTATE	SQLCODE	Error Text
X0A0F	-10015	Sort Error: PROCESSHANDLE_GETMINE_ failed
X0A0G	-10016	Sort Error: PROCESSHANDLE_DECOMPOSE_ failed
X0A0H	-10017	Sort Error: DEVICE_GETINFOBYLDEV_ failed
X0A0I	-10018	Sort Error: FILENAME_FINDSTART_ failed
X0A0J	-10019	Sort Error: FILENAME_FINDNEXT_ failed
X0A0K	-10020	Sort Error: FILENAME_FINDFINISH_ failed
X0A0L	-10021	Sort Error: FILE_GETINFORISTBYNAME_ failed
X0A0M	-10022	Sort Error: FILE_CREATE failed
X0A0N	-10023	Sort Error: FILE_OPEN_ failed
X0A0O	-10024	Sort Error: SetMode failed
X0A0P	-10025	Sort Error: FileClose failed
X0A0Q	-10026	Sort Error: AWAITIOX failed
X0A0R	-10027	Sort Error: FILE_GETINFORIST failed
X0A0S	-10028	Sort Error: POSITION failed
X0A0T	-10029	Sort Error: FILE_GETINFO_ failed
X0A18	-10044	Sort Error: IO did not complete
X0A1B	-10047	Sort Error: Wrong length read
X0B2T	-11101	MXUDR: Unknown message type: <value>.
X0B2V	-11103	MXUDR: Invalid routine handle: <string>.
X0B2W	-11104	MXUDR: CLI Error: <error-text>.
X0B2X	-11105	MXUDR: Invalid Language Manager param mode. Parameter <parameter-value>.
X0B30	-11108	MXUDR: Unable to allocate memory for object <object-name>.
X0B32	-11110	MXUDR: Unexpected error during message processing: <string>.
X0B33	-11111	MXUDR: Internal error: <value>.
X0B35	-11113	MXUDR: Internal error: An unexpected UNLOAD request arrived for UDR handle <string>.
X0B5L	-11201	Language Manager initialization failed. Details: Error occurred while loading Java System Class <class-name>.
X0B5M	-11202	Language Manager initialization failed. Details: Unable to initialize JVM.
X0B5N	-11203	The Language Manager failed to create its class loader, possibly due to corrupt LmClassLoader.class file.
X0B5Q	-11206	Java class <class-file-name> was not found in external path <path-name>.
X0B5R	-11207	Java class <class-file-name> failed to initialize.
X0B60	-11216	Java execution: Data overflow occurred while retrieving data at parameter position <parameter-number>.
X0B61	-11217	Java execution: Data overflow occurred while retrieving data at parameter position <parameter-number>. Value is truncated.
X0B63	-11219	Specified signature is invalid. Reason: the number of parameters <value> must match the number of parameters in Java method.
X0B65	-11221	Specified signature is invalid. Reason: Missing [ ] for OUT/INOUT parameter at position <value>.
X0B66	-11222	Specified signature is invalid. Reason: Unknown parameter type used at position <value>.
X0B67	-11223	Language Manager encountered internal error <detail-text>.
X0B68	-11224	JVM raised an exception. Details: <detail-text>.

SQLSTATE	SQLCODE	Error Text
X0B69	-11225	Specified signature is invalid. Reason: Unknown or unsupported type used as a return type.
X0B6A	-11226	Java execution: Invalid null input value at parameter position <value>.
X0B6B	-11227	Java execution: Data overflow occurred while retrieving data at parameter position <value>.
X0B6C	-11228	Floating point conversion error <detail-text>.
X0D01	-13001	Java execution: Data overflow occurred while retrieving data at parameter position <value>. Value is truncated.
X0D04	-13004	A Java method completed with an uncaught Java exception. Details: <string>.
X0D05	-13005	A Java method completed with an uncaught java.sql.SQLException. Details: <string>.
X0D06	-13006	A Java method completed with an uncaught java.sql.SQLException with invalid SQLSTATE. The uncaught exception had an SQLCODE of <SQLCODE-value> and SQLSTATE of <SQLSTATE-value>. Details: <string>.
X0D07	-13007	Language Manager is out of memory <string>.
X0D08	-13008	The operation failed because the Java Virtual Machine ran out of memory.
X0D09	-13009	Language Manager encountered internal error <string>.
X0D0A	-13010	JVM raised an exception. Details: <string>.
X0D0B	-13011	Specified signature is invalid. Reason: The Java signature for a Java main method must be (java.lang.<string>[ ]).
X0D0C	-13012	All SQL parameters associated with a Java main method must have a parameter mode of IN.
X0D0D	-13013	All SQL parameters associated with a Java main method must be an SQL character type.
X0D0E	-13014	Unable to open the output source file <name>.
X0D0F	-13015	Unable to open the module definition file <name>.
X0D0G	-13016	Descriptor name <name> conflicts with SQLC default name <name>.
X0D0H	-13017	Descriptor <name> is multiply defined.
X0D0I	-13018	Descriptor name <name> is invalid.
X0D0J	-13019	Statement name <name> uses <name>, a reserved name SQLC generates.
X0D0K	-13020	Statement name <name> is multiply defined.
X0D0L	-13021	<name> is already defined.
X0D0M	-13022	Cursor <name> is already defined.
X0D0N	-13023	<name> is already defined as a dynamic cursor.
X0D0O	-13024	Cursor <name> was not declared.
X0D0Q	-13026	The EXEC SQL MODULE statement must precede any cursor definitions or executable SQL statements.
X0D0R	-13027	Only one EXEC SQL MODULE statement is allowed.
X0D0S	-13028	Cannot open static cursor <name> because <name> is out of scope at time of open.
X0D0T	-13029	<line-number-detail-text>
X0D0U	-13030	<line-number-detail-text>
X0D0V	-13031	Expecting a single host variable of type string.
X0D0W	-13032	Not expecting input host variables for static cursor <name>.
X0D0X	-13033	Host variable <name> is in different scope than when cursor <name> was declared.
X0D0Z	-13035	Invalid line number <num> for line pragma; ignoring the rest.
X0D12	-13038	Array size <name> expected to be an unsigned integer near line <num>.

SQLSTATE	SQLCODE	Error Text
X0D13	-13039	Function definition is not allowed within an SQL declare section near line <num>.
X0D14	-13040	Expecting ")" near line <num>.
X0D16	-13042	Unnamed declaration near line <num>.
X0D17	-13043	Expecting <name> near line <num>.
X0D18	-13044	Type specification <type> is not a recognized type near line <num>.
X0D19	-13045	Unexpected class declaration near line <num> ignored.
X0D1A	-13046	Expecting "}" to end member declaration near line <num>.
X0D1B	-13047	Undefined tag <name> near line <num>.
X0D1C	-13048	Tag <name> redefined near line <num>.
X0D1D	-13049	Input file not good near line <num>.
X0D1E	-13050	Cursor <name> not closed.
X0D1F	-13051	Cursor <name> not opened.
X0D1G	-13052	Cursor <name> not fetched.
X0D1H	-13053	Cursor <name> not opened or closed.
X0D1I	-13054	Cursor <name> not fetched or closed.
X0D1J	-13055	Cursor <name> not opened or fetched.
X0D1K	-13056	Cursor <name> not used.
X0D1L	-13057	End-of-file processing generated unexpected cursor status of <num> for cursor <name>.
X0D1M	-13058	Unable to open SQL CLI header file <name>.
X0D1O	-13060	Unable to open the listing file <name>.
X0D1P	-13061	Invalid NUMERIC precision specified near line <num>.
X0D1Q	-13062	Unsigned long long type not allowed near line <num>.
X0D1R	-13063	Identifier <name> not defined near line <num>.
X0D1S	-13064	Identifier <name> is not a member of struct <name> near line <num>.
X0D1T	-13065	End of file was found after <name> when <name> was expected, near line <num>.
X0D1U	-13066	Identifier <name> was expected to be a structure type near line <num>.
X0D1V	-13067	Unable to open source file <name>.
X0D1X	-13069	Missing module specification string argument after -g option.
X0D1Y	-13070	Module Group Specification String <MVSS-string> is not a Regular Identifier, or is longer than 31 characters.
X0D1Z	-13071	Module Tablespec Specification String <MTSS-string> is not a Regular Identifier, or is longer than 31 characters.
X0D20	-13072	Module Version Specification String <MVSS-string> is not a Regular Identifier, or is longer than 31 characters.
X0D21	-13073	Module name <module-name> is not a valid OSS file name, or is longer than 128 characters.
X0D22	-13074	One or more of the first three parts of the externally qualified module name <module-name> is longer than 128 characters.
X0D23	-13075	Externally qualified module name <module-name> is not a Regular Identifier, or is longer than 248 characters.
X0D24	-13076	Catalog name <catalog-name> is not a valid OSS file name, or is longer than 128 characters.
X0D25	-13077	Schema name <schema-name> is not a valid OSS file name, or is longer than 128 characters.

SQLSTATE	SQLCODE	Error Text
X0DDW	-13500	SQLCO errors
X0DDX	-13501	Invalid command option <name>.
X0DDY	-13502	Source file name must be specified.
X0DDZ	-13503	Missing filename for command option <name>.
X0DE0	-13504	Missing timestamp command option.
X0DE1	-13505	Source input file <name> cannot be opened.
X0DE2	-13506	COBOL output source file <name> cannot be opened.
X0DE3	-13507	Error while parsing source: <name>.
X0DE4	-13508	Expecting <name>, found <name>.
X0DE5	-13509	Expecting <name> after <name>, found <name>.
X0DE6	-13510	The SQL declare section might not contain COPY or REPLACE.
X0DE7	-13511	End of input file while processing EXEC SQL.
X0DE8	-13512	Input file error while processing EXEC SQL.
X0DE9	-13513	The BIT data type is not implemented in Trafodion.
X0DEA	-13514	The CHARACTER SET attribute is not implemented in Trafodion.
X0DEB	-13515	Picture <name> is not valid for a host variable.
X0DEC	-13516	Unexpected end of input file encountered after line <num>.
X0DED	-13517	Line <num> is too long to process and has been truncated.
X0DEE	-13518	Line <num> cannot be interpreted as a COBOL line type.
X0DEF	-13519	Line <num> contains an unterminated character literal.
X0DEG	-13520	Line <num> does not correctly continue a character literal.
X0DEH	-13521	Line <num>: DISPLAY host variables must be SIGN LEADING SEPARATE.
X0DEI	-13522	DECLARE SECTION cannot be nested.
X0DEJ	-13523	END DECLARE SECTION without a matching BEGIN DECLARE SECTION.
X0DEK	-13524	DECLARE SECTION encountered in unexpected program section.
X0DEL	-13525	Variable <name> might not be allocated correctly for a host variable.
X0DEM	-13526	Line <num>, <name>: <name> clause is not valid for a host variable.
X0DEN	-13527	The first declaration in an SQL DECLARE SECTION must have level 01 or 77.
X0DEO	-13528	Line <num>: Variable <name> is not alphabetic and cannot have a CHARACTER SET clause.
X0DEP	-13529	Missing END DECLARE SECTION detected at line <num>.
X0DM8	-13800	Line <num>: <name> is not a valid character set name.
X0F00	-15000	SQLCI error messages.
X0F04	-15004	Error <num> on change directory attempt to <name>.
X0F06	-15006	Error <num> while reading from file.
X0F07	-15007	Error <num> while opening file <name>.
X0F08	-15008	The specified statement does not exist in the history buffer.
X0F09	-15009	The requested help topic is too long.
X0F0A	-15010	The help file could not be opened.
X0F0B	-15011	No help is available for the requested topic.
X0F0C	-15012	File read error on the help file.
X0F0E	-15014	Section <name> not found in file <name>.
X0F0I	-15018	Break was received. The last statement might be lost.

SQLSTATE	SQLCODE	Error Text
X0F0Q	-15026	Break rejected.
X0F0R	-15027	SQL statement not ready. Try Break later.
X0F0S	-15028	Break error.
X0F0T	-15029	Operation failed due to insufficient memory.
X0F0U	-15030	The specified define already exists. Use alter or delete and add.
X0F0V	-15031	The specified define does not exist.
X0F0W	-15032	An error occurred while adding, altering or deleting this define.
X0F0X	-15033	Break was received.
X0F0Y	-15034	Invalid LOG file name.
X0F0Z	-15035	Permission denied to access this file
X0F10	-15036	Invalid filecode OR invalid function argument
X0FRR	-15999	SQLCI internal error.
X0G00	-16000	Error message file not found.
X0G01	-16001	No message found for error or warning <sqlcode>.
X0J00	-19000	Internal error in internal stored procedure processing.
X0J01	-19001	Error in field description of internal stored procedure.
X0J02	-19002	No such internal stored procedure: <name> defined.
X0J03	-19003	Internal stored procedure failed without any error information returned.
X0J0K	-19020	Stored procedure <name> expects <num> input parameters.
X0J0L	-19021	Stored procedure <name> returns with error: <text>.
X0K00	-20000	SQL Utilities error messages.
X0K31	-20109	<text>
X0P01	-25001	Program <executable>, executing on <node>, has encountered a version error.
X0P2S	-25100	Remote node <node> runs an incompatible version of Trafodion. The Trafodion version (version) of node is <version-1>, the local node does not support versions older than <version-2>.
X0P2T	-25101	Remote node <node> runs an incompatible version of Trafodion. The Trafodion version (version) of <node> is <version-1>, the local node supports only version <version-2>.
X0P2U	-25102	Remote node <node> runs a version of Trafodion which cannot interoperate with other versions. The Trafodion version (version) of <node> is <version-1>.
X0P8C	-25300	Module <module> had module version <version-1>; node <node> does not support module versions lower than <version-2>.
X0P8D	-25301	Module <module> had module version <version-1>; the local node does not support module versions higher than <version-2>.
X0P8I	-25306	A required system module has module version <version-1>; node <node> does not support query plans from modules with module version lower than <version-2>.
X0P8J	-25307	The query plan can be executed only by a node with Trafodion version (version) <version-1>, the version of <node> is <version-1>.
X0P8K	-25308	The query plan has plan version <version-1>, the local Trafodion version (version) can execute only query plans with plan version <version-1>.
X0P8L	-25309	Module <module> can be executed only by a node with Trafodion version (version) version1, the version of <node> is <version-1>.
X0P8M	-25310	Module <module> has module version <version-1>, the local Trafodion version (version) can execute modules only with module version <version-1>.
X0P8N	-25311	System module <module> has a wrong module version. The expected module version is <version-1>. The actual module version is <version-2>.

<b>SQLSTATE</b>	<b>SQLCODE</b>	<b>Error Text</b>
X0U08	-30008	Internal error. Rowset index is out of range.
X0U09	-30009	Internal error. Trying to add more elements than maximum rowset size.
X0U0A	-30010	Internal error. Rowset is corrupted.
X0U0B	-30011	More than one INTO statement in the same query is not supported.
X0U0C	-30012	Rowset index <name> must be specified last in the derived column list of <name>.
X0U0D	-30013	Hostvar used to set input size of rowset has zero or negative value.
X0U0E	-30014	Hostvar used to set input size of rowset is not of type short, int, or long.
X0U0K	-30020	Embedded UPDATE/DELETE cannot be used with SELECT . . .INTO and rowset.
XW02S	-100	The "no data" completion condition (SQLCODE = +100).
XW10C	-1012	No privileges were granted. You lack grant option on the specified privileges.
XW10D	-1013	Not all privileges were granted. You lack grant option on some of the specified privileges.
XW10F	-1015	Some of the specified privileges could not be revoked.
XW82Y	-8106	The last row fetched by this cursor was updated or deleted between the FETCH and UPDATE/DELETE. . .WHERE CURRENT. . . of statements.

## Chapter 12. File-System Errors

Some error messages generated by the Trafodion platform include file-system error codes. For example:

### SQL 1024

```
File system error <error-number> occurred on <text-string-1>. <text-string-2>.
```

This section lists all file-system error codes and provides the corresponding error text for each code number. The error text can sometimes help you troubleshoot a problem. If the initial error message and file-system error text are insufficient to help you solve a problem, or if you need more information, contact the [Trafodion User mailing list](#).

Error	Text
0000	The operation completed successfully.
0001	A read procedure reached end-of-file or a write procedure reached end of tape.
0002	The operation specified is not allowed on this type of file.
0003	An open or purge of a partition failed.
0004	An open operation for an alternate key file failed.
0005	Sequential buffering not used because no space was available in the process-control buffer for the sequential block buffer.
0006	A system message was received from another process.
0007	This process cannot accept a command because the receiving file is not opened correctly.
0008	The operation was successful (examine message control word for additional status).
0009	A read through a locked record was successful.
0010	The new record or file could not be created because a file by that name or a record with that key already exists.
0011	The file is not in the directory or the record is not in the file, or the specified tape file is not on a labeled tape.
0012	The file is in use.
0013	The filename was not specified in proper form.
0014	That device does not exist on this segment.
0015	The disk or segment specified for a file RENAME operation does not match the name of the disk or segment of the file.
0016	No file with that file number has been opened.
0017	A paired-open was specified and the file is not open by the primary process, the parameters supplied do not match the parameters supplied when the file was opened by the primary, or the primary process is not alive.
0018	The segment specified does not exist in the network.
0019	There is no more space for devices in the logical device table.
0020	File name is too long to be opened across a network, or swap file or segment name is not acceptable.
0021	An illegal <count> was specified in a file-system call, or the operation attempted to transfer too much or too little data.

Error	Text
0022	The application parameter or buffer address is out of bounds.
0023	The disk address is out of bounds, or the maximum number of blocks in an alternate-key file is exceeded.
0024	Privileged mode is required for this operation.
0025	AWAITIO[X] or CANCEL attempted on file opened for waited I/O.
0026	AWAITIO[X] or CANCEL or CONTROL 22 attempted on a file with no outstanding I/O requests.
0027	An operation was attempted with outstanding no-waited I/O requests pending.
0028	The number of outstanding non-blocking operations would exceed that specified; an attempt was made to open a disk file or receiving file with the maximum number of concurrent operations more than 1; an attempt to ADD more than the configured maximum number of sub devices for an I/O process; or sync depth exceeds number the opener can handle; or trying to run more than 254 processes from the same program file.
0029	A required parameter is missing in a procedure call, or two mutually exclusive parameters were supplied.
0030	Message system is unable to obtain memory because either no entry is available in the message block pool or the maximum number of RECEIVE or SEND message blocks are already in use.
0031	Unable to obtain file-system buffer space.
0032	Unable to obtain storage pool space.
0033	I/O process is unable to obtain sufficient buffer space.
0034	Unable to obtain a file-system control block.
0035	Unable to obtain an I/O process control block, or the transaction or open lock unit limit has been reached.
0036	Unable to lock physical memory; not enough memory available.
0038	Attempt to perform operation on wrong type of system.
0039	The server process received a request with a sync ID older than the set of saved replies.
0040	The operation timed out. A command did not complete within the time specified by its <time-limit> parameter.
0041	A checksum error occurred on a file synchronization block.
0042	Attempt to read from unallocated extent.
0043	Unable to obtain disk space for file extent.
0044	The disk directory or device control table is full.
0045	The file is full; or two entries for <process-name> were already in the process pair directory.
0046	An invalid key was specified; key length passed to CREATE exceeds 255 bytes; or application failed to open an alternate-key file.
0047	The alternate key data is not consistent with primary file data.
0048	Security violation; illegal operation attempted.
0049	Access violation; attempt to use an unexpired labeled tape for output; or a mismatch between a DEFINE Use attribute (input or output/extend) and the current operation (read or write).
0050	Directory error on a disk.
0051	Directory on a disk is marked bad.
0052	Error in the disk free space table.
0053	File system internal error.
0054	I/O error in disk free space table or in Data Access Manager undo area.
0055	I/O error in disk directory; the file is no longer accessible.
0056	I/O error on disk label; the disk is no longer accessible.

Error	Text
0057	The disk free space table is full.
0058	The disk free space table is marked bad.
0059	The disk file is bad; there is a mismatch in the internal file control block, or the file structure in a structured file is inconsistent.
0060	The file resides on a removed disk, the device is stopped or not open, or a server has failed and a process has been replaced by a different process with the same name since the server was opened.
0061	No more file opens are permitted on this disk or device; the system administrator issued a STOPOPENS command or the number of open files reached the maximum allowed.
0062	The disk was mounted but no mount order was given, so the file open is not permitted.
0063	The disk was mounted and the mount is in progress, so a file open is not permitted.
0064	The disk was mounted and the mount is in progress, so a file open is not permitted.
0065	Only special requests permitted - or special request to RAID-1 disk pair attempted with only one device in special state.
0066	The device is stopped, a hard failure occurred on the controller, the disk and controller are not compatible, or both halves of a RAID-1 disk are down.
0070	Continue the file operation.
0071	A duplicate record was encountered.
0072	An attempt was made to access an unmounted or nonexistent partition, or to access a secondary partition.
0073	The disk file or record is locked.
0074	The number of read updates without replies exceeds the receive depth.
0075	Requesting process has no current process transaction identifier.
0076	Transaction is in the process of ending.
0078	Transaction identifier is invalid or obsolete.
0079	A transaction attempted to update or delete a record which it has not previously locked.
0080	Invalid operation on protected file or non-protected disk.
0081	Operation is not valid for a transaction which still has non-blocking I/Os outstanding on a disk or process file.
0082	Transaction Services not running on this segment or on the remote segment.
0083	Attempt to begin more concurrent transactions than can be handled.
0084	Transaction Services has not been configured on this segment or on the remote segment.
0085	A device has not been started for Transaction Services.
0086	BEGINTRANSACTION is disabled either by the operator or because one or more Transaction Services limits have been reached.
0087	Waiting on a READ request and did not get it.
0088	A CONTROL READ is pending so a second READ is not valid.
0089	A remote device cannot accept text because it has no buffer available.
0090	The transaction was aborted by the system because its parent process died, a server using the transaction failed, or a message to a server using the transaction was canceled.
0091	A Transaction Services crash occurred during commitment of the transaction; the transaction may or may not have been committed.
0092	Distributed transaction aborted by system because the path to a remote segment that was part of the transaction was down.
0093	A transaction was aborted because it spanned too many transaction log files.
0094	A transaction was aborted by operator command.

Error	Text
0095	A transaction was aborted because of Data Access Manager process takeover by backup.
0096	The transaction was aborted because it exceeded the AUTOABORT timeout duration.
0097	Transaction aborted by call to ABORTTRANSACTION.
0098	Allocation of a Transaction Control Block failed because the local table is full, or the table on a remote segment is full.
0099	Process attempted to use features of a microcode option that is not installed on this segment.
0100	Device is not ready or the controller is not operational.
0101	The tape is write protected.
0102	Printer paper out, bail open or end of ribbon.
0103	Disk not ready due to power failure.
0104	No response from printer.
0105	Invalid printer vertical format unit buffer.
0106	A buffered WRITE has failed; data in printer buffer was lost.
0110	Only BREAK access is permitted.
0111	Operation aborted because of BREAK.
0112	READ or WRITEREAD preempted by operator message or too many user console messages.
0113	DEFINE class or attributes are not valid for the attempted function.
0119	Error code value was too large to fit into an 8-bit buffer; file-system error number is greater than 255.
0120	Data parity error, or attempt to access a tape whose density is higher than the switch setting on the tape drive.
0121	Data overrun error, hardware problem.
0122	Request aborted due to possible data loss caused by reset of circuit, bus sequence error; or Data Access Manager process takeover.
0123	Subdevice is busy.
0124	A line reset is in progress, loss of data is possible.
0130	Illegal disk address requested, or formatting error occurred.
0131	Write-check error from disk; internal circuitry fault.
0132	Seek incomplete from disk; cylinder address not reached after retry.
0133	Access not ready on disk; cylinder address not reached.
0134	Address compare error on disk.
0135	Write-protect violation with disk write.
0136	Disk unit ownership error (dual-port disk).
0137	Controller buffer parity error.
0138	Interrupt overrun; a device interrupted the processor before the software could respond.
0139	Controller error; internal diagnostic failure.
0140	Modem error (communication link not yet established, modem failure, momentary loss of carrier, or disconnect).
0148	Attempt to read unwritten data.
0150	End-of-tape marker detected.
0151	Runaway tape detected, or attempt to access a tape whose density is lower than the switch setting on the tape drive.
0152	Unusual end-tape unit went off-line.
0153	Tape drive power restored.
0154	BOT detected during backspace files or backspace records.

Error	Text
0155	Only nine-track magnetic tape allowed on this system.
0156	Tape command rejected.
0157	I/O process internal system error.
0160	Request is invalid for device state; protocol error.
0161	Impossible event occurred for line state.
0162	Operation timed out.
0163	EOT received or power at autocall unit is off.
0164	Disconnect received or data line is occupied (busy).
0165	RVI received or data line not occupied after setting call request.
0166	ENQ received or auto call unit failed to set present-next-digit.
0167	EOT received on line bid, or data-set-status not set
0168	NAK received on line bid, or auto-call unit failed to clear present-nextdigit after digit-present was set.
0169	WACK received on line bid, auto-call unit set abandon-call-and-retry, or station disabled or undefined.
0170	No ID sequence received during circuit assurance mode or invalid message control word entry number on write.
0171	No response received on bid/poll/select, or reply invalid.
0172	Reply not proper for protocol; invalid control sequence or invalid data.
0173	Maximum allowable NAKs received (transmission error), invalid message control word on WRITE, or invalid request ID.
0174	WACK received or bus frame aborted.
0175	Incorrect alternating ACK received, or command rejected.
0176	Poll sequence ended with no responder.
0177	Text overrun (insufficient buffer space for data transfer).
0178	No address list specified.
0179	Application buffer is incorrect, control request pending, or autopoll active.
0180	Unknown device status received.
0181	Sub device expected status information but received data instead.
0187	Operation returning with no useful data.
0188	Damage to logical flow of events.
0189	Response not yet available.
0190	Device error; hardware problem.
0191	Device power on, or terminal reset.
0192	Device in diagnose mode; system operator running diagnostics.
0193	Invalid or missing microcode file.
0194	Device use or mount request rejected by operator.
0195	Operation requires use of Tape Services but it is not running; tape operation is not allowed.
0196	A tape label record is missing or incorrect.
0197	An SQL error has occurred.
0198	A DEFINE of the given name could not be found.
0199	The disk file is protected by security software.
0200	The device is owned by an alternate port.

Error	Text
0201	The current path to the device is down, an attempt was made to write to a non-existent process, the message-system request was incorrectly formatted, or an error was found in the message system interface.
0210	Device ownership changed during operation.
0211	The node performing the operation failed during the operation.
0213	Channel data parity error (path error).
0214	Channel timeout (path error).
0215	I/O attempted to absent memory page (hardware path error).
0216	Memory breakpoint encountered during this I/O operation.
0217	Memory parity error during this I/O (hardware path error).
0218	Interrupt timeout occurred on a channel, or a controller, modem, or the line between, or lost the modem clock (path error).
0219	Illegal device reconnect (path error).
0220	Protect violation; an I/O controller attempted an illegal write.
0221	Controller handshake violation (path error).
0222	Bad channel status from EIO instruction (path error).
0223	Bad channel status from IIO instruction (path error).
0224	Controller error (fatal error).
0225	No unit assigned or multiple units assigned to the same unit number (path error).
0230	Node power failed, then restored.
0231	Controller power failed, then restored.
0232	Access is denied due to error in communication with the security monitor.
0233	Error in call to SERVERCLASS_SEND_.
0240	Network line handler error; operation not started. Ownership switch was performed.
0241	Network error; operation not started.
0246	External cluster bypass error; operation aborted.
0248	Network line handler error; operation aborted.
0249	Network error; operation aborted.
0250	All paths to the system are down.
0251	Network protocol error (path error).
0252	Required class is not available.
0255	Net line handler flooded; too many interrupts.
0512	An invalid parameter was specified.
0513	A file name was missing.
0514	The sequential I/O procedures do not support the specified device type.
0515	The specified access is invalid.
0516	The specified buffer address is invalid.
0517	The specified file code in the SET^FILE call does not match the file code of the file.
0518	The block buffer provided to OPEN^FILE is too small.
0519	The block length specified in the SET^FILE call does not match the block buffer length in OPEN^FILE.
0520	The specified record length was either too small or too large.
0521	The specified file is not a valid EDIT file.

Error	Text
0522	Either the SET^FILE or CHECK^FILE operation is not valid on an open file or OPEN^FILE was called for a file already open.
0523	An EDITREAD or EDITREADINIT error occurred.
0524	The specified file was not open.
0525	The requested operation was inconsistent with the access mode.
0526	The required operation failed because of insufficient stack space.
0527	The temporary buffer required for a non-blocking WRITE^FILE operation was not provided.
0530	The program called WRITE^FILE for the receiving file before calling READ^FILE.
0531	A call to CHECK^BREAK could not open the receiving file the receiving file was opened without calling OPEN^FILE.
0532	A non-blocking I/O operation has been restarted.
0533	An internal sequential I/O error occurred.
0534	A discrepancy was detected between the common file-control-block checksum and the previous checksum.
0535	A discrepancy was detected between the file file-control-block checksum and the previous checksum.
0541	A data structure version is incompatible with the requested operation.
0550	File operation attempted at illegal position.
0551	Duplicate exists for insertion-ordered alternate key.
0561	The item code in a list is not recognized.
0563	The size of an output buffer was too small.
0564	The operation is not supported for this file type.
0565	A malformed request was denied.
0566	This reply is malformed or not appropriate.
0567	The define used is incompatible for use with target system's TOS version.
0570	An out-of-sequence message was received.
0571	A duplicate message was received.
0572	Message cannot be accepted because sequence number has been reset.
0573	The requested process handle cannot be returned.
0578	The block size specified is too large.
0579	The record size specified is too large for the given block size, file type and format.
0580	An open failed because the file was oversize and the opener did not specify use of 64-bit primary keys.
0581	An operation involving 32-bit primary keys was attempted on an open which specified use of 64-bit keys.
0582	Alternate key information could not be returned because it cannot be expressed in the superseded format of the parameter.
0583	An extent size specified is too large.
0584	The operation could not be performed because a software component does not support format-2 disk files.
0586	Transaction_Keep_ was attempted without a valid transaction dialog message.
0587	Transaction_Keep_ was called when there was already a kept transaction.
0588	There was no kept transaction but the operation required one.
0589	The operation could not be performed because there was a kept transaction.
0590	The parameter value is invalid or inconsistent with another.
0593	The request was canceled.

Error	Text
0594	A tape-catalog error was returned to Tape Services. Refer to the event log for detailed information.
0595	An error was returned to Tape Services. Refer to the event log for detailed information.
0597	A required item is missing from an item list.
0632	Not enough stack space to complete request.
0633	Operation is invalid because a performance measurement utility is running.
0634	A logical device number exceeded 16 bits.
0635	A disk cannot be accessed because the other side is locked.
0638	Process cannot be stopped until process returns to stopmode 1.
0639	Process cannot be stopped until process goes to stopmode 0.
0700	The sequence number of the message received by the Data Access Manager process from a recovery process does not match.
0701	The Data Access Manager process received a message from a recovery process that requires that the Data Access Manager process be in the STARTED state; it is currently in the STOPPED state.
0702	The Data Access Manager process received an erroneous message from a recovery process. The message requested a physical REDO and also requested that a transaction log be generated.
0703	The Data Access Manager process encountered a Creation Volume Sequence Number in a transaction-log record sent by a recovery process that is more recent than the CRVSN of the File Label.
0704	The Data Access Manager process encountered a Previous Volume Sequence Number in a transaction-log record sent by a recovery process that does not match the Volume Sequence Number of the data block on disk.
0705	Generated by the Data Access Manager process when it receives a Transaction Services Transaction Log Disk request type message and the Data Access Manager process is not an transaction-log disk.
0706	Generated by the Data Access Manager process when it receives a request message that is inappropriate for a Transaction Log Data Access Manager Process.
0707	Generated by the Data Access Manager process when the Disk Process Name Stamp (DPNameTimeStamp) in the message sent by a recovery process does not match the current DPNameTimeStamp of the disk.
0708	The Data Access Manager process encountered a File Label that had its UndoNeeded flag set when a recovery request specified that the UndoNeeded flag must not be set.
0709	The Data Access Manager process encountered a File Label that had its RedoNeeded flag set when a recovery request specified that the RedoNeeded flag must not be set.
0711	The Data Access Manager process received a corrupt transaction-log record in a message from a recovery process.
0751	A tape manager returned an error to Tape Services. Refer to the event log for detailed information.
0899	An attempt to switch nodes failed.
1024	The specified SQL subset is not defined to the file system.
1025	The supplied row or update value violates one of the constraints for the table.
1026	The selection expression on an SQL view has been violated.
1027	The Data Access Manager process encountered a bad SQL label or tree of labels.
1028	The Data Access Manager process accessed a label of an unexpected type during an OPEN or during an SQL label operation.
1029	A request to share an existing SQL open failed because no matching open was found.
1030	An invalid lock key length was specified for an SQL table.
1031	Some of the supplied values for DECIMAL or VARCHAR columns are invalid, or the supplied row is too long. Also, the disk process might have encountered a bad column in a stored row or a value in an update on a row that would change the length of a VARCHAR column in an entry-sequenced table.

Error	Text
1032	The SQL row description is inconsistent.
1033	The SQL key column description is inconsistent, or the specified key is too long.
1034	SQL internal error: The requested operation has failed because of an inconsistency in specifying the SQL catalog.
1035	SQL internal error.
1036	SQL internal error.
1037	SQL internal error.
1038	SQL internal error.
1039	An SQL UPDATE statement was attempted, but update intent was not specified when the cursor was declared.
1040	There is no current row. The cursor position is either before the first row of the set, after the last row, or between two rows.
1041	SQL internal error.
1042	The operation required a default value for a column that was defined as NO DEFAULT.
1043	SQL internal error.
1044	The operation is not allowed while an SQL cursor is open.
1045	SQL internal error.
1046	SQL internal error.
1047	The SQL index being used is marked invalid because the catalog manager has not successfully loaded it.
1048	SQL internal error.
1049	SQL internal error.
1050	SQL internal error.
1051	SQL internal error.
1052	A row was encountered that resides in a block having a data parity error. The row does not satisfy the WHERE clause.
1053	An ECC error or a checksum error occurred indicating that it is impossible to process the accessed block. No data is returned.
1054	Unable to access a non-protected table or protection view that has been altered by an uncommitted DDL statement.
1055	Unable to perform a utility operation while an uncommitted DDL operation from another transaction exists.
1056	Unable to access a table that is being recovered by Transaction Services.
1057	Unable to access a table that is being altered by another user.
1058	Unable to access a table that is being dropped by another user.
1059	Unable to access a protection view whose underlying table does not exist or is inconsistent.
1060	SQL internal error.
1061	The cursor is no longer defined in the Data Access Manager process.
1062	SQL internal error.
1063	SQL internal error.
1064	The table cannot be dropped because protection views are still defined for the table.
1065	This error message has two possible causes: 1) Either an SQL internal error has occurred. 2) An attempt was made to execute either an UPDATE WHERE CURRENT OF or DELETE WHERE CURRENT OF statement by using a cursor declared with the BROWSE ACCESS option.
1066	Internal error: Occurred in OPEN.

Error	Text
1067	Internal error: Occurred in the file system or Data Access Manager process OPEN protocol.
1068	SQL internal error.
1069	SQL internal error.
1070	The process's program file is not licensed.
1071	SQL internal error.
1072	SQL internal error.
1073	SQL internal error.
1074	Internal error: SQL file system procedure.
1075	A FETCH was attempted following a FETCH that failed. This left the cursor in an undefined position.
1076	SQL internal error.
1077	The redefinition timestamp for a partition does not match the other partitions. This is a serious consistency failure.
1078	The disk process encountered an invalid row.
1079	The requested key compression option is inconsistent with the data type, offset in row, or descending flag of some of the key columns.
1080	The transaction ID does not match the current transaction ID for a protected table with a lock protocol or for a non-protected temporary table.
1081	SQL internal error.
1082	SQL internal error.
1083	An internal input SQL structure has an invalid format, as indicated by an incorrect EYE^CATCHER data item value. The program might have corrupted the SQL region or SQL executor segment, or an SQL internal error might have occurred.
1084	Unable to insert into an SQL view that does not allow insertions.
1085	SQL internal error or access incompatible SQL objects that were created on an SQL system with a later release date than the SQL system doing the accessing.
1086	Unable to unlock an SQL table that has locks through either STABLE ACCESS or REPEATABLE ACCESS.
1087	The SQL file system detected an internal disk process error.
1088	SQL internal error.
1089	SQL internal error.
1090	The requested SQL operation cannot be completed because of current limitations on message sizes.
1091	The file or table cannot be purged until the NOPURGEUNTIL date.
1092	The operation cannot be performed because the resulting disk directory entry would be too long. Too many columns, partitions, indexes, protection views, or constraints have been defined.
1093	The operation cannot be performed because the resulting row would exceed the RECLENGTH value defined for the relative table.
1094	The limit on the number of columns that can make up a key has been exceeded for indexes or key-sequenced tables.
1095	An invalid value has been supplied for the BLOCKSIZE attribute.
1096	The BLOCKSIZE value for this table is too small for the row length of the table.
1097	Unable to access an object that is off-line or has an inconsistent definition.
1098	The supplied MAXEXTENTS value is too large, or the total size of the partitions would exceed the largest allowable table size.
1099	The definitions of the table and/or index partitions are inconsistent, or the index label and corresponding underlying table values are inconsistent.
1100	An operand was truncated during assignment of character data.

Error	Text
1101	Truncation was needed, but prohibited during assignment of character data.
1102	An overflow occurred during expression evaluation.
1103	An underflow occurred during expression evaluation.
1104	An SQL column of type DECIMAL contained values that are not digits.
1105	Unable to assign a negative value to a column defined as unsigned.
1106	An unsigned numeric has a negative value.
1107	Division by zero occurred during expression evaluation.
1108	Data type of column not supported by this release.
1109	An invalid SQL data type was encountered.
1110	An operation between incompatible SQL types was requested.
1111	SQL internal error.
1112	Arithmetic operation was requested in an unexpected unsigned data type.
1113	Invalid operator value during expression evaluation.
1114	Invalid LIKE pattern during expression evaluation.
1115	A specified SYSKEY value exceeds the current defined size of the relative SQL table.
1116	The SQL file system aborted the transaction because an SQL statement could not be completed.
1117	Unable to use an undefined index.
1118	The specified view is not defined.
1119	The specified partition is not defined.
1120	SQL internal error.
1121	This error message has two possible causes: 1) A remote user specified local-only authority in the SECURE attribute for the object being created or altered. 2) The SECURE attribute did not grant read authority to all users being granted write authority.
1122	The supplied KEYTAG value is already defined for this table.
1123	SQL internal error.
1124	SQL internal error.
1125	SQL internal error.
1126	SQL internal error.
1127	Unable to update an SQL catalog table from a process that is not licensed.
1128	An operand was scale truncated during expression evaluation.
1129	Scale truncation was needed but prohibited during expression evaluation.
1130	Unable to use SQL on a system where the product is not installed.
3501	More control information was received than this dialect allows.
3502	Server does not have sufficient available storage for this request.
3503	Server does not support this dialect.
3504	Server does not support this request type.
3505	Server version is not current.
4001	Operation not permitted. Process does not have the appropriate privileges or permissions to perform the requested operation.
4002	No such file or directory.
4003	No such process or table entry.
4004	Interrupted system call.
4005	I/O error.

Error	Text
4006	No such device or address.
4007	Argument list too long.
4008	Exec format error.
4009	Bad file descriptor.
4010	No children.
4011	No more processes.
4012	Insufficient user memory.
4013	Permission denied.
4014	Bad address.
4016	Mount device busy.
4017	File already exists.
4018	Cross-device link.
4019	No such device.
4020	Not a directory.
4021	Is a directory.
4022	Invalid function argument.
4023	File table overflow.
4024	Maximum number of files already open.
4025	Invalid operation on terminal device.
4026	Object (text) file busy.
4027	File too large.
4028	No space left on device.
4029	Illegal seek.
4030	Read only file system.
4031	Too many links.
4032	Broken pipe or no reader on socket.
4033	Argument out of range.
4034	Value out of range.
4035	No message of desired type.
4036	Identifier removed.
4045	Deadlock condition.
4046	No record locks available.
4061	No data sent or received.
4099	Function not implemented.
4101	Operation would block.
4102	Operation now in progress.
4103	Operation already in progress.
4104	Socket operation on non socket.
4105	Destination address required.
4106	Message too long.
4107	Protocol wrong type for socket.
4108	Protocol not available.

Error	Text
4109	Protocol not supported.
4110	Socket type not supported.
4111	Operation not supported on socket.
4112	Protocol family not supported.
4113	Address family not supported.
4114	Address already in use.
4115	Can't assign requested address.
4116	Network is down.
4117	Network is unreachable.
4118	Network dropped connection on reset.
4119	Software caused connection abort.
4120	Connection reset by remote host.
4121	No buffer space available.
4122	Socket is already connected.
4123	Socket is not connected.
4124	Can't send after socket shutdown.
4126	Connection timed out.
4127	Connection refused.
4128	Host is down.
4129	No route to host.
4131	File name too long.
4132	Directory not empty.
4180	Invalid data in buffer.
4181	No reply in buffer.
4182	Partial buffer received.
4183	Interface error from SPI.
4184	Version mismatch.
4185	XDR encoding error.
4186	XDR decoding error.
4195	Out-of-band data available.
4196	Invalid socket call.
4197	File type not supported.
4198	C file (code 180) not odd unstructured.
4199	Insufficient internal memory.
4200	Too many symbolic links during path name resolution.
4201	File-set catalog internal consistency error.
4202	Root file set is not mounted.
4203	POSIX not running or not installed.
4204	Illegal byte sequence.
4205	Process is not common runtime-environment (CRE) compliant but requests a service that depends on CRE.
4206	Illegal service requested.
4207	An unexpected OSS subsystem error occurred.

Error	Text
4208	Illegal operation attempted on file descriptor.
4209	Logic error.
4211	Current working directory or filename longer than PATH_MAX.
4212	An error occurred during invocation of a DEFINE procedure.
4213	A cross node exec has been attempted while holding a semaphore.
4214	An invalid message tag had been encountered when setlocale_from_msg() function was called. There was no corresponding message for the message tag.
4215	Positioning of a file directory failed because there were more than 65535 names in the directory beginning with the same first two characters.
4216	The function is supported but not for the referenced object type.
4217	Socket transport server not running.
4218	Message queue server not running.
4219	Terminal Helper process not running.
4220	An operation was attempted on a large file using a small file I/O API.